

Chapter 9: Priority Queues ADT

CS401

Michael Y. Choi, Ph.D.

**Department of Computer Science
Illinois Institute of Technology**

Revised Nell Dale Presentation

9.1 Priority Queues

- A priority queue is an abstract data type with an interesting accessing protocol - only the *highest-priority* element can be accessed
- Priority queues are useful for any application that involves processing items by priority

The Interface

```
package ch09.priorityQueues;

public interface PriorityQueueInterface<T>
{
    void enqueue(T element);
    // Throws PriQOverflowException if this priority queue is full;
    // otherwise, adds element to this priority queue.

    T dequeue();
    // Throws PriQUnderflowException if this priority queue is empty;
    // otherwise, removes element with highest priority from this
    // priority queue and returns it.

    boolean isEmpty();
    // Returns true if this priority queue is empty; otherwise, returns false.

    boolean isFull();
    // Returns true if this priority queue is full; otherwise, returns false.

    int size();
    // Returns the number of elements in this priority queue. }
```

9.2 Priority Queue Implementations


- There are many ways to implement a priority queue
 - **An Unsorted List** - dequeuing would require searching through the entire list
 - **An Array-Based Sorted List** - Enqueuing is expensive
 - **A Sorted Linked List** - Enqueuing again is $O(N)$
 - **A Binary Search Tree** - On average, $O(\log_2 N)$ steps for both enqueue and dequeue
 - **A Heap** - (next section) guarantees $O(\log_2 N)$ steps, even in the worst case

9.3 The Heap


- **Heap** An implementation of a Priority Queue based on a complete binary tree, each of whose elements contains a value that is greater than or equal to the value of each of its children
- In other words, a heap is an implementation of a Priority Queue that uses a binary tree that satisfies two properties
 - the *shape property*: the tree must be a complete binary tree
 - the *order property*: for every node in the tree, the value stored in that node is greater than or equal to the value in each of its children.

Tree Terminology


- A full binary tree




- A complete binary tree



Two Heaps Containing the Letters 'A' through 'J'



(a)






(b)

The dequeue operation


reheapDown (element)

Effect: Adds element to the heap.

Precondition: The root of the tree is empty.



The enqueue operation




(a) Add K

reheapUp (element)

Effect: Adds element to the heap.





Precondition: The last index position of the tree is empty.











(b) reheapUp

The enqueue operation


steps b, c represent the “reheap up” operation



- a) enqueue ('M')
- b) enqueue ('C')
- c) enqueue ('X')
- d) enqueue ('A')
- e) enqueue ('D')
- f) dequeue ()
- g) enqueue ('H')
- h) dequeue ()




Heap Implementation



A Non-linked Representation of Binary Trees

- A binary tree can be stored in an array in such a way that the relationships in the tree are not physically represented by link members, but are *implicit* in the algorithms that manipulate the tree stored in the array.
- We store the tree elements in the array, level by level, left-to-right. We call the array `elements` and store the index of the last tree element in a variable `lastIndex`.
- The tree elements are stored with the root in `elements[0]` and the last node in `elements[lastIndex]`.

A Binary Tree and Its Array Representation




elements

[0]	G
[1]	D
[2]	I
[3]	B
[4]	F
[5]	H
[6]	J
[7]	A
[8]	C
[9]	E
	⋮

lastIndex: 9

A Binary Search Tree Stored in an Array with Dummy Values



elements

[0]	50
[1]	40
[2]	60
[3]	29
[4]	45
[5]	-1
[6]	70
[7]	-1
[8]	-1
[9]	42
	⋮

lastIndex: 9

Array Representation continued

- To implement the algorithms that manipulate the tree, we must be able to find the left and right child of a node in the tree:
 - $\text{elements}[\text{index}]$ left child is in $\text{elements}[\text{index} * 2 + 1]$
 - $\text{elements}[\text{index}]$ right child is in $\text{elements}[\text{index} * 2 + 2]$
- We can also determine the location of its parent node:
 - $\text{elements}[\text{index}]$'s parent is in $\text{elements}[(\text{index} - 1) / 2]$.
- This representation works best, space wise, if the tree is complete (which it is for a heap)


Beginning of HeapPriQ.java

```
//-----  
// HeapPriQ.java                      by Dale/Joyce/Weems                      Chapter  
9 // Priority Queue using Heap (implemented with an ArrayList)  
//  
// Two constructors are provided: one that use the natural order of the  
// elements as defined by their compareTo method and one that uses an  
// ordering based on a comparator argument.  
//-----  
package ch09.priorityQueues;  
import java.util.*; // ArrayList, Comparator  
  
public class HeapPriQ<T> implements PriQueueInterface<T>  
{  
    protected ArrayList<T> elements; // priority queue elements  
    protected int lastIndex;          // index of last element in priority queue  
    protected int maxIndex;           // index of last position in ArrayList  
  
    protected Comparator<T> comp;  
  
    . . .
```


The enqueue method

```
public void enqueue(T element) throws PriQOverflowException
// Throws PriQOverflowException if this priority queue is full;
// otherwise, adds element to this priority queue.
{
    if (lastIndex == maxIndex)
        throw new PriQOverflowException("Priority queue is full");
    else
    {
        lastIndex++;
        elements.add(lastIndex, element);
        reheapUp(element);
    }
}
```


The `reheapUp` algorithm is pictured on the next slide




(a) Add K



(b) Move hole up



(c) Move hole up



(d) Place element into hole

reheapUp operation


```
private void reheapUp(T element)
// Current lastIndex position is empty.
// Inserts element into the tree and ensures shape and order properties.
{
    int hole = lastIndex;
    while ((hole > 0) // hole is not root and element > hole's parent
        &&
        (comp.compare(element, elements.get((hole - 1) / 2)) > 0))
    {
        elements.set(hole, elements.get((hole - 1) / 2)); // move hole's parent down
        hole = (hole - 1) / 2; // move hole up
    }
    elements.set(hole, element); // place element into final hole
}
```

The dequeue method


```
public T dequeue() throws PriQUnderflowException
// Throws PriQUnderflowException if this priority queue is empty;
// otherwise, removes element with highest priority from this
// priority queue and returns it.
{
    T hold;          // element to be dequeued and returned
    T toMove;        // element to move down heap

    if (lastIndex == -1)
        throw new PriQUnderflowException("Priority queue is empty");
    else
    {
        hold = elements.get(0);          // remember element to be returned
        toMove = elements.remove(lastIndex); // element to reheap down
        lastIndex--;                     // decrease priority queue size
        if (lastIndex != -1)
            reheapDown(toMove);          // restore heap properties
        return hold;                     // return largest element
    }
}
```


The reheapDown algorithm is pictured on the next slide




(a) reheapDown (E);



(b) Move hole down



(c) Move hole down



(d) Fill in final hole

reheapDown operation

```
private void reheapDown(T element)
// Current root position is "empty";
// Inserts element into the tree and ensures shape and order properties.
{
    int hole = 0;          // current index of hole
    int next;              // next index where hole should move to

    next = newHole(hole, element); // find next hole
    while (next != hole)
    {
        elements.set(hole, elements.get(next)); // move element up
        hole = next;                          // move hole down
        next = newHole(hole, element);         // find next hole
    }
    elements.set(hole, element);                // fill in the final hole
}
```

```

private int newHole(int hole, T element)
// If either child of hole is larger than element return the index
// of the larger child; otherwise return the index of hole.
{
    int left = (hole * 2) + 1;
    int right = (hole * 2) + 2;
    if (left > lastIndex)
        // hole has no children
        return hole;
    else
    if (left == lastIndex)
        // hole has left child only
        if (comp.compare(element, elements.get(left)) < 0)
            // element < left child
            return left;
        else
            // element >= left child
            return hole;
    else
    // hole has two children
    if (comp.compare(elements.get(left), elements.get(right)) < 0)
        // left child < right child
        if (comp.compare(elements.get(right), element) <= 0)
            // right child <= element
            return hole;
        else
            // element < right child
            return right;
    else
    // left child >= right child
    if (comp.compare(elements.get(left), element) <= 0)
        // left child <= element
        return hole;
    else
        // element < left child
        return left;
}

```

The newHole method

Heaps Versus Other Representations of Priority Queues

	enqueue	dequeue
Heap	$O(\log_2 N)$	$O(\log_2 N)$
Linked List	$O(N)$	$O(1)$
Binary Search Tree		
Balanced	$O(\log_2 N)$	$O(\log_2 N)$
Skewed	$O(N)$	$O(N)$