



**PART NO: OP1010**

**PART NAME: COVER PLATE**

**Operation No. 1010**

| S. No.        | Description                                   |    | Specification (Standard) |     |       | Method of checking       | Freq. of Inspn. | 1st Shift |         | 2 nd Shift |         | 3rd Shift |         |
|---------------|-----------------------------------------------|----|--------------------------|-----|-------|--------------------------|-----------------|-----------|---------|------------|---------|-----------|---------|
|               |                                               |    |                          |     |       |                          |                 | 1 Half    | 2 Half  | 1 Half     | 2 Half  | 1 Half    | 2 Half  |
| 01            | Crank Bore Diameter                           |    | 39.300                   | ±   | 0.050 | Air gauge                | 4nos/shift      |           |         |            |         |           |         |
| 02            | Crank bore position(89.50/9.0)                |    | 0.200                    | ref | YXW   | P.gauge/CMM              | 1no/shift       |           |         |            |         |           |         |
| 03            | Machining Ref(9places)                        |    | 13.000                   | ±   | 0.200 | Vernier                  | 2nos/shift      |           |         |            |         |           |         |
| 04            | Mtg.Face Flatness                             |    | 0.060                    |     | max.  | Tripad/CMM               | 1no/shift       |           |         |            |         |           |         |
| 05            | Mtg Face Flatness(Zone)                       |    | 0.030                    |     | max.  | Tripad/CMM               | 1no/shift       |           |         |            |         |           |         |
| 06            | Mtg.Face Flatness)Inlet side)                 |    | 0.020                    |     | max.  | Tripad/CMM               | 1no/shift       |           |         |            |         |           |         |
| 07            | Mounting face roughness                       |    | Rz 3.2                   |     | max.  | R.tester                 | 1no/Day         |           |         |            |         |           |         |
| 08            | Mounting Hole Dia(7places)                    |    | 6.500                    | ~   | 7.000 | Plug gauge               | 2nos/shift      |           |         |            |         |           |         |
| 09            | Mounting hole position                        |    | 0.500                    |     |       | P.gauge/CMM              | 1no/shift       |           |         |            |         |           |         |
| 10            | Dowel hole dia(2places)                       |    | 6.300                    | ±   | 0.050 | Air gauge                | 4nos/shift      |           |         |            |         |           |         |
| 11            | Dowel hole position                           |    | 133.60,12.40<br>(0.20)   |     |       | CMM/Position gauge       | 1no/shift       |           |         |            |         |           |         |
| 12            | Inlet Hole Dia                                | SC | 21.300                   | +   | 0.060 | Air gauge                | 4nos/shift      |           |         |            |         |           |         |
| 13            | Inlet Hole Depth                              |    | 6.000                    | ±   | 0.300 | Vernier/D.gauge          | 2nos/shift      |           |         |            |         |           |         |
| 14            | Inlet Bore Dia                                |    | 17.600                   | ±   | 0.050 | plug gauge/Vernier       | 2nos/shift      |           |         |            |         |           |         |
| 15            | Inlet Step Bore Depth                         |    | 17.000                   | ±   | 0.200 | Vernier/D.gauge          | 2nos/shift      |           |         |            |         |           |         |
| 16            | Inlet position                                |    | 152.50,26.50<br>(0.50)   |     |       | CMM/Position gauge       | 1no/shift       |           |         |            |         |           |         |
| 17            | Inlet milling height                          |    | 48.600                   | ±   | 0.100 | CMM/L.H                  | 1no/shift       |           |         |            |         |           |         |
| 18            | Thread                                        |    | M6x1.0                   |     |       | TPG                      | 2nos/shift      |           |         |            |         |           |         |
| 19            | PlungerStep Dia                               |    | 15.000                   | ±   | 0.100 | Vernier/P.gauge          | 2nos/shift      |           |         |            |         |           |         |
| 20            | Step dia Depth                                |    | 7.000                    | ±   | 0.200 | Vernier/D.gauge          | 2nos/shift      |           |         |            |         |           |         |
| 21            | Plunger Bore Dia                              | SC | 14.000                   | +   | 0.021 | Air gauge                | 4nos/shift      |           |         |            |         |           |         |
| 22            | Plunger Bore Depth from face(58.90+1.5mm)     |    | 60.400                   | ±   | 0.150 | Vernier/D.gauge          | 2nos/shift      |           |         |            |         |           |         |
| 23            | Plunger bore finish                           |    | Rz                       |     | 6.300 | R.tester                 | 1no/Day         |           |         |            |         |           |         |
| 24            | Circlip Groove Dia                            |    | 15.700                   | +   | 0.110 | G.vernier/Contour        | 1no/shift       |           |         |            |         |           |         |
| 25            | Criclip Groove Width                          |    | 1.150                    | +   | 0.140 | Contour/w.gauge          | 1no/shift       |           |         |            |         |           |         |
| 26            | Criclip Groove Depth                          |    | 1.500                    | +   | 0.100 | Vernier with circlip     | 1no/shift       |           |         |            |         |           |         |
| 27            | Drill dia                                     |    | 4.000                    | ±   | 0.100 | plug gauge/Vernier       | 2nos/shift      |           |         |            |         |           |         |
| 28            | Outlet Bore Dia                               | SC | 17.020                   | +   | 0.030 | Air gauge                | 4nos/shift      |           |         |            |         |           |         |
| 29            | Outlet Bore Height                            |    | 28.300                   | ±   | 0.075 | Height gauge             | 2nos/shift      |           |         |            |         |           |         |
| 30            | Outlet Bore Depth                             |    | 7.000                    | ±   | 0.200 | Vernier/D.gauge          | 2nos/shift      |           |         |            |         |           |         |
| 31            | Diameter                                      |    | Ø 23.435                 | +   | 0.250 | Vernier                  | 2nos/shift      |           |         |            |         |           |         |
| 32            | Outlet Height                                 |    | 30.000                   | -   | 0.200 | Height gauge/Vernier/Cmm | 2nos/shift      |           |         |            |         |           |         |
| 33            | Outlet position(21.0,1.75)                    |    | 0.400                    | ref | Y,X,W | CMM/Position gauge       | 1no/shift       |           |         |            |         |           |         |
| 34            | Diameter(Through)                             |    | 10.000                   | ±   | 0.200 | Plug gauge               | 2 nos/shift     |           |         |            |         |           |         |
| 35            | Ø4.0mm hole position                          |    | 0.100                    | ref | U,V   | CMM/Position gauge       | 1no/shift       |           |         |            |         |           |         |
| 36            | Center distance(M6 to Inlet)                  |    | 17.000                   | ±   | 0.200 | CMM/Position gauge       | 1no/shift       |           |         |            |         |           |         |
| Abbreviations |                                               |    |                          |     |       | Remarks                  |                 | OK / NG   | OK / NG | OK / NG    | OK / NG | OK / NG   | OK / NG |
| NP            | No Production                                 |    |                          |     |       | QA                       | Inspected by    |           |         |            |         |           |         |
| SC            | Significant Characteristic                    |    |                          |     |       |                          | Checked by-     |           |         |            |         |           |         |
|               | TAF / P2 / 9.1B JAN-2012(Rev date:06.10.2023) |    |                          |     |       |                          | Approved by     |           |         |            |         |           |         |