

Capturing from Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

Apply a display filter... <Ctrl-F>

No.	Time	Source	Destination	Protocol	Length	Info
3572	58.848360700	2600:1901:1:7c5::	2401:4900:cafc:8be7::	QUIC	268	Protected Payload (KP0)
3573	58.848362200	2600:1901:1:7c5::	2401:4900:cafc:8be7::	QUIC	99	Protected Payload (KP0)
3574	58.848363200	13.107.139.11	172.20.10.2	TCP	54	443 → 58975 [ACK] Seq=9191 Ack=991372 Win=4195584 Len=0
3575	58.848517500	Intel_ca:b1:51	Broadcast	ARP	42	ARP Announcement for 172.20.10.2
3576	58.848662100	172.20.10.2	13.107.139.11	TCP	1414	58975 → 443 [ACK] Seq=1064812 Ack=9191 Win=65024 Len=1360 [TCP PDU reassembled in 3584]
3577	58.860946600	13.107.139.11	172.20.10.2	TCP	54	443 → 58975 [ACK] Seq=9191 Ack=992732 Win=4195584 Len=0
3578	58.861006500	172.20.10.2	13.107.139.11	TCP	1414	58975 → 443 [ACK] Seq=1066172 Ack=9191 Win=65024 Len=1360 [TCP PDU reassembled in 3584]
3579	58.863896600	2401:4900:cafc:8be7::	2a03:2880:f335:120::	TCP	1414	[TCP Retransmission] 52463 → 443 [PSH, ACK] Seq=656 Ack=1 Win=65280 Len=1340
3580	58.865485000	2401:4900:cafc:8be7::	2600:1901:1:7c5::	QUIC	98	Protected Payload (KP0), DCID=e65d0a35d52d1075
3581	58.875787000	13.107.139.11	172.20.10.2	TCP	54	443 → 58975 [ACK] Seq=9191 Ack=994092 Win=4195584 Len=0
3582	58.875848000	172.20.10.2	13.107.139.11	TCP	1414	58975 → 443 [ACK] Seq=1067532 Ack=9191 Win=65024 Len=1360 [TCP PDU reassembled in 3584]
3583	58.885925400	13.107.139.11	172.20.10.2	TCP	54	443 → 58975 [ACK] Seq=9191 Ack=996812 Win=4195584 Len=0
3584	58.885987500	172.20.10.2	13.107.139.11	TLSv1.3	2774	Application Data
3585	58.886574800	2401:4900:cafc:8be7::	2600:1901:1:7c5::	QUIC	465	Protected Payload (KP0), DCID=e65d0a35d52d1075
3586	58.886682100	20.42.65.94	172.20.10.2	TLSv1.3	157	Application Data
3587	58.886837000	20.42.65.94	172.20.10.2	TCP	54	443 → 50413 [ACK] Seq=9097 Ack=1769 Win=4195584 Len=0
3588	58.888776800	172.20.10.2	20.42.65.94	TCP	54	50413 → 443 [ACK] Seq=3502 Ack=9097 Win=261888 Len=0
3589	58.891289800	20.42.65.94	172.20.10.2	TLSv1.3	101	Application Data

> Frame 3579: Packet, 1414 bytes on wire (11312 bits), 1414 bytes captured (11312 bits) on interface \Device\NPF{...}

> Ethernet II, Src: Intel_ca:b1:51 (28:95:29:ca:b1:51), Dst: 2a:49:e9:26:3c:64 (2a:49:e9:26:3c:64)

> Internet Protocol Version 6, Src: 2401:4900:cafc:8be7:6c99:b21e:1dd5:3949, Dst: 2a03:2880:f335:120::face

> Transmission Control Protocol, Src Port: 52463, Dst Port: 443, Seq: 656, Ack: 1, Len: 1340

0000 2a 49 e9 26 3c 64 28 95 29 ca b1 51 86 dd 60 0b *I &cd()-Q-
0010 44 08 05 50 06 40 24 01 49 00 ca bc 8b e7 6c 99 D: P @S I: -...1-
0020 b2 1e 1d 45 39 49 2a 03 28 80 f3 35 01 20 fa ce ...9I* (5: ...
0030 b0 0c 00 00 01 67 cc ef 01 bb 8f ce 76 ed 58 4a ...g: ...v-XJ
0040 b3 5b 50 18 00 ff 31 ee 00 00 5f c5 d7 30 bf f8 ...P:1: ...0-
0050 38 31 50 49 1d b6 20 90 d5 a8 13 e0 33 1a cb 0d 81PI: ...3: ...
0060 b2 e8 39 5d 55 29 52 7a 07 9a 99 b4 a9 55 44 a6 ...9U)Kz ...UD-
0070 ba 58 d7 d0 0b b2 f9 1f 4b 6a 52 8b 94 89 c1 db -X: ... KJR: ...
0080 af 63 f7 53 0a 60 6a 0b 77 c9 2b 8c c0 05 8b bd -c: S: j: w+: ...
0090 af 19 86 97 2b ca 09 62 9c 08 97 c8 a3 54 37 8b ...+ : b: ...T7-
00a0 91 7e 23 fc 4a cd 8c be 84 b5 cb 54 c6 00 fe 11 ...# J: ...T: ...
00b0 0a 38 55 17 7b b4 49 6d 82 2f d2 a7 43 48 08 a5 -BU: p: Im: /-CH-
00c0 86 83 c6 a5 14 6f 4a b1 56 91 82 76 6f e9 28 4a ...oJ V: {o (J
00d0 11 a3 35 49 77 9e 88 36 87 17 43 49 49 24 1d 20 ...SIw: 6 -CII\$-
00e0 0e f3 d8 7f 19 b7 54 32 46 4e 46 50 0b 2a cb b0 ...T2 FNFP: *.
00f0 43 46 aa 5a 98 11 19 f1 36 5c 46 06 67 7c 21 80 CF: 2: ...6\F: g|: |
0100 72 36 88 d3 c9 1c 51 10 43 75 cf 94 30 47 7d 62 n6: ...Q: Cu: -0G|b
0110 4c 6e b9 02 cb b6 b7 48 33 c2 84 18 0b dc 46 6c Ln: ...H 3: ...F1
0120 fd 5c b4 50 c5 8d 36 4a 4f 10 bb 24 39 71 45 0b -\ P: 63 O: -59eE-
0130 a5 12 53 6c 27 c4 c3 75 2c 76 2a dc 58 c0 fa 34 -S1: 6: O: -59eE-
0140 59 b7 77 63 4a 61 a8 4d 2a 48 e9 a3 73 b0 1a 86 Y: wclNa M: *H: s: ...
0150 c9 e6 95 8e a2 a8 15 e5 18 bc 72 9e f3 42 62 0a ...e: -p: -B: ...
0160 46 47 11 76 6c 4f c3 1a 87 98 3f da 77 b2 f8 36 FG: v10: ...2: w: 6

Wi-Fi: <live capture in progress> Packets: 4759 Profile: Default 8:46 AM