

Wireshark interface showing a packet capture from Wi-Fi. The packet list displays several QUIC packets (715-741) and a selected UDP packet (776). The packet details pane shows the structure of the selected packet, including Ethernet II, Internet Protocol Version 6, User Datagram Protocol, and Data (29 bytes). The packet bytes pane displays the raw hex and ASCII data.

No.	Time	Source	Destination	Protocol	Length	Info
715	18.752292000	2401:4900:cabc:8be7...	2600:1901:1:7c5::	QUIC	219	Protected Payload (KP0), DCID=fc82f7132c463dea
716	18.753019600	2401:4900:cabc:8be7...	2600:1901:1:7c5::	QUIC	1288	Protected Payload (KP0), DCID=fc82f7132c463dea
717	18.753139900	2401:4900:cabc:8be7...	2600:1901:1:7c5::	QUIC	475	Protected Payload (KP0), DCID=fc82f7132c463dea
727	18.926998600	2600:1901:1:7c5::	2401:4900:cabc:8be7...	QUIC	646	Protected Payload (KP0)
728	18.927001800	2600:1901:1:7c5::	2401:4900:cabc:8be7...	QUIC	184	Protected Payload (KP0)
729	18.927802900	2401:4900:cabc:8be7...	2600:1901:1:7c5::	QUIC	93	Protected Payload (KP0), DCID=fc82f7132c463dea
730	18.930814000	2600:1901:1:7c5::	2401:4900:cabc:8be7...	QUIC	89	Protected Payload (KP0)
731	18.956025900	2600:1901:1:7c5::	2401:4900:cabc:8be7...	QUIC	86	Protected Payload (KP0)
732	18.972709700	2401:4900:cabc:8be7...	2600:1901:1:7c5::	QUIC	94	Protected Payload (KP0), DCID=fc82f7132c463dea
733	19.056638600	2600:1901:1:7c5::	2401:4900:cabc:8be7...	QUIC	255	Protected Payload (KP0)
738	19.097930700	2401:4900:cabc:8be7...	2600:1901:1:7c5::	QUIC	98	Protected Payload (KP0), DCID=fc82f7132c463dea
741	19.302756000	2600:1901:1:7c5::	2401:4900:cabc:8be7...	QUIC	86	Protected Payload (KP0)
776	22.454022300	2401:4900:cabc:8be7...	2001:4860:4826:7700...	UDP	91	50313 → 443 Len=29
777	22.653762300	2001:4860:4826:7700...	2401:4900:cabc:8be7...	UDP	86	443 → 50313 Len=24
834	25.316348700	172.20.10.2	172.20.10.15	UDP	86	57621 → 57621 Len=44
868	30.556199400	2401:4900:cabc:8be7...	2001:4860:4826:7700...	UDP	91	61941 → 443 Len=29
869	30.741777100	2001:4860:4826:7700...	2401:4900:cabc:8be7...	UDP	88	443 → 61941 Len=26
900	37.005217600	fe80::5e9e:367e:7ca...	fe80::2849:e9ff:fe2...	DNS	96	Standard query 0x2e29 A time.windows.com

Frame 776: Packet, 91 bytes on wire (728 bits), 91 bytes captured (728 bits) on interface \Device\NPF_{...}

Ethernet II, Src: Intel_ca:b1:51 (28:95:29:ca:b1:51), Dst: 2a:49:e9:26:3c:64 (2a:49:e9:26:3c:64)

Internet Protocol Version 6, Src: 2401:4900:cabc:8be7:6c99:b21e:1dd5:3949, Dst: 2001:4860:4826:7700::

User Datagram Protocol, Src Port: 50313, Dst Port: 443

Data (29 bytes)

```
0000 2a 49 e9 26 3c 64 28 95 29 ca b1 51 86 dd 60 07 *I &ld( )..Q ..
0010 ee 20 00 25 11 40 24 01 49 00 ca bc 8b e7 6c 09 - %0$ I... 1.
0020 b2 1e 1d d5 39 49 20 01 48 60 48 26 77 00 00 00 ....9I - H'M&w...
0030 00 00 00 00 00 00 c4 89 01 bb 00 25 61 3a 4c e9 .....%a:L
0040 89 13 e3 2f d1 f2 6d e1 7f 4e bc e2 9f ec 1e a3 .../..m- N.....
0050 07 ad 02 e4 1c a5 a7 33 c0 0e f4 .....3 ...
```