

Problem

You are given an integer n , you have to convert it into a string.

Please complete the partially completed code in the editor. If your code successfully converts n into a string s the code will print "Good job". Otherwise it will print "Wrong answer".

n can range between -100 to 100 inclusive.

Sample Input 0

100

Sample Output 0

Good job

Submissions

Leaderboard

Discussions

Editorial

Change Theme

Language

Java 7



```
22 public class Solution {
23     }
24 }
25
26 //The following class will prevent you from te
27 class DoNotTerminate {
28
29     public static class ExitTrappedException exte
30
31     private static final long serialVersionUID =
32 }
33
34 public static void forbidExit() {
35     final SecurityManager securityManager = new
36     @Override
37     public void checkPermission(Permission perm
38         if (permission.getName().contains("exitVM"
39             throw new ExitTrappedException();
40     }
41 }
42 };
43 System.setSecurityManager(securityManager);
44 }
45 }
46 }
```

Line: 13 Col: 32

Upload Code as File

Run Code

Submit Code

☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

1 100

Your Output (stdout)

1 Good job

Expected Output

Download

1 Good job



Problem

Static initialization blocks are executed when the class is loaded, and you can initialize static variables in those blocks.

It's time to test your knowledge of Static initialization blocks.

You can read about it [here](#).

You are given a class Solution with a main method. Complete the given code so that it outputs the area of a parallelogram with breadth **B** and height **H**. You should read the variables from the standard input.

If $B \leq 0$ or $H \leq 0$, the output should be "java.lang.Exception:

Breadth and height must be positive" without quotes.

Input Format

There are two lines of input. The first line contains **B**: the breadth of the parallelogram. The next line contains **H**: the height of the parallelogram.

Constraints

- $-100 \leq B \leq 100$
- $-100 \leq H \leq 100$

Output Format

If both values are greater than zero, then the main method must output the area of the parallelogram. Otherwise, print "java.lang.Exception: Breadth and height must be positive" without quotes.

Sample input 1

1
3

Sample output 1

3

Sample input 2

-1
2

Sample output 2

java.lang.Exception: Breadth and height must

[Change Theme](#)

Language

Java 7



```
7 13 public class Solution {
14     B = sc.nextInt();
15     H = sc.nextInt();
16
17     if (B <= 0 || H <= 0) {
18         flag = false;
19         System.out.println("java.lang.Exce
20             positive");
21     }
22
23
24
25
26 public static void main(String[] args){
27     if(flag){
28         int area=B*H;
29         System.out.print(area);
30     }
31
32     }//end of main
33
34 }//end of class
35
36
```

Line: 21 Col: 6

[Upload Code as File](#)[Run Code](#)[Submit Code](#)☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

[Download](#)

1 1
2 3

Your Output (stdout)

1 3

Expected Output

1 3

[Download](#)

Problem

You are given a list of student information: ID, FirstName, and CGPA. Your task is to rearrange them according to their CGPA in decreasing order. If two student have the same CGPA, then arrange them according to their first name in alphabetical order. If those two students also have the same first name, then order them according to their ID. No two students have the same ID.

Hint: You can use comparators to sort a list of objects. See the [oracle docs](#) to learn about comparators.

Input Format

The first line of input contains an integer N , representing the total number of students. The next N lines contains a list of student information in the following structure:

ID Name CGPA

Constraints

$$2 \leq N \leq 1000$$

$$0 \leq ID \leq 100000$$

$$5 \leq |Name| \leq 30$$

$$0 \leq CGPA \leq 4.00$$

The name contains only lowercase English letters. The **ID** contains only integer numbers without leading zeros. The CGPA will contain, at most, 2 digits after the decimal point.

Output Format

After rearranging the students according to the above rules, print the first name of each student on a separate line.

Sample Input

```
5
33 Rumpa 3.68
85 Ashis 3.85
56 Samiha 3.75
19 Samara 3.75
22 Fahim 3.76
```

Sample Output

```
Ashis
Fahim
Samara
Samiha
Rumpa
```

Change Theme

Language

Java 7



```
1 import java.util.*;
2
3 class Student {
4     private int id;
5     private String fname;
6     private double cgpa;
7
8     public Student(int id, String fname, double cgpa) {
9         this.id = id;
10        this.fname = fname;
11        this.cgpa = cgpa;
12    }
13
14    public int getId() {
15        return id;
16    }
17
18    public String getFname() {
19        return fname;
20    }
21
22    public double getCgpa() {
23        return cgpa;
24    }
25 }
```

Line: 67 Col: 1

Upload Code as File

Run Code

Submit Code

☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

```
1 5
2 33 Rumpa 3.68
3 85 Ashis 3.85
4 56 Samiha 3.75
5 19 Samara 3.75
6 22 Fahim 3.76
```

Your Output (stdout)

```
1 Ashis
2 Fahim
3 Samara
4 Samiha
```

Problem

In computer science, a stack or LIFO (last in,

A string containing only parentheses is balanced if the following is true: 1. if it is an empty string 2. if A and B are correct, AB is correct, 3. if A is correct, (A) and {A} and [A] are also correct.

Examples of some correctly balanced strings are: "{}()", "{()}", "({})"

Examples of some unbalanced strings are: "{((", "{()}", "[[", "){}" etc.

Given a string, determine if it is balanced or not.

Input Format

There will be multiple lines in the input file, each having a single non-empty string. You should read input till end-of-file.

The part of the code that handles input operation is already provided in the editor.

Output Format

For each case, print 'true' if the string is balanced, 'false' otherwise.

Sample Input

```
{ } ( )
( { ( ) } )
{ } (
[ ]
```

Sample Output

```
true
true
false
true
```

Change Theme

Language

Java 7



```
1 import java.util.*;
2
3 class Solution {
4
5     public static void main(String[] args) {
6
7         Scanner sc = new Scanner(System.in);
8
9         while (sc.hasNext()) {
10             String input = sc.next();
11             Stack<Character> stack = new Stack
12             boolean balanced = true;
13
14             for (char ch : input.toCharArray())
15
16                 if (ch == '(' || ch == '{' ||
17                     stack.push(ch);
18             } else {
19                 if (stack.isEmpty()) {
20                     balanced = false;
21                     break;
22                 }
23
24                 char top = stack.pop();
25
```

Line: 45 Col: 1

Upload Code as File

Run Code

Submit Code

☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

```
1 { } ( )
2 ( { ( ) } )
3 { } (
4 [ ]
```

Your Output (stdout)

```
1 true
2 true
3 false
4 true
```

Expected Output

Download

Problem

You are given a phone book that consists of people's names and their phone number. After that you will be given some person's name as query. For each query, print the phone number of that person.

Input Format

The first line will have an integer n denoting the number of entries in the phone book. Each entry consists of two lines: a name and the corresponding phone number.

After these, there will be some queries. Each query will contain a person's name. Read the queries until end-of-file.

Constraints:

A person's name consists of only lower-case English letters and it may be in the format 'first-name last-name' or in the format 'first-name'. Each phone number has exactly 8 digits without any leading zeros.

$$1 \leq n \leq 100000$$

$$1 \leq \text{Query} \leq 100000$$

Output Format

For each case, print "Not found" if the person has no entry in the phone book. Otherwise, print the person's name and phone number. See sample output for the exact format.

To make the problem easier, we provided a portion of the code in the editor. You can either complete that code or write completely on your own.

Sample Input

```
3
uncle sam
99912222
tom
11122222
harry
12299933
uncle sam
uncle tom
harry
```

Sample Output

```
uncle sam=99912222
Not found
harry=12299933
```

Change Theme

Language

Java 7

```
1 import java.util.*;
2
3 public class Solution {
4
5     public static void main(String[] args) {
6
7         Scanner sc = new Scanner(System.in);
8         int n = Integer.parseInt(sc.nextLine())
9
10        HashMap<String, String> phoneBook = ne
11
12        for (int i = 0; i < n; i++) {
13            String name = sc.nextLine();
14            String phone = sc.nextLine();
15            phoneBook.put(name, phone);
16        }
17
18        while (sc.hasNextLine()) {
19            String query = sc.nextLine();
20
21            if (phoneBook.containsKey(query))
22                System.out.println(query + "="
23            } else {
24                System.out.println("Not found"
25            }
26        }
27    }
28 }
```

Line: 31 Col: 1

Upload Code as File

Run Code

Submit Code

☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

Input (stdin)

Download

```
1 3
2 uncle sam
3 99912222
4 tom
5 11122222
6 harry
7 12299933
8 uncle sam
9 uncle tom
10 harry
```

Your Output (stdout)

Problem

For this problem, we have **2** types of queries you can perform on a **List**:

1. Insert **y** at index **x**:

Insert
x y

2. Delete the element at index **x**:

Delete
x

Submissions

Given a list, **L**, of **N** integers, perform **Q** queries on the list. Once all queries are completed, print the modified list as a single line of space-separated integers.

Leaderboard

Input Format

The first line contains an integer, **N** (the initial number of elements in **L**).

The second line contains **N** space-separated integers describing **L**.

The third line contains an integer, **Q** (the number of queries).

Discussions

The **2Q** subsequent lines describe the queries, and each query is described over two lines:

- If the first line of a query contains the String **Insert**, then the second line contains two space separated integers **x y**, and the value **y** must be inserted into **L** at index **x**.
- If the first line of a query contains the String **Delete**, then the second line contains index **x**, whose element must be deleted from **L**.

Editorial

Constraints

- $1 \leq N \leq 4000$
- $1 \leq Q \leq 4000$
- Each element in is a 32-bit integer.

Output Format

Print the updated list **L** as a single line of space-separated integers.

Sample Input

```
5
12 0 1 78 12
2
Insert
5 23
Delete
0
```

Sample Output

[Change Theme](#)

Language

Java 7



```
1 import java.util.*;
2
3 public class Solution {
4     public static void main(String[] args) {
5         Scanner sc = new Scanner(System.in);
6
7         int n = sc.nextInt();
8         List<Integer> list = new ArrayList<>()
9
10        for (int i = 0; i < n; i++) {
11            list.add(sc.nextInt());
12        }
13
14        int q = sc.nextInt();
15
16        while (q-- > 0) {
17            String operation = sc.next();
18
19            if (operation.equals("Insert")) {
20                int index = sc.nextInt();
21                int value = sc.nextInt();
22                list.add(index, value);
23            } else if (operation.equals("Delete")) {
24                int index = sc.nextInt();
25                list.remove(index);
26            }
27        }
28
29        for (Integer i : list) {
30            System.out.print(i + " ");
31        }
32        System.out.println();
33    }
34}
```

Line: 36 Col: 1

[Upload Code as File](#)[Run Code](#)[Submit Code](#)

Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.



Sample Test case 0

Input (stdin)

[Download](#)

```
1 5
2 12 0 1 78 12
3 2
4 Insert
5 5 23
6 Delete
7 0
```

Your Output (stdout)

```
1 0 1 78 12 23
```

Expected Output

[Download](#)

Problem

Let's play a game on an array! You're standing at index 0 of an n -element array named **game**. From some index i (where $0 \leq i < n$), you can perform one of the following moves:

- Move Backward: If cell $i - 1$ exists and contains a 0 , you can walk back to cell $i - 1$.
- Move Forward:
 - If cell $i + 1$ contains a zero, you can walk to cell $i + 1$.
 - If cell $i + \text{leap}$ contains a zero, you can jump to cell $i + \text{leap}$.
 - If you're standing in cell $n - 1$ or the value of $i + \text{leap} \geq n$, you can walk or jump off the end of the array and win the game.

Submissions

Leaderboard

In other words, you can move from index i to index $i + 1$, $i - 1$, or $i + \text{leap}$ as long as the destination index is a cell containing a 0 . If the destination index is greater than $n - 1$, you win the game.

Function Description

Complete the canWin function in the editor below.

canWin has the following parameters:

- int leap: the size of the leap
- int game[n]: the array to traverse

Discussions

Returns

- boolean: true if the game can be won, otherwise false

Input Format

The first line contains an integer, q , denoting the number of queries (i.e., function calls).

The $2 \cdot q$ subsequent lines describe each query over two lines:

1. The first line contains two space-separated integers describing the respective values of n and leap .
2. The second line contains n space-separated binary integers (i.e., zeroes and ones) describing the respective values of $\text{game}_0, \text{game}_1, \dots, \text{game}_{n-1}$.

Constraints

- $1 \leq q \leq 5000$
- $2 \leq n \leq 100$
- $0 \leq \text{leap} \leq 100$
- It is guaranteed that the value of $\text{game}[0]$ is always 0 .

Sample Input

STDIN	Function
4	$q = 4$ (number of queries)
5 3	$\text{game}[]$ size $n = 5$, $\text{leap} =$
0 0 0 0 0	$\text{game} = [0, 0, 0, 0, 0]$

Change Theme

Language Java 7

```
1 import java.util.*;
2
3 public class Solution {
4
5     public static boolean canWin(int leap, int
6         return canReach(0, leap, game);
7     }
8
9     private static boolean canReach(int pos, i
10
11     // Win if we reach or cross the end
12     if (pos >= game.length) {
13         return true;
14     }
15
16     // Invalid move
17     if (pos < 0 || game[pos] == 1) {
18         return false;
19     }
20
21     // Mark as visited
22     game[pos] = 1;
23
24     // Try jump, forward, and backward
25     return canReach(pos + leap, leap, game
```

Line: 51 Col: 1

Upload Code as File

Run Code

Submit Code

☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

Sample Test case 0

9 0 1 0

Your Output (stdout)

1	YES
2	YES
3	NO
4	NO

Expected Output Download

1	YES
2	YES
3	NO
4	NO

Problem

Sometimes it's better to use dynamic size arrays. Java's [Arraylist](#) can provide you this feature. Try to solve this problem using Arraylist.

You are given n lines. In each line there are zero or more integers. You need to answer a few queries where you need to tell the number located in y^{th} position of x^{th} line.

Take your input from System.in.

Input Format

The first line has an integer n . In each of the next n lines there will be an integer d denoting number of integers on that line and then there will be d space-separated integers. In the next line there will be an integer q denoting number of queries. Each query will consist of two integers x and y .

Constraints

- $1 \leq n \leq 20000$
- $0 \leq d \leq 50000$
- $1 \leq q \leq 1000$
- $1 \leq x \leq n$

Each number will fit in signed integer.

Total number of integers in n lines will not cross 10^5 .

Output Format

In each line, output the number located in y^{th} position of x^{th} line. If there is no such position, just print "ERROR!"

Sample Input

```
5
5 41 77 74 22 44
1 12
4 37 34 36 52
0
3 20 22 33
5
1 3
3 4
3 1
4 3
5 5
```

Sample Output

```
74
52
37
ERROR!
ERROR!
```

Explanation

The diagram below explains the queries:

	1	2	3	4	5
line 1	41	77	74	22	44
queries					

Change Theme

Language

Java 7

```
1  import java.util.*;
2
3  public class Solution {
4      public static void main(String[] args) {
5          Scanner sc = new Scanner(System.in);
6
7          int n = sc.nextInt();
8          ArrayList<ArrayList<Integer>> list = n
9
10
11         for (int i = 0; i < n; i++) {
12             int d = sc.nextInt();
13             ArrayList<Integer> row = new Array
14
15             for (int j = 0; j < d; j++) {
16                 row.add(sc.nextInt());
17             }
18
19             list.add(row);
20
21         }
22
23         int q = sc.nextInt();
24
25         for (int i = 0; i < q; i++) {
26             int x = sc.nextInt();
27             int y = sc.nextInt();
```

Line: 37 Col: 1

Upload Code as File

Run Code

Submit Code

☐ Test against custom input

Congratulations!

You have passed the sample test cases. Click the submit button to run your code against all the test cases.

✓ Sample Test case 0

Input (stdin)

Download

✓ Sample Test case 1

```
1  5
2  5 41 77 74 22 44
3  1 12
4  4 37 34 36 52
5  0
6  3 20 22 33
7  5
8  1 3
9  3 4
10 3 1
11 4 3
12 5 5
```