

1. What items are needed to set a PRV correctly? **Gauge, Allen Wrench, Spanner Wrench and Hydraulic Pressure**
2. The acronym FLOT stands for Flying Lead Orientation Tool. **True**
3. A standard hydraulic fitting can be used in place of a high-pressure hydraulic fitting. **False**
4. What is the difference between a PSIA and PSIG gauge? **Absolute & Gauge**
5. What can an absolute gauge do that a standard gauge cannot? **Show ambient pressure**
6. What is the ft. lb rating on a class one end effector? **50 ftlb to 200 ftlb, 36 cc motor**
7. It is acceptable to adjust a relief while the circuit is pressurized. **False**
8. What is the max input flow used on the CI high pressure kit? **8 gpm**
9. In order to increase a PRV setting you turn the adjustment valve counterclockwise. **False**
10. The wands that are included in the 5k water blaster kits are Cavi-Blaster Wand and High Pressure Water Wand? **True**
11. A super zip jet has 3 functions. **True**
12. A Seanic Torque Tool cannot be connected to the 12 station Valve Pack. **False**
13. All pump kits should be thoroughly flushed with sea water before storage. **False**
14. How many points of contact are required on manipulator held tools? **Two**
15. It is OK to modify tooling as needed without consent from the office. **False**
16. How often should torque tool verification units be certified? **Annually**