

Learning union of k-testable languages

Statistical and symbolic language modeling project

Rania el Bouhssini, Martin Laville and Félix Jamet

December 22, 2018

Contents

1	Introduction	2
2	k-test vector	3
2.1	Definition	3
2.2	Putting the pieces together	4
2.3	Tests	4
3	Sources	5

1 Introduction

Unless explicitly specified, all definitions and algorithms in this document are coming from Linard et al. [1].

We will present a possible implementation of those definitions and algorithms in a modular fashion, using Python3. Modular meaning here that we will implement concepts as they come and assemble them later as a whole when the necessary parts are complete. So if an `__init__` appears in the wild without its enclosing `class`, it's nothing to worry about.

2 k-test vector

2.1 Definition

A k-testable language can be described using a k-test vector which is a 4-tuple $Z = \langle I, F, T, C \rangle$:

- $I \in \Sigma^{k-1}$ is a set of allowed prefixes,
- $F \in \Sigma^{k-1}$ is a set of allowed suffixes,
- $T \in \Sigma^k$ is a set of allowed segments, and
- $C \in \Sigma^{<k}$ is a set of allowed short strings satisfying $I \cap F = C \cap \Sigma^{k-1}$.

We will refer to I , F , T and C respectively as the allowed prefixes, suffixes, infixes and short strings. An intuitive way to formulate the constraint on short strings is that the short strings of length $k - 1$ have to be both prefixes and suffixes and vice versa.

This definition can be translated into an init.

Init k-test vector:

```
def __init__(self, prefixes, suffixes, infixes, shorts):
    self.k = len(next(iter(prefixes))) + 1
    self.prefixes = prefixes
    self.suffixes = suffixes
    self.infixes = infixes
    self.shorts = shorts
    self.ensure_correct_definition()
```

We then write `ensure_correct_definition` to make sure that the created k-test vector respects the conditions of the definition.

Ensure correct definition:

```
def ensure_correct_definition(self):
    def same_length(collection, reference_length):
        return all(map(lambda x: len(x) == reference_length, collection))

    errors = []
    if not same_length(self.prefixes, self.k - 1):
        errors.append('incorrect prefix length')
    if not same_length(self.suffixes, self.k - 1):
        errors.append('incorrect suffix length')
    if not same_length(self.infixes, self.k):
        errors.append('incorrect infix length')
    if not all(map(lambda x: len(x) < self.k, self.shorts)):
        errors.append('incorrect short string length')
    presuffixes = self.prefixes & self.suffixes
    shorts_len_k = set(filter(lambda x: len(x) == self.k - 1, self.shorts))
    if presuffixes != shorts_len_k:
        errors.append('short strings conditions not satisfied')

    if len(errors) > 0:
        raise ValueError(', '.join(errors).capitalize() + '.')
```

2.2 Putting the pieces together

All the blocks seen previously are simply put together in the `ktestable` class.

```
class ktestable(object):
    <<Init k-test vector>>
    <<Ensure correct definition>>
```

2.3 Tests

We put together some tests to ensure that the implementation works at least superficially as intended:

```
tests = {
    'invalid example': ({'aa'}, {'aa'}, {'aaaa'}, {'ada'}),
    'valid example': ({'aa'}, {'aa'}, {'aaa'}, {'aa'})
}

for name, parameters in tests.items():
    try:
        aaaa = ktestable(*parameters)
        print('The creation of %s went well' % name)
    except ValueError as e:
        print('The creation of %s failed:\n - ' % name, e)
    print()
```

The creation of invalid example failed:

- Incorrect infix length, incorrect short string length, short strings conditions not satisfied.

The creation of valid example went well

3 Sources

1. Linard, A., de la Higuera C., Vaandrager F.: Learning Unions of k -Testable Languages (<http://www.sws.cs.ru.nl/publications/papers/fvaan/kTestable/main.pdf>)