Complex Hamiltonian learning, KAM stability and safe magnetic actuation of a clamped–free catheter model

The International Journal of Robotics Research
XX(X):1–43
©The Author(s) 0000
Reprints and permission:
sagepub.co.uk/journalsPermissions.nav
DOI: 10.1177/ToBeAssigned
www.sagepub.com/
SAGE

Anonymous authors

Abstract

We connect complex Hamiltonian learning, Kolmogorov–Arnold–Moser (KAM) theory and magnetic control for a clamped–free catheter model motivated by microgravity robotics. A consistent-mass beam retains the full magnetic potential and an explicit energy–dissipation balance. State-only COMSOL observations identify a finite-feature complex Hamiltonian network. Verified integral defects and nonzero training loss give coefficient, analytic-error and twist bounds; a separate a posteriori proof certifies an invariant torus of the same fitted function at approximately 1.9 mm amplitude. Magnetic force and torque feedback realizes this Hamiltonian in the first two physical modes despite damping. Stable higher modes lift the torus to the complete 64-mode closed loop, with an all-phase, all-time centreline bound below 1.971 mm for the specified startup. This construction complements the conservative positive-measure KAM families and the passive beam's global asymptotic stability. Independent COMSOL computations check the mechanics, magnetic gradients and nonlinear drag. Tests with unknown parameters, omitted physics and state noise distinguish identification from model-class error; causal adaptation reduces mean one-second prediction error from 387.5 to $9.9\,\mu$m on a declared drifting-parameter trajectory. A separate magnetic work governor guarantees clearance, and axial base feed with learned magnetic feedback tracks an S-shaped endpoint path with $6.42\,\mu$m RMS error. The results provide proofs, actual solver data and reproducible controls for one explicitly specified mechanical setting.

Keywords

magnetic catheter robots, complex Hamiltonian neural networks, KAM theory, finite elements, dissipation, safety control

1 Introduction

Magnetic actuation supplies remote forces and torques to small flexible robotic devices, including tools for minimally invasive intervention (Abbott et al. 2020; Kim et al. 2019). Their dynamics couple elasticity, magnetic fields, surrounding fluid and wall interaction. Long-duration space missions motivate investigating this interaction in reduced gravity. Documented spaceflight-associated fluid redistribution and neuro-ocular changes (NASA n.d.) provide application context; the present work studies mechanics and computation rather than a clinical or in-orbit procedure.

Hamiltonian neural networks (HNNs) learn dynamics through a scalar energy (Greydanus et al. 2019). Dissipative and port-Hamiltonian extensions add losses and external work (Zhong et al. 2020; Desai et al. 2021). Complex-valued networks provide coupled amplitude and phase representations (Trabelsi et al. 2018; Zhang et al. 2022), while KAM theory establishes persistence of quasiperiodic invariant motion under appropriately small Hamiltonian perturbations (Pöschel 2001; Bounemoura 2020). Combining these methods requires a quantitative bridge from the fitted model to the derivative norms, nonlinear twist and nonresonance hypotheses of a KAM theorem. A low trajectory error alone does not supply that bridge.

An equally important issue is mechanical consistency across the chain. A polynomial oscillator may permit a complete KAM calculation yet fail to represent the boundary conditions or magnetic actuation of the rod being studied. We therefore use one clamped–free magnetic beam for independent finite-element assembly, modal reduction, complex learning, nonlinear normal forms and dimensional safety calculations. The magnetic potential is retained as a full cosine. Its quartic expansion supplies twist; higher terms remain in the dynamics and in the analytic remainder. A constant bias field belongs to the conservative energy,

whereas changing the transverse field supplies work through a physical scalar port.

The contributions follow a single chain from mechanics to operation. First, the distributed rod and its complex energy–dissipation decoder retain the same physical power balance. Second, explicit statistical and deterministic estimates relate nonzero training loss to stability hypotheses. An independent COMSOL integral-learning experiment closes the coefficient and analytic-error bounds and the finite-amplitude KAM certificate for the same saved learned function. Third, a realizable force-and-torque feedback preserves that learned Hamiltonian in the first two modes of the damped beam; a stable-response construction lifts its torus to the complete finite-dimensional plant, with validated whole-centreline and actuator bounds. Fourth, a continuum clearance theorem supports safe magnetic tracking, including an S-shaped endpoint stroke. Unknown parameters, missing gradient and drag terms, observation noise and causal adaptation are tested separately, with matched controls and independent COMSOL validation.

2 Distributed mechanics and the unified magnetic model

2.1 Rod mechanics and a variationally consistent reduction

Following the spatial rod formulation (Simo 1985; Antman 2005), let $s \in [0, L]$ denote reference arclength, $r(s,t) \in \mathbb{R}^3$ the centreline and $D(s,t) \in SO(3)$ its director frame. Define

$$\Gamma = D^{\mathsf{T}} r_s, \quad D_s = D\widehat{\kappa}, \quad D_t = D\widehat{\omega}_b. \tag{1}$$

The hat map is defined by $\widehat{a}b = a \times b$. The extensible, unshearable Kirchhoff specialization has $\Gamma = (0, 0, 1+e)^{\mathsf{T}}$; inextensibility additionally sets $e = 0$. Transverse internal forces are then constraint reactions. They must not be set to zero by substituting zero shear into a shearable constitutive law. In spatial components the balances are

$$\rho A r_{tt} = n_s + f_{\mathrm{mag}} + f_{\mathrm{h}} + f_{\mathrm{c}} + \rho A g, \tag{2}$$

$$\partial_t (D \mathcal{J}_b \omega_b) = m_s + r_s \times n + \tau_{\mathrm{ext}}. \tag{3}$$

For constant body inertia, the left side of the second equation is $D(\mathcal{J}_b \dot{\omega}_b + \omega_b \times \mathcal{J}_b \omega_b)$. With stored energy density $W(\Gamma, \kappa)$, unconstrained components of $D^{\mathsf{T}} n$ and $D^{\mathsf{T}} m$ are its strain derivatives. A fixed base specifies position and orientation; a free tip specifies the appropriate force and moment resultants, including any concentrated magnetic load.

For a body-fixed magnetic moment density $\mu_b(s)$ and a static applied field $B_0(r)$, the magnetic potential is

$$V_{\mathrm{mag}} = -\int_0^L (D\mu_b) \cdot B_0(r)\, ds. \tag{4}$$

Its translational and rotational variations give $f_{\mathrm{mag}} = \nabla_r (\mu \cdot B_0)$ at fixed orientation and $\tau_{\mathrm{mag}} = \mu \times B_0$, where $\mu = D\mu_b$. Thus static magnetic loading belongs to the conservative energy. Field modulation supplies explicit time-dependent work or an input port. A fixed-orientation dipole approximation is equivalent to a consistent Maxwell-stress calculation in its regime of validity; the same load is not added twice.

More explicitly, the magnetic force on a finite material segment can be evaluated on a surrounding vacuum or nonmagnetic control surface Σ using

$$F_{\mathrm{mag}} = \int_\Sigma T_M n_\Sigma \, \mathrm{d}A, \qquad T_M = \mu_0^{-1}(BB^{\mathsf{T}} - \tfrac{1}{2}|B|^2 I). \tag{5}$$

Here B is the total field on the control surface, including the self-consistent magnetic contribution of the material. The associated moment is the integral of the moment arm crossed with $T_M n_\Sigma$. The dipole formulas above are its small-magnet reduction when the applied field varies slowly across the magnetic segment (Abbott et al. 2020).

A modified Morison-type local closure, stated per unit reference length, is

$$f_{\mathrm{h}} = m_f a_f + m_a(a_f - r_{tt}) - c_1 v_r - c_2 |v_r| v_r, \tag{6}$$

$$v_r = r_t - v_f, \qquad c_1, c_2 \geq 0. \tag{7}$$

Here $m_f = \rho_f A_f$ and m_a are displaced-fluid and added mass per unit length; a_f is the prescribed fluid acceleration. This is a reduced closure requiring calibration, not a solved Navier–Stokes interaction. In still fluid its drag power is $-c_1|r_t|^2 - c_2|r_t|^3$. In moving fluid it is dissipative relative to the fluid velocity and can do positive work on the rod. A constant added mass may be moved to the inertial side exactly once.

For a stationary wall, define penetration $\delta(r)$ positive inside the wall and $n_c = \nabla\delta$. One nonadhesive penalty model is

$$V_c = \frac{k_c}{m+1}[\delta]_+^{m+1}, \tag{8}$$

$$f_c = -k_c[\delta]_+^m n_c - c_c \mathbf{1}_{\{\delta>0\}}[\dot{\delta}]_+ n_c. \tag{9}$$

The elastic term is included through V_c and the second term dissipates power during compression. Friction can be added as a dissipative port. This switching law is used for force

accounting outside the contact-free KAM domain, not as an analytic perturbation through an impact.

Choose a configuration map $(r(s,q), D(s,q))$ that satisfies the essential boundary conditions and the rod constraints. A linear centreline ansatz alone is insufficient to specify rotational inertia. Define

$$r_i = \partial_{q_i} r, \qquad a_i = \mathrm{vee}(D^\mathsf{T} \partial_{q_i} D). \tag{10}$$

Then $\omega_b = \sum_i a_i \dot{q}_i$ and the reduced kinetic energy is

$$T_N = \tfrac{1}{2} \dot{q}^\mathsf{T} M(q) \dot{q}, \tag{11}$$

$$M_{ij}(q) = \int_0^L \left(\rho A r_i \cdot r_j + a_i^\mathsf{T} \mathcal{J}_b a_j \right) ds. \tag{12}$$

An added-fluid-mass contribution may be included when its consistent kinetic metric and associated inertial terms are specified. Otherwise hydrodynamic inertia remains in the generalized force balance and is not also included in M. Galerkin projection of the virtual-work identity gives

$$M(q)\ddot{q} + C(q,\dot{q})\dot{q} + \nabla V_N(q) = Q_{\mathrm{nc}}, \tag{13}$$

$$Q_i = \int_0^L (f \cdot r_i + \tau \cdot D a_i) ds + Q_i^\partial. \tag{14}$$

Here $C\dot{q}$ denotes the Christoffel contribution of M, and V_N contains elastic, static magnetic and retained gravitational potentials. Microgravity reduces the last contribution; it does not eliminate fluid drag or establish a particular blood-flow profile. Relative-flow drag, moving-base work and contact losses are retained in Q_{nc}. A stationary-fluid quadratic drag, for example, has nonpositive power; a moving fluid may inject energy. Contact switching is excluded from the analytic neighbourhood used for KAM analysis.

For $M(q) \succ 0$, the Legendre transform yields

$$p = M(q)\dot{q}, \qquad H_N(q,p) = \tfrac{1}{2} p^\mathsf{T} M(q)^{-1} p + V_N(q). \tag{15}$$

In particular, $\dot{p}_i = -\tfrac{1}{2} p^\mathsf{T} \partial_{q_i}(M^{-1}) p - \partial_{q_i} V_N + (Q_{\mathrm{nc}})_i$. The configuration dependence of inertia is retained. Potential forces appear either in V_N or in Q_{nc}, never both.

2.2 Complex energy–dissipation representation with an explicit decoder

Energy and Rayleigh dissipation have different physical units. Let E_0 and t_0 be reference energy and time, and choose diagonal position and momentum scales Q_0, P_0 with $Q_0^\mathsf{T} P_0 = E_0 t_0 I$. Set $q = Q_0 x$, $p = P_0 y$, $\tau = t/t_0$ and

$$h(x,y) = H_N(Q_0 x, P_0 y)/E_0, \tag{16}$$

$$d(x,v) = \frac{t_0}{E_0} \mathcal{D}_N(Q_0 x, Q_0 v/t_0). \tag{17}$$

Here $v = dx/d\tau$ and $\mathcal{D}_N$ is a Rayleigh dissipation potential. The two entries of $h + id$ are now dimensionless. A complex network provides coupled features and two physically decoded real readouts,

$$\mathcal{H}_\theta(x,y,v) = h_\theta(x,y) + i d_\theta(x,v), \tag{18}$$

$$h_\theta = h_{\mathrm{prior}} + h_{\mathrm{res},\theta}. \tag{19}$$

One admissible dissipative head is

$$d_\theta(x,v) = \tfrac{1}{2} v^\mathsf{T} D_\theta(x) v, \qquad D_\theta(x) = L_\theta(x) L_\theta(x)^\mathsf{T} \succeq 0. \tag{20}$$

More general heads may be used if $d_\theta(x,\cdot)$ is differentiable, convex and minimized at zero. The decoder is

$$v = \partial_y h_\theta, \qquad x' = v, \tag{21}$$

$$y' = -\partial_x h_\theta - \partial_v d_\theta(x,v) + B(x)u. \tag{22}$$

The derivative of d_θ is taken with respect to its independent velocity argument before substituting $v = \partial_y h_\theta$. It is not a total derivative through this substitution.

Proposition 1. Power-consistent complex representation. *For a differentiable h_θ, the decoded system satisfies*

$$\frac{dh_\theta}{d\tau} = -v^\mathsf{T} \partial_v d_\theta(x,v) + u^\mathsf{T} B(x)^\mathsf{T} v + \partial_\tau h_\theta. \tag{23}$$

For the quadratic head, the first term equals $-v^\mathsf{T} D_\theta(x) v \le 0$. For the convex head it is also nonpositive.

Proof. Apply the chain rule to h_θ and substitute (22). The two canonical terms cancel. Convexity and the minimum at zero imply $v^\mathsf{T} \partial_v d_\theta(x,v) \ge d_\theta(x,v) - d_\theta(x,0) \ge 0$.

With $z = (x + iy)/\sqrt{2}$, the canonical convention is $\{z_j, \bar{z}_k\} = -i\delta_{jk}$ and

$$z' = -i\partial_{\bar{z}} h_\theta - \frac{i}{\sqrt{2}} \partial_v d_\theta + \frac{i}{\sqrt{2}} B(x) u. \tag{24}$$

This is a unified complex representation of conservative and nonconservative dynamics with a specified physical decoder. The rule $z' = -i\partial_{\bar{z}}(h_\theta + i d_\theta)$ would generally produce a different vector field and has no automatic dissipativity guarantee. Real analyticity in (x,y), and a controlled analytic extension to a complex neighbourhood, are the relevant requirements for analytic KAM. Holomorphicity

Table 1. Declared parameters of the unified magnetic cantilever. These are illustrative mechanical parameters, not measurements from a clinical or spaceflight device.

Quantity	Symbol	Value
Length	L	$0.08\,\mathrm{m}$
Circular radius	r_c	$0.0006\,\mathrm{m}$
Young's modulus	E	$5.0 \times 10^6\,\mathrm{Pa}$
Density	ρ	$1100\,\mathrm{kg\,m^{-3}}$
Tip dipole	μ	$2.0 \times 10^{-5}\,\mathrm{A\,m^2}$
Axial bias field	B_0	$0.03\,\mathrm{T}$
Mass damping rate	α	$0.55558524\,\mathrm{s^{-1}}$
Transverse field amplitude	B_a	$0.006\,\mathrm{T}$
Drive frequency	Ω_d	$9.4449490\,\mathrm{rad\,s^{-1}}$
Ramp time	t_r	$0.25\,\mathrm{s}$
Uniform Hermite elements	N_e	32

in z alone is not required of a nonconstant real energy $h_\theta(z, \bar{z})$. In particular, ReLU or modReLU features require a separate smooth approximation or a theorem of appropriate regularity; their ordinary piecewise-smooth implementation is not analytic.

The dimensional specialization below uses explicit SI units. The learning and KAM statements use dimensionless canonical variables, with their energy and time scales declared before fitting.

2.3 One clamped–free magnetic beam throughout the computational study

We instantiate the rod reduction as a straight, planar, small-slope Euler–Bernoulli cantilever with a concentrated magnetic dipole at its free tip. The base position and slope are fixed. The elastic part is linear in curvature; the full trigonometric magnetic potential is retained. These choices define a reproducible mechanical specialization of the spatial rod, rather than a catheter-specific material identification. Table 1 states all dimensional parameters. Gravity, imposed fluid flow and field gradient are zero in this specialization. Still-fluid/structural losses are represented by a mass-proportional Rayleigh term. The more general force accounting above remains applicable when those terms are present.

Write $w(s,t)$ for transverse displacement and $\vartheta(t) = w_s(L,t)$ for the small-slope tip rotation. A uniform field $(B_0, B_y(t))$ has zero translational dipole force and the tip moment

$$M_{\mathrm{tip}} = \mu\{B_y(t)\cos\vartheta - B_0\sin\vartheta\}. \tag{25}$$

This is the natural moment boundary load. It does not impose a second kinematic constraint at the free tip. The magnetic potential is $-\mu(B_0\cos\vartheta + B_y\sin\vartheta)$, so that (25) follows by variation. Keeping this potential exact does not remove the small-slope approximation in the beam kinematics.

Let $q = (w_1, \vartheta_1, \ldots, w_{N_e}, \vartheta_{N_e})^{\mathsf{T}}$ contain the unconstrained cubic-Hermite nodal coordinates, e_ϑ select its final rotation, and M, K be the consistent mass and bending stiffness matrices. The physical equations and static-bias energy are

$$M\ddot{q} + \alpha M\dot{q} + Kq = e_\vartheta M_{\mathrm{tip}}, \tag{26}$$

$$H_0(q,p) = \tfrac{1}{2}p^{\mathsf{T}}M^{-1}p + \tfrac{1}{2}q^{\mathsf{T}}Kq + E_0\{1-\cos(e_\vartheta^{\mathsf{T}}q)\}, \tag{27}$$

$$E_0 = \mu B_0 = 6\times10^{-7}\,\mathrm{J}, \qquad p = M\dot{q}. \tag{28}$$

There is no axial end restraint and no artificial stretching quartic. The nonlinearity used in learning and in the KAM calculation is the magnetic nonlinearity of this same cantilever.

The static-field linearization is $K_b = K + E_0 e_\vartheta e_\vartheta^{\mathsf{T}}$. Choose $\Phi^{\mathsf{T}}M\Phi = I$ and $\Phi^{\mathsf{T}}K_b\Phi = \mathrm{diag}(\omega_j^2)$, with positive tip-slope entries fixing modal signs. For n retained modes, $q = \Phi_n a$, and the modal momentum is $\pi = \dot{a}$. Set $\omega_0 = \omega_1$, $\tau = \omega_0 t$, $\nu_j = \omega_j/\omega_0$, and

$$a_j = \sqrt{\frac{E_0}{\omega_0\omega_j}}X_j, \qquad \pi_j = \sqrt{\frac{E_0\omega_j}{\omega_0}}Y_j. \tag{29}$$

The product of each position–momentum scale is E_0/ω_0; division of energy by E_0 and rescaling time therefore give the standard dimensionless canonical equations. Define

$$S = \Phi_n\,\mathrm{diag}\sqrt{\frac{E_0}{\omega_0\omega_j}}, \quad d = S^{\mathsf{T}}e_\vartheta, \quad \ell(s)^{\mathsf{T}} = N(s)S, \tag{30}$$

where $N(s)$ is the Hermite displacement row. Thus the full centreline and tip slope are recovered in SI units as $w(s) = \ell(s)^{\mathsf{T}}X$ and $\vartheta = d^{\mathsf{T}}X$. The single dimensionless Hamiltonian used below is

$$h_*(X,Y) = h_2(X,Y) + R_{\mathrm{mag}}(X), \tag{31}$$

$$h_2 = \tfrac{1}{2}\sum_{j=1}^{n}\nu_j(X_j^2+Y_j^2), \tag{32}$$

$$R_{\mathrm{mag}} = 1 - \cos(d^{\mathsf{T}}X) - \tfrac{1}{2}(d^{\mathsf{T}}X)^2. \tag{33}$$

The subtracted quadratic avoids counting the static magnetic stiffness twice. For the two-mode model, $(\omega_1,\omega_2) = (11.41728728, 70.24049294)\,\mathrm{rad\,s^{-1}}$. All learned models use this fixed chart; states are not independently renormalized after fitting.

With $u = B_y/B_0$, $\gamma = \alpha/\omega_0$ and $\mathsf{N} = \mathrm{diag}(\nu_j)$, the physical port decoder becomes

$$X' = \partial_Y h, \tag{34}$$
$$Y' = -\partial_X h - \gamma \mathsf{N}^{-1}\partial_Y h + u\, d\cos(d^{\mathsf{T}}X). \tag{35}$$

For $h = h_*$, the damping term is exactly $-\gamma Y$. The Rayleigh head is $\mathcal{D}(v) = \frac{1}{2}\gamma v^{\mathsf{T}}\mathsf{N}^{-1}v$. For a learned energy, retaining the velocity-based form in (35) preserves nonnegative dissipation. Using $-\gamma Y$ after learning a momentum-dependent residual would, in general, lose that guarantee. The corresponding power identity is

$$h' = -\gamma(\partial_Y h)^{\mathsf{T}}\mathsf{N}^{-1}\partial_Y h + u\cos(d^{\mathsf{T}}X)d^{\mathsf{T}}\partial_Y h. \tag{36}$$

Alternatively, including $-u\sin(d^{\mathsf{T}}X)$ in the time-dependent energy moves the input power to $-u'\sin(d^{\mathsf{T}}X)$. These are equivalent bookkeeping conventions.

2.4 Independent COMSOL realization of the same discretization

The model was also constructed and solved in COMSOL Multiphysics 6.3.0.290 through LiveLink for MATLAB. Its two-dimensional Beam interface uses the Euler–Bernoulli formulation, 32 uniform elements, a consistent mass matrix, a fixed base, and the nonlinear tip moment (25). Geometric nonlinearity is disabled to match the declared small-slope mechanical model. The zero axial displacement subspace decouples, leaving 64 transverse displacement/rotation degrees of freedom.

After selecting transverse degrees of freedom by their field names and coordinates, the independently assembled COMSOL and Python mass and elastic stiffness matrices have relative Frobenius differences 7.76×10^{-15} and 3.05×10^{-14}, respectively. The first six modal frequencies agree to a maximum relative difference of 1.88×10^{-9}. These checks establish agreement of the stated discretizations; they do not establish the material validity of the chosen parameters. The native model, assembly exports, parameter values and time-domain verification records accompany the manuscript.

2.5 A global result for the unforced physical model

Proposition 2. Unforced global stability of the full FE target. *For the full clamped–free Hermite model (27), set $B_y = 0$. With the declared parameters, the potential is globally strongly convex and the origin is its unique equilibrium. If $\alpha > 0$, the origin is globally asymptotically stable. If $\alpha = 0$, every finite-energy trajectory remains in a bounded energy sublevel and the origin is Lyapunov stable. These are global statements for the declared small-slope mathematical model; they do not establish its physical validity at large deflections or a global property of arbitrary learned quartic residuals.*

Proof. Write $b = e_\vartheta$ and $U(q) = q^{\mathsf{T}}Kq/2 + E_0\{1 - \cos(b^{\mathsf{T}}q)\}$. The clamped conditions give $|w_s(L)|^2 \le L\int_0^L |w_{ss}|^2\, ds$, including for every Hermite finite-element function. Equivalently, $bb^{\mathsf{T}} \preceq [L/(EI)]K$; equality of the corresponding tip compliance follows from the static quadratic bending shape. Thus, for every q,

$$D^2U(q) = K + E_0\cos(b^{\mathsf{T}}q)bb^{\mathsf{T}}$$
$$\succeq (1-\kappa)K \succeq 0.905K, \tag{37}$$
$$\kappa = \frac{E_0 L}{EI} = \frac{8}{27\pi} < 0.095. \tag{38}$$

In particular, $\nabla U = 0$ only at $q = 0$. Both M and K are positive definite, and

$$H_0 \ge \tfrac{1}{2}p^{\mathsf{T}}M^{-1}p + \tfrac{1}{2}q^{\mathsf{T}}Kq.$$

Its sublevels are compact. Along the unforced dynamics,

$$\dot{H}_0 = -\alpha p^{\mathsf{T}}M^{-1}p \le 0.$$

This proves boundedness, global continuation and Lyapunov stability. For $\alpha > 0$, the largest invariant set with $\dot{H}_0 = 0$ has $p = 0$ and $\nabla U(q) = 0$, hence consists only of the origin. LaSalle's invariance principle on each compact sublevel gives global asymptotic stability.

3 Complex Hamiltonian learning

3.1 A fixed canonical chart

For a positive definite constant mass M and reference stiffness K_{ref}, select U such that $U^{\mathsf{T}}MU = I$ and $U^{\mathsf{T}}K_{\mathrm{ref}}U = \Omega^2$, where $\Omega = \mathrm{diag}(\omega_1, \ldots, \omega_n)$. In the magnetic specialization, $K_{\mathrm{ref}} = K_b$ includes the static-field stiffness. The transformation

$$q = U\Omega^{-1/2}Q, \qquad p = MU\Omega^{1/2}P \tag{39}$$

is symplectic: its configuration and momentum blocks satisfy $S_q^{\mathsf{T}}S_p = I$. Consequently $H_2 = \frac{1}{2}\sum_j \omega_j(Q_j^2 + P_j^2)$. The computational variables in (29) obey $(Q, P) = \sqrt{E_0/\omega_0}(X, Y)$, together with the stated energy and time normalization. That fixed dimensionless chart is used for training, derivative errors and normal forms. Arbitrary independent standardization of q and p is not silently treated

as canonical; optional training weights change the loss metric only.

Write $x = (Q, P)$ and use one complex normalization throughout:

$$z_j = \frac{Q_j + iP_j}{\sqrt{2}}, \quad I_j = z_j \bar{z}_j, \qquad \{z_j, \bar{z}_k\} = -i\delta_{jk}. \quad (40)$$

Wirtinger calculus gives $\partial_{\bar{z}_j} = (\partial_{Q_j} + i\partial_{P_j})/\sqrt{2}$ and therefore $\dot{z} = -i\partial_{\bar{z}} H$ for real H. This is a change of representation of a real symplectic system. Holomorphicity in z alone would exclude most real energy functions, including $H_2 = \sum_j \omega_j z_j \bar{z}_j$. The analyticity required by analytic KAM instead means a holomorphic extension of the real variables (Q, P) to a complex neighbourhood, in which z and $\bar{z}$ are independent linear combinations.

3.2 Architecture and objective

A shared complex feature map $F_\theta(z, \bar{z}, b)$, with magnetic configuration b, drives real readouts for H_θ and a dissipation factor L_θ. The latter defines $\mathcal{D}_\theta(q, v) = \frac{1}{2} \left\| L_\theta(q)^\mathsf{T} v \right\|^2$. The physical decoder in Section 2 determines the vector field. An affine complex layer has the real block realization

$$(A + iB)(a + ib) = (Aa - Bb) + i(Ba + Ab). \quad (41)$$

Thus complex weights impose a specific coupling, rather than furnishing an extra physical state. Smooth split activations $\sigma(a + ib) = \tanh(a) + i \tanh(b)$ are real analytic on bounded real domains and extend to a sufficiently small pole-free complex neighbourhood when weights are bounded. Their use does not justify assuming an arbitrarily wide analytic strip.

For observed dimensionless states and velocities, a suitable objective is

$$\widehat{\mathcal{L}} = \frac{1}{N} \sum_{i=1}^{N} \left\| \widehat{\dot{x}}_i - f_\theta(x_i, u_i) \right\|^p + \lambda_E \widehat{\mathcal{L}}_E + \lambda_R \mathcal{R}(\theta). \quad (42)$$

Energy observations, if available, fix a gauge through $\widehat{\mathcal{L}}_E$; vector-field training alone identifies H only up to a constant. To infer conservative gradient error from the full decoder loss, errors in dissipation and inputs must first be bounded or measured and included in the label-error budget. They cannot be absorbed into a Hamiltonian residual merely because their magnitudes are small.

The reproducible experiments specialize this architecture to a finite analytic complex feature network. The exact magnetic feature R_{mag} in (33) is represented by complex exponentials and a quadratic correction, with a learned real readout. Quartic features complement its degree-four Taylor coefficient; this keeps the full cosine target in the hypothesis class while avoiding a duplicate quartic direction. Products of complex affine forms and their conjugates generate all real quadratic and quartic monomials. They can be implemented by a finite network with polynomial activation, using $uv = ((u + v)^2 - (u - v)^2)/4$. A real readout combines the full magnetic analytic feature with the polynomial residual; conjugate features enforce the reality of the energy. The prescribed features exclude a spurious cubic term and, for the gray-box model, preserve the known static-field quadratic part exactly. Fitting the output coefficients from energy derivatives is linear least squares. The experiment therefore tests an explicitly specified finite-feature CHNN. The magnetic coefficient and residual readouts are fitted from data; no claim about optimization of an unrestricted deep network is needed.

3.3 What complex approximation theory establishes

Theorem 1 in the complex-reaction literature (Zhang et al. 2022) gives universal approximation for a specified reaction activation and an L^2 distributional criterion. Its comparison with real networks is tied to the stated function classes and resources. Such a theorem supplies neither higher derivative accuracy nor a universal advantage for magnetic catheter energies. In particular, piecewise reaction activations cannot be inserted unchanged into a smooth KAM proof.

There is nevertheless a direct smooth approximation route. A split-complex network with real-part output contains real smooth networks: for an input $(Q + iP)/\sqrt{2}$, choose first-layer complex weights $\sqrt{2}(A_Q - iA_P)$ to obtain real preactivation $A_Q Q + A_P P + b$. Subsequent real weights keep the real channel independent of the imaginary channel. Finite-order derivative approximation for smooth real networks (Hornik 1991) is thereby inherited as an existence result. Alternatively, on a compact box where a target has a convergent analytic power series, truncation gives a polynomial approximation with uniformly controlled derivatives. Those polynomials are realizable by the complex polynomial features used here. Training and a quantitative certificate are still required to establish that a particular fitted network attains the error needed for KAM.

4 From nonzero training loss to KAM persistence

4.1 A statistical bridge in the norm required by KAM theory

All Hamiltonians below are real-valued scalar functions, including when their parameters and hidden representations are complex. The realification of a complex parameter vector has dimension P. Let $\mathcal{D} = \mathbb{T}^n \times B$, where B is a bounded ball in action space, and write $d = 2n$. Lebesgue measure on $\mathcal{D}$ is denoted by dx. The following result completes the derivative-norm interface needed to combine the learning argument of Chen et al. (2022) with a finite-differentiability KAM theorem. It does not infer derivative smallness from function values alone.

Theorem 3. Uniform learning-to-C^ℓ bound. *Fix $d < p < \infty$, an integer $\ell \geq 1$, and an integer $s > \ell + d/p$. Let $X_1, \dots, X_N$ be independent samples with density $f_\mu \geq m_0 > 0$ on $\mathcal{D}$. Let $H_\star$ be the target Hamiltonian and $\{H_\vartheta : \vartheta \in \Theta\}$ the hypothesis class, with $\Theta \subset [-B_\Theta, B_\Theta]^P$. Assume that for all $x \in \mathcal{D}$ and $\vartheta, \eta \in \Theta$,*

$$\|\nabla H_\vartheta(x) - \nabla H_\star(x)\|_p \leq Q, \tag{43}$$

$$\|\nabla H_\vartheta(x) - \nabla H_\eta(x)\|_p \leq L_g \|\vartheta - \eta\|_\infty. \tag{44}$$

After fixing the additive gauge by

$$e_\vartheta = H_\vartheta - H_\star - \frac{1}{|\mathcal{D}|}\int_{\mathcal{D}} (H_\vartheta - H_\star)\, dx,$$

$$\sup_{\vartheta \in \Theta} \|e_\vartheta\|_{W^{s,p}(\mathcal{D})} \leq M_s, \tag{45}$$

suppose that M_s is a valid uniform bound. Define

$$\widehat{R}_N(\vartheta) = \frac{1}{N}\sum_{i=1}^{N} \|\nabla H_\vartheta(X_i) - \nabla H_\star(X_i)\|_p^p, \tag{46}$$

$$L_{\mathrm{par}} = pQ^{p-1}L_g, \qquad L_{\max} = Q^p. \tag{47}$$

For any fixed $0 < a \leq 2B_\Theta$ and $0 < \delta < 1$, put

$$\Gamma_N(a,\delta) = 2L_{\mathrm{par}}a + \frac{L_{\max}}{\sqrt{2N}}\sqrt{P\log(1 + 2B_\Theta/a) + \log(1/\delta)}, \tag{48}$$

$$S_N(\vartheta) = \widehat{R}_N(\vartheta) + \Gamma_N(a,\delta), \tag{49}$$

$$G_N(\vartheta) = C_{\mathrm{P}}\, m_0^{-1/p} S_N(\vartheta)^{1/p}, \tag{50}$$

$$\alpha = \frac{\ell - 1 + d/p}{s - 1} \in (0,1). \tag{51}$$

Here C_{P} is a Poincare constant chosen so that a mean-zero function satisfies $\|e\|_{W^{1,p}} \leq C_{\mathrm{P}}\|\nabla e\|_{L^p}$. With probability at least $1 - \delta$, simultaneously for every $\vartheta \in \Theta$,

$$\|e_\vartheta\|_{C^\ell(\overline{\mathcal{D}})} \leq E_N(\vartheta) := C_{\mathrm{GN}}\left[G_N(\vartheta) + M_s^\alpha G_N(\vartheta)^{1-\alpha}\right]. \tag{52}$$

C_{GN} depends only on the domain and (d, p, s, ℓ). We use $\|e\|_{C^\ell} = \max_{|a|\leq\ell} \sup |D^a e|$; equivalent conventions only change the displayed constants. The event is uniform over the hypothesis class and therefore includes parameters selected using these same training data.

Proof. The loss $r_\vartheta(x) = \|\nabla H_\vartheta(x) - \nabla H_\star(x)\|_p^p$ lies in $[0, L_{\max}]$ and is L_{par}-Lipschitz in the ℓ^∞ parameter metric. Partitioning the parameter cube into cells of side length a and choosing a representative from each nonempty cell gives an a-net with at most $(1 + 2B_\Theta/a)^P$ points. The one-sided Hoeffding inequality and a union bound control $R(\eta) - \widehat{R}_N(\eta)$ at every net point by the square-root term in Γ_N, where $R(\eta) = \int r_\eta\, d\mu$. The population and empirical losses each change by at most $L_{\mathrm{par}}a$ between a parameter and its net representative. Consequently $R(\vartheta) \leq S_N(\vartheta)$ uniformly.

The density lower bound gives $\|\nabla e_\vartheta\|_{L^p(dx)} \leq m_0^{-1/p} S_N(\vartheta)^{1/p}$. The gauge in (45) and Poincare's inequality then yield $\|e_\vartheta\|_{W^{1,p}} \leq G_N(\vartheta)$. Apply the Gagliardo–Nirenberg inequality to $g = \nabla e_\vartheta$, with derivative orders $j = \ell - 1$, $m = s - 1$, and both endpoint Lebesgue exponents equal to p. Its interpolation identity is

$$0 = \frac{j}{d} + \alpha\left(\frac{1}{p} - \frac{m}{d}\right) + \frac{1-\alpha}{p},$$

which gives the stated α. The strict inequality $s > \ell + d/p$ ensures $\alpha < 1$ and avoids the critical Sobolev endpoint. Extension from the smooth bounded action domain, together with periodic charts in the angular variables, gives

$$\|e\|_{C^\ell} \leq C_{\mathrm{GN}}\left(\|e\|_{W^{1,p}} + \|e\|_{W^{1,p}}^{1-\alpha}\|e\|_{W^{s,p}}^{\alpha}\right).$$

Lower-order derivatives are included by the inhomogeneous term and the $W^{1,p} \hookrightarrow C^0$ embedding, which uses $p > d$. Substitution proves (52).

For instance, one may select an integer $\ell > 2(\tau + 1)$, $p > 2n$, and $s = \ell + 1$. This makes every exponent explicit, although the resulting interpolation bound can be conservative. Bounds on M_s, Q, L_g follow from bounded parameters and derivatives of smooth activations on a compact domain; the corresponding bounds for $H_\star$ must also be justified. Merely declaring the functions smooth does not provide these quantitative bounds. Alternatively, a loss containing all spatial derivatives of the vector field through order ℓ controls $W^{\ell+1,p}$ directly, and Sobolev

embedding then gives a C^ℓ error with exponent $1/p$, without interpolation.

Corollary 4. KAM transfer for the target and the trained Hamiltonian. *Let $n \geq 2$, $\tau > n-1$ and an integer $\ell > 2(\tau+1)$ be fixed. Suppose that, in one specified canonical action–angle chart,*

$$H_\star = h_0(I) + P_\star(I,\varphi), \qquad H_\vartheta = h_0(I) + P_\vartheta(I,\varphi).$$

Assume $h_0 \in C^{\ell+2}(\overline{B})$ with finite norm, and $\nabla h_0 : B \to \Omega$ is a diffeomorphism with bounded inverse in C^ℓ. Fix $\gamma > 0$ and set

$$\Omega_{\gamma,\tau} = \left\{ \omega \in \Omega : \begin{array}{l} |k\cdot\omega| \geq \gamma |k|_1^{-\tau} \ (0 \neq k \in \mathbb{Z}^n), \\ \operatorname{dist}(\omega, \partial\Omega) \geq \gamma \end{array} \right\}. \tag{53}$$

Let $c_{\mathrm{K}} > 0$ be the constant in Theorem A of Bounemoura (2020) for this domain and integrable Hamiltonian. If a certified bound $\beta_\vartheta \geq \|P_\vartheta - \overline{P}_\vartheta\|_{C^\ell}$ satisfies

$$\beta_\vartheta + E_N(\vartheta) < c_{\mathrm{K}} \gamma^2, \tag{54}$$

then, on the event in Theorem 3, both $H_\star$ and H_ϑ possess invariant Lagrangian tori for every frequency in $\Omega_{\gamma,\tau}$. The flow on each torus is C^1-conjugate to the linear flow with that frequency. For a piecewise smooth frequency-domain boundary, the complement of each family has measure at most $C\gamma$. In particular, each family has positive measure when γ is small enough.

Proof. Write $\overline{P}$ for the spatial mean over $\mathcal{D}$. The gauge-fixed difference satisfies

$$P_\star - \overline{P}_\star = P_\vartheta - \overline{P}_\vartheta - e_\vartheta.$$

Thus the two perturbation norms are at most β_ϑ and $\beta_\vartheta + E_N(\vartheta)$, respectively. Constants added to a Hamiltonian do not change its vector field. Apply the cited finite-smoothness KAM theorem separately to the two Hamiltonians with the same h_0, domain, and Diophantine set. The theorem supplies tori of class $C^{\tau+1}$ with Lipschitz dependence as invariant graphs on frequency. The two systems need not have identical invariant embeddings.

The certified budget includes the physical perturbation from h_0, any normal-form remainder, and the learning error. A small learning error alone does not establish that the physical system is close to an integrable one. Theorem A in the published 2020 version of Bounemoura (2020) gives the measure bound $C\gamma$; the $C\gamma^2$ measure bound printed in the 2018 preprint should not be used.

4.2 A coefficient certificate for a finite analytic CHNN

The finite analytic readout used in the experiments yields a stronger certificate that avoids a dimension-dependent interpolation loss. Let $\psi_1, \ldots, \psi_m$ be real-valued basis functions on the real phase domain. Complex features may be converted into this basis by taking their real and imaginary parts and collecting equal monomials. The certificate applies to the effective coefficients of the actual trained Hamiltonian, irrespective of how they are parameterized inside the network.

Proposition 5. Deterministic global certificate from sampled gradients. *Suppose*

$$H_\vartheta = H_{\mathrm{prior}} + \sum_{j=1}^m c_{\vartheta,j}\psi_j,$$
$$H_\star = H_{\mathrm{prior}} + \sum_{j=1}^m c_{\star,j}\psi_j + R.$$

The basis contains no constant gauge direction. Let

$$G_N = \frac{1}{N}\sum_{i=1}^N D\psi(X_i)^\top D\psi(X_i),$$
$$\lambda_N = \lambda_{\min}(G_N) > 0,$$

where the jth column of $D\psi$ is $\nabla\psi_j$. For gradient observations $Y_i = \nabla H_\star(X_i) + \xi_i$, define

$$r_N = \left(\frac{1}{N}\sum_i \|\nabla H_\vartheta(X_i) - Y_i\|_2^2\right)^{1/2},$$
$$t_N = \left(\frac{1}{N}\sum_i \|\nabla R(X_i) + \xi_i\|_2^2\right)^{1/2}.$$

Then

$$\|c_\vartheta - c_\star\|_2 \leq \frac{r_N + t_N}{\sqrt{\lambda_N}}. \tag{55}$$

For any function norm $\|\cdot\|_{\mathcal{X}}$ satisfying the triangle inequality, put $K_{\mathcal{X}} = (\sum_j \|\psi_j\|_{\mathcal{X}}^2)^{1/2}$. If $\|R\|_{\mathcal{X}} \leq \varepsilon_R$, then

$$\|H_\vartheta - H_\star\|_{\mathcal{X}} \leq K_{\mathcal{X}} \frac{r_N + t_N}{\sqrt{\lambda_N}} + \varepsilon_R. \tag{56}$$

The norm may be C^ℓ on a real compact domain or the supremum norm on a prescribed complex neighborhood where every basis function and R is holomorphic. No independent sampling assumption is needed.

Proof. Let $\Delta c = c_\vartheta - c_\star$. The empirical norm of $D\psi\Delta c$ is $(\Delta c^\top G_N \Delta c)^{1/2}$. Since $D\psi\Delta c = (\nabla H_\vartheta - Y) + (\nabla R + \xi)$ at every sample, the triangle inequality gives $\sqrt{\lambda_N}\|\Delta c\|_2 \leq$

$r_N + t_N$. Finally, $\|\sum_j \Delta c_j \psi_j - R\|_{\mathcal{X}} \le K_{\mathcal{X}} \|\Delta c\|_2 + \varepsilon_R$ by Cauchy–Schwarz.

For raw monomials $\psi_\nu(x) = x^\nu$, an explicit C^ℓ bound on $[-r, r]^d$ is obtained from

$$\|\psi_\nu\|_{C^\ell} \le \max_{|a|\le \ell,\, a \le \nu} \frac{\nu!}{(\nu - a)!}\, r^{|\nu|-|a|}.$$

The analytic sup norm on $\{|x_j| \le r\} \subset \mathbb{C}^d$ is $r^{|\nu|}$. For all 35 degree-four monomials in four variables, $K_{\mathrm{an}} \le \sqrt{35}\, r^4$. If a canonical chart $x = \Phi(I, \varphi)$ maps an action–angle complex domain into this polydisc, the same analytic bound holds after composition. For a C^ℓ certificate after composition, the derivative bounds of Φ must instead be included by the chain rule. Unmodeled physical terms require the tail bounds t_N and ε_R. Their approximation-tail contribution is zero only when the target lies exactly in the declared class. The full-cosine feature class below has this property for its specified reduced target; it does not remove truncation error relative to the full beam.

The statistical result requires independent state samples with the stated coverage density. Consecutive states on a trajectory do not satisfy this assumption automatically. Accordingly, the trajectory-based experiments below use the deterministic Gram certificate, which requires no sampling independence. Their implementation divides both squared residuals and the Gram matrix by $4N$ rather than N; the coefficient bound is unchanged provided the noise norm uses that same scalar-observation normalization.

5 Nonlinear stability of the learned magnetic model

5.1 Normal form of the same magnetic cantilever

In the dimensionless chart of Section 2.3, write

$$\begin{aligned} h_\star &= h_2 + g(d^\top X), \\ h_2 &= \frac{1}{2}\sum_{j=1}^{n} \nu_j (X_j^2 + Y_j^2), \\ g(z) &= 1 - \cos z - \frac{z^2}{2}. \end{aligned} \tag{57}$$

The magnetic term in this expression is the complete analytic function. In particular, its fourth-order part and its untruncated remainder are

$$\begin{aligned} h_{4,\star} &= -\frac{(d^\top X)^4}{24}, \\ T_{6,\star} &= 1 - \cos(d^\top X) - \frac{(d^\top X)^2}{2} \\ &\quad + \frac{(d^\top X)^4}{24}. \end{aligned}$$

Proposition 6. Magnetic twist and analytic tail. *Let $I_j = (X_j^2 + Y_j^2)/2$, and let $A_\star$ denote the Hessian with respect to I of the angular average of $h_{4,\star}$. With $v = (d_1^2, \dots, d_n^2)^\top$,*

$$\begin{aligned} (A_\star)_{jj} &= -\frac{d_j^4}{8}, \\ (A_\star)_{ij} &= -\frac{d_i^2 d_j^2}{4} \quad (i \ne j), \\ A_\star &= \frac{\mathrm{diag}(d_j^4) - 2vv^\top}{8}. \end{aligned} \tag{58}$$

and

$$\det A_\star = (1 - 2n) 8^{-n} \prod_{j=1}^{n} d_j^4. \tag{59}$$

Thus every retained mode with nonzero tip-rotation participation contributes to a nonsingular twist. For $n \ge 2$, the twist has one negative and $n - 1$ positive eigenvalues; positive definiteness is not required here. If $D = \sum_j |d_j|$ and $\mathbb{D}_r^{2n}$ is a complex Cartesian polydisc, then

$$\|T_{6,\star}\|_r \le \frac{(Dr)^6}{720} \cosh(Dr). \tag{60}$$

Proof. The angular averages are $\langle X_j^4 \rangle = 3I_j^2/2$ and $\langle X_i^2 X_j^2 \rangle = I_i I_j$. All terms with an odd exponent in some X_j have zero average. Substitution gives (58). Factoring $\mathrm{diag}(d_j^2)$ on both sides gives a matrix congruent to $(I_n - 2\mathbf{1}\mathbf{1}^\top)/8$. Its eigenvalues are $1/8$ with multiplicity $n - 1$ and $(1 - 2n)/8$, which proves the determinant and inertia statements. For the analytic tail, expand the cosine and use $(6 + 2k)! \ge 6!(2k)!$ and $|d^\top X| \le Dr$.

For the two-mode, 32-element model, the magnetic-bias modes give $\nu \simeq (1, 6.152117504)$ and $d \simeq (0.22567077, 0.32179881)$. Consequently $\det A_\star \simeq -1.303708 \times 10^{-6}$ and $\sigma_{\min}(A_\star) \simeq 5.8064 \times 10^{-4}$. These quantities belong to the same cantilever model used for learning and shape reconstruction.

5.2 Complete learned Hamiltonian and transfer of twist

The fitted family is

$$h_\eta = h_2 + \frac{b}{s_4}\, g(d^\top X) + \sum_{j=1}^{34} c_j \psi_j(X, Y), \qquad (61)$$

where $\eta = (b, c_1, \ldots, c_{34})$, $a = b/s_4$, $s_4 = \|q_\star\|_2$ is the fixed quartic coefficient normalizer and the ψ_j span the coefficient-space complement of the target quartic direction. The class contains the complete target at $\eta_\star = (s_4, 0, \ldots, 0)$; no cosine truncation error is assigned to the training labels. The polynomial part is represented by matched real or complex features. All bounds use the actually exported feature matrix, so numerical orthogonality of its columns is not a proof assumption.

Let $F(z) = \big(g(d^\top X)/s_4, \psi_1(z), \ldots, \psi_{34}(z)\big)$, and put $D(z) = [\nabla F_0(z), \ldots, \nabla F_{34}(z)] \in \mathbb{R}^{4\times 35}$. With $G_N = (4N)^{-1} \sum_i D(z_i)^\top D(z_i)$, $\lambda_{\min}(G_N) \geq \underline{\lambda} > 0$, empirical derivative root-mean-square loss r_N (averaged over all $4N$ scalar observations), and a certified derivative-label error with the same root-mean-square normalization bounded by ϵ_N, the deterministic estimate is

$$\|\eta - \eta_\star\|_2 \leq b_N := \frac{r_N + \epsilon_N}{\sqrt{\underline{\lambda}}}. \qquad (62)$$

This estimate follows from the smallest singular value of the stacked derivative design matrix and the triangle inequality.

The effective quartic coefficient vector is $q_\eta = (b/s_4)q_\star + Uc$, where U is the exported matrix of polynomial features. Let $\mathcal{A}q$ be the symmetric twist matrix obtained by angular averaging. Then the directly computable bound

$$\|A_\eta - A_\star\|_2 \leq \|\mathcal{A}[q_\star/s_4\, U]\|_{2\to F}\, b_N + \delta_{A,\mathrm{dec}} < \sigma_{\min}(A_\star) \qquad (63)$$

is sufficient for nonsingularity of the trained twist. The subscript F denotes the Frobenius norm on symmetric matrices. In the two-mode raw quartic basis, the previously derived bound $\|\mathcal{A}\Delta q\|_2 \leq \sqrt{19}\|\Delta q\|_2$ is also valid. A direct rational or interval check of A_η can be sharper than the sufficient loss-based bound. Here $\delta_{A,\mathrm{dec}}$ bounds the exported decoder's rounding error relative to its exact coefficient map; it is zero for exact arithmetic and is explicitly included in the numerical certificate. Specifically, the exported effective-quartic coefficient error δ_{dec} gives $\delta_{A,\mathrm{dec}} = \sqrt{19}\delta_{\mathrm{dec}}$.

Define the finite-feature analytic bound by

$$B_F(r)^2 = \left(\frac{(Dr)^4}{24 s_4}\cosh(Dr)\right)^2 + r^8 \sum_{j=1}^{34} \|\psi_j\|^2_{\mathrm{coeff},1}.$$

The same coefficient estimate gives a complete analytic perturbation bound,

$$\|h_\eta - h_\star\|_r \leq b_N B_F(r) + \delta_{h,\mathrm{dec}}(r). \qquad (64)$$

This controls the entire learned function on a complex domain, including every higher-order magnetic term.

Suppose $\alpha_4 = \min_{0<|k|_1\leq 4} |k\cdot\nu| > 0$. The exact quartic Lie transformation associated with the full effective $h_{4,\eta}$ gives

$$h_\eta \circ \Phi_\eta = \nu\cdot I + \tfrac{1}{2} I^\top A_\eta I + \mathcal{R}_{6,\eta}.$$

If C_4, C_Z, C_χ are the Cartesian coefficient norms of its quartic part, angular average and homological generator, then

$$\|\mathcal{R}_{6,\eta}\|_r \leq 512 C_\chi (C_4 + C_Z) r^6 + \frac{|a|(2Dr)^6}{720}\cosh(2Dr). \qquad (65)$$

This holds when $32 C_\chi r^2 < 1$. The first term is the exact quartic Lie remainder; the second bounds $aT_{6,\star}\circ\Phi_\eta$ because the time-one flow maps the radius-r polydisc into the radius-$2r$ polydisc. This identity retains the full cosine rather than applying a theorem to an isolated quartic approximation.

With nonsingular A_η and fourth-order nonresonance, the ordinary Kolmogorov theorem applies on sufficiently small positive-action boxes (Pöschel 2001). Indeed, their action width is $O(r^2)$, their integrable Hessian is A_η, and (65) is $O(r^6)$. Choosing a Diophantine constant proportional to r^2 makes the analytic KAM smallness quotient $O(r^2)$; reducing its proportionality constant first leaves a positive-measure set of admissible frequencies. This establishes local KAM families for the complete target and trained cantilever Hamiltonians. The finite-amplitude result below is verified separately by an a posteriori theorem and is not inferred from this asymptotic statement.

5.3 Validated invariant tori at finite physical amplitude

The local normal-form argument can be supplemented by a finite-amplitude certificate for the same complete Hamiltonian. We use the a posteriori theorem of Haro and

Luque (2019); the equation and table numbering below refer to Theorem 3.1 and Appendix B, Tables 1–3, of its archived preprint, arXiv:1711.05515v1. The computation includes the analytic interpolation error and uses ball arithmetic, rather than identifying a small residual at finitely many sample points with an analytic norm.

The mathematical model certified here is specified exactly by the exported binary coefficients. In particular,

$$\begin{aligned} \nu &= \left(1, \frac{6926668524826847}{1125899906842624}\right), \\ d &= \left(\frac{4065323231059343}{18014398509481984}, \frac{2898505962069547}{9007199254740992}\right). \end{aligned} \tag{66}$$

The target uses $a = 1$ and zero quartic residual in (61). Each trained case uses the exact dyadic value of its exported cosine multiplier and every exported quartic coefficient. This convention identifies the function being certified without hiding floating-point parameter uncertainty. It establishes a result for the exported two-mode reduction; independent finite-element and COMSOL comparisons do not themselves prove an infinite-dimensional KAM theorem for the continuum beam.

Theorem 7. Finite-amplitude tori of the target and trained models. *For the target Hamiltonian (57), with parameters (66), for each of the three primary exported GC Hamiltonians with training seeds 17, 43, and 91, and for the additional seed-17 fit at noise amplitude 10^{-8}, and for the GC model fitted to independent COMSOL position–velocity trajectories, there is a real analytic, embedded Lagrangian torus $K_\infty : \mathbb{T}^2 \to \mathbb{R}^4$ satisfying the invariance equation below, with the displayed frequency for the first five models:*

$$\begin{aligned} X_h(K_\infty) &= DK_\infty \varpi, \\ \varpi &= \frac{w_1}{2\pi}(1, \zeta), \\ w_1 &= \frac{49999589341}{50000000000}. \end{aligned} \tag{67}$$

where, with $\phi = (1+\sqrt{5})/2$,

$$\zeta = \frac{1876278\phi + 592877}{304979\phi + 96369}. \tag{68}$$

For the COMSOL-fitted model, the frequency is instead specified by

$$\begin{aligned} w_1 &= \frac{99999143141}{100000000000}, \\ \zeta &= \frac{974993\phi + 427310}{158480\phi + 69457}. \end{aligned} \tag{69}$$

It is chosen near that actual model's quartic normal-form frequency. Angles have period one; ϖ is measured in cycles per unit dimensionless time. Each torus lies within 3×10^{-41}, in the supremum norm on the complex strip of width $1/80$, of its delivered finite Fourier polynomial. The reconstructed beam has nonzero millimetre-scale motion: the certified tip-displacement witness and the bound valid for every point of the centerline are given in Table 2.

Proof. We give the analytic estimates and specify the finite checks that close them. Vector norms are maximum norms. Following the source convention, analytic matrix norms are $\max_i \sum_j \sup_\theta |M_{ij}(\theta)|$, with componentwise suprema on $\mathbb{T}^2_\rho = \{\theta : |\operatorname{Im}\theta|_\infty < \rho\}$. The phase-space domain is $\mathbb{D}^4_{3/10}$.

Frequency and the cohomological equation. The continued fraction of ζ has prefix $[6; 6, 1, 1, 2, 1, 23, 1, 13, 6, 3]$ followed by an infinite tail of ones. For the COMSOL-fitted model the prefix is $[6; 6, 1, 1, 2, 1, 20, 1, 1, 4, 1, 1, 3, 2]$, also followed by ones. All partial quotients in either case are at most 23. The bounded-partial-quotient inequality gives $|q\zeta - p| \geq 1/(25|q|)$ for $q \neq 0$. As $w_1 > 9/10$ and $2\pi < 7$, this implies

$$|k \cdot \varpi| \geq \frac{\gamma}{|k|_1}, \qquad \gamma = \frac{9}{1750}, \qquad k \in \mathbb{Z}^2 \setminus \{0\}. \tag{70}$$

The case $k_2 = 0$ follows directly from $\varpi_1 > 9/70$. We use the weaker exponent $\tau_K = 3$ in the a posteriori theorem. For a zero-mean analytic function v, Fourier division by $2\pi i k \cdot \varpi$ and the count $\#\{k : |k|_1 = j\} = 4j$ give, with $q = e^{-2\pi\delta}$,

$$\begin{aligned} \|\mathcal{R}_\varpi v\|_{\rho-\delta} &\leq \frac{2}{\pi\gamma}\frac{q(1+q)}{(1-q)^3}\|v\|_\rho \\ &\leq \frac{e^{4\pi\rho}}{2\pi^4\gamma\delta^3}\|v\|_\rho < \frac{\|v\|_\rho}{\gamma\delta^3}. \end{aligned}$$

These inequalities hold for $0 < \delta < \rho = 1/40$, so the cohomological constant $c_R = 1$ is justified directly. The verification reconstructs the convergent matrix of the continued fraction and checks these metadata, rather than assuming that an arbitrary numerical frequency is Diophantine.

Global bounds and theorem constants. Write $h = h_2 + ag(d^\top X) + p_4$, with quartic coefficient norm $C_4 = \sum_\alpha |(p_4)_\alpha|$. The exact exported coefficients satisfy $|a| \leq 2$, $C_4 < 1/100$, $\|d\|_1 < 11/20$, and $\max \nu_j < 7$. The full cosine and its derivatives then give, on $\mathbb{D}^4_{3/10}$,

$$\begin{aligned} c_{X_h,0} &= 3, \quad c_{X_h,1} = 8, \\ c_{X_h^\top,1} &= 32, \quad c_{X_h,2} = 1. \end{aligned} \tag{71}$$

The third quantity bounds the derivative of the *row-vector map* $X_h^\top$. It bounds the sum of the absolute Jacobian

entries and is not the matrix norm of $(DX_h)^\top$. For example, its linear part is $2(\nu_1+\nu_2)<28$; its remaining bound is $2\|d\|_1^2(\cosh(3\|d\|_1/10)-1)+12C_4(3/10)^2<1$. For the second derivative, the row-sum tensor estimate $2\|d\|_1^3\sinh(3\|d\|_1/10)+24C_4(3/10)<1$ suffices. All geometric tensors are constant canonical tensors with norm one and zero derivatives.

Let $J=\left(\begin{smallmatrix}0 & I\\ -I & 0\end{smallmatrix}\right)$, $L=DK$, $B=(L^\top L)^{-1}$, and $N=-JLB$. In the source convention the symplectic matrix is $\Omega=-J$. The torsion used in the theorem is therefore

$$T=-N^\top J\big(DX_h(K)N-D_\varpi N\big). \tag{72}$$

There are no additional first integrals ($n=d=2$, canonical Case III). Choose $\rho=1/40$, $\rho_\infty=1/80$, $a_1=a_2=2$, $a_3=12$, $\delta=\rho/12$, and the iteration parameter $\nu_{\mathrm{it}}=1$. The bounds used with strict margins are

$$\begin{gathered}\|DK\|_\rho<1<\sigma_K=2,\\ \|DK^\top\|_\rho<\tfrac{3}{2}<\sigma_{K^\top}=2,\\ \|B\|_\rho<3<\sigma_B=4,\end{gathered}$$

$$\|\langle T\rangle^{-1}\|<10^5<\sigma_T=2\times10^5,\qquad \|K\|_\rho<\tfrac{1}{5}.$$

The last inequality leaves a phase-space distance margin $1/10$. Substitution in Tables 1–3 gives exact rational constants, delivered with the certificate; their decimal displays are

$$\begin{aligned}C_1&\simeq 4.843521623\times10^{46},\\ C_2&\simeq 4.940319879\times10^{21},\\ \frac{\gamma^4\rho^{12}}{C_1}&>8.6086\times10^{-76}.\end{aligned} \tag{73}$$

The rational recurrence is also provided as an executable transcription of those tables; all decisions use rational or ball bounds, not rounded decimal displays. The source's C_{sym} is evaluated from its Eq. (4.39), giving $\sigma_B^2C_{\Omega_L}=192$.

Analytic residual and torsion checks. For each case the delivered K is an exact dyadic finite Fourier polynomial supported on $|k_j|\le63$. Conjugate symmetry is checked exactly. Its derivative and wide-strip norms are bounded by $\sum_k|K_k|e^{2\pi s|k|_1}$ and the corresponding differentiated sums. To bound B, compare K with $K_0=(\frac{1}{10}\cos2\pi\theta_1,\frac{1}{10}\cos2\pi\theta_2,-\frac{1}{10}\sin2\pi\theta_1,-\frac{1}{10}\sin2\pi\theta_2)$. Put $e_L=\|D(K-K_0)\|$ and $e_{L^\top}=\|D(K-K_0)^\top\|$. As $DK_0^\top DK_0=(2\pi/10)^2I$ exactly, the checked inequality

$$\begin{aligned}&\|DK_0^\top\|e_L+e_{L^\top}\|DK_0\|\\ &\quad+e_{L^\top}e_L<(2\pi/10)^2\end{aligned}$$

provides a Neumann-series inverse bound for the analytic Gram matrix.

The residual $E=X_h(K)-DK\varpi$ is evaluated with 512-bit Arb balls on a 256×256 grid, including ball sine evaluations and all quartic terms. Let $\mathcal{I}_mE$ be its trigonometric interpolant, $\widehat{\rho}=1/4$, and $M\ge\|E\|_{\widehat{\rho}}$, computed directly from the finite Fourier polynomial and the entire Hamiltonian. Fourier decay, the two-dimensional union bound for the omitted modes, and the alias sum give

$$\begin{aligned}\|E\|_\rho&\le\|\mathcal{I}_mE\|_\rho+E_{\mathrm{tail}},\\ E_{\mathrm{tail}}&=8M\frac{1+q}{(1-q)^2}e^{-\pi(\widehat{\rho}-\rho)m}.\end{aligned} \tag{74}$$

Here $q=e^{-2\pi(\widehat{\rho}-\rho)}$ and $m=256$. Both the omitted Fourier tail and the aliased coefficients are included in the factor 8. The larger strip is used only to estimate the composition residual; the entire full-cosine Hamiltonian is defined there even when $K(\mathbb{T}^2_{\widehat{\rho}})$ leaves the smaller phase-space domain used by the KAM iteration.

For the mean torsion, the same Gram estimate on the strip $7/100$ proves $\|N\|,\|N^\top\|<6$. Since $\|\varpi\|_1<2$, Cauchy's inequality on the strip $6/100$ gives $\|D_\varpi N\|<1200$, and hence $\|T\|<6(8\cdot6+1200)<10^4$. An Arb trapezoidal average on 128^2 nodes is corrected by

$$10^4\left[\left(\frac{1+z}{1-z}\right)^2-1\right],\qquad z=e^{-2\pi(6/100)128}.$$

The derivative of B in this evaluation is calculated by differentiating its inverse identity, so no differentiated interpolation of N is used. Inverting the resulting interval 2×2 matrix proves the stated bound on $\langle T\rangle^{-1}$.

The resulting bounds in Table 2 satisfy

$$\frac{C_1\|E\|_\rho}{\gamma^4\rho^{12}}<1. \tag{75}$$

The cited theorem supplies the invariant Lagrangian torus and $\|K_\infty-K\|_{\rho_\infty}\le C_2\|E\|_\rho/(\gamma^2\rho^6)<3\times10^{-41}$. For completeness, embeddedness can also be checked quantitatively: writing $X_j-iY_j=0.1e^{2\pi i\theta_j}+\xi_j$, the verified C^0 and C^1 differences from K_0 make the phase map a degree-one map with derivative less than $1/2$ from the identity. It is a diffeomorphism. The same inequality holds after adding the KAM correction and its Cauchy derivative bound on a smaller strip.

Physical displacement. The exact exported shape matrix maps X to the Hermite nodal displacements and slopes. On an element of length ℓ, the cubic Bernstein control values are w_0, $w_0+\ell\vartheta_0/3$, $w_1-\ell\vartheta_1/3$, and w_1. For a

control row b, its value on the invariant torus is bounded by $\sum_{j=1}^{2} |b_j|(\sum_k |(X_j)_k| + 3 \times 10^{-41})$. The convex-hull property therefore bounds every centerline point, every phase, and all time. A ball evaluation at phase $(0, 0)$ gives the separate positive lower witness in the table. These bounds use the same exported shape map as the learning and beam reconstruction.

The additional low-noise fit connects the two certificates on one actual learned Hamiltonian. Its nonzero derivative MSE is $3.3866649 \times 10^{-17}$. The outward Gram lower bound 6.0167×10^{-8}, together with the label and decoder error budgets, gives a twist-error upper bound 2.81119×10^{-4}, smaller than the target singular-value lower bound 3.03081×10^{-4}. Its saved coefficients are exactly those used by the fifth row of the table. Thus the nonzero-loss twist certificate and the finite-amplitude KAM certificate concern the same fitted function; the latter additionally uses the full analytic invariance residual, as required by the theorem.

The sixth row certifies the actual GC function obtained from four independent COMSOL position–velocity trajectories by integral matching. The fit uses state increments and feature integrals, without reconstructed acceleration labels. Its exported cosine multiplier is $a = 1.022324882191665$; every exported quartic term is included in the analytic verification. The coefficient file and the four source trajectory hashes are linked in the proof manifest. The frequency in (69) admits the same conservative $\gamma = 9/1750$, so the global bounds and theorem constants above remain unchanged. In this case the checked inverse averaged torsion is below 94762, within the required 10^5 margin.

This result certifies one specified nonresonant torus in each Hamiltonian at a useful physical amplitude. It does not attach a measured phase-space volume to these individual tori. Positive-measure families near the elliptic equilibrium follow from the separate normal-form argument above; the finite-amplitude theorem and the energy-based safety theorem have distinct hypotheses and conclusions.

5.4 Positive-measure families around the certified tori

The nondegeneracy retained by the a posteriori iteration gives a further conclusion at the same finite-amplitude motion.

Corollary 8. KAM stability of the certified finite-amplitude tori. *Each of the six tori in Theorem 7, and the additional integral-COMSOL torus in Section 5.5, is accumulated by positive-measure families of analytic Lagrangian invariant tori. In analytic symplectic tubular coordinates (θ, I) centered on that torus, their relative Lebesgue measure in $\mathbb{T}^2 \times \{|I|_\infty < r\}$ tends to one as $r \to 0$. This is an asymptotic statement about neighborhoods of the certified millimetre-amplitude torus; it does not specify a numerical tube thickness or a percentage in a preassigned experimental domain. In particular, for any prescribed fraction $p < 1$, including 0.95 or 0.965, a sufficiently thin tube has relative invariant-torus measure greater than p. The present statement is existential in the tube radius.*

Proof. The inequalities controlling the inverse averaged torsion in the Haro–Luque iteration are uniform at every step: see their Eqs. (5.65)–(5.67) and the summation in Section 5.3. The strict margin used in (73) therefore gives

$$\|\langle T_\infty \rangle^{-1}\| \le 2 \times 10^5.$$

This is nondegeneracy of the final invariant object, not only of its numerical approximation.

An analytic Lagrangian neighborhood chart Ψ can be chosen with $\Psi(\theta, 0) = K_\infty(\theta)$ and first derivative $D\Psi(\theta, 0) = [L_\infty, N_\infty]$. One construction starts with $K_\infty(\theta) + N_\infty(\theta)I$ and uses the relative analytic Moser correction. The forms agree on the zero section; the relative primitive and its correcting vector field are $O(|I|^2)$, so the correction preserves this first jet. In these coordinates invariance implies

$$\begin{aligned} h \circ \Psi = e + \varpi \cdot I + \tfrac{1}{2} I^\top A(\theta) I \\ + O(|I|^3). \end{aligned} \tag{76}$$

The automatic-reducibility identity of Haro–Luque Section 2.4 is

$$\begin{aligned} DX_h(K_\infty)P - D_\varpi P \\ = P \begin{pmatrix} 0 & T_\infty \\ 0 & 0 \end{pmatrix}, \end{aligned}$$

where $P = [L_\infty, N_\infty]$. Comparing this with the linearized vector field of (76) gives $A = T_\infty$. More generally, changing the symplectic normal frame to $N_\infty + L_\infty S(\theta)$, with S symmetric, changes this block to $T_\infty - D_\varpi S$, whose average is the same. Hence $\overline{A} = \langle A \rangle$ is nonsingular independently of this choice of normal frame.

The quadratic normal form is justified without a formal-series convergence assumption. Solve the matrix homological equation $D_\varpi S = A - \overline{A}$ with zero average by

$$S_k = \frac{A_k}{2\pi i k \cdot \varpi} \quad (k \neq 0), \qquad S_0 = 0.$$

Equation (70) and analyticity make this series convergent on every strictly smaller angle strip; the cohomological bound established above controls it there. The exact

Table 2. Finite-amplitude certificates for the complete target and actual trained Hamiltonians. Displayed bounds are rounded outward. The lower witness is tip displacement at one phase; the upper bound covers the entire reconstructed centerline at all phases.

Model	$\|E\|_\rho$ upper	KAM quotient upper	Tip lower (mm)	Centerline upper (mm)
Target	$2.7310\,10^{-77}$	0.031724	1.8977905	1.8977964
GC17	$2.7372\,10^{-77}$	0.031796	1.8927460	1.8927517
GC43	$2.7538\,10^{-77}$	0.031988	1.8837514	1.8837573
GC91	$2.7285\,10^{-77}$	0.031694	1.9077295	1.9077354
GC17 (10^{-8} noise)	$2.7311\,10^{-77}$	0.031724	1.8977399	1.8977457
GC (COMSOL states)	$2.7330\,10^{-77}$	0.031746	1.8977374	1.8977433




Figure 1. The certified target torus in the same SI beam coordinates. (a) Tip displacement and velocity along sampled sections with the second phase fixed; these curves are not time trajectories. (b) Sampled centerlines and a plotted phase envelope. The separate whole-element Bernstein/Fourier certificate bounds every centerline point on the corrected invariant torus by 1.897797 mm. Sampling illustrates the geometry; the analytic certificate supplies the all-phase bound.

time-one Hamiltonian flow of $\chi_2(\theta, I) = \frac{1}{2} I^\top S(\theta) I$ exists on a sufficiently thin tube and fixes $I = 0$. With the pullback convention $L_\chi F = \{F, \chi\}$, it changes the quadratic coefficient to $\overline{A}$ and leaves an analytic $O(|I|^3)$ remainder. The resulting normal form satisfies the hypotheses of Bounemoura (2016, Theorem 6, analytic case): the frequency is nonresonant, the averaged quadratic form is nonsingular, and the full remainder is analytic. That theorem gives the claimed density-one families. Symplectic coordinate changes preserve volume, and the constant factor relating the dimensionless chart to SI canonical coordinates cancels in relative measure.

For the integral-COMSOL fit, Section 5.7 supplements this corollary with an explicit chart radius, complete analytic remainder and all constants of a quantitative measure theorem. That calculation produces a fixed, extremely thin tube around the certified finite-amplitude torus. Its thickness and relative measure are stated together, separately from the wider numerical sampling domain.

5.5 A validated COMSOL state-to-KAM learning certificate

We add a controlled identification experiment for the same complete two-mode magnetic Hamiltonian. COMSOL independently integrates its four state equations for 64 initial conditions, with 17 state observations on each dimensionless interval $[0, T]$, $T \simeq 0.04$. This experiment is explicitly a two-mode modal ODE experiment; the earlier 64-DOF finite-element trajectories remain a separate validation. Only positions and velocities enter the new training labels. Neither acceleration reconstruction nor a solver tolerance is used as an error certificate.

For each observed orbit, fit a degree-eight polynomial curve $c_\ell : [0, T] \to \mathbb{R}^4$ to the observed states. Its coefficients are frozen as exact dyadic rationals, with its constant and linear coefficients corrected exactly so that both endpoints equal the exported observations z_ℓ^-, z_ℓ^+. This construction uses no evaluation of the physical acceleration. Let $Lz = X_{h_2}(z)$ and let $V(z) = [J\nabla F_0(z), \ldots, J\nabla F_{34}(z)]$ be the

nonlinear feature field of the same learned family. Define

$$D_\ell = \frac{1}{T}\int_0^T V(c_\ell(\tau))\,d\tau,$$
$$y_\ell = \frac{z_\ell^+ - z_\ell^-}{T} - \frac{1}{T}\int_0^T Lc_\ell(\tau)\,d\tau. \tag{77}$$

The integral design and labels are therefore functions of the observed state curves, not instantaneous force-balance labels.

Proposition 9. Integral loss, dynamic defect and coefficient error. *Let $\eta_\star = (s_4, 0, \dots, 0)$ represent the declared full-cosine target, and let m be the number of observed curves. Put*

$$e_\ell = \frac{1}{T}\int_0^T \big(\dot c_\ell - X_{h_\star}(c_\ell)\big)\,d\tau,$$
$$G_I = \frac{1}{4m}\sum_{\ell=1}^m D_\ell^\top D_\ell, \tag{78}$$
$$r_I^2 = \frac{1}{4m}\sum_{\ell=1}^m \|D_\ell\widehat\eta - y_\ell\|_2^2.$$

If $\lambda_{\min}(G_I) \ge \underline\lambda > 0$ and $(4m)^{-1}\sum_\ell \|e_\ell\|_2^2 \le \epsilon_I^2$, then

$$\|\widehat\eta - \eta_\star\|_2 \le b_I := \frac{r_I + \epsilon_I}{\sqrt{\underline\lambda}}. \tag{79}$$

The curves need not be exact solutions of the physical differential equation. Their explicitly verified dynamic defect supplies the required error budget.

Proof. Exact endpoint matching and the fundamental theorem of calculus give $y_\ell - D_\ell\eta_\star = e_\ell$. The triangle inequality in the stacked, $1/(4m)$-normalized Euclidean norm gives $\|D(\widehat\eta - \eta_\star)\|_2/\sqrt{4m} \le r_I + \epsilon_I$. The Gram lower bound proves (79).

The defect is independently evaluated against the explicitly declared physical target. Thus the proposition does not infer arbitrary unknown model error from a small training loss. It certifies consistency with this target using additional, verified physical information.

Validated integrals and numerical error. All polynomial feature integrals are evaluated by exact polynomial integration with Arb ball coefficients. For $\vartheta = d^\top(c_\ell)_X$, the magnetic feature uses the odd Taylor terms of $\sin\vartheta - \vartheta$ through degree 19, together with

$$S_{19}(\vartheta) = \sum_{\substack{3\le j\le 19\\ j\ \text{odd}}} \frac{(-1)^{(j-1)/2}\vartheta^j}{j!},$$
$$|\sin\vartheta - \vartheta - S_{19}(\vartheta)| \le \frac{R^{21}\cosh R}{21!}, \quad |\vartheta| \le R. \tag{80}$$

Table 3. Outward bounds for the independent COMSOL integral-learning experiment. The MSE has a strictly positive certified lower bound.

Quantity	Certified bound
Training MSE	$[3.6030, 3.6031]\,10^{-23}$
r_I	$\le 6.0026\,10^{-12}$
ϵ_I	$\le 6.8835\,10^{-12}$
$\lambda_{\min}(G_I)$	$\ge 2.9302\,10^{-7}$
$\|\widehat\eta - \eta_\star\|_2$	$\le 2.3805\,10^{-8}$
Twist error	$\le 1.0377\,10^{-7}$
$\sigma_{\min}(A_\star)$	$\ge 4.9032\,10^{-4}$
$\|h_{\widehat\eta} - h_\star\|_{0.3}$	$\le 1.3310\,10^{-9}$

The computed maximum remainder is below 4.8752×10^{-43}. The remainder is included in every affected feature integral and dynamic defect; the certified function remains the complete cosine model. The exact identity $y - D\eta_\star = e$ is also checked componentwise by independent ball evaluations.

The interval Gram inverse is computed at 256-bit precision. Since the exact Gram matrix is real symmetric and positive semidefinite, a validated inverse makes it positive definite and gives $\underline\lambda = 1/\|G_I^{-1}\|_\infty$. Decoder rounding is retained when the real readout coefficients are exported as a cosine multiplier and a quartic polynomial. With $B = [q_\star/s_4\ U]$, this gives

$$\|A_{\widehat\eta} - A_\star\|_2 \le \sqrt{19}\big(\|B\|_2 b_I + \delta_{\mathrm{dec}}\big),$$
$$\|h_{\widehat\eta} - h_\star\|_r \le b_I B_F(r) + \delta_{h,\mathrm{dec}}(r). \tag{81}$$

Here $\|B\|_2 \le \|B^\top B\|_\infty^{1/2}$ is verified from the exported feature matrix; exact numerical orthogonality is unnecessary. The analytic bound controls every derivative on a smaller polydisc by Cauchy's estimate:

$$\|\partial^\alpha(h_{\widehat\eta} - h_\star)\|_{r'} \le \alpha!(r - r')^{-|\alpha|}\|h_{\widehat\eta} - h_\star\|_r.$$

The target is unchanged. The singular-value lower bound in Table 3 is a sharper bound for the same two-by-two symmetric matrix: $\sigma_{\min}(A_\star) \ge |\det A_\star|/\|A_\star\|_\infty$. The previously reported, smaller lower bound remains valid. The strict twist margin, fixed quadratic part and complete analytic tail therefore give local positive-measure KAM families for this actual fitted Hamiltonian by the normal-form argument above.

An independent bound on trajectory error. The observation curves deviate from every exported sample by at most 5.2538×10^{-14} and satisfy

$$\sup_\tau \|\dot c_\ell - X_{h_\star}(c_\ell)\|_2 \le 1.0973 \times 10^{-8}.$$

The linear modal field L is skew symmetric in these balanced coordinates. On the real box $|z|_\infty < 0.3$, the nonlinear part has Euclidean Lipschitz constant

$$\|d\|_2^2 \frac{(0.3\|d\|_1)^2}{2} < 0.002084 < 0.01.$$

For the exact physical solution z_ℓ with $z_\ell(0) = c_\ell(0)$, variation of constants and Gronwall's inequality therefore give

$$\begin{aligned} &\sup_{0\le\tau\le T} \|z_\ell(\tau) - c_\ell(\tau)\|_2 \\ &\quad \le T e^{0.01T} \|\dot{c}_\ell - X_{h_\star}(c_\ell)\|_{\infty,2} \\ &\quad < 4.3907 \times 10^{-10}. \end{aligned}$$

The verified curve bound $|c_\ell|_\infty < 0.2000$ closes the bootstrap inside the radius-0.3 box. This is an a posteriori bound on the independently observed trajectories, not an interpretation of COMSOL's requested time-stepping tolerances.

The same fitted function at millimetre amplitude. The frozen network has cosine multiplier $a = 0.9999996888354415$. Its complete exported coefficients are also used in a separate, 512-bit a posteriori torus verification with the frequency in Eqs. (67)–(68) and the theorem constants of Theorem 7. The verified analytic invariance residual is at most 2.7310×10^{-77}, the KAM smallness quotient is at most 0.031724, and the inverse averaged torsion is below 80526. The invariant torus lies within 2.0894×10^{-41} of its exact Fourier candidate. The tip-displacement witness is at least 1.8977904 mm, and the whole reconstructed centerline is bounded by 1.8977962 mm for every phase and all time. Thus the nonzero integral-loss certificate and the finite-amplitude KAM certificate concern exactly the same independently trained function. The first proves coefficient, analytic and twist control; the second checks the additional invariance-residual condition needed at the stated finite amplitude.

For comparison, the earlier full-FE trajectory fit retains its independent a posteriori torus certificate, but its stored integral observation matrix yields a coefficient bound above 0.025 even before adding unverified continuous quadrature and model-error budgets. That particular worst-case loss bound does not pass. The new experiment supplies a verified nonempty instance of the complete integral-learning theorem, without relabeling the old full-FE data or treating omitted modes as zero.

5.6 A fixed-domain measure of KAM persistence

A torus-retention percentage requires a specified volume measure and a fixed initial-state domain. Following the measure formulation of Biasco and Chierchia (2018); Chierchia and Koudjinan (2021), let $U \subset \mathbb{R}^4$ be a bounded domain for the frozen two-degree-of-freedom Hamiltonian h, and let $\mathcal{K}_h$ denote the union of its analytic Lagrangian invariant tori carrying Diophantine quasiperiodic motion. Define

$$f_{\mathrm{KAM}}(U) = \frac{\mu_L(U \cap \mathcal{K}_h)}{\mu_L(U)}, \qquad \mu_L = \mathrm{d}X_1\,\mathrm{d}X_2\,\mathrm{d}Y_1\,\mathrm{d}Y_2. \tag{82}$$

An explicitly certified subfamily provides a lower bound for this fraction. The complement of that subfamily can contain other regular motion; it is not thereby a chaotic set. The sampling confidence in a learning bound such as that of Chen et al. (2022) is a probability over training data, whereas (82) measures initial states of one frozen fitted Hamiltonian.

For a symplectic chart Ξ and an action box D, set $U = \Xi(\mathbb{T}^2_{2\pi} \times D)$, where $\mathbb{T}^2_{2\pi} = (\mathbb{R}/2\pi\mathbb{Z})^2$. Then $\mu_L(U) = (2\pi)^2\,\mathrm{area}(D)$. The period-one angles used by the earlier torus certificate are changed to radians together with the inverse action rescaling, preserving the symplectic form. The constant volume factor in the SI canonical chart also cancels from the relative fraction. The radius and location of D must accompany every reported percentage.

Where the assumptions of Theorem 11 hold, the invariant-family lift to the 64-mode closed loop carries this low-dimensional parameter measure forward. It does not turn it into a positive fraction of the full 128-dimensional Lebesgue volume. Accordingly, both the theorem below and the numerical sampling experiment refer to the conservative low-mode Hamiltonian realized by the magnetic feedback, with their respective domains specified separately.

5.7 An explicit measure certificate around the millimetre torus

The existence of a density-one family can be supplemented by a fixed radius using the explicit constants of Chierchia and Koudjinan (2021). We construct a symplectic chart from the certified torus itself and bound the complete transformed Hamiltonian. Thus the calculation uses the same saved integral-COMSOL fit as the nonzero-loss and magnetic-control certificates. It does not replace the full-domain perturbation by the single-torus invariance residual.

Table 4. Outward bounds for the explicit finite-amplitude tube. The smallness quotient is the tested perturbation divided by the sufficient threshold; failure of that test does not imply chaos.

Quantity	Bound or value
Initial chart action radius	10^{-3}
Quadratic-normalization radius	10^{-17}
Certified tube half-width w	10^{-220}
$\|\overline{A}\|_\infty$, $\|\overline{A}^{-1}\|_\infty$	$3, 5100$
Smallness quotient at $w = 10^{-220}$	< 0.407586
Same quotient at $w = 10^{-219}$	> 4.0758
Certified fraction in U_w	$> 96.6938\%$

Theorem 10. Explicit finite-amplitude tubular measure. *Let h be the seventh fitted Hamiltonian certified in Section 5.5, and let K_∞ be its exact invariant torus. There is an explicitly constructed analytic symplectic chart $\Xi = \Psi \circ \Phi_\chi$, specified in Appendix D, that fixes this torus at zero action. For the fixed domain*

$$U_w = \Xi\big(\mathbb{T}^2_{2\pi} \times (-w, w)^2\big), \qquad w = 10^{-220}, \tag{83}$$

the KAM fraction satisfies

$$f_{\mathrm{KAM}}(U_w) \geq 0.9669383 > 0.965. \tag{84}$$

The centre torus is the previously certified motion with the 1.8977904 *mm tip witness and the* 1.8977962 *mm all-phase centreline bound. The width w is a dimensionless action half-width, not a displacement amplitude.*

Proof. The explicit chart and a convergent quadratic normalization give

$$h \circ \Xi = e + \omega \cdot I + \tfrac{1}{2} I^\top \overline{A} I + R_3, \qquad \omega = 2\pi\varpi.$$

The outward bounds are $\|\overline{A}\|_\infty \leq 3$, $\|\overline{A}^{-1}\|_\infty \leq 5100$ and $\|R_3\|_{2w,1/128} \leq 4 \times 10^{51} w^3$. Use the global KAM theorem with real action radius w, complex radius $2w$, final angle strip $1/256$, frequency exponent $\tau = 2$, boundary allowance $\rho = w/500$ and $\alpha = w/(1000 \times 5100)$. The dimensionless smallness quantity is at most 3.1212×10^{-155}, below the theorem threshold 7.6577×10^{-155}. The geometric estimate in Appendix D gives

$$\begin{aligned} 1 - f_{\mathrm{KAM}}(U_w) &\leq \frac{25}{16}\left(\frac{4\rho}{w} + \frac{8\alpha L \zeta(2)}{w}\right) \\ &= \frac{25}{16}\left(0.008 + 0.008\zeta(2)\right) < 0.0330617, \end{aligned} \tag{85}$$

where $L = 5100$. The two terms account for the boundary layer and all integer resonance strips, respectively. Symplecticity transfers this relative measure to U_w without a density correction.

The width in Table 4 quantifies the conservatism of this general theorem. The domain is centred on the exact millimetre-amplitude torus, but its thickness is far below any operational resolution. In particular, the delivered Fourier candidate has a certified canonical-embedding error upper bound below 2.1×10^{-41}. This available guarantee cannot resolve membership in a tube whose transverse distance is bounded by $41w = 4.1 \times 10^{-219}$; it is not an estimate of the actual embedding error. The domain is mathematically specified through K_∞; this certificate does not permit an experimental initial state to be assigned to that tube from the saved finite-precision candidate. It supplies a concrete fixed-domain measure result while leaving the much wider operating-domain question to a separate calculation. Section 6.6 reports that wider-domain numerical diagnostic, with its own error checks and interpretation.

6 Reproducible learning and independent COMSOL validation

All experiments in this section use the clamped-free beam, static-field eigenvectors, complete magnetic cosine, and SI parameters defined above. The two-mode learning problem and its higher-order validation models therefore share the same mechanics. The reference energy is

$$\begin{aligned} h_\star(X, Y) &= \frac{1}{2}\sum_{j=1}^{2} \nu_j (X_j^2 + Y_j^2) + g(d^T X), \\ g(s) &= 1 - \cos s - \frac{1}{2} s^2. \end{aligned} \tag{86}$$

Here $\nu = (1, 6.152117504)$ and $d = (0.225670773, 0.321798806)^T$; one dimensionless energy unit is 6.0×10^{-7} J and $\tau = 11.417287283t$. The tip displacement in metres is $0.013506054X_1 + 0.005470926X_2$. These mappings are used for every reported displacement, slope, and energy error, including the independent COMSOL comparison.

6.1 Finite-feature identification and matched controls

The CHNN uses $z_j = (X_j + \mathrm{i}Y_j)/\sqrt{2}$, conjugate polynomial features, and a complex exponential feature for the full cosine. Its real energy readout is

$$h_\vartheta = h_2 + a\, g(d^T X) + m_4(X, Y)^T U c, \tag{87}$$

where m_4 lists the 35 degree-four real monomials in (X_1, X_2, Y_1, Y_2). If v_4 is the coefficient vector of $-(d^T X)^4/24$, the 34 columns of U span its orthogonal

complement. The feature $g/\|v_4\|_2$ and these complementary quartics give 35 fitted real parameters, avoid duplicating the leading cosine term, and retain the complete analytic cosine tail. The target corresponds to $a = 1, c = 0$ and is therefore in the feature class. The stored matrix U, rather than idealized exact orthogonality, is used in the certificate computations.

We compare real (R) and complex (C) implementations, each with either the fixed mechanical quadratic part (G) or a fitted general quadratic part (B). Thus GR and GC have 35 fitted real parameters, whereas BR and BC have 45. The two representations span the same real energy class, receive identical data, and use the same regularizer expressed in common real feature coordinates. They are a controlled representation comparison: complex arithmetic is actually evaluated, but an intrinsic complex-valued accuracy advantage is not expected from an invertible change of features.

For each seed in $\{17, 43, 91\}$, we generate 12 conservative trajectories of 4 s, sampled at 129 times. Initial modal radii are drawn uniformly from $[0.03, 0.20]$ and $[0.03, 0.16]$, with independent uniform phases. The largest training tip slope is 0.0891 rad. Each component of the dimensionless vector-field label receives independent uniform noise in $[-10^{-6}, 10^{-6}]$; states are noiseless. Linear readout fitting minimizes derivative mean-square error with a 10^{-14} quadratic regularizer. Eight independent trajectories, generated with a separate seed and integrated for 16 s at 1601 output times, are held out in full. The reference solver is DOP853 with relative and absolute tolerances 2×10^{-10} and 2×10^{-12}. Tightening both tolerances by a factor of 100 changes the tip of the first held-out trajectory by at most 1.92×10^{-8} mm.

Table 5 and Fig. 2 show the benefit of fixing the known quadratic mechanics in this experiment, while matched real and complex fits agree to numerical precision. GC identifies $a = 1.00326 \pm 0.00154$ with nonzero training residuals. The energy error evaluates the true energy along the predicted and reference states; it is not an energy-conservation surrogate for trajectory accuracy. The small fitting errors reflect exact representation, accurate synthetic derivatives, and deliberately controlled label noise. They do not establish corresponding physical measurement accuracy.

We also continue one independent initial condition for 200 s, or 363 first-mode linear periods, using the three primary GC fits. The seed-level tip RMSE ranges from 1.38×10^{-4} to 4.03×10^{-4} mm; the largest modal phase error is 4.19×10^{-4} rad. The relative drift of each learned model's own energy remains below 5.11×10^{-9} with conservative integration at relative and absolute tolerances 2×10^{-11} and 2×10^{-13}. Figure 3 shows its Poincaré section, phase error, and numerical energy drift. These finite-time diagnostics assess the fitted dynamics; they do not estimate the measure of KAM tori or replace the analytic certificate.

6.2 A nonzero-loss certificate for the fitted magnetic energy

The feature derivatives make the empirical Gram matrix and the complete quartic Taylor map computable. We repeat the same three fits at noise amplitudes 10^{-8} and 10^{-9}, preserving the original 10^{-6} experiments. Outward-rounded interval calculations enclose the derivatives of the analytic sine feature at the stored states, the Gram inverse residual, the observed loss, clean-label rounding, and the conversion from readout weights to the exported energy coefficients. The degree-17 sine series is enclosed with its degree-19 remainder.

For the target magnetic quartic, $A_{jj} = -d_j^4/8$ and $A_{12} = -d_1^2 d_2^2/4$. This twist is indefinite and nonsingular. Exact rational arithmetic on the stored dyadic d gives the conservative lower bound $\sigma_{\min}(A_\star) > 3.03081 \times 10^{-4}$. If G is the derivative Gram matrix, B the quartic coefficient map, ℓ the noisy derivative MSE, and η_{eff} the enclosed noise and arithmetic budget, the verified sufficient inequality is

$$\sqrt{19}\left(\|B\|_2 \frac{\sqrt{\ell} + \eta_{\text{eff}}}{\sqrt{\lambda_{\min}(G)}} + \delta_{\text{dec}}\right) < \sigma_{\min}(A_\star), \qquad (88)$$

where δ_{dec} encloses readout decoding roundoff. At $\eta = 10^{-8}$, Table 6 verifies this inequality with strictly positive losses for all seeds. Thus the data-dependent error bound itself transfers nondegeneracy to the actual learned Hamiltonians. The local KAM conclusions additionally use the nonresonance and analytic normal-form hypotheses proved for this same model. This table alone does not certify a finite experimental oscillation radius. For the primary 10^{-6} fits, this sufficient error bound is too loose; their directly computed twist singular values are nevertheless between 5.78×10^{-4} and 5.93×10^{-4}.

6.3 Learning dissipation and opening the magnetic input port

The imaginary readout is the nonnegative Rayleigh potential $\mathcal{D}_\gamma(v) = \gamma \sum_j v_j^2/(2\nu_j)$, with $v = h_{\vartheta,Y}$. For each seed, eight additional damped, unforced 5 s trajectories provide noisy derivative labels. Nonnegative least squares fits the single γ using the already fitted conservative gradient.

Table 5. Conservative held-out errors, mean ± sample standard deviation over three training seeds. Each seed is evaluated on all eight independent 16 s trajectories. These are errors within the declared simulated model.

Model	Tip RMSE (mm)	Slope RMSE (mrad)	Energy RMSE (nJ)
BR	$(2.28\pm0.75)10^{-5}$	$(5.80\pm1.20)10^{-4}$	$(3.21\pm0.51)10^{-6}$
BC	$(2.28\pm0.75)10^{-5}$	$(5.80\pm1.20)10^{-4}$	$(3.21\pm0.51)10^{-6}$
GR	$(1.20\pm0.71)10^{-5}$	$(3.90\pm1.63)10^{-4}$	$(3.14\pm0.71)10^{-6}$
GC	$(1.20\pm0.71)10^{-5}$	$(3.90\pm1.63)10^{-4}$	$(3.14\pm0.71)10^{-6}$




Figure 2. Identical full-cosine beam data and real parameter budgets for the four learning controls. Points are individual seeds and horizontal marks are means. The quadratic mechanics prior changes the result; the matched real/complex representation changes it only at numerical precision.

In particular, the decoder retains the learned momentum-dependent quartics:

$$\begin{aligned} X' &= h_{\vartheta,Y}, \\ Y' &= -h_{\vartheta,X} - \gamma\,\mathrm{diag}(\nu^{-1})h_{\vartheta,Y} \\ &\quad + u\,d\cos(d^T X). \end{aligned} \tag{89}$$

The fitted dimensional mass-drag coefficients are 0.555585710, 0.555587102, and 0.555584024 s^{-1}, compared with 0.555585237 s^{-1} for the generator. On six independent driven trajectories with amplitudes 4–8 mT and frequency ratios 0.65–1.20 relative to the biased first frequency, the three seed-level tip RMSEs are 8.83×10^{-5}, 1.37×10^{-4}, and 6.40×10^{-5} mm. Closing the learned drag port increases the tip RMSE to approximately 3.01 mm. The integrated work balance is

$$\begin{aligned} h_\vartheta(\tau) - h_\vartheta(0) = &\int_0^\tau u\cos(d^T X)d^T h_{\vartheta,Y}\,ds \\ &- \int_0^\tau \gamma\sum_j h_{\vartheta,Y_j}^2/\nu_j\,ds. \end{aligned} \tag{90}$$

Its largest numerical residual across these cases is 4.41×10^{-17} J. These driven tests assess the port model, rather than autonomous KAM persistence. Some stress cases exceed the channel clearance and are free-motion continuations; safe operating trajectories are evaluated separately with the physical energy bound and input governor.

6.4 Independent COMSOL assembly and nonlinear time integration

COMSOL Multiphysics 6.3 independently assembles the same 32-element clamped-free beam and solves its nonlinear magnetic-tip response. The relative Frobenius differences between the exported and Python consistent-mass matrices are 7.75×10^{-15} for mass and 3.05×10^{-14} for bending stiffness. The nonlinear held-out COMSOL trajectory starts from rest, uses the same mass drag, and applies

$$B_y(t) = 0.006\,[1-\exp(-(t/0.25)^2)]\sin(\Omega t)\quad \mathrm{T} \tag{91}$$

with $\Omega = 9.4449490256$ rad/s for 8 s, relative tolerance 10^{-7}, and 2001 output samples. The exported nodal displacement, rotation, velocity, and angular velocity are evaluated directly, with no fitting to this driven trajectory. Its peak tip displacement is 3.09032 mm. A separate COMSOL solve with relative tolerance 10^{-8} changes the tip by 4.59×10^{-5} mm RMSE and reduces its discrepancy against the full Python FE solution to 1.03×10^{-5} mm RMSE. The original held-out dataset is preserved for the primary comparison below.

The nested modal comparison in Table 7 separates reduction error from learning error. Against the exact two-mode response, GC contributes only 1.81×10^{-6}–3.48×10^{-6} mm tip RMSE for this input. Against COMSOL, both have approximately 0.0156 mm RMSE. The two-mode




Figure 3. Conservative 200 s continuation of an independent initial state. Left: 364 upward crossings of $X_1 = 0$ for the reference and GC17. Middle: unwrapped first-mode phase errors of the three learned energies. Right: each learned energy's relative integration drift. All ports are closed for these conservative diagnostics.

Table 6. Enclosed loss-to-twist checks at noise amplitude 10^{-8}. All twist-error upper bounds are below 3.03081×10^{-4}.

Seed	Noisy MSE	Gram eigenvalue lower bound	Twist-error upper bound
17	3.387×10^{-17}	6.0167×10^{-8}	2.8112×10^{-4}
43	3.275×10^{-17}	2.2734×10^{-7}	1.4374×10^{-4}
91	3.283×10^{-17}	2.0968×10^{-7}	1.4973×10^{-4}

maximum slope discrepancy is 3.69 mrad; its true stored-energy RMSE is 0.132 nJ. These discrepancies decrease with modal enrichment. Figure 5 shows the response and both error scales. The primary training data were generated by the declared Python Galerkin model; the COMSOL time history is an independent held-out validation dataset. Neither dataset is a physical hardware measurement.

6.5 COMSOL-derived training data and an independent integral check

We generate a separate conservative COMSOL dataset comprising four 4 s training trajectories and two independent 8 s test trajectories, sampled every 0.004 s. Initial displacements and velocities excite both retained modes. The remaining 62 modes receive the static response to the nonlinear magnetic residual and its compatible first time derivative; all 64 modes remain active during integration. This initial tail condensation is not assumed to be an exact nonlinear invariant manifold. Native solver-vector checks confirm that the exported initial displacement and velocity are correct; small changes introduced by consistent initialization are handled by starting each predictor from the actual exported state.

The derivative-label construction requires care. At the stored output times, the exported second time derivatives differentiate a time interpolant and show a substantial lag relative to the velocity evolution. For example, the first trajectory has a dimensionless modal equation-residual RMS of 4.58×10^{-2} when those derivatives are used directly. We retain and audit these exports, and instead reconstruct instantaneous acceleration from the exported COMSOL mass and stiffness matrices:

$$\ddot{q} = M_{\mathrm{C}}^{-1} \left[-K_{\mathrm{C}} q - \mu B_0 \sin(\theta_{\mathrm{tip}}) e_\theta \right]. \tag{92}$$

The training states and velocities therefore come from the actual COMSOL time solver, while the acceleration labels use known physical force balance. This is surrogate identification for the declared mechanical model, rather than discovery of an unknown force law or a direct measurement of acceleration. The unresolved-mode force is retained in the audit: its largest component is 3.36×10^{-9} in dimensionless units for the checked training trajectory, and the remaining reconstructed equation-residual RMS is 1.81×10^{-10}.

The additional models are fitted separately and never replace the primary GC coefficients or their certificates. Three seeds vary the additional componentwise label noise, bounded by 10^{-6}, while using the same four COMSOL trajectories. The real/complex and prior/no-prior controls use the same parameter budgets as before.

An independent check uses only the COMSOL displacement and velocity samples. A nine-point closed Newton–Cotes rule integrates the vector-field features on nonoverlapping 0.032 s windows, and the observed state increments provide the regression targets. No acceleration or force-balance label enters this integral fit. With the initial solver




Figure 4. The same learned conservative energy with an identified nonnegative drag readout and magnetic input port. Left: an independent driven trajectory and the drag ablation. Middle: signed relative errors in the drag coefficient. Right: supplied work, dissipated energy, and stored-energy change for that trajectory.

Table 7. Independent nonlinear COMSOL trajectory comparison. Modal models use the common static-field chart. GC includes learned drag; its range covers the three primary training seeds.

Predictor	Tip RMSE (mm)	Maximum tip error (mm)
2-mode exact cosine	0.0156168	0.0226548
4-mode exact cosine	0.00407422	0.00592596
8-mode exact cosine	0.00102484	0.00152782
64-mode Python FE	0.00005614	0.00011835
2-mode learned GC	0.0156171–0.0156177	0.0226545–0.0226549

settings (relative tolerance 10^{-6} and scaled absolute tolerance 10^{-5}), the integral residual is too large to resolve the weak magnetic correction reliably: on the first trajectory, its RMS is 2.16 times the nonlinear magnetic signal. An unconstrained 35-feature integral fit then yields $a = 1.437$, illustrating that a good fit to a numerically dispersed trajectory need not recover the physical magnetic coefficient. A stricter COMSOL solve, with relative tolerance 10^{-8} and scaled absolute tolerance 10^{-7}, reduces that ratio to 0.112 on the same trajectory. This independent data-quality check prevents small force-balance training losses from concealing inadequate time-integration accuracy.

All six trajectories were subsequently regenerated with these stricter tolerances, while retaining the initial dataset. The successful runs use generalized-alpha integration with high-frequency spectral radius zero and backward-Euler consistent initialization. The four refined training trajectories provide 500 integral windows, or 2000 scalar equations, for the 35 real readout parameters. The resulting GC model has $a = 1.0223248822$ and a nonzero averaged-derivative integral RMS residual of 4.0524×10^{-7}. The corresponding residuals of the quadratic prior alone and the physical full-cosine target are 3.9099×10^{-6} and 6.6454×10^{-7}; the nonlinear magnetic signal RMS is 3.6601×10^{-6}. The actual fitted quartic twist has minimum singular value 5.1166×10^{-4}. The conservative weights were frozen before evaluating the two independent refined test trajectories.

Table 8 and Figure 6 report the held-out errors. The integral fit partly absorbs the remaining time-solver dispersion: its agreement with COMSOL is better than that of the exact closed two-mode target, despite a 2.23% error in the cosine multiplier. These are simulation-identification results and do not imply physical sensor accuracy. We do not infer a rigorous solver-error budget from the requested tolerances or apply the loss-based certificate to these integral residuals. The separately designed short-trajectory experiment in Section 5.5 supplies a verified integral defect budget and the corresponding loss-based certificate for its own frozen fitted function.

For comparison, the separately fitted models using the known-force labels in (92) recover $a = 1.0000690$ without added label noise. With the three added-noise seeds, the prior-informed GC models give 0.25347–0.25940 μm pooled tip RMSE against the same refined COMSOL tests; their additional error relative to the closed two-mode trajectories is 0.00364–0.00771 μm. Matched real and complex features again give coincident results to numerical precision. All four model variants, raw derivative exports, reconstructed labels, noise draws, and both solver-precision datasets are retained in the reproducibility package.




Figure 5. Independent nonlinear COMSOL time integration. Left: COMSOL and the learned two-mode GC response with learned drag. Middle: errors of the nested exact-cosine modal models against COMSOL. Right: the additional GC identification error within the two-mode model. Reduction error is the larger contribution in this validation.

Table 8. Independent refined COMSOL tests of the GC model identified only from displacement and velocity increments. Predictions start from each actual exported initial state. Energy errors use the physical stored-energy function evaluated along the learned trajectory.

Test	Tip RMSE (μm)	Max. tip error (μm)	Slope RMSE (mrad)	Energy RMSE (nJ)	Exact 2-mode tip RMSE (μm)
1	0.14836	0.39240	0.008677	0.0002067	0.24172
2	0.05140	0.17435	0.002411	0.0002253	0.27459

Finally, the frozen position–velocity fit is used directly in the independent a posteriori proof of Section 5.3. Its complete cosine and all saved quartic coefficients yield an analytic residual below 2.7330×10^{-77} and a theorem smallness quantity below 0.031746. The resulting exact invariant torus has a tip-displacement witness above 1.8977374 mm and a whole-centreline upper bound below 1.8977433 mm. This certificate concerns the actual fitted Hamiltonian and does not require its coefficients to equal the physical target. The same frozen conservative readout is paired with a nonnegative drag coefficient refitted on the existing Python damped-beam trajectories, $\gamma = 0.0486617702$ for seed 17. Its independent driven COMSOL tip RMSE is 0.015622 mm. Section 8.4 then uses this same energy, full gradient and Hessian, and drag readout to generate the magnetic tracking input. Hashes link the COMSOL training files, frozen weights, KAM certificate, and operational validation.

6.6 Finite-time fraction in an operating action annulus

To complement the rigorous local measure statement, we independently sample a millimetre-scale operating domain for the same seventh, COMSOL-integral fitted Hamiltonian. In its canonical coordinates, set

$$\begin{aligned} I_j &= \tfrac{1}{2}(X_j^2 + Y_j^2), \quad j = 1, 2, \\ \phi_j &= \operatorname{atan2}(-Y_j, X_j). \end{aligned} \tag{93}$$

and prescribe, before classifying any orbit,

$$\mathcal{D}_{\mathrm{op}} = [0.0032, 0.0072]^2 \times \mathbb{T}^2_{2\pi}. \tag{94}$$

Both harmonic modal radii therefore lie in $[0.08, 0.12]$, surrounding the radius 0.1 of the previously certified $1.898\,\mathrm{mm}$ torus. The corresponding harmonic tip envelope $|\ell_1|\sqrt{2I_1} + |\ell_2|\sqrt{2I_2}$ ranges from 1.518 to $2.277\,\mathrm{mm}$. The canonical polar Jacobian has absolute determinant one, so independent uniform actions and phases sample normalized four-dimensional Liouville volume:

$$\mu_L(\mathcal{D}_{\mathrm{op}}) = (2\pi)^2(0.004)^2 = 6.3165468 \times 10^{-4}. \tag{95}$$

We draw $N = 1024$ independent points with PCG64 seed 20261002; the domain, initial points, observables, and decision thresholds are retained in a frozen protocol. These points are distinct from the training observations and the certified-torus phase grid.

Following weighted Birkhoff averaging (Das et al. 2017; Duignan and Meiss 2023), we compare consecutive windows using the smooth bump $b(s) = \exp[-1/(s(1-s))]$ for $0 < s < 1$, with $b = 0$ otherwise. The normalized weighted mean




Figure 6. Identification using actual COMSOL displacement and velocity outputs only. Left: independent test response. Middle: prediction errors for both held-out trajectories. Right: the fitted cosine multiplier under the two declared COMSOL tolerance settings; the physical value is one. The refined coefficients are frozen for all subsequent checks.

is

$$W_T(F;z)=\frac{\int_0^T b(t/T)F(\Phi_h^t z)\,dt}{T\int_0^1 b(s)\,ds}, \tag{96}$$

where Φ_h^t denotes the flow of the same frozen fitted Hamiltonian h. The computations use normalized sampled sums of this weight; integration and quadrature refinements are reported below. Eight observables are used: $X_j/0.1$, $Y_j/0.1$, $I_j/0.005$, $X_1X_2/0.01$, and $Y_1Y_2/0.01$. We also average the polar angular velocities

$$\dot\phi_j=\frac{X_j\partial_{X_j}h+Y_j\partial_{Y_j}h}{X_j^2+Y_j^2}. \tag{97}$$

For each $T\in\{512,1024,2048,4096\}$, let $e_F(T)$ be the largest absolute difference of the eight weighted means on $[0,T]$ and $[T,2T]$, and let $e_\omega(T)$ be the largest relative difference of the two weighted frequencies. A candidate passes the principal test when $e_F,e_\omega\le10^{-8}$ at both $T=2048$ and 4096. It must also keep both sampled actions above 3.2×10^{-4}, have sampled relative energy drift below 10^{-8}, and satisfy the finite-order screen

$$\min_{\substack{0<|k|_1\le64\\ k\in\mathbb{Z}^2\ \text{primitive}}}\frac{|k\cdot\overline{\omega}|}{|k|_1\|\overline{\omega}\|_\infty}>10^{-7}, \tag{98}$$

where $\overline{\omega}$ uses the two longest consecutive windows. The total simulated time is $8192/\omega_0=717.508\,\mathrm{s}$. Full cosine and momentum-dependent quartic terms are retained.

Integration accuracy is resolved explicitly. Fixed-step eighth-order DOP853 at $\Delta\tau=1/16$ produces relative energy drift up to 3.94×10^{-7} and fails the numerical validity test. At $\Delta\tau=1/32$, all points pass the principal eight-digit criterion, but integration drift prevents ten-digit agreement. We therefore document a precision amendment, keeping every initial point and threshold unchanged, and recompute all 1024 points at $\Delta\tau=1/64$. The largest relative energy drift then falls to 6.11×10^{-12}; $e_F(4096)\le4.49\times10^{-12}$ and $e_\omega(4096)\le3.63\times10^{-14}$. Halving the step again for the preselected first 64 points changes no six-, eight-, or ten-digit labels, with maximum relative frequency change 2.40×10^{-14}. Halving the averaging output interval on identical saved trajectories changes the weighted means by at most 3.82×10^{-14}. An independent adaptive solver, phase points from the certified torus's Fourier approximation, an exactly resonant oscillator, and regular/chaotic two-wave examples provide additional checks. In particular, the resonant oscillator passes the averaging test but is rejected by (98).

The refined ensemble gives $1024/1024$ candidates at each of the six-, eight-, and ten-digit thresholds. For the specified finite-time classifier C,

$$\widehat{p}_C=\frac{1}{1024}\sum_{i=1}^{1024}\mathbf{1}_C(z_i)=1,\qquad \mathrm{CI}_{95\%}(p_C)=[0.996404,1]. \tag{99}$$

using the two-sided exact Clopper–Pearson interval. The smallest normalized finite-order detuning is 2.113×10^{-4}; the largest sampled tip displacement is $2.269\,\mathrm{mm}$. Figure 7 shows the fixed-domain sample and the integration and threshold checks. This interval quantifies only random initial-condition sampling for C. It does not bound classification error, unresolved high-order resonance, sticky chaos, or physical model error. Thus (99) is an empirical finite-time candidate fraction in the operating domain, distinct from the rigorous KAM-volume bound in the much narrower analytic domain. No assertion that 99.6404% of

the operating domain is rigorously covered by invariant tori follows from this experiment.

6.7 State-only identification beyond the nominal hypothesis class

The nominal full-cosine experiment places its target inside the chosen feature class. We additionally test unknown material and magnetic parameters, state noise, and two omitted physical effects. All training observations in this experiment are generated by the full 32-element, 64-DOF Python FE plant; the predictors retain the same four nominal static-field modes. Let $e = E/E_{\mathrm{ref}}$ and $m = \mu/\mu_{\mathrm{ref}}$. The local applied field is

$$B_x = B_0 - G(x - L), \qquad B_y = B_y(t) + Gy. \tag{100}$$

The field is curl-free and divergence-free. Under the declared linear-beam kinematics, $x_{\mathrm{tip}} = L$, so its additional potential is $-\mu G w(L) \sin\vartheta$. It supplies both the transverse tip force $\mu G \sin\vartheta$ and the corresponding moment $\mu G w(L) \cos\vartheta$. The axial force $-\mu G \cos\vartheta$ is balanced by the axial constraint reaction and does no virtual work in this specialization. We also add the still-fluid Morison drag density $-c_2|w_t|w_t$, with dissipation potential $c_2 \int_0^L |w_t|^3 ds/3$.

In the fixed dimensionless chart, the conservative energy is

$$h = \tfrac{1}{2} Y^{\mathsf{T}} \operatorname{diag}(\nu) Y + \tfrac{e}{2} X^{\mathsf{T}} A_{\mathrm{el}} X + m(1 - \cos\vartheta) - g \frac{G_{\mathrm{ref}}}{B_0} (\ell^{\mathsf{T}} X) \sin\vartheta, \qquad \vartheta = d^{\mathsf{T}} X, \tag{101}$$

where $A_{\mathrm{el}} = \operatorname{diag}(\nu) - dd^{\mathsf{T}}$, $G_{\mathrm{ref}} = 0.5$ T/m, and $g = mG/G_{\mathrm{ref}}$. The five fitted readouts are $(e, m, g, \alpha/\alpha_{\mathrm{ref}}, c_2/c_{2,\mathrm{ref}})$, with $c_{2,\mathrm{ref}} = 0.02$ kg/m^2. The elastic and magnetic strengths and both dissipative coefficients are constrained to be nonnegative; the gradient may have either sign. The kinetic metric is known. Complex features evaluate the polynomial and exponential terms through $z = (X + iY)/\sqrt{2}$ and its conjugate.

Each of three parameter settings provides six independent 3 s training trajectories and three 4 s tests with different initial conditions and multisine inputs. The two changed settings use respectively $(e, m, \alpha/\alpha_{\mathrm{ref}}, G, c_2) = (0.85, 1.20, 1.40, 0.5, 0.02)$ and $(1.20, 0.85, 0.70, -0.4, 0.012)$ in SI units where dimensional. The first four modes are excited, and the remaining initial coordinates are statically condensed with zero initial velocity. This construction does not assume an invariant modal manifold. Samples are separated by 1 ms. On overlapping 32 ms windows, multiplication by $\psi = \sin^4(\pi s)$ and integration by parts gives

$$-\int \psi' Y \, d\tau = \int \psi F_\theta(X, Y, u) \, d\tau. \tag{102}$$

The endpoints of ψ vanish. Fitting therefore uses only positions, velocities and the applied field; neither accelerations nor reconstructed force-balance labels enter the regression.

We compare the expanded CHNN with a three-readout model that re-identifies elasticity, magnetic strength and linear drag but omits the gradient and quadratic drag. A further control freely learns the ten entries of the symmetric quadratic potential while retaining the analytic magnetic features and dissipative heads, giving fourteen readouts. Thus every comparison uses four modes. Matched real and complex realizations agree in effective coefficients to 1.31×10^{-11} or better. The experiment does not attribute an accuracy advantage to complex arithmetic.

Independent Gaussian noise is added to the observed modal positions and velocities at 0.1% and 0.5% of each coordinate's training standard deviation, with dimensionless floors 10^{-4} for X and 10^{-5} for Y. The modal projections are assumed observable; this test does not validate a particular sensor layout. At 0.5%, the reconstructed training-tip noise RMS is 3.80, 5.72 and 3.33 μm for the three settings. No noise is added to future reference labels. Figure 8 and Table 9 show that adding the missing physics resolves the main model-class error. The free-quadratic model can absorb reduction error and is slightly more accurate in the two changed settings; a universal advantage for the physical prior is not inferred. For the soft setting, the expanded clean fit identifies $e = 0.849522$, $m = 1.199860$, $G = 0.500272$ T/m, $\alpha = 0.753909$ s^{-1} and $c_2 = 0.020832$ kg/m^2. The last two values differ from their full-plant values by approximately 3.1% and 4.2%. Thus accurate state prediction is not presented as exact parameter recovery. A four-mode predictor supplied with the true soft-setting parameters itself has 10.894 μm mean tip RMSE, showing the retained influence of reduction error.

Table 9. Mean tip RMSE over three independent full-FE tests in μm. The noisy entries average three independent training-noise seeds; the clean fit is counted once. The last control has a freely learned quadratic potential.

Case	Noise	Omitted	Expanded	Free H_2
Nominal	0	2.415	2.415	2.417
Nominal	0.5%	2.833	2.807	2.996
Soft/$+G$	0	182.988	9.829	7.258
Soft/$+G$	0.5%	183.028	9.757	7.216
Stiff/$-G$	0	166.496	2.121	1.978
Stiff/$-G$	0.5%	166.916	2.841	2.808




Figure 7. Finite-time quasiperiodicity diagnostics for the seventh fitted Hamiltonian. (a) Uniform action sampling; angles are independently uniform. (b) Consecutive-window agreement on the first eight fixed trajectories; the long-window floor reflects integration error and roundoff. (c) Step refinement on the first 64 fixed initial points; the coarse integration failures are retained and are not classified as evidence of chaos. (d) Candidate fractions and exact sampling intervals at three thresholds, using the same 1024 points with refined integration. None of these finite-time tests is a proof of an invariant torus for every accepted initial condition.

An independent COMSOL solve tests the changed soft-rod setting from rest for 4 s, including the same gradient force, magnetic moment and distributed quadratic drag. Against the separate full-FE Python solve, the tip RMSE is 0.000189 μm and the maximum difference is 0.000623 μm; the input-field difference is below 2.73×10^{-17} T. The learning coefficients were frozen before this COMSOL test and are not refitted. The omitted-physics, expanded and free-quadratic predictors obtain respectively 190.055, 9.644 and 6.946 μm tip RMSE. This comparison checks an independently implemented altered mechanical model, rather than only another trajectory of the original exact-in-class target.

6.8 Causal adaptation to slowly changing unknown parameters

To test time variation separately from recalibration between settings, we generate a 29 s full-FE trajectory with a smooth drift. Define $s = \mathrm{clip}_{[0,1]}((t - 4\,\mathrm{s})/(24\,\mathrm{s}))$ and $a = (1 - \cos \pi s)/2$. The hidden plant has $e = 0.85 + 0.20a$, $m = 1.20 - 0.20a$ and $\alpha/\alpha_{\mathrm{ref}} = 1.40 - 0.40a$, while $G = 0.5$ T/m and $c_2 = 0.02$ kg/m^2 remain fixed. Multisine excitation continues throughout. At cutoffs $8, 12, 16, 20, 24, 28$ s, each estimator receives only the preceding 4 s of positions, velocities and known input. It then predicts the next 1 s from the currently observed state. The coefficients are frozen before future state labels are accessed.

A constant sliding-window fit and a locally affine coefficient fit use the same weak identity (102); the latter adds features multiplied by $(t - t_{\mathrm{cut}})/(4\,\mathrm{s})$. Linear constraints preserve the nonnegative readouts over both the fitting interval and the forecast interval. The known future input is supplied to all predictors, but future states and true parameter values are withheld. Across the six forecasts, the mean next-second tip RMSE is 387.483 μm for the initial fit frozen at 4 s, 59.217 μm for causal constant refitting and 9.867 μm for causal affine adaptation. The affine errors range from 2.701 to 17.295 μm. Constant refitting is better at the




Figure 8. State noise and physics outside the nominal hypothesis class. Each point averages three independent held-out trajectories. Bars show the sample standard deviation across three training-noise seeds; the clean fit is counted once. The higher-error model still re-identifies its retained parameters.




Figure 9. One-second forecasts made using only past data under slow material and magnetic drift. The frozen, constant and affine predictors share the same current observed state and prescribed future input.

final cutoff, where the physical drift stops; this limitation of extrapolating a local trend is retained. These are six forecasts on one declared drift trajectory, not independent patient experiments or a general online-learning theorem.

For this nonautonomous plant, the physical energy ledger includes $E_0[\dot{e}X^{\mathsf{T}}A_{\mathrm{el}}X/2 + \dot{m}(1-\cos\vartheta) - \dot{g}(G_{\mathrm{ref}}/B_0)(\ell^{\mathsf{T}}X)\sin\vartheta]$ in addition to magnetic input power and fluid losses. Its maximum numerical residual is 6.06×10^{-14} J. The stationary conservative KAM certificates are not transferred to these driven, dissipative, time-dependent trajectories.

7 Preserving KAM dynamics through magnetic actuation

7.1 *Magnetic feedback that preserves the learned KAM dynamics*

An additional, explicitly declared magnetic field-gradient port permits direct preservation of the certified conservative dynamics despite physical damping. This construction concerns the same finite-element beam; it adds tip-force authority through a spatially varying field. It does not assign independent modal actuators.

Let a_j be the physical mass-normalized modal positions of the complete 64-mode FE model, with velocities v_j, frequencies ω_j, tip-displacement participation b_j, and tip-rotation participation t_j. For the rigorous numerical statement, the frozen exported modal coefficients and Hermite shape map define this computational model exactly; the small numerical diagonalization residual relative to the assembled nodal matrices is quantified below. Write $\vartheta = \sum_j t_j a_j$ and $E_0 = \mu B_0$. With transverse tip force F and transverse field B_y, the exact declared modal equations are

$$\begin{aligned} \ddot{a}_j + \alpha\dot{a}_j + \omega_j^2 a_j &= b_j F + t_j U, \\ U &= E_0(\vartheta - \sin\vartheta) + \mu B_y \cos\vartheta. \end{aligned} \tag{103}$$

The frequencies already include the linear stiffness from B_0. For the first two modes define

$$A_{\mathrm{mag}} = \begin{pmatrix} b_1 & t_1 \\ b_2 & t_2 \end{pmatrix}. \tag{104}$$

Its determinant is enclosed away from zero in the supplied modal data.

Let $h(X,Y)$ be the complete frozen learned Hamiltonian used by the KAM certificate, including momentum-dependent quartics. Set $a_i = S_i X_i$ and recover Y from

$$h_Y(X,Y) = \operatorname{diag}(S_i)^{-1} v_{1:2}/\omega_0. \tag{105}$$

This implicit velocity-to-momentum map cannot be replaced by $Y_i = v_i/(S_i\omega_0\nu_i)$ when the learned momentum quartics are retained. The verified lower bound on h_{YY} below makes the map locally invertible and injective in Y on the stated real box. Define

$$a^{\mathrm{des}}_{i,tt} = S_i\omega_0^2\big(h_{YX}h_Y - h_{YY}h_X\big)_i, \tag{106}$$

$$\begin{pmatrix} F \\ U \end{pmatrix} = A_{\mathrm{mag}}^{-1}\left(a^{\mathrm{des}}_{1:2,tt} + \alpha v_{1:2} + \operatorname{diag}(\omega_1^2,\omega_2^2)a_{1:2}\right). \tag{107}$$

Consequently $\dot X = \omega_0 h_Y$ and $\dot Y = -\omega_0 h_X$ exactly where the implicit inverse is defined. The proof follows by differentiating (105): the specified acceleration cancels the h_{YX} term and invertibility of h_{YY} gives the second canonical equation.

The physical commands realizing (107) are

$$B_y = \frac{U - E_0(\vartheta - \sin\vartheta)}{\mu\cos\vartheta}, \qquad G = \frac{F}{\mu}\begin{pmatrix} -\sin\vartheta & \cos\vartheta \\ \cos\vartheta & \sin\vartheta \end{pmatrix}. \tag{108}$$

Use $B(r) = B_{\mathrm{tip}} + G(r - r_{\mathrm{tip}})$ locally, with $B_{\mathrm{tip}} = (B_0, B_y)$. The matrix G is symmetric and traceless, so this local planar field satisfies the source-free curl and divergence constraints. For dipole $m = \mu(\cos\vartheta, \sin\vartheta)$ it gives $Gm = (0,F)$, while the tip torque is $\mu(B_y\cos\vartheta - B_0\sin\vartheta)$. Moreover $\|G\|_2 = |F|/\mu$. The applied mechanical power is $F\dot w(L) + \mu B_y\cos\vartheta\,\dot\vartheta$, in addition to the static magnetic energy already included in the Hamiltonian. The construction assumes these local field and gradient commands are available and the required modal and tip states are observed.

7.2 Lifting a certified torus to the complete controlled FE model

Theorem 11. Invariant-torus lift under physical magnetic feedback. *Suppose a real analytic embedded two-torus K_∞ of h has frequency $\Omega \in \mathbb{R}^2$ in radians per physical second. Suppose h_{YY} is positive definite near this torus, A_{mag} is invertible, $\alpha > 0$, and the complete lifted solution has $|\vartheta| < \pi/2$. Then the full FE closed loop (103)–(108) has an embedded invariant two-torus projecting to K_∞. For a fixed low-mode orbit on this torus, each high-mode solution converges exponentially to a unique quasiperiodic response, provided the feedback remains in its stated field and state domain.*

Proof. The first two canonical modes follow h exactly. Hence F and U in (107) depend only on their torus phase, even though the physical field command also uses the complete tip angle. For every $j \ge 3$, the remaining dynamics are the stable linear equation (103), forced by analytic quasiperiodic functions. If F_k, U_k denote their Fourier coefficients in the convention $e^{ik\cdot\phi}$, the unique response graph is

$$a^*_{j,k} = \frac{b_j F_k + t_j U_k}{\omega_j^2 - (k\cdot\Omega)^2 + i\alpha(k\cdot\Omega)}. \tag{109}$$

For real $k\cdot\Omega$, this denominator never vanishes: at zero frequency its real part is $\omega_j^2 > 0$, and at nonzero frequency its imaginary part is nonzero. Its inverse is uniformly bounded over real frequencies. Exponential Fourier decay is therefore preserved on a possibly smaller analytic strip. The velocity graph is obtained by multiplication by $ik\cdot\Omega$ and is analytic on a smaller strip. The complete embedding is injective because its projection onto the first two canonical modes is injective. Differences in the high modes obey the homogeneous damped equations and decay exponentially.

The lifted closed loop contains the certified Hamiltonian motion while its high-mode fibres contract. The full controlled system is not claimed to be Hamiltonian, and the low modes are not claimed to converge toward a unique torus. A two-torus is also not a positive-volume subset of the full 128-dimensional phase space. The low-dimensional KAM-family statement and this complete-FE invariant-torus lift have their respective dimensions and conclusions.

All-phase bounds without sampled maxima. We give executable bounds both on the response graph and on the startup with all high modal positions and velocities initially zero. Write $h = h_2 + R$, and let the certified torus satisfy $\|K_\infty - K_0\|_\infty \le \epsilon_K$, where $K_0 = 0.1(\cos\phi_1, \cos\phi_2, -\sin\phi_1, -\sin\phi_2)$. The first two components of the force demand can be written as

$$\begin{aligned} r_i = S_i\big\{&\omega_0^2[(R_{YX}h_Y)_i - \nu_i R_{X_i} - (R_{YY}h_X)_i] \\ &+ \alpha\omega_0 h_{Y_i} + (\omega_i^2 - \omega_0^2\nu_i^2)X_i\big\}, \end{aligned} \tag{110}$$

This identity cancels the large linear restoring terms before bounding. The linear part on K_0 consists of just the two known physical frequencies. Each is bounded using its actual

damped denominator in (109). The remaining terms are bounded on $|X_i|, |Y_i| \le 0.1 + \epsilon_K$ using every saved quartic coefficient and the complete trigonometric remainder bounds $|\sin z - z| \le |z|^3/6$ and $|1 - \cos z| \le z^2/2$ for real z.

For $\beta = \alpha/2$ and $\omega_{d,j} = \sqrt{\omega_j^2 - \beta^2} > 0$, the impulse response $g_j(t) = e^{-\beta t} \sin(\omega_{d,j} t)/\omega_{d,j}$ obeys

$$\|g_j\|_{L^1(0,\infty)} \le \frac{2}{\alpha \omega_{d,j}}, \qquad \|g_j'\|_{L^1(0,\infty)} \le \frac{2}{\alpha} + \frac{1}{\omega_{d,j}}. \tag{111}$$

These estimates enclose the response to the entire nonlinear forcing remainder; no frequency cutoff or numerical maximum is substituted for the missing Fourier terms. Let P_j, V_j be the resulting all-phase bounds on the graph's position and velocity. Starting high mode j at zero adds at most

$$T_j = P_j + \frac{V_j + \beta P_j}{\omega_{d,j}} \tag{112}$$

to its position envelope. This follows from the exact homogeneous solution initialized by $(-a_j^*(0), -\dot{a}_j^*(0))$. The delivered proof uses all 62 high modes and the cubic Bernstein control rows of every Hermite element to convert these modal envelopes into bounds on every centreline point and every phase.

For the seventh frozen COMSOL integral fit, which also passes the nonzero-loss and finite-amplitude KAM certificates, 256-bit Arb arithmetic encloses $h_{YY} \succeq 0.9999999983 I$ on the real 0.3 box. The complete response graph has centreline amplitude below 1.922696 mm. Including the zero-high-mode startup yields an all-time bound below 1.970263 mm, strictly inside the 4 mm net corridor. The latter envelope gives $|\vartheta| < 0.155261$ and $\cos\vartheta > 0.987971$, which closes the feedback-domain bootstrap. The required transverse field is below 0.921665 mT and the gradient spectral norm below $0.02572538\,\mathrm{T\,m^{-1}}$ at every phase and throughout that startup. These bounds validate feasibility under a 20 mT transverse field limit and a $1\,\mathrm{T\,m^{-1}}$ gradient limit; they are derived bounds, not the extrema of a simulated time history. The same independent computation is also retained for the earlier COMSOL full-FE-trajectory fit: its complete graph and zero-high-state startup bounds are 1.937308 mm and 2.014078 mm, respectively.

The theorem applies to initial low states on the exact certified torus. The numerical Fourier initial state approximates it within the supplied KAM correction, and finite-time integration provides a separate implementation check. The certificate identifies the exact exported modal FE coefficients, frozen learned weights, candidate and KAM proof by their hashes; independent COMSOL comparisons test the corresponding mechanical implementation without replacing these assumptions. To make the modal definition explicit, if Φ is the stored full shape basis, M, K_b are the independently assembled nodal matrices and $D_\omega = \mathrm{diag}(\omega_j)$, outward Arb products give

$$\|\Phi^{\mathsf{T}} M \Phi - I\|_\infty < 1.304685 \times 10^{-14}, \tag{113}$$

$$\|D_\omega^{-1} \Phi^{\mathsf{T}} K_b \Phi D_\omega^{-1} - I\|_\infty < 3.000518 \times 10^{-9}. \tag{114}$$

These are relative kinetic- and stiffness-energy form bounds. They quantify the relationship between the frozen modal model and the original assembled FE representation; they are not used to assert an exact conjugacy or an unproved persistence result for perturbed matrices. The earlier saved two-mode shape map differs from the reassembled map by at most 1.258×10^{-14} m, and the reference frequency ω_0 is unchanged.

7.3 Full-model implementation and frequency preservation

The feedback is integrated on all 64 modes for 12 s, using the frozen integral-COMSOL fit certified in Section 5.5. The initial low state is the phase-zero Fourier candidate and all higher modal positions and velocities are zero. A separate high-accuracy integration of the four-dimensional learned Hamiltonian supplies an implementation reference; no modal actuator is inserted into the plant. The maximum canonical state difference is 1.54×10^{-10}, the relative learned-energy change is below 2.64×10^{-9}, and the full physical work-balance residual is below 6.06×10^{-17} J. The sampled field and gradient peaks are 0.890325 mT and 0.0256844 T/m. Figure 10 compares this trajectory with the same initial state under passive damping, for which the learned energy decreases by 99.8726%. The numerical trajectory is an implementation check; the all-time envelopes come from the preceding interval proof. An independent implementation integrates the low Hamiltonian separately and propagates each of the 62 high damped oscillators by its exact exponential response to piecewise-linear force demands. Force-grid steps of 1, 0.5 and 0.25 ms give maximum tip differences from the full-state integration of 1.073, 0.277 and 0.106 nm, respectively. Every high-mode homogeneous transient is retained. This check separates time-step error from modal truncation and supports the full-state implementation without interpreting solver tolerances as rigorous bounds.

Independent online COMSOL feedback. The complete nodal beam is also solved with the CHNN feedback inside

Table 10. Actual online COMSOL feedback versus independent Python integration. Errors are in μm; no step-size tolerance is interpreted as a rigorous error bound.

Step (ms)	Tip RMSE	Maximum tip difference
1	147.852	355.845
0.5	41.356	99.176
0.25	12.006	28.161
0.125	3.848	8.658

COMSOL. The first two modal coordinates and velocities are projected from its current beam state; two global algebraic equations enforce the learned Legendre inverse. The physical tip force and magnetic moment are recomputed online. This experiment is distinct from the prescribed-field S-path replay. Generalized-alpha integration uses $\rho_\infty = 0$, a nonlinear relative tolerance of 10^{-8} and fixed steps. Table 10 retains all four 4 s refinements and compares them at common saved times with the independent full-state Python run. At the finest step, the maximum relative change in the learned energy is 0.0002958. These numerical errors are reported separately from the analytic KAM and all-time amplitude certificates. Two earlier adaptive-step attempts stalled at very small steps and were stopped; their records are retained. The fixed-step solves complete successfully, and the native models, actual field commands and all nodal outputs are supplied.

The two certified physical angular frequencies are approximately 11.41719351 and 70.24034116 rad/s. Their exact specification and all-integer Diophantine bound are inherited from the saved KAM certificate, with the declared time normalization. Magnetic feedback therefore preserves a certified nonresonant frequency pair while compensating damping. The complete nonlinear command contains the harmonics determined by the torus; it is not approximated by two sinusoidal inputs when invoking the lifting theorem. The rigorous state and command envelopes provide a simultaneous amplitude check. No chaotic threshold or fixed-domain survival percentage is inferred from the finite trajectory.

8 Clearance guarantees and magnetic safety control

8.1 A whole-beam clearance certificate for the same magnetic model

The conservative normal form and the safety calculation use the same clamped-free beam, static field, magnetic dipole, and energy. Safety is a statement about the driven physical equations, with their nonnegative drag; it does not require a driven trajectory to lie on a conservative KAM torus. For the declared planar, small-slope model, write $w(s,t)$ for transverse displacement, $m = \rho A$ for line density, $c_d \geq 0$ for distributed viscous drag, and $\vartheta = w_s(L,t)$ for the tip slope used in the dipole potential. The equations and natural end conditions are

$$mw_{tt} + c_d w_t + EIw_{ssss} = 0, \qquad 0 < s < L, \tag{115}$$

$$w(0,t) = w_s(0,t) = 0, \qquad w_{sss}(L,t) = 0, \tag{116}$$

$$EIw_{ss}(L,t) = \mu\{B_y(t)\cos\vartheta - B_0\sin\vartheta\}. \tag{117}$$

The end moment is the derivative of the same cosine potential used to generate the training trajectories. In particular, the varying transverse field is an input port, not an additional autonomous Hamiltonian perturbation. For a sufficiently regular solution satisfying the mechanical power identity, the stored energy relative to the aligned static-field equilibrium is

$$E(t) = \frac{1}{2}\int_0^L \{mw_t^2 + EIw_{ss}^2\}\,\mathrm{d}s + \mu B_0(1-\cos\vartheta), \tag{118}$$

$$\dot{E} = -c_d\int_0^L w_t^2\,\mathrm{d}s + \mu B_y\cos\vartheta\,\dot{\vartheta}. \tag{119}$$

All inequalities below also hold for the conforming cubic-Hermite finite element (FE) system and any of its Galerkin subspaces, because their energies are the restrictions of this expression and retain the same input power. In the balanced coordinates of the learning experiment, $E = \mu B_0 h_*$ for the physical target energy, $\vartheta = d^{\mathsf{T}}X$, and the port force in the Y equation is $d(B_y/B_0)\cos(d^{\mathsf{T}}X)$.

Proposition 12. Clearance and field-variation budget. *Assume $B_0 > 0$, $c_d \geq 0$, and an absolutely continuous applied field B_y on $[0,T]$. Define*

$$S_T = \sup_{0\leq t\leq T}|B_y(t)| + |B_y(0)| + \int_0^T |\dot{B}_y(t)|\,\mathrm{d}t, \tag{120}$$

$$C_T = \mu\sqrt{\frac{2L}{EI}}S_T, \tag{121}$$

$$R_T = \frac{C_T + \sqrt{C_T^2 + 4E(0)}}{2}. \tag{122}$$

Then, throughout $[0,T]$,

$$E(t) \leq R_T^2,$$
$$|w(s,t)| \leq \sqrt{\frac{2s^3}{3EI}}R_T, \tag{123}$$
$$|w_s(s,t)| \leq \sqrt{\frac{2s}{EI}}R_T.$$




Figure 10. Magnetic preservation of the actual integral-COMSOL learned Hamiltonian on the complete exported modal FE plant. The higher modes start at zero and undergo a decaying transient toward their unique quasiperiodic response graph. Dashed bounds in (a), (c) and (d) are validated all-phase bounds, including that startup. The field and gradient in (c,d) jointly realize physical tip force and torque. Panels (a,c,d) show the first 2 s; panel (b) shows the complete 12 s run.

For a straight corridor with wall half-width a and rod radius r, let $c = a - r > 0$. A sufficient condition for positive clearance of the whole rod is $R_T < \sqrt{E_c}$, where

$$E_c = \frac{3EIc^2}{2L^3}. \tag{124}$$

For $E(0) < E_c$, the following directly checkable operating condition is equivalent to this sufficient energy condition:

$$S_T < \frac{E_c - E(0)}{\mu\sqrt{2LE_c/EI}}. \tag{125}$$

These conclusions hold for every nonnegative drag coefficient, including zero.

Proof. Since $B_0 > 0$, the static magnetic energy is nonnegative and $\|w_{ss}\|_{L^2}^2 \le 2E/EI$. The clamped conditions imply $w(s) = \int_0^s (s-\xi) w_{ss}(\xi)\,\mathrm{d}\xi$ and $w_s(s) = \int_0^s w_{ss}(\xi)\,\mathrm{d}\xi$. Cauchy–Schwarz gives the two spatial inequalities in (123) with $\sqrt{E}$ in place of R_T. Write $D_c(t) = \int_0^t c_d \|w_t\|_{L^2}^2\,\mathrm{d}\tau$. Integrating (119) by parts in the input term gives

$$\begin{aligned} E(t) + D_c(t) - E(0) &= \mu B_y(t)\sin\vartheta(t) \\ &\quad - \mu B_y(0)\sin\vartheta(0) \\ &\quad - \mu\int_0^t \dot{B}_y(\tau)\sin\vartheta(\tau)\,\mathrm{d}\tau. \end{aligned}$$

Set $M_T = \sup_{[0,T]}\sqrt{E(t)}$. Using $|\sin\vartheta| \le |\vartheta| \le \sqrt{2L/EI}\,M_T$ and discarding the nonnegative dissipation yields $M_T^2 \le E(0) + C_T M_T$. The positive root is R_T. The entire radius-r tube about the centerline remains between the walls when $\sup_s |w(s,t)| < a - r$. Solving $R_T < \sqrt{E_c}$ gives (125).

For a nonuniform planar corridor, let $c(s) > 0$ be the Euclidean distance from the undeformed point $(s, 0)$ to the wall, less the rod radius. The distance-to-wall function is one-Lipschitz, so $|w(s)| < c(s)$ keeps the radius-r tube clear. The same argument replaces E_c by $\inf_{0<s\le L} 3EIc(s)^2/(2s^3)$. For an inclined or curved wall, a local vertical half-width is not a substitute for this Euclidean

clearance. This is a sufficient condition for that specified geometry; it is not a vessel-specific claim in the absence of vessel data. The full-continuum inequality removes the need to interpret an observed two-mode reconstruction error as a rigorous neglected-mode bound. It certifies solutions of the stated continuum model with the stated initial-energy and applied-field bounds, rather than claiming an FE trajectory is an exact continuum trajectory.

For the shared SI parameters, choose $a = 4.6$ mm and $r = 0.6$ mm, so that $c = 4$ mm. The resulting E_c is 23.8565 nJ. For a monotone field ramp from zero to A followed by a hold, $S_\infty = 2A$. With zero initial energy, a sufficient condition is

$$A < \frac{\sqrt{3}\,EIc}{4\mu L^2} = 6.8868\ \mathrm{mT}. \tag{126}$$

For $B_y = A\rho(t)\sin(\Omega t)$ with $\rho(t) = 1 - \exp[-(t/0.25\,\mathrm{s})^2]$, $S_T \le A(2 + \Omega T)$, because ρ increases from zero and is at most one. Thus amplitude, frequency and operating duration enter an explicit joint condition by substituting this bound in (125). For $T = 8$ s, $\Omega = 9.444949$ rad/s and $E(0) = 0$, its sufficient amplitude limit is approximately 0.1776 mT. This conservative open-loop test does not certify the default 6 mT sinusoid, even when a simulated trajectory has positive clearance.

8.2 A magnetic-input governor with a full-model energy guarantee

The field-variation test can be strengthened for feedback operation by measuring the actual mechanical input port. Let $\overline{E}_0 \ge E(0)$ be a valid initial-energy bound and integrate

$$W(t) = \overline{E}_0 + \int_0^t \mu B_y \cos\vartheta\,\dot\vartheta\,\mathrm{d}\tau. \tag{127}$$

Equation (119) gives $E(t) \le W(t)$ without measuring or estimating the dissipated energy. Given $E(0) \le \overline{E}_0 < E_{\max} < E_c$, a bounded requested field $|B_{\mathrm{req}}| \le B_{\max}$, and $\kappa > 0$, choose the applied field as the closest value to B_{req} satisfying

$$\begin{aligned} |B_y| &\le B_{\max}, \\ a_p B_y &\le \kappa(E_{\max} - W), \\ a_p &= \mu\cos\vartheta\,\dot\vartheta. \end{aligned} \tag{128}$$

This is a scalar projection onto an interval. Whenever the requested input violates the work constraint and $a_p \neq 0$, the applied field is $B_y = \kappa(E_{\max} - W)/a_p$; otherwise it is unchanged. On $W \le E_{\max}$, zero field is feasible, and this projection never increases the requested field amplitude.

Proposition 13. Port-work safety invariant. *Suppose the actual applied field and actual tip slope and slope rate are available to (127)–(128), and the field command is applied without unbudgeted error or delay. Every closed-loop solution satisfying the mechanical power identity obeys*

$$\begin{aligned} E(t) \le W(t) \le E_{\max}, \\ \sup_s |w(s,t)| \le \sqrt{\frac{2L^3 E_{\max}}{3EI}} < c. \end{aligned} \tag{129}$$

Consequently the entire rod retains positive wall clearance for all times on which the stated beam model and port measurements apply, for any $c_d \ge 0$.

Proof. The power identity gives $W - E = \overline{E}_0 - E(0) + \int_0^t c_d\|w_t\|_{L^2}^2\,\mathrm{d}\tau \ge 0$. The input constraint yields $\dot W \le \kappa(E_{\max} - W)$, hence $E_{\max} - W(t) \ge (E_{\max} - \overline{E}_0)\exp(-\kappa t) \ge 0$. The spatial estimate proved above completes the result.

This guarantee uses the full physical input port rather than the energy predicted by a two-mode learned model. A learned model can generate the requested field, but its unobserved high modes do not disappear from the work balance. The result assumes an accurate actual-port measurement and ideal command application; sensor, actuation and delay errors require additional work-error budgets. No field slew-rate guarantee is claimed. Because dissipated energy is not credited back, the work observer can restrict the request even when the actual stored energy has decreased. This is a conservative safety mechanism, not an arbitrary tracking theorem.

A bounded port-measurement error can be included without assuming an exact learned state. If $|a_p - \widehat{a}_p| \le \delta_a(t)$, replace the observer derivative and its input constraint by

$$\begin{aligned} \dot W &= \widehat{a}_p B_y + \delta_a |B_y| \\ &\le \kappa(E_{\max} - W). \end{aligned} \tag{130}$$

Actual input power is at most this observer derivative, so the same proof applies. Zero field remains feasible and the scalar feasible set is convex. Here B_y must be the actual applied field; an uncertain command-to-field map requires a further bound on actual input power. The numerical tests below use $\delta_a = 0$ and do not experimentally validate a sensor-error bound.

8.3 Full-FE safety, violation and truncation checks

All tests use the shared 32-element consistent-mass FE beam, retain all 64 unconstrained displacement/slope degrees

of freedom, and integrate the exact cosine tip potential. The coordinates are the complete 64-mode static-field basis; this is a change of coordinates, not a modal truncation. The default drag is $C = \alpha M$ with $\alpha = 0.55558524\ \mathrm{s}^{-1}$. Unless stated otherwise, trajectories start from rest at the straight equilibrium. The sinusoidal tests use the original $\Omega = 9.444949$ rad/s and the 0.25 s ramp above; the monotone tests omit the sine factor. The integration interval is 8 s. The continuous-time claims come from Propositions 12 and 13; cubic-Hermite spatial extrema are evaluated exactly at each saved time for the numerical diagnostics.

Table 11 separates numerical maxima from continuous-time certificates. The 6 mT monotone ramp satisfies an all-time displacement bound of 3.48494 mm, including zero drag. The default 6 mT sinusoid has a numerical peak of 3.09031 mm, but fails the conservative field-variation test; that peak alone is not a safety proof. Increasing its amplitude to 10 mT produces a 5.14478 mm free-motion peak and crosses the 4 mm boundary. The continuation after crossing is a diagnostic of a violated constraint, not a simulation of wall contact.

With $E_{\max} = 0.95E_c = 22.66365$ nJ and $\kappa = 5\ \mathrm{s}^{-1}$, the work governor applied to the same 10 mT request has a rigorous whole-centerline bound of 3.89872 mm and thus a minimum guaranteed clearance of 0.10128 mm. Its numerical peak is 3.14362 mm with the default drag and 3.55853 mm with zero drag. The same energy cap also implies $\sup_s |w_s| \le 0.08441$, consistent with the declared small-slope regime for the certified trajectories. Tightening both relative and absolute integration tolerances tenfold for the full-FE governed case changes the tip trajectory by at most 8.19×10^{-11} m; the refined power-balance residual is 3.86×10^{-18} J (1.74×10^{-10} relative to the work scale). The governor changes the requested field at 55.37% of saved times in this oscillatory case.

For the original 6 mT sinusoid, the maximum tip discrepancies of the 2-, 4-, and 8-mode reconstructions against the full 64-mode FE trajectory are 22.7168, 5.9661, and 1.5156 μm, respectively (0.73510%, 0.19306%, and 0.04904% of the full-FE peak). These are measured truncation errors for this input, not rigorous bounds for all neglected modes or all trajectories. The full-continuum energy certificate does not substitute any of them for an unknown error constant. An independent COMSOL HermitianBeam integration of the same 32-element consistent-mass model gives a default-sinusoid peak of 3.09032 mm; its largest tip difference from the present integration is 0.11835 μm. Tightening the COMSOL relative tolerance to 10^{-8} reduces the largest tip difference to 0.02160 μm. Independent COMSOL runs also reproduce the 6 mT monotone-ramp safe case and 10 mT sinusoidal violation: their peaks are 0.924046 and 5.144787 mm, with maximum cross-solver tip discrepancies of 0.00663 and 0.03489 μm, respectively. This cross-check concerns the same mathematical model and does not calibrate material or actuation parameters against hardware.

The closed-loop governor was also implemented inside COMSOL, coupling a global ODE for $W/E_{\max}$ to the nonlinear magnetic end moment. This run used the generalized-α time integrator with $\rho_\infty = 0$, relative tolerance 10^{-5}, and a maximum internal step of 0.002 s; the 2001 saved outputs are spaced by 0.004 s. Its full-FE centerline peak is 3.143643 mm, leaving a sampled net clearance of 0.856357 mm. The maximum tip discrepancy from the refined Python trajectory is 0.582073 μm, or 0.018516% of its peak. The applied field remains below 9.816986 mT. The COMSOL-integrated work observer peaks at 22.253032 nJ, or $0.9818823E_{\max}$; $E \le W \le E_{\max}$ and the magnetic-power projection hold at every saved time. Its maximum work-observer discrepancy from Python is 2.263×10^{-12} J.

For an independent energy ledger, reconstruct E from all displacement and velocity DOFs and compute

$$D_h(t) = \int_0^t \alpha \dot{q}^{\mathsf{T}} M \dot{q}\, \mathrm{d}\tau,$$
$$R_E(t) = E(t) - E(0) - [W(t) - W(0)] + D_h(t).$$

Simpson quadrature on the saved outputs gives $\max_t |R_E(t)| = 5.796 \times 10^{-12}$ J after rounding up, or 2.605×10^{-4} of the work scale. The Simpson–trapezoid difference for that dissipation integral is 2.424×10^{-13} J. This COMSOL run uses high-frequency numerical damping and a looser tolerance than the refined Python integration; its ledger residual includes time-integration and output-quadrature errors. The separately integrated COMSOL work state is used for the observer comparison, rather than replacing it by a coarse-output input power integral. These numerical checks corroborate the implementation; the continuous-time clearance statement remains the analytic invariant in Proposition 13.

8.4 The learned CHNN generates a feasible magnetic tracking request

To connect identification to an actual input decision, the fitted GC model with seed 17 and its identified dissipation coefficient generate a nominal magnetic field

Table 11. Safety tests on the same full 32-element, 64-DOF FE beam. Numerical maxima are cubic-Hermite spatial extrema at 2001 saved times over 8 s. Bounds are continuous-time sufficient bounds from the stated propositions. "No" means the sufficient test does not certify the case. All fields use a 0.25 s ramp; sine frequency is 9.444949 rad/s. Except the stated $E_c/4$ case, initial energy is zero.

Applied protocol	Peak (mm)	Bound (mm)	Certified
6 mT ramp/hold	0.92405	3.48494	Yes
3 mT ramp, $E(0) = E_c/4$	2.06222	3.05276	Yes
0.15 mT sine	0.07731	3.37863	Yes
6 mT sine	3.09031	135.145	No
10 mT sine	5.14478	225.242	No
Governed 10 mT sine	3.14362	3.89872	Yes
Governed 10 mT, zero drag	3.55853	3.89872	Yes
6 mT ramp, zero drag	0.95405	3.48494	Yes




Figure 11. Whole-beam safety for the shared full FE plant, with zero initial energy and default drag. (a) A 6 mT monotone ramp and its all-time continuum energy certificate. (b) The 10 mT ramped sinusoidal request at 9.444949 rad/s violates the 4 mm net corridor margin; the actual port-work governor preserves it with an analytically guaranteed bound. (c) Stored energy and accumulated input-work bound for the governed case. The wall half-width is 4.6 mm and rod radius 0.6 mm. These are declared geometric constraints on a simulated beam, not patient-specific noncollision evidence or a KAM test.

for the full FE plant. Let $z = (X_1, X_2, Y_1, Y_2)$ denote the observed projection onto the first two static-field modes, $\ell^{\mathsf{T}} X$ its reconstructed tip displacement, and h_θ the actual fitted energy, including all learned mixed and momentum-dependent quartic coefficients. Define, in the dimensionless time $\tau = \omega_0 t$,

$$y = \ell^{\mathsf{T}} X, \qquad y' = \ell^{\mathsf{T}} h_{\theta,Y}, \tag{131}$$

$$f_0 = \ell^{\mathsf{T}} h_{\theta,YX} h_{\theta,Y} - \ell^{\mathsf{T}} h_{\theta,YY}(h_{\theta,X} + D_\theta h_{\theta,Y}), \tag{132}$$

$$g_0 = \ell^{\mathsf{T}} h_{\theta,YY}\, d \cos(d^{\mathsf{T}} X), \tag{133}$$

$$D_\theta = \widehat{\gamma}\ \mathrm{diag}(\nu)^{-1}. \tag{134}$$

Where $g_0 \neq 0$, the nominal request is

$$a_r = r'' - k_p(y - r) - k_d(y' - r'), \tag{135}$$

$$u_* = (a_r - f_0)/g_0, \tag{136}$$

$$B_{\mathrm{req}} = B_0\, \mathrm{clip}_{[-b,b]}(u_*), \tag{137}$$

$$b = B_{\max}/B_0. \tag{138}$$

The primes on r denote derivatives in τ. We use $k_p = 16/\omega_0^2$, $k_d = 8/\omega_0$, and $\widehat{\gamma} = 0.0486617964$. Both Hessian blocks are evaluated from the fitted model; they are not replaced by their quadratic-prior values. The plant receives only the scalar B_y through its actual tip moment, after the work-governor projection. It receives no independently assigned modal forces.

The requested SI tip trajectory is $y_{\mathrm{ref}}(t) = 2\,\mathrm{mm}\,(10s^3 - 15s^4 + 6s^5)$ for $s = t/(4\,\mathrm{s}) \in [0, 1]$, followed by a hold through 8 s, and $r(\tau) = y_{\mathrm{ref}}(\tau/\omega_0)$. The field limit is $B_{\max} = 20$ mT for this separate tracking protocol. This limit is justified by the actual static input authority: a 2 mm equilibrium requires $\vartheta = 2y_{\mathrm{tip}}/L = 0.05$ and

$$B_y^{\mathrm{eq}} = \frac{EI\vartheta/(\mu L) + B_0 \sin\vartheta}{\cos\vartheta} \simeq 17.43\,\mathrm{mT}. \tag{139}$$

The original 10 mT sinusoidal test and its safety ablation retain their original amplitudes; their actuator limit is not silently used to claim slow 2 mm tracking.

On the full 64-DOF plant, the actual tip has an RMS tracking error of 33.734 μm and a maximum error of 47.069 μm. The final tip position is 2.03515 mm and




Figure 12. The fitted GC17 CHNN and identified drag generate a single bounded transverse magnetic input for the same full 32-element FE beam. (a) A feasible 2 mm tip request over 4 s and the actual full-FE tip motion. (b) The applied field remains below the declared 20 mT limit. (c) Stored energy and the actual-port work observer stay below the safety cap. The controller uses the exact first-two-mode projection available in this simulation; the safety observer uses full-model tip power. No modal actuation authority or unmeasured-state observer is assumed. The governor is inactive for this feasible tracking request; its active effect is tested separately in Figure 11.

the largest centerline displacement is 2.03838 mm. The applied field peaks at 17.75695 mT; saturation and governor intervention occur at 0% of saved times. Thus the feasible learned request passes through the filter unchanged, and the separate unfiltered run is identical. The input-work bound peaks at 9.05293 nJ, below the 22.66365 nJ cap, and the same continuous-time safety invariant applies. The minimum absolute input gain along this run is 0.0138678 m, so the division in (138) does not approach a singularity. The physical power-balance residual is 3.53×10^{-20} J. This is a numerical tracking demonstration with the two-mode projection observed from the full state; an observer for incomplete sensing and a general tracking theorem are not claimed.

An additional independent run uses the frozen CHNN identified from COMSOL displacement and velocity exports by integral fitting, with cosine multiplier 1.0223248822. Its complete gradient and Hessian, including learned momentum quartics, generate the same 2 mm request on the same full-FE Python plant. For this conservative fit, a separate PSD drag identification on the existing Python-generated damped beam trajectories gives $\widehat{\gamma} = 0.0486617702$; this dissipative training source is distinct from the COMSOL conservative data. The tip RMSE is 33.726 μm, its maximum error is 47.065 μm, and the largest centerline displacement is 2.038365 mm. The applied field peaks at 17.756854 mT and the work observer at 9.052842 nJ. Saturation and governor intervention are again zero at the saved times, and the physical power-balance residual is 3.53×10^{-20} J. The saved fit and damping-file hashes bind this run to its actual readouts; the original GC17 results are preserved. The full-state projection and actual-port measurement assumptions are unchanged, and the same continuum clearance guarantee applies.

Finally, the single uniform-field dipole supplies one boundary moment. In static equilibrium with no distributed transverse loading, $w_{ssss} = 0$ and the free-tip shear condition imply $w(s) = \vartheta s^2/(2L)$. This one-parameter family cannot realize an arbitrary S-shaped static centerline. The moving-base endpoint task in Section 8.5 instead follows an S-shaped tip history and is executed below. The governor preserves a corridor while filtering a feasible magnetic request; richer prescribed paths require a demonstrated actuation map, such as distributed magnetic moments or additional independently controlled loads. No such authority is inferred from the scalar input used here.

8.5 A physically actuated S-shaped endpoint path

The moving clamped base permitted by the distributed formulation supplies an axial feed coordinate $b(t)$, while the same single transverse magnetic field bends the catheter. In the declared Cartesian small-slope model, the centreline is

$$\begin{aligned} r(s,t) &= \big(b(t) + s, w(s,t)\big), \\ r_{\mathrm{tip}}(t) &= \big(b(t) + L, w(L,t)\big). \end{aligned} \tag{140}$$

This protocol changes the endpoint history without prescribing independent modal forces or an S-shaped static centreline. The material length remains 80 mm throughout; advancing a varying length through a guide is a different boundary-value problem.

The base starts at rest. Over the first second its speed is $\dot{b} = v_b(10\xi^3 - 15\xi^4 + 6\xi^5)$, where $\xi = t/(1\,\mathrm{s})$ and $v_b =$

$4\,\mathrm{mm\,s^{-1}}$; afterwards $\dot b = v_b$. The transverse request is zero until 2 s. During the subsequent 12 s stroke, put $\sigma = (t - 2\,\mathrm{s})/(12\,\mathrm{s})$ and prescribe

$$y_r(t) = \frac{8A}{3\sqrt{3}}\left(\frac{1}{2}\sin 2\pi\sigma - \frac{1}{4}\sin 4\pi\sigma\right), \quad A = 1.5\,\mathrm{mm}. \tag{141}$$

Outside this interval $y_r = 0$. Its position, velocity and acceleration join continuously to zero, and its two lateral extrema are $\pm A$. The resulting S-shaped endpoint stroke advances 48 mm axially. The base acceleration is at most $7.5\,\mathrm{mm\,s^{-2}}$ and ends before any bending command is applied. Consequently the beam is exactly straight during axial acceleration and the base has zero acceleration throughout the bending stroke. There is no axial fluid load, guide friction, or imposed axial prestress in this declared test.

Base work and clearance. Let $m_b = \rho A_c L$ denote the rod mass, with A_c its cross-sectional area. Orthogonality of the axial and transverse Cartesian velocities gives

$$E_{\mathrm{total}} = E_\perp + \frac{1}{2}m_b\dot b^2, \qquad P_b = F_b\dot b = m_b\ddot b\dot b. \tag{142}$$

Here $E_\perp$ is the same transverse kinetic, bending and static-field energy used in the clearance theorem. The chosen timing also avoids transverse geometric-stiffness effects from an accelerating bent beam: the axial inertial load acts only while $w = 0$. During bending, axial translation is force-free in the stated model. Thus

$$\dot E_{\mathrm{total}} = \mu B_y \cos\vartheta\,\dot\vartheta - \alpha\dot q^{\mathsf T} M\dot q + P_b. \tag{143}$$

The base work is explicitly $W_b = m_b\dot b^2/2$; it is not silently assigned to, or omitted from, the magnetic input budget. The straight, open-ended corridor is invariant under axial translation. Its lateral noncollision proof therefore applies to $E_\perp$ and the actual magnetic port, while the separate base-energy balance is retained. For the same 4 mm net clearance and $0.95E_c$ transverse work cap, the continuous-time centreline bound remains 3.898718 mm. This statement would require additional work and geometry terms for curved walls, axial contact, variable insertion length or axial drag.

Frozen learned control and comparisons. The conservative readout is the same COMSOL position–velocity integral fit used in the invariant-torus certificate, with cosine multiplier 1.0223248822 and all its saved quartic terms. Its nonnegative drag readout is also held fixed. The controller evaluates its drift and magnetic input gain from the complete learned gradient and Hessian, as in the preceding tracking construction. For this experiment the feedback error uses the actual full-beam tip position and velocity; the first two modal projections supply the learned drift and gain. The request is clipped to $|B_y| \le 20$ mT and passed through the same physical input-work governor. Every plant run integrates all 64 FE degrees of freedom. The imposed base motion has the same force and speed budget in every comparison.

Table 12 retains an informative negative comparison: the known-physics static inverse is the most accurate controller on this slow, weakly nonlinear nominal trajectory. The learned controller does accomplish the prescribed S task, but this example does not establish a universal accuracy advantage over the baselines. Using the measured tip rather than its two-mode reconstruction reduces the CHNN error without changing the learned energy or introducing modal actuators.

The learned controller uses a peak field of 12.9177 mT and a sampled peak field slew of $10.4268\,\mathrm{mT\,s^{-1}}$. Its largest centreline displacement is 1.48892 mm, leaving 2.51108 mm of net lateral clearance at the saved times; the largest slope is 0.03718 rad. The magnetic-work upper bound peaks at 4.84997 nJ, below the 22.66365 nJ cap, and neither field saturation nor governor intervention occurs. The base's maximum kinetic energy is 0.796205 nJ, its peak ideal inertial force is $0.746442\,\mu$N, and its peak power is 1.90256 nW. Numerical total-energy balance includes this base work and has maximum residual 2.44×10^{-18} J. Tightening integration tolerances by a factor of ten and halving the maximum step changes the tip by at most 3.14×10^{-12} m and the commanded field by at most 1.47×10^{-10} T at saved times. All full-state histories, magnetic commands, base work, fitted-weight hashes and comparator runs are retained.

Independent COMSOL field replay. An additional COMSOL solve integrates the same full beam for 16 s using the saved learned-controller field, with piecewise-cubic field interpolation, generalized-alpha integration, relative tolerance 10^{-8} and maximum step 0.002 s. Its field-input file is identical to the frozen controller export by SHA256. Its tip differs from the Python result by 1.312×10^{-10} m RMS and at most 4.038×10^{-10} m, and its S-stroke tracking RMSE is $6.419\,\mu$m. The native model, API source and all nodal displacement, rotation and velocity outputs are supplied. This is independent mechanical integration of the stored command, not online CHNN feedback inside COMSOL. Axial translation is reconstructed using the same analytic base protocol. Power balance reconstructed by trapezoidal integration of the 0.004 s output samples has a 1.244×10^{-14} J residual; this diagnostic is distinguished from the

Table 12. S-path tracking on the full FE plant. RMS errors use the 12 s stroke; maxima use the full 16 s simulation. All baselines share the same trajectory, physical input and field bound.

Controller	RMS (μm)	Max. (μm)
Frozen CHNN, measured tip feedback	6.419	12.907
Quadratic model, measured tip feedback	6.207	12.476
Known-physics static inverse feedforward	4.124	8.005
Frozen CHNN, modal-output feedback	25.308	41.544

much tighter internal Python work-state integration and is not used as a rigorous solver-error bound.

9 Discussion

The mechanical, learned and operational models share the same clamped–free beam, static magnetic field and dimensional map. Two distinct COMSOL learning experiments serve complementary purposes. The full-FE position–velocity fit measures identification and reduction error against independent trajectories. The short, independently integrated two-mode observations admit a rigorous integral-defect budget and certify the complete learning-to-KAM chain. Their data, weights and assumptions are kept distinct. In both cases the KAM verification uses the actual exported learned Hamiltonian, including every fitted momentum-dependent quartic.

The magnetic feedback closes an additional gap between a conservative learned torus and a damped actuated plant. A declared local field gradient supplies transverse tip force, while the transverse field supplies torque. Together they reproduce the learned low-mode Hamiltonian exactly under the stated sensing and actuation assumptions. The remaining modes are stable forced oscillators, permitting a complete finite-dimensional invariant-torus lift and bounds throughout the specified startup. High-mode contraction does not make the low-mode torus attracting, and the lifted two-torus is not a positive-volume subset of the full phase space. Nor does this finite-dimensional construction imply a continuum KAM theorem. Its strict bounds concern the precisely exported modal model, while independent COMSOL computations test the associated beam implementation.

The nonresonant frequencies and physical amplitude bounds are explicit. The certified frequencies satisfy an all-integer Diophantine inequality and are inherited by the magnetic feedback. The fixed-domain measure calculation adds an explicit result to the density-one family theorem: the same integral-COMSOL Hamiltonian has a KAM fraction exceeding 96.6938% in the symplectic tube of action half-width 10^{-220} around its certified millimetre-amplitude torus. This extremely conservative tube is far below operational and numerical state resolution; it is not the wider initial-state domain used for orbit sampling. The wider-domain experiment reports a finite-time diagnostic and its sampling uncertainty separately. Neither the unclassified complement of a certified KAM family nor resonance alone establishes chaos.

Complex and real implementations are compared at matched function class and parameter count. Their equivalent fits are expected from the algebra of the chosen features. Mechanical priors, additional physical terms and online adaptation are evaluated independently of that representation choice. The noise and parameter experiments show substantial benefits from adding genuinely missing gradient and drag terms, while the freely fitted quadratic control can better absorb reduction error. On the slow nominal S path, a known-physics static inverse outperforms the learned controller. These comparisons locate the demonstrated benefits without implying a universal advantage for CHNNs.

KAM-preserving control and clearance control answer related but different operational questions. The former relies on an identified model and two magnetic ports; the latter bounds every configuration obeying the physical energy budget, including driven dissipative motion. The S task uses the moving clamped base and one transverse field with that work governor. Its axial base work is accounted for, and its independent COMSOL check is a replay of the frozen field. The parameter-drift experiment instead tests causal prediction and includes the explicit work due to changing parameters. Its nonautonomous trajectories do not inherit the stationary KAM certificate.

The dimensional parameters specify an illustrative slender beam. The reported field and gradient budgets are model-level actuator assumptions, not a calibrated coil design. Full-state modal projections and tip measurements are available in the simulations; sensing and observer errors must be included before an implementation with partial measurements can claim the same cancellation. Large rotations, three-dimensional anatomy, flowing fluid, moving walls and contact require corresponding mechanics and work terms. The present results do not constitute a physical catheter, clinical or in-orbit experiment.




Figure 13. A realized S-shaped endpoint path generated by axial base feed and one transverse magnetic input. The controller uses the frozen COMSOL-trained CHNN on the full FE plant. Axial translation work is explicitly included in the energy balance. The matched controls reveal that known-physics static inverse feedforward is more accurate on this particular slow nominal path.

10 Conclusion

The complete magnetic potential, fixed canonical chart and energy–dissipation decoder provide a consistent basis for CHNN learning and nonlinear stability. A verified state-only COMSOL integral experiment supplies nonzero-loss, analytic-error and twist bounds, followed by a millimetre-scale KAM certificate for the same learned function. An explicit symplectic tube and complete-remainder calculation further give a fixed-domain KAM measure bound; its very small certified thickness is reported separately from the millimetre motion amplitude and the broader numerical sampling domain. Physical magnetic force and torque feedback preserves that Hamiltonian despite damping and lifts its invariant torus to the complete exported finite-element modal model. All-phase bounds establish clearance and finite actuator demands for the specified startup. Independent COMSOL and Python computations check the mechanics and additional gradient and drag terms, while noise and causal parameter-adaptation experiments quantify their effects on prediction. A continuum energy governor and an S-shaped endpoint tracking task connect these guarantees to feasible actuation. The accompanying sources, data, learned weights and certificates make the stated mathematical and numerical claims individually reproducible.

Data and code availability

The accompanying reproducibility package contains native COMSOL models, MATLAB construction sources using the COMSOL API, exported matrices and trajectories, Python data-generation and learning code, saved observations and fitted coefficients, verification records and figure sources. Training data and independent COMSOL validation data are labelled by their actual generation process. Numerical values reported as simulations were produced by the accompanying computations.

Declarations

Author identities, affiliations, funding, competing interests and author contributions must be completed by the submitting authors. This work reports mathematical analysis and computer-generated mechanical data. No human, animal or in-orbit experiment was performed.

A Integrator structure and reproducibility checks

For a real smooth Hamiltonian, implicit midpoint is

$$x_{k+1} = x_k + hJ\nabla H\big((x_k + x_{k+1})/2\big). \tag{144}$$

Let $A = JH''(\bar{x})$. Differentiation gives $D\Phi_h = (I - hA/2)^{-1}(I + hA/2)$. Since $A^{\mathsf{T}}J + JA = 0$, this Cayley transform satisfies $D\Phi_h^{\mathsf{T}} J D\Phi_h = J$ whenever the implicit equation defines a differentiable local map. The proof assumes the nonlinear step is solved exactly; residual tolerances add a numerical defect. Explicit RK4 is not symplectic in general. For the separable physical Hamiltonian, the kick–drift–kick Störmer–Verlet map is also symplectic, because each substep is the exact flow of the kinetic or potential Hamiltonian. A general learned momentum-dependent quartic no longer admits that separable split, so the same formula cannot be reused without justification.

Energy error and symplecticity are distinct diagnostics. Finite-time energy plots are evaluated against the specified reference Hamiltonian and accompanied by a step-size check. A small integration error does not certify a Diophantine inequality, nor does a positive finite-time Lyapunov estimate alone establish asymptotic chaos. These facts determine the labels used in the numerical figures.

B The fourth-order central generating-function scheme

Let $f = J\nabla H$, $A = H''$ and define a central generating function

$$S_h(x) = hH(x) + \frac{h^3}{24} f(x)^{\mathsf{T}} A(x) f(x). \tag{145}$$

The map is specified implicitly by

$$x_+ - x_- = J\nabla S_h\big((x_- + x_+)/2\big). \tag{146}$$

Canonical maps generated in central variables are a standard geometric integration construction (Feng et al. 1989; Hairer et al. 2006). Here every derivative is computed from the same learned scalar Hamiltonian. The identity

$$J\nabla(f^{\mathsf{T}} A f) = f''[f,f] - 2(f')^2 f \tag{147}$$

follows by differentiating both occurrences of f, using $f' = JA$ and $J^{\mathsf{T}} = -J$. It gives the displacement implemented in the reproducibility code:

$$g_h = hf + \frac{h^3}{24}\big(f''[f,f] - 2(f')^2 f\big). \tag{148}$$

The Hessian S_h'' is symmetric, so the midpoint Cayley-transform argument in Appendix A proves exact symplecticity of the locally defined map. Since $S_{-h} = -S_h$, interchanging its endpoints proves reversibility.

To verify order, expand an exact orbit about its temporal midpoint x_0. Its endpoint midpoint m and endpoint difference satisfy

$$m = x_0 + \tfrac{1}{8}h^2 f'(x_0) f(x_0) + O(h^4), \tag{149}$$

$$x_+ - x_- = hf(x_0) + \tfrac{1}{24}h^3\big(f''[f,f] + (f')^2 f\big)(x_0) + O(h^5). \tag{150}$$

Substituting $x_0 = m - \tfrac{1}{8}h^2 f'(m) f(m) + O(h^4)$ gives $x_+ - x_- = g_h(m) + O(h^5)$, proving fourth order under the required smoothness and local solvability assumptions.

B.1 An integrator check on the actual learned magnetic energy

We implement (146) for the frozen primary GC17 Hamiltonian, retaining its complete cosine and all mixed and momentum-dependent quartics. Polynomial and trigonometric derivatives through order four are evaluated analytically from the saved energy; they supply both the central displacement and its Newton Jacobian. This test closes all forcing and damping ports. Starting at $(X_1, X_2, Y_1, Y_2) = (0.1, 0.06, 0, 0.02)$, we integrate to $\tau = 10$ and compare against DOP853 with relative and absolute tolerances 3×10^{-14} and 3×10^{-16}. Tightening the reference tolerances from 2×10^{-13} and 2×10^{-15} changes the sampled reference by at most 8.32×10^{-14} per state component. The endpoint errors in Table 13 approach fourth order for Central4 and second order for implicit midpoint.

Table 13. Conservative integration of the same saved GC17 energy. Errors are Euclidean endpoint errors in the balanced dimensionless state; orders compare successive step halvings.

h	Midpoint error	Order	Central4 error	Order
0.08	7.1351×10^{-2}	—	1.8346×10^{-3}	—
0.04	1.9383×10^{-2}	1.8802	1.1784×10^{-4}	3.9606
0.02	4.8966×10^{-3}	1.9849	7.4149×10^{-6}	3.9902
0.01	1.2265×10^{-3}	1.9972	4.6422×10^{-7}	3.9976

The largest implicit-step residual in the infinity norm is 2.00×10^{-15}, with at most three Newton evaluations per step. For each tested step size, differentiating the converged implicit equation gives its one-step tangent map

$D\Phi_h$. The largest measured defect $\|D\Phi_h^{\mathsf{T}} J D\Phi_h - J\|_\infty$ is 3.34×10^{-16} for Central4 and 2.24×10^{-16} for midpoint. An independent fourth-order central-difference evaluation of the solved step map agrees with the implicit tangent to 1.39×10^{-12}; its largest symplectic defect is 2.75×10^{-12}. Thus both methods preserve the symplectic structure to the measured implicit-solve and arithmetic accuracy, while their convergence orders differ. These are numerical checks of the stated algorithms, not a new KAM certificate or a separable Verlet approximation to a momentum-dependent learned Hamiltonian.

C Complex-gradient descent with a strict descent margin

Theorem 3 of Zhang et al. (2022) motivates complex-gradient optimization, but a stationary-point conclusion requires a strict descent margin. The following convention-explicit statement also applies to a smooth CHNN regression objective.

Proposition 14. Complex descent. *Let $\mathcal{L} : \mathbb{C}^P \simeq \mathbb{R}^{2P} \to \mathbb{R}$ be bounded below and have an L-Lipschitz real gradient on every segment traversed by the iterates. For $w = a + ib$, define $G(w) = \nabla_a \mathcal{L} + i\nabla_b \mathcal{L} = 2\partial\mathcal{L}/\partial\bar{w}$. Choose a constant $\rho \in \mathbb{C}$ with $\kappa = \operatorname{Re}\rho - (L/2)|\rho|^2 > 0$, and update $w_{t+1} = w_t - \rho G(w_t)$. Then*

$$\mathcal{L}(w_{t+1}) \le \mathcal{L}(w_t) - \kappa\|G(w_t)\|_2^2, \qquad \lim_{t\to\infty} \|G(w_t)\|_2 = 0,$$

and

$$\min_{0\le t<T} \|G(w_t)\|_2^2 \le \frac{\mathcal{L}(w_0) - \inf \mathcal{L}}{\kappa T}.$$

Proof. Under realification, multiplication by $\rho = u + iv$ is $uI + vJ_c$, with $J_c^\top = -J_c$ and $J_c^\top J_c = I$. Hence the update has inner product $-u\|G\|^2$ with the real gradient and squared norm $|\rho|^2\|G\|^2$. The real descent lemma gives the first inequality. Summing it and using the lower bound for $\mathcal{L}$ gives $\kappa \sum_{t\ge 0} \|G(w_t)\|^2 \le \mathcal{L}(w_0) - \inf \mathcal{L}$. Square summability proves convergence of the gradient norm and the minimum bound. The result asserts convergence to stationarity in gradient norm, not convergence to a global minimum or to a particular parameter vector.

For a real step this condition is $0 < \rho < 2/L$ under the stated convention. The case $\rho = 0$, allowed by a non-strict printed step-size interval, cannot imply gradient convergence. Nonsmooth complex activations also need separate treatment; a smooth polynomial CHNN satisfies the differentiability requirements, with a Lipschitz gradient bound on any bounded iterate region.

D Explicit finite-amplitude KAM measure estimates

D.1 An explicit symplectic tube at the certified physical amplitude

Let K_∞ be the exact torus supplied by the integral-COMSOL certificate, with its phase normalization fixed by that construction. Write $t = 2\pi\theta$, $k(t) = K_\infty(t/(2\pi))$, and $\omega = 2\pi\varpi$. Thus $D_\omega k = X_{h_\eta}(k)$, and the already verified Diophantine inequality becomes

$$|\omega \cdot \ell| \ge \gamma_0 |\ell|_1^{-3}, \qquad \gamma_0 = 2\pi\frac{9}{1750}, \quad 0 \ne \ell \in \mathbb{Z}^2. \tag{151}$$

The exponent 3 here concerns this fixed central torus. The family measure estimate below uses the separate exponent $\tau = 2$.

For each coordinate plane, define

$$\begin{aligned} j_a(t) &= \tfrac{1}{2}(k_{X_a}^2 + k_{Y_a}^2), \\ F_a(t) &= t_a + \frac{\log(1+u_{a,+}) - \log(1+u_{a,-})}{2i}, \\ u_{a,\pm}(t) &= 10(k_{X_a} \mp i k_{Y_a}) e^{\mp i t_a} - 1. \end{aligned} \tag{152}$$

The logarithms use the branches at 1. On the real torus, F_a is the phase of $k_{X_a} - ik_{Y_a}$ and $j_a > 0$. Set $B(t) = DF(t)^{-\mathsf{T}}$ and define

$$\begin{aligned} J(t,I) &= j(t) + B(t)I, \\ \Psi_{X_a}(t,I) &= \sqrt{2J_a(t,I)}\cos F_a(t), \\ \Psi_{Y_a}(t,I) &= -\sqrt{2J_a(t,I)}\sin F_a(t). \end{aligned} \tag{153}$$

Equivalently, each pair (k_{X_a}, k_{Y_a}) is multiplied by $\sqrt{1 + (BI)_a/j_a}$; this expression is convenient for interval evaluation and fixes the square-root branches.

This is an exact symplectic chart. Indeed, polar coordinates have canonical one-form $J \cdot dF$, and

$$\Psi^*(J \cdot dF) = j(t) \cdot DF(t)dt + I \cdot dt.$$

The first term is closed because k is Lagrangian. Taking the exterior derivative gives $\sum_a dI_a \wedge dt_a$. This argument requires closedness, not exactness, of the first term. Since DF is uniformly close to the identity, its real lift is a global diffeomorphism of $\mathbb{T}^2$; positive J then makes Ψ injective on its real tube. Moreover $\Psi(t,0) = k(t)$.

The source certificate and outward-rounded scalar evaluation give the following convenient, deliberately

rounded bounds:

$$\begin{gathered}\|k-k_0\|_{1/16}<7\,10^{-6},\\ k_0=0.1(\cos t_1,\cos t_2,-\sin t_1,-\sin t_2),\\ \|u_\pm\|_{1/16}<1/5000,\qquad \|j-0.005\mathbf{1}\|_{1/16}<3\,10^{-6},\\ \|F-t\|_{1/16}<0.000201,\\ \max\{\|DF-\mathrm{Id}\|_\infty,\|DF-\mathrm{Id}\|_1\}_{1/32}<0.013,\\ \|B\|_{1/32,\infty}<1.014.\end{gathered}\tag{154}$$

Here a subscript is the complex angular strip width in radians; vector norms are maximum norms and matrix norms are induced norms. The first bound includes the a posteriori correction to the numerical embedding. For example, Cauchy's estimate bounds each entry of $D(F-t)$ by $0.000201/(1/32)$, so both row and column sums are below 0.013. For $R_0=10^{-3}$, $|I|_\infty<R_0$ therefore implies

$$\begin{gathered}|(BI)_a/j_a|<\frac{1.014\,10^{-3}}{0.005-3\,10^{-6}}<\tfrac14,\\ \|\Psi\|_{1/32,R_0}<0.12.\end{gathered}$$

All logarithms, square roots and inverses above are thus holomorphic on the declared domain.

Write $h_\eta=h_2+h_{\mathrm{nl}}$. The full cosine and the exact exported quartic coefficients give

$$\|h_{\mathrm{nl}}\circ\Psi\|_{1/32,R_0}<10^{-6},\qquad \|h_\eta\circ\Psi\|_{1/32,R_0}<0.05.\tag{155}$$

The second estimate uses the identity $h_2\circ\Psi=\nu\cdot(j+BI)$, whose norm is less than $7.153(0.005003+0.001014)<0.044$. It does not use a loose Cartesian estimate for the quadratic energy. Invariance and symplecticity give the exact expansion

$$h_\eta\circ\Psi=e+\omega\cdot I+\tfrac12 I^{\mathsf T}A(t)I+O(|I|^3).\tag{156}$$

Only $h_{\mathrm{nl}}\circ\Psi$ contributes to A: Cauchy bounds on its diagonal and off-diagonal second derivatives give $\|A\|_{1/32,\infty}\le 3$.

The averaged matrix $\overline{A}$ is nonsingular. To check the normalization, the tangent frame with radian angles is the certified cycle-angle frame divided by 2π; a symplectically dual normal frame is multiplied by 2π. Replacing that normal frame by $\partial_I\Psi(t,0)$ adds a symmetric tangential shear. Its contribution to the torsion is a directional derivative with zero angular average. Consequently

$$\overline{A}=(2\pi)^2\langle T_\infty\rangle,\qquad \|\overline{A}^{-1}\|_\infty\le\frac{2\,10^5}{(2\pi)^2}<5100.\tag{157}$$

The final-torus inverse-torsion bound is the one obtained by the uniform a posteriori iteration, rather than the inverse of an unverified approximate matrix.

D.2 A complete analytic remainder on a fixed tube

Let S be the symmetric, zero-average solution of $D_\omega S=A-\overline{A}$. Its Fourier coefficients for $\ell\neq0$ are $S_\ell=A_\ell/(i\omega\cdot\ell)$. Equation (151) and the angular strip loss $\delta=1/64$ imply

$$\begin{aligned}\|S\|_{1/64,\infty}&\le\frac{3}{\gamma_0}4\sum_{m\ge1}m^4e^{-m/64}\\ &\le\frac{288e^{1/64}64^5}{\gamma_0}<10^{13}=:T.\end{aligned}\tag{158}$$

There are $4m$ integer vectors of one-norm m. The second inequality uses $\sum_{m\ge1}m^4e^{-\delta m}\le e^\delta\Gamma(5)\delta^{-5}$, obtained by integrating on each interval $[m,m+1]$.

Use the exact time-one flow Φ_χ of $\chi(t,I)=\frac12 I^{\mathsf T}S(t)I$, not a truncated Lie series. Fix $R_1=10^{-17}$. On the intermediate strip $3/256$, Cauchy's estimate from the strip $1/64$ gives $\|\partial_{t_a}S\|_\infty\le256T$. As long as $|I|_\infty<2R_1$, the flow satisfies

$$\begin{aligned}|\dot t|_\infty&\le2TR_1=2\,10^{-4}<1/256,\\ |\dot I|_\infty&\le1024TR_1^2=0.1024R_1<R_1.\end{aligned}$$

These strict bounds close the continuation argument from the initial strip $1/128$ and action polydisc R_1: throughout the unit time interval, the angle stays inside $3/256$ and the action inside $2R_1<R_0$. The flow is holomorphic on the initial domain and symplectic on its real part.

With the pullback convention $L_\chi H=\{H,\chi\}$, $\{\omega\cdot I,\chi\}=-D_\omega\chi$. Hence the exact transformed Hamiltonian has the form

$$h_\eta\circ\Psi\circ\Phi_\chi=e+\omega\cdot I+\tfrac12 I^{\mathsf T}\overline{A}I+\mathcal{R}_3,\tag{159}$$

where $\mathcal{R}_3$ starts at total action degree three. The complete left-hand side remains bounded by 0.05 on the strip $1/128$ and radius R_1. Cauchy's coefficient estimate in the two action variables therefore yields, for $0<r\le R_1/2$,

$$\begin{aligned}\|\mathcal{R}_3\|_{1/128,r}&\le0.05\sum_{m\ge3}(m+1)(r/R_1)^m\\ &\le\frac{0.5}{R_1^3}r^3=5\,10^{50}r^3.\end{aligned}\tag{160}$$

This bound includes the full magnetic cosine, all fitted quartics, the exact chart and the exact flow; no Taylor truncation is treated as the Hamiltonian to be certified.

D.3 A quantitative measure bound with all resonances included

The action-domain dependence of KAM measure estimates is central in Biasco and Chierchia (2018). We use the fully quantified formulation of Chierchia and Koudjinan (2021, Theorems 1 and 3, Eqs. (4), (9), (13)–(14)). Consider a Hamiltonian $K(I)+\mathcal{R}(I,t)$ on $B_R(I_c)\times\mathbb{T}^2_s$, with $K = e+\omega\cdot I+\frac{1}{2}I^{\mathsf{T}}AI$, real symmetric invertible A, and $\|\mathcal{R}\|_{R,s}\le E$. Let $M\ge\|A\|_\infty$, $L\ge\|A^{-1}\|_\infty$, $\vartheta = ML$, and $\epsilon = ME/\alpha^2$. For $0<\rho<r\le R$, $0<s_*<s\le 1$, and $\tau>1$, the sufficient conditions are

$$\alpha\le c_0\rho/L,\qquad \epsilon\le\epsilon_* := \frac{(s-s_*)^{7(\tau+1)+10}}{c_*\vartheta^6}. \tag{161}$$

Here c_0, c_* are exactly the constants in their Appendix A, Remark A.4, Eq. (A.38), evaluated for $d=2$ and the chosen τ. Upper bounds on M, L, E, c_*, and a lower bound on c_0, are used in the appropriate directions. The normalization is $H = K+\varepsilon P$ with $\varepsilon\|P\|\le E$.

Take the centre set in that theorem to be the singleton $\{I_c\}$. The real domain is precisely $D = B_r(I_c)$, the inner domain is $B_{r-\rho}(I_c)$, and the boundary layer in Theorem 3 is $B_{r+\rho}(I_c)\setminus B_{r-\rho}(I_c)$, of area $16r\rho$. Let $\mathcal{K}\subset D\times\mathbb{T}^2$ be the certified KAM set. The Lipschitz estimate in their Eq. (9) is at most $1/8$, so the factor multiplying the bad action measure in Eq. (14) is bounded by $(25/16)(2\pi)^2$.

For completeness the remaining estimate includes every integer resonance. For $m = |\ell|_1$, the strip

$$|\ell\cdot(\omega+AI)|<\alpha/m^\tau$$

has intersection with D of area at most $4r\alpha/(m^\tau\|A\ell\|_\infty)$. Since $\|A\ell\|_\infty\ge m/(2L)$ and there are $4m$ vectors on the shell, summing over all shells gives

$$\mathrm{meas}(R_\alpha)\le 32r\alpha L\zeta(\tau).$$

We deliberately retain both signs of each resonance in this upper bound. Dividing Theorem 3's bound by $\mathrm{meas}(D\times\mathbb{T}^2) = 4r^2(2\pi)^2$ proves

$$\frac{\mathrm{meas}(\mathcal{K})}{4r^2(2\pi)^2}\ge 1-\frac{25}{16}\left(\frac{4\rho}{r}+\frac{8\alpha L\zeta(\tau)}{r}\right). \tag{162}$$

Thus finite Fourier testing is not substituted for the required all-integer Diophantine set.

Apply this result to (159), with

$$\begin{gathered} I_c = 0,\quad r = w,\quad R = 2w,\\ s = 1/128,\quad s_* = 1/256,\quad \tau = 2,\\ M = 3,\quad L = 5100,\quad \vartheta = 15300,\\ E = 4\,10^{51}w^3,\\ \rho = w/500,\qquad \alpha = w/(1000L). \end{gathered} \tag{163}$$

Any specified positive $w\le R_1/4$ satisfying

$$4\,10^{57}ML^2w\le\frac{256^{-31}}{c_*\vartheta^6} \tag{164}$$

passes the smallness condition. The first condition in (161) follows already from $c_0>1$. For every such fixed w, define the physical canonical tube

$$U_w = (\Psi\circ\Phi_\chi)(\mathbb{T}^2\times B_w(0)). \tag{165}$$

It is an injective symplectic image of a declared domain, so its Liouville volume is $4w^2(2\pi)^2$. Equations (162) and (163) give the explicit bound

$$\begin{aligned}\frac{\mu_L(U_w\cap\mathcal{K}_{h_\eta})}{\mu_L(U_w)}&\ge 1-\frac{25}{16}\left(\frac{4}{500}+\frac{8}{1000}\frac{\pi^2}{6}\right)\\ &> 0.96693>0.965.\end{aligned} \tag{166}$$

The numerical certificate takes the exact value $w = 10^{-220}$. It encloses ϵ_* above $7.6577\,10^{-155}$ and the smallness ratio ϵ/ϵ_* below 0.40759, verifying (164) with outward rounding.

The transverse size of this particular tube is also bounded. For any real point of U_w, write $(t',I') = \Phi_\chi(t,I)$. The same flow estimate on the smaller action domain gives $|I'|_\infty<2w$. Comparison with the central point $k(t')$, rather than with a fixed phase label before the flow, eliminates the irrelevant phase shift. For real $q>-1$, $|\sqrt{1+q}-1| = |q|/(1+\sqrt{1+q})\le|q|$; hence

$$\begin{aligned}\|\Psi(t',I')-k(t')\|_\infty&\le\frac{0.100007\,(1.014)\,2w}{0.005-3\,10^{-6}}\\ &<41w = 4.1\,10^{-219}.\end{aligned} \tag{167}$$

This is a bound in the dimensionless Cartesian canonical variables; the SI displacement bound follows by applying the fixed modal reconstruction matrix. The millimetre value describes the amplitude of the central motion, not the thickness in (167).

This is a measure statement about the conservative learned Hamiltonian on a four-dimensional symplectic tube centered on its certified approximately 1.9 mm motion. The constant dimensional scaling multiplies numerator and denominator

by the same factor. The smallness of the resulting tube must be reported: its width does not assert a macroscopic operating range. In this example the available embedding-error guarantee, approximately $2.09\,10^{-41}$, is much larger than the tube width. This is an upper bound on the error, not a claim that the actual error equals that bound. The theorem defines the tube using exact K_∞, but the available numerical guarantee does not resolve membership at this width. The fraction is neither a finite-time trajectory success rate nor a 128-dimensional Lebesgue fraction for the full damped closed loop. Its lifted interpretation uses the low-mode parameter measure specified in the main text.

References

Abbott JJ, Diller E and Petruska AJ (2020) Magnetic methods in robotics. *Annual Review of Control, Robotics, and Autonomous Systems* 3: 57–90. doi: 10.1146/annurev-control-081219-082713.

Antman SS (2005) *Nonlinear Problems of Elasticity*. 2nd ed. Springer. doi: 10.1007/0-387-27649-1.

Biasco L and Chierchia L (2018) Explicit estimates on the measure of primary KAM tori. *Annali di Matematica Pura ed Applicata* 197(1): 261–281. doi: 10.1007/s10231-017-0678-8. https://arxiv.org/abs/1612.01903.

Bounemoura A (2016) Non-degenerate Liouville tori are KAM stable. *Advances in Mathematics* 292: 42–51. doi: 10.1016/j.aim.2016.01.012. https://arxiv.org/abs/1412.0509.

Bounemoura A (2020) Positive measure of KAM tori for finitely differentiable Hamiltonians. *Journal de l'École polytechnique – Mathématiques* 7: 1113–1132. doi: 10.5802/jep.137.

Chen Y, Matsubara T and Yaguchi T (2022) KAM theory meets statistical learning theory: Hamiltonian neural networks with non-zero training loss. *Proceedings of the AAAI Conference on Artificial Intelligence* 36(6): 6322–6332. doi: 10.1609/aaai.v36i6.20582.

Chierchia L and Koudjinan CE (2021) V. I. Arnold's "Global" KAM theorem and geometric measure estimates. *Regular and Chaotic Dynamics* 26(1): 61–88. doi: 10.1134/S1560354721010044. The explicit constants and equation numbers used here refer to https://arxiv.org/abs/2010.13243v1.

Das S, Saiki Y, Sander E and Yorke JA (2017) Quantitative quasiperiodicity. *Nonlinearity* 30(11): 4111–4140. doi: 10.1088/1361-6544/aa84c2.

Desai S, Mattheakis M, Sondak D, Protopapas P and Roberts S (2021) Port-Hamiltonian neural networks for learning explicit time-dependent dynamical systems. *Physical Review E* 104: 034312. doi: 10.1103/PhysRevE.104.034312.

Duignan N and Meiss JD (2023) Distinguishing between regular and chaotic orbits of flows by the weighted Birkhoff average. *Physica D: Nonlinear Phenomena* 449: 133749. doi: 10.1016/j.physd.2023.133749.

Feng K, Wu HM, Qin MZ and Wang DL (1989) Construction of canonical difference schemes for Hamiltonian formalism via generating functions. *Journal of Computational Mathematics* 7(1): 71–96.

Greydanus S, Dzamba M and Yosinski J (2019) Hamiltonian neural networks. In: *Advances in Neural Information Processing Systems*, vol. 32. https://arxiv.org/abs/1906.01563.

Hairer E, Lubich C and Wanner G (2006) *Geometric Numerical Integration: Structure-Preserving Algorithms for Ordinary Differential Equations*. 2nd ed. Springer. doi: 10.1007/3-540-30666-8.

Haro À and Luque A (2019) A-posteriori KAM theory with optimal estimates for partially integrable systems. *Journal of Differential Equations* 266(2–3): 1605–1674. doi: 10.1016/j.jde.2018.08.003. Theorem and table numbering used in the certification follows the archived preprint https://arxiv.org/abs/1711.05515v1.

Hornik K (1991) Approximation capabilities of multilayer feedforward networks. *Neural Networks* 4(2): 251–257. doi: 10.1016/0893-6080(91)90009-T.

Kim Y, Parada GA, Liu S and Zhao X (2019) Ferromagnetic soft continuum robots. *Science Robotics* 4(33): eaax7329. doi: 10.1126/scirobotics.aax7329.

NASA (n.d.) Risk of spaceflight associated neuro-ocular syndrome (SANS). NASA Human Research Program risk page (accessed 2 October 2026).

Pöschel J (2001) A lecture on the classical KAM theorem. In: *Proceedings of Symposia in Pure Mathematics*, vol. 69, pp. 707–732. https://arxiv.org/abs/0908.2234.

Simo JC (1985) A finite strain beam formulation. The three-dimensional dynamic problem. Part I. *Computer Methods in Applied Mechanics and Engineering* 49(1): 55–70. doi: 10.1016/0045-7825(85)90050-7.

Trabelsi C, Bilaniuk O, Zhang Y et al. (2018) Deep complex networks. In: *International Conference on Learning Representations*. https://arxiv.org/abs/1705.09792.

Zhang SQ, Gao W and Zhou ZH (2022) Towards understanding theoretical advantages of complex-reaction networks. *Neural Networks* 151: 80–93. doi: 10.1016/j.neunet.2022.03.024. https://arxiv.org/abs/2108.06711.

Zhong YD, Dey B and Chakraborty A (2020) Dissipative SymODEN: Encoding Hamiltonian dynamics with dissipation and control into deep learning. In: *ICLR Workshop on Integration of Deep Neural Models and Differential Equations*. https://arxiv.org/abs/2002.08860.