Supplementary material: Full-phase complex Hamiltonian learning with conservative certification and dissipative magnetic feedback

The International Journal of Robotics Research
XX(X):1–59
©The Author(s) 0000
Reprints and permission:
sagepub.co.uk/journalsPermissions.nav
DOI: 10.1177/ToBeAssigned
www.sagepub.com/
SAGE

Anonymous authors

The proofs use the full four-coordinate learned energy and the same prescribed finite-Gauss mechanical graph as the article. The observation certificates distinguish numerical-reference fidelity from physical measurement error. The conservative-family theorem is instantiated by its completed numerical application below. The prospective independent-anchor and statistical-risk results retain their additional assumptions. The port-power and sampled physical-energy statements use separate nonconservative arguments. Their numerical applications and the KAM certificate retain the original θ_0. The jet-regularized outputs have separate parameter identities; their finite-record comparisons and the new complex output's analytic domain do not transfer these earlier certificates.

S1 Local and accumulated error of the conservative midpoint step

This proof supplies explicit constants for the accuracy statement in the article. Let $J_c = \left(\begin{smallmatrix} 0 & I_2 \\ -I_2 & 0 \end{smallmatrix}\right)$ and let $f = J_c \nabla \widehat{H}$ be C^2 on an open domain. Assume a common convex neighborhood contains all states and segments used below. Let M, L, B_2 bound $f, Df, D^2 f$, respectively, in a fixed vector norm and its induced multilinear norms. Exact trajectories and the unique local midpoint branches must remain in this domain through time T. These are domain hypotheses, not conclusions from a formal order calculation.

For an exact solution $x(t)$,

$$x'' = Df(x)f(x), \qquad x''' = D^2 f(x)[f(x), f(x)] + Df(x)Df(x)f(x).$$

Consequently $\|x''\| \le LM$ and $\|x'''\| \le M_3 := B_2 M^2 + L^2 M$. For $x_0 = x(0)$ and $x_h = x(h)$, the composite defect of the exact endpoint in the midpoint equation is

$$d_h = x_h - x_0 - hf((x_0 + x_h)/2).$$

The one-panel midpoint quadrature remainder for $\int_0^h f(x(t))\,dt$ is bounded by $M_3 h^3/24$. Moreover, linear interpolation of a twice differentiable trajectory gives

$$\|x(h/2) - (x_0 + x_h)/2\| \le LMh^2/8.$$

Applying the Lipschitz constant L to this chord-midpoint discrepancy yields

$$\|d_h\| \le \left(\frac{M_3}{24} + \frac{L^2 M}{8}\right) h^3 = \left(\frac{B_2 M^2}{24} + \frac{L^2 M}{6}\right) h^3 = C_d h^3.$$

Both estimates follow by the integral Taylor remainder, so bounded continuous second derivatives of f suffice.

Let $y = \Phi_h(x_0)$ be the exact solution of the implicit midpoint equation. Subtraction from the defect equation gives

$$\|y - x_h\| \le (hL/2)\,\|y - x_h\| + \|d_h\|\,.$$

For $hL/2 \le \kappa < 1$, the one-step bound is therefore $\|y - x_h\| \le C_\ell h^3$ with $C_\ell = C_d/(1-\kappa)$.

Two initial states and their midpoint endpoints similarly satisfy

$$\|\Phi_h(x) - \Phi_h(y)\| \le \frac{1 + hL/2}{1 - hL/2}\,\|x - y\| \le e^{\Lambda h}\,\|x - y\|\,, \qquad \Lambda = L/(1-\kappa).$$

The last inequality follows by integrating $d\log[(1+a)/(1-a)]/da = 2/(1-a^2)$ and using $0 \le a \le \kappa$, or from $\log[(1+a)/(1-a)] \le 2a/(1-a)$. Writing $e_n = \|x_n - x(nh)\|$ gives $e_{n+1} \le e^{\Lambda h} e_n + C_\ell h^3$. For $e_0 = 0$,

$$e_n \le C_\ell h^3 \frac{e^{\Lambda n h} - 1}{e^{\Lambda h} - 1} \le C_\ell h^2 \frac{e^{\Lambda T} - 1}{\Lambda}.$$

Continuous limits cover $\Lambda = 0$. A nonzero initial error contributes the additional term $e^{\Lambda T} e_0$.

If an implementation returns $\widetilde{y}$ with algebraic residual $r = \widetilde{y} - x - hf((x+\widetilde{y})/2)$, contraction gives

$$\|\widetilde{y} - \Phi_h(x)\| \le \frac{\|r\|}{1 - hL/2}.$$

These errors enter the same accumulated-error recursion. Per-step residuals of order h^3 preserve the stated global second-order rate under the same domain bounds. They do not imply that the computed map satisfies the exact symplectic Jacobian identity.

S2 Strict finite-output inverses in the observed canonical chart

The following certificate replaces numerical rank by a strict inverse for the selected finite-output designs. It uses the prescribed finite Gauss-eight metric, with all its mechanical buffers shared exactly by the full-phase GC. At each selected moving node, interpret the stored binary64 $q_{\mathrm{obs}}, v_{\mathrm{obs}}$ as exact input numbers and define

$$p_{\mathrm{obs}} = G(q_{\mathrm{obs}})v_{\mathrm{obs}}, \qquad x_{\mathrm{obs}} = (q_{\mathrm{obs}}, p_{\mathrm{obs}}).$$

The metric and this momentum are enclosed by direct interval evaluation of the finite graph, rather than by a midpoint replacement. These points need not be the exact states of the native initial-value problem. For the specified reference with known kinetic energy and configuration-only unknown correction, they nevertheless satisfy

$$H_{*,p}(x_{\mathrm{obs}}) = v_{\mathrm{obs}}, \qquad (H_\theta - H_*)_p(x_{\mathrm{obs}}) = N_{\theta,p}(x_{\mathrm{obs}}).$$

Thus the momentum-error label at these exact constructed points is structurally zero. No additional equality between p_{obs} and true native momentum is needed to test the function $N_{\theta,p}$ there. Noise or trajectory-error budgets are required if a subsequent claim transfers the result to true physical states or dynamics; this certificate does not declare those budgets zero.

Let $\chi_\alpha(x) = \prod_{j=1}^{4}(x_j/s_j)^{\alpha_j}$, where the s_j are the exact four GC scale buffers. Physical coordinate derivatives retain the factor $1/s_j$. For total even degrees two and four, use the selected eight rest configuration-gradient rows on the configuration-only columns and the selected 37 moving momentum-gradient rows on the other columns. For degrees two, four and six the corresponding dimensions are 15 and 114. A column permutation places each full selected design in the form

$$A_{45} = \mathrm{diag}(A_{q,8}, A_{p,37}), \qquad A_{129} = \mathrm{diag}(A_{q,15}, A_{p,114}).$$

The cross blocks vanish by polynomial differentiation: rest configuration derivatives leave all momentum factors intact, and momentum derivatives annihilate configuration-only monomials. There is no additional row weighting or column equilibration in these strict matrices.

Lemma S1. Dyadic approximate inverse certificate. *Suppose an interval matrix encloses the exact square design A, and let R be a specified exact dyadic matrix. Define $E = I - RA$. If*

$$\|E\|_\infty \le \eta_\infty < 1,$$

then A is nonsingular and

$$\|A^{-1}\|_\infty \le \frac{\|R\|_\infty}{1-\eta_\infty}.$$

If also $\|E\|_1 \le \eta_1 < 1$ and $\eta_2 \ge \sqrt{\eta_1\eta_\infty}$ satisfies $\eta_2 < 1$, then

$$\|A^{-1}\|_1 \le \frac{\|R\|_1}{1-\eta_1},$$
$$\|A^{-1}\|_2 \le \sqrt{\frac{\|R\|_1\|R\|_\infty}{(1-\eta_1)(1-\eta_\infty)}},$$
$$\|A^{-1}\|_F \le \frac{\|R\|_F}{1-\eta_2}.$$

Each square-root bound may be enlarged by directed rational rounding.

Proof. The Neumann series gives $(I-E)^{-1}$ and its induced-norm bounds. Since $RA = I - E$ is nonsingular and the matrices are square, A is nonsingular and $A^{-1} = (I-E)^{-1}R$. Use $\|E\|_2 \le \sqrt{\|E\|_1\|E\|_\infty}$, $\|BC\|_F \le \|B\|_2\|C\|_F$ and $\|A^{-1}\|_2 \le \sqrt{\|A^{-1}\|_1\|A^{-1}\|_\infty}$. The alternative bounds $\|A^{-1}\|_F \le \sqrt{n}\|A^{-1}\|_\infty$ and $\|A^{-1}\|_F \le \sqrt{n}\|A^{-1}\|_1$ may further tighten the result.

The computation uses 512-bit outward interval arithmetic for the direct metric, monomials and complete matrix product. An ordinary midpoint inverse merely proposes R; each entry is then rounded onto the exact 2^{-96} grid. The proof uses only the full interval enclosure of $I - RA$, not the accuracy of that floating inversion. All selected input words, row identities, basis exponents, scales, matrix enclosures and dyadic inverse entries are retained.

Block	η_∞ upper	$\|A^{-1}\|_\infty$ upper	$\|A^{-1}\|_F$ upper
$A_{q,8}$	$5.616\,10^{-15}$	0.207182	0.182883
$A_{p,37}$	$1.737\,10^{-13}$	1.013895	0.477587
$A_{q,15}$	$5.446\,10^{-14}$	1.781184	1.044917
$A_{p,114}$	$2.594\,10^{-9}$	514.632787	113.561027

Consequently the selected designs have exact ranks 45 and 129. For a block diagonal inverse, the infinity and spectral norms are the maximum of the block norms, and squared Frobenius norms add. Row or column permutations do not change these norms. The resulting combined infinity bounds are less than 1.013895 and 514.632787 respectively.

For an exact coefficient identity $z = Aa + t - \xi$, the inverse now supplies the nontrivial finite-output step

$$a = A^{-1}z + A^{-1}(\xi - t).$$

Actual signed residuals, pointwise tail bounds and label/evaluation allowances must still be inserted before concluding a learning-error bound. The zero reference label for N_p at the constructed points does not assert that the learned N_p, its tail, or its evaluation error is zero. The q-gradient rows retain their own nonzero reference label-error budget. Neural analytic remainders outside this finite representative, the appropriate real and complex domains, and any KAM acceptance remain separate certificates. This inverse does not turn dependent moving nodes into iid samples, certify native solver accuracy, or establish identification of an unknown physical plant.

S3 Finite-output observation acceptance for a full-phase Hamiltonian

Let the same known kinetic graph be used in

$$H_*(q,p) = T_G(q,p) + V_4(q) + U(q), \qquad H_\theta(q,p) = T_G(q,p) + V_4(q) + N_\theta(q,p), \quad T_G = \tfrac{1}{2}p^{\mathsf{T}}G(q)^{-1}p.$$

Fix the physical canonical coordinates $x = (q_1, q_2, p_1, p_2)$ and their positive stored scales s_j. For $D = 4$ or 6, use all monomials

$$\chi_\beta(x) = \prod_{j=1}^{4} (x_j/s_j)^{\beta_j}, \qquad |\beta| = 2, 4, \ldots, D.$$

There are $n = 45$ or 129 columns. This is a finite representative of an output, not a restriction of the neural-network hypothesis class. For each admitted output choose an explicitly identified representative and define its actual remainder by

$$P_\theta = \chi^{\mathsf{T}} a_\theta, \qquad \rho_\theta = N_\theta - P_\theta, \qquad E_\theta = N_\theta - U = \chi^{\mathsf{T}} a_\theta + \rho_\theta - U. \tag{S1}$$

No reference coefficient is used as a network training label or as an assumed value of a_θ.

Exact observation anchors and row units. At rest anchors $(Q_i, 0)$, let sealed potential-gradient labels satisfy

$$Y_i = \nabla(V_4 + U)(Q_i) + \xi_i.$$

The label-fidelity allowance must include whatever initial-rest, finite-difference, actual-clock, observation and numerical errors occur in its construction. It is not replaced by a solver tolerance. For moving records, define the exact observed-state chart

$$z_l = (\bar{q}_l, \bar{p}_l), \qquad \bar{p}_l = G(\bar{q}_l)\bar{v}_l, \tag{S2}$$

where $\bar{q}_l, \bar{v}_l$ are the exact represented observation numbers and G is the prescribed exact graph. Since $H_{*,p}(z_l) = \bar{v}_l$, the reference momentum-gradient correction is zero at these anchors, irrespective of whether they are true IVP states. This is structural information from the shared kinetic model, not an observation of native momentum or force.

Let $\mathcal{L}$ consist of chosen q-derivative rows at rest and chosen p-derivative rows at moving anchors. Form

$$r_{q,i} = N_{\theta,q}(Q_i, 0) + V_{4,q}(Q_i) - Y_i, \qquad r_{p,l} = N_{\theta,p}(z_l). \tag{S3}$$

Only the selected components of these vector expressions are retained. The V_4 derivative is that of the actual common scalar mechanical potential; a rounded surrogate stiffness matrix needs a separate error allowance. No reference ∇U is used to form the signed residual. With ξ containing the selected rest errors and zero moving entries,

$$r = \mathcal{L}E_\theta - \xi. \tag{S4}$$

Interval evaluation may enclose this exact r instead of returning a single number. Its numerical width is distinct from physical label error.

Physical derivative rows contain $1/s_j$. If different row units or weights are desired, declare a positive diagonal matrix W and set $\widetilde{\mathcal{L}} = W\mathcal{L}$, $\widetilde{A} = WA$ and $\widetilde{r} = Wr$, where $A_{ij} = \mathcal{L}_i\chi_j$. The same W multiplies noise and point remainders. A normalized-coordinate derivative uses row weight s_j. Counts of dependent curve nodes are not weights justified by iid sampling. The present square inverse construction uses physical rows, $W = I$, and no extra column scaling.

After a recorded column permutation, the exact design is

$$A = A_q \oplus A_p, \qquad (n_q, n_p) = (8, 37) \text{ or } (15, 114).$$

Rest configuration derivatives leave every momentum factor zero, and momentum derivatives annihilate all configuration-only monomials. This structural statement uses the literal rest anchor $p = 0$; an uncertain nonzero rest momentum cannot silently be inserted while retaining the same zero blocks. Column permutations must also be applied to a_θ, every output derivative row and every inverse artifact.

Observation-chart and input errors. A numerical $G\bar{v}$ is only an approximation to (S2). Enclose the exact chart jointly in the design A and the model residual r. If instead a certificate is intended at true physical anchors, a common state-error

contract is needed. For example, if $|q^* - \bar{q}| \le d_q$ and $|v^* - \bar{v}| \le d_v$, then on a containing real segment

$$|p_i^* - \bar{p}_i| \le \sum_j G_{ij}^{\mathrm{abs}} d_{v,j} + \sum_{j,k} G_{ij,k}^{(1),\mathrm{abs}} |\bar{v}_j| d_{q,k}.$$

Add $\sum_j \varepsilon_{G,ij} |\bar{v}_j|$ if the nominal chart uses an approximate metric rather than the exact graph. Derivative observations shifted between two anchors obey the componentwise allowance

$$|\partial_j E_\theta(x) - \partial_j E_\theta(\bar{x})| \le \sum_k \sup_{[x,\bar{x}]} |\partial_{jk} E_\theta| \, d_{x,k}.$$

For this transport, sound candidate-specific bounds on $|\partial_{jk} N_\theta| + |\partial_{jk} U|$ suffice; the desired small learning error is not assumed to prove itself. All segments and evaluation boxes must lie in their certified domains. State uncertainty may instead be enclosed directly when evaluating A and r. These are alternative bookkeeping conventions: a state mismatch must be covered, but need not be charged twice. In particular, the exact observed-chart inverse does not alone certify true physical-state error.

Lemma S2. Strict design inverse and signed finite-output identity. *Suppose an interval matrix encloses the actual $\widetilde{A}$ and a fixed exact dyadic matrix R satisfies*

$$\sup_{\widetilde{A}} \|I - R\widetilde{A}\|_\infty \le \eta < 1.$$

For each actual matrix define $J = (R\widetilde{A})^{-1} R$ and $\kappa = \eta/(1-\eta)$. Then $J\widetilde{A} = I$ and $\|(R\widetilde{A})^{-1} - I\|_\infty \le \kappa$. Let

$$t_N = \widetilde{\mathcal{L}}\rho_\theta, \qquad t_U = \widetilde{\mathcal{L}}U, \qquad F_\alpha(x) = \partial^\alpha \chi(x)^{\mathsf{T}}.$$

For every multi-index α for which the terms exist,

$$\begin{aligned} \partial^\alpha E_\theta(x) = {} & F_\alpha(x) J\widetilde{r} + F_\alpha(x) JW\xi \\ & + \big[\partial^\alpha \rho_\theta(x) - F_\alpha(x) J t_N\big] + \big[F_\alpha(x) J t_U - \partial^\alpha U(x)\big]. \end{aligned} \tag{S5}$$

Proof. The Neumann series gives the inverse and the stated bound. Applying the observation operator to (S1), then using (S4), gives $\widetilde{A}a_\theta = \widetilde{r} + W\xi - t_N + t_U$. Apply J, differentiate the decomposition and substitute.

This identity keeps every reference and network remainder term. It is often preferable to enclose their sum directly as

$$C_{\alpha,\theta}(x) = \partial^\alpha(\rho_\theta - U)(x) - F_\alpha(x) J\widetilde{\mathcal{L}}(\rho_\theta - U),$$

preserving cancellation. If $U = P_U + \rho_U$ with P_U in the finite span, then $J\widetilde{\mathcal{L}}P_U$ is exactly its coefficient vector. Thus P_U cancels from the final reference remainder. The degree-six term of U belongs to the 129-column representative, but not to the 45-column representative. Replacing J by R does not preserve this exact cancellation unless the $J - R$ correction is retained.

Uniform derivative gains and computable bounds. Let Ω be the target complex rectangle, with $|x_j| \le r_j$; its modulus bounds must include both real and imaginary half-widths. A valid column envelope is

$$g_{\alpha,\beta} = \prod_{j=1}^{4} \frac{(\beta_j)_{\alpha_j} \, r_j^{\beta_j - \alpha_j}}{s_j^{\beta_j}},$$

with the term zero if some $\beta_j < \alpha_j$. Put $G_\alpha = \sum_\beta g_{\alpha,\beta}$ and, for $v \ge 0$, define

$$\mathcal{G}_\alpha(v) = \sum_\beta g_{\alpha,\beta} v_\beta + G_\alpha \kappa \|v\|_\infty.$$

Then an enclosure of the signed vector $R\widetilde{r}$ gives

$$\sup_{\Omega} |F_\alpha J\widetilde{r}| \le \mathcal{G}_\alpha(|R\widetilde{r}|).$$

The matrix-vector sum is enclosed *before* absolute values are taken. This is the signed principal term. If $|W\xi| \le \zeta$ on a common fidelity event, its contribution is bounded by $\mathcal{G}_\alpha(|R|\zeta)$. A separately certified operator $\beta_{\alpha,2} \ge \sup_\Omega \|F_\alpha J\|_2$ permits the alternative bound $\beta_{\alpha,2}\|W\xi\|_2$; the minimum of two sound bounds may be used. Pointwise matrix-entry enclosures and input errors must refer to this same row order and scaling.

For a sound bound $c_{\alpha,\theta} \ge \sup_\Omega |C_{\alpha,\theta}|$, one therefore obtains the explicit acceptance inequality

$$\|\partial^\alpha E_\theta\|_\Omega \le b_{\alpha,\theta} := \mathcal{G}_\alpha(|R\widetilde{r}|) + \mathcal{G}_\alpha(|R|\zeta) + c_{\alpha,\theta}. \tag{S6}$$

A conservative alternative bounds each bracket in (S5) separately, using its target-domain derivative bound and its transported observation-point remainder bound. Dropping either point tail, final tail or $J - R$ term is not valid. The observation points extend to a larger real domain than Ω; their point remainders need their own domain certificate. The selected network's 69 size bounds do not by themselves supply a small polynomial remainder, and are not class-uniform bounds.

For all orders $1 \le |\alpha| \le 3$, use the resulting component bounds to form full four-coordinate canonical increments

$$\delta_0 = \max_i b_{\mathbf{e}_i}, \qquad \delta_1 = \max_i \sum_j b_{\mathbf{e}_i+\mathbf{e}_j},$$

$$\delta_{t1} = \sum_{i,j} b_{\mathbf{e}_i+\mathbf{e}_j}, \qquad \delta_2 = \max_i \sum_{j,k} b_{\mathbf{e}_i+\mathbf{e}_j+\mathbf{e}_k}.$$

The sums retain ordered multiplicities. These are the learning-error inputs to the separately verified full-phase parameter-family KAM bridge. They do not replace the actual family invariance defect. Joint complex domains, explicit varying embeddings, complete angle/parameter tails, nonresonance, geometry, mean torsion and all scalar preservation gates must still be certified for the same output and the family $H_\lambda = H_\theta + \lambda(H_* - H_\theta)$.

Theorem S3. Simultaneous accepted outputs and no false acceptance. *Assume a common observation-fidelity event $\mathcal{E}$ of probability at least $1 - \delta$ supplies the stated label and input-state allowances for all eligible rows. The design and its strict inverse are independent of the neural candidate, although they may depend on the observed input geometry. Every candidate must have its own sound model-evaluation, representative-remainder and domain certificates. On $\mathcal{E}$,* (S6) *holds simultaneously for every candidate passing these tests, including outputs selected using the same data. If acceptance also requires the complete parameter-family KAM hypotheses with these error budgets, every accepted output has the stated physical-conservative-endpoint KAM conclusion. Consequently, for any measurable certificate-based procedure that returns an output or rejects,*

$$\mathbb{P}\{\textit{the procedure accepts an output with a false certified derivative or KAM conclusion}\} \le \delta.$$

Proof. On the common event, the preceding deterministic identities and bounds hold for each soundly certified output, irrespective of its selection rule. The family bridge is then an ordinary deterministic implication. A false accepted conclusion is therefore contained in $\mathcal{E}^c$. No union over candidate parameters is required.

This is a pathwise accepted-output theorem, not a uniform population-risk bound for all raw networks, a guarantee of optimization success or a lower bound on acceptance probability. A common sound noise event must actually be established; a model-specific post-fit remainder cannot replace it. For fixed numerical-reference fidelity bounds the statement can be entirely deterministic, rather than assigning an invented failure probability. Neither fourteen dependent training curves nor the row counts 80 and 22428 become iid phase samples.

For a future independent configuration draw with the previously fixed selectors, the separate finite-q excitation theorem gives $\delta_q = 18/2^{48}$ for eight configurations or $53/2^{48}$ for fifteen. A joint fidelity-and-q-rank event has probability at least $1 - \delta - \delta_q$. This probability does not guarantee a well-conditioned mixed block, small tails or a KAM pass. If strict inverse certification is required before acceptance, rank failure causes rejection and adds no false-acceptance probability. The

archived forty-point QR choice has its own exact rank witness; the future-draw probability is not a retrospective claim about that choice. Finite-grid laws still need a separate quantitative continuous-law coupling for a statistical theorem requiring positive phase density.

S4 Prospective excitation and sample counts for accepted full-phase outputs

A quantitative learning–KAM connection requires information in every learned canonical direction. The present construction supplements the deterministic observed-chart inverse with a quantitative prospective sampling result. It does not assign an independent sampling law to the archived forced trajectories. It also does not assert that a training algorithm finds an acceptable output.

Fix positive physical scales $s = (s_1, s_2, s_3, s_4)$ before collecting observations and let $u_j = x_j/s_j$. For $D = 4$ or 6, split all nonconstant even-total-degree monomials of degree at most D into configuration-only columns χ_q and columns containing at least one momentum factor χ_p. Their dimensions are $(8, 37)$ or $(15, 114)$. These are representatives used in a certificate; the neural Hamiltonian itself retains its full four-coordinate architecture.

At rest anchors $x = (s_1u_1, s_2u_2, 0, 0)$, observe both configuration derivatives with normalized rows $s_j\partial_{x_j}$, $j = 1, 2$. The mixed columns vanish in these rows. At moving anchors $x = s \odot u$, use both normalized momentum rows $s_j\partial_{x_j}$, $j = 3, 4$; configuration-only columns vanish in these rows. For the prescribed shared kinetic model, $v = G(q)^{-1}p$ gives the structural reference label $U_p = 0$. This is a sampling protocol for canonical anchors, not a claim that arbitrary snapshots of a physical trajectory have this law. Enforcing such anchors experimentally, or transporting from another sampling law, is an additional data requirement.

Let $b = q, p$, $d_b = \dim \chi_b$, and let $B_b(u)$ be the two-row normalized derivative matrix on the corresponding cube $\mathcal{C}_q = [-1, 1]^2$ or $\mathcal{C}_p = [-1, 1]^4$. Define

$$M_b = \mathbb{E}_{\mathrm{unif}(\mathcal{C}_b)} B_b^{\mathsf{T}} B_b, \qquad K_b(u) = \mathrm{tr}(M_b^{-1} B_b(u)^{\mathsf{T}} B_b(u)).$$

These fixed population matrices are positive definite. Indeed, vanishing rest gradient forces a configuration polynomial to be constant, while vanishing momentum gradient forces a mixed polynomial to be configuration-only. Both possibilities are excluded by the specified column sets. The rational arithmetic certificate independently checks positive elimination pivots, the exact inverse and $\mathbb{E}K_b = d_b$. All moments use $\mathbb{E}u^a = 0$ for odd a and $1/(a + 1)$ for even a.

Lemma S4. Conditioning under independent anchors. *Draw n_b independent anchors from a fixed density π_b relative to the uniform probability measure, where $\pi_b > 0$ almost everywhere. Use the row multiplier $\pi_b(u)^{-1/2}$ and suppose*

$$K_b(u)/\pi_b(u) \le L_b \quad \textit{almost everywhere}.$$

For $0 < \varepsilon_b < 1$, with failure probability at most

$$d_b \exp[-\varepsilon_b^2 n_b/(2L_b)],$$

the weighted design A_b satisfies

$$n_b^{-1} A_b^{\mathsf{T}} A_b \succeq (1 - \varepsilon_b) M_b. \tag{S7}$$

The event is simultaneous over all coefficient vectors and hence over all neural outputs having sound representatives and remainder certificates.

Proof. Apply the lower matrix Chernoff bound to the independent positive semidefinite summands

$$X_i = M_b^{-1/2} B_b(u_i)^{\mathsf{T}} B_b(u_i) M_b^{-1/2}/\pi_b(u_i).$$

Each has expectation I, and its largest eigenvalue is at most its trace, bounded by L_b. Corollary 5.2 and Remark 5.3 of Tropp, *User-Friendly Tail Bounds for Sums of Random Matrices*, https://tropp.caltech.edu/papers/

Tro11-User-Friendly-preprint.pdf, give the stated bound. No independence between the two rows of one anchor is assumed; their matrix product is a single summand.

The code supplies a uniform-cube bound $K_b \le \overline{K}_b$ by an exact tensor Bernstein expansion of the leverage polynomial in $t_j = u_j^2 \in [0,1]$. Uniform sampling permits $L_b = \overline{K}_b$. A more economical full-support protocol fixes

$$\pi_b(u) = \tfrac{1}{2}[1 + K_b(u)/d_b], \qquad \tfrac{1}{2} \le \pi_b(u) \le \tfrac{1}{2}[1 + \overline{K}_b/d_b]. \tag{S8}$$

It is normalized because $\mathbb{E}K_b = d_b$, and $K_b/\pi_b = 2d_bK_b/(d_b + K_b) \le 2d_b$. Thus $L_b = 2d_b$ is valid. Rejection sampling from the uniform cube uses the explicit upper density envelope, with no physical solve needed for rejected proposals. The protocol and all scales must be fixed before the draw. Actual draws and accepted observations have not been produced here.

For $\varepsilon_q = \varepsilon_p = 1/2$, allocating failure probability $1/40$ to each block gives the explicit sufficient count

$$n_b = \lceil 8L_b \log(40d_b) \rceil .$$

The arithmetic certificate lists uniform and mixture counts separately. They bound design conditioning, not the number of observations required for successful optimization or a necessary sample lower bound.

Theorem S5. Simultaneous derivative transport for accepted outputs. *For each output write the actual error as*

$$E_\theta = N_\theta - U = \chi_q^{\mathsf{T}} c_{q,\theta} + \chi_p^{\mathsf{T}} c_{p,\theta} + w_\theta.$$

The reference representative, if used in this identity, is for verification only and is not supplied as a training label. At each sample use the weighted normalized derivative rows above. Suppose the corresponding observed residual, common label-fidelity error, and actual remainder are r_b, ξ_b and $\mathcal{L}_b w_\theta$, with

$$r_b = A_b c_{b,\theta} + \mathcal{L}_b w_\theta - \xi_b.$$

Let the sound allowances be

$$R_b = \|r_b\|_2/\sqrt{n_b}, \quad Z_b \ge \|\xi_b\|_2/\sqrt{n_b}, \quad T_{b,\theta} \ge \|\mathcal{L}_b w_\theta\|_2/\sqrt{n_b}.$$

On the two conditioning events of Lemma S4,

$$\|M_b^{1/2} c_{b,\theta}\|_2 \le (R_b + Z_b + T_{b,\theta})/\sqrt{1-\varepsilon_b}.$$

For a target real or complex domain Ω, let $F_{\alpha,b}(x) = \partial_x^\alpha \chi_b(x)^{\mathsf{T}}$ and certify

$$C_{\alpha,b} \ge \sup_{x\in\Omega} \big(F_{\alpha,b} M_b^{-1} F_{\alpha,b}^*\big)^{1/2}, \qquad W_{\alpha,\theta} \ge \sup_{\Omega} |\partial_x^\alpha w_\theta|.$$

Here $*$ conjugates the target-domain row, and the derivatives retain the physical factors $1/s_j$. Then, simultaneously for every soundly certified output, including one selected from the same observations,

$$\|\partial_x^\alpha E_\theta\|_\Omega \le \sum_{b=q,p} C_{\alpha,b} \frac{R_b + Z_b + T_{b,\theta}}{\sqrt{1-\varepsilon_b}} + W_{\alpha,\theta}. \tag{S9}$$

The stated probability is at least $19/20$, reduced by any separately allocated failure probability of the common fidelity event.

Proof. The residual identity, the triangle inequality and (S7) imply the coefficient bound. Differentiate the decomposition and apply the ordinary complex Cauchy–Schwarz inequality to $F_{\alpha,b} M_b^{-1/2} M_b^{1/2} c_{b,\theta}$. Both matrix events hold for all coefficient vectors, so adaptively choosing an output requires no union bound over network parameters. Candidate-dependent tails must actually be verified; they are not discarded on account of this simultaneity.

For $1 \le |\alpha| \le 3$, these derivative budgets feed the same full-phase family bridge as the deterministic observed-chart bounds. A KAM conclusion additionally requires actual family embeddings, complete angle and parameter tails, nonresonance, varying geometry and mean torsion, and all scalar preservation gates. This theorem provides a quantitative prospective excitation and interpolation component; it does not retrospectively establish iid population risk for the existing data, remove physical-label uncertainty, or replace those family certificates. The Rademacher bound for the full neural class in Chen et al. (2022) and a guarantee of successful training are distinct claims and are not inferred from this finite-output result.

S5 A finite-base-measure observation corollary

This corollary supplements the continuous-base prospective construction, which remains unchanged. Its finite-base Gram matrices are newly defined below, rather than identified with the continuous-base matrices. It does not identify archived trajectories with independent phase-space samples. Let $x = (q_1, q_2, p_1, p_2)$, $h = (1/25, 1/25, 1/50, 1/25)$ and $\mathcal{S} = \{-1, -2/3, -1/3, 0, 1/3, 2/3, 1\}$. Let ν_q be uniform on $\mathcal{S}^2$, embedded at $(h_1 y_1, h_2 y_2, 0, 0)$, and let ν_p be uniform on $\mathcal{S}^4$, embedded at $h \odot y$. Both base measures are finite. In particular they have no positive Lebesgue density to which a continuous-domain Morrey argument could be applied.

The vector χ_q contains the 15 nonconstant configuration-only monomials of even total degree at most six. The vector χ_p contains the 114 monomials of even total degree at most six having a momentum factor. Each monomial has the physical definition $\chi_\beta(x) = \prod_j (x_j/h_j)^{\beta_j}$. Define B_q by the two derivatives $h_j \partial_{x_j}$, $j = 1, 2$, at rest, and B_p by $h_j \partial_{x_j}$, $j = 3, 4$, on the moving support. The resulting matrices have two rows and d_b columns, where $d_q = 15$ and $d_p = 114$.

Proposition S6. Finite-grid rank and exact importance law. *For $b = q, p$, the matrix*

$$M_b = \mathbb{E}_{\nu_b} B_b^{\mathsf{T}} B_b$$

is positive definite. With $K_b = \operatorname{tr}(M_b^{-1} B_b^{\mathsf{T}} B_b)$, the density $\pi_b = (1 + K_b/d_b)/2$ is strictly positive relative to ν_b, has mean one and satisfies $K_b/\pi_b \le 2d_b$. All these quantities at support points are rational.

Proof. A zero Gram quadratic form forces both derivative polynomials to vanish at every support point, because the base masses are positive. Each derivative has total degree at most five, hence coordinate degrees at most five. Successive application of the one-variable root bound on seven distinct nodes proves that it vanishes identically. In the rest block, both configuration derivatives vanishing forces a constant polynomial, and no constant column is present. In the moving block, both momentum derivatives vanishing forces a configuration-only polynomial, whereas each column has a momentum factor. Linear independence of the monomials therefore forces the coefficient vector to be zero in both cases. Rational coordinates give rational Gram entries, inverses and leverage values. The trace identity $\mathbb{E}_{\nu_b} K_b = \operatorname{tr}(M_b^{-1} M_b) = d_b$ proves normalization, and $K_b/\pi_b = 2d_b K_b/(d_b + K_b) \le 2d_b$.

To implement this exact law, choose an integer $D_b > 0$ such that $D_b K_b$ is integral at every support point and assign weight $w_y = d_b D_b + D_b K_b(y)$. If m_b is the support size, then

$$\sum_y w_y = 2d_b D_b m_b, \qquad \frac{w_y}{\sum_z w_z} = \frac{\pi_b(y)}{m_b}.$$

Common integer factors may be cancelled. A uniform ticket in $\{0, \dots, W_b - 1\}$ is obtained by requesting $k = \lceil \log_2 W_b \rceil$ fresh bits and rejecting integers at least W_b; $W_b = 1$ requires no bits. No reduction modulo W_b is used. Every accepted ticket is exactly uniform. Independent fresh fair bits therefore generate independent anchors with replacement. This is a randomness assumption: provider identity, a fixed seed or a replayable transcript does not prove that physical bits are independent and fair.

Corollary S7. Common-event conditioning on the finite base. *Draw $n_q = 1536$ and $n_p = 15368$ independent anchors with these laws. Let A_b stack $B_b(Y_i)/\sqrt{\pi_b(Y_i)}$. Under the stated fair-bit model,*

$$\mathbb{P}\left\{A_b^{\mathsf{T}} A_b/n_b \succeq M_b/2 \text{ for } b = q, p\right\} \ge 19/20.$$

The event controls every coefficient vector, including one selected using the same observations.

Proof. One whitened anchor summand is positive semidefinite, has mean I, and has maximum eigenvalue bounded by its trace, hence by $2d_b$. The lower matrix Chernoff estimate used for the prospective construction gives

$$\mathbb{P}\{A_b^{\mathsf{T}} A_b/n_b \not\succeq M_b/2\} \le d_b \exp[-n_b/(16d_b)].$$

The declared integer counts satisfy $n_b \ge 16d_b \log(40d_b)$. Each failure probability is therefore at most $1/40$, and a union bound proves the claim. The two derivative rows at one anchor form one summand; no independence between those rows is required or asserted. The matrix inequality is simultaneous for every coefficient vector.

S5.1 Reference fidelity and signed coefficient reconstruction

Fix a returned analytic energy correction N and a prescribed configuration-only reference correction U. For the executed experiment, N is the already frozen 736-coordinate GC output. Decompose its error as

$$E = N - U = P_N - P_U + w, \qquad w = (N - P_N) - (U - P_U).$$

Here P_N is the finite, even degree-six Chebyshev least-squares representative, with its exact stored coefficients; it is not assumed to be a convergent Taylor truncation of N. The reference representative P_U is used only in verification. Exact coefficient rescaling from prior scales s_j to h_j by $\prod_j (h_j/s_j)^{\beta_j}$ preserves each physical polynomial. Consequently it preserves the remainder function, but it does not itself certify that function at new observation points.

At rest, labels are directed evaluations of the full finite-Gauss reference gradient minus the quartic-prior gradient. The full reference is $H_* = \frac{1}{2} p^{\mathsf{T}} G_8(q)^{-1} p + \frac{1}{2} q^{\mathsf{T}} K q + 1 - \cos(d^{\mathsf{T}} q)$. Its kinetic configuration derivative vanishes exactly at $p = 0$, so the reference correction has

$$\partial_{q_j} U = d_j \{\sin(d^{\mathsf{T}} q) - d^{\mathsf{T}} q + (d^{\mathsf{T}} q)^3/6\}.$$

The moving labels are exactly $\partial_p U = 0$ because the reference and learned prior share the entire kinetic graph. These labels are not the derivatives of P_U, exported COMSOL forces, or physical measurements. They are sealed before production evaluation of N and the representatives at the new anchors.

Let the observed derivative label be $Y_{bi,j}$, with a sound common fidelity bound $|Y_{bi,j} - \partial_j U(x_{bi})| \le f_{bi,j}$. With normalized rows define

$$\begin{aligned} r_{bi,j} &= h_j \{\partial_j N(x_{bi}) - Y_{bi,j}\}, \\ t_{bi,j} &= h_j \partial_j w(x_{bi}), \\ \xi_{bi,j} &= h_j \{Y_{bi,j} - \partial_j U(x_{bi})\}, \\ s_{bi} &= r_{bi} - t_{bi} = B_{bi} c_b - \xi_{bi}. \end{aligned}$$

The same factor h_j acts on residual, label uncertainty and point remainder. At rest the mixed polynomial columns vanish under these derivatives; momentum derivatives annihilate the configuration-only columns. Thus these are the separate equations for the two blocks of the same complete error polynomial.

Group repeated anchors with their multiplicities m_{bi} and put $\omega_{bi} = m_{bi}/(n_b \pi_b(Y_i))$. Set

$$\begin{aligned} \overline{G}_b &= \sum_i \omega_{bi} B_{bi}^{\mathsf{T}} B_{bi}, \\ b_b &= \sum_i \omega_{bi} B_{bi}^{\mathsf{T}} s_{bi}, \\ \zeta_{b,k} &= \sum_{i,j} \omega_{bi} |B_{bi,jk}| h_j f_{bi,j}. \end{aligned}$$

Neither B_{bi} nor s_{bi} includes an importance factor here; $1/\pi_b$ occurs exactly once in ω_{bi}. Equivalently, all un-grouped residual, fidelity and remainder rows may be weighted by $1/\sqrt{\pi_b}$. Squared norms and Gram entries use exact rational $1/\pi_b$, avoiding a rounded irrational square root. The empirical Gram matrix retains its full cross-parity entries.

Proposition S8. Validated signed inverse. *Suppose $\overline{G}_b \succ 0$ and a verified interval solve encloses*

$$\overline{G}_b^{-1}([b_b] + [-\zeta_b, \zeta_b]) \subseteq [c_b].$$

Then $[c_b]$ contains the actual coefficient vector of $P_N - P_U$. This conclusion is deterministic under the common fidelity bounds.

Proof. The exact signed identity gives $\overline{G}_b c_b = b_b + \sum_i \omega_{bi} B_{bi}^{\mathsf{T}} \xi_{bi}$. The last vector is bounded componentwise by ζ_b; applying the validated inverse proves containment. A residual interval containing zero is a consistency check, rather than a substitute for a verified inverse or validated interval solve.

If $|x_j| \le R$ on the original complex rectangle Ω, put $C_{b,\beta} = \sup |[c_{b,\beta}]|$. For every $1 \le |\alpha| \le 3$,

$$\begin{aligned} \|\partial^\alpha E\|_\Omega \le \sum_b \sum_{\beta \ge \alpha} C_{b,\beta} \frac{\beta!}{(\beta-\alpha)!} \frac{R^{|\beta|-|\alpha|}}{\prod_j h_j^{\beta_j}} \\ + W_{N,\alpha} + W_{U,\alpha}, \end{aligned} \tag{S10}$$

where $W_{N,\alpha}$ and $W_{U,\alpha}$ are certified bounds for $\partial^\alpha(N - P_N)$ and $\partial^\alpha(U - P_U)$ throughout Ω. The reference target remains the rectangle $|\operatorname{Re} x_j| \le 3/50$, $|\operatorname{Im} x_j| \le 1/100$; one may take a certified $R \ge \sqrt{37}/100$. This bound includes the physical derivative factors h_j^{-1} and all mixed derivatives. It does not replace the full target by the finite anchor support.

S5.2 Acceptance and interpretation

The scalar norm alternative on the same common matrix event is

$$\|M_b^{1/2} c_b\|_2 \le \sqrt{2} \min\{R_b + Z_b + T_b, \widetilde{R}_b + Z_b\},$$

where the four quantities bound respectively the normalized RMS residual, fidelity, point remainder and signed-corrected residual. All use the identical rows $h_j \partial_j / \sqrt{\pi_b}$. The two alternatives and the signed inverse are consequences of the same identities. Selecting the direction-preserving analysis after the scalar estimate does not require another independent sample, change a predeclared threshold, or guarantee that the refinement is accurate enough for KAM acceptance.

For any measurable selection of outputs and sound individual certificates, acceptance based on the common event and a common fidelity event of failure allowance α_{fid} satisfies

$$\mathbb{P}\{\text{acceptance and a false asserted conclusion}\} \le 1/20 + \alpha_{\mathrm{fid}}.$$

This is an unconditional false-acceptance statement. It is not conditional coverage given acceptance, nor an optimization-success guarantee. For the specified exact-reference oracle, directed intervals give deterministic fidelity, so no probabilistic label allowance is needed. When both realized Gram inequalities are also certified directly, the asserted output bound is a pathwise implication for that realized experiment, independent of whether one invokes its prospective probability estimate.

Finally, form the four canonical derivative budgets with all ordered multiplicities as in the observation-error construction. To reuse a previously certified conservative family, these new budgets must fit its fixed exact allowances under a validated substitution or monotonicity argument. The same Hamiltonian, physical reference, parameter family, approximate embeddings, varying mean torsion, target domain and remaining KAM hypotheses must remain bound to that application. Otherwise the affected conditions must be recomputed. This is a conditional numerical acceptance rule; it does not assert that the new signed enclosures or their family application have passed merely because the sampling design is well conditioned.

S5.3 Executed fixed-output application

The declared experiment retained all 16904 anchor draws, grouped into 49 distinct rest nodes and 2394 distinct moving nodes. The 2443 block nodes share 2394 physical neural-evaluation points. All 49 rest-label pairs were enclosed by the directed full-sine reference oracle, with their exact interval midpoints and radii. The two moving reference derivatives are exactly zero. The reference labels and their seal precede the production neural evaluations. Both realized full Gram inequalities were verified without imposing population parity zeros on the empirical matrices.

The scalar norm estimate initially exceeded all four fixed family allowances. A subsequent direction-preserving analysis used the same realized observations, exact importance weights, fixed output, target rectangle and whole-domain remainders. It introduced no additional draw, reference label, optimization or threshold change. The signed coefficient enclosures were independently verified by exact normal-equation reconstruction and inverse validation. Their full physical derivative budgets obey

$$\delta_0 < 1.898 \times 10^{-8}, \quad \delta_1 < 2.368 \times 10^{-6},$$
$$\delta_{t1} < 6.398 \times 10^{-6}, \quad \delta_2 < 5.777 \times 10^{-4}.$$

These decimal bounds are rounded outward for presentation. The actual comparisons use the complete rational enclosures, each strictly below its unchanged family allowance; the rounded decimals are not substituted into those comparisons.

The source-bound application retains the same Hamiltonians $H_\lambda = T_G + V_4 + (1-\lambda)N + \lambda U$, the complete degree-ten response polynomial, the validated varying mean torsion and its inverse, the complex domains and the real-embedding test. The complete family defect remains below 3.848×10^{-41}; all eight scalar acceptance quotients remain below 0.04136. Consequently, for every real $\lambda \in [0,1]$, this same conservative family has a real analytic embedded invariant two-torus with the fixed exact rotation vector. The torus is analytic on the strip of width $1/400$ and lies within 3.949×10^{-22} of the corresponding degree-ten approximation. At $\lambda = 1$ its Hamiltonian is exactly the prescribed finite-Gauss conservative reference. This is a per-parameter existence conclusion with uniform bounds, rather than a claim of analytic dependence on λ or a torus of the forced or dissipative equations.

The new anchors verify an already trained fixed network against its declared numerical reference. They do not supply a new iid training experiment, a continuous-density risk bound for the entire neural class, or fidelity for an uncalibrated measured plant.

S5.4 A certified invariant torus of the full-phase learned Hamiltonian

Let $\widehat{H}_{\mathrm{GC}}$ denote the selected two-hidden-layer complex Hamiltonian, with its stored binary64 buffers interpreted as exact real constants and its smooth parameter constraints evaluated in exact real arithmetic. In physical canonical coordinates $x = (q_1, q_2, p_1, p_2)$,

$$\widehat{H}_{\mathrm{GC}}(q,p) = \tfrac{1}{2} p^{\mathsf{T}} G_8(q)^{-1} p + V_4(q) + N_{\mathrm{GC}}(q,p).$$

Here G_8 is the prescribed finite Gauss–Legendre mechanical graph, V_4 is the fourth-order potential, and N_{GC} is the trained full-phase correction. The correction includes its prescribed real readout, total evenization and constant energy gauge. Its real-analytic extension treats the four canonical coordinates independently; it retains both configuration and momentum derivatives.

Write $\varphi = (1+\sqrt{5})/2$ and fix the period-one rotation vector

$$\nu = \frac{\Omega_1}{2\pi}(1,\alpha), \qquad \Omega_1 = \frac{499974648628101}{500000000000000}, \qquad \alpha = \frac{2524851\varphi + 622102}{410497\varphi + 101143}. \tag{S11}$$

All strip and matrix norms below follow the entrywise analytic supremum convention: $\|A\|_\rho = \max_i \sum_j \sup_{\mathbb{T}^2_\rho} |A_{ij}|$.

Theorem S9. Fixed full-phase learned Hamiltonian. *For the frozen selected GC checkpoint and the finite Gauss mechanical graph specified by the accompanying reproducibility certificate, there exists an analytic invariant torus with rotation vector* (S11). *More precisely, the saved 8064-mode rational Fourier polynomial K_{128} admits a real-analytic invariant embedding with a holomorphic extension K_∞ to $\mathbb{T}^2_{1/400}$ satisfying*

$$J_4 \nabla \widehat{H}_{\mathrm{GC}}(K_\infty) = DK_\infty \nu, \qquad \|K_\infty - K_{128}\|_{1/400} < 9.018 \times 10^{-24}.$$

The restriction of K_∞ to the real torus is a real embedding. The image remains in the certified complex canonical domain

$$|\operatorname{Re} x_j| < 3/50, \qquad |\operatorname{Im} x_j| < 1/100, \qquad j = 1, \dots, 4.$$

Proof. The exact-raw network and mechanical certificates establish a real-type holomorphic Hamiltonian on the stated domain, together with the required first, second and third Hamiltonian derivative bounds. The continued fraction in (S11) has bounded positive partial quotients and a golden tail. The all-integer arithmetic certificate therefore supplies

$$|k \cdot \nu| \geq \gamma/|k|_1 \quad (k \in \mathbb{Z}^2 \setminus \{0\}), \qquad \gamma = \frac{4828522443384859}{5764607523034234 88}.$$

The corresponding uniform cohomological bound is valid with exponent $\tau = 1$ and $c_R = 1/7$ at every analytic strip loss.

The coefficients of K_{128} satisfy exact conjugate reality and total oddness. Direct Fourier majorants establish its complex-domain inclusion, Gram inverse and real embedding. Put

$$L = DK_{128}, \quad B = (L^{\mathsf{T}}L)^{-1}, \quad N = J_4LB, \quad T = N^{\mathsf{T}}J_4\big(J_4D^2\widehat{H}_{\mathrm{GC}}(K_{128})N - D_\nu N\big).$$

The transpose is the analytic transpose. All four canonical coordinates and the complete 4×4 Hamiltonian Hessian enter these expressions. Whole-strip bounds at $\rho_T = 7/200$, a 96×96 real quadrature, and the infinite alias estimate

$$|\langle T\rangle_{ij} - (T_{96})_{ij}| \leq \frac{4M_T e^{-2\pi\rho_T 96}}{(1 - e^{-2\pi\rho_T 96})^2} < 1.686 \times 10^{-6}$$

give an invertible continuous mean with $\|\langle T\rangle^{-1}\|_\infty < 19026.13$. Every saved Fourier mode is retained with its original derivative multiplier when folded onto the quadrature grid.

For $E = J_4\nabla\widehat{H}_{\mathrm{GC}}(K_{128}) - DK_{128}\nu$, a separate outer-strip proof at $\widehat{\rho} = 1/10$ bounds the composed field by $M_X < 55.544$. It uses full first-affine Fourier bounds, a complete second-preactivation interval cover on the four imaginary corners, the separate-variable maximum principle and a certified Cauchy tube. An outward-arithmetic 448×448 discrete Fourier transform then encloses the interpolation polynomial on $\rho = 1/40$. Its weighted componentwise coefficient sums and the full analytic alias-and-tail bound yield

$$\|E\|_{1/40} < 1.196 \times 10^{-42}.$$

The finite polynomial $DK_{128}\nu$ is represented exactly within the signed interpolation cube. All numerical sample enclosures, including the independent real-metric derivative remainders, enter the transform. Odd-parity Nyquist modes are retained.

Apply the canonical $n = d = 2$ case of Haro and Luque (2019, Theorem 3.1), with the audited arXiv version 1 conventions. Set $\rho_\infty = 1/400$, $a_1 = 2$ and choose each auxiliary σ as $11/10$ times its corresponding outward certified bound. These strict positive margins satisfy the theorem's hypotheses; all constants and all eight preservation and contraction inequalities are recomputed with these parameters. Their maximum quotient is less than 6.942×10^{-4}, with a sufficient residual threshold greater than 1.722×10^{-39}. The resulting displacement is less than 9.018×10^{-24}, lies within the certified domain margin, and preserves the real embedding by the normalized phase estimate. The sign adjustment between the saved normal frame and the theorem's canonical convention changes the sign of T and leaves its mean inverse norm unchanged. The theorem gives the asserted torus.

This statement concerns the specified learned conservative Hamiltonian. Its data-to-model population guarantees, dissipative trajectories and magnetic feedback require their respective learning and power-transport estimates. The finite-Gauss reference and the declared coordinate normalization remain part of the model specification.

S6 Uniform geometry and scalar gates for the actual conservative family

Keep the exact four canonical coordinates, frozen GC checkpoint, finite Gauss mechanical graph and prescribed period-one frequency of the learned torus certificate. Set

$$H_\lambda = H_{\mathrm{GC}} + \lambda(U - N), \quad P_\lambda = K_0 + V_\lambda, \quad V_\lambda = \sum_{j=1}^{m} \lambda^j U_j, \qquad 0 \le \lambda \le 1.$$

Every response is its actually saved rational Fourier polynomial. A change to an earlier U_j requires reconstruction of the subsequent response chain, its residual and all bounds in this section.

Matrix norms are the entrywise analytic supremum induced row-sum norm; transpose norms are bounded separately. At a selected strip let v, d, d^t, w, w^t bound respectively

$$\|V_\lambda\|, \quad \|DV_\lambda\|, \|(DV_\lambda)^{\mathsf{T}}\|, \quad \|D_\nu DV_\lambda\|, \quad \|(D_\nu DV_\lambda)^{\mathsf{T}}\|.$$

These follow uniformly for real $\lambda \in [0,1]$ by summing the actual weighted Fourier majorants of all U_j. The period-one directional multiplier is $2\pi|k \cdot \nu|$; with the specified algebraic frequency it equals $\Omega_1|k_1 + \alpha k_2|$. No sampled maximum substitutes for these complete analytic-strip norms.

Domain and Hamiltonian derivatives. At $\rho = 1/40$, subtract each componentwise response majorant from the certified four-coordinate image margins of K_0 in $|\operatorname{Re} x_i| < 3/50$, $|\operatorname{Im} x_i| < 1/100$. A positive remaining margin supplies an open theorem tube; the calculator uses half the remaining radius as a strict reserve. Let $(\delta_0, \delta_1, \delta_{t1}, \delta_2)$ be the accepted full-phase data-to-output bounds for $Y = J\nabla(U - N)$, its derivative, its transposed derivative and its ordered bilinear second derivative on this same rectangle. Then

$$c_0 = \widehat{c}_0 + \delta_0, \quad c_1 = \widehat{c}_1 + \delta_1, \quad c_{t1} = \widehat{c}_{t1} + \delta_{t1}, \quad c_2 = \widehat{c}_2 + \delta_2$$

are valid uniform real-parameter field inputs. These statements do not extend an inner rectangle estimate to the larger residual angle strip. The separate angle–parameter product-domain proof is still needed for the residual Cauchy tail.

Lemma S10. Finite norm transport. *Put* $L_0 = DK_0$, $B_0 = (L_0^{\mathsf{T}} L_0)^{-1}$, $N_0 = JL_0B_0$, *and* $W_0 = D_\nu L_0$. *Let* $l_0, l_0^t, b_0, n_0, n_0^t, w_0, w_0^t, h_0, z_0$ *be valid bounds for* $L_0, L_0^{\mathsf{T}}, B_0, N_0, N_0^{\mathsf{T}}, W_0, W_0^{\mathsf{T}}, D_\nu(L_0^{\mathsf{T}}L_0), D_\nu N_0$. *Write*

$$g = l_0^t d + d^t l_0 + d^t d, \quad \eta_B = b_0 g.$$

If $\eta_B < 1$, *the varying Gram matrix is invertible and*

$$b = \frac{b_0}{1 - \eta_B}, \quad \Delta b = \frac{b_0^2 g}{1 - \eta_B}, \quad \Delta n = db + l_0 \Delta b, \quad \Delta n^t = \Delta b\, l_0^t + b d^t$$

bound B, $B - B_0$, $N - N_0$ *and* $N^{\mathsf{T}} - N_0^{\mathsf{T}}$. *One may take* $n = \min\{(l_0 + d)b, n_0 + \Delta n\}$ *and* $n^t = \min\{b(l_0^t + d^t), n_0^t + \Delta n^t\}$.

Set

$$\begin{aligned}
\Delta h &= w^t l_0 + w_0^t d + w^t d + d^t w_0 + l_0^t w + d^t w, \\
h &= h_0 + \Delta h, \quad c = b^2 h, \\
\Delta c &= \Delta b\, hb + b_0 \Delta h\, b + b_0 h_0 \Delta b, \\
\Delta z &= wb + w_0 \Delta b + dc + l_0 \Delta c.
\end{aligned}$$

Then $D_\nu N$ *is bounded by* $z = z_0 + \Delta z$. *For the saved canonical torsion convention*

$$T_\lambda(P) = N^{\mathsf{T}} J\{DX_\lambda(P)N - D_\nu N\},$$

define

$$q_0 = c_1 n_0 + z_0, \quad \Delta q = c_2 v n + c_1 \Delta n + \Delta z, \qquad t = \Delta n^t (q_0 + \Delta q) + n_0^t \Delta q.$$

Provided all straight state segments remain in the common convex analytic rectangle, uniformly in real λ,

$$\|\langle T_\lambda(P_\lambda)\rangle - \langle T_\lambda(K_0)\rangle\|_\infty \le t.$$

Proof. Expand the Gram difference and use the inverse Neumann identity. The normal-frame bounds follow from $N = JLB$ and analytic transpose symmetry $B^{\mathsf{T}} = B$. For the directional derivative use the exact identities $C = D_\nu B = -B(W^{\mathsf{T}} L + L^{\mathsf{T}} W)B$ and $D_\nu N = JWB + JLC$. The displayed Δh retains all six terms of the middle-factor difference; telescoping the two outer inverse factors gives Δc. Next, $\|DX_\lambda(P) - DX_\lambda(K_0)\| \le c_2 v$. Expand $DX_\lambda(P)N - D_\nu N$ about K_0, then expand its left N^{T} factor. Averaging cannot increase this entrywise analytic norm. No exact invariance or Lagrangian identity is used.

The accepted signed fixed-map certificate supplies $I_* \ge \sup_{\lambda\in[0,1]} \|\langle T_\lambda(K_0)\rangle^{-1}\|_\infty$. Consequently $I_* t < 1$ is a sufficient varying-map nondegeneracy test, with inverse bound $I_*/(1 - I_* t)$. Its failure is not a singularity certificate. The current $I_* \simeq 19036.55$ requires a change less than approximately $5.253\,10^{-5}$ for this particular sufficient test. An unsigned pointwise transport can be much larger than the actual signed continuous mean.

A genuine direct frame inverse. The construction frame is $M = [L, JLB]$, not an assumed exactly symplectic frame. Put $\Omega = L^{\mathsf{T}} JL$. Since B is symmetric,

$$M^{\mathsf{T}} J M = \begin{pmatrix} \Omega & -I \\ I & B\Omega B \end{pmatrix}.$$

Thus $\kappa = \max(1, b^2)\|\Omega\| < 1$ proves M invertible. It gives

$$\|M^{-1}\| \le \frac{\max(n^t, l^t)}{1-\kappa}, \qquad \left\| M^{-1} - \begin{pmatrix} N^{\mathsf{T}} J \\ -L^{\mathsf{T}} J \end{pmatrix} \right\| \le \frac{\kappa \max(n^t, l^t)}{1-\kappa}.$$

The implementation bounds Ω_0 from the actual harmonic normalization S: it computes the exact rational $\|S^{\mathsf{T}} JS - J\|$, adds the normalized DK_0 remainder products, and then adds the varying DK products. It does not assume that the stored floating-point S is exactly symplectic. Direct-frame reduced upper-right torsion is used to construct responses. The KAM theorem's saved torsion above is supplied separately; these two matrices are not declared equal at a non-Lagrangian approximate embedding.

The eight actual scalar gates. Use the unchanged certified (ν, γ, τ, c_R), $\rho = 1/40$, $\rho_\infty = 1/400$, $a_1 = 2$, and the ordinary canonical $n = d = 2$ Haro–Luque Case III constants. Replace the scalar calculator inputs by the newly proved uniform

$$k = \sup\|DP_\lambda\|, \quad k^t = \sup\|(DP_\lambda)^{\mathsf{T}}\|, \quad b = \sup\|B_\lambda\|, \quad I = \sup\|\langle T_\lambda\rangle^{-1}\|,$$

the remaining domain radius and (c_0, c_1, c_{t1}, c_2) above. Choose strict auxiliary bounds $\sigma_K > k, \sigma_{K^t} > k^t, \sigma_B > b, \sigma_T > I$; the supplied finite calculator uses the admissible ratio $11/10$. All Table 1–3 constants are recomputed from these inputs by the same previously audited exact-rational constants engine. This is shared constants code, not a new independent derivation of all table entries.

To make the mapping explicit, write $\ell = \rho/a_3$ for its strip loss, $E = \sup_{\lambda\in[0,1]} \|X_\lambda(P_\lambda) - D_\nu P_\lambda\|_\rho$, and denote its newly computed table constants by $C_E, C_{\mathrm{sym}}, C_K, C_B, C_{T^{-1}}$. The required dimensionless inequalities, each strictly less than one,

are

$$
\begin{aligned}
g_1 &= (a_1 a_3)^{4\tau} C_E E/(\gamma^4 \rho^{4\tau}),\\
g_2 &= E/(\ell \nu_{\mathrm{iter}}), \qquad g_3 = 2C_{\mathrm{sym}} E/(\gamma \ell^{\tau+1}),\\
g_4 &= \frac{2C_K E}{(\sigma_K - k)\gamma^2 \ell^{2\tau+1}(1 - a_1^{1-2\tau})},\\
g_5 &= \frac{4C_K E}{(\sigma_{K^t} - k^t)\gamma^2 \ell^{2\tau+1}(1 - a_1^{1-2\tau})},\\
g_6 &= \frac{C_B E}{(\sigma_B - b)\gamma^2 \ell^{2\tau+1}(1 - a_1^{1-2\tau})},\\
g_7 &= \frac{C_{T^{-1}} E}{(\sigma_T - I)\gamma^2 \ell^{2\tau+1}(1 - a_1^{1-2\tau})},\\
g_8 &= \frac{C_K E}{r_{\mathrm{dom}} \gamma^2 \ell^{2\tau}(1 - a_1^{-2\tau})}.
\end{aligned}
$$

These are respectively contraction, residual/iteration, approximate symplectic inverse, preservation of DP, its transpose, Gram inverse, mean torsion inverse and domain distance. Here $\nu_{\mathrm{iter}} = 1$ is a theorem parameter and is not the two-component frequency ν. The calculator evaluates the eight slopes g_i/E with exact rational arithmetic; their reciprocal maximum is a new conditional residual threshold. If I is only a proposed target, every resulting gate and threshold remains explicitly conditional. A scalar calculation does not turn that target into a proved mean-inverse bound.

The KAM C^0 correction is its newly computed $C_2 E/(\gamma^2 \rho^{2\tau})$. For real embedding use the actual retained-strip normalized harmonic errors, adding $\|S^{-1}\|\|V\|$ and $\|S^{-1}\|\|DV\|$. Then add the KAM correction to the former and $2\|S^{-1}\|$ times that correction divided by ρ_∞ to the latter. The already audited normalized phase test

$$
a > 2e_0, \qquad \frac{2e_1 + (88/7)e_0}{6(a - 2e_0)} < \tfrac{1}{2}
$$

must hold uniformly. The preliminary response-only phase test in the finite calculator does not include an as-yet unknown KAM correction.

Proposition S11. Conditional uniform family acceptance. *If the full same-chain residual E, uniform domain, derivatives, Gram inverse and continuous mean inverse are verified as stated, all eight fresh gates pass, and the corrected normalized phase test passes, then the canonical a-posteriori theorem applies for each real $\lambda \in [0,1]$ to this actual four-coordinate pair, with the same prescribed frequency. In particular it applies to the physical endpoint. No analytic exact K_λ family is assumed in constructing P_m.*

The lower residuals remain actual nonzero coefficients. In particular $\langle DK_0^{\mathsf{T}} J e_j\rangle = -\sum_{r=1}^{j} \langle DU_r^{\mathsf{T}} J e_{j-r}\rangle$. This compatibility identity and the approximate-symplectic gate replace any invalid assumption of exact Lagrangianity. A passed learned-model threshold, the fixed-map signed inverse, or the newly verified e_1 alone is not a substitute for the full varying-family hypotheses.

A concrete alternative when unsigned torsion transport fails. Use the actual P_m on a containing angle–parameter product domain and certify its Gram inverse there. Evaluate the parameter Taylor coefficients of $\langle T_\lambda(P_m)\rangle$, retaining their signed two-by-two entries and complete angle-quadrature aliases. A modulus M_T on $|\lambda| \le R$ bounds the tail after L_T by $M_T/[R^{L_T}(R-1)]$. Verify the determinant is separated from zero on real $[0,1]$, for example by exact interval Bernstein subdivision of the signed matrix polynomial with the entrywise tail added, and bound its inverse by adjugate/determinant. No symmetry of the approximate saved mean is assumed. The necessary series graph includes physical G, G_q, G_{qq}, the actual network Hessian, the derivative of $N = JLB$ and its analytic Gram inverse. This is a specific new continuous-mean certificate to compute; it cannot be inherited from the fixed K_0.

S7 Observation-based acceptance of a full-phase Hamiltonian family

Let $x = (q_1, q_2, p_1, p_2)$ be physical canonical coordinates, let $J = \left(\begin{smallmatrix} 0 & I_2 \\ -I_2 & 0 \end{smallmatrix}\right)$, and fix a prescribed reference and a learned energy

$$H_* = T_G + V_4 + U(q), \qquad \widehat{H}_\vartheta = T_G + V_4 + N_\vartheta(q,p), \qquad T_G = \tfrac{1}{2} p^{\mathsf{T}} G(q)^{-1} p. \tag{S12}$$

The real scalar N_ϑ may be supplied by a complex-valued network with a real, coefficient-sharp readout. Its complexification must be holomorphic on every domain used below. No holomorphicity in the physical variable $q + ip$ is imposed, and no momentum derivative of N_ϑ is set to zero. Define

$$e_\vartheta = N_\vartheta - U, \quad Y_\vartheta = -J\nabla e_\vartheta, \quad H_{\vartheta,\lambda} = T_G + V_4 + (1-\lambda)N_\vartheta + \lambda U, \qquad 0 \le \lambda \le 1. \tag{S13}$$

Thus $X_{H_{\vartheta,\lambda}} = X_{\widehat{H}_\vartheta} + \lambda Y_\vartheta$.

A finite observation certificate. Fix positive coordinate scales s_j and the complete set χ of nonconstant even-total-degree monomials in x_j/s_j through degree $D = 4$ or 6. Its dimension is 45 or 129. For an output choose an identified polynomial $P_\vartheta = \chi^{\mathsf{T}} a_\vartheta$ and write $\rho_\vartheta = N_\vartheta - P_\vartheta$. This decomposition does not restrict the network to a polynomial class.

The observation operator $\mathcal{L}$ contains the selected physical configuration derivatives at rest anchors $(Q_i, 0)$ and momentum derivatives at moving anchors. The latter may use the exact observation chart $(\bar{q}, G(\bar{q})\bar{v})$. The reference correction satisfies $U_p = 0$ at every such anchor. This is a consequence of the shared kinetic graph in (S12), independent of any assertion that the chart point is a true trajectory state. At rest, labels have the form $Y_i = \nabla(V_4 + U)(Q_i) + \xi_i$. With the selected components, the actual residual is

$$r_{q,i} = N_{\vartheta,q}(Q_i, 0) + V_{4,q}(Q_i) - Y_i, \qquad r_{p,l} = N_{\vartheta,p}(\bar{q}_l, G(\bar{q}_l)\bar{v}_l).$$

Here G and V_4 are the same prescribed scalar graph as in (S12). The resulting signed residual obeys

$$r_\vartheta = \mathcal{L} e_\vartheta - \xi. \tag{S14}$$

All label, state, clock, discretization and numerical allowances needed for this identity must be included in a common fidelity certificate. When nominal and true anchors differ, their joint interval enclosure or a sound state-transport allowance is required. Evaluation widths are retained separately from physical label errors.

Let W be a declared positive diagonal row weight, applied to the residual, label errors and observation remainders alike. Put $\widetilde{\mathcal{L}} = W\mathcal{L}$, $A = \widetilde{\mathcal{L}}\chi^{\mathsf{T}}$ and $\widetilde{r}_\vartheta = W r_\vartheta$. Each physical derivative includes its factor $1/s_j$. The observation design and its inverse are independent of the candidate, although they may depend on the observed input geometry. Every candidate's model and remainder certificates refer to this same declared design. For the square design suppose a fixed exact matrix R satisfies

$$\sup_A \|I - RA\|_\infty \le \eta < 1, \qquad J_A = (RA)^{-1}R, \qquad \kappa = \eta/(1-\eta), \tag{S15}$$

where the supremum covers the actual joint anchor enclosure. Column permutations, row order and weights are common to all terms. Write $F_\alpha(x) = \partial_x^\alpha \chi(x)^{\mathsf{T}}$ and define

$$C_{\alpha,\vartheta}(x) = \partial_x^\alpha(\rho_\vartheta - U)(x) - F_\alpha(x) J_A \widetilde{\mathcal{L}}(\rho_\vartheta - U). \tag{S16}$$

Lemma S12. Pathwise output-error bounds. *Let Ω be a real or complex target rectangle, with valid modulus bounds $|x_j| \le r_j$. Define*

$$g_{\alpha,\beta} = \prod_{j=1}^{4} \frac{(\beta_j)_{\alpha_j} r_j^{\beta_j - \alpha_j}}{s_j^{\beta_j}}, \quad G_\alpha = \sum_\beta g_{\alpha,\beta}, \qquad \mathcal{G}_\alpha(v) = \sum_\beta g_{\alpha,\beta} v_\beta + G_\alpha \kappa \|v\|_\infty,$$

with $g_{\alpha,\beta} = 0$ if some $\beta_j < \alpha_j$. Suppose $|W\xi| \le \zeta$ and $c_{\alpha,\vartheta} \ge \sup_\Omega |C_{\alpha,\vartheta}|$ are sound. Then

$$\|\partial_x^\alpha e_\vartheta\|_\Omega \le b_{\alpha,\vartheta} := \mathcal{G}_\alpha(|R\widetilde{r}_\vartheta|) + \mathcal{G}_\alpha(|R|\zeta) + c_{\alpha,\vartheta}. \tag{S17}$$

The signed matrix–vector product in the first term is enclosed before taking absolute values. On a common fidelity event this conclusion holds simultaneously for every output having sound individual certificates, including an output selected from the same observations.

Proof. The Neumann series in (S15) gives $J_A A = I$ and $\|(RA)^{-1} - I\|_\infty \le \kappa$. By (S14),

$$Aa_\vartheta = \widetilde{r}_\vartheta + W\xi - \widetilde{\mathcal{L}}(\rho_\vartheta - U).$$

Substitution into the differentiated error decomposition gives the exact identity

$$\partial_x^\alpha e_\vartheta = F_\alpha J_A \widetilde{r}_\vartheta + F_\alpha J_A W\xi + C_{\alpha,\vartheta}.$$

For any vector y, write $J_A y = Ry + [(RA)^{-1} - I]Ry$. The monomial envelope bounds the first term by $\sum_\beta g_{\alpha,\beta}|(Ry)_\beta|$ and the second by $G_\alpha \kappa \|Ry\|_\infty$. Use $|RW\xi| \le |R|\zeta$ and the remainder bound to obtain (S17). The argument is deterministic for each data realization and uses no selection rule for ϑ. Both the observation-point remainder and the target-domain remainder remain in (S16); neither is discarded.

A prospective independent-anchor alternative. Split χ into configuration-only columns χ_q and mixed columns χ_p. Their dimensions are $(d_q, d_p) = (8, 37)$ or $(15, 114)$. Write $x_j = s_j u_j$ with fixed $s_j > 0$, and put $D_q = \mathrm{diag}(s_1, s_2)$ and $D_p = \mathrm{diag}(s_3, s_4)$. For $b = q, p$, let

$$B_b(u) = D_b \nabla_{x,b} \chi_b(x(u))^\mathsf{T}, \qquad A_b^{(i)} = \pi_b(u_i)^{-1/2} B_b(u_i),$$

where $\nabla_{x,q} = (\partial_{q_1}, \partial_{q_2})^\mathsf{T}$ at rest and $\nabla_{x,p} = (\partial_{p_1}, \partial_{p_2})^\mathsf{T}$ at moving canonical anchors. Thus B_b contains derivatives with respect to the normalized coordinates on $[-1, 1]^2$ or $[-1, 1]^4$, respectively, and A_b stacks the displayed two-row blocks. Put

$$M_b = \mathbb{E}_{\mathrm{unif}} B_b^\mathsf{T} B_b, \qquad K_b(u) = \mathrm{tr}(M_b^{-1} B_b(u)^\mathsf{T} B_b(u)).$$

The column sets exclude the respective derivative nullspaces, so $M_b \succ 0$. Fix the scales and densities $\pi_b > 0$ relative to uniform probability before drawing the anchors. Draw n_b anchors independently within each block and use row weights $\pi_b(u)^{-1/2}$. Suppose $K_b/\pi_b \le L_b$ almost everywhere. For $0 < \varepsilon_b < 1$ and $0 < \alpha_b < 1$, the sufficient count

$$n_b \ge \frac{2L_b}{\varepsilon_b^2} \log \frac{d_b}{\alpha_b} \tag{S18}$$

gives a common event $\mathcal{E}_{\mathrm{des}}$, of probability at least $1 - \alpha_q - \alpha_p$, on which

$$n_b^{-1} A_b^\mathsf{T} A_b \succeq (1 - \varepsilon_b) M_b, \qquad b = q, p. \tag{S19}$$

Each anchor contributes one positive semidefinite two-row product; the two derivative rows at an anchor need not be independent. The representation, scales, matrices, leverage functions and laws are fixed before collection. For example, $\pi_b = (1 + K_b/d_b)/2$ is a normalized full-support density and permits $L_b = 2d_b$.

Write the actual error as $e_\vartheta = \chi_q^\mathsf{T} c_{q,\vartheta} + \chi_p^\mathsf{T} c_{p,\vartheta} + w_\vartheta$. Any reference polynomial in this identity is used for verification, not as a prescribed training label. For each anchor, transform the physical residual, fidelity error and remainder gradient by the same diagonal scale and importance weight:

$$r_{b,\vartheta}^{(i)} = \pi_b(u_i)^{-1/2} D_b r_{b,\vartheta}^{\mathrm{phys,(i)}}, \qquad \xi_b^{(i)} = \pi_b(u_i)^{-1/2} D_b \xi_b^{\mathrm{phys,(i)}},$$
$$(\mathcal{L}_b w_\vartheta)^{(i)} = \pi_b(u_i)^{-1/2} D_b \nabla_{x,b} w_\vartheta(x(u_i)).$$

Here the physical block residual has the sign convention $r_{b,\vartheta}^{\mathrm{phys,(i)}} = \nabla_{x,b} e_\vartheta(x(u_i)) - \xi_b^{\mathrm{phys,(i)}}$. The stacked block residual identity is therefore

$$r_{b,\vartheta} = A_b c_{b,\vartheta} + \mathcal{L}_b w_\vartheta - \xi_b.$$

With every term scaled and weighted as above, let

$$R_{b,\vartheta} = \|r_{b,\vartheta}\|_2/\sqrt{n_b}, \quad Z_b \geq \|\xi_b\|_2/\sqrt{n_b}, \quad T_{b,\vartheta} \geq \|\mathcal{L}_b w_\vartheta\|_2/\sqrt{n_b}.$$

If

$$C_{\alpha,b} \geq \sup_{x\in\Omega}(F_{\alpha,b}M_b^{-1}F_{\alpha,b}^*)^{1/2}, \qquad W_{\alpha,\vartheta} \geq \sup_{\Omega}|\partial_x^\alpha w_\vartheta|,$$

then a second admissible budget is

$$b_{\alpha,\vartheta} = \sum_{b=q,p} C_{\alpha,b}\frac{R_{b,\vartheta}+Z_b+T_{b,\vartheta}}{\sqrt{1-\varepsilon_b}} + W_{\alpha,\vartheta}. \tag{S20}$$

Here $*$ conjugates the target-domain row. Counts in (S18) count independent anchors, not derivative rows or dependent trajectory snapshots.

Lemma S13. Common design and fidelity events. *The design assumptions above imply* (S19) *with the stated probability. On its intersection with a common event $\mathcal{E}_{\mathrm{fid}}$ supporting the fidelity allowances, the derivative bounds* (S20) *hold simultaneously for every soundly certified output. No independence between the two block events or between design and fidelity events is needed for the union bound.*

Proof. Positive definiteness follows because a vanishing rest gradient makes a configuration polynomial constant, whereas a vanishing momentum gradient makes a mixed polynomial configuration-only. The specified columns exclude both nullspaces. Moreover $\mathbb{E}K_b = d_b$, so the displayed mixture density integrates to one, is at least $1/2$, and satisfies $K_b/\pi_b = 2d_bK_b/(d_b+K_b) \leq 2d_b$. For one block, the independent matrices

$$M_b^{-1/2}B_b(u_i)^{\mathsf{T}}B_b(u_i)M_b^{-1/2}/\pi_b(u_i)$$

have expectation I, are positive semidefinite and have largest eigenvalue at most their trace L_b. The lower matrix Chernoff estimate of Lemma S4 bounds failure by $d_b\exp[-\varepsilon_b^2 n_b/(2L_b)] \leq \alpha_b$. The union bound gives the joint event. On that event the residual identity and triangle inequality imply

$$\|M_b^{1/2}c_{b,\vartheta}\|_2 \leq (R_{b,\vartheta}+Z_b+T_{b,\vartheta})/\sqrt{1-\varepsilon_b}.$$

Complex Cauchy–Schwarz applied to $F_{\alpha,b}M_b^{-1/2}M_b^{1/2}c_{b,\vartheta}$ proves (S20). Each matrix event holds for all coefficient vectors, whereas each output's actual remainder must be certified. Consequently selection of that output using the observations does not require a union bound over network parameters.

Uniform hypotheses for the conservative family. Use either of the preceding derivative budgets for $1 \leq |\alpha| \leq 3$. Define

$$\begin{aligned} \delta_0 &= \max_i b_{\mathbf{e}_i,\vartheta}, & \delta_1 &= \max_i \sum_j b_{\mathbf{e}_i+\mathbf{e}_j,\vartheta}, \\ \delta_{t1} &= \sum_{i,j} b_{\mathbf{e}_i+\mathbf{e}_j,\vartheta}, & \delta_2 &= \max_i \sum_{j,k} b_{\mathbf{e}_i+\mathbf{e}_j+\mathbf{e}_k,\vartheta}. \end{aligned} \tag{S21}$$

These bound Y_ϑ, DY_ϑ, its transpose and its ordered second derivative. If the actual learned field has bounds $(\widehat{c}_0,\widehat{c}_1,\widehat{c}_{t1},\widehat{c}_2)$ on Ω, valid uniform real-parameter inputs are

$$(c_0,c_1,c_{t1},c_2) = (\widehat{c}_0+\delta_0,\widehat{c}_1+\delta_1,\widehat{c}_{t1}+\delta_{t1},\widehat{c}_2+\delta_2). \tag{S22}$$

Every sum retains physical-coordinate factors and ordered multiplicities.

For a prescribed period-one frequency ν, consider the same output's exact finite embedding polynomial

$$P_{\vartheta,m}(\varphi,\lambda) = K_{\vartheta,0}(\varphi) + \sum_{j=1}^{m}\lambda^j U_{\vartheta,j}(\varphi), \qquad D_\nu = \nu\cdot\partial_\varphi.$$

Each response and every subsequent certificate refer to its complete preceding prefix. Let $\|\cdot\|_\rho$ denote the componentwise maximum analytic norm on the angle strip of half-width ρ; for a matrix use $\|A\|_\rho = \max_i \sum_j \sup_{\mathbb{T}^2_\rho} |A_{ij}|$, with transpose bounds supplied separately. Impose the following quantitative hypotheses. Fix retained widths $0 < \rho_\infty < \rho$.

1. The Hamiltonians in (S13) are real on real states and analytic on a common domain. For real $\lambda \in [0,1]$, the image $P_{\vartheta,m}(\mathbb{T}^2_\rho, \lambda)$ has a strict uniform tube of radius $r_{\mathrm{dom}} > 0$ in Ω. The metric is invertible there, and (S22) bounds the actual field and its derivatives on this tube.
2. The frequency satisfies $|k \cdot \nu| \geq \gamma |k|_1^{-\tau}$ for $k \in \mathbb{Z}^2 \setminus \{0\}$, with certified $\gamma > 0$, $\tau \geq 1$ and the corresponding period-one cohomological constant. For every real λ, write

$$L_\lambda = D_\varphi P_{\vartheta,m}, \quad B_\lambda = (L_\lambda^{\mathsf{T}} L_\lambda)^{-1}, \quad \mathcal{N}_\lambda = J L_\lambda B_\lambda.$$

   The Gram inverse is defined on the whole strip, and there are uniform bounds $k \geq \|L_\lambda\|_\rho$, $k^t \geq \|L_\lambda^{\mathsf{T}}\|_\rho$, $b \geq \|B_\lambda\|_\rho$ and

$$I \geq \sup_{\lambda \in [0,1]} \|\langle T_\lambda \rangle^{-1}\|_\infty, \qquad T_\lambda = \mathcal{N}_\lambda^{\mathsf{T}} J \{ DX_{H_{\vartheta,\lambda}}(P_{\vartheta,m}) \mathcal{N}_\lambda - D_\nu \mathcal{N}_\lambda \}. \tag{S23}$$

   The average is that of this varying embedding, with its signed entries and complete integration errors. Transposes are analytic transposes. Neither exact Lagrangianity nor equality with a construction frame's reduced torsion is assumed for the approximate embedding.
3. The full defect

$$\mathcal{R}_\vartheta(\varphi, \lambda) = X_{H_{\vartheta,\lambda}}(P_{\vartheta,m}) - D_\nu P_{\vartheta,m}$$

   has a certified bound $E \geq \sup_{\lambda \in [0,1]} \|\mathcal{R}_\vartheta\|_\rho$. In particular, if it is analytic on $\mathbb{T}^2_{\widehat{\rho}} \times \{|\lambda| \leq R_\lambda\}$ with $\widehat{\rho} > \rho$, $R_\lambda > 1$ and modulus at most M, write $\mathcal{R}_\vartheta = \sum_{j \geq 0} e_{\vartheta,j} \lambda^j$. For any finite set $S \subseteq \{0, \ldots, L\}$ and sound $\epsilon_j \geq \|e_{\vartheta,j}\|_\rho$, a complete admissible bound is

$$E = \sum_{j \in S} \epsilon_j + \sum_{\substack{0 \leq j \leq L \\ j \notin S}} M / R_\lambda^j + \frac{M}{R_\lambda^L (R_\lambda - 1)}. \tag{S24}$$

   Numerical Fourier coefficients retain their interval radii, all representative modes including Nyquist, and all infinite angle aliases. For an even grid size n, the complete interpolation allowance for coefficient j is

$$2 \frac{M}{R_\lambda^j} \left(\frac{1+q}{1-q} \right)^2 (2q^{n/2} - q^n), \qquad q = e^{-2\pi(\widehat{\rho} - \rho)}.$$

   Any symmetry reducing the sampling is an exact identity of the specified field and embedding. The outer product domain is certified separately; the bounds on Ω do not imply its enlargement to that domain.
4. Choose admissible strip-loss and iteration parameters of the canonical analytic a posteriori theorem, including $\ell = \rho / a_3$, $a_1 > 1$, and a positive iteration parameter ν_{iter}. From the uniform inputs just listed, recompute its Case III constants $C_E, C_{\mathrm{sym}}, C_K, C_B, C_{T^{-1}}, C_2$. Choose $\sigma_K > k$, $\sigma_{K^t} > k^t$, $\sigma_B > b$ and $\sigma_T > I$. All eight dimensionless tests must be strictly below one:

$$\begin{aligned}
g_1 &= \frac{(a_1 a_3)^{4\tau} C_E E}{\gamma^4 \rho^{4\tau}}, & g_2 &= \frac{E}{\ell \nu_{\mathrm{iter}}}, & g_3 &= \frac{2 C_{\mathrm{sym}} E}{\gamma \ell^{\tau+1}}, \\
g_4 &= \frac{2 C_K E}{(\sigma_K - k) \gamma^2 \ell^{2\tau+1} (1 - a_1^{1-2\tau})}, & g_5 &= \frac{4 C_K E}{(\sigma_{K^t} - k^t) \gamma^2 \ell^{2\tau+1} (1 - a_1^{1-2\tau})}, & & \\
g_6 &= \frac{C_B E}{(\sigma_B - b) \gamma^2 \ell^{2\tau+1} (1 - a_1^{1-2\tau})}, & g_7 &= \frac{C_{T^{-1}} E}{(\sigma_T - I) \gamma^2 \ell^{2\tau+1} (1 - a_1^{1-2\tau})}, & & \\
g_8 &= \frac{C_K E}{r_{\mathrm{dom}} \gamma^2 \ell^{2\tau} (1 - a_1^{-2\tau})}. & & & &
\end{aligned} \tag{S25}$$

   The constants and auxiliary parameters have the conventions of Section S6; they belong to these uniform inputs, rather than to a different Hamiltonian or embedding.

5. The input real embeddings and the theorem's corrected real embeddings satisfy a sound uniform embedding test, including the C^0 correction $\Delta = C_2 E/(\gamma^2\rho^{2\tau})$ and its retained-strip derivative allowance. This may be verified by the normalized harmonic phase criterion with the correction added to both norm budgets.

Theorem S14. Learning-to-family acceptance on a common event. *Suppose a common fidelity event $\mathcal{E}_{\mathrm{fid}}$ has probability at least $1-\alpha_{\mathrm{fid}}$. On this event let either the strict finite observation certificate of Lemma S12 apply, or let the independent-anchor construction satisfy (S18) and Lemma S13. An output is accepted only when its own sound derivative, remainder and domain certificates give (S21) and all five uniform hypotheses above are verified for that same output, reference and complete embedding prefix.*

On the corresponding common good event, every accepted output has the certified derivative bounds and, for every real $\lambda \in [0,1]$, a real analytic invariant torus $K^*_{\vartheta,\lambda}$ with the prescribed frequency:

$$X_{H_{\vartheta,\lambda}}(K^*_{\vartheta,\lambda}) = D_\nu K^*_{\vartheta,\lambda}, \qquad \|K^*_{\vartheta,\lambda} - P_{\vartheta,m}(\cdot,\lambda)\|_{\rho_\infty} \le \Delta. \tag{S26}$$

The constant Δ is uniform in λ. In particular $\lambda = 1$ gives an invariant torus of the prescribed conservative reference H_*.

For any measurable data-dependent rule that returns an output or rejects, including one using the same observations for training and selection, let A *denote acceptance and* F *the event that a stated derivative or conservative-family conclusion for the returned output is false. Then*

$$\mathbb{P}(\mathsf{A}\cap\mathsf{F}) \le \begin{cases} \alpha_{\mathrm{fid}}, & \textit{strict finite observation route},\\ \alpha_{\mathrm{fid}}+\alpha_q+\alpha_p, & \textit{independent-anchor route}. \end{cases} \tag{S27}$$

If all fidelity allowances are deterministic, the first route is a deterministic implication. The theorem supplies neither a lower bound on acceptance probability nor a guarantee that optimization produces an acceptable output. It makes no conditional-confidence assertion given acceptance.

Proof. Fix a realization in the common good event and any accepted output. Lemma S12, or Lemma S13, bounds every required derivative of the actual scalar e_ϑ. Canonical multiplication by J only permutes coordinates and changes signs. The triangle inequality and ordered derivative sums therefore give (S21). For real $0 \le \lambda \le 1$, the identity $X_{H_{\vartheta,\lambda}} = X_{\widehat{H}_\vartheta} + \lambda Y_\vartheta$ then proves (S22) on the certified inner tube.

For completeness, Cauchy's estimate on the separate product domain gives $\|e_{\vartheta,j}\|_{\widehat{\rho}} \le M/R_\lambda^j$. The triangle inequality on $|\lambda| \le 1$, followed by summation of the infinite geometric tail, proves (S24). The Fourier interpolation allowance adds all omitted modes and their aliases, while interval sample and transform widths remain in the finite interpolant. No coefficient above the input polynomial degree is set to zero in this argument.

For each fixed real λ, the certified common domain, nonresonance, Gram and actual mean inverse bounds satisfy the analytic canonical a posteriori theorem's hypotheses. Its constants are bounded by the recomputed uniform constants in (S25); the eight strict inequalities provide its contraction and preservation conditions. That theorem yields a real analytic invariant map with the bound Δ. The final embedding test gives the asserted real torus embedding. Applying this deterministic implication separately to each real λ proves (S26) with the same bound. Analytic dependence of the exact tori on λ is not needed for this statement.

All implications just established hold simultaneously for every accepted output on the common event. A false accepted conclusion is therefore contained in its complement. The common fidelity bound, and in the independent-anchor case the union bound of Lemma S13, prove (S27). No union over possible selected network parameters is required.

The independent-anchor assertion requires its specified sampling law and common fidelity event. A collection of dependent trajectories does not acquire that law by contributing many time nodes. A successful conditioning event supplies the coefficient inequality; small observed residuals and actual remainders are additional acceptance requirements. These conclusions concern the specified finite-dimensional reference equations and are neutral with respect to comparisons between real and complex parametrizations.

Proposition S15. A separate dissipative port structure. *On a real domain $\mathcal{D} \subset \Omega \cap \mathbb{R}^4$ with $G = SS^{\mathsf{T}} \succ 0$, let a configuration-only complex head define*

$$\widehat{M}_\psi(q) = \mathrm{Re}(L_\psi(q)L_\psi(q)^*), \quad \widehat{R}_\psi = S\widehat{M}_\psi S^{\mathsf{T}}, \quad \widehat{v} = \partial_p \widehat{H}_\vartheta = G^{-1}p + N_{\vartheta,p}.$$

For the specified magnetic port $g(q) = d\cos(d^{\mathsf{T}}q)$ and the learned port-Hamiltonian equations

$$q' = \widehat{v}, \qquad p' = -\partial_q \widehat{H}_\vartheta - \widehat{R}_\psi \widehat{v} + g(q)u,$$

the head is real symmetric positive semidefinite and

$$\frac{d\widehat{H}_\vartheta}{d\tau} = -\widehat{v}^{\mathsf{T}}\widehat{R}_\psi\widehat{v} + u\, g^{\mathsf{T}}\widehat{v}. \tag{S28}$$

For the reference plant with $v_* = G^{-1}p$ and $R_* = SM_*S^{\mathsf{T}} \succeq 0$, set $e_p = N_{\vartheta,p} = \widehat{v} - v_*$. If $\|\widehat{M}_\psi - M_*\|_2 \le \delta_M$ is separately certified, and $a \ge \|S^{\mathsf{T}}\widehat{v}\|_2$, $b \ge \|S^{\mathsf{T}}e_p\|_2$ and $\bar{m} \ge \|\widehat{M}_\psi\|_2$, then

$$\begin{aligned} |g^{\mathsf{T}}v_* - g^{\mathsf{T}}\widehat{v}| &\le \sum_j |g_j|\, b_{\mathbf{e}_{2+j},\vartheta}, \\ v_*^{\mathsf{T}}R_*v_* &\ge \widehat{v}^{\mathsf{T}}\widehat{R}_\psi\widehat{v} - 2\bar{m}ab - \delta_M(a+b)^2. \end{aligned} \tag{S29}$$

These port identities do not apply the conservative KAM theorem to a dissipative system. Reference-plant safety additionally requires the energy, state enclosure, guard, command and intersample hypotheses of the physical-energy safety theorem.

Proof. For a real vector z, $z^{\mathsf{T}}\widehat{M}_\psi z = \|L_\psi^* z\|_2^2 \ge 0$. The two Hamiltonian terms cancel by skew symmetry, proving (S28) with the full learned velocity. Since $U_p = 0$, the learned-to-reference velocity error is exactly $e_p = \partial_p e_\vartheta = N_{\vartheta,p}$. The first inequality of (S29) follows from its componentwise derivative bounds. For the second put $z = S^{\mathsf{T}}\widehat{v}$ and $\eta = S^{\mathsf{T}}e_p$. Expand $(z-\eta)^{\mathsf{T}}M_*(z-\eta)$ about $\widehat{M}_\psi$, retain its nonnegative quadratic term in η, and bound the cross term and matrix error by $2\bar{m}ab$ and $\delta_M(a+b)^2$. All momentum-error terms are retained. The reference physical-power identity is $H_*' = u\, g^{\mathsf{T}}v_* - v_*^{\mathsf{T}}R_*v_*$; its sampled safety implications require the separate stated hypotheses.

Canonical conventions for the conservative continuation. The following identifies the canonical hypotheses used in Theorem S14 with those of Haro–Luque, arXiv:1711.05515v1, Theorem 3.1 and Remark 3.3. Put

$$J_s = \begin{pmatrix} 0 & I_2 \\ -I_2 & 0 \end{pmatrix}, \qquad \Omega_{\mathrm{HL}} = -J_s, \qquad g_{\mathrm{amb}}(u,v) = u^{\mathsf{T}}v.$$

The symplectic form is exact, with primitive $\sum_{j=1}^2 p_j\, dq_j$, and the Hamiltonian convention is $\Omega_{\mathrm{HL}}X_H = (DH)^{\mathsf{T}}$, hence $X_H = J_s\nabla H$. In the canonical compatible Case III, $J_{\mathrm{HL}} = \Omega_{\mathrm{HL}} = -J_s$ and the auxiliary metric matrix is I_4. This auxiliary metric is independent of the mechanical inertia $G_8(q)$ in $\frac{1}{2}p^{\mathsf{T}}G_8(q)^{-1}p$.

For a fixed real parameter λ, write $L = D_\varphi P_m(\varphi,\lambda)$ and $B = (L^{\mathsf{T}}L)^{-1}$, using analytic transposes. The saved normal and torsion conventions are

$$N_s = J_sLB, \qquad T_s = N_s^{\mathsf{T}}J_s\{DX_{H_\lambda}(P_m)N_s - D_\nu N_s\}.$$

The theorem's normal satisfies $N_{\mathrm{HL}} = -N_s$. Its torsion is therefore

$$\begin{aligned} T_{\mathrm{HL}} &= (-N_s)^{\mathsf{T}}(-J_s)\{-DX_{H_\lambda}(P_m)N_s + D_\nu N_s\} \\ &= -T_s. \end{aligned}$$

Thus $\langle T_{\mathrm{HL}}\rangle^{-1} = -\langle T_s\rangle^{-1}$, and their induced infinity norms agree. All entrywise analytic majorants and transpose norms used by the canonical constants are invariant under these fixed sign changes. This identifies the saved inverse bound with hypothesis H4; it does not identify the two torsion matrices themselves. No exact Lagrangianity of the approximate P_m is presumed.

Verification of the analytic theorem's hypotheses. For each fixed real $\lambda \in [0,1]$, the common real-type holomorphic state domain and the uniform field bounds in (S22) provide H1. Canonical geometric structures are constant, so their nonzero zeroth-order bounds are one and their positive-order derivative bounds are zero. Since $n = d = 2$, no additional first integrals are required; one may choose the auxiliary conserved function $c = 0$. Scalar Hamiltonian-gradient norms, if needed, are bounded by four times the corresponding maximum component field bound. The nonconstant mechanical inertia is retained inside H_λ and its field derivatives throughout.

The complete finite Fourier prefix, its exact conjugate reality, and its uniformly positive distance from the boundary of the common inner state domain give H2. Whole-strip complex Gram invertibility gives the full-rank condition H3. Its bound, and the separate bounds for L and L^{T}, receive the strict auxiliary margins σ_B, σ_K and σ_{K^t}. The actually certified continuous signed mean, transported for the same complete prefix and every real $\lambda \in [0,1]$, gives H4 under the sign mapping above. A finite parameter scan or a desired inverse target cannot replace this premise. The fixed exact period-one frequency has its all-integer bounded-continued-fraction lower bound; together with the uniform period-one cohomological estimate it gives H5 with $\tau = 1$ and the certified γ, c_R.

The complete ordinary parameter-series defect, including every computed coefficient and all infinite parameter and angle tails, supplies the theorem's error norm. For each real λ, the same uniform constants and all eight strict Case III tests therefore give the theorem's invariant map and its common C^0 correction bound. The corrected harmonic phase test separately proves that the real map is an embedding. Its derivative allowance uses the Cauchy loss on the final strip, including the factor $2\|S^{-1}\|\Delta/\rho_\infty$ in the derivative norm. Applying the theorem separately to each real parameter proves precisely the quantified per-parameter conclusion of (S26). It does not add analytic parameter dependence, a positive-measure set of frequencies, or a prescribed common energy level.

Identification of the reference endpoint. For the specified scalar graph, let $s = d^{\mathsf{T}} q$ and

$$V_4(q) = \tfrac{1}{2} q^{\mathsf{T}} K_b q + \tfrac{1}{2} s^2 - \tfrac{1}{24} s^4, \qquad U(q) = 1 - \cos s - \tfrac{1}{2} s^2 + \tfrac{1}{24} s^4.$$

The family is an exact identity of real-analytic functions,

$$H_\lambda = T_{G_8} + V_4 + (1-\lambda) N + \lambda U.$$

Consequently

$$H_1 = \tfrac{1}{2} p^{\mathsf{T}} G_8(q)^{-1} p + \tfrac{1}{2} q^{\mathsf{T}} K_b q + 1 - \cos(d^{\mathsf{T}} q).$$

Both N_q and N_p cancel at this endpoint; N_p is retained for every intermediate parameter and throughout the continuation certificates. The endpoint theorem concerns this prescribed finite-Gauss conservative reference. Correspondence with a continuum rod, uncertain measured plant, dissipative trajectory or sampled controller requires the respective additional certificates.

This component is a conditional theorem application. Numerical acceptance requires a completed same-prefix whole-strip residual, the corresponding scalar assembly, and their independent final review; none is inferred from the present convention check.

S8 Numerical application to the full conservative family

The following application instantiates Theorem S14 and the canonical conventions above for the same selected 736-coordinate GC output and the same 129-dimensional finite observation certificate. It uses no additional fit or target coefficient as a training label. All stored network buffers and Fourier coefficients are interpreted as exact constants of their declared graph.

Actual prefix and uniform geometry. The base embedding K_0 is the 8064-mode rational Fourier polynomial used for the learned-system theorem. Each of the ten response polynomials U_j is computed from the complete preceding prefix, and the subsequent certificates use

$$P_{10}(\varphi, \lambda) = K_0(\varphi) + \sum_{j=1}^{10} \lambda^j U_j(\varphi).$$

The retained angle half-width is $\rho = 1/40$ and the outer width is $\widehat{\rho} = 1/10$. Uniform geometry, analytic Gram invertibility and the varying continuous signed mean are verified for every real $\lambda \in [0,1]$. The inverse mean bound is

$$\sup_{0\le\lambda\le1} \|\langle T_\lambda\rangle^{-1}\|_\infty < 25539.514.$$

It is obtained from the signed mean at the complete degree-three prefix and a certified transport through the remaining actual responses. It is not the inverse mean at K_0 or a finite parameter scan. The observation-derived first-, second- and third-order energy-error bounds enter the uniform field constants in (S22), with all momentum derivatives retained.

Complete residual series. Write the ordinary parameter series of the exact composed defect as

$$\mathcal{R}_{10}(\varphi,\lambda) = X_{H_\lambda}(P_{10}) - D_\nu P_{10} = \sum_{j\ge0} r_j(\varphi)\lambda^j.$$

Vector analytic norms here take the maximum of the component suprema on the whole retained angle strip. Table S1 gives upward-rounded bounds on $\|r_j\|_{1/40}$. The zeroth coefficient comes from the complete learned-field strip certificate, and the first from a complete 448×448 Fourier calculation. For each coefficient $2 \le j \le 14$, a complete 384×384 Fourier enclosure retains every sample ball and representative, including the Nyquist modes. The exact half-shift reconstruction, angular weights and all infinite angle aliases are included. An independent reverse-axis transform verifies all complete Fourier coefficient bounds. Separate raw-model replays at two actual grid points and one fresh nongrid point check the composed coefficient evaluator against the original neural and mechanical graph.

Table S1. Whole-strip ordinary parameter-coefficient bounds for the same complete P_{10}. Display rounding is upward; the sum is formed from the exact rational endpoints before rounding.

Order j	Upper bound on $\|r_j\|_{1/40}$
0	1.19552×10^{-42}
1	7.09445×10^{-43}
2	1.36625×10^{-43}
3	2.66122×10^{-46}
4	5.18925×10^{-49}
5	1.01274×10^{-51}
6	1.97800×10^{-54}
7	3.86361×10^{-57}
8	7.54577×10^{-60}
9	1.47356×10^{-62}
10	2.87754×10^{-65}
11	1.48568×10^{-41}
12	5.33047×10^{-45}
13	2.36871×10^{-48}
14	1.18583×10^{-51}

The finite degree of P_{10} does not truncate the nonlinear composed residual at degree ten. In particular its eleventh coefficient is retained. A direct product-domain certificate proves holomorphicity for $\varphi \in \mathbb{T}^2_{1/10}$ and $|\lambda| \le 512$, together with the residual majorant $M < 0.937873$. This certificate evaluates the full prescribed inertia and raw constrained neural graph; it does not assume containment in the older local state tube. Cauchy's estimate therefore gives

$$\sum_{j>14} \|r_j\|_{1/40} \le \frac{M}{512^{14}(512-1)} < 2.158 \times 10^{-41}. \tag{S30}$$

Consequently, uniformly for real $\lambda \in [0,1]$,

$$\|\mathcal{R}_{10}(\cdot,\lambda)\|_{1/40} \le \sum_{j=0}^{14} \|r_j\|_{1/40} + \frac{M}{512^{14}(512-1)} < 3.848 \times 10^{-41}. \tag{S31}$$

The full learning-error, geometry, domain and actual-mean inputs give a sufficient complete-defect budget greater than 9.303×10^{-40}.

Strict inequalities and embedding. The eight Case III inequalities are evaluated anew with the exact complete defect from (S31), rather than a pointwise residual or a desired target. Their upward-rounded values are in Table S2; each must be strictly less than one. The largest value is below 0.04136.

Table S2. The eight actual uniform strict tests for P_{10}.

Test	Upper bound
Quadratic contraction	4.13578×10^{-2}
Iteration allowance	1.02610×10^{-38}
Approximate symplectic inverse	7.45219×10^{-32}
DP_{10} preservation	1.07339×10^{-17}
DP_{10}^{T} preservation	1.07352×10^{-17}
Gram-inverse preservation	1.58011×10^{-16}
Mean-inverse preservation	2.18268×10^{-7}
Domain-distance preservation	2.15032×10^{-19}

The resulting uniform C^0 correction is $\Delta < 3.949 \times 10^{-22}$ on the final strip of width $1/400$. The remaining state-domain distance exceeds 0.001836. Let S_h be the fixed real invertible harmonic normalization used to construct K_0, and define

$$\kappa_a(\varphi) = a\big(\cos(2\pi\varphi_1), \cos(2\pi\varphi_2), -\sin(2\pi\varphi_1), -\sin(2\pi\varphi_2)\big)^{\mathsf{T}},$$
$$K_{\mathrm{harm}} = S_h \kappa_a, \quad a = \frac{5764607523034235}{144115188075855872} \simeq 0.04.$$

Put $s_h = \|S_h^{-1}\|_\infty$ and $\rho_\infty = 1/400$. The actual certified upper bounds obey

$$\eta_0 \geq \sup_{\lambda\in[0,1]} \|S_h^{-1} P_{10} - \kappa_a\|_{\rho_\infty}, \qquad \eta_1 \geq \sup_{\lambda\in[0,1]} \|D_\varphi (S_h^{-1} P_{10} - \kappa_a)\|_{\rho_\infty}.$$

These include the base harmonic remainder and all ten responses; they are upper bounds, rather than assumed exact norms. Define

$$b_0 = \eta_0 + s_h \Delta, \qquad b_1 = \eta_1 + \frac{2 s_h \Delta}{\rho_\infty}.$$

The added derivative allowance follows by Cauchy's estimate at the real torus, summing the two angle derivatives of the corrected map. The certified quantities satisfy $a > 2b_0$ and

$$\frac{2b_1 + (88/7)b_0}{6(a - 2b_0)} < 0.005686 < \frac{1}{2}.$$

Thus the corrected real maps are embeddings, as well as invariant maps.

Application and endpoint. The fixed exact Diophantine frequency, canonical structures, common analytic domain, full-rank geometry, actual varying mean and the strict inequalities now satisfy all hypotheses of Theorem S14. Applying it separately to every real $\lambda \in [0, 1]$ proves the invariant tori and common displacement bound in article Theorem 4. At $\lambda = 1$ both N_q and N_p cancel exactly, leaving the prescribed conservative finite-Gauss reference. This application uses the realized deterministic observation certificate; the separate finite-base anchor experiment is not required for this conclusion. Its completed numerical-reference application is reported in Supplementary Section S5; the continuous-base population-risk protocol retains its additional unverified premises. The sampled dissipative plant is covered by its separate physical-energy proof.

S9 Complex-gradient descent with a strict descent margin

Theorem 3 in the published version of Zhang et al. (2022) motivates complex-gradient optimization, but a stationary-point conclusion requires a strict descent margin. The following convention-explicit statement also applies to a smooth CHNN regression objective.

Proposition S16. Complex descent. *Let $\mathcal{L} : \mathbb{C}^P \simeq \mathbb{R}^{2P} \to \mathbb{R}$ be bounded below and have an L-Lipschitz real gradient on every segment traversed by the iterates. For $w = a + ib$, define $G(w) = \nabla_a \mathcal{L} + i\nabla_b \mathcal{L} = 2\partial\mathcal{L}/\partial\bar{w}$. Choose a constant $\rho \in \mathbb{C}$ with $\kappa = \operatorname{Re}\rho - (L/2)|\rho|^2 > 0$, and update $w_{t+1} = w_t - \rho G(w_t)$. Then*

$$\mathcal{L}(w_{t+1}) \le \mathcal{L}(w_t) - \kappa\|G(w_t)\|_2^2, \qquad \lim_{t\to\infty} \|G(w_t)\|_2 = 0,$$

and

$$\min_{0\le t<T} \|G(w_t)\|_2^2 \le \frac{\mathcal{L}(w_0) - \inf \mathcal{L}}{\kappa T}.$$

Proof. Under realification, multiplication by $\rho = u + iv$ is $uI + vJ_c$, with $J_c^\top = -J_c$ and $J_c^\top J_c = I$. Hence the update has inner product $-u\|G\|^2$ with the real gradient and squared norm $|\rho|^2\|G\|^2$. The real descent lemma gives the first inequality. Summing it and using the lower bound for $\mathcal{L}$ gives $\kappa \sum_{t\ge 0} \|G(w_t)\|^2 \le \mathcal{L}(w_0) - \inf \mathcal{L}$. Square summability proves convergence of the gradient norm and the minimum bound. The result asserts convergence to stationarity in gradient norm, not convergence to a global minimum or to a particular parameter vector.

For a real step this condition is $0 < \rho < 2/L$ under the stated convention. The case $\rho = 0$, allowed by a non-strict printed step-size interval, cannot imply gradient convergence: for $\mathcal{L}(w) = |w|^2$ and $w_0 \neq 0$, every iterate equals w_0 and $G(w_t) = 2w_0 \neq 0$. Nonsmooth complex activations require separate treatment. The present literal complex $\tanh$ networks are smooth as real maps wherever their poles are excluded. On a bounded parameter region with a uniform pole margin, the smooth regression objective admits finite local Lipschitz bounds. Applying the proposition to a training sequence would still require a verified common iterate region and the strict step-size margin above.

This realification argument is an optimization component motivated by Zhang et al. (2022); it does not transfer that paper's exponential-loss learning conclusions to the present mechanical regression. The actual GC conservative fit uses 400 full-batch Adam updates on its 736 real parameter coordinates, with the previously fitted PSD matrix head fixed. Training-only checkpoint selection returns update 385. The independent matrix-head fit uses damped Gauss–Newton steps with Armijo search. Its fitting auxiliary quantities belong to that head-identification problem, not to the GC conservative objective. Neither algorithm is the constant-complex-step iteration of this proposition. The finite Adam record and the head's accepted decreases therefore do not establish the proposition's gradient-norm convergence conclusion. The identification-error and a-posteriori KAM results are independent of such convergence: they do not assume that the accepted frozen parameters are stationary or globally optimal.

S10 A conditional learning-to-analytic-KAM implication

We relate the energy generalization estimate of Chen et al. (2022) to the analytic invariance residual required by Haro and Luque (2019, Theorem 3.1). The argument combines an interior gradient estimate with interpolation on a complex torus strip. This conditional statistical route requires hypotheses on the sampling distribution and the entire hypothesis class. A deterministic a-posteriori certificate for an individual learned Hamiltonian has a distinct scope: it establishes the existence of an invariant torus of that Hamiltonian without a population-risk or generalization statement.

For the specified four-coordinate model the target is $H_\star = T_{G_8} + V_4 + U(q)$, and the learned energy is $H_\vartheta = T_{G_8} + V_4 + N_\vartheta(q,p)$. Their shared kinetic graph and canonical normalization are retained; in particular, no derivative $N_{\vartheta,p}$ is set to zero.

S10.1 The conditional statistical input and its energy gauge

Work in one fixed canonical coordinate and time normalization, with phase dimension $m = 2n$ and $n \ge 2$. Let $D \subset \mathbb{R}^m$ be a bounded, connected Lipschitz domain. The conservative target is $H_\star$, and $\mathcal{H} = \{H_\vartheta : \vartheta \in \Theta\}$ is a hypothesis class fixed before the data are drawn. All energies are real valued on D, even when the network parameters are complex. Fix a finite exponent $p > m$ and a confidence parameter $0 < \alpha < 1$. Assume $H_\star, H_\vartheta \in W^{1,p}(D)$, using their continuous representatives, and define the pointwise conservative loss

$$\ell_\vartheta(x) = \|\nabla H_\vartheta(x) - \nabla H_\star(x)\|_p^p. \tag{S32}$$

Assume that $X_1, \dots, X_N$ are independent and identically distributed with law P supported on D, whose density relative to Lebesgue measure satisfies $f_P \geq m_P > 0$. Assume $0 \leq \ell_\vartheta \leq L_{\max}$ uniformly on the entire class and domain. Let $\overline{\mathfrak{R}}_N$ be a valid upper bound for the empirical Rademacher complexity of this loss class, with the normalization in Lemma 2 of Chen et al. (2022). Define

$$\widehat{L}_{p,N}(\vartheta) = \frac{1}{N}\sum_{i=1}^{N} \ell_\vartheta(X_i),$$
$$A_N(\vartheta, \alpha) = \widehat{L}_{p,N}(\vartheta) + 2\overline{\mathfrak{R}}_N + 3L_{\max}\sqrt{\frac{2\log(4/\alpha)}{N}}. \tag{S33}$$

Under these assumptions the cited generalization bound supplies an event $\mathcal{G}_\alpha$, with $\mathbb{P}(\mathcal{G}_\alpha) \geq 1 - \alpha$, on which $\mathbb{E}_P \ell_\vartheta \leq A_N(\vartheta, \alpha)$ simultaneously for every $\vartheta \in \Theta$. This uniformity is essential when the same data select the fitted parameters.

Define the gauge-fixed error

$$e_\vartheta = H_\vartheta - H_\star - c_\vartheta, \qquad c_\vartheta = \frac{1}{|D|}\int_D (H_\vartheta - H_\star)\, dx. \tag{S34}$$

Let C_P satisfy $\|e\|_{L^p(D)} \leq C_P \|\nabla e\|_{L^p(D)}$ for mean-zero functions, and let C_S be a valid constant in $W^{1,p}(D) \hookrightarrow C^0(\overline{D})$, using $\|e\|^p_{W^{1,p}} = \|e\|^p_{L^p} + \|\nabla e\|^p_{L^p}$.

Proposition S17. Conditional energy bound. *On $\mathcal{G}_\alpha$, simultaneously for every member of the class,*

$$\|e_\vartheta\|_{C^0(\overline{D})} \leq \varepsilon_\vartheta,$$
$$\varepsilon_\vartheta := C\left(\frac{A_N(\vartheta, \alpha)}{m_P}\right)^{1/p}, \tag{S35}$$
$$C = C_S(1 + C_P^p)^{1/p}.$$

Proof. The density lower bound and the uniform risk event give

$$\int_D \|\nabla e_\vartheta\|_p^p \, dx \leq m_P^{-1}\mathbb{E}_P \ell_\vartheta \leq m_P^{-1} A_N(\vartheta, \alpha).$$

Poincare's inequality applies because (S34) has zero mean. Consequently $\|e_\vartheta\|_{W^{1,p}} \leq (1 + C_P^p)^{1/p}(A_N/m_P)^{1/p}$. The Sobolev embedding, valid because $p > m$, proves the assertion.

The exponent $1/p$ in (S35) follows from the pth-power definition of the loss (S32); a linear dependence on that loss would require different definitions. For the four-dimensional phase space considered here, this first-order embedding requires $p > 4$. Here p is the integrability exponent in $W^{1,p}$, not a derivative order. Using weak-increment observations or a combined Hamiltonian–damping residual to bound $\widehat{L}_{p,N}$ additionally requires conservative-gradient label-error estimates, including errors in dissipation and input subtraction. The trajectory sampling scheme, with consecutive and overlapping windows, does not meet the iid state-sampling hypothesis of Proposition S17.

S10.2 A real gradient bound with explicit domain loss

Proposition S18. Interior gradient estimate from energy values. *Let $e \in C^2(D)$ satisfy $\sup_D |e| \leq \varepsilon$ and $\max_j \sup_D |\partial_{jj} e| \leq B$, with $B \geq 0$. Let $S \subset D$ and $r > 0$ satisfy $x + [-r, r]\mathbf{e}_j \subset D$ for every $x \in S$ and coordinate unit vector $\mathbf{e}_j$. Then*

$$\sup_{x \in S} \|\nabla e(x)\|_\infty \leq b_r(\varepsilon, B) := \inf_{0 < h \leq r}\left(\frac{\varepsilon}{h} + \frac{Bh}{2}\right). \tag{S36}$$

For $B > 0$ this is

$$b_r(\varepsilon, B) = \begin{cases} \sqrt{2B\varepsilon}, & 0 \leq \varepsilon \leq Br^2/2, \\ \varepsilon/r + Br/2, & \varepsilon > Br^2/2. \end{cases} \tag{S37}$$

For $B = 0$, take $b_r(\varepsilon, 0) = \varepsilon/r$.

Proof. For $0 < h \le r$, the fundamental theorem of calculus gives

$$\left|\partial_j e(x) - \frac{e(x+h\mathbf{e}_j) - e(x-h\mathbf{e}_j)}{2h}\right| \le \frac{1}{2h}\int_{-h}^{h} |\partial_j e(x+t\mathbf{e}_j) - \partial_j e(x)|\, dt \le \frac{Bh}{2}.$$

The difference quotient has magnitude at most ε/h. Taking the infimum proves (S36). For $B\varepsilon > 0$, the unconstrained minimizer is $h = \sqrt{2\varepsilon/B}$; otherwise use $h = r$ or take the appropriate zero limit. This proves (S37).

The estimate only needs bounds on the pure second derivatives of the *error*; a full Hessian operator bound is a stronger sufficient condition. A certified sum of target and network Hessian bounds also suffices. An additive energy constant has no effect on this step.

Let $J = \left(\begin{smallmatrix} 0 & I_n \\ -I_n & 0 \end{smallmatrix}\right)$, and fix a reference embedding $K_0 : \mathbb{T}^n \to D$ and frequency $\omega \in \mathbb{R}^n$. Suppose its real image has the coordinate-segment margin in Proposition S18, and that an independently justified target residual obeys

$$\|J\nabla H_\star(K_0) - DK_0\omega\|_0 \le \delta_\star. \tag{S38}$$

The subscript 0 denotes the supremum over real angles, with the maximum norm for vector components. Since $\|J\|_{\infty\to\infty} = 1$, the learned invariance residual satisfies

$$\begin{aligned} E_\vartheta &= J\nabla H_\vartheta(K_0) - DK_0\omega, \\ \|E_\vartheta\|_0 &\le \delta_\star + b_r(\varepsilon_\vartheta, B) =: \delta_\vartheta \quad \text{on } \mathcal{G}_\alpha. \end{aligned} \tag{S39}$$

In particular, a certificate for an invariant torus of H_ϑ cannot be substituted for the target residual in (S38). If K_0 is an exact torus of $H_\star$, then $\delta_\star = 0$; otherwise its defect must be included.

The actual finite-observation certificate also admits a deterministic application. Suppose Lemma S12 supplies the first-derivative bounds for the same frozen full-phase $H_\vartheta, H_\star$ on the real image $K_0(\mathbb{T}^n)$. Taking their physical-coordinate component maximum as in (S21) gives G_{det} and hence $\|E_\vartheta\|_0 \le \delta_\star + G_{\mathrm{det}}$ directly. The identical known kinetic metric in the two Hamiltonians is retained in this use of the deterministic theorem. Substitution of G_{det} for $b_r(\varepsilon_\vartheta, B)$ in the analytic step below gives a deterministic residual bound without a statistical assumption. Its applicability requires the actual configuration and momentum observation residuals, label fidelity, signed observation-point remainders, inverse correction and target-domain remainder on the common domain. The GC conservative fit has no profiled potential nuisance. A small floating-point weak loss does not supply these hypotheses. No iid probability interpretation is attached to correlated windows.

S10.3 Analytic continuation of the residual with a certified outer bound

Write $\mathbb{T}^n_R = \{\theta \in \mathbb{C}^n/\mathbb{Z}^n : |\operatorname{Im}\theta|_\infty < R\}$. For a vector function, $\|F\|_R = \max_j \sup_{\mathbb{T}^n_R} |F_j|$. Assume that K_0 extends holomorphically to this strip and that $K_0(\mathbb{T}^n_R)$ lies in a pole-free complex domain of H_ϑ. Assume a *certified upper bound*

$$\|E_\vartheta\|_R \le M. \tag{S40}$$

For example, if verified constants satisfy $\sup_{K_0(\mathbb{T}^n_R)} \|J\nabla H_\vartheta\|_\infty \le C_X$ and $\|DK_0\|_R \le C_K$, then one may *choose* $M = C_X + C_K\|\omega\|_\infty$. Here the matrix norm is $\|A\|_R = \max_i \sum_j \sup_{\mathbb{T}^n_R} |A_{ij}|$, as in the analytic norm convention of Haro and Luque (2019). Point samples of a complex extension do not certify these suprema.

Lemma S19. Residual interpolation on a torus strip. *Let F be a bounded holomorphic periodic vector function on $\mathbb{T}^n_R$ with $\|F\|_0 \le \delta$ and $\|F\|_R \le M$. For $0 < \rho < R$, set $\bar\delta = \min\{\delta, M\}$. Then*

$$\|F\|_\rho \le \bar\delta^{\,1-\rho/R} M^{\rho/R}. \tag{S41}$$

If either bound is zero, the right-hand side is interpreted by continuity.

Proof. First suppose $M \geq \bar{\delta} > 0$ and that the extension is continuous on the closed strip. Given $x + iy$ with $t = |y|_\infty > 0$, put $v = y/t$. For each component define the one-variable function $g(w) = F_j(x + wv)$ on $0 \leq \operatorname{Im} w \leq R$. The real parts $x + (\operatorname{Re} w)v$ range over real angles, so the lower boundary has bound $\bar{\delta}$ and the upper boundary has bound M. The function is bounded throughout this strip. Set

$$\beta = R^{-1} \log(M/\bar{\delta}), \qquad G(w) = \bar{\delta}^{-1} g(w) e^{i\beta w}.$$

Both horizontal boundaries satisfy $|G| \leq 1$. To justify the maximum principle on this unbounded domain, use $G_\eta(w) = G(w) \exp(-\eta w^2 - \eta R^2)$, with $\eta > 0$. Its modulus is at most one on the horizontal boundaries and tends to zero on the vertical boundaries of expanding rectangles. The rectangle maximum principle, followed by expansion and then $\eta \downarrow 0$, gives $|G(w)| \leq 1$. In particular,

$$|F_j(x + iy)| = |g(it)| \leq \bar{\delta} \exp(\beta t) = \bar{\delta}^{1-t/R} M^{t/R}.$$

Since $\bar{\delta} \leq M$, this expression is nondecreasing in t. Taking $t \leq \rho$ and the componentwise supremum proves the claim. For an open outer strip, apply the argument with $\rho < R' < R$ and let $R' \uparrow R$. Zero bounds follow by replacing the bounds with positive ones and taking a limit. This also covers real angles $t = 0$.

Combining the energy and gradient estimates with the strip lemma gives, on $\mathcal{G}_\alpha$, the analytic residual bound

$$\begin{aligned} \|E_\vartheta\|_\rho &\leq \mathcal{E}_\vartheta, \\ \mathcal{E}_\vartheta &:= \bar{\delta}_\vartheta^{1-\rho/R} M^{\rho/R}, \\ \bar{\delta}_\vartheta &:= \min\{M, \delta_\vartheta\}, \end{aligned} \tag{S42}$$

where δ_ϑ is defined by (S39). There is no dimension factor for this maximum-component norm.

For the real energy readout of the complex network, analytic continuation means complexification of the real canonical variables, not application of a real-part operation at complex arguments. If $H(x) = \operatorname{Re} F(x)$ on real x and F has a holomorphic extension, its extension is $[F(z) + F^\#(z)]/2$, where $F^\#(z) = \overline{F(\bar{z})}$ is a holomorphic function obtained by conjugating coefficients. For the actual network, the jth conjugate feature pair on real phase space becomes the independent linear expressions $(Q_j/s_j + iP_j/s_{2+j})/s_0$ and $(Q_j/s_j - iP_j/s_{2+j})/s_0$, $j = 1, 2$, after complexification. Here Q, P are physical canonical coordinates, $s_1, \ldots, s_4$ are the four stored state scales, and s_0 is the stored binary64 normalization constant used by that network. Intermediate complex $\tanh$ layers must remain separated from their poles on the whole declared complex domain. Bounds for one trained network do not establish corresponding uniform bounds for a parameter class.

S10.4 The precise a-posteriori KAM endpoint

We use the ordinary theorem of Haro and Luque (2019, Theorem 3.1, equations (3.9)–(3.11), arXiv v1), specialized to $d = n \geq 2$ and canonical geometry. This specialization has no additional first integrals; their constants are zero as in the cited Remark 3.2. In this paragraph $\mathcal{B}$ denotes the complex phase domain and is distinct from the scalar Hessian bound B. The following are the corresponding H1–H5 requirements, imposed independently of the empirical training loss:

- H1. The exact symplectic and metric structures and H_ϑ extend analytically to $\mathcal{B}$, with the specified analytic bounds. In canonical coordinates the geometric structures are constant, as in the cited Remark 3.3. The required Hamiltonian bounds concern $\|DH_\vartheta\|_\mathcal{B}$, $\|X_{H_\vartheta}\|_\mathcal{B}$, $\|DX_{H_\vartheta}\|_\mathcal{B}$, $\|D^2 X_{H_\vartheta}\|_\mathcal{B}$ and $\|D(X_{H_\vartheta}^\mathsf{T})\|_\mathcal{B}$ in the cited tensor-norm convention. As emphasized in its Section 3.1, this last derivative of a row-vector function and the transpose of the Jacobian have different tensor-norm definitions and are not interchangeable. The optional first integral c of that theorem may be chosen constant, with zero derivative bound.
- H2. The embedding K_0 and DK_0 extend continuously to the closed strip of width ρ, are holomorphic inside it, and satisfy $\operatorname{dist}(K_0(\mathbb{T}^n_\rho), \partial\mathcal{B}) > 0$, $\|DK_0\|_\rho < \sigma_K$ and $\|(DK_0)^\mathsf{T}\|_\rho < \sigma_{K^\mathsf{T}}$.
- H3. The tangent frame $L = DK_0$ has maximal rank throughout the closed complex strip, and its metric Gram inverse $\mathsf{B} = (L^\mathsf{T} L)^{-1}$ satisfies $\|\mathsf{B}\|_\rho < \sigma_B$. The transpose is bilinear, not a Hermitian adjoint. The normal frame is defined by equations (3.2)–(3.5) of the cited theorem, with the same symplectic sign convention. For the present canonical

application put $\Omega_{\mathrm{HL}} = -J$, $N_s = JL\mathsf{B}$ and $N_{\mathrm{HL}} = -N_s$. If $T_s = N_s^{\mathsf{T}} J(DX_{H_\vartheta}(K_0)N_s - D_\omega N_s)$, then $T_{\mathrm{HL}} = -T_s$ and $\|\langle T_{\mathrm{HL}}\rangle^{-1}\| = \|\langle T_s\rangle^{-1}\|$. This is the same sign identification as in the canonical conservative-family application; no exact Lagrangianity of the approximate embedding is presumed.

H4. For the resulting torsion matrix T of equations (3.6)–(3.7), computed using X_{H_ϑ}, the real-angle average has an inverse satisfying $|\langle T\rangle^{-1}| < \sigma_T$. Small gradient error by itself does not establish this condition.

H5. For fixed $\gamma > 0$ and $\tau \geq n-1$, the frequency obeys $|k\cdot\omega| \geq \gamma|k|_1^{-\tau}$ for every $k \in \mathbb{Z}^n \setminus \{0\}$. A finite search for small divisors does not prove this all-integer assertion.

For $0 < \rho_\infty < \rho$, these data determine the explicit theorem constants C_1, C_2, C_3 of the cited Appendix B. Its smallness condition is exactly

$$\frac{C_1\|E_\vartheta\|_\rho}{\gamma^4\rho^{4\tau}} < 1. \tag{S43}$$

Accordingly, checking

$$\frac{C_1\mathcal{E}_\vartheta}{\gamma^4\rho^{4\tau}} < 1 \tag{S44}$$

and H1–H5 supplies, on $\mathcal{G}_\alpha$, an invariant analytic map K_∞ for the learned conservative Hamiltonian with the prescribed frequency, analytic on the strip of width ρ_∞. The cited theorem also gives

$$\|K_\infty - K_0\|_{\rho_\infty} \leq \frac{C_2\|E_\vartheta\|_\rho}{\gamma^2\rho^{2\tau}} \leq \frac{C_2\mathcal{E}_\vartheta}{\gamma^2\rho^{2\tau}}. \tag{S45}$$

To conclude that the corrected real map is an embedding, impose in addition a sound injectivity and immersion criterion for that corrected map. If the right-hand side of (S45) is Δ, its derivative on the real torus differs from DK_0 by at most $n\Delta/\rho_\infty$ in the induced infinity norm, by the coordinatewise Cauchy estimate. The real-embedding certificate must include this derivative allowance and the C^0 allowance Δ. A positive harmonic-amplitude margin and strict normalized phase test provide such a certificate for the four-coordinate learned instance. The corresponding criterion for a conservative continuation must be verified uniformly for its own complete embedding prefix and correction bound. Full rank of the approximate complex tangent frame alone is not an injectivity certificate for the corrected real map. Under this additional condition, the real restriction of K_∞ is an embedded invariant torus.

The zero-residual case is already invariant and admits $K_\infty = K_0$; the weak inequality also covers this case. The constants and geometric bounds must correspond to this Hamiltonian, domain and pair of strip widths. The conclusion concerns a conservative torus, not attraction, dissipative control, all trajectories, or a positive-measure family without an additional family argument.

Proposition S20. Deterministic certification of an arbitrary training output. *Let* A *be any possibly randomized training and checkpoint-selection procedure, and let* $\widehat{\vartheta} = \mathsf{A}(\mathcal{Z}, \xi)$ *be its finite output parameters, including data-dependent preprocessing constants. For each realized dataset* $\mathcal{Z}$ *and random seed* ξ*, consider the exact exported Hamiltonian* $H_{\widehat{\vartheta}}$ *and any candidate* K_0*, frequency* ω *and verification domain. Suppose these objects satisfy H1–H5 and the corrected real-embedding criterion above in the same coordinate, time and norm conventions, and a valid deterministic bound* $\overline{E} \geq \|J\nabla H_{\widehat{\vartheta}}(K_0) - DK_0\omega\|_\rho$ *satisfies*

$$\frac{C_1\overline{E}}{\gamma^4\rho^{4\tau}} < 1.$$

Then $H_{\widehat{\vartheta}}$ *has the invariant torus and correction bound stated above, with* $\overline{E}$ *in place of* $\mathcal{E}_\vartheta$*. No sampling-independence, descent, stationarity or optimality condition on the training output is required.*

Proof. Fix an arbitrary realization $(\mathcal{Z}, \xi)$ and its exact output. The verified hypotheses and residual bound satisfy Haro and Luque (2019, Theorem 3.1), which gives the asserted torus and correction estimate. This implication holds for every realization; no property of the procedure producing the candidate is used.

This result concerns acceptance of a particular frozen function. It requires verified bounds for that function, rather than class-wide statistical constants, and does not guarantee that the training procedure produces an acceptable candidate. The finite-observation identity of Lemma S12 and its field increments (S21) likewise apply to arbitrary selected parameters under their stated observation and remainder hypotheses.

S10.5 An explicit risk threshold and the probability statement

For $B > 0$, $M > 0$, set

$$s = \rho/R, \qquad \kappa = \frac{\gamma^4 \rho^{4\tau}}{C_1}, \qquad T_0 = \left(\frac{\kappa}{M^s}\right)^{1/(1-s)}. \tag{S46}$$

If $T_0 > \delta_\star$, define the positive admissible energy error

$$\varepsilon_{\mathrm{allow}} = \min\left\{\frac{Br^2}{2}, \frac{(T_0 - \delta_\star)^2}{2B}\right\}. \tag{S47}$$

A sufficient empirical-risk and complexity condition is

$$A_N(\vartheta, \alpha) < m_P \left(\frac{\varepsilon_{\mathrm{allow}}}{C}\right)^p. \tag{S48}$$

Indeed, (S35) then yields $\varepsilon_\vartheta < \varepsilon_{\mathrm{allow}} \le Br^2/2$ and hence $\delta_\star + \sqrt{2B\varepsilon_\vartheta} < T_0$. Raising to $1 - s$ and multiplying by M^s proves (S44). The general criterion (S44) remains available when $B = 0$ or the optimal difference step is limited by r; these cases are covered directly by (S44).

Corollary S21. Uniform event and post-fit acceptance. *Suppose the statistical assumptions preceding Proposition S17 hold. Let $\widehat{\vartheta}$ be any data-dependent selection from the fixed class. Define acceptance to require valid deterministic bounds for all analytic, reference-residual and geometric assumptions above, including the corrected real-embedding certificate, together with (S44) evaluated using (S35). Let $\mathcal{A}$ be this acceptance event and $\mathcal{K}$ the event that the asserted learned invariant torus exists. Then*

$$\mathbb{P}(\mathcal{A} \cap \mathcal{K}^c) \le \alpha. \tag{S49}$$

Proof. On the uniform event $\mathcal{G}_\alpha$, the energy estimate applies to every parameter, including $\widehat{\vartheta}$. All subsequent implications are deterministic whenever the acceptance conditions hold. Thus erroneous acceptance is contained in $\mathcal{G}_\alpha^c$, whose probability is at most α.

Equation (S49) is not the claim $\mathbb{P}(\mathcal{K} \mid \mathcal{A}) \ge 1 - \alpha$. If the acceptance probability is positive, the immediate conditional bound is instead at most $\alpha/\mathbb{P}(\mathcal{A})$ for failure. An unconditional success probability of at least $1 - \alpha$ requires the remaining conditions to hold for the selected model; a procedure that can reject that model gives only the joint-event guarantee above. Application of this statistical result requires uniform parameter-class bounds, a valid complexity estimate for the realified complex architecture, iid state samples with a positive density lower bound, and conservative pointwise label-error estimates. The correlated weak-window sampling scheme does not satisfy the iid hypothesis. Moreover, bounds for the fitted Hamiltonian are model-specific and do not provide the class-wide complexity or distributional constants required in (S33). The numerical trajectory-based results are therefore interpreted through their deterministic estimates, without a population-confidence claim for the fitted model. The conditional statistical learning-to-KAM route in this section has not been instantiated by the present experiments.

Remark S1. Necessity of quantitative regularity bounds. Real energy closeness alone does not control a vector field: on a bounded real interval, $e_k(q) = k^{-1}\sin(k^2 q)$ has sup norm tending to zero and derivatives of unbounded amplitude. Even a real Hessian bound does not supply (S40): the entire, 2π-periodic functions $e_k(q) = k^{-2}\sin(kq)$ have $\|e_k\|_0 \to 0$, $\|e_k'\|_0 \to 0$ and $\|e_k''\|_0 \le 1$, while $|e_k'(i\rho)| = k^{-1}\cosh(k\rho)$ diverges at any fixed $\rho > 0$. A pole-free extension together with a quantitative outer bound, not analyticity alone, is what makes Lemma S19 useful. These examples concern scalar functions and do not assert unboundedness within a separately constrained finite network class.

S11 A class-level obstruction and a prospective statistical budget

The results in this component concern the conservative correction $N_\theta(q, p)$ of the actual 736-real-coordinate architecture. Its kinetic and quartic mechanical terms are fixed. They cancel in the error $e_\theta = N_\theta - U$, where $U(q) = 1 - \cos(d^T q) - (d^T q)^2/2 + (d^T q)^4/24$. All coordinate derivatives below are physical canonical derivatives in the fixed dimensionless time convention. The phase dimension is four; the Sobolev derivative order is one. The choice $p = 6 > 4$ is an integrability exponent and is not a sixth-order Sobolev norm.

The conditional generalization lemma uses

$$\ell_\theta(x) = \sum_{j=1}^{4} |\partial_j e_\theta(x)|^6, \qquad A_N = \widehat{L}_{6,N} + 2\overline{\mathfrak{R}}_N + 3L_{\max}\sqrt{2\log(4/\alpha)/N}.$$

This is Lemma 2 on page 6327 (PDF page 6) of Chen, Matsubara and Yaguchi (2022), with empirical Rademacher normalization $1/N$. The loss class must be fixed before independent identically distributed sampling. A density lower bound and the other analytic and KAM conditions remain separate hypotheses. The archived centered weak objective, including its kinematic and dissipation terms, is not this pointwise sixth-power conservative-gradient loss.

S11.1 An explicit member family of the present unrestricted class

Let $s_j > 0$ be the stored four state scales, $s_0 > 0$ the stored binary64 normalization, and $a > 0$ the stored correction energy scale. Set the first raw row to $Rq_{11} = 1$, $br_1 = 1$ and all its other entries to zero. Set the second raw matrix entry $A_{11} = 1$ and all other second-layer entries and biases to zero. Its constrained effective entry is a fixed number $c > 0$. Choose the final real readout entry to be t and all remaining readout entries zero. These assignments are permitted by the source architecture for every finite $t \in \mathbb{R}$. They have real coefficients, so the sharp branches coincide with their originals. Evenization and the zero gauge give exactly

$$N_t(x) = at\left[\frac{f(y_1) + f(-y_1)}{2} - f(0)\right], \qquad f(y) = \tanh(c\tanh(1 + y/s_0)), \quad y_1 = x_1/s_1.$$

This construction preserves $N_t(0) = 0$ and $DN_t(0) = 0$. Writing $b = \tanh(1)$ and $w = \tanh(cb)$ gives

$$f''(0) = -\frac{2c}{s_0^2}(1 - w^2)(1 - b^2)[b + c(1 - b^2)w] < 0.$$

Thus the even correction is nonconstant. At $y_1 = 1/2$ the program also encloses a nonzero derivative of the unit-readout member:

$$\partial_1 N_1(s_1/2, 0, 0, 0) \simeq -1.2572616598890178\,10^{-10}.$$

For fixed U, $\partial_1(N_t - U) = t\partial_1 N_1 - \partial_1 U$ is unbounded as $|t| \to \infty$. By continuity it is nonzero on an open set. Consequently the unrestricted source class has no finite uniform $L_{\max}$, pure-Hessian bound, or bounded derivative class to which the displayed bounded-loss lemma could be applied. The small positive factor a does not change this conclusion. This is a class-level obstruction, not a statement about the particular returned checkpoint's finite derivatives.

The first real weights are also unrestricted. Replacing Rq_{11} by v makes the first preactivation $1 + vy_1/s_0$. Its nearest complex-tanh poles have imaginary distance $\pi s_0/(2|v|)$ in the normalized state coordinate, tending to zero. Evenization does not cancel the two distinct pole sets with opposite nonzero real parts. The existing real-state imaginary-part constraints alone therefore do not give one positive complex neighbourhood for the whole unrestricted class.

S11.2 A bounded class can be fixed before a new experiment

The maximum absolute raw parameter in the unchanged returned checkpoint is less than 1.662. Hence the prospective raw box $\Theta_2 = [-2, 2]^{736}$ contains it. Declaring this new class before fresh independent sampling does not require changing its weights or retraining. The box was not preregistered for the old fourteen trajectories; no retrospective iid claim follows.

For explicit bounds let $T = 2$, $b_j > 0$ be the stored first-layer constraint buffers and $h_j = s_0 b_j s_j$. Define the real box $D = \prod_j [-h_j, h_j]$. Let ρ_1, ρ_2 be the stored constraints and β the stored second-layer previous-imaginary bound. The smooth absolute values dominate absolute values. On D,

$$|\operatorname{Im} z_1| \le \rho_1, \quad \sum_k |W_{2,ik}| \le W_2 := \rho_2/\beta, \quad \sum_k |W_{3,k}| \le W_3 := 32T.$$

The second preactivation has imaginary part at most $\eta_2 = \rho_2 \max\{1, \tan(\rho_1)/\beta\} < \pi/4$. Both hidden outputs have modulus at most one. Put

$$d_1 = \sec^2 \rho_1, \qquad d_2 = \sec^2 \eta_2, \qquad k_j = \frac{T/s_0 + \rho_1/(s_0 b_j)}{s_j}.$$

The chain rule, $|\tanh' z| \le \sec^2 \eta$ and $|\tanh'' z| \le 2\sec^2 \eta$ on $|\operatorname{Im} z| \le \eta < \pi/4$ give, including the two evenization branches,

$$|\partial_j N_\theta| \le a W_3 d_2 W_2 d_1 k_j =: g_j,$$
$$|\partial_{jj} N_\theta| \le a W_3 \{2 d_2 (W_2 d_1 k_j)^2 + 2 d_2 W_2 d_1 k_j^2\} =: b_j^N.$$

With $A = |d_1^{\mathrm{mech}}| h_1 + |d_2^{\mathrm{mech}}| h_2$, Taylor's theorem gives $|\partial_j U| \le |d_j^{\mathrm{mech}}| A^5/120$ and $|\partial_{jj} U| \le |d_j^{\mathrm{mech}}|^2 A^4/24$ for $j = 1, 2$; both are zero for momentum coordinates. The code adds these bounds and takes upward dyadic endpoints. The resulting valid, deliberately loose envelopes satisfy

$$L_{\max} < 3.408\, 10^{-34}, \qquad B < 0.002426.$$

There is also an explicit uniform complex neighbourhood of this bounded class. Put $\bar\rho_1 = 0.17$ and

$$t_c = \frac{\bar\rho_1 - \rho_1}{2 \sum_j (T/s_0 + \rho_1/(s_0 b_j))}.$$

For every centre in D and every complex increment $|\Delta x_j| \le s_j t_c$, the first imaginary part is below $\bar\rho_1$. The second is at most $\rho_2 \tan(\bar\rho_1)/\beta < 0.681470 < \pi/4$. A safe common physical polydisc radius is $2.715\, 10^{-5}$. This proves finiteness and a pole margin; it does not prove a numerical covering or Rademacher constant. In particular, a theorem for ordinary scalar real activations cannot be transferred without checking the realified block activations, the parameter constraints and all variable weights. Input dimension four and parameter dimension 736 play different roles in such a covering argument.

S11.3 A known Sobolev constant for a prospective uniform box law

For the next real-risk estimate, use the mean-centered representative $e_\theta^\circ = e_\theta - \mathbb{E}_{\mathrm{unif}(D)} e_\theta$. This shift changes neither its gradient loss nor its Hessian. The bound below concerns this representative; converting it to the original zero-at-origin energy gauge would require the corresponding constant allowance. The later gradient and strip budgets are insensitive to this additive constant.

For a convex $D \subset \mathbb{R}^d$, $p > d$ and a mean-zero C^1 function e, the fundamental theorem of calculus along $[x, y]$, Hölder's inequality and the change of variables $z = x + t(y - x)$ give

$$|e(x)| \le \frac{\operatorname{diam}_{p'} D}{|D|} \int_0^1 \int_D |\nabla e(x + t(y - x))|_p \, dy \, dt \le \frac{p}{p - d} \operatorname{diam}_{p'} D \, |D|^{-1/p} \|\nabla e\|_{L^p(D)}.$$

The integral $\int_0^1 t^{-d/p} dt = p/(p - d)$ is finite. Under the uniform probability law on D, a risk bound A_N therefore gives $\|e_\theta^\circ\|_\infty \le C_u A_N^{1/6}$ with the explicit sufficient constant $C_u = 6 \sum_j h_j$. This avoids inventing an unspecified Sobolev/Poincaré constant. It is a prospective sampling law, not a description of the archived trajectories.

S11.4 The available fixed-embedding route has no positive budget

Use the actual frozen learned candidate K_0, $\rho = 1/40$, $R = 1/10$ and its certified scalar threshold $\kappa \simeq 1.7224511135\, 10^{-39}$. Original full Fourier modes are summed with their exact $2\pi i k \cdot \nu$ multipliers. The certified outer learned-field bound plus a direct Fourier bound on $D_\nu K_0$ gives $\|E_{\mathrm{GC}}\|_R \le M < 56.006$. The real-to-strip interpolation route would require

$$\delta_\star + b_r(\varepsilon, B) < T_0, \qquad T_0 = (\kappa / M^{\rho/R})^{1/(1-\rho/R)} < 5.397\, 10^{-53}.$$

At the one real angle $(7/23, 11/29)$, evaluation of the original finite-Gauss reference field at this same K_0 gives

$$\|X_{H_\star}(K_0) - D_\nu K_0\|_0 > 6.3417\,10^{-11}.$$

Thus no nonnegative energy-error allowance can meet this particular sufficient triangle/interpolation criterion. A one-point lower bound suffices for this rejection; no strip upper bound is inferred from it. This does not disprove KAM, learning, or the already completed moving family argument. The latter changes the embedding through a complete degree-ten response and certifies the cancellations that the fixed-map triangle estimate discards.

For sensitivity only, set $\delta_\star = 0$ while formally retaining the above κ, M, margins and other hypotheses. These data have not been jointly established for a replacement exact-target embedding. Using the prospective box, $p = 6$ and the explicit C_u, B gives $\log_{10} A_{\mathrm{allow}} \simeq -615.31817$. With $\alpha = 1/20$, even if the empirical and Rademacher terms were artificially zero, the chosen confidence envelope would require

$$N > 18L_{\max}^2 \log(4/\alpha)/A_{\mathrm{allow}}^2, \qquad \log_{10} N \simeq 1165.59827.$$

This is a budget of this conservative sufficient bound, not an information-theoretic necessary sample count or a statistical certificate. A chosen expected loss 0.01 has no justification from the centered weak objective, the sixth-power physical loss, or these KAM constants.

S11.5 A different finite-output prospective option

The separately proved degree-six representative design uses fifteen configuration columns and 114 mixed columns. Recomputing its outward Chernoff count gives 1536 rest anchors and 15368 moving anchors, 16904 independent accepted anchors in total, with block failure allowances $1/40$. Degree four needs 5061 anchors. Two derivative rows at one anchor count as one independent matrix summand. These are sufficient conditioning counts, not optimization or full-class population-risk guarantees. Actual sampling, label fidelity, all weighted signed remainders, output acceptance and the KAM conditions remain necessary. The event may apply simultaneously to soundly certified returned neural outputs; that fact does not turn it into Chen's entire-class empirical-risk theorem.

S12 Explicit loss-class complexity for a bounded constrained complex network

Fix the original graph buffers and the prospective parameter set $\Theta_T = [-T, T]^P$, with $T = 2$ and $P = 736$ real coordinates. The two hidden widths are $n = 16$. There are 160 first-layer coordinates, 544 second-layer coordinates and 32 real readout coordinates. The fixed kinetic and quartic mechanical terms cancel from the conservative error. Consequently only the correction N_θ occurs in the loss considered below. This parameter set is to be fixed before a new independent sample; membership of an existing fitted output does not make an archived trajectory sample independent or preregistered for this class.

Write $s_0, s_1, \ldots, s_4, a > 0$ for the fixed normalization and energy scales, $b_j > 0$ for the fixed first-layer constraint buffers, and $D = \prod_{j=1}^4 [-s_0 b_j s_j, s_0 b_j s_j]$. All their stored binary64 values are interpreted as exact rational constants. Let $\sigma_\epsilon(t) = \sqrt{t^2 + \epsilon^2}$, with the actual positive stored squared smoothing constant. Thus $\sigma_\epsilon \geq |t|$ and $|\sigma_\epsilon'| \leq 1$.

For one first-layer row, suppress its row index and put

$$S_1 = \sum_{j=1}^4 b_j \sigma_\epsilon(I_j) + \sigma_\epsilon(\beta_1), \qquad f_1 = \frac{\rho_1}{\rho_1 + S_1}.$$

The symbols R_j, I_j denote the four real and four imaginary raw input coefficients. In the physical independent real coordinates the complex preactivation is exactly

$$z_1(x) = r_1 + i\beta_1 f_1 + \sum_{j=1}^4 (R_j + iI_j f_1) \frac{x_j}{s_0 s_j}.$$

For one second-layer row the graph is

$$S_2 = \sum_{k=1}^{n} \sigma_\epsilon(B_k) + \beta \sum_{k=1}^{n} \sigma_\epsilon(A_k) + \sigma_\epsilon(\beta_2), \qquad f_2 = \frac{\rho_2}{\rho_2 + S_2},$$

$$z_2 = \sum_{k=1}^{n} (A_k + iB_k) f_2 \tanh(z_{1,k}) + r_2 + i\beta_2 f_2.$$

Here $\beta > 0$ is the stored previous-imaginary bound; it need not equal the exact transcendental value $\tan \rho_1$. The output is $F_\theta = \sum_k (c_k + id_k) \tanh(z_{2,k})$. On real phase space the deployed energy correction is

$$N_\theta(x) = a \left\{ \frac{\operatorname{Re} F_\theta(x) + \operatorname{Re} F_\theta(-x)}{2} - \operatorname{Re} F_\theta(0) \right\}.$$

Its holomorphic realization uses the two sharp branches as well as the two evenization branches. The derivative bounds below respect all four. There is no trainable readout bias.

S12.1 A parameter Lipschitz bound with the constraint derivatives retained

For a complex scalar function of the real raw parameters, a bound C means that the sum of the absolute values of its parameter derivatives is at most C. This bounds its directional derivative by $C\|\dot\theta\|_\infty$. Define

$$J_1 = 1 + \sum_j b_j, \quad C_1 = 1 + \frac{TJ_1}{\rho_1}, \quad P_1 = (1 + C_1)J_1,$$

$$k_j = \frac{T + \rho_1/b_j}{s_0 s_j}, \qquad \kappa_j = \frac{1 + C_1}{s_0 s_j}.$$

Since $\rho_1 + S_1 \geq \rho_1$, differentiation of the actual quotient gives

$$\|D_\theta f_1\|_1 \leq J_1/\rho_1, \qquad \|D_\theta(I_j f_1)\|_1, \|D_\theta(\beta_1 f_1)\|_1 \leq C_1.$$

It follows that $\|D_\theta z_1\|_1 \leq P_1$, $|\partial_j z_1| \leq k_j$, and $\|D_\theta \partial_j z_1\|_1 \leq \kappa_j$. These are bounds for the raw-parameter graph, not a replacement graph with independent effective coefficients.

Put

$$\eta_2 = \rho_2 \max\{1, \tan(\rho_1)/\beta\}, \quad \phi_1 = \sec^2 \rho_1, \quad \phi_2 = \sec^2 \eta_2, \qquad W_2 = \frac{\rho_2}{\min\{1, \beta\}}, \quad W_3 = 2nT.$$

Assume $\rho_1, \eta_2 < \pi/4$, as checked by directed interval arithmetic for the fixed buffers. On the real domain the first and second hidden values have modulus at most one. On each applicable strip, $|\tanh'| \leq \phi_i$ and $|\tanh''| \leq 2\phi_i$. Therefore the first hidden values and their physical input derivatives have parameter derivative bounds

$$H_1 = \phi_1 P_1, \qquad H_{1j} = \phi_1(\kappa_j + 2P_1 k_j),$$

respectively, and $|\partial_j \tanh z_1| \leq \phi_1 k_j$.

For the second row define

$$J_2 = n(1 + \beta) + 1, \qquad C_2 = 1 + TJ_2/\rho_2, \qquad Q_2 = 2nC_2,$$

$$P_2 = Q_2 + W_2 H_1 + 1 + C_2, \qquad A_{2j} = W_2 \phi_1 k_j, \qquad B_{2j} = Q_2 \phi_1 k_j + W_2 H_{1j}.$$

Differentiating f_2 gives $\|D_\theta f_2\|_1 \leq J_2/\rho_2$. Each of $A_k f_2, B_k f_2, \beta_2 f_2$ has parameter derivative bound C_2; summing the complex coefficients gives Q_2. In particular, $\|D_\theta z_2\|_1 \leq P_2$, $|\partial_j z_2| \leq A_{2j}$ and $\|D_\theta \partial_j z_2\|_1 \leq B_{2j}$. The real second bias contributes the explicit 1 in P_2.

Proposition S22. Physical gradient sensitivity to all raw parameters. *For every $x \in D$ and $\theta, \theta' \in \Theta_T$,*

$$|\partial_j N_\theta(x) - \partial_j N_{\theta'}(x)| \le K_j \|\theta - \theta'\|_\infty,$$

where a fully explicit sufficient constant is

$$K_j = a\phi_2\{2nA_{2j} + W_3(B_{2j} + 2P_2A_{2j})\}.$$

Proof. The second hidden input derivative is $\tanh'(z_2)\partial_j z_2$. The product and chain rules give its parameter derivative bound $\phi_2 B_{2j} + 2\phi_2 P_2 A_{2j}$. The readout contributes $2n\phi_2 A_{2j}$ from its n real and n imaginary raw coefficients, and at most W_3 times the hidden derivative bound from all upstream parameters. This proves the displayed bound for the raw readout gradient after multiplication by a. Taking the real part is equivalent to averaging the two sharp branches, which preserves the bound because conjugation changes no absolute value. Differentiating the evenization gives one positive and one negative input chain sign, each with weight $1/2$; these weights sum to one. The zero-gauge term has zero physical input derivative. Finally integrate the parameter directional derivative along the line segment between θ and θ'. The raw cube is convex, and the imaginary-part constraints hold at every point on this segment.

Let U be the fixed physical correction and let B_j be valid uniform bounds for $|\partial_j(N_\theta - U)|$ on $D \times \Theta_T$. Let $L_{\max}$ be a valid uniform bound for $\ell_\theta = \sum_j |\partial_j(N_\theta - U)|^6$. The real scalar map $t \mapsto |t|^6$ has derivative bounded by $6B_j^5$ on $[-B_j, B_j]$. Consequently

$$|\ell_\theta(x) - \ell_{\theta'}(x)| \le K_\ell \|\theta - \theta'\|_\infty, \qquad K_\ell = 6\sum_j B_j^5 K_j.$$

S12.2 Covering and the empirical Rademacher normalization

For a fixed sample $x_1, \dots, x_N$, use

$$\widehat{\mathfrak{R}}_N(\mathcal{L}) = \frac{1}{N}\mathbb{E}_\sigma \sup_{\theta \in \Theta_T} \sum_{i=1}^N \sigma_i \ell_\theta(x_i).$$

For every $\eta > 0$, a coordinate grid in $[-T, T]$ has an η-cover with at most $1 + 2T/\eta$ points: take $-T + k\eta$ for $0 \le k \le \lfloor 2T/\eta \rfloor$ and round down. Thus the raw cube has a cover of cardinality at most $(1 + 2T/\eta)^P$, and the sample loss vectors have an ℓ_∞ cover of radius $K_\ell\eta$. For the finite representatives, the boundedness $0 \le \ell \le L_{\max}$ gives Euclidean vector norm at most $L_{\max}\sqrt{N}$. The finite-class exponential-moment inequality therefore yields

$$\widehat{\mathfrak{R}}_N(\mathcal{L}) \le K_\ell\eta + L_{\max}\sqrt{\frac{2P\log(1 + 2T/\eta)}{N}}.$$

Indeed, approximating each loss vector changes its signed average by at most $K_\ell\eta$. For a finite set of M vectors v, the bound $\mathbb{E}e^{t\sum_i \sigma_i v_i} \le e^{t^2\|v\|_2^2/2}$, followed by the log-sum-exp inequality and optimization in t, gives $L_{\max}\sqrt{2\log M/N}$. This also covers $M = 1$ by continuity. For $T = 2$, the logarithm is precisely $\log(1 + 4/\eta)$. This derivation uses no scalar-real-activation covering theorem.

On the common iid event of the bounded-loss lemma of Chen et al. (2022), with probability at least $1 - \alpha$, every output in this fixed class simultaneously satisfies

$$\mathbb{E}\ell_\theta \le \widehat{L}_{6,N}(\theta) + 2K_\ell\eta + \frac{L_{\max}}{\sqrt{N}}\{2\sqrt{2P\log(1 + 4/\eta)} + 3\sqrt{2\log(4/\alpha)}\}.$$

All terms on the right are explicit except the observed empirical loss. The same event allows data-dependent output selection; it does not guarantee that optimization returns an output with a small empirical loss.

For a desired risk $r > e \ge 0$ and an actually achieved empirical bound $\widehat{L}_{6,N} \le e$, put $\delta = r - e > 0$ and $\eta = \delta/(4K_\ell)$ when $K_\ell > 0$. A fully explicit sufficient sample budget for a strict risk bound below r is

$$N > \frac{4L_{\max}^2}{\delta^2}\{2\sqrt{2P\log(1 + 4/\eta)} + 3\sqrt{2\log(4/\alpha)}\}^2.$$

No iid draw or empirical-loss achievement is asserted by this formula. If no positive risk allowance exists in a chosen KAM sufficient route, the formula does not repair that obstruction. In particular, the positive one-point physical residual at the frozen reference embedding still rules out its previously considered triangle/interpolation budget. Substitution of a counterfactual zero-target-defect allowance serves only as a sensitivity calculation. It is neither a necessary sample lower bound nor an alternative to the completed varying-embedding proof.

S13 A complex-domain obstruction and a local parameter class

All parameters below are realified raw coordinates of the four-dimensional, two-hidden-layer complex network. The stored binary64 scales are interpreted as exact real constants. The sharp extension averages a literal network with the conjugate-coefficient network; the even extension averages its values at x and $-x$; the real zero gauge subtracts the value at zero.

S13.1 An interior pole of a member of the full raw box

Consider the member of $\Theta_2 = [-2,2]^{736}$ whose only nonzero raw entries are the four first-row real input weights, each equal to two, the corresponding real bias, equal to one, the second-layer entry $A_{11} = 1$, and the real readout entry $A_{11} = 1$. Every imaginary raw coordinate is zero. Let s_0 be the stored normalization, s_j the physical state scales, $\epsilon = \sqrt{\epsilon_2}$ the actual smooth-absolute constant, and β the stored preceding-layer bound. The constrained second-layer entry is

$$c = \frac{\rho_2}{\rho_2 + 17\epsilon + \beta(\sqrt{1+\epsilon_2} + 15\epsilon)} > 0, \qquad w_j = \frac{2}{s_0 s_j}.$$

Consequently the literal scalar network is $f(x) = \tanh(c\tanh(1 + \sum_j w_j x_j))$. It has real coefficients, so both sharp branches agree. Put

$$y = \arctan\frac{\pi}{2c}, \qquad t = \frac{y}{\sum_j w_j}, \qquad x_\star = (-1/w_1 + it, it, it, it).$$

The exact-buffer interval calculation verifies $|\operatorname{Re} x_{\star,j}| < 0.06$ and $|\operatorname{Im} x_{\star,j}| < 0.01$ for every coordinate. Since $0 < y < \pi/2$, the first activation is finite and

$$1 + \sum_j w_j x_{\star,j} = iy, \qquad c\tanh(iy) = ic\tan y = i\pi/2.$$

The second activation therefore has a genuine simple pole. Its argument has nonzero derivative $cw_j \sec^2 y$ in every coordinate, so the pole is not removable by composition. At the opposite even branch the first argument is $2 - iy$, and

$$\operatorname{Re}\{c\tanh(2-iy)\} = \frac{c\sinh 4}{\cosh 4 + \cos(2y)} > 0.$$

Thus that branch is analytic near $x_\star$ and cannot cancel the pole. The sharp average is identical, the energy factor is strictly positive, and the finite zero gauge cannot cancel a pole. Uniform holomorphy, and hence any finite uniform analytic modulus on the original complex rectangle, is false for the entire raw box Θ_2. This is an actual class member and a symbolically exact pole, not rejection of a sufficient numerical guard.

S13.2 A prospective local class around the unchanged output

Let θ_0 denote the unchanged frozen output and define $\Theta_{\mathrm{loc}} = \{\theta : \|\theta - \theta_0\|_\infty \le 10^{-3}\}$. Every one of the 736 real raw coordinates, including all biases and both readout components, varies in this box. The original quotient constraints are recomputed with interval arithmetic from these raw intervals. No effective weight is varied independently. The calculation verifies that the local box lies strictly inside Θ_2.

For the expanded complex rectangle

$$\Omega^+ = \{x : |\operatorname{Re} x_j| \le 0.061, |\operatorname{Im} x_j| \le 0.011\},$$

write each interval affine weight as $W_{ij} = A_{ij} + iB_{ij}$ and its bias as $a_i + ib_i$. Valid uniform first-layer imaginary bounds are

$$\eta_{1i} = \sup|b_i| + \sum_j (\sup|A_{ij}|\,0.011 + \sup|B_{ij}|\,0.061).$$

For $|\operatorname{Im} z| \le \eta < \pi/2$, the exact complex identities for $\tanh z$ give $|\operatorname{Im}\tanh z| \le \tan\eta$ and $|\tanh z| \le \max\{1, \tan\eta\}$. Hence second-layer bounds are

$$\eta_{2i} = \sup|b_{2i}| + \sum_k \left(\sup|A_{2ik}|\tan\eta_{1k} + \sup|B_{2ik}|\max\{1, \tan\eta_{1k}\}\right).$$

Both sets of bounds are strictly below $\pi/2$ in the certificate. They therefore prove holomorphy for every local-class member on an open neighbourhood of Ω^+. The sign- and conjugation-symmetric domain also covers every even and sharp branch. A uniform literal modulus is the sum of the readout moduli times the second hidden moduli. Twice this bound times the fixed energy scale covers the zero-gauged network.

The mean-centered error is $e^\circ_\theta = e_\theta - \mathbb{E}_{\mathrm{unif}(D)} e_\theta$, with $e_\theta = N_\theta - U$ and the original real sampling box D. The latter need not lie inside Ω^+. The certificate separately bounds the same network on D and uses

$$\|e^\circ_\theta\|_{\Omega^+} \le \|N_\theta\|_{\Omega^+} + \|U\|_{\Omega^+} + \|N_\theta\|_D + \|U\|_D.$$

For $U = 1 - \cos(d^T q) - (d^T q)^2/2 + (d^T q)^4/24$, a domain with $|d^T q| \le S$ has $|U| \le S^6 e^S/720$. Every point of the original Ω admits a coordinate polydisc of radius 10^{-3} inside Ω^+, so Cauchy estimates may use this explicit positive margin. This is a prospective restricted class around the existing output; it is neither a preregistered class for the archived training trajectories nor a new population-risk or KAM certificate by itself.

A connected complex collar of the sampling and target domains. Let $h_j = s_0 b_j s_j$ be the original physical real sampling halfwidths and set $H_j = \max\{h_j, 0.061\}$. For the same local raw parameter box, the domain

$$\mathcal{C} = \{x : |\operatorname{Re} x_j| \le H_j, |\operatorname{Im} x_j| \le 0.011\}$$

contains both D and Ω^+. Replacing the real halfwidths in the preceding affine guard by H_j yields first- and second-layer imaginary bounds below 0.507252 and 1.056127, respectively. Both are strictly below $\pi/2$. The same sign and conjugation argument therefore proves uniform holomorphy of every local-class member on a neighbourhood of $\mathcal{C}$. Bounding the entire reference correction by its sixth-order exponential tail and subtracting its real D mean gives

$$\sup_{\theta\in\Theta_{\mathrm{loc}}} \|e_\theta - \mathbb{E}_{\mathrm{unif}(D)} e_\theta\|_{\mathcal{C}} < 5.374\,10^{-9}.$$

This supplies an explicit common analytic domain and modulus for any subsequent, separately proved propagation inequality. It does not assert that a tensor Bernstein-ellipse bound holds on a larger uncertified box, or that a population-risk acceptance criterion has been satisfied.

S14 What an integrated training residual measures

Let $\mathcal{Q}_i$ be the fixed positive quadrature on an observed window of duration $\Delta_i > 0$. At its nodes put $p = G(q)v$, let $\widehat{R}(q)$ be the fixed learned damping matrix, and let $R_\star(q) = a(G(q) - K_r)$ be the specified physical reference damping. Define $H_4 = T_G + V_4$, $H_\star = H_4 + U(q)$, and $\widehat{H} = H_4 + N(q,p)$. For the observed port input $g(q)u$, write

$$r_{4i} = \frac{\Delta p_i - \mathcal{Q}_i[-\partial_q H_4 - \widehat{R}v + gu]}{\Delta_i},$$
$$C_i = \frac{\mathcal{Q}_i[\partial_q U]}{\Delta_i}, \qquad D_i = \frac{\mathcal{Q}_i[(R_\star - \widehat{R})v]}{\Delta_i}.$$

These quantities use raw canonical momentum-rate units; the coordinate loss scales have not been divided out. Linearity of the same quadrature gives the exact algebraic identities

$$E_i := \frac{\Delta p_i - \mathcal{Q}_i[-\partial_q H_\star - R_\star v + gu]}{\Delta_i} = r_{4i} + C_i + D_i,$$
$$r_{\mathrm{GC},i} := \frac{\Delta p_i - \mathcal{Q}_i[-\partial_q \widehat{H} - \widehat{R}\partial_p \widehat{H} + gu]}{\Delta_i} = r_{4i} + \frac{\mathcal{Q}_i[\partial_q N + \widehat{R}\partial_p N]}{\Delta_i}.$$

Indeed $\partial_p H_4 = G^{-1}p = v$ at every node, while $\partial_p \widehat{H} = v + \partial_p N$. Substituting these derivatives into the two residuals and collecting terms proves both formulas.

Consequently minimizing the observed integrated residual can reward cancellation of the baseline residual through a combination of conservative and damping-related terms. The identity alone does not identify the pointwise error $\nabla N - (\partial_q U, 0)$, nor does it imply that the learned correction equals the physical correction. Quadrature defects, observation fidelity, and the fixed damping mismatch are separate quantities. A nonzero Hessian $D^2N(0)$, when $D^2U(0) = 0$, is a directly observable lower-order discrepancy, but is not by itself a proof of which mechanism caused it.

S15 A fixed-output local order mismatch

Proposition. Let N be the frozen complex network, $U(q) = 1 - \cos(d^T q) - (d^T q)^2/2 + (d^T q)^4/24$, $\widehat{H} = H_4 + N$, and $H_\star = H_4 + U$. For every real $0 < t \le 10^{-6}$ and $x = te_1$ in physical canonical coordinates,

$$\|X_{\widehat{H}}(x) - X_{H_\star}(x)\|_2 > 10^{21}\|X_{H_4}(x) - X_{H_\star}(x)\|_2.$$

This statement concerns this fixed output on this explicit small axis. The absolute errors are extremely small, and no conclusion about all complex networks, the full verification grid, or practical control accuracy is implied.

Proof. The exact-raw interval evaluation certifies $\partial_{11}N(0) > 5\,10^{-9}$, whereas $D^2U(0) = 0$. Put $e^\circ = N - U - \mathbb{E}_{\mathrm{unif}(D)}(N - U)$. The separately verified analytic collar bounds $|e^\circ|$ by $M = 5.374\,10^{-9}$ on the complex coordinate disc $|z| \le R = 10^{-2}$. This disc lies inside the certified collar. Evenization of N and evenness of U imply an even Taylor expansion $e^\circ(ze_1) = \sum_{k\ge 0} a_{2k} z^{2k}$. Cauchy's inequalities yield $|a_{2k}| \le M/R^{2k}$ and $2a_2 = \partial_{11}N(0)$. Therefore, with $s = t/R$,

$$|\partial_1(N - U)(te_1) - \partial_{11}N(0)t| \le \frac{2M}{R} s\{(1 - s^2)^{-2} - 1\}.$$

After division by t, the right side is increasing for $0 < t < R$. At $t = 10^{-6}$ it is less than $2.150\,10^{-12}$, whence throughout the stated interval

$$\partial_1(N - U)(te_1) > 4.99\,10^{-9}t.$$

The exact mechanical buffers satisfy $\|d\|_2 < 0.4$ and $|d_1| < 0.23$. The real sine remainder gives

$$\|\nabla U(te_1)\|_2 \le \frac{\|d\|_2 |d_1|^5}{120} t^5 < 3\,10^{-6}t^5.$$

Consequently the ratio of the two gradient errors is greater than $4.99\,10^{-9}/(3\,10^{-6}t^4)$, which exceeds 10^{21} for all $0 < t \le 10^{-6}$. The canonical symplectic matrix is Euclidean orthogonal, so these gradient-error norms equal their Hamiltonian-field error norms. This proves the claim. An additional exact-raw interval gradient evaluation at $t = 10^{-6}$ checks the quantitative separation directly. □

S16 A positive risk budget for the actual conservative-family field inputs

The real loss class remains the bounded raw cube $\Theta_2 = [-2, 2]^{736}$. Its risk is

$$R_D(\theta) = \mathbb{E}_{\mathrm{Unif}(D)} \sum_{j=1}^{4} |\partial_j(N_\theta - U)|^6, \qquad D = \prod_j [-h_j, h_j],$$

with the original stored physical halfwidths. The raw class is fixed before future independent sampling. The archived fourteen trajectories, and the subsequent finite-grid observations drawn from another law, are not this uniform continuous sample. The previously proved loss envelope, parameter Lipschitz constant and Chen common risk event on D are reused unchanged. No uniform holomorphy of the whole raw cube on the target is assumed: that stronger assertion is false. For acceptance one must separately verify a holomorphic continuation and an outer modulus for the returned output.

For the actual checkpoint θ_0, one available source-bound certificate is uniform on $\|\theta-\theta_0\|_\infty \le 10^{-3}$. The box is contained in Θ_2. Its four sharp/even branches are holomorphic on the connected collar

$$\mathcal{C}=\{z:|\Re z_j|\le H_j,\ |\Im z_j|\le I\},\qquad H_j=\max\{h_j,61/1000\},\quad I=11/1000.$$

For $e=N_\theta-U$ and $f=e-\mathbb{E}_D e$, it gives $|f|\le M$ on $\mathcal{C}$, with a positive directed bound $M<5.374\,10^{-9}$. This is a local-box analytic condition, not a statement that every member of Θ_2 is pole free on $\mathcal{C}$. The strict pole margins imply holomorphy on a neighbourhood of this closed collar. Only $N_\theta-U$ is continued; the kinetic graph cancels and is not required to be invertible throughout an artificially enlarged domain.

The mean-zero convex-box inequality already proved for $p=6>4$ gives

$$\|f\|_D\le\varepsilon:=C_uR_D^{1/6},\qquad C_u=6\sum_j h_j.$$

Subtracting the mean changes no derivative of positive order.

S16.1 Quantitative continuation on the original target

The final target remains $\Omega=\{|\Re z_j|\le 3/50,|\Im z_j|\le 1/100\}$. Put $\delta_c=1/2000$, and first continue to $\Omega'=\{|\Re z_j|\le 121/2000,|\Im z_j|\le 21/2000\}$. This enlarged set contains every closed coordinate polydisc of radius δ_c centred at Ω.

For each $z\in\Omega'$, choose the real centre

$$c_j=\mathrm{clip}(\Re z_j,-h_j+a,h_j-a),\qquad a=1/1000.$$

The real cube $c+[-a,a]^4$ lies in D. For the actual h_j, the product Bernstein ellipse of parameter 16 over this cube lies in $\mathcal{C}$. The ellipse has real and imaginary halfwidths $a(16+1/16)/2$ and $a(16-1/16)/2$, respectively. The product ellipse of parameter 9 contains the polydisc $\|w-c\|_\infty\le I/3$; all these inclusions are checked with the exact stored rational halfwidths.

Let a_k be the four-variable Chebyshev coefficients about c. The real integral formula and the product contour formula give

$$|a_k|\le 2^{s(k)}\min\{\varepsilon,M16^{-|k|}\},$$

where $s(k)$ counts nonzero components. Since $\min(u,v)\le u^{1/5}v^{4/5}$, the product geometric series implies

$$\|f\|_{\|w-c\|_\infty\le I/3}\le C_0\varepsilon^{1/5}M^{4/5},\qquad C_0=\frac{16}{(1-9/16^{4/5})^4}.$$

Here $9^5<16^4$, so the denominator is strictly positive.

Connect c to z by $c(t)=c+t(z-c)$. The actual halfwidths give $\|z-c\|_\infty\le V=1/50$. Every polydisc of radius $\gamma(t)=I-(21/2000)t$ about $c(t)$ lies in $\mathcal{C}$. The real-boundary assertion follows by checking its two affine endpoint inequalities, and the imaginary-boundary assertion follows directly. Starting at $t_0=0$, set

$$t_{k+1}=\min\{1,t_k+\gamma(t_k)/(10V)\}.$$

This reaches 1 after finitely many steps because $\gamma(t)\ge 1/2000$ on $[0,1]$. If a bound E_k holds on the polydisc of radius $\gamma(t_k)/3$, the next such polydisc is contained in the concentric polydisc of radius $5\gamma(t_k)/12$. Indeed,

$$V\Delta t+\gamma(t_{k+1})/3\le\gamma(t_k)\{1/3+1/10-(21/2000)/(30V)\}=499\gamma(t_k)/1200<5\gamma(t_k)/12.$$

The polydisc three-circle inequality follows by applying the scalar Hadamard theorem to $\zeta \mapsto f(c+\zeta v)$ for each fixed unit polydisc direction. Thus

$$E_{k+1} \le E_k^{\lambda} M^{1-\lambda}, \qquad \lambda = \frac{\log(12/5)}{\log 3} \in (0,1).$$

If the exact recurrence takes m steps, put $\Lambda = \lambda^m$ and $\beta = \Lambda/5 > 0$. Uniformly for $z \in \Omega'$,

$$|f(z)| \le C_0^{\Lambda} C_u^{\beta} M^{1-\beta} R_D^{\beta/6} =: F(R_D).$$

This is a finite, deliberately conservative propagation argument. It does not assume convergence of one Taylor expansion over the target. At zero risk it follows by continuity, or the identity principle.

Cauchy's formula on the radius-δ_c polydiscs gives all 34 positive-order derivatives through degree three. Retaining every ordered multiplicity,

$$\delta_0 \le F/\delta_c, \qquad \delta_1 \le 5F/\delta_c^2, \qquad \delta_{t1} \le 20F/\delta_c^2, \qquad \delta_2 \le 30F/\delta_c^3.$$

The coefficients are the exact sums of the relevant multiindex factorials: a Hessian row sums to $2+3=5$, all ordered Hessian entries sum to $4\cdot 2+12=20$, and the ordered third derivatives of one gradient component sum to $6+12+6+6=30$.

Let $a_0, a_1, a_{t1}, a_2 > 0$ be the actual same-P_{10} field allowances, not a counterfactual fixed-map residual threshold. Define

$$F_* = \tfrac{1}{2}\min\{a_0\delta_c, a_1\delta_c^2/5, a_{t1}\delta_c^2/20, a_2\delta_c^3/30\} > 0.$$

An exact integer $K > 0$ is chosen by outward logarithmic arithmetic so that $F(2^{-K}) < F_*$. The positive risk allowance is represented exactly as $r_* = 2^{-K}$, without materializing an exponentially long denominator. It implies four strict field-input inequalities against the actual family allowances. This step uses neither an artificial zero target defect nor an earlier complete error certificate to infer the risk hypothesis.

S16.2 What the statistical and KAM implications require

On Chen's common event for Θ_2 one has, for every returned output,

$$R_D \le \widehat{L}_{6,n} + 2K_\ell\eta + \frac{L_{\max}}{\sqrt{n}}\{2\sqrt{1472\log(1+4/\eta)} + 3\sqrt{2\log(4/\alpha)}\}.$$

For $r_* = 2^{-K}$ choose $\eta = r_*/(8K_\ell)$ and require a sound empirical true-loss bound at most $r_*/2$, including common reference-label fidelity. With $\Delta = r_*/2$, the existing sufficient sample formula is

$$n > \frac{4L_{\max}^2}{\Delta^2}\{2\sqrt{1472\log(1+4/\eta)} + 3\sqrt{2\log(4/\alpha)}\}^2.$$

The program returns an exact integer exponent J for the sufficient budget $n = 2^J$, and does not assert that the empirical requirement is achieved. No new sample or optimization is performed.

The common real risk event concerns the entire raw cube. The continuation step additionally needs the returned output's analytic certificate, such as the verified local box above. Its actual approximate embeddings, frequency, invariant-torus defect, varying mean inverse and other KAM gates must also be bound to that output. In particular the P_{10} residual certificate is attached only to θ_0; it is not transferred to another raw-cube member merely because that member passes a risk test. For the actual checkpoint these remaining family certificates already exist, but the risk premise must still be tested rather than assumed.

S16.3 A nonvacuity check for the present trained output

An existing directed reference/gradient cache supplies a real point $x_0 \in \operatorname{int} D$ and a verified nonzero component magnitude $|\partial_j(N_{\theta_0} - U)(x_0)| \ge g > 0$. The original raw-class chain bounds give, independently of any complete output-error certificate,

$$|\partial_{jk} N_\theta| \le aW_3\{2\phi_2(W_2\phi_1)^2 + 2\phi_2 W_2\phi_1\}k_j k_k.$$

The reference contribution is bounded by $|d_j d_k|(|d_1|h_1 + |d_2|h_2)^4/24$ for configuration indices, and zero otherwise. Let L_j be the resulting positive Hessian-row sum. With

$$r = \min\{\tfrac{1}{2}\min_k(h_k - |x_{0k}|), g/(2L_j)\} > 0,$$

the component remains at least $g/2$ on $x_0 + [-r, r]^4$. Hence

$$R_D(\theta_0) \geq (g/2)^6 \frac{r^4}{\prod_k h_k} > 0.$$

This deterministic lower bound and r_* are explicitly compared. A positive sufficient threshold alone is not an instantiation for the trained output. If this lower bound exceeds r_*, no sample-size increase can make the true risk satisfy this particular sufficient test; that diagnoses the conservatism of this route, not impossibility of learning or KAM.

S17 Differentiable low-order coefficients of the scalar energy

Let $x = (q_1, q_2, p_1, p_2)$, let $s_j > 0$ denote the four fixed state scales, and set $y_j = x_j/s_j$. Let $E > 0$ be the outer energy scale. In the computational formulas below, σ denotes the stored binary64 value of $\sqrt{2}$; the exact canonical coordinate change elsewhere uses the mathematical square root. The real scalar residual energy has the form

$$N_\theta(x) = E\left\{\frac{F_\theta(y) + F_\theta(-y)}{2} - F_\theta(0)\right\}, \tag{S50}$$

where F_θ is the scalar output of the original two-hidden-layer network on real inputs. In the complex architecture, F_θ is the real part of its complex readout, with the first affine layer acting on $(z, \overline{z})$, where $z = (y_q + iy_p)/\sigma$. The vector θ consists of the original real raw coordinates, including the coordinates entering the two affine constraints.

Write the Taylor expansion at the origin as

$$E^{-1}N_\theta(s \odot y) = \sum_{|\alpha|=2} c_\alpha(\theta) y^\alpha + \sum_{|\alpha|=4} c_\alpha(\theta) y^\alpha + O(\|y\|^6). \tag{S51}$$

There are $10 + 35 = 45$ coefficients. They are ordinary Taylor coefficients: the physical derivative satisfies

$$\partial_x^\alpha N_\theta(0) = E\,\alpha!\, c_\alpha(\theta) \prod_{j=1}^4 s_j^{-\alpha_j} \qquad (|\alpha| = 2 \text{ or } 4). \tag{S52}$$

Thus neither a factorial nor a physical state scale is included in c_α itself.

Proposition S23. Finite algebra for the normalized coefficients. *Work on the open set of raw parameters for which both hidden layers are regular at $y = 0$. In the quotient algebra*

$$\mathcal{A}_4 = \mathbb{C}[y_1, y_2, y_3, y_4]/\langle y^\alpha : |\alpha| \geq 5\rangle,$$

propagate the four coordinate polynomials through the original affine maps and through the following truncated activation. For $P = c + \delta$, where δ has zero constant coefficient, put $t = \tanh(c)$ and $d_1 = 1 - t^2$, and set

$$\tanh(P) = t + d_1\delta - td_1\delta^2 + \frac{d_1(3t^2 - 1)}{3}\delta^3 + \frac{td_1(2 - 3t^2)}{3}\delta^4 \quad \text{in } \mathcal{A}_4. \tag{S53}$$

Take the real part after the scalar complex readout, if present, and retain the coefficients of total degrees two and four. The result is exactly the vector in (S51) in exact arithmetic. It has the same derivatives with respect to every real raw parameter as direct differentiation of the scalar network.

Proof. The quotient retains all $\binom{8}{4} = 70$ monomials of total degree at most four. Its product is ordinary convolution followed by deletion of terms of total degree greater than four. This requires 495 ordered monomial pairs. The deleted terms form an ideal, so deletion at any intermediate multiplication cannot change a retained coefficient.

The identity $\tanh' = 1 - \tanh^2$ gives $\tanh''/2! = -t(1-t^2)$, $\tanh'''/3! = (1-t^2)(3t^2-1)/3$, and $\tanh''''/4! = t(1-t^2)(2-3t^2)/3$ at c. Since δ has no constant term, its fifth and higher powers vanish in $\mathcal{A}_4$. This proves (S53); applying it successively through the affine and activation layers gives the Taylor polynomial of the original scalar function.

For the complex first layer, split its original effective weight as (W_+, W_-). Its real-coordinate affine weight is exactly

$$W_1 = ((W_+ + W_-)/\sigma, \quad i(W_+ - W_-)/\sigma)\,.$$

This is an identity on real y, rather than a change of parameters. All effective weights, constraint denominators, biases, and readout coordinates remain functions of the original raw parameters. Real part extraction is real-linear and therefore commutes with their real derivatives. Evenization removes odd coefficients and the zero gauge removes the constant coefficient; neither alters a positive even coefficient.

The smooth absolute-value regularization in each constraint has a strictly positive squared offset. The constraints are consequently smooth functions of the real raw parameters. On the stated regular set, all compositions above are smooth in those parameters and analytic in the input near zero. Differentiation of a retained coefficient therefore agrees with differentiating the original network coefficient. The construction retains all original raw coordinates; it imposes no additional architectural zero condition.

For any real direction v and $m \in \{2, 4\}$, the normalization can also be checked by

$$\frac{d^m}{dt^m}\left[E^{-1}N_\theta(s \odot tv)\right]\Big|_{t=0} = m! \sum_{|\alpha|=m} c_\alpha(\theta) v^\alpha. \tag{S54}$$

Mixed derivatives use $\alpha!$ instead of $m!$. A squared penalty on these coefficients is differentiable with respect to the original parameters. A finite value of such a penalty does not establish exact vanishing of the coefficients, a successful optimization, or an error bound away from the origin.

S18 Identification with a low-order physical-jet penalty

The conservative model remains the ordinary full-phase network $\widehat{H}_\theta = H_4 + N_\theta$, with the original two hidden layers, central evenization, sharp realification in the complex case, and $N_\theta(0) = 0$. The real and complex networks have respectively 744 and 736 active real coordinates. No polynomial prefactor, additional decoder, removed parameter, or exact-jet constraint is introduced. The known finite-Gauss metric G and the previously frozen positive semidefinite dissipation head $\widehat{R}(q)$ are shared by both models.

For the specified mechanical reference, the correction is

$$U(q) = 1 - \cos(d^T q) - \tfrac{1}{2}(d^T q)^2 + \tfrac{1}{24}(d^T q)^4.$$

Consequently its zeroth-, second-, and fourth-order jets at the origin are exactly zero, as are all odd-order jets. This is a property of the specified reference model; it is not a new calibration claim about an unobserved physical system. The penalty uses only these known zero jets, not evaluated reference gradients or sixth-order target coefficients.

S18.1 The unchanged centered native-observation loss

The observations are the original fourteen training trajectories, using only (τ, q, v, u). Set $p = G(q)v$, and let $\mathcal{Q}_b$ denote the fixed positive actual-time quadrature in window b, of duration $\Delta_b > 0$. There are $W = 280$ windows. With fixed component

scales $a_p, a_v > 0$, define

$$r_{4b} = \frac{\Delta p_b - \mathcal{Q}_b[-(H_4)_q - \widehat{R}v + ug]}{\Delta_b a_p}, \tag{S55}$$

$$r_b(\theta) = r_{4b} + \frac{\mathcal{Q}_b[(N_\theta)_q + \widehat{R}(N_\theta)_p]}{\Delta_b a_p}, \tag{S56}$$

$$k_\theta = (N_\theta)_p / a_v. \tag{S57}$$

All vector divisions are componentwise. The plus sign and the full $\widehat{R}(N_\theta)_p$ term follow by substituting $\widehat{H}_p = v + (N_\theta)_p$ into $\dot{p} = -\widehat{H}_q - \widehat{R}\widehat{H}_p + ug$; no momentum derivative of the learned correction is omitted. Put

$$F_{\mathrm{nat}}(\theta) = \frac{1}{2W}\sum_b \|r_b(\theta)\|_2^2 + \frac{\kappa}{2W}\sum_b \frac{\mathcal{Q}_b[\|k_\theta\|_2^2]}{\Delta_b}, \tag{S58}$$

$$F_4 = F_{\mathrm{nat}}(N = 0) > 0, \tag{S59}$$

where κ is the original stored binary64 value of 0.1. Thus $F_{\mathrm{nat}}/F_4 = 1$ at the common zero-readout initial function. The exact positive stored F_4 is used as a declared normalization; its numerical value is replayed before training.

S18.2 A physical-gradient Gram for each homogeneous jet

Let $S = \mathrm{diag}(s_1, \ldots, s_4)$ be the common stored state scale, $E > 0$ the common actual output-energy scale, and $y = S^{-1}x$. Write the local expansion as

$$N_\theta(Sy) = E\{P_2(y) + P_4(y) + \mathcal{R}_{\geq 6}(y)\}, \qquad P_m(y) = \sum_{|\alpha|=m} c_{m,\alpha} y^\alpha.$$

Here $c_{m,\alpha} = s^\alpha D_x^\alpha N_\theta(0)/(E\alpha!)$ is an ordinary Taylor coefficient, rather than a raw derivative. There are $n_2 = 10$ and $n_4 = 35$ such coefficients. Their differentiable calculation does not replace the deployed full network by its polynomial.

Fix the known common rectangle $D = S\prod_j[-b_j, b_j]$. Explicitly, $b_j = \sigma d_j$, where $\sigma = \mathrm{float64}(\sqrt{2})$ and d_j is the stored first-layer normalized-domain buffer; thus the physical halfwidth is $s_j\sigma d_j$. All factors are interpreted as exact stored constants. These are the original constraint rectangle halfwidths, and are not selected using reference-label errors. Let $Y \sim \mathrm{Unif}\prod_j[-b_j, b_j]$, $w = (1, 1, \kappa, \kappa)$, and $t = (a_{p,1}, a_{p,2}, a_{v,1}, a_{v,2})$. Define

$$(G_{mj})_{\alpha\gamma} = \alpha_j\gamma_j\,\mathbb{E}Y^{\alpha+\gamma-2e_j}, \tag{S60}$$

$$A_m = \frac{E^2}{4F_4}\sum_{j=1}^4 \frac{w_j}{s_j^2 t_j^2} G_{mj}. \tag{S61}$$

The first expression is zero if $\alpha_j\gamma_j = 0$. Otherwise its moment equals zero when any exponent is odd, and equals $\prod_i b_i^{\nu_i}/(\nu_i + 1)$ when every exponent ν_i is even. All these matrices therefore have exact rational entries for the declared stored constants. Moreover,

$$c_m^T A_m c_m = \frac{1}{4F_4}\mathbb{E}\sum_j w_j \left|\frac{\partial_{x_j}[EP_m(S^{-1}x)]}{t_j}\right|^2.$$

This is a deterministic full-rectangle physical force/velocity penalty in the original observation units. It is an added physical prior, not an additional trajectory sample or a population-risk observation. Every A_m is positive definite: zero integral would make every derivative of the homogeneous polynomial vanish on an open box, so that polynomial would be constant and hence zero for $m > 0$.

The implementation stores symmetric binary64 matrices $\widetilde{A}_m$, not falsely exact quadrature matrices. Their exact dyadic entries have positive rational LDL pivots. The separately recorded rational quantity

$$\mu_m = \|A_m^{-1}(\widetilde{A}_m - A_m)\|_\infty < 1$$

also gives $(1-\mu_m)A_m \preceq \widetilde{A}_m \preceq (1+\mu_m)A_m$. Indeed the generalized error matrix is similar to the real symmetric matrix $A_m^{-1/2}(\widetilde{A}_m - A_m)A_m^{-1/2}$, whose eigenvalues are bounded in modulus by that induced norm. Exact and stored matrices, their rounding bounds, and their inverses are recorded separately.

S18.3 Soft constraints and deterministic low-jet consequences

The fixed objective is

$$\mathcal{J}(\theta) = F_{\mathrm{nat}}(\theta)/F_4 + \lambda_2 c_2^T \widetilde{A}_2 c_2 + \lambda_4 c_4^T \widetilde{A}_4 c_4, \qquad \lambda_2 = \lambda_4 = 1.$$

The two coefficients are fixed before fitting because both penalties are in the same native-loss units; no oracle validation is used to tune them. This choice is not asserted to be optimal. If the exact objective is at most $L \geq 0$, nonnegativity gives $c_m^T \widetilde{A}_m c_m \leq L/\lambda_m$.

For any multiindex β, put

$$\ell_{m\beta,\alpha}(y) = Es^{-\beta}(\alpha)_\beta y^{\alpha-\beta}\mathbf{1}_{\{\alpha\geq\beta\}}.$$

With $\widetilde{A}_m$ interpreted as its exact dyadic SPD matrix,

$$|D_x^\beta[EP_m(S^{-1}x)]| \leq \sqrt{L/\lambda_m}\,\sqrt{\ell_{m\beta}(y)^*\widetilde{A}_m^{-1}\ell_{m\beta}(y)}.$$

The Hermitian quadratic expression handles complex y as well as real y. If $|y_j| \leq r_j$, replace each component of ℓ by its positive modulus bound $v_{m\beta,\alpha}$ and the inverse by its entrywise absolute value. The resulting uniform gain is the explicit square root of $v_{m\beta}^T|\widetilde{A}_m^{-1}|v_{m\beta}$. It is zero for $|\beta| > m$. Adding the two bounds controls the returned output's second- and fourth-order Taylor part, including all 34 positive-order derivatives through order three. Since the reference has zero low jets, this is also the low-order part of the conservative error. It controls neither $\mathcal{R}_{\geq 6}$ nor the complete learned error or a KAM gate. A floating training-loss value alone is not an outward certificate of the exact objective; any rigorous application must separately include rounding and coefficient-evaluation errors.

S18.4 One fixed exploratory comparison

Both networks start at the same H_4 using exact zero readouts, share the same positive stored E, and receive 400 full-batch projected-Adam updates with identical optimizer settings. Every active raw coordinate is projected to $[-2,2]$ after each update; optimizer moments are retained. This is a new optimization protocol and has no inherited convergence guarantee. Checkpoints are selected only by the minimum finite total training objective, with the earliest checkpoint breaking a tie. No rest-only target label, oracle gradient, old validation, or KAM certificate participates in fitting or checkpoint selection.

The previously disclosed full-phase oracle anchors may subsequently provide a paired exploratory diagnostic of H_4, real, and complex outputs, separating configuration-force and momentum-velocity errors. They are reused observations, not a new untouched holdout for these adaptively proposed candidates. Unequal widths, topology and derivative conditioning remain material limitations of any advantage claim. New outputs require their own error, analytic-domain, KAM and control certificates; none of those for an older checkpoint is transferred.

S19 A nonzero jet-compatible member of the existing complex class

The numerical coefficient in this existence construction uses the original certified checkpoint's fixed normalization and energy scale. At any other positive common energy scale the exact zero jets and nonzero sixth coefficient persist, with the physical coefficient rescaled accordingly. The constructed parameters are not the fitted parameters of either $\widehat{H}_R^J$ or $\widehat{H}_C^J$.

Lemma (a sparse parameter point of the unmodified class). Consider the existing width-16, two-hidden-layer literal complex-tanh network, with its existing sharp realification, central evenization, and zero-energy gauge. Keep the fixed physical normalization buffers and the two imaginary-part constraints unchanged. The original 736-coordinate raw parameter class $[-2,2]^{736}$ contains a parameter point whose real energy correction N is nonzero and satisfies

$$D^\alpha N(0) = 0 \qquad (|\alpha| \leq 5), \qquad \partial_{q_1}^6 N(0) \neq 0.$$

Its hidden computation has nonzero imaginary biases and weights. No polynomial prefactor, additional layer, or fixed-jet decoder is required.

Construction and proof. All nonlisted raw parameters are zero. In first-layer paths $j = 1, 2, 3$ set

$$R_{q,j1} = j/2, \qquad b_{r,j} = 1/4, \qquad b_{i,j} = 1/32, \qquad R_{q,j2} = R_{p,jk} = I_{q,jk} = I_{p,jk} = 0.$$

Let ϵ_2 denote the stored binary64 value of $(10^{-12})^2$, $\sigma = \mathrm{float64}(\sqrt{2})$, and let $s_1 > 0$ be the fixed first physical state-scale buffer, interpreted as an exact dyadic number. Write d_k for the four fixed normalized-domain buffers, $\rho_1 = \mathrm{float64}(.15)$, $\rho_2 = \mathrm{float64}(.6)$, and $\tau_1 = \mathrm{float64}(\tan(.15))$. The constrained first imaginary bias is the same in all three paths:

$$\lambda_1 = \frac{\rho_1}{\rho_1 + \sqrt{\epsilon_2}\sum_{k=1}^{4} d_k + \sqrt{(1/32)^2 + \epsilon_2}}, \qquad b = \frac{1}{4} + \frac{i\lambda_1}{32}.$$

The imaginary constraint does not involve the first-layer real slopes. Thus, in physical coordinates, the three preactivations are exactly $b + jaq_1$, where $a = (2\sigma s_1)^{-1}$; the ratios $1 : 2 : 3$ are exact, including the stored normalization constants.

In second-layer rows $j = 1, 2, 3$ set only the diagonal raw weights $A_{jj} = 1/4$, $B_{jj} = 1/16$, with biases $b_{r,j} = 1/8$ and $b_{i,j} = 1/64$. Each row has fifteen zero weights of each type. Keeping their smooth absolute values in the constraint gives the same factor in all three rows:

$$\lambda_2 = \frac{\rho_2}{\rho_2 + \sqrt{(1/16)^2 + \epsilon_2} + 15\sqrt{\epsilon_2} + \tau_1\big(\sqrt{(1/4)^2 + \epsilon_2} + 15\sqrt{\epsilon_2}\big) + \sqrt{(1/64)^2 + \epsilon_2}}.$$

Put

$$c = \lambda_2(1/4 + i/16), \qquad d = 1/8 + i\lambda_2/64, \qquad F(z) = \tanh\big(c\tanh(b + z) + d\big).$$

The first three literal hidden outputs are $F(aq_1)$, $F(2aq_1)$, and $F(3aq_1)$. The other output weights vanish. Choose real readout weights

$$(w_1, w_2, w_3) = (15/8, -6/8, 1/8), \qquad B_{\mathrm{out}} = 0.$$

All specified raw coordinates belong to $[-2, 2]$. This specifies a sparse point in the original parameter space; it does not remove any of its 736 trainable coordinates.

For $F(z) = \sum_{k\geq 0} f_k z^k$, realification on real arguments followed by the existing evenization and gauge gives

$$N(q_1) = E\sum_{k\geq 1} \mathrm{Re}(f_{2k}) a^{2k} q_1^{2k} \sum_{j=1}^{3} w_j j^{2k},$$

where $E > 0$ is the unchanged physical energy-scale buffer. Constant terms are removed by the gauge, and every odd total derivative vanishes by evenness. The exact rational identities

$$\sum_j w_j j^2 = 0, \qquad \sum_j w_j j^4 = 0, \qquad \sum_j w_j j^6 = 45$$

therefore cancel all remaining derivatives through total order five. The function depends only on q_1, so all mixed-coordinate derivatives of these orders vanish as well.

The source-bound outward-rounded series calculation at the explicit raw point certifies

$$-\frac{17}{1000} < \mathrm{Re}(f_6) < -\frac{16}{1000}, \qquad -1.1\,10^{-6} < 45Ea^6\,\mathrm{Re}(f_6) < -1.0\,10^{-6}.$$

Consequently its sixth derivative is nonzero. The displayed interval is for the coefficient of q_1^6; the sixth derivative is $6!$ times that coefficient.

For completeness, this member is analytic on the original target rectangle and on the slightly larger rectangle $|\mathrm{Re}\, x_k| \leq .061$, $|\mathrm{Im}\, x_k| \leq .011$. Indeed, the largest first preactivation imaginary part is at most $\eta_1 = \lambda_1/32 + 3a(.011) < .2$. For

$|\operatorname{Im} z| \le \eta_1 < \pi/4$, $|\tanh z| \le 1$ and $|\operatorname{Im}\tanh z| \le \tan\eta_1$. The second preactivation therefore satisfies

$$\eta_2 \le \frac{\lambda_2}{64} + \frac{\lambda_2}{16} + \frac{\lambda_2}{4}\tan\eta_1 < .11 < \frac{\pi}{2}.$$

The same estimates hold for the sign and conjugation branches of the sharp-even extension. Both tanh layers are pole-free there, and the gauged correction obeys $|N| \le (11/2)E$. □

Scope. This is an existence and exact-jet cancellation result in the existing network class. It does not assert that an optimization algorithm reaches this parameter point, that this member approximates the physical correction, or that its nonzero imaginary computation has an advantage over real networks. It neither replaces the frozen trained output nor inherits its KAM or control certificates. Adding this correction to the fixed mechanical prior preserves that prior's zeroth-, second-, and fourth-order jets; identifying a useful sixth-order correction remains a separate learning problem.

S20 Complex-domain verification of the new outputs

The following test applies to the selected raw parameters of each newly frozen output, with its actual common physical energy scale. It does not reuse the parameters, analytic certificate, or KAM result of an earlier trained output. Let W_1, b_1, W_2, b_2, w_3 be the actual effective affine maps, reconstructed with directed arithmetic from the exact binary64 raw buffers and constraints. Their input is the full physical canonical state (q_1, q_2, p_1, p_2).

On a symmetric product rectangle $|\operatorname{Re} x_j| \le H_j$, $|\operatorname{Im} x_j| \le I_j$, define, separately for every neuron,

$$\eta_{1\ell} = |\operatorname{Im} b_{1\ell}| + \sum_j \big(|\operatorname{Re} W_{1\ell j}| I_j + |\operatorname{Im} W_{1\ell j}| H_j\big).$$

If $\eta_{1\ell} < \pi/2$, put $M_{1\ell} = \max(1, \tan\eta_{1\ell})$ and $J_{1\ell} = \tan\eta_{1\ell}$. The literal complex tanh is holomorphic there, with modulus at most $M_{1\ell}$ and imaginary part bounded in modulus by $J_{1\ell}$. A sufficient second-layer guard is

$$\eta_{2m} = |\operatorname{Im} b_{2m}| + \sum_\ell \big(|\operatorname{Re} W_{2m\ell}| J_{1\ell} + |\operatorname{Im} W_{2m\ell}| M_{1\ell}\big) < \pi/2.$$

If both guards pass, all first- and second-layer tanh arguments avoid their poles. Sign and conjugation preserve the symmetric input rectangle and these absolute-value bounds; hence they cover every branch of the sharp-even extension. Subtracting the zero gauge does not affect holomorphy. Its full gauged energy correction obeys

$$|N| \le 2E \sum_m |w_{3m}| \max(1, \tan\eta_{2m}).$$

The source-bound arithmetic applies this test separately on the original rectangle $(H, I) = (.06, .01)$ and its collar $(.061, .011)$, without reducing either rectangle. The new complex output passes both tests. For the new real output the first-layer test passes but the second-layer triangle guard is unresolved. A sufficient-bound failure is not a verified pole, a failure of actual holomorphy, or a comparison of approximation quality.

For a passing rectangle write $M = \max(1, \tan\eta)$ and $\phi = \sec^2\eta$ for a layer's neuron. Local ordinary Taylor coefficient majorants for its positive-degree tanh increment through degree three are

$$\phi\Delta + M\phi\Delta^2 + \frac{\phi(3M^2+1)}{3}\Delta^3.$$

Indeed $|\tanh'| \le \phi$, $|\tanh''|/2! \le M\phi$, and $|\tanh'''|/3! \le \phi(3M^2+1)/3$. Propagating these positive polynomial majorants through the two actual affine maps bounds all 34 physical partial derivatives of N of orders one, two, and three. Multiplication by $\alpha!$ converts each ordinary Taylor coefficient into its derivative bound. There is no additional factor for the average of sharp and even branches.

Alternatively, the uniform modulus on the passing collar gives the Cauchy bound $|D^\alpha N| \le \alpha! M_N (10^3)^{|\alpha|}$ on the original rectangle. Each complex coordinate circle of radius .001 about a point in the original rectangle lies in the collar. These are bounds for the learned correction, not for its error against the physical reference. They do not establish a risk event, a KAM

torus, or safety of a newly controlled trajectory. Any full-Hamiltonian application must also retain the independently justified domain of its fixed mechanical part.

S21 Embedding the common-scale complex output in the original bounded class

Let $\mathcal{N}_E$ denote the existing centrally even, zero-gauged, width-16 complex network class with fixed physical state scales and fixed hidden-layer constraints, outer energy scale $E > 0$, and 736 raw real coordinates in $\Theta_2 = [-2, 2]^{736}$. Its last layer is the unconstrained complex linear readout $w = A + iB$, with no bias. The hidden constraints depend only on hidden parameters, not on A, B.

Lemma (an exact class embedding). For $0 < t \leq 1$, keep every hidden raw coordinate unchanged and set $T_t(A, B) = (tA, tB)$ in the last layer. Then $T_t\Theta_2 \subseteq \Theta_2$ and, as exact functions wherever the hidden network is defined,

$$N_{tE,\theta} = N_{E,T_t\theta}.$$

All existing derivatives of these functions are equal as well. In particular, the entire smaller-energy class is a subset of the original fixed-energy function class.

Proof. Let $h_\vartheta(x)$ be the complex last hidden feature. Literal readout $\sum_m (A_m + iB_m)h_{\vartheta,m}(x)$ is linear in the 32 readout raw coordinates over the reals. Sharp realification, central evenization, and subtraction of the zero value are real-linear operations. Thus multiplying both A and B by t multiplies the full unscaled gauged output by exactly t. Multiplication by the outer scale E proves the identity. The hidden constraints are unchanged, and a contraction of the readout coordinates preserves $[-2, 2]^{736}$. Differentiating the function identity proves the derivative identity. □

For the new selected complex output, the actual stored dyadic buffers satisfy

$$E_{\mathrm{new}} = \frac{5904746009606923}{1237940039285380274899124224} = \frac{E_{\mathrm{old}}}{16}, \qquad E_{\mathrm{old}} = \frac{5904746009606923}{77371252455336267181195264}.$$

The state scales, domain buffers, unit inner scales, and hidden constraint constants agree exactly with the original bounded class. Dividing its new final raw A, B by 16 therefore gives an explicit member of that original 736-coordinate class with precisely the same function and physical gradient. The division is exact for the actual stored readout coordinates, as checked by dyadic rational identities. The new checkpoint is left unchanged; the transformed point is only a mathematical witness.

Consequently an actually established common real-domain risk event uniform over the original class would also cover this output, and the previously verified real-domain complexity upper bounds remain admissible. This does not establish that event for the present data: the fourteen training trajectories are not iid uniform-D states, the native/jet training objective is not Chen's empirical sixth-gradient risk, and the previously disclosed finite discrete anchors are not new continuous- D samples. No population-risk acceptance follows from this embedding.

The embedding also supplies no proximity to the old selected raw point, no use of its local analytic parameter box, and no transfer of its KAM, control, or observation-acceptance certificates. Actual complex-domain verification of the new function is a separate result; uniform real-risk class membership is distinct from holomorphy of every class member on the target complex rectangle. This lemma does not compare real and complex approximation quality.

S22 A population-risk bridge through a finite polynomial representative

Let $D = \prod_{j=1}^{4}[-h_j, h_j]$ be the original real observation rectangle, with uniform probability measure, and retain the original target complex rectangle Ω. These two rectangles need not contain one another. Let $e = N - U$ denote a real-valued, centrally even, gauged conservative energy error, and choose one fixed polynomial representative

$$P_c(x) = \sum_{\alpha\in\mathcal{A}} c_\alpha \chi_\alpha(x), \qquad \chi_\alpha(x) = (x/h)^\alpha, \qquad \mathcal{A} = \{\alpha \in \mathbb{N}^4 : |\alpha| \in \{2, 4, 6\}\}.$$

There are 129 coefficients. Put $r = e - P_c$ by definition; no Taylor convergence of the full network on either rectangle is assumed. For the frozen-output diagnostic, P_N is the exact finite auxiliary representative defined by its dyadic monomial coefficients, and $U_6(q) = (d^T q)^6/720$. The actual error representative is $P_c = P_N - U_6$, rather than P_N alone. Therefore

$r = (N - P_N) - (U - U_6)$. Both real-$D$ and complex-Ω remainder certificates must use this same identity. In particular, the separately verified triangle bounds add the network and the entire-reference tails.

All coefficients c are real. Define the exact physical-gradient Gram

$$Q_{\alpha\gamma} = \mathbb{E}_D \sum_{j=1}^{4} \partial_j \chi_\alpha \, \partial_j \chi_\gamma.$$

This matrix includes the cross terms between degrees two, four, and six. It is positive definite: a polynomial with zero gradient norm is constant on the open real box, while the chosen basis contains no constant.

Proposition (a conditional risk-to-derivative estimate). Suppose that the same representative has verified remainder bounds

$$\|\nabla r\|_{L^2(D;\ell^2)} \le \rho_D, \qquad \sup_{x\in\Omega} |D^\beta r(x)| \le \rho_{\Omega,\beta} \quad (1 \le |\beta| \le 3).$$

The complex remainder and its derivatives must exist on Ω; an output-specific holomorphy certificate on a neighborhood is a sufficient condition. A remainder certificate on Ω alone supplies no bound on D. For the true population risk

$$R_6 = \mathbb{E}_D \sum_{j=1}^{4} |\partial_j e|^6$$

one has

$$\|c\|_Q \le 4^{1/3} R_6^{1/6} + \rho_D.$$

For $v_\beta(x) = (D^\beta \chi_\alpha(x))_{\alpha\in\mathcal{A}}$, let

$$\kappa_\beta \ge \sup_{x\in\Omega} \sqrt{v_\beta(x)^* Q^{-1} v_\beta(x)}.$$

Then

$$\sup_{\Omega} |D^\beta e| \le \kappa_\beta \{4^{1/3} R_6^{1/6} + \rho_D\} + \rho_{\Omega,\beta}.$$

Proof. The coefficient norm equals $\|\nabla P_c\|_{L^2(D;\ell^2)}$. The triangle inequality gives the sum of the L^2 norms of ∇e and ∇r. At a point, $\|z\|_2 \le 4^{1/3}\|z\|_6$ for $z \in \mathbb{R}^4$; Jensen's inequality then bounds $\|\nabla e\|_{L^2(D;\ell^2)}$ by $4^{1/3} R_6^{1/6}$, since the uniform measure is a probability measure. The complex Hermitian Cauchy–Schwarz inequality in the Q inner product gives $|v_\beta^T c| \le \|c\|_Q \sqrt{v_\beta^* Q^{-1} v_\beta}$. Finally add the remainder bound. □

If $|x_j| \le z_j$ on Ω, a finite rational majorant is obtained by replacing each component of v_β by

$$a_{\beta,\alpha} = (\alpha)_\beta \prod_j z_j^{\alpha_j - \beta_j} / h_j^{\alpha_j} \mathbf{1}_{\alpha \ge \beta}$$

and observing that the squared actual supremum is at most $a_\beta^T |Q^{-1}| a_\beta$. Thus one may choose $\kappa_\beta = \sqrt{a_\beta^T |Q^{-1}| a_\beta}$; the numerical implementation may round this chosen bound outward. The same ordered row sums as in the actual family certificate convert these 34 derivative bounds into four field budgets. Write their resulting form as

$$B_i(R_6) = K_i \{4^{1/3} R_6^{1/6} + \rho_D\} + T_i, \qquad i = 1, \dots, 4.$$

For fixed same-output family allowances A_i, define

$$s = \min_i \frac{A_i - T_i}{K_i} - \rho_D.$$

If every $K_i > 0$ and $s > 0$, the sufficient population-risk cap is $R_6 \le s^6/16$ (with strict or outward-slack comparisons as required by the receiving certificate). If the certified s is nonpositive, this bound supplies no positive risk cap; that failure does not prove that the underlying function or KAM torus fails.

Statistical and model boundaries. The proposition is deterministic. A genuine common empirical-to-real- population event is separately required before an empirical loss can be substituted for R_6; a finite-grid acceptance experiment or pointwise

post-fit test is not that event. The representative and both remainders must refer to the same returned output. Existing mean, embedding, and residual certificates for one frozen Hamiltonian cannot be assigned to another parameter vector. For a new output the relevant family inputs and gates must be verified separately, even when a class-uniform real risk event is available.

S22.1 A real-risk lower bound for the frozen output

Here the frozen output is specifically N_0 at the original certified parameter θ_0, rather than either jet-regularized output. The numerical lower bound and receiving family allowances retain that same identity. This test concerns the same frozen output and uniform measure on the original real D. It does not estimate population risk from sampled observations. Let $x_0 = (-1/25, -1/75, 1/50, 0)$ and let C be the closed real cube of halfwidth $r = 10^{-3}$ about x_0, strictly contained in D. An outward-rounded raw-network point evaluation and a whole-cube Hessian enclosure certify

$$|\partial_1 e(x_0)| \geq g > 1.2682\,10^{-10}, \qquad \sup_C \sum_j |\partial_{1j} e| \leq L < 1.804\,10^{-8}.$$

The reference Hessian is bounded independently by its entire cosine remainder, without interval subtraction of nearly cancelling terms. Since $Lr < g/2$, the real mean-value theorem gives $|\partial_1 e| \geq g/2$ throughout C. Consequently

$$R_6 \geq (g/2)^6 \frac{r^4}{\prod_j h_j}.$$

The cube volume ratio uses the uniform probability measure on D; the factors 2^4 in the two volumes cancel. This bound controls an integral over a nonzero-volume set, rather than substituting a pointwise error for a population risk.

For the fixed polynomial dual gains and the fixed existing complex remainder bounds above, every nonnegative ρ_D restricts any cap delivered by this sufficient-condition formula to at most

$$\frac{1}{16}\left\{\min_i \frac{A_i - T_i}{K_i}\right\}^6.$$

The source-bound exact comparison places the actual real-risk lower bound strictly above this ceiling. Thus the frozen output does not satisfy this particular sufficient risk condition, even if the real remainder estimate were improved. This does not exclude sharper complex remainder bounds, smaller valid dual gains, higher polynomial degree, or another KAM argument, and it does not invalidate the independently established KAM result for this output.

S23 Local time-dependent Birkhoff structure of the dissipative equations

Work in the four real canonical coordinates $x = (q_1, q_2, p_1, p_2)$ and, within this section, write $t = \tau$ for dimensionless time. Fix one of the following two pairs:

$$\begin{aligned} &H = \widehat{H} = \tfrac{1}{2} p^{\mathsf{T}} G(q)^{-1} p + V_4(q) + N(q,p), && R = \widehat{R}(q), \\ &H = H_* = \tfrac{1}{2} p^{\mathsf{T}} G(q)^{-1} p + V_*(q), && R = R_*(q). \end{aligned}$$

Each pair defines its own vector field and its own local flow. They are not identified by an energy-error bound. With a prescribed input $u(t)$, set

$$X(t,x) = \begin{pmatrix} H_p \\ -H_q + F \end{pmatrix}, \qquad F(q,p,t) = -R(q) H_p(q,p) + g(q) u(t), \qquad g(q) = d\cos(d^{\mathsf{T}} q). \tag{S62}$$

All statements are local on a real open domain where the prescribed inertia is positive definite and the actual neural and damping graphs are smooth. On one open held-input interval these graphs give smooth coefficients. More generally, assume X is C^3 in (t,x) on a common neighborhood, sufficient for the local flow and the derivatives below.

For sign clarity distinguish

$$\omega_{\mathrm{can}} = \sum_{a=1}^{2} dq_a \wedge dp_a, \qquad \Omega_0 = -\omega_{\mathrm{can}} = \sum_{a=1}^{2} dp_a \wedge dq_a, \qquad J_c = \begin{pmatrix} 0 & I_2 \\ -I_2 & 0 \end{pmatrix}.$$

Thus the coefficient matrix of Ω_0 is $-J_c$, $X_H = J_c \nabla H$, and $\iota_{X_H}\Omega_0 = -d_x H$. This is the sign convention used for the Birkhoff action below; changing every two-form sign changes no nondegeneracy assertion.

S23.1 What a scalar integrating factor would require

Since $\iota_X \Omega_0 = -d_x H + \sum_a F_a\, dq_a$, Cartan's formula gives

$$\mathcal{L}_X \Omega_0 = d_x \left(\sum_a F_a\, dq_a \right). \tag{S63}$$

Write $F_q = (\partial_{q_b} F_a)_{ab}$ and $F_p = (\partial_{p_b} F_a)_{ab}$. The coefficient matrix of this Lie derivative is

$$\begin{pmatrix} F_q^{\mathsf{T}} - F_q & -F_p \\ F_p^{\mathsf{T}} & 0 \end{pmatrix}. \tag{S64}$$

The Hamiltonian Hessian cancels from this expression only after its complete mixed derivatives are included in DX.

Proposition S24. Criterion for the scalar ansatz. *A nowhere-zero scalar $\mu(t)$ satisfies $(\partial_t + \mathcal{L}_X)(\mu\Omega_0) = 0$ if and only if, with $\gamma(t) = \mu'(t)/\mu(t)$,*

$$F_p = -\gamma(t) I_2, \qquad F_q = F_q^{\mathsf{T}}. \tag{S65}$$

For prescribed or held input these conditions read

$$R(q) H_{pp}(q,p) = \gamma(t) I_2, \qquad \partial_{q_b} F_a = \partial_{q_a} F_b.$$

When they hold, $\mu(t) = \mu(t_0) \exp \int_{t_0}^{t} \gamma(s)\, ds$.

Proof. Insert (S64) into $\mu' \Omega_0 + \mu \mathcal{L}_X \Omega_0 = 0$ and compare all blocks. The stated exponential solves the remaining scalar equation.

Allowing a state-dependent scalar does not remove this obstruction while keeping a symplectic two-form in four dimensions. Indeed, $d_x(\mu\Omega_0) = d_x\mu \wedge \Omega_0$, and the map $\alpha \mapsto \alpha \wedge \Omega_0$ from one-forms to three-forms is invertible here. Closedness therefore forces $d_x \mu = 0$ on each connected state neighborhood. This particular restriction fails in two-dimensional phase space, where every three-form vanishes.

The current full-phase model must use

$$H_{pp} = G^{-1} + N_{pp}, \qquad H_{pq_b} = -G^{-1} G_{q_b} G^{-1} p + N_{pq_b} \tag{S66}$$

for the learned pair; the reference pair omits the N derivatives. The scalar condition is neither a consequence of positive semidefinite R nor of a small learned error. In particular, the reference identity $R_* = a(G - K_r)$, with the declared $a > 0$, gives $R_* H_{*,pp} = a(I - K_r G^{-1})$, not an assumed scalar drag. If $K_r \neq 0$ and G is nonconstant on an open configuration set, this matrix cannot equal one state-independent scalar γI_2 throughout that set: $(a - \gamma)G = aK_r$ would otherwise force G constant, while $\gamma = a$ would force $K_r = 0$. This is an obstruction to the scalar ansatz, not to general Birkhoff structures.

There is a still stronger obstruction to retaining simultaneously the special potentials $\theta = \sum_a [p_a + A_a(q,t)] dq_a$ and the unmodified Birkhoff function $H_B = H$. In one degree of freedom, or if $d_q(A_a dq_a) = 0$, their equations require $\partial_t A = -F = RH_p - gu$, whereas $\partial_p \partial_t A = 0$. For prescribed input the latter identity requires $RH_{pp} = 0$. Even allowing a configuration curl does not repair the nonzero symmetric-damping case with invertible H_{pp}. Indeed, put $C_{ab} = \partial_{q_a} A_b - \partial_{q_b} A_a$. The equations then give $F = CH_p - \partial_t A$, so $-RH_{pp} = CH_{pp}$ requires $C = -R$. Since C is skew symmetric and R is symmetric, this forces $R = 0$. In the nonzero dissipative mechanical reference, $H_{*,pp} = G^{-1}$ is invertible and $R_* \neq 0$,

so this particular construction is incompatible. An integral along an already known trajectory does not establish the required partial-derivative identities for a function of independent (q, p, t).

S23.2 A general local construction

Let Φ_{t,t_0} be the genuine nonautonomous local flow of (S62), and shrink the time interval and initial neighborhood so that it is a diffeomorphism onto its image. Define

$$\Omega_t = (\Phi_{t,t_0}^{-1})^* \Omega_0. \tag{S67}$$

This construction is available separately for the learned and reference fields, without a conformal-symplectic assumption.

Proposition S25. Transported local symplectic form. *The forms (S67) are closed and nondegenerate, and satisfy*

$$d_x \Omega_t = 0, \qquad \partial_t \Omega_t + \mathcal{L}_{X_t} \Omega_t = 0, \qquad \Phi_{t,t_0}^* \Omega_t = \Omega_0. \tag{S68}$$

Writing $\Omega_t = \frac{1}{2} K_{ij}(t,x) dx_i \wedge dx_j$, and $Q(t, x_0) = D_{x_0} \Phi_{t,t_0}(x_0)$, gives along a trajectory

$$K(t, \Phi_{t,t_0}(x_0)) = Q^{-\mathsf{T}}(-J_c) Q^{-1}, \qquad \dot{Q} = DX(t, \Phi_{t,t_0}(x_0)) Q. \tag{S69}$$

The pointwise PDE is

$$\partial_t K + X^k \partial_k K + (DX)^{\mathsf{T}} K + K DX = 0.$$

Proof. Pullback commutes with d_x and preserves nondegeneracy under a diffeomorphism. The pullback identity follows immediately from the definition. Differentiating it in time proves the transport equation. The tensor transformation law and the variational equation give (S69). In particular, Q is invertible for the local flow; no inverse is asserted beyond its existence domain.

A matrix evolved along only one trajectory does not, by itself, prove spatial closedness on a neighborhood. Closedness here is supplied by the actual field of flow maps in (S67). The preserved relation compares the endpoint forms Ω_t and Ω_s: $\Phi_{t,s}^* \Omega_t = \Omega_s$. It need not preserve the fixed canonical form or fixed canonical volume.

Proposition S26. Local Birkhoff action. *On a sufficiently small common star-shaped state chart W, the transported dynamics admits a time-dependent one-form θ_t and function $H_B(t,x)$ such that*

$$d_x \theta_t = \Omega_t, \qquad \partial_t \theta_t + \iota_{X_t} \Omega_t = -d_x H_B. \tag{S70}$$

The Euler–Lagrange equations of

$$\mathcal{A}[x] = \int [\theta_i(t,x) \dot{x}_i - H_B(t,x)] \, dt$$

are precisely $\dot{x} = X(t,x)$.

Proof. Choose a fixed star center c, put $y = x - c$, and apply the Poincare homotopy at each time:

$$\theta_i(t, c+y) = \int_0^1 s \, y^j K_{ji}(t, c+sy) \, ds.$$

Closedness gives $d_x \theta_t = \Omega_t$. The one-form $\beta_t = \partial_t \theta_t + \iota_{X_t} \Omega_t$ is closed because

$$d_x \beta_t = \partial_t \Omega_t + \mathcal{L}_{X_t} \Omega_t = 0.$$

Thus one may take

$$H_B(t, c+y) = -\int_0^1 \beta_t(c+sy)[y] \, ds + h(t).$$

Its state differential is $-\beta_t$. Variation with fixed endpoints gives

$$K_{ij}(t,x) \dot{x}_j - \partial_{x_i} H_B - \partial_t \theta_i = 0. \tag{S71}$$

Equation (S70) is the same equation with $\dot{x} = X$; nondegeneracy makes the two equivalent. With $D_i = -\partial_{x_i} H_B - \partial_t \theta_i$, these coefficients obey

$$K_{ij} + K_{ji} = 0, \quad \partial_k K_{ij} + \partial_i K_{jk} + \partial_j K_{ki} = 0, \quad \partial_t K_{ij} = \partial_j D_i - \partial_i D_j.$$

The factor $1/2$ in the two-form convention is necessary for $\Omega_t = d_x(\theta_i dx_i)$ with this definition of K.

In space-time, the exact two-form $d_{t,x}(\theta_i dx_i - H_B dt)$ has the suspended vector field $\partial_t + X_t$ in its kernel. This is the corresponding space-time compatibility statement; $d_x \Omega_t = 0$ alone is not a time-transport condition. Gauge changes $\theta \mapsto \theta + d_x\chi$, $H_B \mapsto H_B - \partial_t \chi$ change the action only by an endpoint term. The constructed H_B is not asserted to equal the physical or learned energy.

S23.3 Derivative and input qualifications

Every derivative in (S69) must use the actual field. For a differentiable feedback law $u = u(t, q, p)$,

$$\begin{aligned} DX &= \begin{pmatrix} H_{pq} & H_{pp} \\ -H_{qq} + F_q & -H_{qp} + F_p \end{pmatrix}, \\ F_p &= -RH_{pp} + g(\nabla_p u)^{\mathsf{T}}, \\ \partial_{q_b} F &= -R_{q_b} H_p - RH_{pq_b} + u\partial_{q_b} g + g\partial_{q_b} u, \\ \partial_{q_b} g &= -dd_b \sin(d^{\mathsf{T}} q). \end{aligned}$$

For $\widehat{R} = S\widehat{M}S^{\mathsf{T}}$, in particular,

$$\widehat{R}_{q_b} = S_{q_b}\widehat{M}S^{\mathsf{T}} + S\widehat{M}_{q_b}S^{\mathsf{T}} + S\widehat{M}S^{\mathsf{T}}_{q_b}.$$

Neither these derivatives nor N_p, N_{pp}, N_{pq} may be discarded. For prescribed input only the input state derivatives vanish. Since $g = \nabla_q \sin(d^{\mathsf{T}} q)$, its prescribed-input contribution has zero configuration curl, but the variable-matrix damping still requires its own curl condition for the scalar ansatz.

A fixed finite recorded sequence of exogenous holds defines smooth flows on its open hold intervals. At each switch there is no physical state reset. Propagate the terminal two-form as the initial form for the next interval. The transported form is then continuous and piecewise differentiable, and the endpoint pullback relations compose. The classical time PDE and action equations hold on each open segment; no classical time derivative at an input jump is claimed.

For sampled feedback, a command is constant inside a hold conditional on its recorded value. Differentiating the closed-loop one-step map $x \mapsto \Phi_h(x, \kappa(x))$ instead requires $D_x\Phi_h + D_u\Phi_h D\kappa$. Guard branches, measurement memory and ledger/controller states may also prevent a smooth four-dimensional closed-loop flow. The prescribed-input construction does not silently certify that hybrid map or its switching surfaces.

The construction proves a local structure-existence result for each specified smooth field. Computing its coefficients through the unknown flow or its variational equation is not a low-cost implementation of that flow. A useful discrete Birkhoff method still needs a computable nondegenerate approximation, the correct two-endpoint pullback identity, an applicable generating-function chart and truncation/solver error bounds. No new sampled-safety certificate, dissipative KAM result or performance advantage follows from local structure existence alone.

S24 Computable local forms for the dissipative midpoint map

Pullback identities, preservation of closedness under pullback, and the local primitives used below are standard differential-geometric facts. The construction applies them to the actual learned dissipative field and its computable midpoint maps; it is not a new general Birkhoff theorem.

Let $x = (q, p) \in U \subset \mathbb{R}^4$, with $J = \left(\begin{smallmatrix} 0 & I_2 \\ -I_2 & 0 \end{smallmatrix}\right)$. The actual frozen energy $H = \widehat{H}$ retains all momentum derivatives. For a prescribed held command u, write

$$f^u(x) = \begin{pmatrix} H_p \\ -H_q + F \end{pmatrix}, \qquad F(q, p; u) = -\widehat{R}(q)H_p(q, p) + ug(q), \quad g(q) = d\cos(d^{\mathsf{T}} q). \tag{S72}$$

Here $\widehat{R} = S\,\mathrm{Re}(LL^*)S^\mathsf{T}$ is the separately fitted PSD head composed with the same mechanical metric. On a real chart where the metric is positive definite and the frozen network expressions are smooth, this defines a smooth real field. Throughout one hold u is exogenous and constant.

S24.1 Local solvability, inverse and derivative

The implicit midpoint equation is

$$y = \Phi_h^u(x) = x + hf^u(m), \qquad m = (x+y)/2. \tag{S73}$$

Suppose a closed midpoint ball is mapped into itself by $m \mapsto x + (h/2)f^u(m)$, and $|h|L/2 < 1$, where L bounds $\|Df^u\|$ on that ball. Also require the endpoint and relevant neighbourhoods to remain in the chart. A sufficient self-map condition is $|h| \sup \|f^u\|/2 \le r$ for a midpoint ball of radius r; the endpoint chart must also contain its reflected ball of radius $2r$. The contraction theorem gives a unique midpoint on that branch. The implicit-function theorem then gives a local diffeomorphism. With

$$A = Df^u(m), \qquad B = I - hA/2, \qquad C = I + hA/2,$$

both B and C are invertible under the same norm bound, and

$$D\Phi_h^u(x) = B^{-1}C, \qquad (\Phi_h^u)^{-1} = \Phi_{-h}^u \tag{S74}$$

on compatible local branches. The inverse identity follows by reversing the same midpoint equation; uniqueness identifies the branches. Differentiating (S73) gives $B\,dy = C\,dx$. No unknown exact continuous flow is used to construct this inverse.

Proposition S27. Exact canonical defect of midpoint. *On the stated local branch, $D = D\Phi_h^u(x)$ satisfies*

$$D^\mathsf{T}JD - J = hB^{-\mathsf{T}}(A^\mathsf{T}J + JA)B^{-1}. \tag{S75}$$

For the complete actual field,

$$A = \begin{pmatrix} H_{pq} & H_{pp} \\ -H_{qq} + F_q & -H_{qp} + F_p \end{pmatrix},$$
$$A^\mathsf{T}J + JA = \begin{pmatrix} F_q - F_q^\mathsf{T} & F_p \\ -F_p^\mathsf{T} & 0 \end{pmatrix}. \tag{S76}$$

Proof. B and C are polynomials in the same matrix A, hence commute. Thus $D = CB^{-1}$, and

$$D^\mathsf{T}JD - J = B^{-\mathsf{T}}(C^\mathsf{T}JC - B^\mathsf{T}JB)B^{-1}.$$

Expanding the middle difference cancels the constant and quadratic terms, leaving $h(A^\mathsf{T}J + JA)$. Symmetry of the Hessian of H cancels its terms in (S76).

In particular, every momentum derivative of the learned correction is retained in

$$F_p = -\widehat{R}H_{pp},$$
$$(F_q)_{ij} = -\sum_k (\partial_{q_j}\widehat{R}_{ik})H_{p_k} - \sum_k \widehat{R}_{ik}H_{p_kq_j} + u\partial_{q_j}g_i,$$
$$\partial_{q_j}g_i = -d_i d_j \sin(d^\mathsf{T}q).$$

The magnetic derivative is symmetric for a fixed command, but the full expression is included. The two-form defect generally does not vanish in the presence of damping. Implicit midpoint is therefore not canonically symplectic for this dissipative field. The fact that $H' = -H_p^\mathsf{T}\widehat{R}H_p + ug^\mathsf{T}H_p$ is a separate power identity and does not imply canonical symplecticity.

S24.2 Discrete transported forms

Let $\Phi_n = \Phi_{h_n}^{u_n}$ be a finite sequence of such local diffeomorphisms with compatible domains. Start with a closed, nondegenerate two-form Ω_0, and define the field of forms

$$\Omega_{n+1} = (\Phi_n^{-1})^* \Omega_n. \tag{S77}$$

Then $\Phi_n^* \Omega_{n+1} = \Omega_n$ exactly. Pullback commutes with the exterior derivative, so closedness is retained. Invertibility of $D\Phi_n$ retains nondegeneracy. Writing $\Omega_n = \frac{1}{2} dx^{\mathsf{T}} C_n(x) dx$, its coefficient field is explicitly

$$C_{n+1}(y) = D\Phi_n^{-1}(y)^{\mathsf{T}} C_n(\Phi_n^{-1}(y)) D\Phi_n^{-1}(y).$$

Consequently, along a recorded discrete orbit $x_{n+1} = \Phi_n(x_n)$,

$$C_{n+1}(x_{n+1}) = D_n^{-\mathsf{T}} C_n(x_n) D_n^{-1}. \tag{S78}$$

This is a directly computable recurrence using inverse midpoint and the Jacobian in (S74). An array of matrices at orbit points alone is not a proof of a closed field; closedness here follows from the full pullback definition.

In the Birkhoff sign convention $\theta_0 = p^{\mathsf{T}} dq$ one has $d\theta_0 = \sum_j dp_j \wedge dq_j$ and $C_0 = -J$. Put $\Psi_n = \Phi_0^{-1} \circ \cdots \circ \Phi_{n-1}^{-1}$. Then $\theta_n = \Psi_n^* \theta_0$ and $\Omega_n = d\theta_n = \Psi_n^* d\theta_0$ provide local primitives. The opposite global sign convention gives the same preservation identity. These are time-indexed discrete Birkhoff forms associated with the chosen numerical maps. They do not assert that one fixed canonical form is preserved, or that the numerical map equals the exact continuous dissipative flow.

S24.3 Local consistency with continuous form transport

For one fixed held command suppose $f^u \in C^3$ with bounded derivatives through order three on a common compact neighbourhood, and that both maps and their local inverses remain there. The midpoint local error holds in C^1:

$$\|\Phi_h^u - \varphi_h^u\|_{C^1} = O(|h|^3), \qquad \|\Phi_{-h}^u - \varphi_{-h}^u\|_{C^1} = O(|h|^3),$$

where φ_h^u is used only for this consistency comparison. Both maps expand as $x + hf^u(x) + h^2 Df^u(x) f^u(x)/2 + O(h^3)$; the same expansion for their differentiated equations follows from the bounded third derivatives. For a coefficient field $C \in C^1$, let both inverse Jacobians be bounded by M, $\|C\| \le M_C$ and $\|DC\| \le L_C$ on the relevant segments. If the inverse maps differ by ϵ_0 and their Jacobians by ϵ_1, then

$$\|(\Phi_{-h}^u)^* C - (\varphi_{-h}^u)^* C\| \le 2MM_C\epsilon_1 + M^2 L_C \epsilon_0 = O(|h|^3). \tag{S79}$$

This follows by inserting and subtracting the two mixed matrix products in the pullback formula. A uniform many-step estimate requires additional bounds on the transported fields and their domains; it is not implied by this local estimate alone.

The construction treats each u_n as a prescribed held value. A state-dependent feedback map requires derivatives of the command selection, and nonsmooth switching may preclude a local diffeomorphism across its boundary. The present finite-step construction establishes neither a dissipative KAM theorem nor a new physical-reference sampled-control safety certificate.

The numerical prototype in this component uses implicit midpoint on the learned field. It is a separate calculation from the numerical scheme and validated reference trajectories of the sampled-feedback experiment.

S25 Sampled physical-energy safety using a full-phase learned model

Let the physical reference and the frozen learned energy be

$$H_*(q,p) = \tfrac{1}{2} p^{\mathsf{T}} G(q)^{-1} p + V_*(q), \qquad \widehat{H}(q,p) = H_*(q,p) + e(q,p), \qquad G = SS^{\mathsf{T}} \succ 0.$$

The same canonical state and dimensionless time $\tau = \omega_0 t$ are used in every bound; primes and all hold lengths below refer to τ, while t denotes physical SI time. The physical plant is

$$q' = v_* = H_{*,p}, \qquad p' = -H_{*,q} - R_* v_* + g(q)u, \qquad R_* = S M_* S^{\mathsf{T}}, \quad M_* \succeq 0, \tag{S80}$$

where $g(q) = d\cos(d^{\mathsf{T}} q)$. A separately fitted, configuration-only head supplies $\widehat{M}(q) \succeq 0$ and $\widehat{R} = S\widehat{M}S^{\mathsf{T}}$. Define

$$\widehat{v} = \widehat{H}_p, \quad e_p = \widehat{v} - v_*, \quad y_* = g^{\mathsf{T}} v_*, \quad \widehat{y} = g^{\mathsf{T}}\widehat{v}, \quad d_* = v_*^{\mathsf{T}} R_* v_*, \quad \widehat{d} = \widehat{v}^{\mathsf{T}}\widehat{R}\widehat{v}.$$

On a fixed real domain $\mathcal{D}$, assume sound same-model certificates

$$|e| \le \varepsilon_H, \qquad |e_{p,j}| \le \varepsilon_{p,j}, \qquad \|\widehat{M} - M_*\|_2 \le \delta_M. \tag{S81}$$

These are certificates for the two specified frozen functions; they do not assert joint retraining or identification of an unknown physical plant.

Transport of a learned sample to physical power. At a real state put

$$z = S^{\mathsf{T}}\widehat{v}, \quad \eta = S^{\mathsf{T}} e_p, \quad a \ge \|z\|_2, \quad b \ge \|\eta\|_2, \quad \bar{m} \ge \|\widehat{M}\|_2.$$

Valid choices include

$$a^2 \ge \widehat{v}^{\mathsf{T}} G \widehat{v}, \qquad b^2 \ge \varepsilon_p^{\mathsf{T}} |G| \varepsilon_p,$$

where $|G|$ is the entrywise absolute value. Then

$$|y_* - \widehat{y}| \le \sum_j |g_j|\varepsilon_{p,j} \le \sum_j |d_j|\varepsilon_{p,j}, \qquad d_* \ge \widehat{d} - 2\bar{m}ab - \delta_M(a+b)^2. \tag{S82}$$

Indeed, $S^{\mathsf{T}} v_* = z - \eta$ and

$$\begin{aligned} d_* &= (z-\eta)^{\mathsf{T}}\widehat{M}(z-\eta) + (z-\eta)^{\mathsf{T}}(M_* - \widehat{M})(z-\eta) \\ &\ge z^{\mathsf{T}}\widehat{M}z - 2\bar{m}ab - \delta_M(a+b)^2. \end{aligned}$$

The nonnegative term $\eta^{\mathsf{T}}\widehat{M}\eta$ was discarded. Thus no term involving e_p is removed by identifying the physical and learned velocities.

Let an observation box $C_k \subset \mathcal{D}$ contain the true sampled state. Suppose an interval computation encloses $\widehat{y}(C_k)$, provides a lower bound $\widehat{d_k^-}$ for $\widehat{d}$ throughout C_k, and upper bounds $\bar{a}_k, \bar{b}_k, \bar{m}_k$ for the quantities above. It may return rational values $\widetilde{y}_k, e_{y,k}, \underline{d}_k$ with

$$[\widehat{y_k^-}, \widehat{y_k^+}] + [-E_{p,k}, E_{p,k}] \subseteq [\widetilde{y}_k - e_{y,k}, \widetilde{y}_k + e_{y,k}], \qquad E_{p,k} \ge \sup_{C_k} \sum_j |g_j|\varepsilon_{p,j},$$

$$0 \le \underline{d}_k \le \max\{0, \widehat{d_k^-} - 2\bar{m}_k\bar{a}_k\bar{b}_k - \delta_M(\bar{a}_k + \bar{b}_k)^2\}. \tag{S83}$$

Consequently $|y_*(\tau_k) - \widetilde{y}_k| \le e_{y,k}$ and $\underline{d}_k \le d_*(\tau_k)$. Directed rounding of the error upward and of the credit downward preserves these inequalities. For a real symmetric head, its maximum absolute row sum is a valid choice for $\bar{m}_k$.

Guard and physical derivative hypotheses. Choose $0 < c < E_g$. Assume that the designated physical-energy guard component $\mathcal{G} = \{H_* \le E_g\}$ is compact and strictly contained in the state and clearance domain on which all required reference bounds hold. In particular, it lies in $\mathcal{D}$, with enough margin for the declared observation boxes. For every constant actual command $|u| \le u_{\max}$, assume

$$|y_*'| \le L_y, \qquad |d_*'| \le L_d \tag{S84}$$

up to the first guard exit. Such bounds concern only the unchanged physical reference. Previously certified bounds on a larger guard can be used after independently proving this guard's inclusion. No derivative bound for a former learned Hamiltonian or former command record is used.

Quantized sampled filter. Initially use a sound energy upper bound

$$H_*(x_0) \le W_0 = \left\lceil \max\{0, \widehat{H}^+(x_0) + \varepsilon_H\} \right\rceil_{\Delta_W} < c,$$

where $\lceil\cdot\rceil_{\Delta_W}$ rounds upward on the ledger grid. At later samples a certified fresh bound of the same form may decrease a predicted ledger by taking their minimum. Fresh evaluation is optional: retaining the valid predicted ledger suffices. No fresh reset is assumed in the present numerical record construction.

Suppose $H_*(\tau_k) \le W_k < c$, and choose an exact mathematical hold length $h_k > 0$ and $0 < \alpha < 1$. Admit a nonzero *actual* command only if $|u_k| \le u_{\max}$ and

$$I_k(u_k) := h_k(u_k\widetilde{y}_k + |u_k|e_{y,k} - \underline{d}_k) + \tfrac{1}{2}h_k^2(|u_k|L_y + L_d) \le \alpha(c - W_k). \tag{S85}$$

The command may be binary64, interpreted as its exact represented rational number. It is chosen inside an exact feasible interval and the inequality is checked for that represented value. Rounding an otherwise admissible real command toward zero is not by itself a valid substitute. For a nonzero command define

$$W_{k+1} = \lceil \max\{0, W_k + I_k(u_k)\} \rceil_{\Delta_W} \quad \text{and require} \quad W_{k+1} < c. \tag{S86}$$

If this final check fails, or there is no representable nonzero feasible command, use the separately admissible command $u_k = 0$ and $W_{k+1} = W_k$. The numerical realization uses $\alpha = 1/2$, $u_{\max} = 1/10$ and $\Delta_W = 2^{-80}$.

Safety conclusion and proof. If every observation enclosure and each actual hold satisfy the stated hypotheses, then

$$H_*(\tau_k + s) \le \max\{W_k, W_{k+1}\} < c \quad (0 \le s \le h_k), \qquad H_*(\tau_{k+1}) \le W_{k+1}. \tag{S87}$$

For a nonzero hold, physical power cancellation gives $H'_* = u_k y_* - d_*$. Before a possible first guard exit,

$$H_*(\tau_k + s) \le W_k + sB_k + \tfrac{1}{2}s^2A_k, \quad B_k = u_k\widetilde{y}_k + |u_k|e_{y,k} - \underline{d}_k, \quad A_k = |u_k|L_y + L_d \ge 0.$$

Since $s^2 \le h_k s$, this quadratic is bounded by the affine line joining W_k to $W_k + I_k(u_k)$. Clipping a negative endpoint to zero and rounding upward can only raise that line. Its two endpoints are strictly below c. For $u_k = 0$, use instead the exact physical identity $H'_* = -d_* \le 0$; no derivative reserve or learned credit is required. The strict inequality $c < E_g$ rules out the first exit and induction establishes (S87). If the sample times have no finite accumulation and the physical vector field is locally Lipschitz on the containing compact guard, bounded commands and compactness give forward completeness. This last statement remains conditional on successful sound sample evaluations at every future sample; a finite record is only a finite-horizon instance.

If only an upper bound $0 < h_k^{\mathrm{act}} \le \bar{h}_k$ on the actual holding time is known, use $\bar{h}_k$ in the gate but carry

$$W_{k+1}^{\mathrm{carry}} = \max\{W_k, W_{k+1}^{(\bar{h}_k)}\}.$$

The same affine argument then bounds the whole hold and its possibly earlier endpoint. Carrying only the endpoint at $\bar{h}_k$ is unsound when predicted power is negative and the hold ends earlier. The present mathematical protocol instead specifies exactly $\tau_k = k/1000$; binary64 ODE time tags construct numerical centres and do not replace that exact clock in an independent true-IVP validation.

Relation to a learned-energy ledger. The absence of an e_q term in the sampled gate follows from using the *physical* identity $H'_* = uy_* - d_*$. It is not an assertion that $e_q = 0$. A direct $\widehat{H}$ ledger along the physical plant requires

$$\widehat{H}' = -\widehat{d} + u\widehat{y} + e_q^{\mathsf{T}}\widehat{v} + e_p^{\mathsf{T}}(\widehat{R}\widehat{v} - \widehat{H}_q) + \widehat{v}^{\mathsf{T}}(\widehat{R} - R_*)v_*.$$

Its zero-input derivative need not be nonpositive. For example, take $H_* = (q^2 + p^2)/2$, $\widehat{H} = q^2/2 + p^2$, $R_* = \widehat{R} = 1$ and $g = 1$. At $q = -3r$, $p = r \neq 0$, $u = 0$, these functions satisfy $\widehat{H}' = r^2 > 0$ and $H'_* = -r^2$. For the input-power comparison, instead set $q = 0$ and $p = r \neq 0$. With $u = 3r/2$, the physical derivative is $H'_* = r^2/2 > 0$, whereas $-\widehat{d} + u\widehat{y} = -r^2$. Thus substituting the learned velocity for the physical velocity without (S82) can certify an incorrect power inequality.

Fixed-model instance and scope. The earlier 200-hold instance combines the original certified full-phase energy $\widehat{H}_0$ with the separately trained configuration-only complex PSD head. The GC enters the initial energy bound, the learned port, the learned dissipation and the nominal request; it is not replaced by the prior velocity $G^{-1}p$. The prospective guard uses $c = 3/2000$ and $E_g = 1001c/1000$, subject to its separate domain certificate, and the earlier finite example specifies 200 exact holds of length $1/1000$. Its sinusoidal reference has amplitude 0.003 and frequency 0.5; no tracking-convergence conclusion is asserted. Safety permits arbitrary finite nominal requests after filtering, so the particular tracking gains are not hypotheses of this theorem. The later complete-period instance with 12,567 validated holds is reported separately in article Section 5.

The earlier 200-hold example concerns a finite-dimensional numerical physical reference, not hardware execution or joint reidentification. Its state boxes must independently contain the true reference samples. Ordinary ODE solutions, agreement of two numerical tolerances, or monitoring a few interior points does not establish this premise. Actuator error, uncertain physical time, delay, external force and sensor error require their own budgets. The distributed-viscosity coefficient remains a declared numerical assumption rather than a measured calibration. The conservative KAM result for this GC does not supply these control hypotheses, and neither earlier controllers nor their executed command sequences are transferred to the new composition.

References

Abbott JJ, Diller E and Petruska AJ (2020) Magnetic methods in robotics. *Annual Review of Control, Robotics, and Autonomous Systems* 3: 57–90. doi: 10.1146/annurev-control-081219-082713

Antman SS (2005) *Nonlinear Problems of Elasticity*. 2nd ed. Springer. doi: 10.1007/0-387-27649-1

Chen Y, Matsubara T and Yaguchi T (2022) KAM theory meets statistical learning theory: Hamiltonian neural networks with non-zero training loss. *Proceedings of the AAAI Conference on Artificial Intelligence* 36(6): 6322–6332. doi: 10.1609/aaai.v36i6.20582

Desai SA, Mattheakis M, Sondak D, Protopapas P and Roberts SJ (2021) Port-Hamiltonian neural networks for learning explicit time-dependent dynamical systems. *Physical Review E* 104: 034312. doi: 10.1103/PhysRevE.104.034312

Greydanus S, Dzamba M and Yosinski J (2019) Hamiltonian neural networks. In: *Advances in Neural Information Processing Systems*, vol. 32. https://arxiv.org/abs/1906.01563.

Hairer E (2010) *Geometric Numerical Integration*, Lecture 2: Symplectic integrators. TU München, January–February 2010, Theorem 3, pp. 2–3. https://www.unige.ch/~hairer/poly_geoint/week2.pdf.

Haro À and Luque A (2019) A-posteriori KAM theory with optimal estimates for partially integrable systems. *Journal of Differential Equations* 266(2–3): 1605–1674. doi: 10.1016/j.jde.2018.08.003 Preprint version used: https://arxiv.org/abs/1711.05515v1.

Kim Y, Parada GA, Liu S and Zhao X (2019) Ferromagnetic soft continuum robots. *Science Robotics* 4(33): eaax7329. doi: 10.1126/scirobotics.aax7329

Pöschel J (2001) A lecture on the classical KAM theorem. In: *Proceedings of Symposia in Pure Mathematics*, vol. 69, pp. 707–732. doi: 10.1090/pspum/069/1858551 Preprint version used: https://arxiv.org/abs/0908.2234v1 (Version 1.3, 2009).

Simo JC (1985) A finite strain beam formulation. The three-dimensional dynamic problem. Part I. *Computer Methods in Applied Mechanics and Engineering* 49(1): 55–70. doi: 10.1016/0045-7825(85)90050-7

Trabelsi C, Bilaniuk O, Zhang Y et al. (2018) Deep complex networks. In: *International Conference on Learning Representations*. https://arxiv.org/abs/1705.09792.

Zhang SQ, Gao W and Zhou ZH (2022) Towards understanding theoretical advantages of complex-reaction networks. *Neural Networks* 151: 80–93. doi: 10.1016/j.neunet.2022.03.024 Published version used for theorem numbering.

Zhong YD, Dey B and Chakraborty A (2020) Dissipative SymODEN: Encoding Hamiltonian dynamics with dissipation and control into deep learning. In: *ICLR Workshop on Integration of Deep Neural Models and Differential Equations*. https://arxiv.org/abs/2002.08860.