Supplementary material: Complex energy learning from finite magnetic-rod observations

The International Journal of Robotics Research
XX(X):1–41
©The Author(s) 0000
Reprints and permission:
sagepub.co.uk/journalsPermissions.nav
DOI: 10.1177/ToBeAssigned
www.sagepub.com/
SAGE

Anonymous authors

The proofs concern the full 64-coordinate constant-mass mechanical model and its three-coordinate conservative restriction defined in the article. The selected network has two complex split-tanh heads and 918 real parameters. Its checkpoint SHA-256 prefix is `f51bcea12c2f`. All numerical candidate conclusions below refer to that checkpoint when identified as calibrated. Earlier time-step and fitting diagnostics are explicitly distinguished. Certificates for other architectures and momentum-dependent historical models are not inherited.

The force/coefficient interface uses exact decimal scales $\ell = 1/1000$ m and $E_s = 3/500000000000$ J. Network feature scales are their exact saved binary values and need not equal these decimal numbers. A numerical recorded-state IVP, a compiled simulation trajectory and a physical measurement are different objects; their distinct error requirements remain stated in each result.

S1 Learning a three-dimensional conservative correction

The learning variable can be the configuration rather than the complete canonical state when the kinetic energy is known and the unknown term is a configuration potential. This reduction concerns the domain on which an error function must be learned. It does not reduce the number of degrees of freedom of the Hamiltonian system.

S1.1 The restricted physical model and its learning dimension

Let A and K_3 be fixed symmetric positive definite three-by-three mass and elastic matrices, respectively. Let $d \in \mathbb{R}^3$ and $\kappa > 0$ be the fixed magnetic port and bias coefficient. Consider the real conservative Hamiltonians

$$\begin{aligned} H_\theta(q,p) &= \tfrac{1}{2}p^{\mathsf{T}}A^{-1}p + U_0(q) + W_\theta(q), \\ H_*(q,p) &= \tfrac{1}{2}p^{\mathsf{T}}A^{-1}p + U_0(q) + W_*(q), \\ U_0(q) &= \tfrac{1}{2}q^{\mathsf{T}}K_3 q + \kappa[1-\cos(d^{\mathsf{T}}q)]. \end{aligned} \tag{S1}$$

Here $q, p \in \mathbb{R}^3$, the mass is not fitted, and damping and time-dependent input are excluded from this conservative subsystem. The target W_* and a candidate W_θ are functions of q alone.

The energy-feature candidate has this structure on its trial subspace. More precisely, let M, K_0 be the full mass and elastic matrices and let V be a fixed full-column-rank trial matrix. Set $A = V^{\mathsf{T}}MV$, $K_3 = V^{\mathsf{T}}K_0V$, and $B = A^{-1}V^{\mathsf{T}}M$, so that $BV = I_3$. Its full potential correction is $F_\theta(Bx, x^{\mathsf{T}}K_0x/2)$, and its restriction is

$$W_\theta(q) = F_\theta(q, E_0(q)), \qquad E_0(q) = \tfrac{1}{2}q^{\mathsf{T}}K_3q. \tag{S2}$$

The four feature entries $(q, E_0(q))$ have only three independent real variables on this surface. For example, the centered scalar readout is

$$\begin{aligned} s(q) &= (q_1/Q_1, q_2/Q_2, q_3/Q_3, E_0(q)/E_*), \\ W_\theta(q) &= c_{\mathrm{E}} E_0(q) + E_* \left[N_\theta(s(q)) - N_\theta(0) - \sum_{j=1}^{3} \frac{q_j}{Q_j} \partial_j N_\theta(0) \right]. \end{aligned} \tag{S3}$$

The positive Q_j, E_* are the frozen exported feature scales; N_θ is the real scalar readout of the real or realified complex network. Equation (S3) implies $W_\theta(0) = 0$ and $\nabla W_\theta(0) = 0$ because $\nabla E_0(0) = 0$. It does not impose zero quadratic, cubic, or quartic corrections. The coefficient c_{E} occurs linearly.

For arbitrary full configurations, $E_0(x)$ is not determined by Bx. In that case

$$V^{\mathsf{T}} \nabla_x F_\theta(Bx, E_0(x)) = F_{\theta,q} + F_{\theta,E} V^{\mathsf{T}} K_0 x,$$

whereas the restricted force is $\nabla_q W_\theta = F_{\theta,q} + F_{\theta,E} K_3 q$ at $(q, E_0(q))$. Thus unrestricted full-field observations require the separate preparation, transfer, and conservative-label error estimates. The reduction below does not assert autonomous closure of a projected full trajectory.

Fix $\ell > 0$, $E_s > 0$, and $R > 0$, and use the normalized configuration cube and potentials

$$\Omega = [-R, R]^3, \qquad q = \ell z, \qquad w_\theta(z) = W_\theta(\ell z)/E_s, \quad w_*(z) = W_*(\ell z)/E_s. \tag{S4}$$

In the physical interface $\ell = 10^{-3}$ and $E_s = 6 \times 10^{-12}$ J. The normalization E_s need not be identified with the exact exported binary value E_* in (S3). Write $f_\theta = \nabla_z w_\theta$, $f_* = \nabla_z w_*$ and $g_\theta = f_\theta - f_*$. A normalized conservative-force label means a label for f_*, including its sign and the factor ℓ/E_s. For a vector field g, write $\|g\|_{\infty,\Omega} = \max_j \sup_{z\in\Omega} |g_j(z)|$.

Proposition S1. Exact reduction of the error domain. *Let Π be any probability law for (Z, P) on $\Omega \times \mathcal{P}$, with configuration marginal ν. For $1 \le p < \infty$, the physical canonical vector-field error obeys*

$$\begin{aligned} X_{H_\theta} - X_{H_*} &= (0, -(E_s/\ell) g_\theta(z)), \\ \mathbb{E}_\Pi \| X_{H_\theta}(\ell Z, P) - X_{H_*}(\ell Z, P) \|_p^p &= (E_s/\ell)^p \mathbb{E}_\nu \| g_\theta(Z) \|_p^p. \end{aligned} \tag{S5}$$

Moreover, a uniform potential-error bound on Ω is the same bound, multiplied by E_s, on every momentum fiber above that cube. No positive density in the momentum variables is needed for these identities.

Proof. The common kinetic and reference potential terms cancel in $H_\theta - H_*$. Its physical configuration gradient is $(E_s/\ell) g_\theta$, and its momentum gradient is zero. Applying the canonical matrix $J = \left(\begin{smallmatrix} 0 & I_3 \\ -I_3 & 0 \end{smallmatrix}\right)$ gives the first identity. The integrand is independent of P, so integration with respect to the joint law gives its integral against the configuration marginal. The potential statement follows from the same cancellation and the definition of $w_\theta - w_*$.

S1.2 A configuration-space version of the statistical energy bound

The statistical component used here is the uniform bounded-loss generalization inequality in Chen, Matsubara and Yaguchi, *KAM Theory Meets Statistical Learning Theory: Hamiltonian Neural Networks with Non-zero Training Loss*, AAAI 2022, Lemma 2. Their Poincare–Sobolev step is on the complete phase domain. Proposition S1 permits that step to be performed on Ω for the present model.

Let Θ be a hypothesis class fixed before sampling. Suppose $Z_1, \ldots, Z_N$ are iid with law ν whose Lebesgue density satisfies $\rho \ge m > 0$ on Ω. For a fixed finite $p \ge 1$, suppose

$$0 \le \|g_\theta(z)\|_p^p \le \Lambda_p \quad (z \in \Omega,\ \theta \in \Theta).$$

Let $\overline{\mathfrak{R}}_{p,N}$ be a valid upper bound for the empirical Rademacher complexity of this true loss class, with the normalization of the cited lemma. If observed labels Y_i satisfy $\|Y_i - f_*(Z_i)\|_p \le \eta$ for every i, set

$$\begin{aligned} \widehat{L}_{p,N}(\theta) &= N^{-1}\sum_i \|f_\theta(Z_i) - Y_i\|_p^p, \\ A_{p,N}(\theta,\delta) &= \left(\widehat{L}_{p,N}(\theta)^{1/p} + \eta\right)^p + 2\overline{\mathfrak{R}}_{p,N} + 3\Lambda_p\sqrt{\frac{2\log(4/\delta)}{N}}. \end{aligned} \tag{S6}$$

With probability at least $1-\delta$, simultaneously for all θ,

$$\mathbb{E}_\nu\|g_\theta\|_p^p \le A_{p,N}(\theta,\delta). \tag{S7}$$

Indeed, apply the cited lemma to the iid pairs $(Z_i, f_*(Z_i))$. The triangle inequality for the finite-sample L^p norm bounds the unobserved true empirical loss by the first term of (S6). This argument allows arbitrary label errors satisfying the stated deterministic cap; it does not require those errors to be iid. The class bounds and the complexity bound must still be justified for the whole fixed class.

Theorem S2. Three-dimensional energy reception. *Assume $p > 3$, $w_*, w_\theta \in W^{1,p}(\Omega)$, and the preceding statistical hypotheses. Define*

$$e_\theta = w_\theta - w_* - \frac{1}{|\Omega|}\int_\Omega (w_\theta - w_*)\,dz.$$

On the event (S7), uniformly in θ,

$$\|e_\theta\|_{C^0(\Omega)} \le C_{p,R}\left(\frac{A_{p,N}(\theta,\delta)}{m|\Omega|}\right)^{1/p}, \qquad C_{p,R} = 2R\,3^{1-1/p}\frac{p}{p-3}. \tag{S8}$$

The physical error is E_s times this quantity on every momentum fiber. If $W_\theta(0) = W_*(0) = 0$, the absolute error in this fixed physical energy gauge is at most twice the right-hand side of (S8), multiplied by E_s.

Proof. First take a continuously differentiable scalar u. Convexity of the cube and the segment identity imply, for $z \in \Omega$,

$$|u(z) - \overline{u}| \le \operatorname{diam}_{p'}(\Omega)\int_0^1 \frac{1}{|\Omega|}\int_\Omega \|\nabla u(z + t(y-z))\|_p\,dy\,dt, \qquad p' = \frac{p}{p-1}.$$

Holder's inequality for the inner probability integral and the change of variables $x = z + t(y-z)$ bound that inner integral by $t^{-3/p}(|\Omega|^{-1}\int_\Omega \|\nabla u\|_p^p)^{1/p}$. Here $z + t(\Omega - z) \subset \Omega$ and the Jacobian is t^3. The integral of $t^{-3/p}$ is $p/(p-3)$, and $\operatorname{diam}_{p'}(\Omega) = 2R3^{1-1/p}$. This proves the asserted deterministic inequality for smooth u. Smooth approximation in $W^{1,p}$ on a cube extends it to the continuous representative: apply the same inequality to differences of smooth approximants after mean centering to obtain uniform convergence, and identify the limit with their L^p limit. Finally, the density and risk bounds give $\int_\Omega \|\nabla e_\theta\|_p^p\,dz \le A_{p,N}/m$. Proposition S1 gives the momentum-fiber statement. For the anchored gauge, $w_\theta(z) - w_*(z) = e_\theta(z) - e_\theta(0)$; the triangle inequality gives the additional factor two.

Thus $p = 4$ is sufficient for this first-order energy estimate; the corresponding six-dimensional argument requires $p > 6$. The pth root in (S8) cannot be omitted for a pth-power loss. Ordinary mean-square training has $p = 2$ and does not itself meet $p > 3$. If an independent uniform force bound $\|g_\theta\|_\infty \le B_0$ is available, then for $p \ge 2$, $\mathbb{E}\|g_\theta\|_p^p \le B_0^{p-2}\mathbb{E}\|g_\theta\|_2^2$; this is an additional boundedness argument, not equivalence of Sobolev embeddings in different dimensions.

S1.3 A mean-square route with a quantitative force regularity prior

The following deterministic result can use any valid population-risk bound, including (S7) with $p = 2$. It avoids replacing mean-square training by an unexecuted fourth-power objective, at the cost of an independent force Lipschitz bound.

Theorem S3. A boundary-valid three-dimensional cone estimate. *Let $g : \Omega \to \mathbb{R}^3$ be continuous and let every component be L-Lipschitz with respect to Euclidean distance. Suppose ν has density at least $m > 0$ and $\mathbb{E}_\nu\|g\|_2^2 \le a$. For every*

$0 < h \le R$,

$$\|g\|_{\infty,\Omega} \le Lh + \sqrt{\frac{6a}{m\pi h^3}}. \tag{S9}$$

Consequently define the sufficient uniform-force allowance

$$\varepsilon_3(a; L, m, R) = \inf_{0<h\le R} \left(Lh + \sqrt{\frac{6a}{m\pi h^3}} \right). \tag{S10}$$

When $a = 0$ the allowance is zero. If $a, L > 0$, its minimizing radius is

$$h = \min\left\{ R, \left(\frac{3}{2L}\sqrt{\frac{6a}{m\pi}} \right)^{2/5} \right\}.$$

In the interior regime the allowance is proportional to $a^{1/5}$.

Proof. Fix $z \in \Omega$ and a component j, and put $b = |g_j(z)|$. For each coordinate choose the direction toward the more distant face of the cube. The corresponding octant of the radius-h ball centered at z is contained in Ω for $h \le R$, including when z is on a face, edge, or corner. Its volume is $\pi h^3/6$. Throughout this octant $|g_j| \ge (b - Lh)_+$, so

$$a \ge m\frac{\pi h^3}{6}(b - Lh)_+^2.$$

If $b \le Lh$, (S9) already holds; otherwise solve the last inequality for b. Take the supremum in z, j and then the infimum in h. If $a = 0$, continuity and a positive density imply $g = 0$ everywhere. For $a, L > 0$, differentiation of the displayed one-variable objective gives the stated minimizer. If $L = 0$, the objective is minimized at $h = R$; a sharper bound in this constant-field case is $\|g\|_{\infty,\Omega} \le \sqrt{a}$.

For a d-dimensional cube the same proof uses the inward orthant volume $c_d h^d$, where $c_d = |B_1^d|/2^d$, and gives $\inf_h\{Lh + \sqrt{a/(mc_d h^d)}\}$. Its interior risk exponent is $1/(d+2)$: $1/5$ for three configuration variables and $1/8$ for six phase variables. This improves the interpolation exponent. It does not remove the need for iid configuration sampling, a density lower bound, class-wide bounds, or a small observed training loss.

If $g_\theta = \nabla(w_\theta - w_*)$ has the allowance ε, integration on line segments gives

$$\sup_{\Omega} |w_\theta - w_* - w_\theta(0) + w_*(0)| \le 3R\varepsilon. \tag{S11}$$

For the mean-zero energy gauge, the sufficient bound is instead $6R\varepsilon$. Both follow by integrating the componentwise gradient bound along a segment in the convex cube, and, for the latter, averaging the resulting difference between two points.

S1.4 Reception of the Hessian and the cubic and quartic jets

Small force error does not alone control the derivatives needed by the normal form. The next result lists the additional orders separately. For a multi-index α, $|\alpha|$ denotes its total degree, $\alpha! = \prod_i \alpha_i!$, and D^α denotes the corresponding ordinary real partial derivative.

Theorem S4. Low-order derivative reception. *Suppose $g = \nabla(w_\theta - w_*)$ and $\|g\|_{\infty,\Omega} \le \varepsilon$. For $k \in \{1, 2, 3\}$, assume $g \in C^{k+1}(\Omega)$ and that every component derivative of total order $k+1$ has absolute value at most B_{k+1} on Ω. For $|\alpha| = k$, every component satisfies*

$$|D^\alpha g_j(0)| \le J_k(\varepsilon, B_{k+1}, R) := \inf_{0<h\le R/k} \left(\frac{2^k\varepsilon}{h^k} + \frac{kB_{k+1}h}{2} \right). \tag{S12}$$

When $\varepsilon, B_{k+1} > 0$, take

$$h = \min\{R/k, (2^{k+1}\varepsilon/B_{k+1})^{1/(k+1)}\}.$$

In the interior regime the bound equals $(k+1)B_{k+1}^{k/(k+1)}\varepsilon^{1/(k+1)}$.

Let $c_{\theta,\beta}$ and $c_{*,\beta}$ be ordinary Taylor coefficients of the normalized potentials, so their definition includes division by $\beta!$. For $d = 2, 3, 4$ and $|\beta| = d$,

$$|c_{\theta,\beta} - c_{*,\beta}| \le \frac{J_{d-1}(\varepsilon, B_d, R)}{\beta!}. \tag{S13}$$

In particular, the normalized Hessian operator error is at most $3J_1$.

Proof. For a coordinate unit vector e_i define $\Delta_{h,i}u(z) = u(z + he_i) - u(z)$ and $\Delta_h^\alpha = \prod_i \Delta_{h,i}^{\alpha_i}$. Choose $i_1, \dots, i_k$ with α_i occurrences of coordinate i. Repeated use of the fundamental theorem of calculus gives

$$h^{-k}\Delta_h^\alpha g_j(0) = \int_{[0,1]^k} D^\alpha g_j \left(h \sum_{r=1}^{k} t_r e_{i_r} \right) dt.$$

All evaluation points and their segments from zero lie in Ω when $h \le R/k$. The derivative bounds imply that the integrand differs from $D^\alpha g_j(0)$ by at most $B_{k+1}h\sum_r t_r$. Its integral is at most $kB_{k+1}h/2$. On the other hand, the binomial coefficients in Δ_h^α have absolute sum 2^k, so $|\Delta_h^\alpha g_j(0)| \le 2^k\varepsilon$. Combining the two estimates proves (S12). Direct minimization gives the stated radius and interior value. Zero bounds follow by taking limits.

For $|\beta| = d$, choose j with $\beta_j > 0$ and set $\alpha = \beta - e_j$. Then $D^\beta(w_\theta - w_*) = D^\alpha g_j$. Divide by $\beta!$ to obtain (S13). Every Hessian entry is at most J_1; its maximum row sum and hence its symmetric operator norm are at most $3J_1$.

The three required priors are bounds on $D^3(w_\theta - w_*)$, $D^4(w_\theta - w_*)$, and $D^5(w_\theta - w_*)$, respectively. A fifth-derivative bound alone is not substituted for the third- and fourth-derivative bounds. A certified sum of the candidate and target bounds suffices for each order. The force Lipschitz constant in Theorem S3 instead concerns $D^2(w_\theta - w_*)$ and is a separate, lower-order prior. For physical derivatives the degree-d allowance is multiplied by $E_s\ell^{-d}$; for coefficients of $W(\ell z)$ it is multiplied only by E_s.

Here is an explicit spectral consequence. Suppose the physical target Hessian $K_* = D_q^2(U_0 + W_*)(0)$ is positive definite. Set

$$\zeta = 3E_s\ell^{-2}J_1, \qquad \upsilon = \|A^{-1}\|_2\zeta. \tag{S14}$$

Then $\zeta < \lambda_{\min}(K_*)$ implies $K_\theta > 0$. If $\omega_{*,1} \le \omega_{*,2} \le \omega_{*,3}$ are the positive target frequencies and $\upsilon < \omega_{*,1}^2$, the corresponding ordered candidate frequencies satisfy

$$|\omega_{\theta,j} - \omega_{*,j}| \le \frac{\upsilon}{\sqrt{\omega_{*,1}^2 - \upsilon} + \omega_{*,1}} =: \Delta_\omega. \tag{S15}$$

Indeed, the mass-normalized symmetric Hessian perturbation has norm at most υ. The variational eigenvalue bounds therefore give $|\omega_{\theta,j}^2 - \omega_{*,j}^2| \le \upsilon$; factor the difference of squares to obtain (S15). Thus a positive target divisor margin

$$\Delta_* := \min_{k \in \mathbb{Z}^3,\, 1 \le |k|_1 \le 4} |k \cdot \omega_*|$$

remains positive for the candidate if $4\Delta_\omega < \Delta_*$. This finite-order condition supports the degree-four normal form; it is not an all-integer Diophantine assertion.

The six quadratic, ten cubic, and fifteen quartic coefficient intervals in (S13), with their physical scales, can be passed to a spectrum and Birkhoff normal-form verifier. The verifier must include the cubic homological correction to the quartic term and prove a nonzero twist determinant uniformly over the admitted intervals. A center-point determinant is insufficient for the whole family. If these conditions and the separate analytic hypotheses of the local elliptic KAM criterion hold for a selected candidate with an equilibrium at the origin, that criterion applies to this same candidate. The learning estimates supply accuracy and jet uncertainty; they do not replace any of those KAM hypotheses.

S1.5 What the dimension reduction establishes and what it leaves open

The real estimates above do not establish a quantitative pole-free complex neighborhood. A realified split-tanh network is continued in the complexified physical coordinates, with independent continued real and imaginary channels. Evaluating a real-part operation at complex arguments is not that continuation. A quantitative outer-domain bound, target regularity

when needed, and the same selected weights are required for analytic interpolation or an analytic KAM certificate. Existing strip-interpolation and local normal-form results may then be used with their own stated hypotheses.

Two examples separate the necessary assumptions. First, on the fixed cube take $u_a(z) = \exp(-|z|_2^2/a^2)$ and subtract its mean. These are real-analytic functions. Their force mean-square integral is at most $3\pi^{3/2}a/2^{3/2}$, while their mean-zero sup norm does not tend to zero: the mean is at most $\pi^{3/2}a^3/|\Omega|$ and $u_a(0) = 1$. Thus three dimensions do not make $W^{1,2}$ embed in C^0, even within real-analytic functions without uniform regularity bounds. Second,

$$v_k(z) = k^{-2}[1 - \cos(kz_1)]$$

has uniformly vanishing force, a force Lipschitz constant at most one, and $\partial_{11}v_k(0) = 1$ for every k. Its fourth derivative at zero has magnitude k^2. Therefore neither a small force nor the cone estimate alone gives small Hessian and quartic errors. The separately stated derivative priors or a higher-order jet receiver are substantive.

The present statements implement the configuration-potential part of the proposed learning-to-KAM route. They do not assert that an optimizer attains a small population risk. In particular, repeated velocities at one configuration, two finite-difference step diagnostics at the same configuration, or correlated trajectory windows do not provide iid configuration coverage with a positive three-dimensional density. A force-label cap received at one prepared point is not a population-risk estimate. Actual selected weights must have their own training record and all the required class, label, regularity, analytic, and normal-form bounds. The arguments apply to real and realified complex potentials alike and do not prove a complex-network advantage or a safety statement for a driven dissipative full-state system.

S2 Finite-trajectory conservative-force reception

S2.1 Removing finite-window bias without assuming exact observations

The preceding finite label is an average along a trajectory. It is not an instantaneous force measurement. This distinction persists even when the momentum increment and the magnetic integral are computed exactly. Let $s_\sigma(t)$ be the dimensionless projected sum of the unknown conservative force and dissipative force on the physical trajectory with sign label $\sigma \in \{+, -\}$. More precisely, for the full native model let

$$s_\sigma(t) = \frac{\ell}{E_s} V^T \{\nabla(E_{\mathrm{el},0} + \mathcal{W}_*)(x_\sigma(t)) + D_*(x_\sigma(t))v_\sigma(t)\}.$$

Here $E_{\mathrm{el},0}(x) = x^T K_0 x/2$ is the nominal elastic potential and $\mathcal{W}_*$ is its unknown full-coordinate correction; its reduced restriction is $W_*(q) = \mathcal{W}_*(Vq)$. The symbol E_s remains the constant energy scale. Put

$$\begin{aligned} P_\sigma &= (\ell/E_s)V^T M v_\sigma, \\ m_\sigma &= (\ell/E_s)V^T b\{\kappa \sin(b^T x_\sigma) - \mu u_\sigma \cos(b^T x_\sigma)\}, \\ f_* &= (\ell/E_s)V^T \nabla \mathcal{W}_*(x_{\mathrm{prep}}). \end{aligned}$$

The sign convention is $\dot{P}_\sigma + s_\sigma + m_\sigma = 0$; the input u_σ is the applied transverse magnetic field. Thus an exact observed-momentum expression is

$$Y(T) = -\frac{1}{2} \sum_{\sigma=+,-} \left\{ \frac{P_\sigma(T) - P_\sigma(0)}{T} + \frac{1}{T} \int_0^T m_\sigma(t)\, dt \right\} - f_0.$$

The magnetic quantities B_m, ϵ_m below refer to this scaled vector m_σ, and ϵ_p refers to P_σ. The prepared full-coordinate position may include saved rounding; the additional transfer to an ideal reduced design node is stated below. The known magnetic force is accounted for separately. Define $S = (s_+ + s_-)/2$ and $f_0 = \ell V^T K_0 x_{\mathrm{prep}}/E_s$. With exact momentum increments and exact magnetic integrals, the paired label is

$$Y(T) = \frac{1}{T} \int_0^T S(t)\, dt - f_0.$$

This identity uses the physical equations. Exact initial-position and opposite-velocity symmetry would remove the initial dissipative term; the following result instead retains an explicit initial allowance.

Proposition S5. A finite-window force receiver. *Suppose* $S \in C^3([0,4T])$, $T>0$, *and* $\sup_{[0,4T]} \|S'''\|_\infty \le B_3$. *Put*

$$\mathcal{R}_T Y = \tfrac{8}{3}Y(T) - 2Y(2T) + \tfrac{1}{3}Y(4T).$$

If f_* *is the desired conservative correction force at the prepared configuration and* $\|S(0) - f_0 - f_*\|_\infty \le I_0$, *then*

$$\|\mathcal{R}_T Y - f_*\|_\infty \le I_0 + \tfrac{1}{3}B_3 T^3. \tag{FW1}$$

For a receiver based on saved endpoint momenta and composite trapezoids, assume additionally that: each scaled projected endpoint momentum has error at most ϵ_p*; each sampled projected magnetic force has error at most* ϵ_m*; and the exact projected magnetic force on each signed trajectory has second derivative bounded by* B_m. *Use exact times, with endpoints* $T, 2T, 4T$ *and maximum panel width* h. *Then the observed receiver satisfies*

$$\|\widehat{\mathcal{R}_T Y} - f_*\|_\infty \le I_0 + \frac{B_3 T^3}{3} + \frac{5B_m h^2}{12} + 5\epsilon_m + \frac{11\epsilon_p}{2T}. \tag{FW2}$$

All bounds concern the same physical model, signed trajectories and normalization. None of $I_0, B_3, B_m, \epsilon_p, \epsilon_m$ *is inferred solely from a small observed weak residual or a coarse–fine difference.*

Proof. The three weights sum to one. Their first and second moments at $(T, 2T, 4T)$ vanish. Thus constants are preserved and the linear and quadratic temporal terms are removed. Taylor's formula with integral remainder gives

$$\mathcal{R}_T Y - (S(0) - f_0) = \int_0^{4T} K_T(u) S'''(u)\, du,$$

where, writing $v = u/T$, $K_T(u) = T^2 k(v)$ and

$$k(v) = \begin{cases} v^2(12 - 7v)/24, & 0 \le v \le 1, \\ \{(4-v)^3 - 12(2-v)^3\}/72, & 1 \le v \le 2, \\ (4-v)^3/72, & 2 \le v \le 4. \end{cases}$$

This kernel is nonnegative: on $[1,2]$ use $4 - v \ge 3(2-v) \ge 0$; the other pieces have the stated sign directly. Exact integration gives $\int_0^4 k(v)\, dv = 1/3$. This proves (FW1), including the initial allowance.

The absolute sum of the averaging weights is 5. A composite trapezoidal average has error at most $B_m h^2/12$, and the sampled-force error contributes at most ϵ_m. Averaging the two signs retains these common bounds. For either sign, the momentum combination has endpoint coefficients, in the order $0, T, 2T, 4T$,

$$\frac{1}{T}\left(-\tfrac{7}{4},\ \tfrac{8}{3},\ -1,\ \tfrac{1}{12}\right).$$

Their absolute sum is $11/(2T)$. These facts give (FW2).

If the two signs have different exact saved clocks, each receiver must be formed on its own clock. Exact Lagrange weights are obtained from the three actual durations; the corresponding kernel and observation constants must then be received for those durations. Changing the negative-velocity label does not change the direction of time.

Interpretation of the saved-data diagnostics. The predeclared diagnostic evaluated all windows of $1, 2, 4, 8, 12, 16, 24, 32, 64, 128, 256$ panels, all specified first-order pairs, and all specified second-order triples. No model was refitted and no best window was selected. At direction 3 on the finer record, the old 12-panel label differs from the declared material force by about 2.15835×10^{-4} in its largest component. The decomposition contains an elastic time-average drift of about 2.16072×10^{-4}, an even dissipative contribution of about 3.32821×10^{-7}, and a negative

averaged weak-residual contribution of magnitude about 5.69840×10^{-7}. These are signed vector terms; their maxima must not be added as if their signs and maximizing coordinates agreed.

The fixed $1, 2, 4$-panel formula reduces the observed discrepancy from the declared material force to about 2.32485×10^{-8} at direction 2 and 1.76758×10^{-7} at direction 3 on the finer records. These are evaluator diagnostics. In contrast, the first-order $12, 24$-panel formula makes the direction-3 discrepancy about 4.28863×10^{-4}, illustrating why a temporal-bias model matters. The old 12-panel momentum slope has endpoint-noise factor $1/(6T)$; the new formula has factor $11/(2T)$, which is 33 times larger. Reduced bias therefore comes with increased sensitivity to endpoint errors. The saved-data comparison supplies neither the continuous observation allowances nor the derivative bounds in (FW2).

The refined receiver uses the recorded observations and known native operators. Constitutive evaluator coefficients enter only the subsequent comparison. This calculation does not identify a general unknown quartic, satisfy iid sampling assumptions, or establish a KAM transfer. Its role is to expose and remove a specific finite-window bias before further configuration measurements are interpreted.

A fourth window and the regularity required by the jet receiver. The C^5 potential regularity used in the fourth-order jet receiver below also motivates one further temporal cancellation, provided the dissipative law and input have the corresponding regularity along the trajectories. For $S \in C^m([0, a_m T])$ define $A(t) = \int_0^1 S(ut)\, du$, including $A(0) = S(0)$. Then $\|A^{(m)}\|_\infty \le \mathcal{B}_m/(m+1)$ when $\|S^{(m)}\|_\infty \le \mathcal{B}_m$. Polynomial interpolation at the positive nodes $a_1 T, \dots, a_m T$, evaluated at zero, consequently has error at most

$$\frac{\mathcal{B}_m T^m \prod_i a_i}{(m+1)!}.$$

Indeed the scalar interpolation remainder applies on the convex hull of zero and all interpolation nodes, component by component. No statistical independence or measured derivative is used in this formula.

For $(a_1, a_2, a_3, a_4) = (1, 2, 4, 8)$ the weights are

$$(64/21, -8/3, 2/3, -1/21),$$

and the continuous temporal allowance is $8B_4T^4/15$. Under the endpoint, magnetic and initial allowances of Proposition S5, the four-window version obeys

$$\|\widehat{\mathcal{R}_T^{(4)} Y} - f_*\|_\infty \le I_0 + \frac{8B_4T^4}{15} + \frac{15B_m h^2}{28} + \frac{45\epsilon_m}{7} + \frac{45\epsilon_p}{7T}.$$

Here B_4 bounds the fourth time derivative of the paired nonmagnetic force, while B_m retains its meaning as a magnetic second-derivative bound. The magnetic weight norm is $45/7$. The combined momentum coefficients at $0, T, 2T, 4T, 8T$ are

$$T^{-1}(-15/8, 64/21, -4/3, 1/6, -1/168),$$

whose absolute sum is also $45/(7T)$. Relative to the three-window formula, endpoint-noise amplification increases by the factor $90/77$. This modest additional cost does not by itself guarantee a better result: the fourth temporal derivative and all observation allowances must still be justified. No observed temporal fit supplies those bounds.

The predeclared four-window diagnostic did not improve the fixed three-window result on either new configuration at either time step. For example, at direction 3 on the fine record its maximum declared-family discrepancy is approximately 1.77537×10^{-7}, compared with 1.76758×10^{-7} for three windows in the same floating diagnostic. These are evaluations of saved finite labels, not continuous-error bounds. The interval reception in Proposition S6 uses its own exact native arithmetic. The negative comparison motivates a separate time-step diagnostic rather than further increasing the extrapolation order.

Proposition S6. Certified arithmetic for a fixed finite-window force label. *Use the same exact native full matrices M, K_0, V, tip vector b, and $d = V^T b$. For each signed observation record $\sigma \in \{+, -\}$, let $\tau_{\sigma,i}$ be its own saved clock and set*

$$p_{\sigma,i} = V^T M v_{\sigma,i}, \qquad m_{\sigma,i} = \kappa \sin(b^T x_{\sigma,i}) - \mu B_{y,\sigma,i} \cos(b^T x_{\sigma,i}).$$

The vectors $x_{\sigma,i}, v_{\sigma,i}$ are the observed full 64-coordinate vectors, assembled directly from the recorded w, θ, w_t, θ_t fields. At the fixed panel counts $n \in \{1,2,4\}$, define $T_{\sigma,n} = \tau_{\sigma,n} - \tau_{\sigma,0}$ and

$$A_{\sigma,n} = \frac{p_{\sigma,n} - p_{\sigma,0}}{T_{\sigma,n}} + \frac{d}{T_{\sigma,n}} \sum_{i=0}^{n-1} \frac{\tau_{\sigma,i+1} - \tau_{\sigma,i}}{2} (m_{\sigma,i} + m_{\sigma,i+1}).$$

All twelve saved clocks start exactly at zero and satisfy, as exact rational identities, $T_{\sigma,2} = 2T_{\sigma,1}$ and $T_{\sigma,4} = 4T_{\sigma,1}$. Their actual-clock Lagrange weights at zero are therefore $(8/3, -2, 1/3)$; their sum is one, their first two time moments vanish, and their absolute sum is five.

For each of the six prescribed signed pairs, let x_g^{prep} be that configuration's own prepared rounded full-coordinate position. With the fixed normalization $S = (10^{-3})/(6\,10^{-12}) = 500000000/3$, the stored-data label is

$$\ell_g = -\frac{S}{2} \sum_{\sigma \in \{+,-\}} \left(\frac{8}{3} A_{\sigma,1} - 2A_{\sigma,2} + \frac{1}{3} A_{\sigma,4} \right) - SV^T K_0 x_g^{\mathrm{prep}}.$$

Exact rational native matrix arithmetic and Arb arithmetic at 256 bits enclose all six labels, using every signed trace's actual saved times in both the slope and trapezoid. No clock, prepared position, or sign is substituted from another configuration.

Only after the completed label process and its output hash are recorded, the evaluator reads the declared stiffness coefficient. The saved readbacks give $a_E = E_{\mathrm{mod}}/(5\,10^6) = 53/50$ in these cases. Against the declared initial formula

$$f_g^{\mathrm{decl}} = (a_E - 1) SV^T K_0 x_g^{\mathrm{prep}},$$

the normalized maximum component errors obey the strict bounds

configuration	*coarse diagnostic*	*fine diagnostic*
original shifted	$9.469\,10^{-8}$	$2.239\,10^{-8}$
direction 2	$9.842\,10^{-8}$	$2.325\,10^{-8}$
direction 3	$7.478\,10^{-7}$	$1.768\,10^{-7}$

Each table entry is an exact rational upper bound on $\|\ell_g - f_g^{\mathrm{decl}}\|_\infty$. All six pairs use the same previously fixed panel counts; no pair or window is selected by error.

Proof. The receiver binds all twelve observation files, the prepared full-coordinate positions, and the native geometry by source hashes. It verifies the saved time and node identities and the native full field/DOF mapping. Binary64 observations and prepared positions are interpreted as exact saved numbers; the native mass is the exact sum $M_0 + M_r$. For every signed clock, the rational Lagrange calculation uses the three actual durations and verifies the constant, linear, and quadratic moment identities before computing the interval label. The label subprocess completes with exit code zero and writes an immutable hashed result before the evaluator subprocess is allowed to parse E_{mod}. The second process evaluates the declared formula and certifies the six displayed rational relaxations.

This result certifies arithmetic on stored finite observations and a subsequent comparison with a declared initial constitutive formula. The vanishing time moments are algebraic identities; no bound on a continuous-time extrapolation remainder, quadrature defect, native solver error, observation error, or unknown physical force follows from them. The records remain development and paired discretization diagnostics. No existing label, dataset purpose, or data split is changed; no training archive is exported, and no new training or native solve is performed.

The initial allowance and its recorded-state part. Use all 64 free transverse displacement/rotation coordinates in their fixed native ordering, and write $E_{\mathrm{el},0}(x) = x^T K_0 x/2$, $\lambda_F = \ell/E_s$ and $d = V^T b$. For the physical signed trajectories define

the scaled full-state quantities

$$\begin{aligned} P_\sigma(t) &= \lambda_F V^T M v_\sigma(t), \\ m_\sigma(t) &= \lambda_F d\{\kappa \sin(b^T x_\sigma(t)) - \mu B_{y,\sigma}(t) \cos(b^T x_\sigma(t))\}, \\ g(x) &= \lambda_F V^T \nabla(E_{\mathrm{el},0} + \mathcal{W}_*)(x), \qquad R(x) = \lambda_F V^T D_*(x), \\ s_\sigma(t) &= g(x_\sigma(t)) + R(x_\sigma(t)) v_\sigma(t). \end{aligned}$$

The full equation gives $\dot{P}_\sigma = -s_\sigma - m_\sigma$. Thus the momentum and magnetic terms use precisely the normalization of Proposition S5. At the prepared rounded position x_{prep}, put

$$f_0 = \lambda_F V^T K_0 x_{\mathrm{prep}}, \qquad f_* = g(x_{\mathrm{prep}}) - f_0.$$

Let $\widehat{x}_\sigma, \widehat{v}_\sigma$ denote the actual saved binary64 first-row full-coordinate values, rather than the intended initial conditions. Define

$$\widehat{\delta}_0 = \tfrac{1}{2} \sum_{\sigma=\pm} \{g(\widehat{x}_\sigma) + R(\widehat{x}_\sigma)\widehat{v}_\sigma\} - g(x_{\mathrm{prep}}), \qquad I_0^{\mathrm{rec}} = \|\widehat{\delta}_0\|_\infty.$$

This quantity alone does not bound the physical initial allowance. For example, suppose the physical initial states lie within $\delta_{x,\sigma}, \delta_{v,\sigma}$ of their saved values in the fixed coordinate norm. If g, R have Lipschitz bounds L_g, L_R on the relevant position neighborhoods and $\|R\|_\infty \le \overline{R}$ there, then a sufficient allowance is

$$I_0 = I_0^{\mathrm{rec}} + U_0, \qquad U_0 = \tfrac{1}{2} \sum_{\sigma=\pm} \{L_g \delta_{x,\sigma} + L_R \delta_{x,\sigma} \|\widehat{v}_\sigma\|_\infty + \overline{R} \delta_{v,\sigma}\}.$$

Indeed, insert and subtract the recorded-state forces and use $R(x)v - R(\widehat{x})\widehat{v} = R(x)(v - \widehat{v}) + (R(x) - R(\widehat{x}))\widehat{v}$. This proves $\|S(0) - f_0 - f_*\|_\infty \le I_0$ without imposing exact position or opposite-velocity symmetry.

Exact reception for the declared linear family. For the saved evaluator family,

$$\nabla(E_{\mathrm{el},0} + \mathcal{W}_*)(x) = a_E K_0 x, \qquad D_* = a_C D_0, \qquad D_0 = \alpha_0 M_0,$$

and both damping matrices are constant. The existing generators fix the mesh and linear geometry, use the mass-proportional coefficient `alpha_mass`, and set the stiffness-proportional coefficient to zero. The rotary patch changes inertia only. The frozen native matrix construction independently defines $D_0 = \alpha_0 M_0$ before runtime rounding. Here the readbacks are $a_E = 53/50$ and $a_C = 5754906970707699/5004266931050173$. Put $G = \lambda_F a_E V^T K_0$ and $C = \lambda_F a_C V^T D_0$. The recorded defect is the exact rational vector

$$\widehat{\delta}_0 = G\left(\frac{\widehat{x}_+ + \widehat{x}_-}{2} - x_{\mathrm{prep}}\right) + C\frac{\widehat{v}_+ + \widehat{v}_-}{2}.$$

If componentwise physical initial-error radii $\rho_{x,\sigma}, \rho_{v,\sigma} \in \mathbb{R}^{64}_{\ge 0}$ are supplied, a sharper directly computable sufficient term is

$$U_0 = \left\| \frac{|G|}{2}(\rho_{x,+} + \rho_{x,-}) + \frac{|C|}{2}(\rho_{v,+} + \rho_{v,-}) \right\|_\infty .$$

These radii have not been certified for the current physical observations.

Exact native rational arithmetic on all twelve saved numerical initial states gives the following strict rational upper bounds. Every sign and time-step record is received separately, with no projection or replacement by x_{prep}.

	I_0^{rec}		δ_{prep}
configuration	coarse	fine	
original shifted	$9.871\,10^{-15}$	$2.861\,10^{-15}$	$1.606\,10^{-18}$
direction 2	$2.782\,10^{-14}$	$1.390\,10^{-14}$	$1.907\,10^{-18}$
direction 3	$1.125\,10^{-13}$	$5.730\,10^{-14}$	$3.931\,10^{-18}$

The last column is a distinct preparation-transfer allowance. For each configuration, the frozen exact modal preparation $q = \ell z$ gives $x_{\mathrm{ideal}} = V\ell z$, whereas the stored label uses its own rounded x_{prep}. For the declared correction force,

$$\delta_{\mathrm{prep}} = \|\lambda_F V^T (a_E - 1) K_0 (x_{\mathrm{prep}} - V\ell z)\|_\infty .$$

Both time-step records share this preparation allowance. Adding it transfers the force-error budget from the rounded configuration to the ideal jet point; a point representation of an interval-certified label also requires its certified arithmetic radius. Arb comparison shows that each present fixed three-window discrepancy is strictly greater than its corresponding I_0^{rec} upper bound. Consequently the recorded initial pairing defect cannot by itself explain those discrepancies. This comparison does not bound U_0 or assign the remaining discrepancy to a particular source.

Endpoint momentum accuracy required by the force budget. For the FW2 majorant of Proposition S5 to fit a force tolerance η, its nonnegative allowances must satisfy

$$\epsilon_p \le \frac{2T}{11}\left(\eta - I_0^{\mathrm{rec}} - U_0 - \frac{B_3 T^3}{3} - \frac{5 B_m h^2}{12} - 5\epsilon_m\right),$$

with a nonnegative bracket. This is a requirement on that certified error budget, not an assertion that cancellations in the actual error are impossible. For every current record the exact first saved duration and coefficient are

$$T = \frac{5902958103587057}{75557863725914323419136}\ \mathrm{s},$$
$$\frac{2T}{11} = \frac{5902958103587057}{41556825049252877880524 8}\ \mathrm{s} \simeq 1.420454545\,10^{-8}\ \mathrm{s}.$$

After subtracting the recorded I_0^{rec} alone, a force tolerance 10^{-7} therefore leaves an optimistic scaled endpoint-momentum ceiling of approximately $1.42045\,10^{-15}$; the uninstantiated terms can only reduce it. No continuous solver or observation accuracy at that scale has been certified by this calculation.

Derivative formulas without an asserted derivative bound. For the declared full equation set $A = a_E K_0$, $D = a_C D_0$, $\theta = b^T x$, $q_\theta = b^T v$, $r_\theta = b^T a$, and $m = \kappa \sin\theta - \mu B_y \cos\theta$. Then

$$\begin{aligned}
a &= -M^{-1}(Ax + Dv + bm),\\
j &= -M^{-1}(Av + Da + b\dot{m}), \qquad k = -M^{-1}(Aa + Dj + b\ddot{m}),\\
\dot{m} &= (\kappa\cos\theta + \mu B_y \sin\theta) q_\theta - \mu \dot{B}_y \cos\theta,\\
\ddot{m} &= (\kappa\cos\theta + \mu B_y \sin\theta) r_\theta + (-\kappa\sin\theta + \mu B_y \cos\theta) q_\theta^2\\
&\quad + 2\mu \dot{B}_y \sin\theta\, q_\theta - \mu \ddot{B}_y \cos\theta,\\
s_\sigma''' &= \lambda_F V^T (A j_\sigma + D k_\sigma).
\end{aligned}$$

Here $a = x''$, $j = x'''$, and $k = x''''$. A bound on these formulas over certified trajectory neighborhoods would supply B_3 and, from $\lambda_F d\ddot{m}$, the magnetic second-derivative allowance. No such neighborhood bounds are supplied by the saved initial-state arithmetic or by the coarse–fine records.

S2.2 A fixed-window time-refinement diagnostic

To test the time-discretization sensitivity of the stored-data receiver in S6, two additional native COMSOL solves were declared before execution. They retain the third preparation $q = (0, 0, 1/2000)\,\mathrm{m}$ and the prescribed velocities $\dot{q} = \pm 100 q$. The source model, material parameters ($E = 5.3 \times 10^6\,\mathrm{Pa}$ and mass-damping coefficient $0.6389230223455499\,\mathrm{s}^{-1}$), drive, spatial mesh, initial-field expressions, generalized-α settings and tolerances were retained. Only the internal step was reduced from 3.90625×10^{-8} to $1.953125 \times 10^{-8}\,\mathrm{s}$. Both signs retain the same 257 requested output times over $20\,\mu\mathrm{s}$, with output spacing $7.8125 \times 10^{-8}\,\mathrm{s}$.

For every sign and internal step, the fixed receiver uses output indices $(1, 2, 4)$. Its own recorded increasing clock is interpreted exactly; the three actual durations satisfy the dyadic relations and yield the predeclared weights $(8/3, -2, 1/3)$.

No window, weight or model parameter was selected from these results. An independent 256-bit Arb receiver reconstructed the projected momentum and magnetic quadrature from the saved displacement, rotation, velocity and drive observations. Material coefficients enter only the subsequent evaluator comparison.

Let $\widehat{f}_h$ denote the paired conservative correction label, and let $f_* = (\ell/E_s)(a_E - 1)K_{03}q$ be the correction in the declared material family, with $a_E = 53/50$. This diagnostic uses the ideal full-coordinate reference $x_{\mathrm{prep}} = Vq$; the preceding fixed stored receiver uses the prescribed rounded full-coordinate position. All three time steps are re-received under the same ideal convention and therefore are not bitwise the earlier rounded-reference quantity. An exact rational calculation bounds the corresponding change in the normalized total reference force by 6.944×10^{-17}. The finite-data arithmetic enclosures give the following upper bounds, rounded upward:

internal step h (s)	$\|\widehat{f}_h - f_*\|_\infty$
7.8125×10^{-8}	7.477611×10^{-7}
3.90625×10^{-8}	1.767437×10^{-7}
1.953125×10^{-8}	3.398021×10^{-8}

The maximum component of the difference between consecutive labels decreases from approximately 5.710174×10^{-7} to 1.427635×10^{-7}, a ratio of approximately 4.000. The finest discrepancy is approximately 5.20 times smaller than that at the previous fine step. Thus the previous observed discrepancy is not a demonstrated numerical floor.

The prescribed initial fields are fixed, but their realized initial states are retained rather than assumed exact. At the three steps, the signed-pair position differences are approximately 1.5625×10^{-14}, 7.8125×10^{-15} and 3.9062×10^{-15} in the native coordinate convention; the velocity antisymmetry defects are approximately 8.1400×10^{-8}, 4.0700×10^{-8} and 2.0350×10^{-8}. These changes can contribute to the observed discrete sensitivity. Both new native solves and the arithmetic receiver terminated with actual exit code zero; a separate 512-bit direct endpoint calculation encloses its results inside the 256-bit reception intervals. This experiment supplies a three-step diagnostic for one declared material and one preparation. It does not instantiate the continuous bounds in S5, separate all error sources, identify unknown constitutive physics, or certify a KAM transfer. No training or checkpoint update was performed.

S2.3 A posteriori enclosures for the recorded-state native IVPs

The preceding time-step comparisons do not certify the error of a continuous trajectory. To supply such a bound for a specified mathematical model, consider

$$M\ddot{x} + D\dot{x} + Kx + b\,g(b^T x, t) = 0, \qquad g(\theta, t) = \kappa \sin\theta - \mu B(t)\cos\theta,$$

where $M = M_0 + M_r$, $K = (53/50)K_0$, $D = \alpha_* M_0$ and $b = e_{64}$. The mass and stiffness entries are interpreted as the exact rational values of the saved finite-element matrices. The drive is the exact decimal law $B(t) = 10^{-4}\cos(11.41692154656479\,t)$. The coefficient α_* is the saved binary value of the material readback. These conventions specify a mathematical IVP; they do not identify the solver's compiled transcendental evaluations with exact arithmetic.

For each sign, let Q be the piecewise cubic Hermite curve through the saved full-coordinate positions and velocities, with $\dot{Q}$ its derivative. The comparison solution starts at that sign's own saved numerical state. Define

$$\begin{aligned} R_Q &= M\ddot{Q} + D\dot{Q} + KQ + b\,g(b^T Q, t), \\ r^2 &= (x - Q)^T K (x - Q) + (\dot{x} - \dot{Q})^T M (\dot{x} - \dot{Q}), \\ c_M^2 &= b^T M^{-1} b, \qquad c_K^2 = b^T K^{-1} b. \end{aligned}$$

Lemma S7. Residual-to-state enclosure. *Suppose M, K are symmetric positive definite, D is symmetric positive semidefinite, and $|B(t)| \le A$. On a time cell, assume $\sqrt{R_Q^T M^{-1} R_Q} \le \bar{\rho}$. Put $L_g = \kappa + \mu A$ and $a = L_g c_M c_K/2$. If $r(t_i) \le r_i$, then throughout that cell*

$$r(t_i + \tau) \le e^{a\tau} r_i + \bar{\rho}\frac{e^{a\tau} - 1}{a}, \qquad 0 \le \tau \le h_i. \tag{CT1}$$

The initial value is $r_0 = 0$ for the recorded-state IVP specified above.

Proof. Write $e = x - Q$. The error equation gives, almost everywhere,

$$r\dot{r} = -\dot{e}^T D\dot{e} - (b^T\dot{e})\{g(b^T x, t) - g(b^T Q, t)\} - \dot{e}^T R_Q.$$

The global force bound $|g(\theta,t) - g(\eta,t)| \le L_g|\theta - \eta|$ and the two energy-dual inequalities yield

$$|b^T e| \le c_K\|e\|_K, \qquad |b^T\dot{e}| \le c_M\|\dot{e}\|_M,$$
$$\|e\|_K\|\dot{e}\|_M \le r^2/2, \qquad |\dot{e}^T R_Q| \le r\bar{\rho}.$$

Thus $\dot{r} \le ar + \bar{\rho}$. A regularized norm establishes the comparison also at $r = 0$. Since Q and $\dot{Q}$ are continuous across the saved nodes, integrating this inequality gives (CT1) without a jump contribution at cell boundaries.

Whole-cell residual reception. Use the degree-nine rational polynomial obtained by replacing the magnetic term in R_Q by

$$b\left\{\kappa(\theta - \theta^3/6) - \mu A(1 - \omega_B^2 t^2/2)(1 - \theta^2/2)\right\}, \qquad \theta = b^T Q.$$

Its Bernstein coefficient vectors β_k on each cell give the uniform mass-dual bound $\max_k \sqrt{\beta_k^T M^{-1}\beta_k}$, by convexity of that norm. If $|\theta| \le \Theta$ and $0 \le \omega_B t \le 1$, a valid additional mass-dual remainder is

$$c_M\left\{\frac{\kappa\Theta^5}{120} + \frac{\mu A}{24}\left(\Theta^4 + (\omega_B t_{i+1})^4\right)\right\}. \tag{CT2}$$

Indeed, the sine remainder is at most $\Theta^5/120$; the product of the two cosine approximations has error at most $(\Theta^4 + (\omega_B t)^4)/24$, since $|1 - \omega_B^2 t^2/2| \le 1$. All polynomial operations and matrix identities are rational. Interval square roots and exponentials supply the outward bounds in (CT1).

For the two half-fine direction-3 records, this reception verifies all eight cells of the fixed four-panel prefix. Exact positive elimination pivots establish definiteness of M, K, M_0. The final radii are bounded by 2.589070×10^{-13} and 2.688128×10^{-13} in the norm of Lemma S7. The growth constant satisfies $a < 479.200675\,\mathrm{s}^{-1}$. These bounds hold for the continuous mathematical IVPs, throughout each cell, rather than only at sampled residual values.

Limits of a generic endpoint estimate. At a saved node the scaled momentum error is at most

$$C_P r(t_i), \qquad C_P = (\ell/E_s)\max_j \sqrt{(V^T M V)_{jj}}.$$

Substitution into the fixed receiver gives a paired momentum allowance less than 0.035010, which exceeds the intended 10^{-7} force tolerance. This is a valid but insufficient upper bound, rather than a lower bound on the actual data error. A direct projected-force reception below retains the spatial and temporal cancellations discarded by this generic estimate.

The certificate concerns solutions starting at the saved numerical states. It supplies neither an error bound for physical measurements, nor a verification of the compiled COMSOL equation or its dense output. A physical initial-state discrepancy requires an additional nonzero initial allowance in (CT1). No learned potential jet or physical KAM transfer follows from the trajectory enclosure alone.

S2.4 Conditional force-derivative bounds from a trajectory tube

Consider the declared native full-coordinate system

$$M\ddot{x} + Kx + D\dot{x} + b\,g(b^T x, t) = 0, \qquad g(\theta,t) = \kappa\sin\theta - \mu B(t)\cos\theta,$$

where $x \in \mathbb{R}^{64}$, $b = e_{64}$, $M = M_0 + M_r$, $K = (53/50)K_0$ and $D = \alpha_* M_0$. The saved material readback gives the exact binary coefficient $\alpha_* = 5754906970707699/9007199254740992$. In particular its ratio to the saved nominal damping coefficient is $5754906970707699/5004266931050173$, rather than an assumed exact $23/20$. The specified drive is

$$B(t) = 10^{-4}\cos(11.41692154656479\,t).$$

Here the displayed decimal drive defines an exact continuous law; the helper also accepts explicit rational overrides if a different literal convention is adopted. This convention does not assert exact evaluation of that law by the numerical solver.

Put $v = \dot{x}$, $a = \ddot{x}$, $j = x^{(3)}$ and $k = x^{(4)}$. Differentiating the smooth declared equation gives

$$\begin{aligned} a &= -M^{-1}(Kx + Dv + bg), \\ j &= -M^{-1}(Kv + Da + b\dot{g}), \\ k &= -M^{-1}(Ka + Dj + b\ddot{g}). \end{aligned}$$

Let $\omega = b^T v$ and $\alpha = b^T a$. Then

$$\begin{aligned} \dot{g} &= (\kappa\cos\theta + \mu B\sin\theta)\omega - \mu B'\cos\theta, \\ \ddot{g} &= (\kappa\cos\theta + \mu B\sin\theta)\alpha + (-\kappa\sin\theta + \mu B\cos\theta)\omega^2 \\ &\quad + 2\mu B'\sin\theta\,\omega - \mu B''\cos\theta. \end{aligned}$$

Consequently the normalized projected restoring-and-dissipative force $s = (\ell/E_s)V^T(Kx + Dv)$ and the separately treated magnetic force $m = (\ell/E_s)V^T b\, g$ satisfy

$$s^{(3)} = (\ell/E_s)V^T(Kj + Dk), \qquad m'' = (\ell/E_s)V^T b\,\ddot{g}.$$

Subtracting a constant nominal force from s does not change its third derivative.

Projection before interval bounds. Bounding all coordinates of j and k separately can discard useful spatial cancellation. For an arbitrary fixed rational λ, define

$$z = \begin{pmatrix} x \\ v \end{pmatrix}, \quad A_\lambda = \begin{pmatrix} 0 & I \\ -M^{-1}(K + \lambda bb^T) & -M^{-1}D \end{pmatrix}, \quad u = \begin{pmatrix} 0 \\ -M^{-1}b \end{pmatrix}, \quad r = g - \lambda\theta.$$

Then $z' = A_\lambda z + ur$ and, for every constant row c,

$$cz^{(n)} = cA_\lambda^n z + \sum_{q=0}^{n-1} cA_\lambda^{n-1-q} u\, r^{(q)}, \qquad 1 \le n \le 3. \tag{DB1}$$

The helper first forms these rational rows exactly. Its default $\lambda = \kappa$ puts the linear magnetic stiffness in A_λ. With $r_\theta = \kappa\cos\theta + \mu B\sin\theta - \lambda$ and $r_{\theta\theta} = -\kappa\sin\theta + \mu B\cos\theta$,

$$r' = r_\theta\omega - \mu B'\cos\theta, \qquad r'' = r_\theta\alpha + r_{\theta\theta}\omega^2 + 2\mu B'\sin\theta\,\omega - \mu B''\cos\theta.$$

The magnetic derivative is recovered as $g'' = \lambda\alpha + r''$. The quantity α itself follows from (DB1) with $c = (0, b^T)$ and $n = 1$; hence this procedure is not circular. For the three rows $c_i = (\ell/E_s)(V^TK, V^TD)_i$, (DB1) with $n = 3$ directly encloses $s_i^{(3)}$. Optional coordinate rows provide a, j, k when needed. Near zero, the evaluation uses $\cos\theta - 1 = -2\sin^2(\theta/2)$ and the degree-seven polynomial for $\sin\theta - \theta$, with rigorous remainder $|\theta|^9/9!$, to retain the linear cancellation.

Required tube and its exact dual bound. On each time segment, the caller must independently certify

$$(x - \widetilde{x})^T K(x - \widetilde{x}) + (v - \widetilde{v})^T M(v - \widetilde{v}) \le R^2. \tag{DB2}$$

The radius R is a norm radius, not an energy. If an energy error $\frac{1}{2}(\delta x^T K\delta x + \delta v^T M\delta v) \le E$ is supplied, one may use $R = \sqrt{2E}$. Exact positive LDL pivots verify that M and K are positive definite. For a row $c = (c_x, c_v)$, define

$$\rho(c)^2 = c_x K^{-1} c_x^T + c_v M^{-1} c_v^T.$$

The Cauchy–Schwarz inequality in this energy metric gives

$$|c(z-\widetilde{z})| \le R\rho(c). \tag{DB3}$$

For a polynomial center $\widetilde{z}(u), 0 \le u \le 1$, the scalar polynomial $c\widetilde{z}(u)$ is formed before bounding its range. Its exact Bernstein coefficients enclose that range; (DB3) supplies the additional tube interval. Interval sine and cosine, the exact drive derivatives and (DB1) then produce componentwise bounds $B_{3,i}$ for $s_i^{(3)}$ and $B_{m,i}$ for m_i''. For the paired force $S = (s_+ + s_-)/2$, the bound is $(B_{3,i,+} + B_{3,i,-})/2$. Bounds over several segments are obtained by their maxima. A common magnetic bound for both signs is obtained by taking the maximum over signs, components and segments.

The method supplies the derivative inputs required by S5 conditional on (DB2). A cubic Hermite curve through the saved observations does not establish (DB2), and neither its interpolation residual nor a coarse–fine difference alone certifies the initial error or a continuous trajectory tube. No numerical tube radius is certified in this component.

S2.5 Reception of the continuous derivative bounds

The completed energy-tube calculation encloses the two declared native full-coordinate IVPs on the first four saved output panels. Each IVP starts from its own saved initial state. Its uniform cell radii use the metric $\delta x^T K \delta x + \delta v^T M \delta v$ with $K = (53/50)K_0$ and $M = M_0 + M_r$. The received all-prefix radius of each cell is applied to the entire cell; a terminal radius is not mistaken for an endpoint-only bound.

Applying the frozen procedure in S2.4 to these verified tubes gives the following componentwise bounds for the paired third derivative, rounded upward:

$$(B_{3,1}, B_{3,2}, B_{3,3}) \le (2.993942 \times 10^{10},\ 4.270068 \times 10^{10},\ 6.523766 \times 10^{12}).$$

For each component, the maximum is first taken over all four cells of each sign and the two signed bounds are then averaged. A common bound on the normalized projected magnetic second derivative, over all cells, signs and components, is

$$B_m \le 2.604809 \times 10^{7}.$$

The actual signed clocks are received separately and their dyadic relations are verified. For their fixed first-panel duration $T \simeq 7.8125 \times 10^{-8}\,\mathrm{s}$, the derivative contributions to S5 satisfy

$$\frac{B_3 T^3}{3} \le 1.036925 \times 10^{-9}, \qquad \frac{5 B_m h^2}{12} \le 6.624371 \times 10^{-8},$$

where h is the largest actual saved panel width. Their sum is at most 6.728064×10^{-8}.

The tube producer and derivative receiver both terminated with actual exit code zero. This receives B_3 and B_m for the stated mathematical IVPs; it does not certify physical measurement error or the compiled or interpolated COMSOL trajectory. Moreover, the generic energy-to-momentum observation allowance remains approximately 0.03501, so the generic endpoint estimate alone does not establish a force tolerance of 10^{-7}. The derivative calculation neither sets the initial pairing allowance to zero nor claims that the full instantaneous-force error bound has been closed.

S2.6 Receiving a fixed label through projected force averages

Proposition S8. Reception through a projected force average. *Use all* 64 *free transverse displacement/rotation coordinates in the fixed native ordering. Let* M, K *be constant symmetric positive definite matrices, let* D *be constant symmetric positive semidefinite, let* V_j *denote column* j *of* V*, and let* $\lambda_F = \ell/E_s > 0$*. For the declared evaluator family these matrices are*

$$M = M_0 + M_r, \qquad K = a_E K_0, \qquad D = a_C D_0 = \alpha_{\mathrm{mass}} M_0,$$

with the native sum and the declared coefficients interpreted exactly. For each sign $\sigma \in \{+,-\}$, let x_σ be the solution of the declared recorded-state initial-value problem

$$Mx_\sigma'' + Dx_\sigma' + Kx_\sigma + b\, m_\sigma(b^T x_\sigma, t) = 0, \qquad m_\sigma(\theta,t) = \kappa \sin\theta - \mu B_{y,\sigma}(t)\cos\theta.$$

Its initial position and velocity are, by definition, that sign's own saved first-row values. This defines a mathematical initial-value problem and does not identify the physical initial state with a saved measurement.

Let Q_σ be the piecewise cubic Hermite interpolant of that sign's saved positions and velocities, with Q_σ' interpolating the saved velocities. Use each sign's actual saved clock, and assume that the received exact clock identities are

$$t_{\sigma,0} = 0, \quad t_{\sigma,1} = T, \quad t_{\sigma,2} = 2T, \quad t_{\sigma,4} = 4T, \qquad T > 0.$$

The interior time $t_{\sigma,3}$ need only lie strictly between $2T$ and $4T$; it need not equal $3T$. Write $I_{\sigma,i} = [t_{\sigma,i}, t_{\sigma,i+1}]$ and $h_{\sigma,i} = t_{\sigma,i+1} - t_{\sigma,i}$ for $0 \le i \le 3$. Define

$$e_{x,\sigma} = x_\sigma - Q_\sigma, \qquad e_{v,\sigma} = x_\sigma' - Q_\sigma', \qquad r_\sigma^2 = e_{x,\sigma}^T K e_{x,\sigma} + e_{v,\sigma}^T M e_{v,\sigma}.$$

In particular, $e_{x,\sigma}(0) = e_{v,\sigma}(0) = 0$. Suppose certified nonnegative numbers $R_{\sigma,i}, J_{\sigma,i}$ satisfy

$$r_\sigma(t) \le R_{\sigma,i}, \qquad \int_0^t r_\sigma(s)\, ds \le J_{\sigma,i} \quad (t \in I_{\sigma,i}).$$

A sufficient choice from whole-cell energy bounds alone is $J_{\sigma,i} = \sum_{q=0}^{i} h_{\sigma,q} R_{\sigma,q}$.

Define the averaging kernel and the normalized nonmagnetic force by

$$\mathcal{W}_T(t) = \begin{cases} 7/4, & 0 \le t < T, \\ -11/12, & T \le t < 2T, \\ 1/12, & 2T \le t \le 4T, \end{cases} \qquad \mathfrak{s}(z,w) = \lambda_F V^T (Kz + Dw).$$

Thus $k = (7/4, -11/12, 1/12, 1/12)$ gives the value of $\mathcal{W}_T$ on the four saved cells, regardless of the location of $t_{\sigma,3}$. Set

$$\begin{aligned} C_{Q,\sigma} &= \frac{1}{T}\sum_{i=0}^{3} k_i \int_{I_{\sigma,i}} \mathfrak{s}(Q_\sigma, Q_\sigma')\, dt, \\ C_{\mathrm{true},\sigma} &= \frac{1}{T}\sum_{i=0}^{3} k_i \int_{I_{\sigma,i}} \mathfrak{s}(x_\sigma, x_\sigma')\, dt, \\ C_Q &= \tfrac{1}{2}(C_{Q,+} + C_{Q,-}), \qquad C_{\mathrm{true}} = \tfrac{1}{2}(C_{\mathrm{true},+} + C_{\mathrm{true},-}). \end{aligned}$$

The integrands defining C_Q are polynomials. For the received rational native matrices, normalization, clocks and saved values, C_Q is therefore an exact rational polynomial integral.

Let $\widehat{F}$ be the already fixed observation-only raw force receiver formed from projected momentum increments and magnetic trapezoids with averaging weights $(8/3, -2, 1/3)$. Its label process is completed and hashed before declared evaluator coefficients are read. Let x_{prep} be a fixed reference preparation, either its own rounded position or the exact ideal reference Vq. Use the same reference for both the nominal subtraction and the declared target, and put

$$f_0 = \lambda_F V^T K_0 x_{\mathrm{prep}}, \qquad \widehat{Y} = \widehat{F} - f_0, \qquad \Delta_Q = \widehat{Y} + f_0 - C_Q = \widehat{F} - C_Q.$$

Changing the reference requires only the exact known nominal adjustment to $\widehat{Y}$; it does not change the fixed raw label $\widehat{F}$. The same fixed raw receiver must be enclosed when receiving Δ_Q. In particular, if directed Arb arithmetic produces the interval $\mathbf{\Delta}_{Q,j}$, use $d_{Q,j} = \sup\{|z| : z \in \mathbf{\Delta}_{Q,j}\}$ as the upper bound on $|\Delta_{Q,j}|$. A point representation of an interval-certified label must retain its certified arithmetic radius in this enclosure.

For each projected component define

$$\begin{aligned} A_{D,j} &= (V_j^T D M^{-1} D V_j)^{1/2}, \\ A_{KM,j} &= (V_j^T K M^{-1} K V_j)^{1/2}, \\ L_j &= (V_j^T K V_j + V_j^T D M^{-1} D V_j)^{1/2}, \\ B_{\sigma,i,j} &= \min\{L_j R_{\sigma,i},\ A_{D,j} R_{\sigma,i} + A_{KM,j} J_{\sigma,i}\}, \\ \Gamma_j &= \frac{\lambda_F}{2T} \sum_{\sigma\in\{+,-\}} \sum_{i=0}^{3} |k_i| h_{\sigma,i} B_{\sigma,i,j}. \end{aligned}$$

Then $|(C_Q - C_{\mathrm{true}})_j| \le \Gamma_j$.

Suppose, in addition, that

$$S(t) = \tfrac{1}{2} \sum_{\sigma\in\{+,-\}} \mathfrak{s}(x_\sigma(t), x'_\sigma(t)) \quad \textit{satisfies} \quad S \in C^3([0,4T]), \qquad \sup_{[0,4T]} \|S'''\|_\infty \le B_3.$$

The fixed saved-data receiver obeys the componentwise bound

$$\left|\widehat{Y}_j - (S_j(0) - f_{0,j})\right| \le |\Delta_{Q,j}| + \Gamma_j + \frac{B_3 T^3}{3} \le d_{Q,j} + \Gamma_j + \frac{B_3 T^3}{3}.$$

For the declared conservative correction at the chosen reference, define

$$f_*^{\mathrm{prep}} = \lambda_F V^T (K - K_0) x_{\mathrm{prep}}, \qquad \delta_0^{\mathrm{rec}} = S(0) - \lambda_F V^T K x_{\mathrm{prep}}, \qquad I_0^{\mathrm{rec}} = \|\delta_0^{\mathrm{rec}}\|_\infty.$$

Since the recorded-state initial values are the saved numbers, δ_0^{rec} *is exactly computable for this declared linear family and its supplied exact reference. In particular,*

$$\begin{aligned} |\widehat{Y}_j - f_{*,j}^{\mathrm{prep}}| &\le d_{Q,j} + \Gamma_j + \frac{B_3 T^3}{3} + |\delta_{0,j}^{\mathrm{rec}}|, \\ \|\widehat{Y} - f_*^{\mathrm{prep}}\|_\infty &\le \max_j (d_{Q,j} + \Gamma_j) + \frac{B_3 T^3}{3} + I_0^{\mathrm{rec}}. \end{aligned}$$

Proof. The dual norm of the linear functional $(e_x, e_v) \mapsto V_j^T(K e_x + D e_v)$ in the product energy norm gives

$$|V_j^T(K e_x + D e_v)| \le \left(V_j^T K V_j + V_j^T D M^{-1} D V_j\right)^{1/2} \left(e_x^T K e_x + e_v^T M e_v\right)^{1/2} = L_j r.$$

Also $e_x' = e_v$ and $e_x(0) = 0$, so Cauchy–Schwarz in the mass norm yields

$$\begin{aligned} |V_j^T K e_x(t)| &= \left| \int_0^t V_j^T K e_v(s)\, ds \right| \le A_{KM,j} \int_0^t r(s)\, ds, \\ |V_j^T D e_v(t)| &\le A_{D,j} r(t). \end{aligned}$$

Both estimates apply to the same error. On a whole cell their minimum is therefore the stated $B_{\sigma,i,j}$. Integrating against the absolute value of the kernel, then taking the half-sum of the two signs, proves $|(C_Q - C_{\mathrm{true}})_j| \le \Gamma_j$.

For every continuous vector function s, direct collection of the three averaging intervals gives

$$\frac{8}{3}\frac{1}{T}\int_0^T s(t)\, dt - 2\frac{1}{2T}\int_0^{2T} s(t)\, dt + \frac{1}{3}\frac{1}{4T}\int_0^{4T} s(t)\, dt = \frac{1}{T}\int_0^{4T} \mathcal{W}_T(t) s(t)\, dt.$$

Consequently C_{true} is the three-window average of S. The Peano-kernel bound of Proposition S5 therefore gives $\|C_{\mathrm{true}} - S(0)\|_\infty \le B_3 T^3/3$. Now use the exact decomposition

$$\widehat{Y} - (S(0) - f_0) = \Delta_Q + (C_Q - C_{\mathrm{true}}) + (C_{\mathrm{true}} - S(0)).$$

The componentwise triangle inequality proves the reception bound. Finally, $S(0) - f_0 = f_*^{\mathrm{prep}} + \delta_0^{\mathrm{rec}}$ gives both prepared-target bounds. The stated interval reception includes the finite arithmetic radius in $d_{Q,j}$ and hence preserves these inequalities.

This organization receives the fixed momentum-and-trapezoid label directly against a continuous nonmagnetic force average. Its Δ_Q already includes the discrepancy of that complete saved-data receiver from the Hermite force average. Separate endpoint-momentum, sampled-magnetic-force and magnetic-quadrature allowances are therefore not added again to this bound. A valid B_3 certificate for the same declared trajectories is still required.

The recorded initial defect is distinct from an unknown physical initial-state allowance. For example, if the same declared force law applies and independently certified componentwise physical initial radii are $\rho_{x,\sigma}, \rho_{v,\sigma}$, a sufficient additional term is

$$U_0 = \left\| \frac{\lambda_F |V^T K|}{2}(\rho_{x,+} + \rho_{x,-}) + \frac{\lambda_F |V^T D|}{2}(\rho_{v,+} + \rho_{v,-}) \right\|_\infty , \qquad I_0 \le I_0^{\mathrm{rec}} + U_0.$$

Here absolute values of matrices are componentwise, and I_0 denotes the physical initial force defect. No such radii, and hence no value of U_0, are established by this proposition. In particular, $e_x(0) = e_v(0) = 0$ for a recorded-state mathematical initial-value problem does not establish $U_0 = 0$ for a physical observation. A claim about a physical trajectory additionally requires initial-state, input and equation/model-discrepancy bounds that apply to that same trajectory; the declared recorded-state tubes alone do not supply them.

The scope is postlabel certification for the declared recorded-state initial-value problems using evaluator coefficients. The statement does not identify a general unknown constitutive force, certify a native compiled equation or its dense output, or establish a complex-network advantage. It changes neither the fixed saved raw label nor any data purpose or training split.

S2.7 Received continuous force bound at the direction-3 configuration

The fixed half-fine direction-3 receiver is now received by Proposition S8. The raw force label was already fixed by the saved observations before this certification. An independent 512-bit recomputation overlaps each of its earlier interval enclosures. The declared material coefficients enter only the subsequent certificate. They are not supplied as labels during that observation-only construction.

The reference preparation in this reception is the ideal point $\bar{x} = V(0, 0, 1/2000)^T$. Accordingly the same nominal force is subtracted there, and the recorded initial allowance includes the whole difference of the two saved initial states from this reference. The two mathematical solutions start at their respective saved first rows; no physical measurement is declared exact.

The components of the force-error budget are listed below. All displayed values are rounded upwards. The quantity $d_{Q,j}$ bounds the complete fixed raw-label minus Hermite nonmagnetic-average discrepancy; it is not a separately fitted residual. The tube term Γ_j uses the minimum of the two rigorously valid projected estimates in the proposition. Totals are rounded upward from the exact component sums; separately rounded displayed entries need not sum to the displayed total.

j	$d_{Q,j}$	Γ_j	$B_{3,j}T^3/3$	$\lvert\delta_{0,j}^{\mathrm{rec}}\rvert$	Total
1	2.999876×10^{-9}	1.502520×10^{-9}	4.758743×10^{-12}	9.950403×10^{-15}	4.507164×10^{-9}
2	4.277506×10^{-9}	6.079664×10^{-10}	6.787091×10^{-12}	1.418104×10^{-14}	4.892274×10^{-9}
3	3.434153×10^{-8}	9.209175×10^{-10}	1.036925×10^{-9}	2.889657×10^{-14}	3.629940×10^{-8}

The largest resulting normalized force-error bound is 3.629940×10^{-8}. Thus this one fixed receiver satisfies the declared 10^{-7} force tolerance for the two recorded-state mathematical IVPs.

This conclusion is stronger than a comparison of saved values with an algebraic material formula: it includes a whole-cell continuous trajectory enclosure and a third-derivative temporal-bias allowance. It remains a postlabel certificate for the specified material family. It supplies no physical measurement/model-discrepancy bound. The eight additional jet-design positions are received separately in Section S2.8. This two-IVP result does not validate a newly trained checkpoint, identify an arbitrary unknown quartic potential, or transfer the candidate-only KAM result to the physical target. The generic endpoint-based 0.035010 upper bound is retained as a valid negative result; the direct projected reception proves a different, sharper inequality for the same fixed data.

S2.8 Actual observations at all eleven design configurations

The eight additional positions of the exact fourth-order design were implemented in native COMSOL. Each position uses $q = \ell z^{(i)}$ and the two prescribed velocities $\dot{q} = \pm 25q\,\mathrm{s}^{-1}$. The existing three positions retain their own earlier prescribed velocities and their finest available saved records. A fixed internal step of 1.953125×10^{-8} s is used for the sixteen new solves; each exports 257 full-field samples over 20 μs with the same source-decimal cosine drive and fixed shifted material. Exact preparation arithmetic bounds every new prescribed initial energy by 5.322879×10^{-12} J. This is a feasibility bound for the prescribed initial values, not a claim that their numerical realization has zero error. All sixteen native processes completed successfully, and the source MPH remained unchanged.

The observation-only label process receives each sign's own saved clock, positions, velocities and magnetic field. It uses the same fixed three windows and weights at every node, subtracting the nominal force at the exact ideal design point. The declared material coefficients do not enter the force labels. The generator material is public in its protocol, so this is not a hidden-target or blind test. Each label is then independently received against its own continuous recorded-state IVPs by Proposition S8. The resulting maximum normalized force allowances, rounded upwards, are

Node	Configuration	Force allowance
0	original	2.274829×10^{-8}
1	direction2	2.363062×10^{-8}
2	direction3	3.629940×10^{-8}
3	jet_node03	4.582830×10^{-8}
4	jet_node04	4.582371×10^{-8}
5	jet_node05	2.530279×10^{-8}
6	jet_node06	3.630746×10^{-8}
7	jet_node07	3.629510×10^{-8}
8	jet_node08	4.582309×10^{-8}
9	jet_node09	1.576921×10^{-8}
10	jet_node10	3.631862×10^{-8}

All eleven selected records meet the fixed 10^{-7} tolerance. The older direction-3 step-1 and step-2 bounds remain approximately 7.531×10^{-7} and 1.797×10^{-7} and do not meet that tolerance. They are retained rather than removed by a posteriori window selection. The three existing finest records were selected by the smallest saved internal step before calculating these bounds. The new eight groups have only their single predeclared step.

All eleven groups are development/training configurations. Neither the 257 time samples nor the two signs at a position are declared independent configuration samples. The smaller $25q$ velocity also reduces damping excitation relative to the earlier $100q$ directions; no improvement in damping identifiability is inferred solely from the added position count.

S3 From prepared forces to a low-order potential jet

Set $\ell = 10^{-3}\,\mathrm{m}$, $E_s = 6\,10^{-12}$ J, and $w(z) = W(\ell z)/E_s$. Here W is the conservative correction: the known nominal elastic and prescribed magnetic forces are removed with the same normalization. Thus observations approximate the positive gradient $\nabla_z w$, rather than the negative mechanical force. A prepared point means the restriction $x = V\ell z$ of the full native state; departures from this prescribed state belong to the label error.

Proposition S9. Three-point symmetric Hessian reception. *Suppose explicitly that $w(z) = z^T Hz/2$ with a constant symmetric matrix H. Let*

$$z^{(0)} = (a,b,c)^T = \left(\frac{1}{2}, \frac{1256189}{200000000}, \frac{26951}{12500000}\right)^T, \quad z^{(1)} = (0,\tfrac{1}{2},0)^T, \quad z^{(2)} = (0,0,\tfrac{1}{2})^T.$$

For $h = (H_{11}, H_{22}, H_{33}, H_{12}, H_{13}, H_{23})^T$, stack the three blocks

$$A(z) = \begin{pmatrix} z_1 & 0 & 0 & z_2 & z_3 & 0 \\ 0 & z_2 & 0 & z_1 & 0 & z_3 \\ 0 & 0 & z_3 & 0 & z_1 & z_2 \end{pmatrix}$$

into $A \in \mathbb{Q}^{9\times 6}$. This matrix has rank six. For $L = (A^TA)^{-1}A^T$, any finite labels $y = Ah + e$ with separately received component bounds $|e_m| \le \eta_m$ satisfy

$$|(Ly - h)_i| \le \sum_{m=1}^{9} |L_{im}|\eta_m.$$

The Hessian in physical q coordinates is $E_s\ell^{-2}H$.

Proof. The third and second axis points determine the off-diagonal entries, H_{22} and H_{33}; then $a \neq 0$ determines H_{11} from the first component at $z^{(0)}$. Thus A has full column rank and $LA = I_6$. Apply L to $y = Ah + e$ and use the triangle inequality. The certificate also verifies these identities exactly using all nine scalar observations.

The numerical application uses the existing fine-step signed labels at these three configurations. Each label is obtained from its actual finite observation window; it is not replaced by the force at the initial point. Its arithmetic radius is added to its individual received force error before applying L. The available numerical errors were evaluated against the declared quadratic material family. They are therefore not general measurement-error certificates for an arbitrary unknown physical law. Proposition S9 allows arbitrary symmetric H only conditional on independently valid errors for that H. Without the quadratic assumption, third- and higher-order contributions cannot be silently absorbed into the Hessian.

Proposition S10. An eleven-point receiver for the complete fourth jet. *Assume $w \in C^5$ on a neighborhood of $[-1/2, 1/2]^3$, with $\nabla w(0) = 0$. Fix the additive gauge $w(0) = 0$, and write*

$$w(z) = \sum_{2\le|\alpha|\le 4} c_\alpha z^\alpha + R_5(z).$$

Append the following eight positions to the preceding three:

$$\begin{array}{cccc} (\frac12,-\frac14,-\frac12), & (-\frac12,0,-\frac12), & (-\frac14,\frac12,-\frac14), & (0,-\frac14,\frac12),\\ (\frac12,\frac14,\frac12), & (-\frac12,\frac12,-\frac12), & (-\frac12,\frac14,\frac14), & (-\frac12,-\frac14,\frac12). \end{array}$$

For the 31 ordinary monomials of degrees two through four, define

$$G_{(i,j),\alpha} = \alpha_j (z^{(i)})^{\alpha - e_j}, \qquad J = (G^TG)^{-1}G^T.$$

The term is zero when $\alpha_j = 0$. Exact rational arithmetic gives $\operatorname{rank} G = 31$ and $JG = I_{31}$. Eleven configurations attain the necessary lower bound $3m \ge 31$.

If $y_{ij} = \partial_j w(z^{(i)}) + e_{ij}$, $|e_{ij}| \le \eta_{ij}$, and $|\partial_j R_5(z^{(i)})| \le \tau_{ij}$, then

$$|(Jy - c)_\alpha| \le \sum_{i,j} |J_{\alpha,(i,j)}|(\eta_{ij} + \tau_{ij}). \tag{S16}$$

For a common componentwise fifth-derivative bound $|D^\nu w| \le M_5$ for all $|\nu| = 5$ on the cube, one may use

$$\tau_{ij} = \frac{M_5}{24}\|z^{(i)}\|_1^4.$$

Proof. The exact 33×31 matrix and its 31×33 left inverse are stored in the certificate, which verifies $JG = I_{31}$ without a floating rank threshold. The gradient Taylor expansion gives $y = Gc + t + e$. Multiplication by J proves (S16). For each $\partial_j w$, apply the third-degree Taylor formula with fourth-order remainder along the segment from 0 to z. The multinomial identity gives $\sum_{|\nu|=4} |z|^\nu/\nu! = \|z\|_1^4/24$. This derives a gradient-tail bound directly; it does not differentiate an unquantified scalar remainder.

The maximal exact left-inverse row sums, rounded upward here, are 39.124439, 52.294639, and 125.879240 within degrees two, three, and four. They multiply a uniform scalar force-error cap at this fixed half-unit design. The old symmetric 33-configuration design has the smaller constants $25890/6589$, 4, and $104/9$ on the same cube, while also receiving three potentially nonzero linear coefficients. The new design minimizes configuration count under the explicit zero-gradient

assumption, at the cost of greater deterministic noise amplification. Using the three existing points plus all eight equal-radius corners would not suffice: that matrix has rank 30, with null polynomial $z_1^4 - z_1^2/2$.

At the preceding three-configuration stage, only the first three positions had observations. That stage did not supply the other eight labels or their error caps. The actual reception below now supplies them for the declared quadratic family; a general unknown target still requires its own fifth-derivative bound. The certificate gives each coefficient's separate contribution from the existing nine scalar error bounds, from future errors, and from M_5. A new label procedure, including finite-window extrapolation, may supply different bounds at each position without changing this exact left inverse.

For consistency with a subsequent jet-to-normal-form calculation, $D^\alpha w(0) = \alpha! c_\alpha$: in particular, $H_{ii} = 2c_{2e_i}$ and $H_{ij} = c_{e_i+e_j}$ for $i \neq j$. The physical derivative is multiplied by $E_s \ell^{-|\alpha|}$. For a fixed candidate, its known signed finite-design tail alias can be subtracted as in the existing force-to-jet receiver; this never removes an unknown target tail or an observation error. The resulting interval jet must still satisfy the spectral, canonical-normalization, Birkhoff nondegeneracy and quantitative analytic KAM conditions uniformly. Neither full design rank nor this three-position quadratic reception is itself a KAM conclusion or an identification of a full 64-coordinate unknown potential. The construction supplies the explicit local-jet interface required between prepared-force learning and those later gates.

As an initial-energy feasibility witness only, $q = \ell z$ and $\dot q = \pm 25 q\,\mathrm{s}^{-1}$ at the proposed positions give exact full-field preparations $x = Vq$, $v = V\dot q$. Under the already declared material interval, their initial energy is below $0.90(6\,10^{-12}\,\mathrm{J})$. At this earlier preparation stage, the velocity was only a feasibility witness: relative to $\pm 100q$, its initial linear damping-force signal is four times smaller and its kinetic energy is sixteen times smaller. A subsequent experimental choice must also meet a separate dissipation-excitation and observation error budget. No COMSOL solve or realized initial-state guarantee is included in this preparation calculation.

S3.1 Composition of observation, preparation, and jet allowances

The finite-window receiver approximates a force at the prepared rounded full state x_i^{prep}, whereas the polynomial design uses the exact point $\bar x_i = V\ell z^{(i)}$. This distinction must be retained. Let

$$F_c(x) = (\ell/E_s) V^T \nabla \mathcal{W}_*(x), \qquad w(z) = \mathcal{W}_*(V\ell z)/E_s.$$

Then $\nabla_z w(z^{(i)}) = F_c(\bar x_i)$. Suppose a separate preparation allowance satisfies

$$\|F_c(x_i^{\mathrm{prep}}) - F_c(\bar x_i)\|_\infty \le d_i.$$

For example, $d_i = L_{c,i}\|x_i^{\mathrm{prep}} - \bar x_i\|_\infty$ suffices if F_c has the corresponding Lipschitz constant on the joining segment. This allowance concerns the correction force: the nominal force is already subtracted at the actual prepared position in the finite label.

Corollary S11. A conditional physical-observation to jet interface. *For every design position, suppose the hypotheses and the common-clock form of Proposition S5 hold, with valid constants for that position. Let r_i enclose the arithmetic error of the reported label midpoint, and define*

$$b_i = I_{0,i} + \frac{B_{3,i}T_i^3}{3} + \frac{5B_{m,i}h_i^2}{12} + 5\epsilon_{m,i} + \frac{11\epsilon_{p,i}}{2T_i} + d_i + r_i.$$

Then each reported component $\hat y_{ij}$ approximates $\partial_j w(z^{(i)})$ with absolute error at most b_i. Under the fifth-derivative and equilibrium assumptions of Proposition S10, the same exact left inverse gives

$$|(J\hat y - c)_\alpha| \le \sum_{i,j} |J_{\alpha,(i,j)}| \left(b_i + \frac{M_5}{24}\|z^{(i)}\|_1^4 \right).$$

For independently computed candidate coefficients $c_{\theta,\alpha}$, a sufficient candidate-to-target allowance is this right-hand side plus $|c_{\theta,\alpha} - (J\hat y)_\alpha|$. If the two signs use different clocks, their individual clock-dependent constants must replace the common-clock terms before this composition.

Proof. Apply the finite-window inequality to the prepared-state target, then the preparation and arithmetic triangle inequalities. This gives the componentwise force allowance b_i at the exact design node. Substitute it into (S16); the final statement is another scalar triangle inequality. No statistical or optimizer property is required for these deterministic implications.

The stored-data interval radii certify r_i. Comparisons against a declared constitutive formula do not by themselves certify $\epsilon_{p,i}, \epsilon_{m,i}, B_{3,i}, B_{m,i}$ or M_5 for an unknown physical target. A recorded-state initial-defect calculation also does not supply a true-state measurement bound. All eleven design positions and their stated error and tail allowances are required for this receiver. Their actual reception for the declared quadratic family is supplied below; a general unknown physical target still requires its own tail and measurement bounds. Once admitted, these ordinary coefficient intervals still have to pass the separate spectral, Birkhoff, analytic-domain and KAM gates; they do not inherit the candidate-only KAM conclusion automatically. The KAM verifier receives the total potential jet after restoring the known nominal elastic and prescribed magnetic coefficients, with the physical factors $E_s \ell^{-|\alpha|}$ applied consistently.

For the declared linear material family, Proposition S8 provides an alternative to the separate endpoint and magnetic budgets. At a reference design node where that proposition has been instantiated, the force error may instead be received componentwise as

$$b_{ij} = d_{Q,ij} + \Gamma_{ij} + \frac{B_{3,ij} T_i^3}{3} + |\delta^{\mathrm{rec}}_{0,ij}|,$$

provided the nominal subtraction and target use the same reference node. Any additional reported-midpoint radius must also be retained. The componentwise b_{ij} replaces b_i in the left-inverse sum above; the fifth-derivative tail and the other design-node requirements remain. The preceding numerical example received only the direction-3 pair. The next subsection receives every required node separately. No physical measurement allowance is supplied by either reception.

S3.2 Instantiated eleven-node coefficient intervals and their limits

The actual label midpoints $\hat{y} \in \mathbb{R}^{33}$ and their componentwise continuous-force and arithmetic allowances η now instantiate the exact left inverse in Proposition S10. For the declared simulation family $\mathcal{W}_*(x) = \beta x^T K_0 x/2$, the reduced correction is quadratic, its origin gradient vanishes and $M_5 = 0$. These are explicit constitutive-family assumptions, not properties inferred from eleven point observations. In that family,

$$c_* = J\hat{y} + e_c, \qquad |(e_c)_\alpha| \le r_\alpha := \sum_{i,j} |J_{\alpha,(i,j)}| \eta_{ij}.$$

Every one of the 31 received intervals contains the corresponding independently evaluated declared coefficient. Their maximum radii within degrees two, three and four are bounded respectively by

$$4.282817 \times 10^{-7}, \qquad 8.141379 \times 10^{-7}, \qquad 1.808799 \times 10^{-6}.$$

The known magnetic quartic has maximum normalized ordinary coefficient approximately 5.363314×10^{-9}. After restoring those prescribed coefficients, all fifteen total quartic coefficient intervals contain zero. This is an information and sign-ambiguity diagnostic; it is not itself a calculation of the Birkhoff twist determinant. In particular, finite design rank and small force error do not establish the uniform twist and analytic conditions for an unknown physical target. For a general C^5 target, the independent fifth-derivative tail in the preceding receiver must also be restored.

S3.3 A finite received-jet loss for the unchanged complex model

Let $\mathcal{A} = \{\alpha \in \mathbb{N}_0^3 : 2 \le |\alpha| \le 4\}$, so $|\mathcal{A}| = 6 + 10 + 15 = 31$. All coefficients below are ordinary monomial coefficients; $D^\alpha w(0) = \alpha!\, c_\alpha$. Write $q = \ell z$, $\ell = 1/1000$, and $E_s = 3/500000000000$. The conservative correction of the retained complex model is

$$W_\theta(q) = c_E E_0(q) + E_{\mathrm{net}} \left[N_\theta(q/Q_*, E_0(q)/E_{\mathrm{net}}) - N_\theta(0) - \sum_{j=1}^{3} \gamma_{\theta,j} q_j / Q_{*,j} \right],$$

where $E_0(q) = \frac{1}{2} q^T K_{03} q$ and $\gamma_{\theta,j} = \partial_j N_\theta(0)$. Here N_θ is the real readout of the existing split-tanh complex network, and E_{net} and Q_* are the saved checkpoint scales. Define $c_{\theta,\alpha}$ by the degree-four Taylor polynomial of $w_\theta(z) = W_\theta(\ell z)/E_s$. The prescribed magnetic potential is kept in the full Hamiltonian, but is not added to these correction coefficients or to the correction labels.

Let $\widehat{c} = Jy$ and $r \geq 0$ be the already received exact centers and radii from the fixed eleven-node force design. Assume that its received deterministic statement is

$$|c_{*,\alpha} - \widehat{c}_\alpha| \leq r_\alpha, \qquad \alpha \in \mathcal{A}. \tag{JG1}$$

For the current receipt, the zero target fifth-derivative tail and $\nabla W_*(0) = 0$ follow from the explicit declared family $W_* = \beta E_0$. They are family priors, not conclusions learned from the eleven positions. A generic unknown target instead needs its own centering and fifth-derivative hypotheses in (JG1).

Fix $s_\alpha = \max\{r_\alpha, 10^{-8}\} > 0$ before any optimizer update, and define the actual mathematical objective

$$L_{\mathrm{jet}}(\theta) = \frac{1}{31} \sum_{\alpha \in \mathcal{A}} \left(\frac{c_{\theta,\alpha} - \widehat{c}_\alpha}{s_\alpha} \right)^2. \tag{JG2}$$

The training inputs in (JG2) are the received centers and radii. No known-zero cubic or quartic coefficient is substituted as a label.

Proposition S12. Received-jet fitting bound. *For every parameter vector of the same model, (JG1)–(JG2) imply*

$$|c_{\theta,\alpha} - c_{*,\alpha}| \leq |c_{\theta,\alpha} - \widehat{c}_\alpha| + r_\alpha \leq s_\alpha \sqrt{31 L_{\mathrm{jet}}(\theta)} + r_\alpha \quad (\alpha \in \mathcal{A}). \tag{JG3}$$

If a reported joint score is $L_{\mathrm{joint}} = \lambda_{\mathrm{jet}} L_{\mathrm{jet}} + L_{\mathrm{other}}$ with fixed $\lambda_{\mathrm{jet}} > 0$ and $L_{\mathrm{other}} \geq 0$, then L_{jet} in the last expression may be replaced by $L_{\mathrm{joint}}/\lambda_{\mathrm{jet}}$.

Proof. The first inequality is the triangle inequality and (JG1). Each nonnegative summand in $31 L_{\mathrm{jet}}$ is at most their sum, which gives the second inequality after taking square roots. Finally $L_{\mathrm{jet}} \leq L_{\mathrm{joint}}/\lambda_{\mathrm{jet}}$. No descent, convexity, optimizer convergence or independent sampling assumption is needed. A point-force loss by itself cannot replace L_{jet} in this argument.

The component residual in the first bound of (JG3) is normally tighter than the bound derived from a single aggregate loss. In a final source-bound check, let $[a_\alpha, b_\alpha]$ enclose the exact-real coefficient of the actual saved weights. A rigorous computable bound is

$$|c_{\theta,\alpha} - c_{*,\alpha}| \leq \Delta_\alpha + r_\alpha, \qquad \Delta_\alpha = \max\{|a_\alpha - \widehat{c}_\alpha|, |b_\alpha - \widehat{c}_\alpha|\}. \tag{JG4}$$

For fixed exact positive scales, the rational expression $\overline{L} = (1/31) \sum_\alpha (\Delta_\alpha / s_\alpha)^2$ is an upper bound for (JG2). Thus it also validates the aggregate version of (JG3). Directly receiving the candidate coefficients in (JG4) requires no candidate fifth-order remainder. Candidate remainder and analytic-domain bounds may still be needed for later claims about functions or Hamiltonian transport beyond the finite jet.

The Torch polynomial implementation is optimizer arithmetic. Its float64 value is not itself a certified upper bound for (JG2). If it uses rounded centers $\widetilde{c}_\alpha$ and fixed rounded positive scales $\widetilde{s}_\alpha$, the corresponding exact-real loss yields instead

$$|c_{\theta,\alpha} - c_{*,\alpha}| \leq \widetilde{s}_\alpha \sqrt{31 \widetilde{L}_{\mathrm{jet}}} + r_\alpha + |\widetilde{c}_\alpha - \widehat{c}_\alpha|.$$

This statement still presupposes the exact-real candidate coefficient; final Arb reception supplies that link despite optimizer rounding of operators, ℓ, E_s and network calculations. Recording the actual normalization and rounding centers prevents an unreported change of loss.

At present the received maximum fourth-order coefficient radius is 1.808799×10^{-6} as an upward decimal bound. Even zero loss therefore does not guarantee that every received quartic error bound is below 10^{-6}. The jet is a deterministic transformation of the same eleven force records, not an independent additional dataset. Reducing (JG2) retains the full complex energy and dissipation heads; it neither replaces the architecture by a scalar prior nor supplies a physical-target spectral, twist or KAM certificate.

S3.4 Precision-weighted calibration of the final complex readout

For fixed hidden layers, let $h_\psi(s) \in \mathbb{C}^{12}$ be the last hidden representation. Its real scalar energy readout is $N_{a,b,\psi}(s) = \mathrm{Re}[(a+ib)^T h_\psi(s) + b_0]$. The centering operation in W_θ is linear in this readout: it removes its constant and its three linear configuration terms, while retaining the response through the quadratic energy feature. Consequently, with the saved feature scales and fixed hidden layers,

$$W_\theta(q) = \sum_{k=0}^{24} \xi_k \Phi_{\psi,k}(q), \qquad \xi = (c_E, a_1, \ldots, a_{12}, b_1, \ldots, b_{12}).$$

The output bias cancels under centering and is held fixed as a gauge. The $\Phi_{\psi,k}$ include the nominal energy skip and the centered real and imaginary hidden readouts, with their actual signs.

Proposition S13. A finite linear fitting block. *For fixed ψ, the 33 normalized force components at the eleven design nodes and the 31 normalized correction coefficients form a linear map $A_\psi \xi \in \mathbb{R}^{64}$. If $\hat{y}$ denotes the force midpoints, $\tilde{c}$ the saved jet centers, and $\eta_i > 0$ and $\tilde{s}_\alpha > 0$ the fixed received scales, the numerical block objective is the weighted least-squares expression*

$$\left\| D^{-1} \left(A_\psi \xi - \begin{pmatrix} \hat{y} \\ \tilde{c} \end{pmatrix} \right) \right\|_2^2, \qquad D = \mathrm{diag}(\eta_1, \ldots, \eta_{33}, \tilde{s}_1, \ldots, \tilde{s}_{31}). \tag{PW1}$$

This is a block of the unchanged complex model. It changes neither its function graph nor the number of stored real parameters.

Proof. The centered potential is linear in ξ. Differentiation at a fixed configuration and extraction of a Taylor coefficient are linear operations, so stacking their values gives $A_\psi \xi$. Positive diagonal scaling gives (PW1). No independence of the 64 rows is asserted: the jet rows are deterministic transformations of the same 33 force observations.

The implemented step uses float64 automatic differentiation to form A_ψ and a single least-squares solve, without a ridge penalty. Its numerical rank and condition estimate are diagnostics, not an exact-rank or exact-optimality certificate. The method was selected after the disclosed earlier fitting results; it is not a blind test. The step fixes the already trained hidden layers and the complete dissipation head. It performs one readout-block solve and zero gradient updates; the preceding full-layer training remains part of its documented history.

The force scales in (PW1) are observation-error allowances. The preceding gradient stage instead normalized point-force residuals by the observed signal RMS while normalizing coefficients by their much smaller received errors. The scores of these two objectives are therefore not directly comparable. Each term of (PW1) is the square of a residual divided by its scale, namely $(r/s)^2$.

The proof of fit is independent of the numerical solver. At the ideal exact design node, let an outward enclosure $[f_i^-, f_i^+]$ contain the force component defined by the saved weights and exact native operators. Set $\delta_i^f = \max\{|f_i^- - \hat{y}_i|, |f_i^+ - \hat{y}_i|\}$. If $|f_{*,i} - \hat{y}_i| \le \eta_i$, then

$$|f_{\theta,i} - f_{*,i}| \le \delta_i^f + \eta_i.$$

The corresponding coefficient statement is (JG4), with the appropriate saved-center rounding allowance. In particular, lying inside a data interval does not mean equality with its unknown target. Neither finite-node fit nor a small coefficient loss alone implies an analytic norm bound, a physical-target twist condition, or a complex-network advantage.

S4 A local KAM criterion for the actual conservative network

Consider the conservative restriction of the full-observation model,

$$H_N(q,p) = \tfrac{1}{2} p^\mathsf{T} A^{-1} p + U_N(q), \qquad A = A^\mathsf{T} > 0. \tag{S17}$$

Here $q, p \in \mathbb{R}^3$, and U_N includes the elastic, prescribed magnetic, and learned potential terms. The centering implemented in the network gives $\nabla U_N(0) = 0$. Dissipation and the time-dependent transverse magnetic input are set to zero in (S17).

The statement below concerns this restriction as its own Hamiltonian system. It does not assume that the restriction is an invariant subsystem of the full finite-element dynamics.

Proposition S14. Local criterion based on the selected weights. *Suppose the real-coordinate continuation of U_N is holomorphic near $q = 0$, and suppose the following conditions hold for the same weights:*

1. *$K_N = D^2U_N(0)$ is positive definite;*
2. *the positive generalized frequencies of (K_N, A) obey $k \cdot \omega_N \neq 0$ for all integer k with $0 < |k|_1 \leq 4$;*
3. *the degree-four Birkhoff normal form is*

$$h_N(I) = \omega_N \cdot I + \tfrac{1}{2} I^{\mathsf{T}} T_N I, \qquad \det T_N \neq 0. \tag{S18}$$

Then every neighborhood of $(q, p) = (0, 0)$ contains a positive-measure family of invariant Lagrangian three-dimensional tori of H_N with Diophantine frequencies. Neither a specified nonzero torus radius nor a specified frequency is asserted.

Proof. Positivity gives a real linear canonical change of coordinates to $H_2 = \sum_{j=1}^{3} \omega_{N,j}(X_j^2 + Y_j^2)/2$. Let $a_j = (X_j + iY_j)/\sqrt{2}$, so that $\{a_j, \bar{a}_k\} = -i\delta_{jk}$ and $I_j = a_j\bar{a}_j$. For a homogeneous monomial $a^\alpha \bar{a}^\beta$,

$$\{H_2, a^\alpha \bar{a}^\beta\} = i\,\omega_N \cdot (\alpha - \beta) a^\alpha \bar{a}^\beta.$$

The second condition solves every cubic homological equation and all quartic equations except the action monomials $\alpha = \beta$. For $H_3 = \sum h_{\alpha\beta} a^\alpha \bar{a}^\beta$, choose

$$\chi_3 = \sum_{|\alpha|+|\beta|=3} \frac{i h_{\alpha\beta}}{\omega_N \cdot (\alpha - \beta)} a^\alpha \bar{a}^\beta.$$

Thus $\{H_2, \chi_3\} = -H_3$. Under the corresponding time-one canonical pullback the effective quartic term is

$$H_{4,\mathrm{eff}} = H_4 + \tfrac{1}{2}\{H_3, \chi_3\}.$$

Its action projection gives (S18); a quartic generating function removes its other monomials. These finite polynomial flows are analytic and locally invertible for sufficiently small (X, Y). Consequently

$$H_N \circ \Psi = h_N(I) + R_5(X, Y), \qquad R_5 = O(\|(X, Y)\|^5). \tag{S19}$$

All normal-form transformations and the remainder in this equation refer to H_N, including its learned cubic terms.

Fix action and time units before the following estimates. More explicitly, for fixed $S_0, \omega_0 > 0$, replace (X, Y) by $(X, Y)/\sqrt{S_0}$, H by $H/(S_0\omega_0)$, and time t by $\omega_0 t$. The resulting equations are canonical, and the strict conditions above are invariant under this fixed rescaling. Use the same symbols for these dimensionless variables. Fix a balanced action box, for example $1 < J_j < 2$, and put $I = \rho^2 J$. This substitution is used to describe shrinking domains; Hamilton's equations and the following KAM application still use the physical canonical actions I. On a slightly larger complex action box and a fixed angle strip $|\operatorname{Im}\theta| < s$, a branch of $\sqrt{I_j}$ is analytic, and

$$X_j = \sqrt{2I_j}\cos\theta_j, \qquad Y_j = -\sqrt{2I_j}\sin\theta_j$$

has $\{\theta_j, I_k\} = \delta_{jk}$ and size $O(\rho)$. Analyticity of (S19) therefore supplies constants $C, M, c_h > 0$, independent of sufficiently small ρ, such that the perturbation has bound $F_\rho = C\rho^5$, the action Hessian of h_N has norm at most M, and the frequency parameterization is analytic on a complex neighborhood of width $h_\rho = c_h\rho^2$. The last assertion follows directly from the affine inverse $I = T_N^{-1}(\omega - \omega_N)$ and $\det T_N \neq 0$. Choose c_h sufficiently small, using $\|T_N^{-1}\|$ and the distance of the balanced box from $I_j = 0$, so that all complex centers $I_0(\omega)$ together with their action offsets $|\delta I| < r_\rho$ remain in the larger complex action box. This ensures that the square-root branches, fixed angle strip, and bound $C\rho^5$ are valid uniformly for every frequency parameter in that neighborhood.

Apply Theorems A and B of Pöschel (2001), using $\tau > 2$, $\nu = \tau + 1$, fixed $s \le 1$, and

$$\alpha_\rho = a\rho^{2+\beta}, \qquad 0 < \beta < \tfrac{1}{2}, \qquad r_\rho = \sqrt{C/M}\,\rho^{5/2}, \qquad a > 0. \tag{S20}$$

In the frequency-parameter formulation the local perturbation includes both the Taylor quadratic part of h_N and R_5, with bound $Mr_\rho^2 + F_\rho = 2C\rho^5$. The theorem's sufficient smallness inequality is met if

$$C\rho^{1-2\beta} \le \frac{\gamma^2 a^2 s^{2\nu}}{4M}, \tag{S21}$$

where $\gamma > 0$ depends only on dimension and τ. Indeed (S21) is exactly $F_\rho \le \gamma^2 \alpha_\rho^2 s^{2\nu}/(4M)$. The remaining requirements $\alpha_\rho s^\nu \le h_\rho$, $r_\rho = o(\rho^2)$, and $r_\rho, s, h_\rho \le 1$ also hold after decreasing ρ. Here $1 - 2\beta > 0$ is essential.

For completeness the Diophantine parameter set is nonempty with positive measure on these shrinking domains. The frequency image is an affine image of a box of side ρ^2. A resonance slab for k has thickness at most $C_k \alpha_\rho/|k|^{\tau+1}$ in frequency space, with a uniform geometric factor depending on T_N. Summing the cross-sectional estimates over integer $k \neq 0$ converges when $\tau > 2$. Including the boundary layer, the excluded fraction is at most a constant times $\alpha_\rho/\rho^2 = a\rho^\beta$, which tends to zero. The Lipschitz estimates in Theorem B preserve positive measure for the torus family. Transforming back by the canonical analytic changes proves the claim in every neighborhood of the equilibrium.

Consequences and limits for learning. This criterion permits changes in the learned quadratic, cubic, and quartic terms. It requires their recomputation from the actual selected network, including the cubic contribution to the quartic normal form. The finite nonresonance checks concern the linear frequencies only through order four; the Diophantine frequencies of the resulting tori are selected from the nearby nonlinear frequency image. No all-integer Diophantine property of ω_N is inferred from a finite search.

The three strict conditions are open conditions on the degree-four jet. A rigorous force-to-jet receiver can therefore supply a sufficient learning criterion: an enclosure of the admissible degree-four jets must pass positivity, the finite frequency gaps, and the twist test uniformly. An independent analytic continuation hypothesis is still needed for the remainder. Such a receiver need not bound a large quadratic change by the much smaller reference magnetic quartic; the quadratic change is included in the new spectrum.

An interval test on the actual network is a posterior criterion for that model. Its success alone does not prove that the physical target has the same low-order jet, that an optimizer will find such weights, or that a finite-data loss guarantees its conditions. A jet penalty based on the prescribed magnetic law is a stated physical prior when the observations cannot resolve those coefficients. It must not be reported as experimental identification of an unknown nonlinearity.

For a specified finite action range the constants in (S21), the normal-form domain, and the chosen Diophantine parameter set must be bounded on that range. The local constant C bounds the remainder after the cubic and quartic canonical transformations; a bound for the original potential's Taylor remainder cannot be substituted for it without controlling these transformations. The local existence conclusion does not by itself certify such a range, identify an individual trajectory as a torus, or transfer a torus to the full damped, driven finite-element model. These limitations also prevent interpreting this result as a control-safety theorem.

S4.1 Received coefficient-guided fit and calibrated checkpoint

Starting from the initial eleven-configuration fit, 200 complete outer cycles update the energy branch by one strong-Wolfe LBFGS iteration and the dissipation branch by one Adam step with the conservative contribution detached. There are 432 energy closure evaluations and 200 dissipation Adam updates. Every complex weight layer changes in both its real and imaginary coordinates. The selected cycle is 200. The coefficient loss drops from approximately 50743.76 to 4.399638, but the maximum point-force residual rises to 2.434500×10^{-4}. Independent coefficient evaluation bounds the largest declared-family quartic discrepancy by 3.342145×10^{-6}. This stage improves the initial high-order error but does not satisfy all received intervals.

The precision-weighted step (PW1) is then applied to those saved hidden layers. It performs one 25-coordinate linear solve with no ridge penalty. Only c_E and the final complex energy weight change; all other saved coordinates remain bitwise

identical to the warm start. The full two-branch graph retains its 918 real parameters. The selected skip is approximately 0.06002256805 and the Euclidean norm of its 24 real neural readout coordinates is approximately 0.0017053353, compared with 0.29265564 before calibration. This change is a final-readout calibration of a previously trained network, not a new full-layer gradient run.

Arb evaluation at 512 bits receives this exact saved graph with exact native operators at the ideal rational nodes. All 33 force residual intervals lie inside their individual received allowances, and all 31 coefficient intervals lie inside the original data intervals. The learner's once-rounded coordinates are separately recorded and are not used as substitutes for the ideal-node check. The maximum finite-node residual has upward bound 1.797797×10^{-8}; the maximum residual-to-allowance ratio is below 0.790301. The corresponding maximum candidate-to-target force bound, using the triangle inequality and the admitted observation error, is 5.023184×10^{-8}. These statements concern the eleven configurations and the explicitly admitted target family.

The strict exact-real upper bound for the actual saved-center coefficient loss is

$$\overline{L}_{\mathrm{jet}} < 1.082009 \times 10^{-2}.$$

Its computation uses rational endpoint bounds on an independent outward expansion, not the float64 training loss. The original data centers and the exported training centers are kept distinct, with the latter's exact rounding allowance included. The maximum normalized coefficient-error bounds are

Degree	Data-based triangle bound	Declared-family comparison
2	4.616863×10^{-7}	3.635946×10^{-8}
3	8.174276×10^{-7}	1.768735×10^{-8}
4	2.066906×10^{-6}	3.908709×10^{-8}

The middle column follows from the data intervals and (JG4). The final column additionally evaluates the explicitly declared quadratic simulation target and is an evaluator comparison, not a training label or a guarantee for an unknown constitutive law. The quartic discrepancy has thus decreased from more than 6.345877×10^{-4} for the initial point-force fit to less than 3.908709×10^{-8} after the disclosed coefficient-guided and final-readout stages.

The calibrated candidate is pole-free on $|z_j| \le 1/64$ and has frequencies approximately

$$(11.73745102,\ 72.26615415,\ 326.09695871)\ \mathrm{rad\,s^{-1}}.$$

Its cubic-corrected quartic Birkhoff twist has two positive and one negative eigenvalues and determinant near -5.271108×10^{19}, strictly excluding zero. Its positive Hessian and finite-order nonresonance satisfy the qualitative local criterion of Proposition S14 for the same saved conservative restriction. No specified finite torus radius or physical-target KAM transfer follows from this candidate-specific calculation.

Finite data also admit a scalar correction. For the comparison subfamily $W(q) = \zeta E_0(q)$, force and coefficient constraints are linear inequalities in an unknown ζ. Exact rational intersection of all 33 force and 31 coefficient intervals is nonempty. Its endpoints are approximately 0.0599999981693 and 0.0600000004402. An exact rational midpoint witness satisfies all 64 inequalities. No material value is assigned to ζ in this calculation. The zero cubic and quartic terms here define this comparison subfamily; they are not extra labels supplied to the complex network. Consequently the received finite data cannot require a nonlinear correction or establish a complex-network advantage. This limitation persists after the substantial improvement in the calibrated network's coefficient fit. All stages use the same development data, without an independent validation or probability claim.

S5 A local KAM criterion for the admitted quadratic target family

Let $I = [\beta_-, \beta_+] \subset (-1, \infty)$ be a compact interval, $A, K_0 \in \mathbb{R}^{3\times 3}$ symmetric positive definite, $d \in \mathbb{R}^3$, and $\kappa > 0$. Consider the conservative family

$$H_\beta(q,p) = \tfrac{1}{2} p^T A^{-1} p + \tfrac{1+\beta}{2} q^T K_0 q + \kappa(1 - \cos(d^T q)). \tag{S22}$$

Here the physical-family hypothesis $W_* = \beta E_0$ is stipulated. Compatibility of observations with I does not establish this constitutive hypothesis for an unknown device.

Lemma S15. Uniform finite-order conditions for the quadratic family. *Write $K_\beta = (1+\beta)K_0 + \kappa dd^T$. Suppose that throughout I the generalized eigenvalues of (K_β, A) are simple, positive and ordered as $\lambda_1 < \lambda_2 < \lambda_3$, with $\omega_j = \sqrt{\lambda_j}$. Suppose further that*

$$\inf_{\beta\in I} |k\cdot\omega(\beta)| > 0 \quad (0 < |k|_1 \le 4), \qquad \inf_{\beta\in I} (d^T u_j(\beta))^2 > 0 \quad (j = 1,2,3),$$

where the eigenvectors are A-orthonormal. Then the quartic Birkhoff twist, in physical canonical actions, has inertia $(2,1,0)$ uniformly on I. In particular its determinant is bounded away from zero. Every member of (S22) satisfies the qualitative local elliptic KAM criterion: sufficiently small neighborhoods of the origin contain a positive-measure family of invariant Lagrangian three-tori. This assertion assigns no numerical torus radius or all-integer Diophantine property to the equilibrium frequency vector.

Proof. The Hessian K_β is positive definite because $1+\beta > 0$. Choose the signs of the eigenvectors so that $d^T u_j > 0$, and let $S = (u_1, u_2, u_3)$. The canonical transformation

$$q = S\,\mathrm{diag}(\omega_j^{-1/2})X, \qquad p = AS\,\mathrm{diag}(\omega_j^{1/2})Y$$

gives $H_2 = \sum_j \omega_j (X_j^2 + Y_j^2)/2$. There is no cubic term. Put $a_j = (d^T u_j)^2/\omega_j > 0$ and $I_j = (X_j^2 + Y_j^2)/2$. The angle averages are $\langle X_j^4\rangle = 3I_j^2/2$ and $\langle X_i^2 X_j^2\rangle = I_i I_j$ for $i \ne j$. The order-four nonresonance hypothesis makes the resonant projection of $-\kappa(d^T q)^4/24$ equal to

$$Z_4 = -\frac{\kappa}{16}\sum_j a_j^2 I_j^2 - \frac{\kappa}{4}\sum_{i<j} a_i a_j I_i I_j = \tfrac{1}{2} I^T T I, \qquad T = -\frac{\kappa}{8} D(2\mathbf{1}\mathbf{1}^T - I_3)D, \quad D = \mathrm{diag}(a_1,a_2,a_3).$$

The middle matrix has eigenvalues $5, -1, -1$ and inverse $-I_3 + (2/5)\mathbf{1}\mathbf{1}^T$. Consequently

$$\det T = -\frac{5\kappa^3}{512}(a_1 a_2 a_3)^2 < 0, \qquad T^{-1} = -\frac{8}{\kappa} D^{-1}[-I_3 + (2/5)\mathbf{1}\mathbf{1}^T]D^{-1}. \tag{S23}$$

Congruence and the negative scalar give two positive and one negative twist eigenvalues. The potential is entire. Simplicity of the spectrum and nonzero overlaps give analytic canonical coordinates locally in β; the displayed sign convention patches them across I. The compact parameter interval and the strict uniform bounds control the finite normal-form transformations, twist inverse and analytic remainders uniformly. The usual small-action rescaling therefore places each member within the classical nondegenerate KAM theorem. The resulting Diophantine frequencies are selected from the nonlinear frequency image; they need not equal $\omega(\beta)$.

An enclosure of the entire parameter interval. Choose a rational $\beta_c \in I$, solely from the received interval. For $K_c = K_{\beta_c}$, set

$$m = \frac{1+\beta_-}{1+\beta_c}, \qquad M = \frac{1+\beta_+}{1+\beta_c}.$$

Since $K_0 \preceq K_c/(1+\beta_c)$, $mK_c \preceq K_\beta \preceq MK_c$ for every $\beta \in I$. The generalized min–max principle then gives $m\lambda_j(\beta_c) \le \lambda_j(\beta) \le M\lambda_j(\beta_c)$. Disjoint outward intervals obtained this way label the eigenvalues throughout I.

To avoid substituting center eigenvectors for an interval family, use

$$P_\beta(t) = \det(K_\beta - tA), \qquad N_\beta(t) = d^T\,\mathrm{adj}(K_\beta - tA)d, \qquad (d^T u_j)^2 = -\frac{N_\beta(\lambda_j)}{P'_\beta(\lambda_j)}.$$

This residue identity follows from the symmetric definite spectral decomposition of $(K_\beta - tA)^{-1}$. Exact spectral projectors of $A^{-1}K_\beta$ give the signed eigenvectors

$$u_j = \left[\prod_{k\neq j} \frac{A^{-1}K_\beta - \lambda_k I_3}{\lambda_j - \lambda_k}\right] A^{-1}d \,/\, \sqrt{(d^T u_j)^2}.$$

Outward evaluation with both β and all λ_j interval-valued encloses the complete family of canonical charts. Exact identities follow from the spectral theorem; residual intervals containing zero serve as implementation checks rather than proofs of those identities. The executable certificate separately verifies all order-at-most-four divisors, the positive overlap lower bounds and (S23).

The interval I in the numerical instance is the exact scalar compatibility intersection of the received 33 force and 31 coefficient constraints. No material value is assigned to β independently of that interval. This is a target-family certificate under a strong constitutive prior. It supplies no identification of unknown physics, necessity of a neural correction, complex-network advantage, invariant full-field trial subspace, or forced/damped KAM statement.

S5.1 A received numerical instance for the entire target family

The exact compatibility interval received from the 33 force and 31 coefficient inequalities is used unchanged. Its endpoints are approximately 0.0599999981693 and 0.0600000004402; these displays do not replace the exact rational endpoints in the calculation. The matrices are the same native $A = M_3$, $K_0 = K_{03}$, d and exact κ used in the current three-coordinate mechanical restriction. No network weights enter this family calculation.

Corollary S16. Qualitative local KAM for every admitted family member. *Under the explicit constitutive hypothesis $W_* = \beta E_0$, every β in the entire received compatibility interval satisfies Lemma S15. The uniform frequency enclosures in physical radians per second are*

Mode	*Strict enclosing interval*
1	$[11.73745098, 11.73745102]$
2	$[72.26615477, 72.26615488]$
3	$[326.09696048, 326.09696086]$

All three squared modal port overlaps are strictly positive throughout the interval. Every integer combination with $0 < |k|_1 \le 4$ satisfies $|k\cdot\omega| > 11.73745099\ \mathrm{rad\,s^{-1}}$. In the physical-action convention of (S23),

$$-6.217103\times10^{17} < \det T(\beta) < -6.217101\times10^{17}, \qquad \sigma_{\min}(T(\beta)) > 98709.9.$$

The twist inertia is $(2,1,0)$. The target family therefore has the qualitative local invariant-three-torus conclusion of Lemma S15. No numerical action or torus radius is asserted.

Proof. The frozen 512-bit Arb calculation receives the exact beta endpoints from the successful scalar feasibility certificate. Exact rational Sylvester tests verify the mass and the lower-endpoint Hessian. Exact Sturm isolation at the interval-selected dyadic center, followed by the Loewner/min–max enclosure, gives disjoint spectral intervals for every beta. The characteristic-resolvent residues and polynomial spectral projectors are evaluated with both beta and the eigenvalues interval-valued. They receive positive port overlaps and enclose the changing eigenbasis. All 64 plus/minus representatives through order four exclude zero. The analytic twist determinant and inverse formulas then give the stated strict bounds; a separate generic quartic $a, \bar{a}$ expansion checks their factors. The real spectral theorem and the angle-average calculation supply the exact identities. The local elliptic reduction and the classical KAM theorem (Pöschel 2001) give the qualitative conclusion.

The result concerns the admitted conservative family directly. It does not establish perturbative transfer from the learned candidate, unknown physical identification, an invariant full-field trial subspace, or necessity of a neural correction.

S6 Physical power, learning errors, and bounded magnetic safety

All derivatives in this section use physical time. The full observation space has $n = 64$ coordinates; its three-coordinate restriction is a different dynamical system. Let

$$M = M_0 + M_r \succ 0, \qquad K_0 \succ 0, \qquad D_0 = \alpha M_0 \succeq 0, \qquad \alpha > 0,$$

with constant symmetric matrices. In particular, D_0 is not αM. For a full-column-rank $V \in \mathbb{R}^{64\times 3}$, put

$$A = V^T M V, \qquad B = A^{-1} V^T M, \qquad q = Bx, \qquad E_0(x) = \tfrac{1}{2} x^T K_0 x, \qquad \theta = b^T x.$$

Thus $BV = I_3$. Fix $\mu > 0$ and a constant bias coefficient $\kappa > 0$. The transverse magnetic field $u = B_y$ is measured in tesla. Define

$$\begin{aligned} U_N(x) &= E_0(x) + \kappa(1 - \cos\theta) + F_N(Bx, E_0(x)), \\ D_N(x) &= a_N(Bx, E_0(x)) D_0, \\ H_N(x, v) &= \tfrac{1}{2} v^T M v + U_N(x), \\ g(x) &= \mu \cos\theta\, b, \qquad y(x, v) = g(x)^T v. \end{aligned} \tag{S24}$$

Here F_N is real-valued on real inputs. The complex network is decoded in real coordinates before differentiation.

The actual network parameterization. With positive saved feature scales Q_j and E_*, distinct from the exact decimal normalization E_s, write $s = (q_1/Q_1, q_2/Q_2, q_3/Q_3, E/E_*)$. Let $N(s)$ be the real energy readout and $(R(s), I(s))$ the two real readouts of the separate complex dissipation network. The candidate is

$$\begin{aligned} F_N(q, E) &= c_E E + E_* \left[N(s) - N(0) - \sum_{j=1}^{3} \gamma_j s_j \right], \qquad \gamma_j = \partial_j N(0), \\ a_N(q, E) &= [1 + c_C + R(s) - R(0)]^2 + [I(s) - I(0)]^2. \end{aligned} \tag{S25}$$

The fourth linear feature term is retained. Removing $\partial_4 N(0) E/E_*$ would define another potential.

Proposition S17. Full-field structure and real-domain bounds. *For differentiable F_N, the full candidate equation*

$$\dot{x} = v, \qquad M\dot{v} = -\nabla U_N(x) - D_N(x) v + g(x) u$$

has the identities

$$\nabla_x F_N(Bx, E_0(x)) = B^T F_q + F_E K_0 x, \tag{S26}$$

$$\dot{H}_N = -a_N v^T D_0 v + u y. \tag{S27}$$

In particular, $D_N \succeq 0$. Suppose the split-tanh network is written as two real hidden layers with matrices W_1, W_2 and final real output rows C_R, C_I. For a real feature box $|s_j| \le r_j$, define

$$\delta_R = |C_R|\,|W_2|\,|W_1| r, \qquad \delta_I = |C_I|\,|W_2|\,|W_1| r,$$

where the products use entrywise absolute values and the displayed outputs are scalars. Then throughout that real box

$$a_- \le a_N \le a_+, \qquad a_- = (\max\{0, |1 + c_C| - \delta_R\})^2, \quad a_+ = (|1 + c_C| + \delta_R)^2 + \delta_I^2. \tag{S28}$$

If, in addition, $D_0 \succeq \lambda_0 M$ for $\lambda_0 > 0$ and $a_- > 0$, then $D_N \succeq a_- \lambda_0 M$ on the box.

Proof. Since $dq = B\,dx$ and $dE_0 = x^T K_0\,dx$, the chain rule gives (S26). Multiplication of the candidate acceleration equation by v^T proves (S27). For the Rayleigh function $\mathcal{R}_N(x, v) = a_N(Bx, E_0(x)) v^T D_0 v/2$, the derivative with respect

to v, with x fixed, is $a_N D_0 v$. There is no spatial derivative of a_N in its dissipated power. Real tanh is globally 1-Lipschitz. Applying this fact to the two real-coordinate hidden layers bounds their output differences from the origin by the two stated matrix products. The reverse triangle inequality bounds the first squared factor from below; the ordinary triangle inequality bounds both factors from above. The Loewner bound follows on multiplication by $D_0 \succeq 0$.

The lower bound in (S28) must be recomputed for the selected trained weights and the relevant full-state feature range. A sum of two squares alone does not exclude a common zero. For a fixed field value u_c, the alternative storage $H_N - \mu u_c \sin\theta$ dissipates at rate $-v^T D_N v$. For a differentiable varying field, including $-\mu u \sin\theta$ in the storage gives supply $-\mu \dot{u} \sin\theta$. With the storage in (S24), the supply is uy and has no $\dot{u}$ term. These are two storage conventions for the same force.

A sufficient coercivity test. For finite split-tanh weights, the real readout satisfies $|N(s)| \le C_N$ on all real features, for an explicit finite constant C_N obtained from its final output row and bias. Set

$$\xi_c = E_* B^T \operatorname{diag}(Q_1^{-1}, Q_2^{-1}, Q_3^{-1})(\gamma_1, \gamma_2, \gamma_3)^T.$$

If $1 + c_E > 0$, then for every $0 < \eta < 1 + c_E$,

$$U_N(x) \ge (1 + c_E - \eta) E_0(x) - E_*(C_N + |N(0)|) - \frac{\xi_c^T K_0^{-1} \xi_c}{2\eta}. \tag{S29}$$

Indeed, the centered position term is $-\xi_c^T x$ and $|\xi_c^T x| \le \sqrt{2E_0 \xi_c^T K_0^{-1} \xi_c} \le \eta E_0 + \xi_c^T K_0^{-1} \xi_c/(2\eta)$. Thus H_N has compact sublevels under this sufficient test. The architecture by itself does not constrain $c_E > -1$.

The physical plant and its errors. On an open configuration region Ω, suppose the physical plant is

$$\dot{x} = v, \qquad M\dot{v} = -\nabla U_*(x) - D_*(x)v + g(x)u + w(x, v, t), \qquad D_*(x) = D_*(x)^T \succeq 0. \tag{S30}$$

It has the same declared mass and magnetic port as the candidate. The generalized force w covers additional physical work, rather than conservative or damping errors already retained in U_*, D_*. Define

$$H_* = \tfrac{1}{2} v^T M v + U_*(x), \quad \Delta U = U_N - U_*, \quad G = \nabla \Delta U, \quad d_* = v^T D_* v, \quad d_N = v^T D_N v.$$

Unlike a full-phase network with learned momentum dependence, this candidate uses exactly $\dot{x} = M^{-1} p$. At the same observed full state (x, v), its port output is therefore exactly y; no potential gradient error changes this equality. Replacing (x, v) by a reduced state or a stale observation requires a separate output-error bound. Along the physical plant the two storage derivatives are

$$\dot{H}_* = -d_* + uy + v^T w, \qquad \dot{H}_N = -d_* + uy + v^T (G + w). \tag{S31}$$

Theorem S18. Physical safety and potential-value transfer. *Let Ω be bounded with compact closure. Assume U_N, U_* are C^2 and D_* is locally Lipschitz on a neighborhood of that closure, and*

$$|U_N - U_*| \le \varepsilon_U \quad \text{on } \overline{\Omega}. \tag{S32}$$

Let $U > 0$, $k > 0$ and use the actual continuous feedback

$$u = -\operatorname{sat}_U(ky), \qquad \operatorname{sat}_U(r) = \max(-U, \min(U, r)), \qquad \Phi(y) = |y| \min(k|y|, U).$$

Suppose $w = 0$, $x(0) \in \Omega$, and for some energy cap c,

$$H_N(x(0), v(0)) + \varepsilon_U \le c, \qquad \inf_{x \in \partial\Omega} U_N(x) - \varepsilon_U > c. \tag{S33}$$

Then the physical solution exists for all $t \ge 0$, remains in Ω, and satisfies

$$H_*(t) \le H_*(0) \le c, \qquad H_N(t) \le c + \varepsilon_U. \tag{S34}$$

Consequently any physical admissible set containing $\{(x,v) : x \in \overline{\Omega},\ H_N(x,v) \le c + \varepsilon_U\}$ *contains this trajectory. Neither a gradient-error bound nor an approximation of* D_* *by* D_N *is needed for this conclusion.*

Proof. The actual field has magnitude at most U and is locally Lipschitz in the state. The first identity in (S31) gives $\dot{H}_* = -d_* - \Phi(y) \le 0$ as long as the solution remains in the declared region. The initial inequality and (S32) give $H_*(0) \le c$. At a first configuration exit, continuity and the strict boundary inequality would imply $H_* \ge U_* \ge U_N - \varepsilon_U > c$, a contradiction. On the compact configuration closure, U_* is bounded below. The energy cap therefore bounds v because $M \succ 0$. The solution stays in a compact subset of its smooth domain, so the standard continuation theorem excludes finite-time escape. Finally $H_N = H_* + \Delta U \le c + \varepsilon_U$ proves the set inclusion.

The theorem concerns the true storage and the exact measured physical port. The learned energy supplies an initial-energy estimate and a guard conversion. Its role here is not a claim that a neural controller outperforms a physical passivity controller. If a positive-work force, an incorrect mass, or an incorrect input map is present, the corresponding extra power cannot be omitted.

Proposition S19. Quantitative error and observation budgets. *Set* $r = (v^T M v)^{1/2}$. *Suppose, on a common declared state region,*

$$\|M^{-1/2}(D_N - D_*)M^{-1/2}\|_2 \le \delta_D, \quad \|M^{-1/2}G\|_2 \le \varepsilon_g, \quad \|M^{-1/2}w\|_2 \le \varepsilon_w.$$

Then

$$d_* \ge \underline{d} := \max\{0, d_N - \delta_D r^2\}. \tag{S35}$$

For exact port feedback the two powers obey

$$\dot{H}_* \le -\underline{d} - \Phi(y) + \varepsilon_w r, \tag{S36}$$

$$\dot{H}_N \le -d_N + \delta_D r^2 - \Phi(y) + (\varepsilon_g + \varepsilon_w) r. \tag{S37}$$

If the applied feedback instead uses $\widehat{y}$ *with* $|y - \widehat{y}| \le \varepsilon_y$, *let* $a = \min(k|\widehat{y}|, U)$. *The term* $-\Phi(y)$ *in either bound may be replaced by*

$$-a(|\widehat{y}| - \varepsilon_y). \tag{S38}$$

Proof. The matrix error gives $|d_N - d_*| \le \delta_D r^2$; retain also $d_* \ge 0$. Weighted Cauchy–Schwarz gives $|v^T G| \le \varepsilon_g r$ and $v^T w \le \varepsilon_w r$. Substitution into (S31) gives the assertions. For the observed output, $uy = u\widehat{y} + u(y - \widehat{y}) \le -a|\widehat{y}| + a\varepsilon_y$.

For example, a certified $D_N \succeq \lambda_N M$ and $\delta_D < \lambda_N$ give true damping at least $(\lambda_N - \delta_D) r^2$. A velocity-proportional disturbance bound $\|M^{-1/2}w\| \le \nu r$ with $\nu \le \lambda_N - \delta_D$ is absorbed by this damping. A constant $\varepsilon_w > 0$ gives a linear term in r and is not absorbed uniformly by quadratic damping near $r = 0$. The same issue affects a nonzero constant gradient bound in (S37). Empirical weak-loss values alone provide none of the uniform constants in this proposition.

Theorem S20. Boundary invariance and bounded-port feasibility. *Let* H *denote either* H_* *or* H_N, *with* H *of class* C^2, *and suppose the sublevel* $S_c = \{(x,v) : H(x,v) \le c\}$ *is compact, lies in the declared smooth domain, and has a regular boundary:* $\nabla_{x,v} H \ne 0$ *on* ∂S_c. *For a specified locally Lipschitz physical force* $w(x,v,t)$, *uniformly locally Lipschitz in the state on finite time intervals, define*

$$P_* = -d_* + v^T w \quad (H = H_*), \qquad P_N = -d_* + v^T(G + w) \quad (H = H_N).$$

Assume the corresponding functions are continuous in time. The saturated feedback above renders S_c *positively invariant if*

$$P(x,v,t) \le \Phi(y(x,v)) \quad \textit{for all } (x,v) \in \partial S_c, \quad t \ge 0. \tag{S39}$$

At a fixed boundary state and time, the smallest available energy derivative among all fields $|u| \le U$ *equals*

$$\min_{|u| \le U} (P + uy) = P - U|y|. \tag{S40}$$

Thus $P - U|y| \le 0$ at every boundary point is necessary for an invariant cap under a bounded continuous feedback. This pointwise feasibility condition alone asserts neither a continuous feedback selection nor an implemented controller.

Proof. Along the saturated closed loop, $\dot{H} = P - \Phi(y)$. The boundary condition is the inward tangent condition for the regular sublevel. To make the invariance argument explicit, a compact regular level has a tubular neighborhood in which distance to the level is bounded by a constant times $|H - c|$. The locally Lipschitz closed-loop field and the locally Lipschitz level normal therefore bound the positive part $h = (H - c)_+$ by $\dot{h} \le L_T h$ in that neighborhood on each finite interval $[0, T]$. Gronwall's inequality with $h(0) = 0$ precludes exit. Initial states strictly inside the sublevel are handled by their first boundary contact. Compactness gives continuation. The scalar minimization is obtained with $u = -U \operatorname{sign} y$ when $y \neq 0$, and with any input when $y = 0$. If its minimum were positive at a boundary state, every available continuous closed loop would initially point strictly out of the sublevel there, contradicting invariance from that initial state.

In particular, at $y = 0$ no magnetic field changes the instantaneous energy derivative. This occurs when $\cos\theta = 0$ or $b^T v = 0$. Restricting $|\theta| < \pi/2$ removes only the former possibility. On a verified part Γ of a boundary where $|y| \ge y_0 > 0$, choosing $k \ge U/y_0$ gives $\Phi(y) = U|y|$. A budget $P \le U y_0 - m$ with $m > 0$ then provides a strict inward margin m on Γ. The remaining boundary still requires (S39); a local nonzero-port calculation does not cover the turning points or the velocity directions orthogonal to b.

A centered, realizable obstruction for a learned-energy cap. Take two coordinates with $M = K_0 = I_2$, $D_* = dI_2$ for $d > 0$, $b = (1, 0)^T$, $\mu > 0$, and

$$U_* = E_0 + \kappa(1 - \cos x_1), \qquad U_N = (1 + \epsilon)E_0 + \kappa(1 - \cos x_1), \qquad \epsilon > 0.$$

This discrepancy is precisely the affine energy skip $F_N = \epsilon E_0$ with zero neural branch, not an uncentered linear force. At $x = (0, 1)^T$, $v = (0, t)^T$ and $0 < t < \epsilon/d$,

$$y = 0, \qquad \dot{H}_N = \epsilon t - dt^2 > 0, \qquad \dot{H}_* = -dt^2 < 0. \tag{S41}$$

Every magnetic input has the same derivative at this state. The H_N sublevel through it has a regular boundary and cannot be invariant under any bounded continuous magnetic feedback, although the true passive energy decreases. The parameters ϵ, t can be arbitrarily small. Hence a small conservative-gradient error and positive damping do not, by themselves, certify invariance of learned energy sublevels on the physical plant.

Restriction and execution scope. On $x = Vq$, $v = VA^{-1}p$, the restricted storage is

$$H_N^{\mathrm{r}}(q, p) = \tfrac{1}{2} p^T A^{-1} p + U_N(Vq), \qquad y^{\mathrm{r}} = \mu \cos(b^T V q) b^T V A^{-1} p.$$

It has its own reduced power identity. It does not identify the physical output with y^{r} on an arbitrary full trajectory, prove invariance of $\operatorname{range}(V)$, or transfer a restricted KAM torus to the full forced dissipative system. A sampled, delayed, or native numerical realization additionally needs full-prefix work, observation, actuation, and numerical-defect bounds for this same physical model. The continuous boundary theorem does not silently inherit a previous held-command record or its safety certificate.

S6.1 Dissipation and coercivity for the calibrated weights

Fresh calculation with the calibrated weights gives $c_C \simeq 0.07237264643$ and $c_E \simeq 0.06002256805$. In particular, $1 + c_E > 0$, so the sufficient global real coercivity condition in (S29) holds for this same network. Its nonnegative dissipation-factor parameterization and full-field power identity hold algebraically. Exact native LDL factorizations again give $D_0 > (6/25)M\,\mathrm{s}^{-1}$, with the exact sum $M = M_0 + M_r$. Exact saved-weight absolute products give the following strict downward relaxations on the full-state feature boxes $|s|_\infty \le r$:

r	a_N lower bound	D_N/M lower bound in s^{-1}
$1/4$	1.0346097	0.2483063
$1/2$	0.9253337	0.2220801
1	0.7250739	0.1740177
$3/2$	0.5492037	0.1318088
2	0.3977230	0.0954535

The last column is a strict Loewner matrix lower bound for every full velocity in the stated configuration domain. The same-checkpoint calculation proves candidate dissipation and coercivity; it does not by itself identify physical damping or certify sampled magnetic feedback. A conditional physical potential guard requires its own uniform potential allowance and implementation assumptions.

S6.2 A conditional physical guard for the calibrated potential

The same saved weights also admit a full-configuration potential-value guard under an explicit physical family. Suppose

$$U_*(x) = (1+\beta)E_0(x) + \kappa(1-\cos(b^T x)),$$

with constant β in the exact scalar compatibility interval in Section S4.1. This is a constitutive family and parameter-interval assumption, not an identification of an arbitrary physical potential from the simulation records. Let E_{net} be the exact saved binary energy scale and set

$$\Omega_4 = \{x : E_0(x) < 4E_{\mathrm{net}}\}, \qquad c = 2.05E_{\mathrm{net}}.$$

Fresh exact-weight bounds on the energy-head gradient and Hessian, an outward origin derivative calculation, and the exact native compliance matrix give the strict relaxations

$$\sup_{\overline{\Omega}_4} |U_N - U_*| < 0.003838998456E_{\mathrm{net}}, \qquad \inf_{\partial\Omega_4} U_N > 4.236161085119E_{\mathrm{net}}.$$

These constants are recomputed for the calibrated weights and the new compatibility interval. They do not reuse the earlier single-configuration checkpoint's margins. With $\varepsilon_U = 0.003838998456E_{\mathrm{net}}$, the certified boundary margin is

$$4.236161085119 - 0.003838998456 - 2.05 = 2.182322086663 > 0.$$

The initial set

$$\mathcal{I} = \{(x,v) : x \in \Omega_4, \quad H_N(x,v) \le 2.046161001544E_{\mathrm{net}}\}$$

contains the origin and an open neighborhood, by continuity and the algebraic centering $H_N(0,0) = 0$. Corollary S21 separately receives all 22 numerical initial records into this fixed set.

Assume the exact same native mass and physical magnetic port, locally Lipschitz physical damping $D_*(x) \succeq 0$, and no unmodeled work. Under actual continuous feedback $u = -\mathrm{sat}_U(ky)$ with the exact full-state port $y = \mu\cos(b^T x)b^T v$, any $U, k > 0$, Theorem S18 applies to every initial state in $\mathcal{I}$. It gives existence for all $t \ge 0$ and

$$x(t) \in \Omega_4, \qquad H_*(t) \le H_*(0) \le c, \qquad H_N(t) \le c + \varepsilon_U.$$

The physical damping assumption in this theorem is distinct from the candidate damping bounds. In particular, the preceding $|s|_\infty \le 2$ candidate bound is not assigned to Ω_4. This is a conditional continuous-feedback safety conclusion; no sampled controller, sensor error, actuation delay, controller rollout or physical-target KAM transfer is certified here.

S6.3 Current-network reception of the 22 recorded numerical initial states

Corollary S21. Fixed-guard reception of all 22 recorded numerical initial states. *Keep the current calibrated complex split-tanh potential U_N, the same exact native full-coordinate matrices $M = M_0 + M_r, K_0$, and the conditional physical-family assumptions of Section S6.2. Let E_{net} be its exact saved binary64 energy scale and set $E_0(x) = x^T K_0 x/2$. Retain*

the already certified domain, cap and error allowance without adjustment:

$$\Omega_4 = \{x : E_0(x) < 4E_{\mathrm{net}}\}, \qquad c = \frac{41}{20}E_{\mathrm{net}}, \qquad \varepsilon_U = \frac{479874807}{125000000000}E_{\mathrm{net}}, \qquad c - \varepsilon_U = \frac{255770125193}{125000000000}E_{\mathrm{net}}.$$

Consider the finest signed records selected in the frozen 11-configuration training protocol: the original shifted configuration, directions 2 and 3, and design nodes 3 through 10, with each of their two velocity-sign labels. For each record use its own unique saved sample with time exactly zero and form

$$x_0 = (w_1, \theta_1, \ldots, w_{32}, \theta_{32})^T, \qquad v_0 = (w_{t,1}, \theta_{t,1}, \ldots, w_{t,32}, \theta_{t,32})^T.$$

Every saved binary64 component is interpreted exactly. Neither vector is replaced by Vq, by an intended preparation, or by the opposite sign. Write $H_N(x, v) = v^T M v/2 + U_N(x)$ and $m_0 = c - \varepsilon_U - H_N(x_0, v_0)$. Both signs in each row satisfy the following strict rational bounds; all terminating decimals are exact outward relaxations:

configuration	$E_0(x_0)/E_{\mathrm{net}} <$	$H_N(x_0, v_0)/E_{\mathrm{net}} <$	$m_0/E_{\mathrm{net}} >$
original shifted	0.011840151418	0.972247611362	1.073913390182
direction 2	0.075607037915	0.237377388001	1.808783613543
direction 3	0.665892667009	0.785898582383	1.260262419161
jet node 3	0.699184876801	0.818661343066	1.227499658478
jet node 4	0.672114306437	0.795381639556	1.250779361988
jet node 5	0.248565856915	0.290319882622	1.755841118922
jet node 6	0.688816911554	0.745602603503	1.300558398041
jet node 7	0.686085823522	0.817887305482	1.228273696062
jet node 8	0.757581829134	0.887146476049	1.159014525495
jet node 9	0.198955734425	0.276686835522	1.769474166022
jet node 10	0.705414332297	0.819033952757	1.227127048787

Thus all 22 saved numerical initial states satisfy the same frozen initial guard. Across these states,

$$0.237377387997 < \frac{H_N(x_0, v_0)}{E_{\mathrm{net}}} < 0.972247611362, \qquad 1.073913390182 < \frac{m_0}{E_{\mathrm{net}}} < 1.808783613547.$$

The unchanged boundary guard has exact margin $2182322086663E_{\mathrm{net}}/10^{12} > 0$.

Proof. The receiver verifies the current guard's actual zero exit code and hashed result before receiving its fixed constants. Each of the 22 observation files is bound to its own completed producer receipt and a launcher receipt with actual MATLAB exit code zero, including the different receipt structures of the original and later producers. The 257 saved times, 33 node identities, and all four 257×33 position/velocity field arrays are checked separately for every record. Exact rational coordinate gaps at most $10^{-15}\,\mathrm{m}$ associate each saved node with a unique native finite-coordinate field row; this is a node-identity check, not an interpolation-error estimate. The saved clamped-root values at the initial sample are exactly zero.

The receiver extracts all 64 free coordinates and evaluates E_0 and $v^T M v/2$ by exact rational arithmetic, adding $M_0 + M_r$ before use. The same-source successful native positive-pivot proof is received; no new LDL factorization is performed. For the energy features only, it computes the exact mass projection $q = Bx_0$, where $B = (V^T M V)^{-1} V^T M$; the full state remains x_0. The centered current energy-head expression is evaluated with outward Arb arithmetic at 512 bits, including its actual complex realification, the exact skip coefficient, the origin readout and the first three origin-gradient subtractions. The magnetic term uses the actual saved tip angle θ_{32}. This yields strict rational lower and upper endpoints for every H_N/E_{net} and m_0/E_{net}. Independent exact rational rounding proves the displayed relaxations. All 22 tests resolve strictly and pass; rejection would have been reported as a valid negative decision rather than as arithmetic failure. Since $E_0 < 4E_{\mathrm{net}}$ and $H_N + \varepsilon_U < c$, each saved vector pair satisfies the theorem's initial inequalities when used as an exact mathematical initial state. The 11 positive/negative pairs have nonzero recorded position and velocity-sum differences, which are retained and evaluated separately.

This corollary receives numerical recorded initial states, not physical measurements. No certified error bound relates a saved binary64 state to a true physical initial state. The continuous safety conclusion still requires the declared physical potential family, the same exact full-state port, $w = 0$, and actual continuous saturated feedback. These forced observation records do not show that such feedback was executed, or certify any sampled, delayed or sensor-error realization. No new native solve, training, gradient update, weight selection, guard adjustment, control run, or physical KAM transfer is established.

S7 A conditional sampled magnetic power guard

Let $x, v \in \mathbb{R}^{64}$ have the native transverse finite-element ordering, let $b = e_{64}$, and set

$$E_0(x) = \tfrac{1}{2} x^T K_0 x, \qquad U_\beta(x) = (1+\beta)E_0(x) + \kappa(1 - \cos b^T x). \tag{S42}$$

Here M, K_0 are the received positive definite native matrices and $\beta \in [\beta_-, \beta_+] \subset (-1, \infty)$ is constant. Consider the explicitly assumed physical family

$$M\dot{v} = -\nabla U_\beta(x) - a(x) D_0 v + \mu u b \cos(b^T x), \qquad \dot{x} = v, \tag{S43}$$

where $D_0 \succeq 0$, a is locally Lipschitz, and $0 \le a(x) \le \bar{a}$. The input u denotes the actual total transverse magnetic field, after quantization, with $|u| \le U$. The preparation cosine field is replaced, not superposed. Define

$$H_\beta = \tfrac{1}{2} v^T M v + U_\beta(x), \qquad y = \mu \cos(b^T x) b^T v. \tag{S44}$$

Then $\dot{H}_\beta = -a(x) v^T D_0 v + uy \le uy$. Discarding the nonnegative dissipation requires no bound on its derivative.

A full-state output-rate majorant. Fix an energy cap $c > 0$, and write $z = M^{-1} b$. On $H_\beta \le c$, set

$$V_c = \sqrt{2c\, b^T M^{-1} b}, \qquad \Theta_c = \sqrt{\frac{2c\, b^T K_0^{-1} b}{1+\beta_-}}, \qquad S_c = \min(1, \Theta_c), \tag{S45}$$

$$A_K = (1+\beta_+)\sqrt{\frac{2c\, z^T K_0 z}{1+\beta_-}}, \qquad A_D = \bar{a}\sqrt{2c\,(D_0 z)^T M^{-1} (D_0 z)}, \tag{S46}$$

$$A_B = (b^T M^{-1} b)(\kappa S_c + \mu U). \tag{S47}$$

For positive μ, κ, a valid majorant is

$$L_y = \mu\{S_c V_c^2 + A_K + A_D + A_B\}. \tag{S48}$$

Indeed, the energy cap bounds $|b^T v|$ and $|b^T x|$ by V_c and Θ_c. Cauchy–Schwarz in the K_0 and M metrics bounds the elastic and dissipative terms in $b^T \dot{v}$ by A_K and A_D, respectively. The remaining magnetic term is bounded by A_B. Differentiating $y = \mu \cos(b^T x) b^T v$ gives $|\dot{y}| \le L_y$. The assumption $\bar{a} < \infty$ is needed for this particular majorant; positive semidefinite dissipation alone does not provide it.

Sampled work and a strict energy ledger. At the actual hold start t_k, suppose a valid observation supplies $|y(t_k) - \widehat{y}_k| \le \varepsilon_k$. Apply a constant actual input u_k for a prescribed duration $h_k > 0$. For every prefix $0 \le s \le h_k$ remaining below the energy cap,

$$H_\beta(t_k + s) - H_\beta(t_k) \le F_k(s) := s(u_k \widehat{y}_k + |u_k| \varepsilon_k) + \tfrac{1}{2} s^2 |u_k| L_y. \tag{S49}$$

Since F_k is convex and $F_k(0) = 0$, $F_k(s) \le \max\{0, F_k(h_k)\}$. Let $\Delta_k = F_k(h_k)$ and let $\lceil \cdot \rceil_g$ denote upward rounding to a fixed positive energy grid g. Assume a trusted initial ledger satisfies $H_\beta(t_0) \le L_0 < c$ and $L_0 \in g\mathbb{Z}_{\ge 0}$. Accept a nonzero proposal only when it satisfies the actual input limit, the current observation is valid, and

$$\Delta_k \le \alpha(c - L_k), \qquad L_{k+1} = \left\lceil \max\{0, L_k + \Delta_k\} \right\rceil_g < c, \qquad 0 < \alpha < 1. \tag{S50}$$

Otherwise apply exactly zero and retain the ledger. The accepted hold obeys $H_\beta(t_{k+1}) \le L_{k+1}$ and remains strictly below c throughout. To prove the latter without circularity, suppose there is a first time at which $H_\beta = c$. Before that time (S48) applies, and (S49) implies

$$H_\beta(t_k + s) \le L_k + \max\{0, \Delta_k\} < c,$$

contradicting the first exit. A rejected or zero proposal uses $\dot{H}_\beta \le 0$ directly. Induction proves the strict energy cap for all holds. A fixed $h_k = h > 0$, or another schedule without finite-time accumulation, excludes Zeno accumulation. The coercive energy then bounds the state for all finite times.

For an opposite-sign proposal, the stronger condition $|\widehat{y}_k| \ge \varepsilon_k + L_y h_k/2$ makes $\Delta_k \le 0$ and makes every prefix work bound nonpositive. This integral statement does not assert instantaneous $u_k y(t) \le 0$; the sufficient instantaneous condition instead uses $|\widehat{y}_k| \ge \varepsilon_k + L_y h_k$.

Connection to the learned potential guard. Suppose the current checkpoint satisfies $|U_N - U_\beta| \le \varepsilon_U$ on $\Omega_4 = \{E_0 < 4E_{\mathrm{net}}\}$. Each separately received numerical initial state can initialize the ledger by rounding an outward upper enclosure of $H_N(t_0) + \varepsilon_U$ upward to the grid, provided the rounded value is strictly below c. For the present $c = 41E_{\mathrm{net}}/20$ and received β_-, $c/(1+\beta_-) < 4E_{\mathrm{net}}$, so the physical energy cap also stays inside Ω_4. The theorem concerns the declared physical family, not a derivative match between the learned and physical potentials.

Observation and execution scope. A rigorous midpoint computation at a saved numerical state supplies an arithmetic observation enclosure. It does not certify a physical sensor. For a tip observation with actual hold-start errors $|\theta - \widehat{\theta}| \le r_\theta$ and $|\omega - \widehat{\omega}| \le r_\omega$, a sufficient additional port error allowance is

$$\mu\{r_\omega + |\widehat{\omega}| \min(2, r_\theta)\},$$

plus the outward error of computing $\mu\cos(\widehat{\theta})\widehat{\omega}$. Timing, sensing and total-field actuation must satisfy their declared contracts to apply the result to an experiment. This initial-proposal reception alone does not execute a controller. The separate numerical execution is treated in Section S7.3; neither reception claims a physical sampled controller run, physical parameter identification, convergence, or control performance.

S7.1 A received sampled-power instance for the calibrated guard

Use the same current checkpoint, $c = 41E_{\mathrm{net}}/20$, $\varepsilon_U = 479874807E_{\mathrm{net}}/125000000000$, the unchanged scalar compatibility interval, and the full 64-coordinate native matrices. For this instance assume additionally $D_*(x) = a(x)D_0$ with $0 \le a(x) \le 6/5$. This finite operator bound is an extra physical hypothesis; it is not inferred from positive semidefiniteness or from the candidate's feature-box dissipation bound.

Exact rational matrix operations and outward square roots give

$$|b^T x| < 0.001909972751, \qquad |b^T v| < 20.504956934$$

on $H_* \le c$. With the actual total-field limit $U = 10^{-4}$ T, (S48) has the strict bound

$$L_y < 49.953396682\ \mathrm{J\,T^{-1}s^{-2}}.$$

Here M is the exact sum of the saved M_0 and M_r entries, and $D_0 = \alpha M_0$ with the exact nominal coefficient from the native operator record. The shifted trajectory damping coefficient and translational-plus-rotary mass are not substituted into D_0.

For each of the 22 separately received numerical initial states, compute an outward enclosure of $y = \mu\cos\theta_{32}\, v_{\theta,32}$ and take its rational midpoint $\widehat{y}_0$. Its arithmetic enclosure radius is strictly below the prescribed allowance $\varepsilon_y = 10^{-8}\,\mathrm{J\,T^{-1}s^{-1}}$. Set the energy grid to $g = 10^{-9}E_{\mathrm{net}}$, the reserve fraction to $\alpha = 1/2$, and initialize

$$L_0 = \left\lceil \overline{H}_N(x_0, v_0) + \varepsilon_U \right\rceil_g.$$

The strict common bounds are $0.241216386 < L_0/E_{\mathrm{net}} < 0.976086611 < c/E_{\mathrm{net}}$. For the nonzero opposite-sign proposal $u_0 = -U\,\mathrm{sign}(\widehat{y}_0)$, exact evaluation of (S50) gives

Hold duration	Accepted nonzero proposals	Upper next ledger/E_{net}
$1\,\mu$s	$22/22$	0.976499156
$10\,\mu$s	$22/22$	1.017677105
$100\,\mu$s	$0/22$	0.976086611

For the $10\,\mu$s holds the computed work majorants obey $0.041462830554 < \Delta_0/E_{\mathrm{net}} < 0.041617370734$. The rejected $100\,\mu$s proposals use the exact zero fallback and retain their initial ledger. These comparisons keep the same field limit, error allowance, cap and rounding grid throughout.

The arbitrary-horizon conclusion follows from the work-ledger theorem only if every subsequent hold also receives a valid current observation and applies the accepted actual total command with the stated timing. This initial-proposal calculation evaluates saved numerical states without executing a trajectory. A separate numerical feedback execution and its reference-IVP certificate appear in Section S7.3. The error allowance is not a physical sensor certificate. Acceptance establishes a conditional energy guard, not monotone decrease on accepted holds or improved control performance.

S7.2 Continuous reception of the three held-field segments

Fix the declared 64-coordinate mathematical equation

$$M\ddot{x} + D\dot{x} + Kx + b\{\kappa \sin(b^{\top}x) - \mu u(t)\cos(b^{\top}x)\} = 0, \quad M = M_0 + M_r, \quad K = \tfrac{53}{50}K_0, \quad D = \alpha_{\mathrm{shift}}M_0,$$

where the saved matrix entries and $\alpha_{\mathrm{shift}} = 5754906970707699/9007199254740992$ are interpreted as exact rationals. Here $b = e_{64}$, time is in seconds, u is in tesla, and $y = \mu\cos(b^{\top}x)b^{\top}\dot{x}$ has units $\mathrm{J}/(\mathrm{T\,s})$. The field u is the actual, constant binary64 total transverse field on each segment; it replaces the preparation cosine. This declared IVP starts at the fresh seed's own saved position and velocity. It asserts neither an exact physical initial state nor identity with a compiled native equation.

Let Q be the piecewise cubic Hermite curve through every retained native position and velocity endpoint. Each cell uses its own exact dyadic duration. All 101 predecessor handoffs, including the physical-time coordinate, are received bitwise. Thus Q and $\dot{Q}$ are continuous across both interior cells and field switches. The exact equation has continuous position and velocity at a field switch, although acceleration may jump. Define

$$e = x - Q, \quad r^2 = \dot{e}^{\top}M\dot{e} + e^{\top}Ke, \quad c_M = \sqrt{b^{\top}M^{-1}b}, \quad c_K = \sqrt{b^{\top}K^{-1}b}.$$

The initial radius is zero once, at the declared saved seed, and is not reset at a continuation boundary. For $|u| \le U = 10^{-4}\,\mathrm{T}$, the scalar magnetic force is globally Lipschitz in angle with constant $\kappa + \mu U$. If ρ bounds the Hermite residual in the M^{-1} norm, then

$$D^{+}r \le ar + \rho, \qquad a = \tfrac{1}{2}(\kappa + \mu U)c_M c_K.$$

Indeed, the damping term is nonpositive, the residual contributes at most $r\rho$, and $|\dot{e}^{\top}b|\,|b^{\top}e| \le c_M c_K r^2/2$. For a cell of duration h with initial radius r_ℓ,

$$\bar{r}(s) = e^{as}r_\ell + \rho\,\frac{e^{as} - 1}{a}, \qquad 0 \le s \le h$$

is a nondecreasing prefix majorant. An outward grid ceiling of $\bar{r}(h)$ supplies the next initial radius. The global force bound removes a tube-closure assumption.

On one cell put $\theta_Q = b^{\top}Q$ and $\Theta \ge \sup|\theta_Q|$. Form the degree-nine polynomial residual

$$R_{\mathrm{pol}} = M\ddot{Q} + D\dot{Q} + KQ + b\{\kappa(\theta_Q - \theta_Q^3/6) - \mu u(1 - \theta_Q^2/2)\}.$$

The omitted scalar force is bounded on the whole cell by

$$\epsilon_{\mathrm{nl}} = \kappa\Theta^5/120 + \mu|u|\Theta^4/24.$$

These real Taylor bounds do not require a small-angle assumption. If $B_0, \dots, B_9$ are the degree-nine Bernstein coefficient vectors of R_{pol}, convexity of the norm gives

$$\rho = \max_j \sqrt{B_j^\top M^{-1} B_j} + c_M \epsilon_{\mathrm{nl}}.$$

The exact rational matrices and inverse are received once, then enclosed in 512-bit Arb balls. All cell arithmetic, including the quadratic forms and stable $\mathrm{expm1}(ah)$ evaluation, uses outward intervals; the reported radius is rounded upward. No per-cell matrix inverse or sampled-residual substitution is used.

At a saved endpoint with tip velocity $v_{\theta,Q}$,

$$|y(x,\dot{x}) - y(Q,\dot{Q})| \le \mu\{c_M r + |v_{\theta,Q}| \min(2, c_K r)\}.$$

For a whole-cell comparison, replace r by its prefix endpoint majorant and $|v_{\theta,Q}|$ by the Bernstein bound on the Hermite velocity. For the controller's actual logged exact rational value $\widehat{y}$, the separate outward readout allowance $|\,\mu\cos(\theta_Q)v_{\theta,Q} - \widehat{y}\,|$ must be added. In particular an exact midpoint of an Arb enclosure need not be converted to binary64. Only a receipt binding the actual logged value to the actual hold-start observation can receive the fixed prospective $\varepsilon_y = 10^{-8}\,\mathrm{J/(T\,s)}$ contract. A saved finite state alone is insufficient. Neither a successful IVP tube nor that sensor inequality alone receives the other causal ledger, cap, timing, actuation, or initial guard hypotheses of the sampled safety theorem.

S7.3 Continuous reception of the recorded calibrated feedback

Proposition S22. Recorded three-hold energy ledger. *Consider the 64-coordinate mathematical initial-value problem*

$$M\ddot{x} + D\dot{x} + Kx + b\{\kappa \sin\theta - \mu u(t)\cos\theta\} = 0, \qquad \theta = b^\top x, \quad b = e_{64},$$

with the exact saved matrices $M = M_0 + M_r$, $K = (53/50)K_0$, *and* $D = \alpha_{\mathrm{shift}} M_0$, *where* $\alpha_{\mathrm{shift}} = 5754906970707699/9007199254740992$. *Its initial position and velocity are the actual saved numerical seed state at* $t_0 \simeq 20\,\mu\mathrm{s}$. *Define*

$$H_\star = \tfrac{1}{2}\dot{x}^\top M\dot{x} + \tfrac{1}{2}x^\top Kx + \kappa(1-\cos\theta), \qquad y = \mu\cos\theta\, b^\top\dot{x}.$$

The three recorded holds have their own exact saved binary64 endpoints $t_0 < t_1 < t_2 < t_3 \simeq 50\,\mu\mathrm{s}$. *On these holds the actual total input is, respectively,* $-u_q, +u_q, 0$, *with*

$$u_q = \frac{1844674407370955}{18446744073709551616}\,\mathrm{T} < 10^{-4}\,\mathrm{T}.$$

The held field replaces the preparation cosine. For this declared IVP, the received bounds imply

$$H_\star(t_j) \le L_j, \qquad H_\star(t) \le 0.910436431\,E_{\mathrm{net}} < c = \tfrac{41}{20}E_{\mathrm{net}} \quad (t_0 \le t \le t_3),$$

where

$$(L_0, L_1, L_2, L_3)/E_{\mathrm{net}} = (0.836050803,\ 0.870553256,\ 0.910436431,\ 0.910436431).$$

This is a statement about the recorded three-hold declared IVP. It does not assert identity with the compiled native equation, a physical initial-state or sensor certificate, native dense-output accuracy, or any future rollout.

Proof. The actual native execution contains one fresh preparation solve and three continuation solves. Each continuation retains all 101 saved solution and time-derivative entries bitwise from its predecessor. The mathematical IVP starts only at the saved seed; the preceding preparation trajectory is not certified by this proposition. The three holds contain 514 retained raw states each, including an extremely short terminal cell of approximately $4.066\,10^{-19}\,\mathrm{s}$. The original all-cell reception is preserved and does not receive the fixed sensor budget.

The separate selected-partition protocol predeclares strides two, four and eight. For each hold, the stride-eight curve retains the original raw indices $0, 8, \dots, 504, 513$, with zero-based indexing. It has 64 Hermite cells per hold and keeps every actual

controller endpoint and its original position and velocity. The final short cell is merged into a wider cell. No source state, input, controller time or error budget is changed. For this new piecewise C^1 curve Q, every selected cell is certified on its entire interval using the residual of the declared 64-coordinate equation. The reconstruction need not interpolate omitted raw samples; no enclosure of those samples or native dense output is inferred.

The comparison radius satisfies

$$r^2 = (\dot{x} - \dot{Q})^\top M(\dot{x} - \dot{Q}) + (x - Q)^\top K(x - Q), \qquad D^+ r \le ar + \rho,$$

where $a = (\kappa + \mu 10^{-4})\sqrt{(b^\top M^{-1} b)(b^\top K^{-1} b)}/2$. It is initialized once at $r(t_0) = 0$ and propagated across all three holds. The polynomial residual uses cubic sine and quadratic cosine terms. Its whole-cell remainder is bounded by $\kappa\Theta^5/120 + \mu|u|\Theta^4/24$. Degree-nine Bernstein coefficient vectors, the M^{-1} norm and outward 512-bit Arb arithmetic give the cell residual bound. Thus neither residual samples nor resetting the radius at field switches is used.

At a hold start, with $c_M = \sqrt{b^\top M^{-1} b}$ and $c_K = \sqrt{b^\top K^{-1} b}$, the received port allowance is

$$\mu\{c_M r + |v_{\theta,Q}| \min(2, c_K r)\} + \left|\mu \cos(\theta_Q) v_{\theta,Q} - \widehat{y}\right|.$$

The second term independently receives the exact rational midpoint $\widehat{y}$ actually used by the bridge; it is not converted to binary64. The resulting upward bounds at the three hold starts are

$$\delta_{y,0} \le 10^{-50}, \qquad \delta_{y,1} < 6.873047\,10^{-9}, \qquad \delta_{y,2} < 1.639569\,10^{-8} \quad \mathrm{J/(T\,s)}.$$

Only the first two holds have nonzero input. Their allowances fit the unchanged prospective $\varepsilon_y = 10^{-8}$. The computed third bound exceeds that budget, and the all-three-sensor contract remains unreceived.

Direct exact-model energy evaluation gives $H_\star(t_0) < 0.832211815\,E_{\mathrm{net}} \le L_0 < c$. An independent energy-dual calculation on $H_\star \le c$ gives an output-rate bound below $49.953391663\,\mathrm{J/(T\,s^2)}$; it fits the already frozen uniform bound $L_y < 49.953396682\,\mathrm{J/(T\,s^2)}$. For each nonzero hold, its actual exact duration $h_j = t_{j+1} - t_j$ is used in

$$\Delta_j = h_j\{u_j \widehat{y}_j + |u_j|\varepsilon_y\} + \tfrac{1}{2} h_j^2 |u_j| L_y.$$

Independent rational arithmetic receives the reserve gate, upward $10^{-9}E_{\mathrm{net}}$ grid ceiling, strict cap gate and matching single transactional commit. The quadratic prefix majorant and first-exit argument then give $H_\star(t) < c$ throughout the first two holds and $H_\star(t_2) \le L_2$. These holds spend a positive energy reserve; they are not certified to have nonincreasing energy.

On the final recorded hold the actual total field is identically zero. Since $D = \alpha_{\mathrm{shift}} M_0 \succeq 0$,

$$\dot{H}_\star = -\dot{x}^\top D \dot{x} \le 0, \qquad H_\star(t) \le L_2 = L_3 < c \quad (t_2 \le t \le t_3).$$

This branch requires neither a port observation nor L_y. It completes the recorded-interval ledger statement without receiving the third sensor contract.

Comparison of reconstructions. The original all-cell reconstruction and the predeclared stride-two and stride-four reconstructions did not receive the required port budget at the second nonzero hold. Their computed upper bounds exceed 10^{-8}; upward rounded displays are $4.972088\,10^{-4}$, $2.132616\,10^{-8}$ and $1.094943\,10^{-8}$, respectively. These are upper bounds, not lower bounds on the actual error. The stride-eight reconstruction receives both required nonzero-hold contracts; its third, unused sensor contract remains unreceived. All original negative outcomes, raw data and actual commands are retained.

References

Abbott JJ, Diller E and Petruska AJ (2020) Magnetic methods in robotics. *Annual Review of Control, Robotics, and Autonomous Systems* 3: 57–90. doi: 10.1146/annurev-control-081219-082713

Chen Y, Matsubara T and Yaguchi T (2022) KAM theory meets statistical learning theory: Hamiltonian neural networks with non-zero training loss. *Proceedings of the AAAI Conference on Artificial Intelligence* 36(6): 6322–6332. doi: 10.1609/aaai.v36i6.20582

Desai SA, Mattheakis M, Sondak D, Protopapas P and Roberts SJ (2021) Port-Hamiltonian neural networks for learning explicit time-dependent dynamical systems. *Physical Review E* 104: 034312. doi: 10.1103/PhysRevE.104.034312

Greydanus S, Dzamba M and Yosinski J (2019) Hamiltonian neural networks. In: *Advances in Neural Information Processing Systems*, vol. 32. https://arxiv.org/abs/1906.01563.

Haro À and Luque A (2019) A-posteriori KAM theory with optimal estimates for partially integrable systems. *Journal of Differential Equations* 266(2–3): 1605–1674. doi: 10.1016/j.jde.2018.08.003 Preprint version used: https://arxiv.org/abs/1711.05515v1.

Kim Y, Parada GA, Liu S and Zhao X (2019) Ferromagnetic soft continuum robots. *Science Robotics* 4(33): eaax7329. doi: 10.1126/scirobotics.aax7329

Pöschel J (2001) A lecture on the classical KAM theorem. In: *Proceedings of Symposia in Pure Mathematics*, vol. 69, pp. 707–732. doi: 10.1090/pspum/069/1858551 Preprint version used: https://arxiv.org/abs/0908.2234v1 (Version 1.3, 2009).

Trabelsi C, Bilaniuk O, Zhang Y et al. (2018) Deep complex networks. In: *International Conference on Learning Representations*. https://arxiv.org/abs/1705.09792.

Zhang SQ, Gao W and Zhou ZH (2022) Towards understanding theoretical advantages of complex-reaction networks. *Neural Networks* 151: 80–93. doi: 10.1016/j.neunet.2022.03.024

Zhong YD, Dey B and Chakraborty A (2020) Dissipative SymODEN: Encoding Hamiltonian dynamics with dissipation and control into deep learning. In: *ICLR Workshop on Integration of Deep Neural Models and Differential Equations*. https://arxiv.org/abs/2002.08860.