

# **Computer Networks**

User Datagram Protocol (UDP) (§6.4)



# Topic

- Sending messages with UDP
  - A shim layer on packets



**Computer Networks** 

2

# User Datagram Protocol (UDP)


- Used by apps that don't want reliability or bytestreams
  - → Voice-over-IP (unreliable)
  - DNS, RPC (message-oriented)
  - DHCP (bootstrapping)

(If application wants reliability and messages then it has work to do!)


**Computer Networks** 

-3

## **Datagram Sockets**




# Datagram Sockets (2)



**Computer Networks** 

# **UDP** Buffering



**Computer Networks** 

6


#### **UDP** Header

- Uses ports to identify sending and receiving application processes
- Datagram length up to 64K
- Checksum (16 bits) for reliability

	32 Bits —	
5	Source port	Destination port
1	UDP length	UDP checksum

# UDP Header (2)

- Optional checksum covers UDP segment and IP pseudoheader
  - Checks key IP fields (addresses)
  - Value of zero means "no checksum"



### **END**

#### © 2013 D. Wetherall

Slide material from: TANENBAUM, ANDREW S.; WETHERALL, DAVID J., COMPUTER NETWORKS, 5th Edition, © 2011. Electronically reproduced by permission of Pearson Education, Inc., Upper Saddle River, New Jersey

Computer Networks 9