Auditing the Winner: An Upper Bound on What Critic Disagreement Adds Beyond the Selector on SWE-Agent Trajectories

Joseph Morante[1,*]
[1] Algoverse AI Research
morantejoseph1@gmail.com
[*] Corresponding author.

The question. When an agent commits the best of n attempts under a learned critic, the committed trajectory is where that critic's confidence and its errors coincide. A common proposal is to audit it with a panel of critics disjoint from the selector and escalate on disagreement. Audit signals are almost always evaluated over *candidate pools*; a deployed auditor runs *after* selection. We evaluate one on the population a selector actually commits, against the selector's own score, with executed gold.

Setup. Pre-registered throughout, with dated amendments. SWE-bench Verified (41 instances, 9 repositories) and SWE-bench Multilingual (114 instances, 37 repositories); `gpt-5-mini` at a 40-step limit; best-of-4 selection by a reward model; a checkpoint-disjoint audit panel; u is the sample SD of rank-normalised panel scores, fit on training repositories only; gold is trajectory-level success under the official `swebench` 5.x harness, positive class failure. Silent failures — committed, agent-declared-complete trajectories that fail hidden tests — were 35% and 45% of the population.

Result. The registered endpoint compares two detectors of silent failure on the committed population, out of fold: the selector's own score alone, and the same score with panel disagreement added. Pooled over 111 rows, 47 failures and 46 repositories, the three estimators that use every row place the gain between -0.030 and $+0.013$ AUROC. Every interval includes zero (Table 1); the loosest pooled upper bound is $+0.12$, above the $+0.05$ we declared actionable. Disagreement alone ranks failures at 0.508 and 0.565. This failure to detect gain held across 4k–16k contexts, pruned windows, eight reward models from 1B to 32B, two re-selection regimes and a panel of LLM judges. The pilot's positives did not replicate on 37 fresh repositories: u_{max} fell from 0.686 to 0.541 and the 1B critic from 0.712 to 0.485.

Population	Estimator	ΔAUROC	95% CI
Verified (34 rows, 12 failures)	registered LORO	-0.114	$[-0.37, +0.22]$
Multilingual (77, 35)	registered LORO	$+0.005$	$[-0.19, +0.22]$
Pooled (111, 47)	logistic LORO	-0.030	$[-0.10, +0.04]$
Pooled	logistic 5-fold, clustered	-0.014	$[-0.09, +0.07]$
Pooled	fixed unit weights	$+0.013$	$[-0.07, +0.12]$

Table 1 | Out-of-fold gain in AUROC from adding panel disagreement u to the selector's own score $-c$, positive class failure. Intervals are repository-clustered bootstraps; LORO is leave-one-repository-out.

Why the population matters. On Verified the selector's own score ranks failures at 0.81 among candidates it passed over and 0.61 among those it committed — the selection-conditional gap measured directly. Pool performance does not answer the deployment question. On Multilingual that critic has no signal in either arm (0.43 and 0.51), so the gap is observed on one benchmark only.

The dissociation. Individual critics carry information their disagreement discards. `gpt-6-sol` ranks silent failures at 0.776 [0.68, 0.87] on the replication and 0.826 on the pilot, while the disagreement of that newer pair falls to 0.41, *below* the weaker trio's 0.51–0.53. Better judges; worse disagreement. Test–retest shows the critics are stable ($r \geq 0.98$), so the failure is in what disagreement measures, not in critic noise.

What we claim, and what we do not. A bound, not an absence. With 47 positives the study supports failure to reject and an upper bound of $+0.12$, above the $+0.05$ this project declared actionable; establishing equivalence would need roughly five times the failures. The reusable contribution is the validation protocol — evaluate an auditor on the committed population, against the selector's own score, with executed gold, out-of-sample scoring and clustering on the real dependence unit — not a new auditor.

Seven ways the instrument lied to us. Each would have produced a publishable-looking result. A sandbox flag hid `numpy` from the gold harness, scoring every trajectory a failure. A judge critic emitted three distinct values over 640 candidates, so best-of-16 silently became first-draw. Harness image pulls failed on an architecture manifest: 41/41 failures in 499 seconds. Our power function reported ≈0.40 power under the true null against a correct 0.010. Repository grouping truncated hyphenated names, so held-out repositories were not held out. Rank normalisation was fit on all rows. And the selector-axis analysis filtered by the *previous* selector's committed candidate, manufacturing $+0.375$ from a collapsed baseline where the correct population gives $+0.012$. The rule we adopted: a rate of exactly 0% or 100%, or a statistic that cannot move, is an instrument, not a result.

The agent axis. A capable open-weight agent was tested against gates registered before the run. Under Amendment 13, `DeepSeek-V4.1-Flash` ran on 114 Multilingual instances at 100 steps: DeepSeek's failure rate is 0.200 against 0.579 for `gpt-5-mini` at the same 100-step cap (four attempts per instance versus one), so the capability gate passed, but no critic separated its failures from its successes above chance (`gpt-5` judge pool AUROC 0.552 against a bar of 0.65; reward models 0.419–0.523; a stronger judge, `gpt-6-sol`, reaches 0.619 as a selector and still misses the bar), so the registered selector gate failed and the cell is descriptive only. No critic cleared the selector bar on that agent; the objection is re-posed, not retired. The 40-step and 100-step gates that preceded it (Amendments 10–12) are recorded in the pre-registration linked below.

Context. Benchmarks and scaffold (Jimenez et al., 2024; Yang et al., 2025a,b); the optimizer's curse (Smith and Winkler, 2006) and reward over-optimisation (Gao et al., 2023); correlated judge errors (Goel et al., 2025; Kohli, 2026); pre-registration (Nosek et al., 2018); clustered ROC (Obuchowski, 1997).

Links. Pre-registration with every dated amendment: https://github.com/morantejr/silentfail-bench-public/blob/main/silentfail_bench/PREREGISTRATION_SWEBENCH_PILOT.md. Code, data and the consistency checker that pins every number above: https://github.com/morantejr/silentfail-bench-public.

What we would like to discuss. Whether the selection-conditional protocol — selected population, selector baseline, out-of-sample incremental value, clustering on the real dependence unit, executed gold, oracle controls on the instrument — is the right default for evaluating audit signals, and what a purpose-built post-selection auditor would have to beat.

References

Leo Gao, John Schulman, and Jacob Hilton. 2023. Scaling laws for reward model overoptimization. *ICML*. https://arxiv.org/abs/2210.10760. arXiv:2210.10760. Cited at: 1.

Shashwat Goel, Joschka Struber, Ilze Amanda Auzina, et al. 2025. Great models think alike and this undermines ai oversight. *arXiv:2502.04313*. https://arxiv.org/abs/2502.04313. Cited at: 1.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, et al. 2024.

SWE-bench: Can language models resolve real-world github issues? *ICLR*. https://arxiv.org/abs/2310.06770. arXiv:2310.06770. Cited at: 1.

Guneet Kohli. 2026. Nine judges, two effective votes: Correlated errors undermine llm evaluation panels. *arXiv:2605.29800*. https://arxiv.org/abs/2605.29800. Cited at: 1.

Brian A. Nosek, Charles R. Ebersole, Alexander C. DeHaven, and David T. Mellor. 2018. The preregistration revolution. *PNAS*, 115(11):2600–2606. https://doi.org/10.1073/pnas.1708274114. Cited at: 1.

Nancy A. Obuchowski. 1997. Nonparametric analysis of clustered roc curve data. *Biometrics*, 53(2): 567–578. https://doi.org/10.2307/2533958. Cited at: 1.

James E. Smith and Robert L. Winkler. 2006. The optimizer's curse: Skepticism and postdecision surprise in decision analysis. *Management Science*, 52(3):311–322. https://doi.org/10.1287/mnsc.1050.0451. Cited at: 1.

John Yang, Carlos E. Jimenez, et al. 2025a. SWE-bench multilingual. *SWE-bench project, https://www.swebench.com/multilingual.html*. https://www.swebench.com/multilingual.html. Cited at: 1.

John Yang, Kilian Lieret, et al. 2025b. mini-swe-agent. *https://github.com/SWE-agent/mini-swe-agent, version 2.4.6*. https://github.com/SWE-agent/mini-swe-agent. Cited at: 1.