

Python

A quickstart into the key concepts of programming

IO

IO

io.ipynb

Getting data inside your program

- Hard coding
- Console IO (interactive)
- Command line IO
- File IO

Console Input Output

- Standard file handles:
 - `sys.stdin`: standard input (keyboard, pipe in)
 - `sys.stdout`: standard output (screen, pipe out)
 - `sys.stderr`: standard error (screen, pipe out)
- Input: read from the console
 - `input([prompt])` returns a value (string)
 - To convert the string to a number, cast the string to the desired data type with `int()`, `float()`
- *File: input_1.py*

Console Output

- The `print` function is the most commonly used command to print information to the “standard output device” which is normally the screen.
- 2 modes to use `print`.
 - Simple print
 - The easiest way to use the `print` command is to list the variables to be printed, separated by comma.
 - Formatted print
 - The more sophisticated way of formatting output uses a syntax very similar to Matlab’s `fprintf` (also similar to C’s `printf`).

Print

- `print()` writes objects to `sys.stdout`, adds `'\n'` (or `'\r\n'`) and applies `str()` conversion function by default
- `print` automatically puts a single space between items and a newline at the end.
- **Syntax:** `print(objects, sep=' ', end='\n', file=sys.stdout, flush=False)`
- **Parameters**
 - `objects` - objects to be printed.
 - `sep` - objects are separated by `sep`. Default value: `' '`
 - `end` - end is printed at last
 - `file` - must be an object with `write(string)` method. Default: `sys.stdout` (screen)
 - `flush` - If `True`, the stream is forcibly flushed. Default value: `False`

Format output

- Different possibilities

```
name = 'Peter'
```

```
age = 23
```

```
print('%s is %d years old' % (name, age))
```

```
print('{} is {} years old'.format(name, age))
```

```
print(f'{name} is {age} years old')
```

- *File: fstring_01.py*
- <https://realpython.com/python-string-formatting/>

Old string formatting

- The % operator (modulo) can be used for string formatting.
- Given format % values (where format is a string), % conversion specifications in format are replaced with zero or more elements of values.
- This operation is commonly known as string interpolation.

Str.format

- **fill-in-the-braces**
 - string type has `format()` method which takes arguments and returns another string which is the original with the method's arguments inserted into it in certain places.
 - `format()` replaces each pair of curly brackets with the corresponding argument.
- **Syntax:** `S.format(item0, item1, item2, ..., itemk)`
 - S: string consisting of substrings and formatting instructions for each item in the form of `{index:format-specifier}`.
 - index refers to the item and format-specifier specifies how the item is formatted. (Optional)

Format output

These are indicated by a pair of curly braces {}

- Empty braces
`'The {} in the {}'.format('car', 'room')` returns 'The car in the room'
- Braces with index
`'{2} color {1}, {0} {3}'.format('dark', 'brown', 'yellow', 'red')` returns 'yellow color brown, dark red'
- Braces with keywords
- braces contain a keyword and parameter of the form <keyword>=<value>
`'{c} color {b}, {a} {d}'.format(a='dark', b='brown', c='yellow', d='red')` returns 'yellow color brown, dark red'

Format output

```
count = 5
```

```
amount = 45.56
```

```
print('count is {0} and amount is  
{1:9.6f}'.format(count, amount))
```

Format specifiers

Conversion	Meaning
d	Signed integer decimal.
i	Signed integer decimal.
o	Unsigned octal.
x	Unsigned hexadecimal (lowercase).
X	Unsigned hexadecimal (uppercase).
e	Floating point exponential format (lowercase).
E	Floating point exponential format (uppercase).
f	Floating point decimal format.
F	Floating point decimal format.
g	Same as "e" if exponent is greater than -4 or less than precision, "f" otherwise.
G	Same as "E" if exponent is greater than -4 or less than precision, "F" otherwise.
c	Single character (accepts integer or single character string).
r	String (converts any python object using repr()).
s	String (converts any python object using str()).
%	No argument is converted, results in a "%" character in the result.

https://www.python-course.eu/python3_formatted_output.php

Format specifiers

- Justification codes
 - < left justifies
 - > right justifies
 - ^centers
- Filling characters
 - Character after : pads with that character
 - `\{ : * ^ 9 \} ' . format ( 3 )` returns `'*****3*****'`
 - + before the field width forces a preceding sign
- Character functions
 - `ord` - Syntax: `ord(< char >)`
 - `chr` - Syntax: `chr(< int >)`

Format specifiers

- single quote \`'`
- double quote \`"`
- backslash \`\`
- alert (bell) \`\a`
- backspace \`\b`
- formfeed \`\f`
- newline \`\n`
- return \`\r`
- tab \`\t`
- vertical tab \`\v`
- <https://realpython.com/python-input-output/>

Format output

- F-string is a string literal that is prefixed with `f` or `F`. These strings may contain replacement fields (delimited by curly braces {} – *fill out the braces*). F-string is evaluated at run time.

Format strings (f-strings)

<https://www.pythoncheatsheet.org/cheatsheet/string-formatting>

Number	Format	Output	description
3.1415926	{:.2f}	3.14	Format float 2 decimal places
3.1415926	{:+.2f}	+3.14	Format float 2 decimal places with sign
-1	{:+.2f}	-1.00	Format float 2 decimal places with sign
2.71828	{:.0f}	3	Format float with no decimal places
4	{:0>2d}	04	Pad number with zeros (left padding, width 2)
4	{:x<4d}	4xxx	Pad number with x's (right padding, width 4)
10	{:x<4d}	10xx	Pad number with x's (right padding, width 4)
1000000	{:,}	1,000,000	Number format with comma separator
0.35	{:.2%}	35.00%	Format percentage
1000000000	{:.2e}	1.00e+09	Exponent notation
11	{:11d}	11	Right-aligned (default, width 10)
11	{:<11d}	11	Left-aligned (width 10)
11	{:^11d}	11	Center aligned (width 10)

Command line arguments

- All of the command line parameters live inside of `sys.argv`, so `import sys` is needed.
- `sys.argv` is a list in Python, which contains the command-line arguments passed to the script.
- The name of the program is always the first item (`argv[0]`)
- The elements of `argv` are strings
- *File: command_line_io.py*
- <https://realpython.com/python-command-line-arguments/>

Command line arguments

File: command_line_io.py

```
import sys
print('This is the name of the
script: ', sys.argv[0])
print('Number of arguments: ',
len(sys.argv))
print('The arguments are: ',
sys.argv)

for arg in sys.argv:
    print(type(arg), arg)
```

Command line

```
(base) PS C:\temp\Develop\PythonDev>
python .\command_line_io.py help me
This is the name of the script:
.\command_line_io.py
Number of arguments:  3
The arguments are:
['.\command_line_io.py', 'help',
'me']
<class 'str'> .\command_line_io.py
<class 'str'> help
<class 'str'> me
(base) PS C:\temp\Develop\PythonDev>
```

Specific information on file io

- <https://realpython.com/read-write-files-python/>
- https://python.camden.rutgers.edu/python_resources/python3_book/files.html
- <http://www.pythonforbeginners.com/files/reading-and-writing-files-in-python>
- <https://www.datacamp.com/community/tutorials/reading-writing-files-python>

File IO

- See: <https://realpython.com/read-write-files-python/>
- File IO is handled natively in the language.
- Write/Read text files in Python is straightforward, it involves these steps:
 - Opening the file and associating it with a file handle.
 - Using the file handle: read from or write to a file
 - Closing the file handle to commit to a disk file. (Do not forget!)

Available access modes

Mode	Name	File Status	Starts At	Position of Writes
'r'	Read Only	File must exist	Beginning	Writing not allowed
'w'	Write Only	File is created OR EMPTIED	Beginning (= end)	Writes (after first) may be positioned with seek
'a'	Append Only	File is created or exists	End	Writes ALWAYS move to the end of the file
'r+'	Read and Write	File must exist	Beginning	Writes (after first) may be positioned with seek
'w+'	Write and Read	File is created OR EMPTIED	Beginning (= end)	Writes (after first) may be positioned with seek
'a+'	Append and Read	File is created or exists	Beginning	Writes ALWAYS move to the end of the file

Write to a file

- `open()` : get a file object handle
 - File objects contain methods and attributes that can be used to collect information about the file.
 - Syntax: `file_object = open('filename', 'mode', 'encoding')`

- A simple example

```
outfile = open("testwrite.txt", "w")
outfile.write("Line number 1\n")
outfile.close()
```

- *File: file_io_write_1.py*

Write to a file

- **write()**
 - used to write a single string to a file.
 - The **write()** function only works with **string** arguments. If you want to write the results of a numerical variable to an output file, you need to convert the number into a string with **str()**
 - It does not add any newline characters unless you explicitly include them in the string.
- **writelines()** expects an iterable as argument (an iterable object can be a tuple, a list, a string, or an iterator in the most general sense). Each item contained in the iterator is expected to be a string.
 - It does not add newline characters between the strings; you need to include them in the strings if needed.


Write to a file

File: file_io_write_1.py

```
fp = open('testfile-write.txt','w')
fp.write('Hello World')
fp.write('Hello World \n')
# write the list
# note, here print is used
# It inserts spaces between arguments and
# appends the line terminator.
l = [0, 1, 2, 3]
print(l, file=fp)
for i in l:
    print(i, file=fp)
for i in l:
    print(i, end=' ', file=fp)
# write the individual elements
for i in l:
    fp.write(str(i))
# write the individual elements with a
# separator
for i in l:
    fp.write(str(i) + '/')
fp.write('\n')
fp.close()
```

testfile-write.txt

```
Hello WorldHello World
[0, 1, 2, 3]
0
1
2
3
0 1 2 3 01230/1/2/3/
```



Reading a file

- Text files are sequences of lines of text, use the **for** loop to iterate through the file object.
- A line of a file is defined to be a sequence of characters up to and including the newline character (`\n`).
- Pattern for processing each line of a text file:

```
for line in myFile:  
    statement1  
    statement2  
    ...
```

- *File: `file_io_forLoop.py`*

Reading a file

File: file_io_forLoop.py

```
txtfile =  
open("test_text.txt", "r")  
  
for aline in txtfile:  
    values = aline.split()  
    if len(values) > 10:  
        print('some text',  
values[0], values[1], ' and  
also ', values[10] )  
  
txtfile.close()
```

result

```
some text Lorem ipsum  and also  quam  
some text Mauris venenatis  and also  Cras  
some text Nunc dictum,  and also  vel  
some text Aenean accumsan  and also  varius  
some text Curabitur commodo  and also  id  
some text In faucibus  and also  diam.  
some text Orci varius  and also  ridiculus  
some text Curabitur interdum,  and also  nulla,  
some text Aliquam vitae  and also  nibh  
some text Phasellus posuere  and also  mollis  
some text Sed malesuada  and also  sodales  
some text Nulla condimentum  and also  vel  
some text Cras et  and also  nisi  
some text Vestibulum vel  and also  ut  
some text Suspendisse id  and also  tincidunt  
some text Nulla sed  and also  urna  
some text Donec tristique  and also  Donec
```

Reading a file

Read from a file handle that has been connected to a file that is open for reading.

- `file.readline()` : read a file line by line
 - The `readline()` function reads a single line from the file and advances the line pointer by one line.
 - It is possible to call `readline()` over and over until the whole file is read in, one line at a time.
 - Usually the `readline()` function is used when you only want to read a single line from the file, i.e. header line.
 - If there is an argument, it indicates the number of bytes to be read.
 - *File: file_io_readline.py*
- `file.readlines()` : return every line in the file, properly separated
 - Reads all the lines of file into a list, with each element string consisting of the line (with `\n`).
 - Careful with large files.
 - *File: file_io_readlines.py*
- `file.read()` : reads in the entire contents of the file as a single string, used when parsing JSON files, HTML or XML files
- `file.read(n)` : reads up to n chars as a single string

Reading a file

- Read all characters in the file

```
fp = open ("filename", "r")  
fp.read()
```

Specify number of bytes

```
fp = open ("filename", "r")  
fp.read(n)
```

- Python reads only strings. You must parse the line or lines yourself.
- Useful functions
 - `string.strip(s)`
 - `string.split(s)`
- *File: file_io_3.py*
- *File: file_io_readline.py*
- *File: file_io_readlines.py*

File IO

- The Pythonic way:

```
with open('file_path', 'w') as file:  
    file.write('hello world !')
```

- The `with` statement automatically takes care of closing the file once it leaves the `with` block, even in cases of error.
 - no need to call `file.close()` when using `with` statement.
 - `with` statement itself ensures proper acquisition and release of resources.

I/O and data formats

- <https://github.com/gjbex/training-material/tree/master/Python/DataFormats>

Libraries & data formats

- Problem: Not portable code, data type size? Encoding? little /big endian?
- Use the *batteries* that are included!
- Standard library (Python 3.x)
 - Comma separated value files: `csv`
 - Semi-structured data: `json`, `htmllib`, `sgmlib`, `xml`
- Non-standard libraries
 - Images: `scikit-image`
 - `pandas`
 - Bioinformatics: `Biopython`
- <https://github.com/gjbex/training-material/tree/master/Python>

Reading and writing csv

- <https://realpython.com/python-csv/>
- <https://www.alexkras.com/how-to-read-csv-file-in-python/>
- Structure of a csv file
 - column 1 name, column 2 name, ...
 - first row data 1, first row data 2, ...
 - second row data 1, second row data 2, ...
 - ...
- **csv library** provides functionality to both read from and write to csv files.

Reading csv

- Steps
 - Open the file
 - Create a CSV reader
 - Skip first line (header)
 - For every line (row) in the file, do something
- *File: file_read_csv_list.py*

Writing csv

- **writer()**
 - function from csv module returns a writer object that converts data into a delimited string and stores in a file object. The function needs a file object with write permission as a parameter.
 - Every row written in the file issues a newline character. To prevent additional space between lines, `newline` parameter is set to "".
- The writer class has following methods
 - **writerow()**
 - writes a single row to a CSV file.
 - It takes an iterable (like a list or tuple) as an argument, where each element represents a column in the CSV row.
 - **writerows()**
 - writes multiple rows to a CSV file.
 - It takes an iterable of iterables (like a list of lists or a list of tuples) as an argument, where each inner iterable represents a row.
- <https://www.tutorialspoint.com/reading-and-writing-csv-file-using-python>
- *File: file_write_csv.py*