SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : SikaWall® 603 Acrylic

Product code : 100000031132

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

 Telephone
 : +60 6799 1762

 Telefax
 : +60 6799 1980

 E-mail address
 : EHS@my.sika.com

Emergency telephone num: :

ber

SECTION 2: Hazards identification

Classification of the hazardous chemical

Hazardous to the aquatic : Category 3

environment - chronic hazard

Label elements

Hazard pictograms : None Signal word : None

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy	64742-52-5	0 -< 1
naphthenic; Baseoil — unspecified		
diuron (ISO)	330-54-1	>= 0.025 -< 0.25

SikaWall® 603 Acrylic



Date of last issue: 05.03.2020 Version **Revision Date:** SDS Number: 100000031132 Date of first issue: 05.03.2020 14.03.2022 1.1

carbendazim (ISO)	10605-21-7	>= 0.0025 -< 0.025
2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1	>= 0.0025 -< 0.025
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-	55965-84-9	>= 0.0003 -< 0.0025
isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))		

SECTION 4: First aid measures

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Flush eyes with water as a precaution. In case of eye contact

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Treat symptomatically. Notes to physician

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Hazardous combustion prod- : No hazardous combustion products are known

ucts

Special protective equipment and precautions for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Specific extinguishing meth- : Standard procedure for chemical fires.

ods

SECTION 6: Accidental release measures

SikaWall® 603 Acrylic



Date of last issue: 05.03.2020 Version Revision Date: SDS Number: 100000031132 Date of first issue: 05.03.2020 1.1 14.03.2022

tive equipment and emer-

gency procedures

Personal precautions, protec- : For personal protection see section 8.

Environmental precautions No special environmental precautions required.

Methods and materials for containment and cleaning up Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

Materials to avoid No special restrictions on storage with other products.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified	64742-52-5	TWA (Mist)	5 mg/m3	MY PEL
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
diuron (ISO)	330-54-1	TWA	10 mg/m3	MY PEL

Individual protection measures, such as personal protective equipment

Eye/face protection Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

SECTION 9: Physical and chemical properties

Appearance : Aqueous solution

Colour : white

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing :

point

Boiling point/boiling range

No data available

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 23 hPa

Relative vapour density : No data available

SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

Density : 1.72 g/cm3

No data available

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic : IC50 (Pseudokirchneriella subcapitata (green algae)): > 100

plants mg/l

Exposure time: 48 h

diuron (ISO):

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic : 10

SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

toxicity)

carbendazim (ISO):

M-Factor (Acute aquatic tox- : 10

icitv)

M-Factor (Chronic aquatic : 10

toxicity)

2-octyl-2H-isothiazole-3-one (OIT):M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal information

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

SECTION 14: Transport information

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health)

Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

ACGIH / TWA : 8-hour, time-weighted average

MY PEL / TWA : Eight-hour time-weighted average airborne concentration
ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

SikaWall® 603 Acrylic



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05.03.2020

 1.1
 14.03.2022
 100000031132
 Date of first issue: 05.03.2020

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN