



NgStyle



NgStyle

The NgStyle directive lets you set a given DOM elements style properties.

```
<div [ngStyle]="{'background-color':'green'}"></div>
```

NgStyle is specially useful when the value is dynamic

```
<div [ngStyle]="{'background-color':person.country === 'UK' ? 'green' : 'red' }"></div>
```



Alternative syntax

Individual style properties can be set using the `[style.<property>]` syntax. In this example we can see that `ngStyle` can also be mixed with other directives.

```
<ul *ngFor="let person of people">
  <li [ngStyle]="{'font-size.px':24}"
      [style.color]="getColor(person.country)">{{ person.name }} ({{ person.country }})
  </li>
</ul>
```



Example

```
<h2>Hello pokedex</h2>
<h2 [ngStyle]='{\'color\':\'green\'}">Hello in green</h2>
<h2 [ngStyle]='{\'color\': bgColor }">Hello in another color</h2>
<h3 [ngStyle]='{\'background-color\': state ? \'red\' : \'blue\', \'color\': \'white\'}">Hello in another color</h3>
<div [ngStyle]='{\'font-size.px\': getSize()}'"> Tamaño cambia </div>
<p [style.color]="bgColor" >Lorem ipsum dolor sit amet, consectetur adipisicing elit. Eveniet, nemo unde, c
<button (click)="state = !state">Click me</button>
```