

Sobel Edge Detection Filter

1 Overview

1.1 Location `$<APPSDKSamplesInstallPath>\samples\opencl\cl\`

1.2 How to Run See the *Getting Started* guide for how to build samples. You first must compile the sample.

Use the command line to change to the directory where the executable is located. The default executables are placed in `$<APPSDKSamplesInstallPath>\samples\opencl\bin\x86` for 32-bit builds and `$<APPSDKSamplesInstallPath>\samples\opencl\bin\x86_64` for 64-bit builds.

Type the following command(s).

1. `SobelFilter`
This applies Sobel edge detection filter on input image.
2. `SobelFilter -h`
This prints the help message.

1.3 Command Line Options Table 1 lists, and briefly describes, the command line options.

Table 1 Command Line Options

Short Form	Long Form	Description
-h	--help	Shows all command options and their respective meaning.
	--device	Devices on which the program is to be run. Acceptable values are <code>cpu</code> or <code>gpu</code> .
-q	--quiet	Quiet mode. Suppresses all text output.
-e	--verify	Verify results against reference implementation.
-t	--timing	Print timing.
	--dump	Dump binary image for all devices.
	--load	Load binary image and execute on device.
	--flags	Specify compiler flags to build the kernel.
-p	--platformId	Select platformId to be used (0 to N-1, where N is the number of available platforms).
-d	--deviceId	Select deviceId to be used (0 to N-1, where N is the number of available devices).
-v	--version	AMD APP SDK version string.
-i	--iterations	Number of iterations for kernel execution.

2 Introduction

The Sobel operator is used in image processing, particularly within edge detection algorithms. Technically, it is a discrete differentiation operator, computing an approximation of the gradient of the image intensity function. The Sobel operator is based on convolving the image with a small, separable, and integer-valued filter in both horizontal and vertical directions; thus, it is relatively inexpensive in terms of computations.

Sobel filtering is a three-step process. Two 3×3 filters (often called kernels) are applied separately and independently on every pixel. Figure 1 shows the weights these kernels apply to pixels in the 3×3 region.

-1	0	+1
-2	0	+2
-1	0	+1

+1	+2	+1
0	0	0
-1	-2	-1

Figure 1 Weight Application by Kernels

The idea behind these two filters is to approximate the derivatives in x and y, respectively. The results of these two filters are Dx and Dy.

The final step approximates the gradient magnitude based on the partial derivatives (Dx and Dy) from the previous steps. The gradient magnitude, which is the result of the Sobel Filter S, is:

$$S = \sqrt{Dx^2 + Dy^2}$$

3 Implementation Details

The input buffer is stored in constant buffer to cache neighboring pixel reads. Each work item calculates the Dx and Dy of a pixel by applying 3x3 filters on nine pixels including the pixel itself. The final pixel value is written by calculating the gradient magnitude of the partial derivatives.

4 Recommended Input Option Settings

For best performance, use large images, such as 2400 x1600.

5 Bibliography

1. en.wikipedia.org/wiki/Sobel_operator

Contact

Advanced Micro Devices, Inc.
One AMD Place
P.O. Box 3453
Sunnyvale, CA, 94088-3453
Phone: +1.408.749.4000

For AMD Accelerated Parallel Processing:
URL: developer.amd.com/appsdk
Developing: developer.amd.com/
Support: developer.amd.com/appsdksupport
Forum: developer.amd.com/openglforum



The contents of this document are provided in connection with Advanced Micro Devices, Inc. ("AMD") products. AMD makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. The information contained herein may be of a preliminary or advance nature and is subject to change without notice. No license, whether express, implied, arising by estoppel or otherwise, to any intellectual property rights is granted by this publication. Except as set forth in AMD's Standard Terms and Conditions of Sale, AMD assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

AMD's products are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or in any other application in which the failure of AMD's product could create a situation where personal injury, death, or severe property or environmental damage may occur. AMD reserves the right to discontinue or make changes to its products at any time without notice.

Copyright and Trademarks

© 2013 Advanced Micro Devices, Inc. All rights reserved. AMD, the AMD Arrow logo, ATI, the ATI logo, Radeon, FireStream, and combinations thereof are trademarks of Advanced Micro Devices, Inc. OpenCL and the OpenCL logo are trademarks of Apple Inc. used by permission by Khronos. Other names are for informational purposes only and may be trademarks of their respective owners.