



Bias/Variance Tradeoff

Rishabh Iyer

University of Texas at Dallas

Acknowledgement: Nick Rouzzi, Vibhav Gogate, David Sontag, Killian Weinberger, Aarti Singh





- PAC learning
- Bias/variance tradeoff
 - small hypothesis spaces (not enough flexibility) can have high bias
 - rich hypothesis spaces (too much flexibility) can have high variance
- Today: more on this phenomenon and how to get around it

High Variance or Overfitting



If we allow very complicated predictors, we could overfit the training data.


Examples: Regression (Polynomial of order k – degree up to $k-1$)



Effect of Model Complexity



If we allow very complicated predictors, we could overfit the training data.



- Bias
 - Measures the accuracy or quality of the algorithm
 - High bias means a poor match
- Variance
 - Measures the precision or specificity of the match
 - High variance means a weak match
- We would like to minimize each of these
- Unfortunately, we can't do this independently, there is a trade-off

- Dataset: $D = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_n, y_n)\}$
- True function is $y = f(x) + \epsilon$
 - Where noise, ϵ , is normally distributed with zero mean and standard deviation σ
- Given a set of training examples, $(x^{(1)}, y^{(1)}), \dots, (x^{(n)}, y^{(n)})$, we fit a hypothesis $g(x) = w^T x + b$ to the data to minimize the squared error

$$\sum_i [y^{(i)} - g(x^{(i)})]^2$$

Some Terminology



Expected Label (given $\mathbf{x} \in \mathbb{R}^d$):

$$\bar{y}(\mathbf{x}) = E_{y|\mathbf{x}}[Y] = \int_y y \Pr(y|\mathbf{x}) \partial y.$$

Expected Test Error (given h_D):

$$E_{(\mathbf{x}, y) \sim P} \left[(h_D(\mathbf{x}) - y)^2 \right] = \int_x \int_y (h_D(\mathbf{x}) - y)^2 \Pr(\mathbf{x}, y) \partial y \partial \mathbf{x}.$$

Expected Classifier (given \mathcal{A}):

$$\bar{h} = E_{D \sim P^n} [h_D] = \int h_D \Pr(D) \partial D$$

Expected Test Error (given \mathcal{A}):

$$E_{\substack{(\mathbf{x}, y) \sim P \\ D \sim P^n}} \left[(h_D(\mathbf{x}) - y)^2 \right] = \int_D \int_{\mathbf{x}} \int_y (h_D(\mathbf{x}) - y)^2 P(\mathbf{x}, y) P(D) \partial \mathbf{x} \partial y \partial D$$

- Variance of a random variable, Z

$$\begin{aligned} \text{Var}(Z) &= E[(Z - E[Z])^2] \\ &= E[Z^2 - 2ZE[Z] + E[Z]^2] \\ &= E[Z^2] - E[Z]^2 \end{aligned}$$

- Properties of $\text{Var}(Z)$

$$\text{Var}(aZ) = E[a^2Z^2] - E[aZ]^2 = a^2\text{Var}(Z)$$

$$\begin{aligned} E_{\mathbf{x},y,D} \left[[h_D(\mathbf{x}) - y]^2 \right] &= E_{\mathbf{x},y,D} \left[[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) + (\bar{h}(\mathbf{x}) - y)]^2 \right] \\ &= E_{\mathbf{x},D} [(\bar{h}_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + 2 E_{\mathbf{x},y,D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) (\bar{h}(\mathbf{x}) - y)] \\ &\quad + E_{\mathbf{x},y} [(\bar{h}(\mathbf{x}) - y)^2] \end{aligned}$$

$$\begin{aligned} E_{\mathbf{x},y,D} \left[[h_D(\mathbf{x}) - y]^2 \right] &= E_{\mathbf{x},y,D} \left[[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) + (\bar{h}(\mathbf{x}) - y)]^2 \right] \\ &= E_{\mathbf{x},D} [(\bar{h}_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2] + 2 E_{\mathbf{x},y,D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) (\bar{h}(\mathbf{x}) - y)] \\ &\quad + E_{\mathbf{x},y} [(\bar{h}(\mathbf{x}) - y)^2] \end{aligned}$$

The middle term of the above equation is 0 as we show below

$$\begin{aligned} E_{\mathbf{x},y,D} [(h_D(\mathbf{x}) - \bar{h}(\mathbf{x})) (\bar{h}(\mathbf{x}) - y)] &= E_{\mathbf{x},y} [E_D [h_D(\mathbf{x}) - \bar{h}(\mathbf{x})] (\bar{h}(\mathbf{x}) - y)] \\ &= E_{\mathbf{x},y} [(E_D [h_D(\mathbf{x})] - \bar{h}(\mathbf{x})) (\bar{h}(\mathbf{x}) - y)] \\ &= E_{\mathbf{x},y} [(\bar{h}(\mathbf{x}) - \bar{h}(\mathbf{x})) (\bar{h}(\mathbf{x}) - y)] \\ &= E_{\mathbf{x},y} [0] \\ &= 0 \end{aligned}$$

Bias-Variance-Noise Decomposition



Returning to the earlier expression, we're left with the variance and another term

$$E_{\mathbf{x},y,D} \left[(h_D(\mathbf{x}) - y)^2 \right] = \underbrace{E_{\mathbf{x},D} \left[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2 \right]}_{\text{Variance}} + E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - y)^2 \right]$$

Bias-Variance-Noise Decomposition



Returning to the earlier expression, we're left with the variance and another term

$$E_{\mathbf{x},y,D} \left[(h_D(\mathbf{x}) - y)^2 \right] = \underbrace{E_{\mathbf{x},D} \left[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2 \right]}_{\text{Variance}} + E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - y)^2 \right]$$

We can break down the second term in the above equation as follows:

$$\begin{aligned} E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - y)^2 \right] &= E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) + (\bar{y}(\mathbf{x}) - y)^2 \right] \\ &= \underbrace{E_{\mathbf{x},y} \left[(\bar{y}(\mathbf{x}) - y)^2 \right]}_{\text{Noise}} + \underbrace{E_{\mathbf{x}} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x}))^2 \right]}_{\text{Bias}^2} + 2 E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) (\bar{y}(\mathbf{x}) - y) \right] \end{aligned}$$

Bias-Variance-Noise Decomposition



Returning to the earlier expression, we're left with the variance and another term

$$E_{\mathbf{x},y,D} \left[(h_D(\mathbf{x}) - y)^2 \right] = \underbrace{E_{\mathbf{x},D} \left[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2 \right]}_{\text{Variance}} + E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - y)^2 \right]$$

We can break down the second term in the above equation as follows:

$$\begin{aligned} E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - y)^2 \right] &= E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) + (\bar{y}(\mathbf{x}) - y)^2 \right] \\ &= \underbrace{E_{\mathbf{x},y} \left[(\bar{y}(\mathbf{x}) - y)^2 \right]}_{\text{Noise}} + \underbrace{E_{\mathbf{x}} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x}))^2 \right]}_{\text{Bias}^2} + 2 E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) (\bar{y}(\mathbf{x}) - y) \right] \end{aligned}$$

The third term in the equation above is 0

Bias-Variance-Noise Decomposition



The third term in the equation above is 0, as we show below

$$\begin{aligned} E_{\mathbf{x},y} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) (\bar{y}(\mathbf{x}) - y) \right] &= E_{\mathbf{x}} \left[E_{y|\mathbf{x}} [\bar{y}(\mathbf{x}) - y] (\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) \right] \\ &= E_{\mathbf{x}} \left[E_{y|\mathbf{x}} [\bar{y}(\mathbf{x}) - y] (\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) \right] \\ &= E_{\mathbf{x}} \left[(\bar{y}(\mathbf{x}) - E_{y|\mathbf{x}} [y]) (\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) \right] \\ &= E_{\mathbf{x}} \left[(\bar{y}(\mathbf{x}) - \bar{y}(\mathbf{x})) (\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x})) \right] \\ &= E_{\mathbf{x}} [0] \\ &= 0 \end{aligned}$$

This gives us the decomposition of expected test error as follows

$$\underbrace{E_{\mathbf{x},y,D} \left[(h_D(\mathbf{x}) - y)^2 \right]}_{\text{Expected Test Error}} = \underbrace{E_{\mathbf{x},D} \left[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2 \right]}_{\text{Variance}} + \underbrace{E_{\mathbf{x},y} \left[(\bar{y}(\mathbf{x}) - y)^2 \right]}_{\text{Noise}} + \underbrace{E_{\mathbf{x}} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x}))^2 \right]}_{\text{Bias}^2}$$

Bias, Variance, and Noise



This gives us the decomposition of expected test error as follows

$$\underbrace{E_{\mathbf{x},y,D} \left[(h_D(\mathbf{x}) - y)^2 \right]}_{\text{Expected Test Error}} = \underbrace{E_{\mathbf{x},D} \left[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2 \right]}_{\text{Variance}} + \underbrace{E_{\mathbf{x},y} \left[(\bar{y}(\mathbf{x}) - y)^2 \right]}_{\text{Noise}} \\ + \underbrace{E_{\mathbf{x}} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x}))^2 \right]}_{\text{Bias}^2}$$

Variance: Captures how much your classifier changes if you train on a different training set. How "over-specialized" is your classifier to a particular training set (overfitting)? If we have the best possible model for our training data, how far off are we from the average classifier?

Bias: What is the inherent error that you obtain from your classifier even with infinite training data? This is due to your classifier being "biased" to a particular kind of solution (e.g. linear classifier). In other words, bias is inherent to your model.

Noise: How big is the data-intrinsic noise? This error measures ambiguity due to your data distribution and feature representation. You can never beat this, it is an aspect of the data.


Bias, Variance, and Noise



$$\underbrace{E_{\mathbf{x},y,D} \left[(h_D(\mathbf{x}) - y)^2 \right]}_{\text{Expected Test Error}} = \underbrace{E_{\mathbf{x},D} \left[(h_D(\mathbf{x}) - \bar{h}(\mathbf{x}))^2 \right]}_{\text{Variance}}$$

$$+ \underbrace{E_{\mathbf{x},y} \left[(\bar{y}(\mathbf{x}) - y)^2 \right]}_{\text{Noise}}$$


$$+ \underbrace{E_{\mathbf{x}} \left[(\bar{h}(\mathbf{x}) - \bar{y}(\mathbf{x}))^2 \right]}_{\text{Bias}^2}$$




2-D Example




50 fits (20 examples each)




Bias



Variance




Noise




Bias-Variance Tradeoff



Large bias, Small variance – poor approximation but robust/stable



Small bias, Large variance – good approximation but unstable



- Low bias
 - ?
- High bias
 - ?

- Low bias
 - Linear regression applied to linear data
 - 2nd degree polynomial applied to quadratic data
- High bias
 - Constant function applied to non-constant data
 - Linear regression applied to highly non-linear data

- Low variance
 - ?
- High variance
 - ?


- Low variance
 - Constant function
 - Model independent of training data
- High variance
 - High degree polynomial

Bias/Variance Tradeoff



- $(\text{bias}^2 + \text{variance})$ is what counts for prediction
- As we saw in PAC learning, we often have
 - Low bias \Rightarrow high variance
 - Low variance \Rightarrow high bias
 - How can we deal with this in practice?

Detecting High Variance/Bias



Regime 1 (High Variance)

In the first regime, the cause of the poor performance is high variance.

Symptoms:

1. Training error is much lower than test error
2. Training error is lower than ϵ
3. Test error is above ϵ

Remedies:

- Add more training data
- Reduce model complexity -- complex models are prone to high variance
- Bagging (will be covered later in the course)

Regime 2 (High Bias)

Unlike the first regime, the second regime indicates high bias: the model being used is not robust enough to produce an accurate prediction.

Symptoms:

1. Training error is higher than ϵ

Remedies:

- Use more complex model (e.g. kernelize, use non-linear models)
- Add features
- Boosting (will be covered later in the course)

How to select the right model?



Model Spaces with increasing complexity:

- Nearest-Neighbor classifiers with varying neighborhood sizes $k = 1, 2, 3, \dots$
Small neighborhood \Rightarrow Higher complexity
- Decision Trees with depth k or with k leaves
Higher depth/ More # leaves \Rightarrow Higher complexity
- Regression with polynomials of order $k = 0, 1, 2, \dots$
Higher degree \Rightarrow Higher complexity
- Kernel Regression with bandwidth h
Small bandwidth \Rightarrow Higher complexity

How can we select the right complexity model ?

Held out Validation Set



We would like to pick the model that has smallest generalization error.

Can judge generalization error by using an independent sample of data.

Hold - out procedure:

n data points available $D \equiv \{X_i, Y_i\}_{i=1}^n$

1) Split into two sets: Training dataset Validation dataset **NOT test Data !!**
 $D_T = \{X_i, Y_i\}_{i=1}^m$ $D_V = \{X_i, Y_i\}_{i=m+1}^n$

2) Use D_T for training a predictor from each model class:

$$\hat{f}_\lambda = \arg \min_{f \in \mathcal{F}_\lambda} \hat{R}_T(f)$$

 Evaluated on training dataset D_T

3) Use D_v to select the model class which has smallest empirical error on D_v

$$\hat{\lambda} = \arg \min_{\lambda \in \Lambda} \hat{R}_V(\hat{f}_\lambda)$$

└─ Evaluated on validation dataset D_v

4) Hold-out predictor

$$\hat{f} = \hat{f}_{\hat{\lambda}}$$

Intuition: Small error on one set of data will not imply small error on a randomly sub-sampled second set of data

Ensures method is “stable”

Cross Validation



K-fold cross-validation

Create K-fold partition of the dataset.

Form K hold-out predictors, each time using one partition as validation and rest K-1 as training datasets.

Final predictor is average/majority vote over the K hold-out estimates.

