Supplementary: Errata, v7 (Zenodo 23291052) to v8

Authors: Smart, Morgan Elliott; Smart, Jasper Keiron; Ara (Grok Bot AI collaborator).
Supplement to SCG-HMH: A Closed Derivative Chain for a Regenerative Nitrogen Plasma-Ring Generator, version 8 (29 October 2026; an erratum of v7, Zenodo 10.5281/zenodo.23291052; licence CC BY 4.0). Every number here is taken from the paper; nothing is new.

Version 8 keeps the design of version 7. It corrects how version 7 explained and booked the cold end, and it adds Section 6.6, the Earth cold side as a regenerative nitrogen chain.

#	v7 said	v8 corrects it to	Why
1	The whole ~116 MW latent heat of the returned stream leaves the boundary at 77 K (v7 Eq. 8a; §6.5)	The latent heat is regenerated: cold vapour recompression returns 61.1 % of it to the start of the expansion loop; 298.47 MW per module is recirculated inside the loop	The design records describe regeneration and return to the preheat stage
2	Mass boundary not stated	The only mass boundary is the 0.4 % vent and its matching top-up (2.3293 kg/s); the vent leaves at the end of the loop before the J–T HX	Closes the mass book
3	Outside heat booked as a cost	The 180 °C waste heat is the external input and free fuel; the books close on the booked point's own waste heat (457.66 MW at 5 T, SF 2); the larger totals are the operational peak, not a requirement	Waste heat is a site limit, not a cost
4	Cold-side rejection left open on Earth	A heat-led LN_2 generator lifts the 46.93 MW residual to the 300 K ambient; first-law residual zero, entropy generation positive	Second law
5	Worked point 141.22 MW at 200,000 rpm read as the operating point	141.22 MW is kept as v7's worked ring (SF 1.07, above the published continuous envelope); the booked baseline on the published envelope is 99.55 MW at 5 T, 150,938 rpm, SF 2 (128.60 MW at SF 1.5)	Published rim-stress envelope of the 0.1 m sleeve
6	One COP	Two COP accounts throughout: COP_th = 0.2175 and COP_e = 124,437 per module at the booked baseline (0.8 kW electricity in, no electric pumps)	Both accounts are needed for an unpaid heat input
7	Electricity-in figures mixed	Three figures, three things: the 11.7 W strip, the 0.8 kW module budget (E_in), and the cluster-level AI Heat-Grid Oracle paid from output	Electrical input books (Section 6.6.23)
8	Author entry for Jasper	**Smart, Jasper Keiron** (full name Jasper Keiron Smart), corrected from the v7 author list at Morgan's request	Author-name correction

Not changed: σ_high = 14,000 S/m; P = 141.22 MW at v7's worked ring; Book 1 (12,043,354×); the Phase-1 gate (σ > 5 S/m, net > 50 W) and the 50.4 kW prediction at the gate conductivity.

Nothing here is an experimental result; the Phase-1 bench decides.