

Purcell Project Markdown

Dan Hudson and Xochitl Morgan

22/October/2020

Load phyloseq object

Phyloseq object was generated on the server using serverScript.R, following the running of this script it was downloaded to the local machine and used to make plots

```
# load data
ps0 <- readRDS("../PrimaryData/phyloObject.rds")

# read metadata
meta <- read.csv("../PrimaryData/purcell_meta.csv")

# add tree
tree <- read_tree("../PrimaryData/purcellFastTree_edit.tre")

# load metadata and tree into phyloseq object
meta <- sample_data(meta)
meta$Individual <- as.factor(meta$Individual)
row.names(meta) <- meta$Sample_name
ps <- merge_phyloseq(ps0, meta, tree)

# unedited phyloseq object
psOG <- ps

# Assign DNA sequences to refseq slot and replace with simple names to improve readability
dna <- Biostrings::DNASTringSet(taxa_names(ps))
names(dna) <- taxa_names(ps)
ps <- merge_phyloseq(ps, dna)
taxa_names(ps) <- paste0("ASV", seq(ntaxa(ps)))
ps

## phyloseq-class experiment-level object
## otu_table() OTU Table: [ 4872 taxa and 60 samples ]
## sample_data() Sample Data: [ 60 samples by 7 sample variables ]
## tax_table() Taxonomy Table: [ 4872 taxa by 6 taxonomic ranks ]
## phy_tree() Phylogenetic Tree: [ 4872 tips and 4870 internal nodes ]
## refseq() DNASTringSet: [ 4872 reference sequences ]
```

Custom Rarefaction Plot

Not run in this Markdown

```

# Data
psdata <- ps

# Loading required library and displaying core configuration
library('doParallel')
detectCores(all.tests = TRUE)

# Setting up and registering the cluster
cl <- makeCluster(detectCores(all.tests = TRUE)-1)
registerDoParallel(cl)

# Calculate alpha diversity
calculate_rarefaction_curves <- function(psdata, measures, depths, parallel = FALSE) {
  require('plyr') # ldply
  require('reshape2') # melt
  require('doParallel')

  # set parallel options if required
  if (parallel) {
    paropts <- list(.packages = c("phyloseq", "reshape2"))
  } else {
    paropts <- NULL
  }

  estimate_rarified_richness <- function(psdata, measures, depth) {
    if(max(sample_sums(psdata)) < depth) return()
    psdata <- prune_samples(sample_sums(psdata) >= depth, psdata)

    rarified_psdata <- rarefy_even_depth(psdata, depth, verbose = FALSE)

    alpha_diversity <- estimate_richness(rarified_psdata, measures = measures)

    # as.matrix forces the use of melt.array, which includes the Sample names (rownames)
    molten_alpha_diversity <- melt(as.matrix(alpha_diversity),
                                  varnames = c('Sample', 'Measure'),
                                  value.name = 'Alpha_diversity')

    molten_alpha_diversity
  }

  names(depths) <- depths # this enables automatic addition of the Depth to the output by ldply
  rarefaction_curve_data <- ldply(depths,
    estimate_rarified_richness,
    psdata = psdata,
    measures = measures,
    .id = 'Depth',
    .progress = ifelse(interactive() && ! parallel, 'text', 'none'),
    .parallel = parallel,
    .paropts = paropts)

  # convert Depth from factor to numeric
  rarefaction_curve_data$Depth <- as.numeric(levels(rarefaction_curve_data$Depth))[rarefaction_curve_data$Depth]

```

```

rarefaction_curve_data
}

rarefaction_curve_data <- calculate_rarefaction_curves(psdata, c('Observed'),
                                                    rep(c(1, 100, 1:150 * 1000),
                                                         each = 10))

summary(rarefaction_curve_data)
saveRDS(rarefaction_curve_data, file = "../PrimaryData/rare_object.rds")

# Data
psdata <- ps

# Load Rarefaction Curve Data Object
rarefaction_curve_data <- readRDS(file = "../PrimaryData/rare_object.rds")
summary(rarefaction_curve_data)

##      Depth      Sample      Measure      Alpha_diversity
## Min.      :      1   X10B      : 1520   Observed:77740   Min.      : 1.0
## 1st Qu.: 31000   X12B      : 1520                      1st Qu.:321.0
## Median : 63000   X12C      : 1520                      Median :403.0
## Mean    : 65150   X13A      : 1520                      Mean    :391.3
## 3rd Qu.: 97000   X13B      : 1520                      3rd Qu.:464.0
## Max.    :150000   X14A      : 1520                      Max.    :674.0
##                      (Other):68620

# Summarise alpha diversity
rarefaction_curve_data_summary <- ddply(rarefaction_curve_data,
                                       c('Depth', 'Sample', 'Measure'),
                                       summarise,
                                       Alpha_diversity_mean = mean(Alpha_diversity),
                                       Alpha_diversity_sd = sd(Alpha_diversity))

colnames(rarefaction_curve_data_summary) <- gsub("X","",
                                                colnames(rarefaction_curve_data_summary))
rarefaction_curve_data_summary$Sample <- gsub("X","", rarefaction_curve_data_summary$Sample)


# Add sample data
rarefaction_curve_data_summary_verbose <- merge(rarefaction_curve_data_summary,
                                              data.frame(sample_data(psdata)),
                                              by.x = 'Sample',
                                              by.y = 'row.names')

# Produce summary df of rarefaction data
df_mod <- summarySE(rarefaction_curve_data_summary_verbose,
                   measurevar = "Alpha_diversity_mean",
                   groupvars = c("Depth", "Sample_type"))
df_mod <- df_mod %>%
  subset(Depth == 1 | Depth == 1000 | Depth == 10000 | Depth == 20000 | Depth == 30000 | Depth == 40000)

ggplot(df_mod, aes(x = Depth,
                  y = Alpha_diversity_mean,
                  ymin = Alpha_diversity_mean - ci,
                  ymax = Alpha_diversity_mean + ci,
                  colour = Sample_type)) +
  geom_errorbar(size = 0.5, width = 2500, alpha = 0.6) +

```

```
geom_line(size = 0.8) +
labs(x = "Tested sequencing depth", y = "Observed Mean", color = "Sample Type")
```



```
ggsave("../Results/S1)Rarefaction_Curve.pdf", width = 11, height = 8)
```

Rarefy

```
# Rarefy to even sequencing depth, 90% of minimum sample depth, seed for randomness is 1
ps_rare <- rarefy_even_depth(ps, rngseed = 1,
                             sample.size = 0.9 * min(sample_sums(ps)),
                             replace = FALSE)
```

```
## `set.seed(1)` was used to initialize repeatable random subsampling.
```

```
## Please record this for your records so others can reproduce.
```

```
## Try `set.seed(1); .Random.seed` for the full vector
```

```
## ...
```

```
## 2430TUs were removed because they are no longer
```

```
## present in any sample after random subsampling
```

```
## ...
```

```
sample_sums(ps)
```

```
##      10A      10B      10C      11A      11B      11C      12A      12B      12C      13A      13B
```

```
## 97672 152224 136830 107226 92295 142349 63696 151049 153224 170086 154765
## 13C 14A 14B 14C 15A 15B 15C 16A 16B 16C 17A
## 146933 160605 171722 140943 175324 114245 168613 120816 131462 141789 153959
## 17B 17C 18A 18B 18C 19A 19B 19C 1A 1B 1C
## 127615 94965 160212 126836 159814 161407 153370 121330 165497 96844 113268
## 20A 20B 20C 2A 2B 2C 3A 3B 3C 4A 4B
## 195853 115506 127239 110007 118680 110327 146390 136636 106307 104581 125868
## 4C 5A 5B 5C 6A 6B 6C 7A 7B 7C 8A
## 131775 160742 121440 88650 140459 164106 92481 137767 138331 120381 140622
## 8B 8C 9A 9B 9C
## 97857 112182 84876 143122 108117
```

```
sample_sums(ps_rare)
```

```
## 10A 10B 10C 11A 11B 11C 12A 12B 12C 13A 13B 13C 14A
## 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326
## 14B 14C 15A 15B 15C 16A 16B 16C 17A 17B 17C 18A 18B
## 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326
## 18C 19A 19B 19C 1A 1B 1C 20A 20B 20C 2A 2B 2C
## 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326
## 3A 3B 3C 4A 4B 4C 5A 5B 5C 6A 6B 6C 7A
## 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326 57326
## 7B 7C 8A 8B 8C 9A 9B 9C
## 57326 57326 57326 57326 57326 57326 57326 57326
```

Alpha Diversity

```
# Calculate alpha diversity, using Richness and Shannon
alpha_summary <- estimate_richness(ps_rare, measures = c("Observed", "Shannon"))
shapiro.test(alpha_summary$Observed)
```

```
##
## Shapiro-Wilk normality test
##
## data: alpha_summary$Observed
## W = 0.99288, p-value = 0.9797
```

```
shapiro.test(alpha_summary$Shannon)
```

```
##
## Shapiro-Wilk normality test
##
## data: alpha_summary$Shannon
## W = 0.97844, p-value = 0.3662
```

```
# Blocking Test
r0 <- alpha_summary$Observed
rS <- alpha_summary$Shannon

f <- c("Clinician", "Self", "Stool") # treatment levels
k <- 3 # number of treatment levels
n <- 20 # number of control blocks

tm <- gl(k, 1, n*k, factor(f)) # matching treatment
```

```

blk <- gl(n, k, k*n) # blocking factor

av0 <- aov(r0 ~ tm + blk)
summary(av0)

##              Df Sum Sq Mean Sq F value    Pr(>F)
## tm              2  106186    53093   14.357 2.27e-05 ***
## blk             19  332244    17487    4.729 2.33e-05 ***
## Residuals      38  140525     3698
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

avS <- aov(rS ~ tm + blk)
summary(avS)

##              Df Sum Sq Mean Sq F value    Pr(>F)
## tm              2   0.849   0.4247    6.675 0.003278 **
## blk             19   4.871   0.2564    4.030 0.000126 ***
## Residuals      38   2.418   0.0636
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

# Test whether the observed number of OTUs differs significantly between samples
# p adjustment using Benjamini and Hochberg
pairwise.t.test(alpha_summary$Observed, sample_data(ps_rare)$Sample_type, p.adjust = "BH")

##
## Pairwise comparisons using t tests with pooled SD
##
## data:  alpha_summary$Observed and sample_data(ps_rare)$Sample_type
##
##              Rectal swab CT Rectal swab ST
## Rectal swab ST 0.1409          -
## Stool          0.0023          0.0646
##
## P value adjustment method: BH

pairwise.t.test(alpha_summary$Shannon, sample_data(ps_rare)$Sample_type, p.adjust = "BH")

##
## Pairwise comparisons using t tests with pooled SD
##
## data:  alpha_summary$Shannon and sample_data(ps_rare)$Sample_type
##
##              Rectal swab CT Rectal swab ST
## Rectal swab ST 0.19          -
## Stool          0.04          0.32
##
## P value adjustment method: BH

# Make adjusted p value dataframe
pObs <- pairwise.t.test(alpha_summary$Observed, sample_data(ps_rare)$Sample_type, p.adjust = "BH")
pSha <- pairwise.t.test(alpha_summary$Shannon, sample_data(ps_rare)$Sample_type, p.adjust = "BH")

variable <- c("Observed", "Observed", "Observed", "Shannon", "Shannon", "Shannon")
group1 <- c("Rectal swab CT", "Rectal swab ST", "Rectal swab CT",

```

```

      "Rectal swab CT", "Rectal swab ST", "Rectal swab CT")
group2 <- c("Stool", "Stool", "Rectal swab ST", "Stool", "Stool", "Rectal swab ST")
pVal <- c(round(pObs$p.value[2,1], 3), round(pObs$p.value[2,2], 3), round(pObs$p.value[1,1], 3),
      round(pSha$p.value[2,1], 3), round(pSha$p.value[2,2], 3), round(pSha$p.value[1,1], 3))
y.position <- c(730, 630, 690, 5.4, 5.1, 5.25)

pAdjusted <- bind_cols(variable, group1, group2, pVal, y.position)


## New names:
## * NA -> ...1
## * NA -> ...2
## * NA -> ...3
## * NA -> ...4
## * NA -> ...5

colnames(pAdjusted) <- c("variable", "group1", "group2", "p", "y.position")

# Plot Observed richness, Shannon, and Simpson diversity values
p <- plot_richness(ps_rare, x = "Sample_type",
      measures = c("Observed", "Shannon"))

# Add boxplot, individual data points, and linked lines using geom layers
p$layers <- p$layers[-1]
p + geom_boxplot() + geom_point() + xlab("Sample Type") +
  geom_line(aes(group = Individual), size = 0.3, linetype = "dashed") +
  theme(axis.text.x = element_text(angle = 315, hjust = 0),
      aspect.ratio = 1, legend.position = "none") +
  stat_pvalue_manual(pAdjusted) +
  stat_compare_means(method = "anova", label.y = 3)

```



```
ggsave("../Results/1)Alpha_Diversity.pdf", width = 7, height = 4.5)
```

Beta Diversity - Bray-Curtis

```
# Ordinate data using Non-metric multidimensional scaling (NMDS) on Bray-Curtis dissimilarity (distance  
bray_dist <- phyloseq::distance(ps_rare, method = "bray")  
ord.nm.ds.bray <- ordinate(ps_rare, "NMDS", "bray")
```


```
## Square root transformation  
## Wisconsin double standardization  
## Run 0 stress 0.1711869  
## Run 1 stress 0.1684076  
## ... New best solution  
## ... Procrustes: rmse 0.04403871  max resid 0.1986753  
## Run 2 stress 0.1712507  
## Run 3 stress 0.1712864  
## Run 4 stress 0.1712903  
## Run 5 stress 0.1684074  
## ... New best solution  
## ... Procrustes: rmse 0.0003485566  max resid 0.002061949  
## ... Similar to previous best  
## Run 6 stress 0.1684197  
## ... Procrustes: rmse 0.001465667  max resid 0.006957013  
## ... Similar to previous best  
## Run 7 stress 0.1711862  
## Run 8 stress 0.1712879  
## Run 9 stress 0.1711864  
## Run 10 stress 0.1684183  
## ... Procrustes: rmse 0.001257738  max resid 0.006842475  
## ... Similar to previous best  
## Run 11 stress 0.168407  
## ... New best solution  
## ... Procrustes: rmse 0.0001416034  max resid 0.0008423535  
## ... Similar to previous best  
## Run 12 stress 0.2132788  
## Run 13 stress 0.2033467  
## Run 14 stress 0.1684073  
## ... Procrustes: rmse 0.0001969173  max resid 0.001092735  
## ... Similar to previous best  
## Run 15 stress 0.2049835  
## Run 16 stress 0.1684107  
## ... Procrustes: rmse 0.0006893125  max resid 0.004159413  
## ... Similar to previous best  
## Run 17 stress 0.1684071  
## ... Procrustes: rmse 0.0001272377  max resid 0.0008562442  
## ... Similar to previous best  
## Run 18 stress 0.1712444  
## Run 19 stress 0.1684073  
## ... Procrustes: rmse 0.0002210374  max resid 0.00137581  
## ... Similar to previous best  
## Run 20 stress 0.1712802
```



```
## *** Solution reached
# Call newly created file to get the stress value of the plot
ord.nmms.bray

##
## Call:
## metaMDS(comm = veganifyOTU(physeq), distance = distance)
##
## global Multidimensional Scaling using monoMDS
##
## Data:      wisconsin(sqrt(veganifyOTU(physeq)))
## Distance: bray
##
## Dimensions: 2
## Stress:    0.168407
## Stress type 1, weak ties
## Two convergent solutions found after 20 tries
## Scaling: centring, PC rotation, halfchange scaling
## Species: expanded scores based on 'wisconsin(sqrt(veganifyOTU(physeq)))'

# Stress plot
stressplot(ord.nmms.bray)
```



```
# Stats
# Test whether the sample types differ significantly from each other using PERMANOVA
adonis(bray_dist ~ sample_data(ps_rare)$Sample_type)

##
## Call:
## adonis(formula = bray_dist ~ sample_data(ps_rare)$Sample_type)
##
## Permutation: free
## Number of permutations: 999
```

```
##
## Terms added sequentially (first to last)
##
##              Df SumsOfSqs MeanSqs F.Model      R2 Pr(>F)
## sample_data(ps_rare)$Sample_type  2      1.3629 0.68145  2.0786 0.06798  0.001
## Residuals                        57     18.6866 0.32784      0.93202
## Total                           59     20.0495      1.00000
##
## sample_data(ps_rare)$Sample_type ***
## Residuals
## Total
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

adonis(formula = bray_dist ~ sample_data(ps_rare)$Individual)

##
## Call:
## adonis(formula = bray_dist ~ sample_data(ps_rare)$Individual)
##
## Permutation: free
## Number of permutations: 999
##
## Terms added sequentially (first to last)
##
##              Df SumsOfSqs MeanSqs F.Model      R2 Pr(>F)
## sample_data(ps_rare)$Individual 19     14.9269 0.78563  6.1346 0.7445  0.001 ***
## Residuals                       40      5.1226 0.12807      0.2555
## Total                           59     20.0495      1.0000
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

adonis(bray_dist ~ sample_data(ps_rare)$Sample_type*sample_data(ps_rare)$Individual)

##
## Call:
## adonis(formula = bray_dist ~ sample_data(ps_rare)$Sample_type *      sample_data(ps_rare)$Individual
##
## Permutation: free
## Number of permutations: 999
##
## Terms added sequentially (first to last)
##
##              Df SumsOfSqs
## sample_data(ps_rare)$Sample_type      2      1.3629
## sample_data(ps_rare)$Individual      19     14.9269
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual 38      3.7597
## Residuals                             0      0.0000
## Total                                59     20.0495
##
##              MeanSqs
## sample_data(ps_rare)$Sample_type      1
## sample_data(ps_rare)$Individual      1
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual 0
## Residuals                             Inf
## Total
```

```
##
## sample_data(ps_rare)$Sample_type F.Model 0
## sample_data(ps_rare)$Individual 0
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual 0
## Residuals
## Total
##
## R2 Pr(>F)
## sample_data(ps_rare)$Sample_type 0.06798 1
## sample_data(ps_rare)$Individual 0.74450 1
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual 0.18752 1
## Residuals 0.00000
## Total 1.00000
```


```
anosim(bray_dist, sample_data(ps_rare)$Sample_type)
```

```
##
## Call:
## anosim(x = bray_dist, grouping = sample_data(ps_rare)$Sample_type)
## Dissimilarity: bray
##
## ANOSIM statistic R: 0.2048
## Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
```

```
BCanoSamp <- (anosim(bray_dist, sample_data(ps_rare)$Sample_type))
summary(BCanoSamp)
```

```
##
## Call:
## anosim(x = bray_dist, grouping = sample_data(ps_rare)$Sample_type)
## Dissimilarity: bray
##
## ANOSIM statistic R: 0.2048
## Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
##
## Upper quantiles of permutations (null model):
## 90% 95% 97.5% 99%
## 0.0296 0.0435 0.0568 0.0732
##
## Dissimilarity ranks between and within classes:
## 0% 25% 50% 75% 100% N
## Between 1 491.250 982.50 1410.50 1769.5 1200
## Rectal swab CT 46 392.750 684.50 1053.25 1752.0 190
## Rectal swab ST 58 513.125 951.50 1353.25 1722.0 190
## Stool 44 267.750 616.25 885.75 1405.0 190
```

```
plot(BCanoSamp)
```



```
anosim(bray_dist, sample_data(ps_rare)$Individual)
```

```
##
## Call:
## anosim(x = bray_dist, grouping = sample_data(ps_rare)$Individual)
## Dissimilarity: bray
##
## ANOSIM statistic R: 0.789
##      Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
```


```
BCanoInd <- anosim(bray_dist, sample_data(ps_rare)$Individual)
summary(BCanoInd)
```

```
##
## Call:
## anosim(x = bray_dist, grouping = sample_data(ps_rare)$Individual)
## Dissimilarity: bray
##
## ANOSIM statistic R: 0.789
##      Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
##
## Upper quantiles of permutations (null model):
##      90%      95%     97.5%     99%
## 0.0732 0.1019 0.1270 0.1512
##
## Dissimilarity ranks between and within classes:
```

##		0%	25%	50%	75%	100%	N
##	Between	44	480.25	909.5	1337.625	1769.5	1710
##	1	9	15.00	21.0	25.500	30.0	3
##	2	16	22.50	29.0	33.000	37.0	3
##	3	5	19.00	33.0	34.000	35.0	3
##	4	8	29.50	51.0	60.000	69.0	3
##	5	10	23.00	36.0	37.000	38.0	3
##	6	1	13.00	25.0	25.500	26.0	3
##	7	20	95.50	171.0	733.750	1296.5	3
##	8	4	15.50	27.0	29.000	31.0	3
##	9	41	41.50	42.0	761.000	1480.0	3
##	10	12	45.00	78.0	137.500	197.0	3
##	11	7	10.50	14.0	18.000	22.0	3
##	12	32	46.50	61.0	62.500	64.0	3
##	13	19	35.50	52.0	423.750	795.5	3
##	14	23	31.00	39.0	41.000	43.0	3
##	15	28	736.50	1445.0	1587.000	1729.0	3
##	16	2	7.50	13.0	15.500	18.0	3
##	17	11	17.50	24.0	29.000	34.0	3
##	18	40	857.00	1674.0	1714.500	1755.0	3
##	19	3	9.00	15.0	16.000	17.0	3
##	20	6	125.00	244.0	394.000	544.0	3

```
plot(BCanoInd)
```

```
## Warning in bxp(list(stats = structure(c(44, 480, 909.5, 1338, 1769.5, 9, : some
## notches went outside hinges ('box')): maybe set notch=FALSE
```



```
BCps.disper <- betadisper(bray_dist, sample_data(ps_rare)$Sample_type)
anova(BCps.disper)
```

```
## Analysis of Variance Table
##
```

```
## Response: Distances
##           Df  Sum Sq  Mean Sq F value Pr(>F)
## Groups      2 0.010371 0.0051855  2.6804 0.07717 .
## Residuals  57 0.110273 0.0019346
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
permutest(BCps.disper)
```

```
##
## Permutation test for homogeneity of multivariate dispersions
## Permutation: free
## Number of permutations: 999
##
## Response: Distances
##           Df  Sum Sq  Mean Sq      F N.Perm Pr(>F)
## Groups      2 0.010371 0.0051855 2.6804   999 0.087 .
## Residuals  57 0.110273 0.0019346
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
permutest(BCps.disper, pairwise = TRUE)
```

```
##
## Permutation test for homogeneity of multivariate dispersions
## Permutation: free
## Number of permutations: 999
##
## Response: Distances
##           Df  Sum Sq  Mean Sq      F N.Perm Pr(>F)
## Groups      2 0.010371 0.0051855 2.6804   999 0.087 .
## Residuals  57 0.110273 0.0019346
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Pairwise comparisons:
## (Observed p-value below diagonal, permuted p-value above diagonal)
##           Rectal swab CT Rectal swab ST Stool
## Rectal swab CT                0.152000 0.402
## Rectal swab ST           0.156123      0.034
## Stool                   0.395585      0.028482
```


```
TukeyHSD(BCps.disper)
```

```
## Tukey multiple comparisons of means
## 95% family-wise confidence level
##
## Fit: aov(formula = distances ~ group, data = df)
##
## $group
##           diff          lwr          upr      p adj
## Rectal swab ST-Rectal swab CT 0.01985443 -0.01361660 0.05332546 0.3337714
## Stool-Rectal swab CT          -0.01203124 -0.04550227 0.02143979 0.6643777
## Stool-Rectal swab ST          -0.03188567 -0.06535670 0.00158536 0.0649792
```

```
# Beta Dispersion Plots
```


```
BCbeta.Dispersion <- BCps.disper
```

```
plot(BCbeta.Dispersion)
```




```
plot(BCbeta.Dispersion, hull = FALSE, ellipse = TRUE)
```

BCbeta.Dispersion



```
boxplot(BCbeta.Dispersion)
```




```
# Bray-Curtis NMDS plot
bcdf <- plot_ordination(ps_rare, ord.nmds.bray, justDF = TRUE)

BC_plot <- ggplot(bcdf, aes(x = NMDS1, y = NMDS2)) +
  geom_line(aes(group = Individual), size = 0.2, linetype = "dashed") +
```



```
geom_point(aes(color = Sample_type)) +
stat_ellipse(aes(color = Sample_type)) +
annotate("text", x = -0.02, y = -0.02, label = "Stress = ") +
annotate("text", x = -0.008, y = -0.02, label = round(ord.nmds.bray$stress, 4)) +
ggtitle("Bray-Curtis Ordination") + labs(color = "Sample Type") +
theme(aspect.ratio = 1, plot.margin = unit(c(0, 1, 0, 0), "pt"))
```

BC_plot



```
ggsave("../Results/2A)Beta_Diversity_BC.pdf", width = 6, height = 4.5)
```

Beta Diversity - Weighted UniFrac

```
# Ordinate data using Non-metric multidimensional scaling (NMDS) on Weighted Unifrac dissimilarity (dis
uni_dist <- phyloseq::distance(ps_rare, method = "wunifrac")
```

```
## Warning in UniFrac(physeq, weighted = TRUE, ...): Randomly assigning root as --
## ASV109 -- in the phylogenetic tree in the data you provided.
```

```
ord.nmds.uni <- ordinate(ps_rare, "NMDS", "wunifrac")
```

```
## Warning in UniFrac(physeq, weighted = TRUE, ...): Randomly assigning root as --
## ASV3449 -- in the phylogenetic tree in the data you provided.
```


```
## Run 0 stress 0.1443313
```

```
## Run 1 stress 0.1443314
## ... Procrustes: rmse 2.53073e-05  max resid 0.0001601472
## ... Similar to previous best
## Run 2 stress 0.2084974
## Run 3 stress 0.2200537
## Run 4 stress 0.1483259
## Run 5 stress 0.2072398
## Run 6 stress 0.1773185
## Run 7 stress 0.1799837
## Run 8 stress 0.1768409
## Run 9 stress 0.1470084
## Run 10 stress 0.2054333
## Run 11 stress 0.1483256
## Run 12 stress 0.1475256
## Run 13 stress 0.1497001
## Run 14 stress 0.1836523
## Run 15 stress 0.1493966
## Run 16 stress 0.1463929
## Run 17 stress 0.1494815
## Run 18 stress 0.206636
## Run 19 stress 0.1475256
## Run 20 stress 0.1475256
## *** Solution reached
```

```
# Call newly created file to get the stress value of the plot
ord.nmfs.uni
```

```
##
## Call:
## metaMDS(comm = ps.dist)
##
## global Multidimensional Scaling using monoMDS
##
## Data:      ps.dist
## Distance: user supplied
##
## Dimensions: 2
## Stress:      0.1443313
## Stress type 1, weak ties
## Two convergent solutions found after 20 tries
## Scaling: centring, PC rotation
## Species: scores missing
```

```
# Stress plot
stressplot(ord.nmfs.uni)
```



```
# Stats
# Test whether the sample types differ significantly from each other using PERMANOVA
adonis(uni_dist ~ sample_data(ps_rare)$Sample_type)
```

```
##
## Call:
## adonis(formula = uni_dist ~ sample_data(ps_rare)$Sample_type)
##
## Permutation: free
## Number of permutations: 999
##
## Terms added sequentially (first to last)
##
##              Df SumsOfSqs  MeanSqs F.Model    R2 Pr(>F)
## sample_data(ps_rare)$Sample_type  2   0.47754 0.238770   5.256 0.15571 0.001
## Residuals                57   2.58939 0.045428           0.84429
## Total                    59   3.06693                1.00000
##
## sample_data(ps_rare)$Sample_type ***
## Residuals
## Total
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
adonis(formula = uni_dist ~ sample_data(ps_rare)$Individual)
```

```
##
## Call:
## adonis(formula = uni_dist ~ sample_data(ps_rare)$Individual)
##
## Permutation: free
## Number of permutations: 999
##
```

```

## Terms added sequentially (first to last)
##
##
##              Df SumsOfSqs  MeanSqs F.Model      R2 Pr(>F)
## sample_data(ps_rare)$Individual 19    1.9315 0.101659  3.5814 0.62979  0.001
## Residuals                        40    1.1354 0.028385          0.37021
## Total                           59    3.0669          1.00000
##
## sample_data(ps_rare)$Individual ***
## Residuals
## Total
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

adonis(uni_dist ~ sample_data(ps_rare)$Sample_type*sample_data(ps_rare)$Individual)

##
## Call:
## adonis(formula = uni_dist ~ sample_data(ps_rare)$Sample_type *      sample_data(ps_rare)$Individual)
##
## Permutation: free
## Number of permutations: 999
##
## Terms added sequentially (first to last)
##
##
##              Df SumsOfSqs
## sample_data(ps_rare)$Sample_type      2    0.47754
## sample_data(ps_rare)$Individual      19    1.93153
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual 38    0.65786
## Residuals                             0    0.00000
## Total                               59    3.06693
##
##              MeanSqs
## sample_data(ps_rare)$Sample_type      0
## sample_data(ps_rare)$Individual      0
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual      0
## Residuals                          -Inf
## Total
##
##              F.Model
## sample_data(ps_rare)$Sample_type      0
## sample_data(ps_rare)$Individual      0
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual      0
## Residuals
## Total
##
##              R2 Pr(>F)
## sample_data(ps_rare)$Sample_type    0.15571      1
## sample_data(ps_rare)$Individual    0.62979      1
## sample_data(ps_rare)$Sample_type:sample_data(ps_rare)$Individual 0.21450      1
## Residuals    0.00000
## Total    1.00000

anosim(uni_dist, sample_data(ps_rare)$Sample_type)

##
## Call:
## anosim(x = uni_dist, grouping = sample_data(ps_rare)$Sample_type)
## Dissimilarity:


```

```
##
## ANOSIM statistic R: 0.1875
##      Significance: 0.001
##
## Permutation: free
## Number of permutations: 999

UWFanoSamp <- (anosim(uni_dist, sample_data(ps_rare)$Sample_type))
summary(UWFanoSamp)

##
## Call:
## anosim(x = uni_dist, grouping = sample_data(ps_rare)$Sample_type)
## Dissimilarity:
##
## ANOSIM statistic R: 0.1875
##      Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
##
## Upper quantiles of permutations (null model):
##   90%   95%  97.5%   99%
## 0.0325 0.0478 0.0615 0.0768
##
## Dissimilarity ranks between and within classes:
##           0%   25%   50%   75% 100%   N
## Between           1 486.75 967.5 1400.25 1770 1200
## Rectal swab CT 34 258.75 546.5  921.00 1727  190
## Rectal swab ST 17 493.25 851.5 1262.50 1763  190
## Stool           22 379.50 819.0 1258.50 1749  190

plot(UWFanoSamp)
```



```
anosim(uni_dist, sample_data(ps_rare)$Individual)
```


```
##
## Call:
## anosim(x = uni_dist, grouping = sample_data(ps_rare)$Individual)
## Dissimilarity:
##
## ANOSIM statistic R: 0.5524
##      Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
```

```
UWFanoInd <- anosim(uni_dist, sample_data(ps_rare)$Individual)
summary(UWFanoInd)
```

```
##
## Call:
## anosim(x = uni_dist, grouping = sample_data(ps_rare)$Individual)
## Dissimilarity:
##
## ANOSIM statistic R: 0.5524
##      Significance: 0.001
##
## Permutation: free
## Number of permutations: 999
##
## Upper quantiles of permutations (null model):
##      90%    95%   97.5%    99%
## 0.0848 0.1119 0.1333 0.1535
##
## Dissimilarity ranks between and within classes:
##      0%    25%    50%    75% 100%    N
## Between 17 470.25 903.5 1336.75 1769 1710
## 1         9  21.00   33.0   77.50  122   3
## 2        64  98.00  132.0  198.00  264   3
## 3         3  91.00  179.0  189.50  200   3
## 4         8 510.00 1012.0 1160.00 1308   3
## 5        12 152.00  292.0  305.00  318   3
## 6         1  48.00   95.0  106.50  118   3
## 7        11 275.50  540.0  702.50  865   3
## 8         4 142.50  281.0  311.00  341   3
## 9       117 274.50  432.0  897.00 1362   3
## 10        10 826.50 1643.0 1652.50 1662   3
## 11         6   9.50   13.0   18.50   24   3
## 12       147 331.50  516.0  518.00  520   3
## 13        15 427.00  839.0 1005.50 1172   3
## 14        18 157.50  297.0  407.00  517   3
## 15       168 964.00 1760.0 1765.00 1770   3
## 16         5  22.00   39.0   39.50   40   3
## 17        14  34.00   54.0  139.50  225   3
## 18       212 561.50  911.0 1141.00 1371   3
## 19         2   9.00   16.0   18.00   20   3
## 20         7 666.00 1325.0 1327.00 1329   3
```

```
plot(UWFanoInd)
```

```
## Warning in bxp(list(stats = structure(c(17, 470, 903.5, 1337, 1769, 9, 21, :
## some notches went outside hinges ('box'): maybe set notch=FALSE
```



```
UWFps.disper <- betadisper(uni_dist, sample_data(ps_rare)$Sample_type)
anova(UWFps.disper)
```

```
## Analysis of Variance Table
##
## Response: Distances
##      Df    Sum Sq   Mean Sq F value Pr(>F)
## Groups    2 0.010549 0.0052747  1.9298 0.1545
## Residuals 57 0.155798 0.0027333
```

```
permutest(UWFps.disper)
```

```
##
## Permutation test for homogeneity of multivariate dispersions
## Permutation: free
## Number of permutations: 999
##
## Response: Distances
##      Df    Sum Sq   Mean Sq      F N.Perm Pr(>F)
## Groups    2 0.010549 0.0052747 1.9298   999  0.172
## Residuals 57 0.155798 0.0027333
```

```
permutest(UWFps.disper, pairwise = TRUE)
```

```
##
## Permutation test for homogeneity of multivariate dispersions
## Permutation: free
## Number of permutations: 999
```


```
##
## Response: Distances
##           Df Sum Sq Mean Sq    F N.Perm Pr(>F)
## Groups      2 0.010549 0.0052747 1.9298    999 0.151
## Residuals 57 0.155798 0.0027333
##
## Pairwise comparisons:
## (Observed p-value below diagonal, permuted p-value above diagonal)
##           Rectal swab CT Rectal swab ST Stool
## Rectal swab CT                0.091000 0.132
## Rectal swab ST          0.081515                0.818
## Stool                    0.128939          0.824097

TukeyHSD(UWFps.disper)


## Tukey multiple comparisons of means
## 95% family-wise confidence level
##
## Fit: aov(formula = distances ~ group, data = df)
##
## $group
##               diff            lwr            upr            p adj
## Rectal swab ST-Rectal swab CT 0.029757314 -0.01002727 0.06954190 0.1787741
## Stool-Rectal swab CT          0.026151485 -0.01363310 0.06593607 0.2617186
## Stool-Rectal swab ST          -0.003605828 -0.04339042 0.03617876 0.9741292

# Beta Dispersion Plots
UWfbeta.Dispersion <- UWFps.disper
plot(UWfbeta.Dispersion)
```


UWfbeta.Dispersion




```
plot(UWfbeta.Dispersion, hull = FALSE, ellipse = TRUE)
```



```
boxplot(UWfbeta.Dispersion)
```




```
# UniFrac NMDS Plot
wuni <- plot_ordination(ps_rare, ord.nmds.uni, justDF = TRUE)
```

```

UWF_plot <- ggplot(wuni, aes(x = NMDS1, y = NMDS2)) +
  geom_line(aes(group = Individual), size = 0.2, linetype = "dashed") +
  geom_point(aes(color = Sample_type)) +
  stat_ellipse(aes(color = Sample_type)) +
  annotate("text", x = -0.32, y = -0.28, label = "Stress = ") +
  annotate("text", x = -0.19, y = -0.28, label = round(ord.nmds.uni$stress, 4)) +
  ggtitle("Weighted UniFrac Ordination") + labs(color = "Sample Type") +
  theme(aspect.ratio = 1, plot.margin = unit(c(0, 0, 0, 1), "pt"),
        axis.title.y = element_blank())

```

UWF_plot



```



ggsave("../Results/2B)Beta_Diversity_wUni.pdf", width = 6, height = 4.5)

```

```

ggarrange(BC_plot, UWF_plot, common.legend = TRUE, legend = c("bottom"),
  align = ("hv"), labels = "AUTO")

```

A**B**

Sample Type — Rectal swab CT — Rectal swab ST — Stool

```
ggsave("../Results/2)Beta_Diversity.pdf", width = 8.5, height = 4.5)
```

RELATIVE ABUNDANCE - Using Taxonomic Level Class

```
# Subset Phyloseq Objects
ps_class <- subset_taxa(ps_rare, Class != "NA")

sample_clin <- subset_samples(ps_class, Sample_type == "Rectal swab CT")
sample_self <- subset_samples(ps_class, Sample_type == "Rectal swab ST")
sample_stool <- subset_samples(ps_class, Sample_type == "Stool")

# Relative Abundance - Clinician Taken Swab
clin_class <- tax_glom(sample_clin, taxrank = "Class") # agglomerate taxa
clin_class <- transform_sample_counts(clin_class, function(x) x/sum(x)) #get abundance in %
clin_melt <- psmelt(clin_class) # create dataframe from phyloseq object
clin_melt$Class <- as.character(clin_melt$Class) #convert to character
clin_melt <- clin_melt[order(-clin_melt$Abundance),]
clin_melt[!clin_melt$Class %in% c(unique(clin_melt$Class)[1:10]), "Class"] <- "Other"

# Relative Abundance - Self Taken Swab
self_class <- tax_glom(sample_self, taxrank = "Class") # agglomerate taxa
self_class <- transform_sample_counts(self_class, function(x) x/sum(x)) #get abundance in %
self_melt <- psmelt(self_class) # create dataframe from phyloseq object
self_melt$Class <- as.character(self_melt$Class) #convert to character
self_melt <- self_melt[order(-self_melt$Abundance),]
```

```

self_melt[!self_melt$Class %in% c(unique(self_melt$Class)[1:10]), "Class"] <- "Other"

# Relative Abundance - Stool Sample
stool_class <- tax_glom(sample_stool, taxrank = "Class") # agglomerate taxa
stool_class <- transform_sample_counts(stool_class, function(x) x/sum(x)) #get abundance in %
stool_melt <- psmelt(stool_class) # create dataframe from phyloseq object
stool_melt$Class <- as.character(stool_melt$Class) #convert to character
stool_melt <- stool_melt[order(-stool_melt$Abundance),]
stool_melt[!stool_melt$Class %in% c(unique(stool_melt$Class)[1:10]), "Class"] <- "Other"

# Set order of bars and get colours
sort.clin <- clin_melt %>%
  plyr::count("Class", wt = "Abundance") %>%
  arrange(desc(freq)) %>%
  pull(Class)
sort.clin <- sort.clin[!sort.clin %in% "Other"]
sort.clin <- append("Other", sort.clin)

sort.self <- self_melt %>%
  plyr::count("Class", wt = "Abundance") %>%
  arrange(desc(freq)) %>%
  pull(Class)
sort.self <- sort.self[!sort.self %in% "Other"]
sort.self <- append("Other", sort.self)

sort.stool <- stool_melt %>%
  plyr::count("Class", wt = "Abundance") %>%
  arrange(desc(freq)) %>%
  pull(Class)
sort.stool <- sort.stool[!sort.stool %in% "Other"]
sort.stool <- append("Other", sort.stool)

barOrder <- unique(c(sort.clin, sort.self, sort.stool))

# Get Colours and Assign to Bacteria
spectralExtra <- colorRampPalette(brewer.pal(11, "Spectral"))(length(barOrder))
cols <- setNames(c(spectralExtra), c(rev(barOrder)))

# Create Custom Legend
dummy_df <- data.frame(
  Class = as.factor(barOrder) ,
  value = c(1,2,3,4,5,6,7,8,9,10,11,12,13))
dummy_df <- mutate(dummy_df, Class = factor(Class, levels = rev(barOrder)))

rel_legend <- get_legend(ggplot(dummy_df, aes(x = Class, y = value)) +
  geom_bar(stat = "identity", aes(fill = Class)) +
  scale_fill_manual(values = cols) +
  theme(legend.text = element_text(size = 8), legend.key.size = unit(0.75, "line"))))

# Plot - Relative Abundance - Clinician Taken Swab
t1_class <- clin_melt %>%

```

```

mutate(Sample = factor(Sample, levels = c("1A", "2A", "3A", "4A", "5A",
                                           "6A", "7A", "8A", "9A", "10A",
                                           "11A", "12A", "13A", "14A", "15A",
                                           "16A", "17A", "18A", "19A", "20A"))) %>%

mutate(Class = factor(Class, levels = rev(barOrder))) %>%
ggplot(aes(x = Sample, y = Abundance, fill = Class)) +
geom_bar(stat = "identity", position = "fill") +
scale_y_continuous(labels = scales::percent_format()) +
theme(text = element_text(size = 7)) +
ggtitle("Clinician - Class - Top 10") +
ylab("Relative abundance") +
scale_fill_manual(values = cols) + theme(legend.position = "none")

# Plot - Relative Abundance - Self Taken Swab
t2_class <- self_melt %>%
  mutate(Sample = factor(Sample, levels = c("1B", "2B", "3B", "4B", "5B",
                                           "6B", "7B", "8B", "9B", "10B",
                                           "11B", "12B", "13B", "14B", "15B",
                                           "16B", "17B", "18B", "19B", "20B"))) %>%


  mutate(Class = factor(Class, levels = rev(barOrder))) %>%
ggplot(aes(x = Sample, y = Abundance, fill = Class)) +
geom_bar(stat = "identity", position = "fill") +
scale_y_continuous(labels = scales::percent_format()) +
theme(text = element_text(size = 7)) +
ggtitle("Self - Class - Top 10") +
ylab("Relative abundance") +
scale_fill_manual(values = cols) + theme(legend.position = "none")

# Plot - Relative Abundance - Stool Sample
t3_class <- stool_melt %>%
  mutate(Sample = factor(Sample, levels = c("1C", "2C", "3C", "4C", "5C",
                                           "6C", "7C", "8C", "9C", "10C",
                                           "11C", "12C", "13C", "14C", "15C",
                                           "16C", "17C", "18C", "19C", "20C"))) %>%

  mutate(Class = factor(Class, levels = rev(barOrder))) %>%
ggplot(aes(x = Sample, y = Abundance, fill = Class)) +
geom_bar(stat = "identity", position = "fill") +
scale_y_continuous(labels = scales::percent_format()) +
theme(text = element_text(size = 7)) +
ggtitle("Stool - Class - Top 10") +
ylab("Relative abundance") +
scale_fill_manual(values = cols) + theme(legend.position = "none")

plots <- ggarrange(t1_class, t2_class, t3_class, nrow = 3, labels = "AUTO")
ggarrange(plots, legend.grob = rel_legend, legend = "right")

```



```
ggsave("../Results/3)Relative_Abundance.pdf", width = 7, height = 8)
```

OTU differential abundance testing with DESeq2

```
ps_deseq <- ps %>%
  tax_glom(taxrank = "Genus")

sample_data(ps_deseq)$Sample_type <- gsub(" ", "_", sample_data(ps_deseq)$Sample_type)
sample_data(ps_deseq)$Sample_type <- as.factor(sample_data(ps_deseq)$Sample_type)

# Convert the phyloseq object to a DESeqDataSet
ds <- phyloseq_to_deseq2(ps_deseq, ~ Sample_type)

## converting counts to integer mode
ds <- DESeq(ds)

## estimating size factors
## estimating dispersions
## gene-wise dispersion estimates
## mean-dispersion relationship
## final dispersion estimates
## fitting model and testing
```


```
## -- replacing outliers and refitting for 151 genes
## -- DESeq argument 'minReplicatesForReplace' = 7
## -- original counts are preserved in counts(dds)
```

```
## estimating dispersions
```

```
## fitting model and testing
```

```
# Plot of Dispersion Estimates
```

```
plotDispEsts(ds, ylim = c(1e-8, 1e4))
```



```
# Extract the result table from the ds object using the DESeq2 function results and filter the OTUs using
alpha <- 0.01
```


```
# Swab CT vs Swab ST
```

```
resCTST <- results(ds, contrast = c("Sample_type", "Rectal_swab_CT", "Rectal_swab_ST"),
                    alpha = alpha)
```

```
resCTST <- resCTST[order(resCTST$padj, na.last = NA), ]
```


```
plotMA(resCTST, alpha = 0.01, main = "MA-plot of Clinician vs Self")
```

MA-plot of Clinician vs Self



```
hist(resCTST$pvalue, col = "gray", main = "Wald Model - Clinician vs Self", xlab = "Original p-values")
```

Wald Model – Clinician vs Self




```
resCTST_sig <- resCTST[(resCTST$padj < alpha), ]
resCTST_sig <- cbind(as(resCTST_sig, "data.frame"), as(tax_table(ps)[rownames(resCTST_sig), ], "matrix"),
head(resCTST_sig)
```



```
##      baseMean log2FoldChange      lfcSE      stat      pvalue      padj
## ASV1580  8.191810      6.205783 0.9102231  6.817871 9.239974e-12 2.808952e-09
## ASV3522 10.246362      7.072852 1.2769844  5.538714 3.046999e-08 4.631439e-06
## ASV1634 55.398735      4.339785 0.7977984  5.439702 5.336990e-08 5.408149e-06
## ASV3554  8.010744      6.131689 1.1953911  5.129441 2.906035e-07 2.208587e-05
## ASV1485 26.218338      4.915912 1.1726628  4.192093 2.763921e-05 1.473097e-03
## ASV1582 14.753210      6.139537 1.4685785  4.180598 2.907429e-05 1.473097e-03
##      Kingdom      Phylum      Class      Order
## ASV1580 Bacteria Proteobacteria Gammaproteobacteria Enterobacterales
## ASV3522 Bacteria Firmicutes Clostridia Clostridiales
## ASV1634 Bacteria Proteobacteria Gammaproteobacteria Pseudomonadales
## ASV3554 Bacteria Firmicutes Clostridia Clostridiales
## ASV1485 Bacteria Proteobacteria Gammaproteobacteria Aeromonadales
## ASV1582 Bacteria Proteobacteria Gammaproteobacteria Enterobacterales
##      Family      Genus
## ASV1580 Yersiniaceae Yersinia
## ASV3522 Clostridiaceae Clostridium_sensu_stricto_5
## ASV1634 Pseudomonadaceae Pseudomonas
## ASV3554 Clostridiaceae Clostridium_sensu_stricto_13
## ASV1485 Aeromonadaceae Aeromonas
## ASV1582 Hafniaceae Hafnia-Obesumbacterium
```


```
# Swab CT vs Stool
resCTS <- results(ds, contrast = c("Sample_type", "Rectal_swab_CT", "Stool"),
                  alpha = alpha)
resCTS <- resCTS[order(resCTS$padj, na.last = NA), ]
plotMA(resCTS, alpha = 0.01, main = "MA-plot of Clinician vs Stool")
```

MA-plot of Clinician vs Stool



```
hist(resCTS$pvalue, col = "gray", main = "Wald Model - Clinician vs Stool", xlab = "Original p-values")
```

Wald Model – Clinician vs Stool




```
resCTS_sig <- resCTS[(resCTS$padj < alpha), ]
resCTS_sig <- cbind(as(resCTS_sig, "data.frame"), as(tax_table(ps)[rownames(resCTS_sig), ], "matrix"))
head(resCTS_sig)
```

##	baseMean	log2FoldChange	lfcSE	stat	pvalue
## ASV3460	371.68353	26.83913	1.1950890	22.45785	1.072464e-111
## ASV3599	569.52608	28.29018	1.3237180	21.37176	2.447353e-101
## ASV940	102.45995	26.62138	1.5030199	17.71193	3.392565e-70
## ASV3146	112.98959	26.83745	1.6813612	15.96174	2.360599e-57
## ASV1183	82.54958	27.21862	1.7630615	15.43827	9.049272e-54
## ASV1254	3585.31720	11.79910	0.7864814	15.00239	7.082408e-51
##	padj	Kingdom	Phylum	Class	
## ASV3460	2.252174e-109	Bacteria	Firmicutes	Negativicutes	
## ASV3599	2.569720e-99	Bacteria	Firmicutes	Clostridia	
## ASV940	2.374796e-68	Bacteria	Firmicutes	Clostridia	
## ASV3146	1.239315e-55	Bacteria	Firmicutes	Bacilli	
## ASV1183	3.800694e-52	Bacteria	Synergistota	Synergistia	
## ASV1254	2.478843e-49	Bacteria	Campilobacterota	Campylobacteria	
##		Order			
## ASV3460		Veillonellales-Selenomonadales			
## ASV3599		Clostridia_or			
## ASV940		Peptostreptococcales-Tissierellales			
## ASV3146		Lactobacillales			
## ASV1183		Synergistales			
## ASV1254		Campylobacterales			
##		Family	Genus		
## ASV3460		Veillonellaceae	Negativicoccus		

```
## ASV3599          Hungateiclostridiaceae Fastidiosipila
## ASV940  Peptostreptococcales-Tissierellales_fa    Gallicola
## ASV3146          Aerococcaceae      Facklamia
## ASV1183          Synergistaceae Pyramidobacter
## ASV1254          Campylobacteraceae  Campylobacter
```


```
# Swab ST vs Stool
resSTS <- results(ds, contrast = c("Sample_type", "Rectal_swab_ST", "Stool"),
                  alpha = alpha)
resSTS <- resSTS[order(resSTS$padj, na.last = NA), ]
plotMA(resSTS, alpha = 0.01, main = "MA-plot of Self vs Stool")
```

MA-plot of Self vs Stool



```
hist(resSTS$pvalue, col = "gray", main = "Wald Model - Self vs Stool", xlab = "Original p-values")
```

Wald Model – Self vs Stool



```
resSTS_sig <- resSTS[(resSTS$padj < alpha), ]
resSTS_sig <- cbind(as(resSTS_sig, "data.frame"), as(tax_table(ps)[rownames(resSTS_sig), ], "matrix"))
head(resSTS_sig)
```

##	baseMean	log2FoldChange	lfcSE	stat	pvalue
## ASV3460	371.68353	29.01258	1.1939331	24.30001	1.960067e-130
## ASV3599	569.52608	30.42730	1.3230276	22.99823	4.854894e-117
## ASV940	102.45995	27.70469	1.5015082	18.45124	5.095997e-76
## ASV3146	112.98959	27.85901	1.6801511	16.58125	9.522523e-62
## ASV1254	3585.31720	11.98355	0.7864397	15.23772	1.986922e-52
## ASV1183	82.54958	26.79915	1.7628105	15.20251	3.403086e-52
##	padj	Kingdom	Phylum	Class	
## ASV3460	5.252978e-128	Bacteria	Firmicutes	Negativicutes	
## ASV3599	6.505558e-115	Bacteria	Firmicutes	Clostridia	
## ASV940	4.552424e-74	Bacteria	Firmicutes	Clostridia	
## ASV3146	6.380090e-60	Bacteria	Firmicutes	Bacilli	
## ASV1254	1.064990e-50	Bacteria	Campilobacterota	Campylobacteria	
## ASV1183	1.520045e-50	Bacteria	Synergistota	Synergistia	
##		Order			
## ASV3460		Veillonellales-Selenomonadales			
## ASV3599		Clostridia_or			
## ASV940		Peptostreptococcales-Tissierellales			
## ASV3146		Lactobacillales			
## ASV1254		Campylobacterales			
## ASV1183		Synergistales			
##		Family	Genus		
## ASV3460		Veillonellaceae	Negativicoccus		
## ASV3599		Hungateiclostridiaceae	Fastidiosipila		
## ASV940		Peptostreptococcales-Tissierellales_fa	Gallicola		
## ASV3146		Aerococcaceae	Facklamia		

```
## ASV1254                      Campylobacteraceae  Campylobacter
## ASV1183                      Synergistaceae  Pyramidobacter

# Save .csv of significant fold change results
resCTST_sig$Comparison <- "Clinician Taken Swab vs Self Taken Swab"
resCTS_sig$Comparison <- "Clinician Taken Swab vs Stool"
resSTS_sig$Comparison <- "Self Taken Swab vs Stool"

SignificantResults <- rbind(resCTST_sig, resCTS_sig, resSTS_sig)
write.csv(SignificantResults, file = "../Results/SignificantFoldChangeResults.csv")
```

Differential Abundance - ggplot Heatmap

```
diffCTST <- resCTST_sig %>%
  select(log2FoldChange, Phylum, Genus)
colnames(diffCTST)[1] <- "CTST_log2FoldChange"

diffCTS <- resCTS_sig %>%
  select(log2FoldChange, Phylum, Genus)
colnames(diffCTS)[1] <- "CTS_log2FoldChange"

diffSTS <- resSTS_sig %>%
  select(log2FoldChange, Phylum, Genus)
colnames(diffSTS)[1] <- "STS_log2FoldChange"

heat <- rbind.fill(as.data.frame(t(diffCTS)), as.data.frame(t(diffSTS)))
heat <- rbind.fill(as.data.frame(heat), as.data.frame(t(diffCTST)))
heat <- t(heat)
heat <- as.data.frame(heat)
colnames(heat) <- c("CTS", "CTS_phylum", "CTS_genus",
                  "STS", "STS_phylum", "STS_genus",
                  "CTST", "CTST_phylum", "CTST_genus")

heat$sigPhylum <- as.character(heat$CTS_phylum)
heat$sigPhylum[nrow(heat)] <- as.character(heat$STS_phylum[nrow(heat)])

heat$sigGenus <- as.character(heat$CTS_genus)
heat$sigGenus[nrow(heat)] <- as.character(heat$STS_genus[nrow(heat)])

heat <- select(heat, -CTS_genus, -STS_genus, -CTST_genus, -CTS_phylum, -STS_phylum, -CTST_phylum)

# file for ggplot based heatmap
SamplingComparison <- c(1:(nrow(heat)*3))
SamplingComparison[1:nrow(heat)] <- "CTS"
SamplingComparison[(nrow(heat)+1):(nrow(heat)*2)] <- "STS"
SamplingComparison[((nrow(heat)*2)+1):(nrow(heat)*3)] <- "CTST"
log2FC <- c(1:(nrow(heat)*3))
log2FC[1:nrow(heat)] <- as.numeric(as.character(heat$CTS))
log2FC[(nrow(heat)+1):(nrow(heat)*2)] <- as.numeric(as.character(heat$STS))
log2FC[((nrow(heat)*2)+1):(nrow(heat)*3)] <- as.numeric(as.character(heat$CTST))
Phylum <- c(1:(nrow(heat)*3))
Phylum[1:nrow(heat)] <- heat$sigPhylum
```

```

Phylum[(nrow(heat)+1):(nrow(heat)*2)] <- heat$sigPhylum
Phylum[((nrow(heat)*2)+1):(nrow(heat)*3)] <- heat$sigPhylum
Genus <- c(1:(nrow(heat)*3))
Genus[1:nrow(heat)] <- heat$sigGenus
Genus[(nrow(heat)+1):(nrow(heat)*2)] <- heat$sigGenus
Genus[((nrow(heat)*2)+1):(nrow(heat)*3)] <- heat$sigGenus
ftp <- as.data.frame(cbind(SamplingComparison, log2FC, Phylum, Genus))


ftp$log2FC <- as.numeric(as.character(ftp$log2FC))
ftp$SamplingComparison <- factor(ftp$SamplingComparison, levels = c("CTST", "CTS", "STS"))

heatLog <- ggplot(ftp, aes(SamplingComparison, Genus, fill = log2FC)) + geom_tile() +
  geom_text(aes(label = sprintf("%.1f", log2FC)), size = 2) +
  theme(axis.title = element_blank(), legend.position = "bottom",
        axis.text.y = element_blank(),
        axis.text.x = element_text(family = "Helvetica", size = 10, face = "plain"),
        plot.background = element_blank(),
        plot.margin = margin(t = 2, r = 0, b = 0, l = 0, unit = "pt"),
        legend.margin = margin(t = 0, r = 0, b = 0, l = 0, unit = "pt")) +
  guides(fill = guide_colourbar(title.position = "bottom", title.hjust = 0.5)) +
  scale_fill_distiller(palette = "RdBu") +
  scale_x_discrete(position = "top", labels = (c("Clinician vs Self",
                                                "Clinician vs Stool",
                                                "Self vs Stool")))

heatPhylum <- ggplot(ftp, aes(SamplingComparison, Genus, fill = Phylum)) + geom_tile() +
  theme(axis.title = element_blank(), legend.position = "bottom",
        axis.text.y = element_text(size = 8),
        axis.text.x = element_blank(), axis.ticks.x = element_blank(),
        plot.margin = margin(t = 16.5, r = 5, b = 11, l = 0, unit = "pt"),
        legend.margin = margin(t = 0, r = 0, b = 0, l = 0, unit = "pt"),
        legend.text = element_text(size = 8), legend.key.size = unit(0.75, "line")) +
  scale_fill_brewer(palette = "Set3", guide = guide_legend(ncol = 3))

heatChanges <- ggarrange(heatPhylum, heatLog, widths = c(1, 2))
heatChanges

```



Species Abundance ggplot Heatmap

```

scale_fill_gradient(low = "white", high = "red") +
guides(fill = guide_colourbar(title.position = "bottom", title.hjust = 0.5))

# Self Swab
heat_self <- subset_samples(heat_ps, Sample_type == "Rectal swab ST")
melted_self <- psmelt(heat_self)
melted_self <- select(melted_self, Individual, Genus, Abundance)
melted_self$Abundance[melted_self$Abundance == 0] <- 1
melted_self$log2Abundance <- log2(melted_self$Abundance)
melted_self$log10Abundance <- log10(melted_self$Abundance)

heatSS <- ggplot(melted_self, aes(Individual, Genus, fill = log10Abundance)) + geom_tile() +
  scale_x_discrete(position = "top") + xlab("Self Taken Swab") +
  theme(axis.title.x = element_text(family = "Helvetica", size = 10, face = "plain"),
        axis.title.y = element_blank(),
        axis.text = element_blank(), legend.position = "bottom", legend.background = element_blank(),
        plot.margin = margin(t = 1, r = 0, b = 0, l = 0, unit = "pt"),
        legend.margin = margin(t = 11, r = 0, b = 0, l = 0, unit = "pt")) +
  scale_fill_gradient(low = "white", high = "red") +
  guides(fill = guide_colourbar(title.position = "bottom", title.hjust = 0.5))

# Stool
heat_stool <- subset_samples(heat_ps, Sample_type == "Stool")
melted_stool <- psmelt(heat_stool)
melted_stool <- select(melted_stool, Individual, Genus, Abundance)
melted_stool$Abundance[melted_stool$Abundance == 0] <- 1
melted_stool$log2Abundance <- log2(melted_stool$Abundance)
melted_stool$log10Abundance <- log10(melted_stool$Abundance)

heatSt <- ggplot(melted_stool, aes(Individual, Genus, fill = log10Abundance)) + geom_tile() +
  scale_x_discrete(position = "top") + xlab("Stool") +
  theme(axis.title.x = element_text(family = "Helvetica", size = 10, face = "plain"),
        axis.title.y = element_blank(),
        axis.text = element_blank(), legend.position = "bottom", legend.background = element_blank(),
        plot.margin = margin(t = 1, r = 0, b = 0, l = 0, unit = "pt"),
        legend.margin = margin(t = 11, r = 0, b = 0, l = 0, unit = "pt")) +
  scale_fill_gradient(low = "white", high = "red") +
  guides(fill = guide_colourbar(title.position = "bottom", title.hjust = 0.5))

heatAbundance <- ggarrange(heatCS, heatSS, heatSt, ncol = 3, common.legend = TRUE, legend = c("bottom"))


```

Combined Heatmaps

```

ggarrange(heatChanges, heatAbundance, widths = c(2, 1), legend = c("bottom"))

```

```
ggsave("../Results/4)Differential_Abundance_heatmap_extra.pdf",width = 11, height = 8)
```

Supplementary 2 - Calculate some stats re deseq2 enrichment

```
mytax <- data.frame(tax_table(ps_deseq))
mytable <- mytax %>%
  group_by(Phylum) %>%
  summarize(Phycount = n_distinct(Genus))

## `summarise()` ungrouping output (override with `.groups` argument)

sigdat <- SignificantResults %>%
  group_by(Comparison, Phylum) %>%
  summarize(count = n_distinct(Genus))

## `summarise()` regrouping output by 'Comparison' (override with `.groups` argument)

mysum <- sum(mytable$Phycount)
#mytable$PhyRatio = mytable$Phycount /mysum
mytable$ConditionA = "Clinician Taken Swab vs Stool"
mytable$ConditionB = "Self Taken Swab vs Stool"
mytable$ConditionC = "Clinician Taken Swab vs Self Taken Swab"

data_long <- tidyr::gather(mytable, condition, Comparison, ConditionA:ConditionC, factor_key = TRUE)
joined2 <- sigdat %>%
```

```


full_join(data_long)

## Joining, by = c("Comparison", "Phylum")
joined2<-joined2 %>%
  mutate_at(c(3), ~replace(., is.na(.), 0))
joined2$Phycount = joined2$Phycount - joined2$count

dat_long <- joined2 %>%
  tidyr::gather("count", "measurement", count, Phycount)
dat_long$measurement = as.numeric(as.character(dat_long$measurement))

ggplot(dat_long) +
  geom_col(aes(x = Phylum, y = measurement, fill = count)) +
  facet_grid(~Comparison) +
  theme(axis.text.x = element_text(angle = 90, vjust = 0.5, hjust=1)) +
  ylab("Total genera") +
  scale_fill_discrete(name = "Treatment-Affected", labels = c("True", "False"))

```



```

ggsave("../Results/S2)TreatmentAffectedGenera.pdf", width = 10, height = 6)

joined2$total = joined2$count + joined2$Phycount
joined2$condition = gsub("ConditionC", 0.019, joined2$condition)
joined2$condition = gsub("ConditionB", 0.15, joined2$condition)
joined2$condition = gsub("ConditionA", 0.195, joined2$condition)
joined2$condition = as.numeric(as.character(joined2$condition))

```

```

f<-NULL;
for(i in c(1:48))
{
  #print(joined2$total[i])
  r<-binom.test(joined2$count[i], joined2$total[i], joined2$condition[i])
  #print(r)
  f<-rbind(f, c(r$statistic, r$parameter, r$null.value, r$p.value))
  ++i
}
colnames(f)[4] = "p.val"
# Not significant after FDR correction
p.adjust(f[,4], method = "BH")

## [1] 1.000000 0.626522 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000
## [9] 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000
## [17] 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000
## [25] 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000
## [33] 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000
## [41] 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000 1.000000

joined2[7:10] = f[,1:4]
colnames(joined2)[7:10] = c("successes", "trials", "pSuccess", "pval")
joined2$p.adjust = p.adjust(f[,4], method = "BH")

```

Supplementary 3 - DESeq2 Significance by Abundance

```

library(patchwork)

sup_ps <- ps_rare %>%
  tax_glom(taxrank = "Genus")

sup_bugs <- as.character(unique(SignificantResults$Genus))
sup_bugsCTST <- as.character(resCTST_sig$Genus)
sup_bugsCTS <- as.character(resCTS_sig$Genus)
sup_bugsSTS <- as.character(resSTS_sig$Genus)

sup_melt <- psmelt(sup_ps)
sup_melt$Phylum <- as.character(sup_melt$Phylum)
sup_melt$Genus <- as.character(sup_melt$Genus)

sup_melt$Significant <- ifelse(sup_melt$Genus %in% sup_bugs, "YES", "NO")
sup_melt$Significant <- factor(sup_melt$Significant, levels = c("YES", "NO"))

sup_melt$CTST <- ifelse(sup_melt$Genus %in% sup_bugsCTST, "YES", "NO")
sup_melt$CTST <- factor(sup_melt$CTST, levels = c("YES", "NO"))

sup_melt$CTS <- ifelse(sup_melt$Genus %in% sup_bugsCTS, "YES", "NO")
sup_melt$CTS <- factor(sup_melt$CTS, levels = c("YES", "NO"))

sup_melt$STS <- ifelse(sup_melt$Genus %in% sup_bugsSTS, "YES", "NO")
sup_melt$STS <- factor(sup_melt$STS, levels = c("YES", "NO"))

```

```


sup_CTST <- ggplot(sup_melt, aes(x = Phylum, y = Abundance, fill = CTST)) +
  geom_col() + labs(subtitle = "Clinician Swab vs Self Swab", fill = "Significant") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1),
        axis.title.x = element_blank(), legend.position = "none")

sup_CTS <- ggplot(sup_melt, aes(x = Phylum, y = Abundance, fill = CTS)) +
  geom_col() + labs(subtitle = "Clinician Swab vs Stool", fill = "Significant") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1),
        axis.title.y = element_blank(), axis.text.y = element_blank(),
        legend.position = "none")

sup_STS <- ggplot(sup_melt, aes(x = Phylum, y = Abundance, fill = STS)) +
  geom_col() + labs(subtitle = "Self Swab vs Stool", fill = "Significant") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1), axis.title.x = element_blank(),
        axis.title.y = element_blank(), axis.text.y = element_blank())

sup_CTST + sup_CTS + sup_STS + plot_layout(ncol = 3)

```



```

ggsave("../Results/S3)SignificanceByAbundance.pdf", width = 10, height = 6)


```

Supplementary 4 - Differential Abundance Figure

```

ggplot(resCTST_sig, aes(x = log2FoldChange, y = reorder(Genus, log2FoldChange), fill= Phylum)) +
  geom_bar(stat = "identity", position = "identity", width = 0.5) +
  labs(title = "Clinician Swab vs Self Swab", y = "Genus", x = "log2 Fold Change") +
  theme(aspect.ratio = 1) +
  scale_fill_brewer(palette = "Set1")


```




```
ggsave("../Results/S4)Differential_Abundance_clinVSself.pdf", width = 7, height = 4)

clinVSstool <- ggplot(resCTS_sig, aes(x = log2FoldChange,
                                     y = reorder(Genus, log2FoldChange),
                                     fill= Phylum)) +
  geom_bar(stat = "identity", position = "identity", width = 0.7) +
  labs(title = "Clinician Swab vs Stool", y = "Genus", x = "log2 Fold Change") +
  scale_fill_brewer(palette = "Set3") +
  theme(axis.text.y = element_text(size = 8),
        legend.text = element_text(size = 8), legend.key.size = unit(0.75, "line"))
clinVSstool
```

Clinician Swab vs Stool



```
selfVSstool <- ggplot(resSTS_sig, aes(x = log2FoldChange,
                                     y = reorder(Genus, log2FoldChange),
                                     fill= Phylum)) +
  geom_bar(stat = "identity", position = "identity", width = 0.7) +
  labs(title = "Self Swab vs Stool", y = "Genus", x = "log2 Fold Change") +
  scale_fill_brewer(palette = "Set3") +
  theme(axis.text.y = element_text(size = 8),
        legend.text = element_text(size = 8), legend.key.size = unit(0.75, "line"))
selfVSstool
```




```
ggarrange(clinVSstool, selfVSstool, ncol = 2, common.legend = TRUE, legend = "right", labels = "AUTO")
```

A

C B

Self Swab vs Stc



```
ggsave("../Results/S4)Differential_Abundance_swabsVSstool.pdf", width = 12, height = 8)
```

Supplementary 5 - Boxplot Sanity Checks

```
resCTS_sig <- resCTS_sig[order(-resCTS_sig$log2FoldChange),]

int <- row.names(resCTS_sig)[1:12]
ASVlabs <- tax_table(ps)[int, 6]
names(ASVlabs) <- int
ASVlabs <- as.list(ASVlabs)

ASV_labeller <- function(variable,value){
  return(ASVlabs[value])
}


# Sanity Plots with Fold Change
tcounts <- t(log2((counts(ds[int, ], normalized = TRUE, replaced = FALSE) + .5))) %>%
  merge(colData(ds), ., by = "row.names") %>%
  tidyr::gather(ASV, log2FC, (ncol(.)-length(int) + 1):ncol(.))

tcounts %>%
  select(Row.names, Sample_type, Individual, ASV, log2FC) %>%
  head %>%
  knitr::kable()
```


Row.names	Sample_type	Individual	ASV	log2FC
10A	Rectal_swab_CT	10	ASV3599	3.017179
10B	Rectal_swab_ST	10	ASV3599	5.359164
10C	Stool	10	ASV3599	-1.000000
11A	Rectal_swab_CT	11	ASV3599	4.888552
11B	Rectal_swab_ST	11	ASV3599	-1.000000
11C	Stool	11	ASV3599	-1.000000

```
ggplot(tcounts, aes(Sample_type, log2FC)) +
  geom_boxplot() + geom_jitter(width = 0.2, height = 0.2, size = 0.4, aes(color = Individual)) +
  facet_wrap(~ASV, scales = "free_y", labeller = ASV_labeller, nrow = 4) +
  labs(x = "Sample Type",
       y = "log2FC",
       title = "Sanity Plots with log2FoldChange Results") +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

Warning: The labeller API has been updated. Labellers taking `variable` and
`value` arguments are now deprecated. See labellers documentation.




```
ggsave("../Results/S5)Sanity_FoldChange_plots.pdf", width = 7, height = 8)
```

```
# Sanity Plots with Abundance
sanity_ps <- subset_taxa(ps_deseq, taxa_names(ps_deseq) %in% int)
sanity <- psmelt(sanity_ps)

ggplot(sanity, aes(Sample_type, Abundance)) +
```

```
geom_boxplot() + geom_jitter(width = 0.2, height = 0.2, size = 0.4, aes(color = Individual)) +
facet_wrap(~Genus, scales = "free_y", nrow = 4) +
scale_y_log10() +
labs(x = "Sample Type",
     y = "log Abundance",
     title = "Sanity Plots with log10 Abundance") +
theme(axis.text.x = element_text(angle = 45, hjust = 1))
```

```
## Warning: Transformation introduced infinite values in continuous y-axis
## Warning: Transformation introduced infinite values in continuous y-axis
## Warning: Removed 474 rows containing non-finite values (stat_boxplot).
```



```
ggsave("../Results/S5)Sanity_logAbundance_plots.pdf", width = 7, height = 8)
```

```
## Warning: Transformation introduced infinite values in continuous y-axis
## Warning: Transformation introduced infinite values in continuous y-axis
## Warning: Removed 474 rows containing non-finite values (stat_boxplot).
```

Session Info

```
sessionInfo()
```

```
## R version 3.6.3 (2020-02-29)
```

```

## Platform: x86_64-apple-darwin15.6.0 (64-bit)
## Running under: macOS Sierra 10.12.6
##
## Matrix products: default
## BLAS:   /Library/Frameworks/R.framework/Versions/3.6/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/3.6/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_NZ.UTF-8/en_NZ.UTF-8/en_NZ.UTF-8/C/en_NZ.UTF-8/en_NZ.UTF-8
##
## attached base packages:
## [1] parallel stats4      stats      graphics  grDevices  utils      datasets
## [8] methods   base
##
## other attached packages:
## [1] patchwork_1.0.1      DESeq2_1.26.0
## [3] SummarizedExperiment_1.16.1 DelayedArray_0.12.3
## [5] BiocParallel_1.20.1   matrixStats_0.56.0
## [7] Biobase_2.46.0        GenomicRanges_1.38.0
## [9] GenomeInfoDb_1.22.1   IRanges_2.20.2
## [11] S4Vectors_0.24.4      BiocGenerics_0.32.0
## [13] ggpubr_0.4.0          ggplot2_3.3.2
## [15] phyloseq_1.30.0       dplyr_1.0.2
## [17] vegan_2.5-6           permute_0.9-5
## [19] Rmisc_1.5             plyr_1.8.6
## [21] lattice_0.20-41       RColorBrewer_1.1-2
##
## loaded via a namespace (and not attached):
## [1] colorspace_1.4-1      ggsignif_0.6.0        ellipsis_0.3.1
## [4] rio_0.5.16            htmlTable_2.1.0       XVector_0.26.0
## [7] base64enc_0.1-3       rstudioapi_0.11       farver_2.0.3
## [10] bit64_4.0.5           AnnotationDbi_1.48.0   codetools_0.2-16
## [13] splines_3.6.3         geneplotter_1.64.0    knitr_1.30
## [16] ade4_1.7-15           Formula_1.2-3         jsonlite_1.7.1
## [19] broom_0.7.0           annotate_1.64.0        cluster_2.1.0
## [22] png_0.1-7             compiler_3.6.3        backports_1.1.10
## [25] Matrix_1.2-18         htmltools_0.5.0       tools_3.6.3
## [28] igraph_1.2.5          gtable_0.3.0          glue_1.4.2
## [31] GenomeInfoDbData_1.2.2 reshape2_1.4.4        Rcpp_1.0.5
## [34] carData_3.0-4         cellranger_1.1.0      vctrs_0.3.4
## [37] Biostrings_2.54.0     multtest_2.42.0       ape_5.4-1
## [40] nlme_3.1-149          iterators_1.0.13      xfun_0.19
## [43] stringr_1.4.0         openxlsx_4.2.2        lifecycle_0.2.0
## [46] XML_3.99-0.3          rstatix_0.6.0         zlibbioc_1.32.0
## [49] MASS_7.3-53           scales_1.1.1          hms_0.5.3
## [52] biomformat_1.14.0     rhdf5_2.30.1          yaml_2.2.1
## [55] curl_4.3              memoise_1.1.0         gridExtra_2.3
## [58] rpart_4.1-15          RSQlite_2.2.0         latticeExtra_0.6-29
## [61] stringi_1.5.3         highr_0.8             genefilter_1.68.0
## [64] foreach_1.5.1         checkmate_2.0.0       zip_2.1.1
## [67] rlang_0.4.8           pkgconfig_2.0.3       bitops_1.0-6
## [70] evaluate_0.14         purrr_0.3.4           Rhdf5lib_1.8.0
## [73] labeling_0.4.2        htmlwidgets_1.5.2     cowplot_1.1.0
## [76] bit_4.0.4             tidyselect_1.1.0      magrittr_1.5

```

## [79]	R6_2.5.0	generics_0.1.0	Hmisc_4.4-1
## [82]	DBI_1.1.0	pillar_1.4.6	haven_2.3.1
## [85]	foreign_0.8-76	withr_2.3.0	mgcv_1.8-33
## [88]	survival_3.2-3	abind_1.4-5	RCurl_1.98-1.2
## [91]	nnet_7.3-14	tibble_3.0.4	crayon_1.3.4
## [94]	car_3.0-9	rmarkdown_2.3	jpeg_0.1-8.1
## [97]	locfit_1.5-9.4	grid_3.6.3	readxl_1.3.1
## [100]	data.table_1.13.2	blob_1.2.1	forcats_0.5.0
## [103]	digest_0.6.27	xtable_1.8-4	tidyr_1.1.2
## [106]	munsell_0.5.0		