



# Planning and Scheduling: Introduction to Planning



Hochschule  
Bonn-Rhein-Sieg



Prof. Dr.-Ing. Gerhard K. Kraetzschmar

# Acknowledgements

- These slides refer to Chapter I of the textbook:  
Malik Ghallab, Dana Nau, and Paolo Traverso:  
Automated Planning: Theory and Practice  
Morgan Kaufmann, 2004
- These slides are an adaptation of slides by Dana Nau
- The contributions of these authors are gratefully acknowledged

# Plans and Planning

## ■ Plan:

- A collection of actions for performing some task or achieving some objective

## ■ Planning:

- There are many programs to aid human planners

- Project management
- Plan storage/retrieval
- Automatic schedule generation


- Automatic plan generation is much more difficult

- Many research prototypes
- Fewer practical systems
- Research is starting to pay off
  - Several successes on difficult practical problems



```
Poces:
00 AB/WSeppRatmeLN 0entbon
00 AVME 200 00001 0entbad
    02 0apbord
    03 0eb10 dampenta bleye0.8,100
    04 0301 0dimeerdil0t
00 BVME 010 04301 03 0eb10 dampenta bleye0.8,100
    02 0ghdella {25,0.0}e dph100
    03 0eshdil0t(125,050)0dpth100
00 CVME 010 07701 03 0eb10 0dimeerdil0t
    02 0ghdella 000,480todeph 10
    03 0eshdil0t(0004.8)e dph100
    [-.]
00 TVME 220 12001 0elt0eonVM1
[-.]
00 AVME 200 00001 0entbad
    02 0apbord
    03 0eb10 dampenta bleye0.8,100
    04 0301 0dimeerdil0t
00 BVME 010 03401 03 0eb10 dampenta bleye0.8,100
    02 0ghs0emilp0k0at(025,125
    03 0gh040widh030 dph050
    04 0ghs0emilp0k0at(025,125
    05 0gh040widh030 dph050
    06 0ghs0emilp0k0at(025,125
    07 0gh040widh030 dph050
00 CVME 010 15401 03 0eb10 dampenta bleye0.8,100
00 TVME 250 48701 0elt0eonVM1
00 A EE 000 322901 02 0ybad 0oveat85dg.F
00 B EE3000 04801 02 0eadpobes0tfem100RPMpine
00 C EE3000 20001 02 0eadpobes0tfem100RPMpine
00 D EE3000 20001 02 0eadpobes0tfem100RPMpine
00 T EE9000 547701 0elt0eonEE
    02 0bigofcppe
00 A ME3000 45701 02 0p0eb0ad0f0so0eig
00 B ME3000 02901 02 0ep0nt0ldr0se0nbad
00 C ME3000 75001 02 0p0st000e p0eat(351.3)0nbad0s0gn0ze
    03 0p0st000e p0eat(384.0)0nbad0s0gn0ze
    31 0p0st000e p0eat(384.0)0nbad0s0gn0ze
00 D ME 000 57101 0ybad 0oveat85dg.Fto0ldfys0d0p0se
00 T ME9000 180701 0elt0eonME
[-.]
01 A TE 000 350001 0f0mp0t0cap0t0g 0bord
01 B TE 000 296701 0f0mf0l0l0p0ct0 0bord
01 T TE 000 646701 0elt0eonTE
99 T 3970 033701 0elt0et0m0f0atue
```


# NASA Unmanned Spacecraft



- Remote Agent eXperiment (RAX)
  - Autonomous AI software for planning/control
  - Ran on the DS1 spacecraft in May 1998
  - For several minutes it was allowed to control the spacecraft
- Mars rover
  - Guided by autonomous AI planning/control software

# Other Examples


- Computer bridge: Bridge Baron
  - Used AI planning to win the 1997 world computer bridge championship
  - Commercial software, thousands of copies sold
- Manufacturing process planning
  - Software included with Amada's sheet-metal bending machines
  - Used to plan bending operations



- Conceptual model
- Restrictive assumptions
- Classical planning
- Relaxing the assumptions
- A running example: Dock Worker Robots

# Conceptual Model

- Ingredients:
- Model of the environment: possible states
- Model of how the environment can change: effects of actions
- Specification of initial conditions and objectives
- Plans of actions that are generated by a planner
- A model of execution of a plan in the environment
- A model of observation of the environment





# Conceptual Model

- State-transition system

$$\Sigma = (S, A, E, \gamma)$$

- $S = \{\text{states}\}$

- $A = \{\text{actions}\}$  (controllable)

- $E = \{\text{events}\}$  (uncontrollable)

- state-transition function

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

- Observation function

$$h : S \mapsto O$$


- Produces observation  $o$  about current state  $s$

- Controller: given observation  $o \in O$ , produces action  $a \in A$

- Planner:

- Input: description of  $\Sigma$ , initial state  $s_0 \in S$ , some objective

- Output: produces a plan to drive the controller






# Conceptual Model

## Possible objectives:

- A set of goal states  $S_g$ 
  - Find sequence of state transitions ending at a goal
- Some condition over the set of states followed by the system
  - e.g., reach  $S_g$  and stay there
- Utility function attached to states
  - Optimize some function of the utilities
- Tasks to perform, specified recursively as sets of sub-tasks and actions



# Conceptual Model: Example

## ■ State transition system

$$\Sigma = (S, A, E, \gamma)$$

where

■  $S = \{s_0, \dots, s_5\}$

■  $A = \{\text{move\_1}, \text{move\_2}\}$   
 $\cup \{\text{put}, \text{take}, \text{load}, \text{unload}\}$

■  $E = \emptyset$

■  $\gamma$  : as shown


■  $h(s) = s$  for every  $s$

■ Input to planner:

■ System  $\Sigma$

■ Initial state  $s_0$

■ Goal state  $s_5$




# Planning Versus Scheduling

## ■ Scheduling

- Decide how to perform a given set of actions using a limited number of resources in a limited amount of time
- Typically NP-complete


## ■ Planning

- Decide what actions to use to achieve some set of objectives
- Can be much worse than NP-complete
  - In the most general case, it is undecidable
  - Most research assumes various collections of restrictions to guarantee decidability
- We will now look at some of the restrictions



# Restrictive Assumptions

- A0 (finite  $\Sigma$ ):
  - The state space  $S$  is finite
  - $S = \{s_0, s_1, s_2, \dots, s_k\}$  for some  $k$
- A1 (fully observable  $\Sigma$ ):
  - The observation function  $h : S \mapsto O$  is the identity function
  - I.e., the controller always knows what state  $\Sigma$  is in



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$


$$A = \{actions\}$$

$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

# Restrictive Assumptions

- A2 (deterministic  $\Sigma$ ):
  - $\forall u \in A \cup E : \|\gamma(s, u)\| = 1$
  - Each action or event has only one possible outcome
- A3 (static  $\Sigma$ ):
  - E is empty: no changes except those performed by the controller
- A4 (attainment goals):
  - A goal state  $s_g$   
or  
a set of goal states  $S_g$



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$


$$A = \{actions\}$$

$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

# Restrictive Assumptions

- A5 (sequential plans):
  - Solution is a linearly ordered sequence of actions  
 $\langle a_1, a_2, \dots, a_n \rangle$
- A6 (implicit time):
  - No durations, instantaneous state transitions
- A7 (off-line planning):
  - Planner does not know the execution status



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$

$$A = \{actions\}$$

$$E = \{events\}$$


$$\gamma : S \times (A \cup E) \mapsto 2^S$$



- Classical planning requires **all eight** restrictive assumptions
  - Complete knowledge about a deterministic, static, finite-state system with attainment goals and implicit time
- Reduces to the following problem:
  - Given  $(\Sigma, s_0, S_g)$
  - find a sequence of actions  $\langle a_1, a_2, \dots, a_n \rangle$
  - that produces a sequence of state transitions
    - $s_1 = \gamma(s_0, a_1)$
    - $s_2 = \gamma(s_1, a_2)$
    - $\vdots$
    - $s_n = \gamma(s_{n-1}, a_n)$
  - such that  $s_n \in S_g$


# Classical Planning: Example

- Same example as before:
  - System is finite, deterministic, static
  - Complete knowledge
  - Attainment goals
  - Implicit time
  - Offline planning
- Classical planning is just path-searching in a graph
  - States are nodes
  - Actions are edges
- Is this trivial?




# Classical Planning

- Very difficult computationally
  - Generalize the earlier example:
    - Five locations, three piles, three robots, 100 containers
  - Then there are  $10^{277}$  states
    - More than  $10^{190}$  times as many states as the number of particles in the universe!
- The vast majority of AI research has been on classical planning
  - Parts I and II of the book
- Too restricted to fit most problems of practical interest
  - But the ideas can sometimes be useful in those problems



# Relax the Assumptions

- Relax A0 (finite  $\Sigma$ ):
  - Discrete, e.g. 1st-order logic:
  - Continuous, e.g. numeric variables
  - Sections:
    - 2.4 (extensions to classical)
    - 10.5 (control-rule planners)
    - 11.7 (HTN planning)
  - Case study: Chapter 21 (manufacturability analysis)
- Relax A1 (fully observable  $\Sigma$ ):
  - If we don't relax any other restrictions, then the only uncertainty is about  $s_0$



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$


$$A = \{actions\}$$

$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

# Relax the Assumptions

- Relax A2 (deterministic  $\Sigma$ ):
  - Actions have more than one possible outcome
  - Seek policy or contingency plan
  - With probabilities:
    - Discrete Markov Decision Processes (MDPs)
    - Chapter 11
  - Without probabilities:
    - Nondeterministic transition systems
    - Chapters 12, 18



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$


$$A = \{actions\}$$

$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

# Relax the Assumptions

- Relax A1 and A2:
  - Finite POMDPs
    - Plan over belief states
    - Exponential time & space
    - Section 16.3
- Relax A0 and A2:
  - Continuous or hybrid MDPs
    - Control theory  
(see engineering courses)
- Relax A0, A1, and A2
  - Continuous or hybrid POMDPs
    - Case study: Chapter 20 (robotics)



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$

$$A = \{actions\}$$


$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$



# Relax the Assumptions

- Relax A3 (static  $\Sigma$ ):
  - Other agents or dynamic environment
    - Finite perfect-info zero-sum games (introductory AI courses)
  - Randomly behaving environment
    - Decision analysis (business, operations research)
    - Can sometimes map this into MDPs or POMDPs
  - Case studies: Chapters 19 (space), 22 (emergency evacuation)
- Relax A1 and A3
  - Imperfect-information games
  - Case study: Chapter 23 (bridge)



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$


$$A = \{actions\}$$

$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

# Relax the Assumptions

- Relax A5 (sequential plans) and A6 (implicit time):
  - Temporal planning
  - Chapters 13, 14
- Relax A0, A5, A6
  - Planning and resource scheduling
  - Chapter 15
- 247 other combinations
  - We won't discuss them all!



$$\Sigma = (S, A; E, \gamma)$$

$$S = \{states\}$$

$$A = \{actions\}$$

$$E = \{events\}$$

$$\gamma : S \times (A \cup E) \mapsto 2^S$$

# A running example: Dock Worker Robots

- Generalization of the earlier example

- A harbor with several locations

- E.g., docks, docked ships, storage areas, parking areas

- Containers


- Going to/from ships

- Robot carts

- Can move containers


- Cranes

- Can load and unload containers



# A running example: Dock Worker Robots

- Locations:  $l_1, l_2, \dots$
- Containers:  $c_1, c_2, \dots$ 
  - Can be stacked in piles, loaded onto robots, or held by cranes
- Piles:  $p_1, p_2, \dots$ 
  - Fixed areas where containers are stacked
  - Pallet at the bottom of each pile
- Robot carts:  $r_1, r_2, \dots$ 
  - Can move to adjacent locations
  - Carry at most one container
- Cranes:  $k_1, k_2, \dots$ 
  - Each belongs to a single location
  - Move containers between piles and robots
  - If there is a pile at a location, there must also be a crane there



# A running example: Dock Worker Robots

- Fixed relations: same in all states

$adjacent(l, l')$     $attached(p, l)$     $belongs\_to(k, l)$

- Dynamic relations: differ from one state to another

$occupied(l)$     $at(r, l)$   
 $loaded(r, c)$     $unloaded(r)$   
 $holding(k, c)$     $empty(k)$   
 $in(c, p)$     $on(c, c')$   
 $top(c, p)$     $top(pallet, p)$

- Actions:

$take(c, k, p)$   
 $put(c, k, p)$   
 $load(r, c, k)$   
 $unload(r)$   
 $move(r, l, l')$

