

Haskell: Notes

Moritz M. Konarski

September 3, 2020

Contents

Variables and functions	1
Variables	1
Haskell source files	1
Comments	1
Variables in imperative languages	1
Functions	1
Local definitions	2
Truth values	3
Equality and other comparisons	3
Infix operators	3
Boolean operations	3
Guards	3
Type basics	5
Functional types	5
Type signatures in code	6
Lists and tuples	7
Lists	7
Tuples	7
Type basics II	9
Classes beyond numbers	9
Building vocabulary	10
Function composition	10
Prelude and the libraries	10
Next steps	12
If then else	12
Introducing pattern matching	12
Tuple and list patterns	13
Let bindings	13
Simple input and output	14
Sequencing actions with <code>do</code>	14

<i>CONTENTS</i>	ii
Recursion	15
Numeric recursion	15
List-based recursion	15

Variables and functions

Variables

- variables are useful

```
a = 3.141592
a^3
```

- code is more readable and modifiable

Haskell source files

- file extension is `.hs`
- to load a file in GHCi type `:l`, to reload type `:r`

Comments

- comments are done like this

```
x = 5      -- a comment
```

- block comments work like this

```
x = 5
{-
  multi-line comment
-}
y = {- inline comment -} 12
```

Variables in imperative languages

- in Haskell, variables can only be declared once and they are immutable
- they must begin with a letter and then can contain letters, numbers, underscores and ticks

Functions

- functions take an argument (or parameter) and gives a resulting value
- they are defined as follows

```
area r = pi * r ^ 2
```

- functions don't use parentheses but they can be used to group expressions and to make code easier to read
- haskell functions can also take multiple arguments

```
areaTriangle b h = (b * h) / 2
```

- functions can also be passed as arguments
- arguments are applied in the order they are given
- functions can be used to define some new functions

Local definitions

- when functions have values local to them, they are declared using `where` – see Heron's formula $A = \sqrt{s(s-a)(s-b)(s-c)}$

```
heron a b c = sqrt (s * (s - a) * (s - b) * (s - c))  
  where  
    s = (a + b + c) / 2
```

- the `where` and local variables are indented by 4 spaces – there can be multiple such statements

Truth values

Equality and other comparisons

- double equal signs are used for comparisons ==
- True and False are the representations of the booleans
- other evaluations are <, >, >=, <=, /=

-- defining operators

```
x /= y = not (x == y)
```

- types are important

Infix operators

- functions that are written between the arguments

```
4 + 9 == 13
-- same as
(==) (4 + 9) 13
```

Boolean operations

- logical and is &&
- logical or is ||
- logical not is not

Guards

- syntactic sugar for piecewise functions

```
-- function for the absolute value of x
absolute x
  | x < 0      = 0 - x      -- -x would also work
  | otherwise = x
```

- the pipe | is followed by a predicate (boolean expression)
- otherwise is used when none of the preceding values are True, it is actually just defined as True
- where works well with guards

```
numOfRealSolutions a b c
| disc > 0 = 2
| disc == 0 = 1
| otherwise = 0
  where
    disc = b^2 - 4*a*c      -- discriminant for above
                           -- descisions
```

Type basics

- all types in haskell have to begin with a capital letter
- types are useful because they define what you can and can't do with them
- `:type` or `:t` checks the type of any expression
- `::` means 'is of type', it indicates the *type signature*
- `True` and `False` are of type `Bool`
- characters are of type `Char`

```
:t 'H'
'H' :: Char
```

- strings are of type list of char

```
:t "hello"
"hello" :: [Char]
```

- type synonyms are different words for the same types

```
[Char] == String
```

Functional types

- functions have types too
- type signature for `not`

```
:t not
not :: Bool -> Bool
-- function from bool to bool
```

- `chr :: Int -> Char` converts int to char ASCII
- `ord :: Char -> Int` converts ASCII to int
- to use these functions you have to use the module `Data.Char` with `:module Data.Char` or `:m Data.Char`
- finding the type signatures of function works by listing all types of the input values in order and then the result value, all separated by `->`

```
xor p q = (p || q) && not (p && q)
:t xor
xor :: Bool -> Bool -> Bool
```


Type signatures in code

- type annotations look exactly like the function signatures

```
xor :: Bool -> Bool -> Bool
xor p q = (p || q) && not (p && q)
```

- this clarifies the function to the compiler and the programmer
- when types are not provided, the compiler infers the types by what data is there
- also, type signatures can help the compiler spot errors for you
- by separating functions with commas we can put multiple ones on the same signature line
- if one writes + instead of ++ for concatenation, the compiler will let you know

Lists and tuples

Lists

- denoted by [and], elements are separated by commas
- all elements must be of the same type

```
numbers = [1,2,3,4]
bools   = [True, False, False]
```

- to add elements to the start of a list, use : (cons), evaluated from right to left

```
[1,2,3,4] == 1:2:3:4:[]
```

- you can only cons elements to a list, not vice versa
- strings are also just lists of characters
- lists can also contain lists – a useful feature

Tuples

- store multiple values in a single value
- tuples will always have a set length, you cannot increase their size – good if you know the amount of needed data
- elements of a tuple do not need to be of the same type

```
(True, 1)
("hello", 'c', 123.23)
```

- tuples can also contain other tuples
- `fst` and `snd` return the first and second elements of a 2-tuple or pair
- `head` and `tail` for lists return the first element and the list minus the first element
- `head` and `tail` are pretty bad though, they will fail if passed an empty list
- functions can use polymorphic types, they can represent a bunch of different types with certain similarities
- type variables allow any type to take their place, they are useful for writing functions that can work on many types
- mathematically that's called polymorphism

```
f :: a -> a
-- takes type a and returns same type a
f :: a -> b
-- takes a and may or may not return the same type
```

- for example `fst` and `snd` work like this

```
-- return first of pair
fst :: (a, b) -> a
-- return second of pair
snd :: (a, b) -> b
```

Type basics II

- in maths you can add any type of number together – for computers that does not work too well
- floats and integers are the least types you need
- this means Haskell needs types for at least those two
- still, the (+) works on any type of number

```
(+) :: (Num a) => a -> a -> a
```

- here Num is a typeclass – a restriction on the types that a function can accept
- the most important numeric types are Int, Integer, Float, and Double
- Int is 32 bit, Integer is arbitrarily long, the others are floating point numbers
- a number in a Haskell program is of type number and is only restricted when it is changed, like 7 is anything, 3.12 is restricted to double and then they are added on the lowest denominator
- monomorphic trouble comes when returned types are incompatible
- using a function that returns Int with a function expecting Double will blow up, it requires conversion

```
-- converts an int into a polymorphic number  
fromIntegral(num)
```

Classes beyond numbers

- there is a typeclass for equations Eq
- length is a function that takes a Foldable, a type that includes lists and more

Building vocabulary

Function composition

- means applying one function to a value and then applying another function to the result

```
-- defining functions
f x = x + 3
square x = x ^ 2
square (f 1)      -- returns 16
f (square 2)      -- returns 7
```

- the parentheses are necessary because otherwise the function would try to take another function as input – an error
- we can make one function of multiple commonly used ones

```
square0fF x = square (f x)
f0fSquare x = f (square x)
```

- another way to do it is with `(.)`, the function composition operator

```
-- functions are applied from right to left
square0fF x = (square . f) x
f0fsquare x = (f . square) x
```

- one can also leave out the `x`, giving

```
square0fF = square . f
```

Prelude and the libraries

- the standard library in Haskell is called the prelude
- it provides the types and general functions
- you can import modules into your program

```
import Data.List
```

- in GHCi use `:m +<name>`
- using the standard library can make programs much shorter

```
-- program that reverses the order of strings
revWords :: String -> String
revWords input = (unwords . reverse . words) input
```



Next steps

If then else

- works like in other languages

```
signum x =  
  if x < 0  
    then -1  
    else if x > 0  
      then 1  
      else 0
```

- there *has* to be an **else** statement because there always has to be a result
- if - then - else can also be translated to guards

```
signu x =  
  | x < 0      = -1  
  | x > 0      = 1  
  | otherwise = 0
```

- both options work the same, sometimes one is more readable than the other

Introducing pattern matching

- long if-else statements are convoluted
- defining piece-wise functions is much better and more readable

```
pts :: Int -> Int  
pts 1 = 10  
pts 2 = 6  
pts 3 = 4  
pts 4 = 3  
pts 5 = 2  
pts 6 = 1  
pts _ = 0
```

- the `_` is a wildcard – matching anything of the functions type
- using some logic, we can make `pts` even shorter

```
pts :: Int -> Int  
pts 1 = 10  
pts 2 = 6
```

```
pts x
| s <= 6    = 7 - x
| otherwise = 0
```

- pattern matching can be overlapped and thus inefficient
- patterns should always match all possible cases

Tuple and list patterns

- the patterns work the same, they are more useful actually

```
head    :: [a] -> a
head (x:_) = x
head []    = error "Prelude.head: empty list"

tail    :: [a] -> [a]
tail (_:xs) = xs
tail []    = error "Prelude.head: empty list"
```

Let bindings

- similar to `where`, different formatting
- can help make functions more readable

```
roots a b c =
    ((-b + sqrt(b * b - 4 * a * c)) / (2 * a),
     (-b - sqrt(b * b - 4 * a * c)) / (2 * a))
-- can be transformed to
short_roots a b c =
    let d = sqrt (b ^ 2 - 4 * a * c)
        two_a = 2 * a
    in ((-b + d) / two_a,
        (-b - d) / two_a)
```


Simple input and output

- program have to interact with the world around them

```
putStrLn "Hello, world!"
```

- `putStr` just misses the new line `putStrLn` has
- these functions are of type `IO ()`, that is `IO` action with type `()` – unit type, tuple with 0 elements – basically nothing
- `IO` occurs in `print`, `read`, `write`

Sequencing actions with `do`

- `do` lets you put actions in order of execution

```
main = do
  putStrLn "Please enter your name:"
  name <- getLine
  putStrLn ("Hello, " ++ name ++ ", how are you")
```

- the final action defines the type of the whole `do` block – here the whole program has type `IO ()`
- the `<-` notation assigns the result of `getLine` to the variable – omitting it will just take the input but don't act on it
- `<-` cannot be the last action
- use `read` to convert string to text, `show` to convert number to string

```
double = read "123.3"
```

```
string_of_double = show double
```

- `<-` can be used to get any result value, just some of them are not worth saving
- the two branches of `if/then/else` statements must all have the same type
- for all sequenced commands we need to start a new `do` block
- for action to return what they say they will, you require the `<-`

Recursion

- a function that has the ability to invoke itself
- a recursive function calls itself in certain circumstances and stops in others

Numeric recursion

- see factorials

```
factorial 0 = 1
factorial n = n * factorial (n - 1)
```

- always write the most restrictive type first
- `go` can be used to translate loops from other languages into Haskell
- many functions have recursive versions – multiplication for example

List-based recursion

- lists make extensive use of recursion, e.g. for length

```
length :: [a] -> Int
length []      = 0
length (x:xs)  = 1 + length xs
```

- recursion is the only way to implement control structures if one only has immutable types
- the list concatenate function is defined recursively too

```
(++) :: [a] -> [a] -> [a]
[] ++ ys      = ys
(x:xs) ++ ys  = x : xs ++ ys
-- basically turns [1,2,3] ++ [4,5,6] into 1:2:3:[4,5,6]
```

- list recursion generally involves an empty list case and then one where the tail is passed to the function again # TODO: implement examples