

Multivariate Symbolic Aggregate Approximation for ECG Analysis

Moritz M. Konarski
Supervised by Prof. Taalaibek M. Imanaliev

Applied Mathematics and Informatics Program,
American University of Central Asia

May 3, 2021
Bishkek, Kyrgyz Republic




Outline

1 Introduction

2 Methods

3 Preliminary Results

What is an ECG?



- electrocardiogram (ECG or EKG) records the heart's electrical activity
- contains up to 12 simultaneous measurements—the leads
- common medical diagnostic tool

Figure 1: Annotated ECG of one heartbeat

MSAX for ECG Analysis

- └ Introduction
- └ ECG Basics
 - └ What is an ECG?




Figure 1: Annotated ECG of one heartbeat

- P wave: blood entering the heart
- QRS complex: heart contraction pumping blood
- T: return of ventricle to polarized state
- U: present in 25%
- muscle contractions caused by electric pulses
- electric pulse can be measured on the skin
- electrodes form leads (need 2 to measure anything)
- most types of heart disease can be detected
- diagnosis and analysis is performed by trained cardiologists
- **datasets available online; contain 2 or more leads (the most significant ones)**
- **I will be using online datasets for my analysis**
- heart diseases are some of the most deadly ones, thus ECG are really important

ECGs as Time Series

Definition

A discrete time series is an ordered sequence which, at discrete points in time, has n values each. If $n = 1$, the series is univariate and if $n > 1$, it is multivariate.

- digital ECGs are discrete multivariate time series:
 - have > 1 value at each point, often $n = 12$
 - recorded at discrete, evenly spaced time points
- time series analysis methods can be applied to ECGs

MSAX for ECG Analysis

└ Introduction

└ ECG Basics

└ ECGs as Time Series

Definition

A discrete time series is an ordered sequence which, at discrete points in time, has n values each. If $n = 1$, the series is univariate and if $n > 1$, it is multivariate.

- digital ECGs are discrete multivariate time series:
 - have > 1 value at each point, often $n = 12$
 - recorded at discrete, evenly spaced time points
- time series analysis methods can be applied to ECGs

- modern ECGs have at least 2, most have 12
- digital ones have set sampling frequencies, even the machines have set frequencies
- multivariate: measure more than 1 lead per time point
- discrete: set sample frequency in the machines
- discrete: because measured at discrete moments in time
- time series: they are data measured at equal time intervals
- n measurements per point in time (i.e. leads)
- $n = 1$ is univariate, $n > 1$ is multivariate

ECG Analysis

- standard method: manual analysis by cardiologist
- automated or computer-assisted ECG analysis seeks to replace that
- multiple stages:(1) signal acquisition; (2) data transformation, processing, filtering; (3) waveform recognition, feature extraction; (4) classification
- current research focus: artificial neural networks

MSAX for ECG Analysis

└ Introduction

└ ECG Analysis

└ ECG Analysis

- standard method: manual analysis by cardiologist
- automated or computer-assisted ECG analysis seeks to replace that
- multiple stages: (1) signal acquisition; (2) data transformation, processing, filtering; (3) waveform recognition, feature extraction; (4) classification
- current research focus: artificial neural networks

- is relatively slow; time is of the essence
- lots of training required
- error prone
- maybe not feasible for long ECGs
- can speed up process
- can pick up details humans miss
- digitizing paper ECGs or recording digital ones
- filtering to remove various types of noise
- reduce complexity of the data
- select important features and neglect irrelevant ones to ease analysis
- often added, figure out if there is some disease present or not
- balance between accuracy and complexity needed
- ann: hand all the steps discussed to a NN; use as good classifier too

SAX, MSAX, and HOTSAX

- Lin *et al.* (2003):
Symbolic Aggregate Approximation (SAX)—simplified, symbolic representation
- Anacleto *et al.* (2020):
Multivariate SAX (MSAX)—expands SAX to multivariate time series
- Keogh *et al.* (2005):
Heuristically Ordered Time series using SAX (HOTSAX)—discord discovery algorithm for SAX

MSAX for ECG Analysis

└ Introduction

└ ECG Analysis

└ SAX, MSAX, and HOTSAX

- Lin *et al.* (2003):
Symbolic Aggregate Approximation (SAX)—simplified, symbolic representation
- Anacleto *et al.* (2020):
Multivariate SAX (MSAX)—expands SAX to multivariate time series
- Keogh *et al.* (2005):
Heuristically Ordered Time series using SAX (HOTSAX)—discord discovery algorithm for SAX

- ecg as letters that mean same thing as original
- guaranteed to behave like the original data
- works on univariate time series
- has been used on ECGs
- takes the correlation between ecg leads into account
- cov mat: covariance between each lead and variance on diag
- uses sax representation to make the finding of discords easier
- can use MSAX just as well

Time Series Discords

Definition

A time series discord is the subsequence of a time series that is most different from all other subsequences.

k time series discords are the k most different subsequences.

- discords represent anomalies in an ECG
- HOTSAX enables fast discord discovery

MSAX for ECG Analysis

└ Introduction

└ ECG Analysis

└ Time Series Discords

- these can be diseases, noise, etc
- the discord does not discern

Definition

A time series discord is the subsequence of a time series that is most different from all other subsequences.

k time series discords are the k most different subsequences.

- discords represent anomalies in an ECG
- HOTSAX enables fast discord discovery

Hypothesis

HOTSAX with MSAX will increase the number of relevant discords detected compared to HOTSAX with SAX.

MSAX for ECG Analysis

- └ Introduction
 - └ Hypothesis
 - └ Hypothesis

HOTSAX with MSAX will increase the number of relevant discords detected compared to HOTSAX with SAX.

- **mention that MSAX to ECGs in particular is new**
- **mention that HOTSAX with MSAX is new**
- **THIS METHOD WILL NOT BE SUPER ACCURATE; MANY ECG changes are relatively small and would get lost in the SAX process**

Step 1: Z-Normalization

Assumption

The time series values are normally distributed.

SAX

- normalize univariate time series
- uses scalar mean and variance

MSAX

- normalize multivariate time series
- uses vector mean and covariance matrix

MSAX for ECG Analysis

└ Methods

└ SAX and MSAX

└ Step 1: Z-Normalization

- say that the process is the same as MSAX based on SAX
- this is assumed and this worked for other people who applied SAX to ECGs
- to compare time series, normalization is the accepted step
- what is this
- takes into account the correlation between leads

Assumption

The time series values are normally distributed.

SAX

- normalize univariate time series
- uses scalar mean and variance

MSAX

- normalize multivariate time series
- uses vector mean and covariance matrix

Step 2: Dimensionality Reduction

PAA

Piecewise Aggregate Approximation (PAA) takes T time series points, splits them into w ($w < T$) segments, and averages each of them.

SAX

- apply PAA to time series

MSAX

- apply PAA to each of the time series individually

MSAX for ECG Analysis

└ Methods

└ SAX and MSAX

└ Step 2: Dimensionality Reduction

- this reduces complexity
- PAA form of time series is shorter and simpler
- it still somewhat corresponds to the original

PAA

Piecewise Aggregate Approximation (PAA) takes T time series points, splits them into w ($w < T$) segments, and averages each of them.

SAX

- apply PAA to time series

MSAX

- apply PAA to each of the time series individually




Figure 2: ECG with PAA (MITBIH/100, $w = 18$, $T = 360$)

Step 3: Discretization

SAX Discretization

Find breakpoints splitting $\mathcal{N}(0, 1)$ into B equiprobable segments.
Assign a letter to each area, starting with a to the left-most segment.
PAA segments get letters based on which area they are in.

SAX

- discretize the time series
- results in one *word*

MSAX

- discretize each time series
- results in one *word* with one letter for each time series

MSAX for ECG Analysis

└ Methods

└ SAX and MSAX

└ Step 3: Discretization

- result is called word
- N is the alphabet size
- big thing here is that this gives defined probability to each letter; makes no sense for real numbers (like PAA values)
- simplifies time series even more
- creates discrete categories, can be more useful

SAX Discretization

Find breakpoints splitting $N(0, 1)$ into B equiprobable segments.
Assign a letter to each area, starting with a to the left-most segment.
PAA segments get letters based on which area they are in.

SAX

- discretize the time series
- results in one word

MSAX

- discretize each time series
- results in one word with one letter for each time series




Figure 3: SAX (MITBIH/100, $w = 18$, $T = 360$, $B = 4$)

Step 4: Distance Measure

MINDIST

A distance measure is defined to compare two SAX words. It is defined for a pair of letters, distances between words are sums of distances between letters.

Table 1: Difference matrix for $B = 4$

	a	b	c	d
a	0	0	0.67449	1.34898
b	0	0	0	0.67449
c	0.67449	0	0	0
d	1.34898	0.67449	0	0

MSAX for ECG Analysis

└ Methods

└ SAX and MSAX

└ Step 4: Distance Measure

- distance is based on letter pairs
- SAX: sqrt of sum of squared distance
- MSAX: sqrt of sum of squared distance; also sum all leads
- this lower-bounds the euclidean distance, meaning that results in SAX should hold true for the real data too

MINDIST

A distance measure is defined to compare two SAX words. It is defined for a pair of letters, distances between words are sums of distances between letters.


Table 1: Difference matrix for $B = 4$

	a	b	c	d
a	0	0	0.67449	1.34898
b	0	0	0	0.67449
c	0.67449	0	0	0
d	1.34898	0.67449	0	0

HOTSAX

- “brute-force” discord discovery is slow, needs T^2 operations
- HOTSAX speeds up discord discovery by considering:
 - discords are rare, start with rarest segment
 - similar segments have similar distances, consider together
- HOTSAX detects anomalies, it is not a classifier
- it uses SAX and MSAX for dimensionality reduction

MSAX for ECG Analysis



- "brute-force" discord discovery is slow, needs T^2 operations
- HOTSAX speeds up discord discovery by considering:
 - discords are rare, start with rarest segment
 - similar segments have similar distances, consider together
- HOTSAX detects anomalies, it is not a classifier
- it uses SAX and MSAX for dimensionality reduction

- this is the basic idea that can speed up the process
- it is not guaranteed to do so, but it does not decrease efficiency
- this speeds up the process even more as we have fewer elements
- because of lower bounding, it still gives accurate results

Implementation

- SAX, MSAX, HOTSAX was implemented in Julia (scientific programming language)
- used annotated digital ECGs from the MIT-BIH arrhythmia database
- HOTSAX was performed for different w , B , subsequence lengths
- results were exported to CSV file and analyzed using the R programming language

MSAX for ECG Analysis

- └ Preliminary Results
- └ Implementation
- └ Implementation

- SAX, MSAX, HOTSAX was implemented in Julia (scientific programming language)
- used annotated digital ECGs from the MIT-BIH arrhythmia database
- HOTSAX was performed for different w , B , subsequence lengths
- results were exported to CSV file and analyzed using the R programming language

- fast, type support, great libraries, JIT compilation
- ecgs have all heart beats annotated
- know which are normal, diseases, noise, etc
- 48 recordings of 30 minutes
- w - paa segments; B - alphabet size; subsequence length for HOTSAX

Preliminary Results

- compared SAX and MSAX using the top $k = 80$ discords (816 sets of discords total)
- analyzed the relevance of results with recall (sensitivity)
- recall for MSAX is higher compared to SAX
- if SAX is applied to two leads and the results combined, it slightly outperforms MSAX

MSAX for ECG Analysis

- └ Preliminary Results
 - └ Preliminary Results
 - └ Preliminary Results

- compared SAX and MSAX using the top $k = 80$ discords (816 sets of discords total)
- analyzed the relevance of results with recall (sensitivity)
- recall for MSAX is higher compared to SAX
- if SAX is applied to two leads and the results combined, it slightly outperforms MSAX

- how many relevant items are selected
- recall = true positive / (true positive + false negative)
- this is done because for medical things it is more useful to look at a couple too many segments than not enough




Figure 4: Boxplot comparing Recall for MSAX and single-lead SAX

MSAX for ECG Analysis

- └ Preliminary Results
- └ Preliminary Results

- msax: average = 17.5%
- sax: average = 6.4%




Figure 4: Boxplot comparing Recall for MSAX and single-lead SAX




Figure 5: Boxplot comparing Recall for MSAX and dual-lead SAX

MSAX for ECG Analysis

- └ Preliminary Results
- └ Preliminary Results

- msax: average = 17.5%
- sax: average = 18.5%




Figure 5: Boxplot comparing Recall for MSAX and dual-lead SAX

Remaining Tasks

- perform tests for statistical significance of the result
- analyze the outliers visible in the boxplots
- compute more sets of discords with different parameters
- explore the influence of the parameters on the result

MSAX for ECG Analysis

- └ Preliminary Results
 - └ Remaining Tasks
 - └ Remaining Tasks

- perform tests for statistical significance of the result
- analyze the outliers visible in the boxplots
- compute more sets of discords with different parameters
- explore the influence of the parameters on the result

- for example t-test, biserial correlation

Thank You!

References I

- [1] G. B. Moody and R. G. Mark, *MIT-BIH Arrhythmia Database*, physionet.org, 1992. DOI: 10.13026/C2F305.
- [2] “The top 10 causes of death,” (), [Online]. Available: <https://www.who.int/news-room/fact-sheets/detail/the-top-10-causes-of-death> (visited on 05/02/2021).
- [3] M. Anacleto, S. Vinga, and A. M. Carvalho, “MSAX: Multivariate Symbolic Aggregate Approximation for Time Series Classification,” in *Computational Intelligence Methods for Bioinformatics and Biostatistics*, P. Cazzaniga, D. Besozzi, I. Merelli, and L. Manzoni, Eds., ser. Lecture Notes in Computer Science, Cham: Springer International Publishing, 2020, pp. 90–97. DOI: 10.1007/978-3-030-63061-4_9.
- [4] Kligfield Paul, Gettes Leonard S., Bailey James J., *et al.*, “Recommendations for the Standardization and Interpretation of the Electrocardiogram,” *Circulation*, vol. 115, no. 10, pp. 1306–1324, 2007. DOI: 10.1161/CIRCULATIONAHA.106.180200.

References II

- [5] L. Xie, Z. Li, Y. Zhou, *et al.*, “Computational Diagnostic Techniques for Electrocardiogram Signal Analysis,” *Sensors*, vol. 20, no. 21, p. 6318, Nov. 5, 2020. DOI: 10.3390/s20216318.
- [6] J. Lin, E. Keogh, S. Lonardi, and B. Chiu, “A symbolic representation of time series, with implications for streaming algorithms,” in *Proceedings of the 8th ACM SIGMOD Workshop on Research Issues in Data Mining and Knowledge Discovery - DMKD '03*, San Diego, California: ACM Press, 2003, pp. 2–11. DOI: 10.1145/882082.882086.
- [7] C. Zhang, Y. Chen, A. Yin, *et al.*, “Anomaly detection in ECG based on trend symbolic aggregate approximation,” *Mathematical Biosciences and Engineering*, vol. 16, no. 4, pp. 2154–2167, 2019, ISSN: 1547-1063. DOI: 10.3934/mbe.2019105.
- [8] E. Keogh, J. Lin, and A. Fu, “HOT SAX: Efficiently Finding the Most Unusual Time Series Subsequence,” in *Fifth IEEE International Conference on Data Mining (ICDM'05)*, Houston, TX, USA: IEEE, 2005, pp. 226–233. DOI: 10.1109/ICDM.2005.79.