

) + h

CS 49 Section

Week 6

Surajit A Bose



Agenda

+

- Logistics and check-ins
- Review of lecture concepts
 - Boolean expressions
 - Control flow
- Section Problems:
 - o <u>Dog Year Calculator</u>
 - o <u>Finding Factors</u>
 - o Rock, Paper, Scissors









How to get hold of me / get help+

4

- The <u>section forum</u>, 24 hr turnaround
- Email: bosesurajit@fhda.edu, 24 hr turnaround
- Office hours:
 - On campus: Tuesdays 12:00 noon to 1:30 pm, room 4218 in the STEM center. Entry is from room 4213
 - By appointment on Zoom
- Other resources:
 - Contact Lane via Canvas
 - Online or in-person tutoring via the STEM center (Room 4213)





Check In

+ 32

Any questions about:

- The **random** module and/or the **math** library
- Variables (names, types, values, assignment, casting)
- Constants
- Arithmetic operators and precedence (**, unary -, *, /, //, %, +, -)
- Compound operators (+=, -=, *=, etc)
- Problems from the homework or extra credit
- Anything else?

Please take the Zoom poll! And thanks to those who filled out the survey!



Lecture Review: Booleans

Boolean Expressions

+

- Reminder: an expression is a statement that can be evaluated
- A boolean expression evaluates to one of two values: True or False
- Like arithmetic expressions:
 - Boolean expressions are built using operators
 - The result is typically stored in a variable
 - For example, given a whole number greater than 1, we could set a
 variable is_prime to the value True or False for that number
- Boolean operators are of two types:
 - Comparison
 - Logical





Boolean Operators: Comparison +

- The boolean comparators are similar to the ones in math
- Given x = 3 and y = 4:

```
o x == y - 1  # x equals y minus 1
o x + 1 != y  # x plus 1 not equal to y
o x < y  # x less than y
o x <= y  # x less than or equal to y
o x > y  # x greater than y
o x >= y  # x greater than or equal to y
```



Boolean Operators: Comparison +

4

- The boolean comparators are similar to the ones in math
- Given x = 3 and y = 4:

```
\circ \mathbf{x} == \mathbf{y} - \mathbf{1} # x equals y minus 1
                                                       True
o x + 1 != y  # x plus 1 not equal to y
                                                       False
0 X < Y
               # x less than y
                                                       True
                 # x less than or equal to y
○ X <= Y</p>
                                                       True
0 X > Y
                  # x greater than y
                                                       False
                   # x greater than or equal to y
○ x >= y
                                                       False
```



Boolean Operators: Comparison +

4

- Note that == and = are very different beasts!
 - \circ x == y 1 is not the same as x = y 1
 - One is an expression: it checks whether the operands on the left and right sides of the operator are equal
 - The other is an assignment: it evaluates the expression on the RHS and stores the resulting value into the variable on the LHS
- Comparison operators can be chained:
 - \circ **x** < **y** and **y** < **z** can be expressed as **x** < **y** < **z**, to check whether the value of **y** is between the values of **x** and **z**





Boolean Operators: Logical

- The logical operators are and, or, and not
- and is True only when both of its operands are True:
 - 3 < 5 and 5 >= 4 are both True, so (3 < 5) and (5 >= 4) is True
 - 3 < 5 is True but 5 < 4 is False, so (3 < 5) and (5 < 4) is False
- or is True when at least one of the operands is True:
 - 3 < 5 and 5 >= 4 are both True, so (3 < 5) or (5 >= 4) is True
 - 3 < 5 is True and 5 < 4 is False, but (3 < 5) or (5 < 4) is True
 - 3 > 5 is False and 5 < 4 is False, so (3 > 5) or (5 < 4) is False
 </p>
- Short circuiting evaluation: operands are evaluated from left to right, so
 - for and, if the left operand is False, the right operand is never evaluated
 - o for or, if the left operand is True, the right operand is never evaluated





Boolean Operators: Logical

- The logical operators are and, or, and not
- not simply reverses the truth value of its operand:
 - 3 > 4 is False, so not (3 > 4) is True
 - o if x < y is True, then not (x < y) is False
 - o if x < y is True, then not (x >= y) is True
- Note the opposites:
 - The opposite of == is !=
 - o The opposite of < is >=
 - The opposite of > is <=
- So if x < 5 is False, then not (x < 5) is True and x >= 5 is True



Operator Precedence

+ 3

From highest to lowest:

- Parentheses
- Arithmetic operators:
 - Exponentiation
 - Unary negation
 - Multiplication, division, integer division, modulus
 - Addition, subtraction
- Comparison operators: equals, less than, etc, all identical in precedence
- Logical not
- Logical and, or





Operator Precedence

4

- Use parentheses rather than relying on implicit precedence
 - x + (y / z) is clearer than x + y / z, even though they are
 equivalent
- Watch out for the higher precedence of logical not!
- If **x** and **y** are both **False**, what is the value of:
 - o not x and y
 - o not (x and y)
 - o not x or y
 - o not (x or y)



Operator Precedence

+ 32

- Use parentheses rather than relying on implicit precedence
 - \circ **x** + (**y** / **z**) is clearer than **x** + **y** / **z**, even though they are equivalent
- Watch out for the higher precedence of logical not!
- If x and y are both False, what is the value of:

```
    not x and y # (not False) and False False
    not (x and y) # not (False and False) True
    not x or y # (not False) or False True
    not (x or y) # not (False or False) True
```









Flashback to Week 2 ...



Control Flow Overview

- while loop: Continuously performs a block of code until a given boolean expression (aka the loop condition) is evaluated to False
- **if** statement: Performs a block of code only when a boolean expression (aka the **if** condition) is **True**, and only once
- **if-else** statement: Performs a block of code when a boolean expression is **True**, or a different block (aka the **else** condition) when the expression is **False**. Either block is performed only once
- **if-elif-else** statement: Performs one of three or more blocks of code depending on which boolean expression is **True**. Only one block of code is performed, and only once
- for loop: Performs some block of code a specific number of times

- The while loop is governed by a boolean expression
- If the expression evaluates to False, the loop is never entered and any code inside the loop is ignored
- If the expression evaluates to True, the loop is entered and the block of code inside it is executed
- At the end of the code block, the boolean is re-evaluated. If the expression is still True, then the loop is re-entered.
- This continues until the boolean evaluates to False.
- This loop is also called an *indefinite loop* because it will run until the associated condition becomes False.

- Beware of infinite loops, where the boolean will never be False!
- Something inside the loop body must eventually alter the loop condition.
- The following code fragment is intended to allow employee lookups based on employee ID numbers. The user enters employee ID numbers one after another, entering '-1' when all lookups are done:

```
employee_id = input("Enter employee ID number: ")
while int(employee_id) != -1 :
    # Some code here to process employee in some way
    next_id = input("Enter employee ID number: ")
```

- Beware of infinite loops, where the boolean will never be False!
- Something inside the loop body must eventually alter the loop condition.
- The following code fragment is intended to allow employee lookups based on employee ID numbers. The user enters employee ID numbers one after another, entering '-1' when all lookups are done:

```
employee_id = input("Enter employee ID number: ")
while int(employee_id) != -1 :
    # Some code here to process employee in some way
    employee_id = input("Enter employee ID number: ")
```

- In this example, the loop continues until the user enters -1.
- This value is called a sentinel, as it guards against the loop going on forever by signalling that the loop should terminate
- Sentinels are often declared as constants

```
SENTINEL = -1
def main():
    employee_id = input("Enter employee ID number: ")
    while int(employee_id) != SENTINEL :
        # Some code here to process employee in some way
        employee_id = input("Enter employee ID number: ")
```



if-elif-else Statement

- The **if-elif-else** construction allows us to check multiple conditions
- For example, to determine whether a given year is a leap year.

```
if year % 4 :
    is_leap = False
elif (year % 100 == 0) and (year % 400) :
    is_leap = False
else :
    is leap = True
```

Note: if year % 4 is equivalent to if (year % 4) != 0





if-elif-else Statement

• What is wrong with this code?

```
x = 5
y = 12
if x = y:
    print("They're equal")
elif x < y:
    print("x is smaller!")
else:
    print("y is smaller!")</pre>
```

if-elif-else Statement

• What is wrong with this code?

```
x = 5
y = 12
if x == y:
    print("They're equal")
elif x < y:
    print("x is smaller!")
else:
    print("y is smaller!")</pre>
```



for Loop

- + 3
- The **for** loop performs its block of code a specified number of times
- It is controlled by a loop variable, usually **i** (for index)
- i is often specified as a range
- Syntax: for i in range(start, stop, step)
 - Default start is 0
 - A specified stop is always required
 - Default step is 1; if a different one is needed, must specify start too
- **i** enters the **for** loop with value 0 or the specified start, increments by 1 or the specified step, and terminates the loop when **i** == **stop**
- Note that the loop does not execute when i has the value of stop.





for Loop

• Example: First 10 odd numbers

```
for i in range(1, 21, 2):
    print(i)
```

Example: Countdown

```
for i in range(10, 0, -1):
    print(i)
print("Blast off!")
```





Section problem: Dog Year Calculator

https://codeinplace.stanford.edu/foothill-cs49/ide/a/dogyearssection

Dog Year Calculator

+ 3

 One dog year is the equivalent of seven human years. Write a Python program that prompts the user to enter an age in human years. Output the equivalent age in dog years:

Enter an age in human years: 12
The age in dog years is 84

- Check that the user enters a positive integer
- Continue prompting for a human age until the user enters zero
- What constants should we use?
- As what type should the input from the user be cast?







+ 42

Here is an example of what one run of your program should look like (user input is *italicized*):

Enter an age in human years: -12

Sorry, please enter a positive number or 0 to exit

Enter an age in human years: 13

The age in dog years is 91

Enter an age in human years: 0



Section problem: Finding Factors

https://codeinplace.stanford.edu/foothill-cs49/ide/a/findingfactors

Finding Factors

+ 4

- Ask the user to enter an integer
- Check that the number is greater than zero
- Print all the factors of the given number one by one
- Ask for another number and repeat until the user enters zero
- What constant should we use?
- How do we obtain the factors?

Here is an example of what one run of your program should look like (user input is *italicized*):

```
Your number: -10
Please input a positive number
Your number: 42
1
```

3

7

21

42 Your number: *53*

1

53

Your number: 0





That's all, folks!

Next up: Graphics!