

LEVERAGING CONTINUOUS INTEGRATION PROCESS  
TO IMPROVE SOFTWARE REUSE

Master Thesis

submitted: January 2017

by: Piero A. Divasto Martínez  
born March 10th 1986  
in Iquique  
Chile

Student ID Number: 012345

---

University of Mannheim  
Chair of Software Engineering  
B6, 26, Gebäudeteil C  
D – 68159 Mannheim  
Phone: +49 621-181-1691, Fax +49 621-181-1692  
Internet: <http://swt.informatik.uni-mannheim.de/>



## Abstract

On the one hand we have the Douglas McIlroy's vision [32] of a software system composed of already existent components. Where you basically put different components, that already exist, together in order to form the system is being built. Although the IT industry has tried for many years to improve the speed and reduce costs of software development by reusing components, this vision is still the exception rather than the rule. On the other hand we have Continuous Integration which is a software development practice where members of a team integrate their work frequently, usually each person integrates at least daily, thus leading to multiple integrations per day. Each integration is verified by an automated build (including test) to detect integration errors as quickly as possible. In this work we present a novel approach that improves the reuse of software by leveraging continuous integration process. Also we present an unobtrusive tool as a proof-of-concept that extracts interface signatures and test classes from a given project, which are sent to a code-search engine to retrieve similar components based on text-driven and test-driven search techniques



# Contents

<b>Abstract</b> . . . . .	iii
<b>List of Figures</b> . . . . .	ix
<b>List of Tables</b> . . . . .	xi
<b>List of Abbreviations</b> . . . . .	xi
<b>1. Introduction</b> . . . . .	1
<b>2. Foundations</b> . . . . .	3
2.1. Software Reuse . . . . .	3
2.1.1. Benefits of Software Reuse . . . . .	4
2.1.2. Challenges of Software Reuse . . . . .	4
2.1.3. Code-search engines . . . . .	6
2.1.3.1. Merobase . . . . .	8
2.1.4. Component retrieval techniques . . . . .	9
2.1.4.1. Test-driven search . . . . .	10
2.1.5. Ranking components . . . . .	11
2.1.5.1. SOCORA . . . . .	12
2.2. Continuous Integration . . . . .	15
2.2.1. What is Continuous Integration? . . . . .	15
2.2.1.1. CI Tools . . . . .	16
2.2.2. Benefits in adopting CI/CD . . . . .	18
2.2.3. Challenges in adopting CI/CD . . . . .	19
2.2.4. Successful CI practices . . . . .	20
2.3. Microservices . . . . .	22
2.3.1. Characteristics of a Microservice Architecture . . . . .	22
<b>3. Usage Scenario</b> . . . . .	27

---

<b>4. Simile</b>	31
4.1. Assumptions	33
4.2. Design	33
4.3. Implementation	34
4.3.1. Simile	35
4.3.2. Cloner	36
4.3.3. Interface signature and test class extraction	37
4.3.4. SOCORA Integration	39
4.3.5. Email result	42
4.3.6. HTTP Controller	45
4.4. CI integration	48
<b>5. Discussion</b>	49
<b>6. Future Work</b>	51
<b>7. Conclusion</b>	53
<b>Bibliography</b>	55
<b>Appendix</b>	61
<b>A. Simile - Code</b>	63
A.1. de.unimannheim.informatik.swt.simile	63
A.1.1. de.unimannheim.informatik.swt.simile.controllers	67
A.1.2. de.unimannheim.informatik.swt.simile.model	71
A.1.3. de.unimannheim.informatik.swt.simile.services	72
A.1.4. de.unimannheim.informatik.swt.simile.util	97
<b>B. Installation of Simile</b>	99
B.1. Installation of Jenkins	99
B.1.1. Docker	99
B.1.1.1. Docker on macOS	99
B.1.1.2. Docker on Linux	100
B.1.2. Jenkins in Docker	101
B.1.3. Jenkins in Tomcat 9	104

---

B.2. Simile Jenkins Plugin installation . . . . .	106
B.3. Simile in Tomcat 9 . . . . .	107





## List of Figures

2.1. The test-driven reuse <i>cycle</i> extracted from [20] . . . . .	11
2.2. Schematic illustration of SOCORA ranking approach [25] . . . . .	13
2.3. SOCORA and Merobase integration (extracted from [25]) . . . . .	14
2.4. The three main states of Git [5] . . . . .	17
4.1. Simile approach . . . . .	32
4.2. Overview of implementation's design . . . . .	33
4.3. Future scenario of Simile supporting several CI Servers . . . . .	34
4.4. Textual search result email . . . . .	44
4.5. Test-driven search result email . . . . .	45
B.1. Docker for Mac installation . . . . .	100
B.2. First page of Jenkins setup . . . . .	103
B.3. Second page of Jenkins setup . . . . .	103
B.4. Third page of Jenkins setup . . . . .	104
B.5. Jenkins home page . . . . .	104
B.6. Tomcat home page . . . . .	105
B.7. Manage Jenkins option . . . . .	106
B.8. Manage Plugins option . . . . .	106
B.9. Upload Plugin section . . . . .	106



## List of Tables

2.1. Potentially reusable aspects of software projects according to [14].	4
---	---



# 1. Introduction

Building software using already existent components is not new. During the 1960s Douglas MacIlroy came up with this vision of a software system composed of components. Where you basically put different pieces (components), that already exist, together in order to form the system being built. During the next 50 years of MacIlroy's vision, the IT industry has tried to improve the speed and reduce the cost of development by reusing software, however this vision is still far for being a reality.

This process has attracted the attention of the industry due to its alleged benefits. Reduction of redundancies, costs reduction, quality improvements, and fostering innovation are some of the benefits that come with reusing software. However this is not an easy task.

The adoption of suitable reuse strategies is pretty challenging as it takes place in a multifaceted environments which incorporate aspects spanning from technical to organizational at different level of abstractions [1]. In general the challenges can be divided in organizational and technical [20, 1]. In the former, problems such as organizational structure, inertia, knowledge, management, among others might affect the success of the implementation of software reuse. For the latter, four core problems have been identified in the literature to implement a sustainable reuse repository: the repository problem [43], the representation problem [37], the usability problem[16], and the retrieval problem [39].

The rise of open-source movement, the improvements in the Internet connectivity, the advances in database, and the emergence of code-search engines have clearly solved the first problem. Techniques such as ranking approaches like SOCORA [25] or the ranking based on use relations presented by Inoue et al., and the idea of parsing source code in order to extract objects introduced by Koders.com <sup>1</sup> have addressed the representation problem. Furthermore test-driven search technique [19, 20] promises to solve the representation, usability and retrieval problems.

---

<sup>1</sup>Discontinued.

On the other hand we have Continuous Integration (CI), which is a software development practice where members of a team integrate their work frequently, usually each person integrates at least daily, thus leading to multiple integrations per day. Each integration is verified by an automated build (including test) to detect integration errors as quickly as possible. Many teams have found that this approach leads to significantly reduced integration problems and allows a team to develop cohesive software quicker [9].

Here is when the following questions came up: *How can Software Reuse and Continuous Integration be best married?*

Software projects that adopt continuous integration normally adopt the agile development technique called test-driven development (TDD), where a test case is created before the actual code that needs to be implemented. Thus, in addition with the frequent commits made by the developers, we found a great chance to improve the chances of reusing software components. Every time new code is pushed to the version control server (VCS), the CI server is triggered. At this moment we are able to analyze the source code and extract test class, along with the interface signature, to send them to a code-search engine. This engine will retrieve the result candidates that meet the functional requirements of the test classes, and then they will be sent to the developers. Consequently the team will realize that what they are working on might be already available in the internet so they would not need to re-implement the same again.

In the following chapters we explain with further details how this approach works. First, in Chapter 2 we provide a background for the approach. Then in Chapter 3 we explained a usage scenario in order to motivate and strengthen the approach which is presented in Chapter 4. There we detail our approach, how we implement it, and the benefits of this proposal. In Chapter 5 and 6 we discuss about potential pros/cons of this work and future work. We finalize this document presenting the conclusions.

## 2. Foundations

In this chapter we will explain the foundations needed to know to understand the work proposed in this document. First we explain what Software Reuse means, its benefits, challenges, code-search engines, component retrieval techniques, and ranking components. Then we talk about Continuous Integration, its benefits, challenges, and successful CI practices. Finally we describe Microservices and its characteristics.

### 2.1. Software Reuse

Douglas McIlroy [32] envisaged in the 1960s a software system composed of already existent components. Where you basically put different components, that already exist, together in order to form the system is being built. Although the IT industry has tried for many years to improve the speed and reduce costs of software development by reusing components, the McIlroy's vision is still the exception rather than the rule.

Despite the fact that it is possible to find several definitions of software reuse in the literature, most of them are similar to the definition proposed by Krueger [27]:

*"Software reuse is the process of creating software systems from existing software rather than building software systems from scratch"*

Since we already have a formal definition of software reuse, the next question would be: What can be reused?. To this regard, the work of [14] defined a list 2.1 of potentially reusable software artifacts:

However, reuse traditionally means the reuse of code fragments and components [34]. When we talk about components, we mean any cohesive and compact unit of software functionality with a well defined interface [22]. Therefore a component can be simple classes or even web-services or Enterprise Beans.

1. architecture	6. estimates (templates)
2. source code	7. human interfaces
3. data	8. plans
4. designs	9. requirements
5. documentation	10. test cases

Table 2.1.: Potentially reusable aspects of software projects according to [14].

Software reuse emerges as a solution for the so called software development crisis [26]. Organizations face several problems in software development including increased costs, delayed schedules, unsatisfied requirements, and software professional shortage. Therefore, by reusing software components projects can reduce time-to-market, lower development costs, and increase software quality [13].

### 2.1.1. Benefits of Software Reuse

Software reuse has not failed to attract the attention of industry due to its alleged benefits. In the industry the need of reduction of redundancies, as well as costs reduction and quality improvements is perceived. Moreover, the vision of fostering innovation and market penetration due to shorter production cycles promised obvious strategic business advantages [1]. Research literature has reported benefits from successful adoption of software reuse:

- Lower cost and faster development
- Higher quality
- Standardized architecture
- Risk reduction

Unfortunately the adoption of suitable reuse strategy is pretty challenging as it takes place in a multifaceted environment and, thus, incorporates aspects ranging from technical to organizational at different level of abstractions [1].

### 2.1.2. Challenges of Software Reuse

Although software reuse brings many benefits, it has failed to take off. Find the right third-party software component to be reused based on a well-defined specification is one of the most challenging approaches because it requires a clear-cut



matching of the potential reuse candidate and the given specification. Although there are several search tools available, most of them are still text-based and it neither reflect nor support the need to match the reuse candidates with the syntactic and semantic characteristics of a specification [20]. Hummel and Janjic, based on software retrieval literature, identified four problems for implementing a sustainable reuse repository.

- Repository problem [43]: This reuse repository should create and maintain a big enough software collection to provide promise search.
- Representation problem [37]: The repository should represent and index its content in a way that makes it easily accessible.
- Usability problem [16]: The repository should permit characterizing a desired component with reasonable effort and precision.
- Retrieval problem [39]: The repository should execute the queries with high precision to retrieve the desired component.

Although the two first challenges have been addressed in the last years, the last two have not been addressed completely. By the rise of open-source movement and the improvements in the Internet connectivity, software developers have got access to vast swathes of free software, thus the problem of sources of components is not a problem any more. Furthermore, with the advances in database and text search technologies code-search engines have made the creation of *Internet-scale* software repositories wherefore this repository problem can be regarded as solved [20]. For the second problem, clever ranking approaches such as the ranking proposed by [24] which ranks those components higher in the result list of a search that are more often used than others amongst the indexed files. Moreover, the idea of parsing source code in order to extract objects and their method introduced by Koders.com, where techniques that addressed the representation problem. However, the last two problems remain still in the focus of interest in the research community.

Beside the technical problems described above, organizational challenges and human factors have been identified as potential inhibitors to a successful implementation of reuse practices [35]. Business strategy, management commitment, and company culture are organizational factors that might affect software reuse [45]. Moreover, technical problems are strongly related to human factors, such as

cognitive efforts, program understanding, and motivation. In the work of [1] the following organizational obstacles were identified in the literature:

- **Organization structure:** Factors like competition, overlapping or unclear responsibilities, priority conflicts, and lack of coordination of reuse activities jeopardize the successful of reuse implementation.
- **Inertia:** Some organizations usually assess their managers and developers based on the success of their isolated projects, which incentives local optimization which impact reuse in a company-wide scale.
- **Knowledge:** If an organization plans to implement reuse practices, it needs clear position organization-wide and research into current methods and techniques for reuse.
- **Measurement:**
- **Management:** As implementing reuse practices require changes in governance strategies, it causes additional overhead that tends to be underestimated in the initial planning, which put at risk successful of reuse.
- **Economic:** Implementation of reusability requires investment and long-term support from management to resolve restrictive resource constraints.
- **Disincentives:** The quality of the reusable component candidates is one of the strongest disincentives. Moreover the criteria applied to measure developers and managers have an impact on their motivation to take part into reuse.

### 2.1.3. Code-search engines

Code-search engines are the heart of the new generations of reuse support tools. For example, Code Conjurer [22] uses Merobase component search engine, Code-Genie relies on Sourcerer [29] or ParseWeb that works over Google Code Search<sup>1</sup> [47]. Next we will describe some code search engines that are still online the time of this work.

- **searchcode<sup>2</sup>** searchcode is a free source code search engine. Code snippets and open source (free software) repositories are indexed and searchable.

---

<sup>1</sup>Shutdown January, 15 2012 [17]

<sup>2</sup><https://searchcode.com/> (accessed: 13.01.2017)

Most information is presented in such a way that you shouldn't need to click through, but can if required.

- NerdyData<sup>3</sup> It is a search engine for source code. It supports HTML, Javascript and CSS. With this search engine you can retrieve the web pages which are using a specific file. For example if you look up for *font-awesome.min.css* it will retrieve the sites that are using this file.
- Spars-J<sup>4</sup> It is a keyword and name matching code search engine on open source XML, Java and JSPs based on component rank and keyword rank algorithm.
- ComponentSource<sup>5</sup> It is a keyword-matching of component descriptions in a marketplace. Here you can find components for different platforms and technologies.
- Satsy: It is a source code search engine that implemented semantic search using input/output queries on multi-path programs with ranking. Based on survey to 30 participants, it retrieved more relevant results than Merobase [46].
- Merobase<sup>6</sup> Merobase is a component search engine that uses Lucene<sup>7</sup> to index programming language units from various open source repositories (such as Sourceforge, Google Code, or the Apache projects) and the open Web. Merobase, when crawling the code, its analysis software identifies the basic abstraction implemented by a module and stores it in a language agnostic description format. This description includes the abstraction's name, methods names, parameter signatures, among others.

Although Google or Yahoo! are not specialized code search engines, they are able to return more precise results than code search engines[21].

---

<sup>3</sup><https://nerdydata.com> (accessed: 13.01.2017)

<sup>4</sup><http://sel.ist.osaka-u.ac.jp/SPARS/> (accessed: 13.01.2017)

<sup>5</sup><https://www.componentsource.com/> (accessed: 13.01.2017)

<sup>6</sup><http://www.merobase.com/> - Official project deprecated, we use a local implementation

<sup>7</sup>Apache LuceneTM is a high-performance, full-featured text search engine library written entirely in Java. It is a technology suitable for nearly any application that requires full-text search, especially cross-platform [8].

### 2.1.3.1. Merobase

Merobase contains special parsers for each supported programming languages (currently it supports Java, C++, and C#, also it supports WSDL files, binary Java classes from JARs and .NET binaries), which extracts syntactical information, stores it in the index and search for it later. Moreover, it contains a special parser for JUnit which is able to extract the interface of the class under test from test cases.

Every time a user make a request to Merobase, the parsers described above are invoked and try to extract as much syntactic information from the query as possible. If none of the parsers recognizes parsable code in the query, it executes a simple keyword search. Based on parsed syntactic information, Merobase supports retrieval by class and operation names, signature matching and by matching the full interface of classes described before.

When a JUnit test case is submitted, a test-driven search is triggered. In this case, Merobase automatically tries to compile, adapt and test the highest ranked candidates. If a candidate is relying on additional classes, the algorithm uses dependency information to locate them as well. It is important to point out that the actual compilation and testing are not carried out on the search server itself, but on dedicated virtual machines within sandboxes. This is due to the fact that this ensures that the executed code does not have the possibility to do anything harmful to the user's system or bring the whole testing-environment down [20].

The current implementation of Merobase, which will we used in our prototype, has been enhanced in several way since the implementation described above [25]. Many new metrics are measured on the software components, both statically and dynamically, when the test cases executed on them. Also, the semantic retrieval of components has been improved by adding a better parser for Java components which supports the creation of entire class hierarchies. With this, information about the components' class hierarchies can be retrieved and stored.

On the other hand, the current implementation is populated with software components extracted from Maven projects mainly extracted from the Maven Central Repository<sup>8</sup>.

---

<sup>8</sup><https://repo1.maven.org/maven2/> (accessed: 15.01.2017)

#### 2.1.4. Component retrieval techniques

As we stated in 2.1.2, several problems of software reuse have been already addressed. Now one of the big problems is how to choose the so-called best component. In this section we will talk about the different component retrieval techniques proposed in the literature. Then we will explain further what test-driven component retrieval means.

[33] divided the component retrieval techniques in six independent groups:

- Information retrieval methods: It is basically the methods of information retrieval used for retrieving candidates by applying textual analysis to software assets. This group has high recall and medium precision.
- Descriptive methods: These methods add additional textual description of assets such as keyword or facet definition, to the textual analysis. These are high precision and high recall.
- Operational semantic methods: These methods use sampling of assets to retrieve candidates. They have very high precision and high recall.
- Denotational semantic methods: These methods use signature methods for retrieving candidates. They have very high precision and high recall.
- Structural methods: These methods deal with the structure of the components to retrieve candidates. This group has very high precision and recall.
- Topological methods: This is an approach to minimize the distance between query and reusable candidates. It is difficult to estimate or define recall and precision for these methods [33].

Although [33] proposed six groups, the last one relies on a *measurable* retrieval techniques so it can be considered as an approach for ranking the candidate components of a query [21].

In the work [21] several retrieval techniques were compared. They compared signature matching, text-based, name-based and interface-driven. These techniques were tested using Merobase search engine. The result they obtained was that the best technique is interface-driven in terms of precision.

Another technique that was presented in [19], is test-driven search. This technique uses test cases as a vehicle to retrieve the component candidates that fit better the requirements of the user. It promises to improve the precision of the searches in comparison with other techniques explained before. Below we will explain with further details how this techniques works.

#### 2.1.4.1. Test-driven search

Simple techniques for component retrieval such as keyword-driven search or signature-driven search may lead to a tons of candidates from which just a small group might be interesting for the user, in spite of the results fulfill the search criteria. This is due to the fact that not all of them fulfill the functional properties of the desire artifact. Here is where test-driven search comes to light.

Test-driven reuse approach was first introduced in [19]. It is a technique that emerges as a solution to the problem of retrieving so many irrelevant component candidates due to large amount of component in a repository. Specifically this technique deals with the usability and retrieval problems we explained before. It relies on test cases written by user (step a), then it extracts the different interfaces defined in the test case (step b), then it makes the search of reuse candidate (step c). Then it run the tests and *cleans* the result set of candidates that do not pass the tests (step d and e). Finally it shows the cleaned result set to the user (step f). This is the test-driven reuse cycle which can be seen in the figure 2.1.

An implementation of this *cycle* is Code Conjurer which can be found in [22] and [20]. This implementation is an Eclipse plugin that delivers proactively reuse recommendations by silently monitoring the user's work and triggering searches automatically whenever this seems reasonable. This tool supports interface-base searches and test-driven searches. For the latter, the tool has a background agent that monitors the required interface of the JUnit test case (also called, *class under test* (CUT)) written by the developer. When a change in the CUT happens, Code Conjurer sends the JUnit test to Merobase where the interfaces are extracted and used to search for results. Then the candidates retrieved are tested against the test provided and the candidates that do not pass the tests are removed. Finally the candidates are shown to the user in Eclipse.

Another tools that uses test-driven search are S6 [40] and CodeGenie [29].



necessary better than the last one. This is because factors such as ... are not being considered for ranking the components.

### 2.1.5.1. SOCORA

The ranking component approach presented in [25] works as follow. First, it establishes a partial ordering of candidates using non-dominated sets determined by non-dominated sorting without assuming any preferences of the user. Depending on the priorities assigned to each selected criterion, it then subrank each non-dominated set in a recursive way until all unique priorities and their corresponding subcriteria are applied to the current level of non-dominated sets, eventually resulting in nested subrankings. Note that in each step, when (new)non-dominated sets are determined by non-dominated sorting, the ranks of sets may change according to their partial ordering. In general, partial subranking are deliberately supported since the user is not required to assign specific priorities to all his/her selected criteria. The priorities are defined by simple integer values (highest value represent more priority than a lower value) with a default priority assignment of 1 for each selected criterion. If the user wants to assign a higher or lower priority to a selected criterion, he/she may increase or decrease the priority by 1 or even a larger number. Both unique and equal priority values may be assigned to selected criteria to establish either a partial or strict ordering. For each priority value, all corresponding criteria are selected to subrank each non-dominated set of non-distinguishable candidates. This process starts with the highest priority value and continues in descending order until the smallest priority value is reached [25]. The figure 2.2 is a schematic illustration of how the component ranking works.

**Merobase integration** The prototype of the ranking component approach is integrated with the component search engine Merobase to retrieve the candidates. The figure 2.3 shows how SOCORA<sup>9</sup> is integrated with Merobase.

In the first step the user's functional requirements are described as a JUnit test specification using a HTML5 web-based GUI. Here the user can specify a set of non-functional *quality* criteria that he/she thinks to be important for his/her needs, also he/she optionally can provide relative priorities to partially order

---

<sup>9</sup>SOCORA prototype <http://socora.merobase.com> (accessed: 13.01.2017)






Figure 2.2.: Schematic illustration of SOCORA ranking approach [25]

them. In the second step, the interface signatures in the JUnit test are extracted and a text-based search is performed in order to find suitable components. In the step 3, the result set of component from the second step are filtered by applying the JUnit test in turn, and those that do not match the filtering criteria are removed. Also, during the compilation and execution of the test, the metric selected by the user are evaluated. In the step 4, the information from the last step is used by the ranking algorithm to order the remaining components in the result set. In the step 5 the remaining components in the result set are displayed to the user. In the last step, the user can further analyze the component candidates by exploring the effects of different partial ordering (step 6a), explore different criteria (step 6b), and can group them in different way to shrink the result set (step 6c).




Figure 2.3.: SOCORA and Merobase integration (extracted from [25])

## 2.2. Continuous Integration

In this chapter we will explain what Continuous Integration (CI) means, we will describe the process steps, its benefits and challenges. Finally we will explain how CI can be leveraged in order to improve Software Reuse.

### 2.2.1. What is Continuous Integration?

The term can be found in the context of micro-processes development in the work of [4]. Then it was adopted by Kent Beck in his definition of Extreme Programming [2]. However, it was Martin Fowler who was credited with establishing the current definitions of the practices. Fowler defines CI as following:

CI is a software development practice where members of a team integrate their work frequently, usually each person integrates at least daily, thus leading to multiple integrations per day. Each integration is verified by an automates build (including test) to detect integration errors as quickly as possible. Many teams has found that this approach leads to significantly reduced integration problems and allows a team to develop cohesive software more rapid[9].

Continuous Integration emerges as a solution for the painful moment of software integration. Although the process of integrating software is not a problem for a one-person project, when it increases in complexity it becomes more problematic. For example, in the old days, a software was divided in modules and each of them were developed independently, once they done, those modules were put together in one step at the end of the project. Doing that led to all sorts of software quality problems, which are costly and often lead to project delays [7].

This step of module integration was a tense moment as errors and failures appeared and they were difficult to find and fix at that stage of the development. In this manner, instead of waiting till the end of modules development to integrate, CI proposes to integrate frequently, usually one person should integrate at least once a day.

Therefore we can break up the CI workflow in the following steps [9]:

#### **CI Workflow:**

- Developers check out code into their private workspaces

- When done, commit the changes to the repository
- The CI server monitors the repository and checks out changes when they occur.
- The CI server builds the system and runs unit and integration tests.
- The CI server releases deployable artifacts for testing.
- The CI server assigns a build label to the version of the code it just built.
- The CI server informs the team of the outcome of the build.
- In case the build or test failed, the team fixes the issue at the earliest opportunity.
- Continue to continually integrate and test throughout the project.

This uncomplicated workflow helps the development team to focus on the current code change till it is verified and validated. Moreover, it provides continuous feedback on the quality of the code.

#### 2.2.1.1. CI Tools

Although the CI is tool agnostic, the selection of them depends on the project, framework in use, skill-set of the stakeholders and other factors. There are however two must-have tools of any CI system: (1) the version control system (VCS) and (2) the CI server.

The most popular VCS are Git, Mercurial and SVN. On top of them, we can find Version Control Platforms (VCP) such as Github, Gitlab or Bitbucket. In terms of CI servers, we can find Jenkins, Hudson, GoCD as open source projects; TravisCI, CircleCI, CodeShip and Team City as commercial tools.

Therefore choosing the appropriate tools is about finding the balance between price, setup, configuration efforts, ease-of-use, integration capabilities between the selected tools, framework suitability and maintainability in respect to current code base.

**Git** Within the several different VCSs available, Git is one of the most popular<sup>10</sup>. Git emerges in 2005 as an alternative to BitKeeper<sup>11</sup> after the break

---

<sup>10</sup><https://rhodecode.com/insights/version-control-systems-2016> (accessed: 14.01.2017)

<sup>11</sup><https://www.bitkeeper.com/> (accessed: 13.01.2017)

of the relationship between the commercial company behind BitKeeper and the community that developed the Linux kernel [5].

The main difference between Git and the other VCSs is the way it thinks about its data. Other VCSs such as Subversion, CVS, Perforce, and so on, think of the information they keep as a set of files and the changes made to each file over time. On the other hand, Git thinks its data like a set of snapshots of a miniature file system. Therefore, every time a user commits, or save the state of the project, Git basically takes a picture of what all the files look like at that moment and store a reference to that snapshot. In addition, Git has three main states where the files can reside in: committed, modified, and staged. Committed means that the data is stored in the local database. Modified means that the file was modified but it has not been committed yet. And staged means that the modified file has been marked to go into the next commit [5]. The figure 2.4 depicts these three states.




Figure 2.4.: The three main states of Git [5]

The git directory is the core of Git as it is where the metadata and object database for a project is stored. The working directory is a single checkout of one version of the project. Finally, the staging area is a file which is generally stored in the Git directory. This file contains information about what will go into the next commit.

**Github** Github<sup>12</sup> is a web-based Git repository hosting service, which offers all the functionality of Git and its own features. It provides several collaboration tools such as wikis, bug tracking, feature requests, and task management as well as access control. Its development started in 2007 as a side project of P. J. Hyett and Chris Wanstrath [48] and it was officially launched on the 10th of April in 2008. Since then, Github has gained popularity through the community reaching more than 50 million projects hosted nowadays.

**Jenkins** Jenkins is an open source automation server developed in Java. It was originally founded in 2006 as *Hudson*, however a dispute with Oracle the community behind Hudson decided to change the project name to Jenkins<sup>13</sup>.

Jenkins enables developers to reliably build, test, and deploy their software. Its extensible and plugin-based architecture has permitted to create a tons of plugins to adapt the CI server to a multitude of build, test, and deployment automation workloads. In 2015, Jenkins surpassed 100.000 known installations making it the most widely deployed automation server<sup>14</sup>.

### 2.2.2. Benefits in adopting CI/CD

Several are the benefits that come with the adoption of Continuous Integration in a software project. In this section we will describe five areas that are improved after CI implementation [41]. It is important to point out that these benefits come along with other practices such as agile transformation [28] and lean software development [38].

- **Shorter time-to-market:** Many benefits come with the adoption of frequent releases. With fast and frequent releases it is possible to get feedback quickly from customer and market, thus the organization gets better understanding of their needs expectations [36]. With that it is possible to focus on the most relevant features. Another benefit of delivering frequently is waste reduction as features can be deployed as soon as they are done [30]. Furthermore, with frequent releases it is possible to experiment with new features easily and with low impact [36].

---

<sup>12</sup><https://github.com/> (accessed: 13.01.2017)

<sup>13</sup><http://archive.is/fl45> (accessed: 13.01.2017)

<sup>14</sup><https://jenkins.io/press/> (accessed: 13.01.2017)

- **Rapid feedback:** With frequent releases is possible to show progress to customers and by that get feedback quickly. With that the development team can focus on important features instead of waste time in features that are not relevant for the customers or the market.
- **Improved software quality:** Researches have reported a decreased in the number of open bugs and production incidents after adopting CI practices [31] and the link between software quality improvement and the heavy reliance on automated test combined with smaller more manageable releases [30].
- **Improved release reliability:** In the work of [36] was proved that a working deployment pipeline along with intensive automated testing and fast rollback mechanism positively affects release reliability and quality. With small and frequent releases fewer things can go wrong in a release according to [11]. In fact, reduction in the stress of developers and other stakeholder have been found by adopting CI [36] [6].
- **Improved developer productivity:** By automating deployment process, environment configuration and other non-value adding tasks, significant time saving for developers have been observed [42]. Also, in the work of [18] was observed that although the setup cost of a deployment pipeline can be high, after it is setup developers can focus on value adding software development works.

### 2.2.3. Challenges in adopting CI/CD

Adopting CI can be very beneficial for a software project as described above, however we can face some challenges that can jeopardize the successful implementation of it. According to the literature, there are seven common challenges in the implementation of a CI:

- **Change resistance:** Transforming the development of a project towards continuous integration practices requires investment and involvement from the entire organization [42]. Therefore any transformation in how an organization works, will receive a resistance on both a personal level and decision level within the organization.

- External constraint: As a software project is part of a context, external constraint may appear. Normally customer preferences and domain imposed restrictions are sources of constraints. For example in highly restricted domains, legal regulations may require extensive testing before new version can be allowed to enter production [42].
- QA effort: The automated tests suit needs to be exhaustive enough in order to ensure the quality of what is being built. Thus it can lead to increase QA efforts due to difficulties in managing the test automation infrastructure [42].
- Legacy code: Normally legacy software has not been design for being automatically tested and may cause integration failures which may inhibit the continuous deployment process. The ownership of legacy code might belong to another company or team which shift the testing responsibility and this might delay the deployment process.
- Complex software: If the complex if the software project is high, then setting up the CI workflow is more challenging [30].
- Environment management: Keeping all the environments used in development, testing and production sync and similar can be challenging. This is due to the fact that differences in the environment configuration can lead to undetected issues appear in production. Therefore is essential to have a good configuration management that provisions environments automatically [30].
- Manual testing: Although automated tests are very beneficial, some aspects of software need to be manually tested such as security issues, performance and UX/UI. Therefore heavy manual testing can impact the overall speed and smoothness of the process [30].

#### 2.2.4. Successful CI practices

In order to reduce the risks in adopting CI practices, eight principles, based on several literature reviews, were defined in [41] which should guide the CI implementation within organizations. These principles are generic solutions which can be adapted in most cases.



- Automate the build: The task that triggers the whole pipeline is the commit. After each commit, the next step should be build the binaries. The executable that result of the build, should go through the pipeline until it gets validated, verified and deployment ready.
- Make your build self-testing:
- Every commit should build on an integration machine
- Keep the build fast
- Keep the build green
- Test in a clone of the production environment
- Everyone can see what is happening
- Automate deployment

These 8 principles should guide the CI/CD implementation within organizations. The principles have been established as best practices through the validation of these concepts through several literature reviews [[42]; [31]; [44]]. They can be viewed almost as a design pattern for adopting CI/CD, offering a generic solution adaptable to most cases.

## 2.3. Microservices

Microservices is a software architecture is usually linked to Martin Fowler in its article [12]. It is an architectural styles that aim to develop applications as a suite of small services independently of each other. Each of this services runs in its process and they communicate with lightweight mechanisms (e.g. HTTP resource API). These services are built around business capabilities and independently deployed by fully automated deployment machinery. Also there is a bare minimum of centralized management of these services, which may be written in different programming languages and use different data storage technologies [12].

This architectural style emerges as a solution to the monolithic style due to its problems. An application built using monolithic architectural style is considered as a single unit with normally three main parts (figure ??): a client-side user interface (i.e. HTML, CSS, JavaScript running on user's machine), a database and a server-side application. The latter is a monolith as it handles HTTP request, execute domain logic, retrieve and update data from the database, and populates and/or select the HTML views sent to the client-side. As it is a single logical executable, any changes made in the system, no matter the size of it, require a build and a deploy of the whole server-side application. It is hard to keep a good modular structure, making it harder to keep changes that must affect one module within that module. Also it is hard to scale as it is necessary to scale the entire application rather than parts of it requiring greater resources. These problems are causing frustrations on people that are using this style, specially nowadays when applications are deployed to the cloud, leading to the microservices architectural style.

### 2.3.1. Characteristics of a Microservice Architecture

In the work of Fowler and Lewis [12] described a list of common characteristic of applications built using microservice architectural style. It is important to point out that all the applications using this style must confirm every characteristic of this list.

#### Componentization via Services

First of all it is important to explain the differences between libraries and

services as the primary way of componentizing is by breaking down software into services. On the one hand libraries are components that are linked into an application and called using in-memory function calls. On the other hand services are out-of-process components which communicate with a mechanism such as a web service request, or remote procedure call [12].

Splitting a software into services brings benefits such as services as components are independently deployable making it easy for changes, or services have more explicit component interfaces by using explicit remote call mechanisms.

### **Organized around Business Capabilities**

Normally in monolithic applications the development teams are divided by technology layers such as front-end team, server-side team and database team. However when teams are divided in this way, even simple changes can lead to a cross-team project taking time and budgetary approval.

In the Microservices approach this is taken in a different way by dividing the application into services organized around business capability. Thus services involve all needed for that business area, including user-interface (UI), database, business logic, and any other external collaboration. Therefore each team is cross-functional, including the full range of skills required for the development of it.

### **Products not Projects**

Usually software development follows a project model where the objective is to deliver some piece of software which, when it is done, is delivered to a maintenance team and the development team is disbanded.

Microservices approach follows the product model instead of project model. In the product model the development team takes full responsibility of the software, in other words it owns the product. This results in day-to-day contact of the developers with the users as they have to take on at least some of the support. Moreover this mentality ties in with the linkage to business capabilities as the focus is on how the software can assist its users to enhance the capabilities instead of put the focus on a list of functionality.

### **Smart endpoints and dumb pipes**

Microservices use the approach of smart endpoint and dumb pipes. Instead

of putting so much smart into the communication mechanism itself, microservices approach aim to be as decoupled and as cohesive as possible. In other word, a microservice works as a black-box which receives a request, applies a logic, and produces a response. Usually two protocols are used, HTTP request-reponse with resource API's and lightweight messaging (e.g. RabbitMQ, ZeroMQ).

### **Decentralized Governance**

Using a centralized approach brings consequences such as standardise on single technology which keeps the team to use the right tool for the job. In contrast to that microservices approach allows to use use the technology that fit the requirements best. For instance, if NodeJS is more appropriate for a service than Java there will not problem choosing it.

### **Decentralized Data Management**

Microservices approach prefer letting each service manage its own database, either different instances of the same database technology, or entirely different database systems - an approach called Polyglot Persistence [? ].

Although this approach has some implications for managing updates or increment of complexity, the benefits are worth it. The common approach to solve the former implication is using transactions but implement it in services is difficult, that is why microservice architectures emphasize transactionless coordination between services, assuming that consistency may be only eventual consistency and problems are dealt with by compensation operations. This is useful in order to respond quickly to demand. In spite of the fact that by using different technologies increases the complexity, it allows the teams to solve the problem with the right tool. For instance if a service needs to just retrieve pages by looking up its ID, a key-value database is more suitable than a relational database. Moreover, as many NoSQL databases are designed to operate over clusters, they can tackle larger volumes of traffic and data which is harder with vertical scaling [10].

### **Design for failure**

As a consequence of using microservice architecture, is that applications need to be designed so that they can tolerate the failure of services. As any service call could fail due to unavailability of the supplier service, the client service must respond as neat as possible.

Although this can be considered as a disadvantage in comparison to monolithic approach, using good monitoring and logging mechanism would help to overcome this. For instance a dashboard which display the status of the different services, current throughput, and latency would help to react in case one or more services go offline.

In conclusion, although microservices architectural style comes with many benefits, it also comes with several difficulties. By splitting up an application into services, we can simplify and speed up the release process, use the right tool for a job, or focus in how to assist better the user instead of a set of functionality. However we have to worry about changes to one service breaking its costumer, or deal with the increment of complexity.

It is important to consider that this style is not a silver bullet. As Fowler described in his blog post [12], the core of The Guardian website <sup>15</sup> was built as a monolith, however every new feature has been added as a microservice that uses the core's API.

---

<sup>15</sup>The Guardian: <https://www.theguardian.com/> (accessed: 04.02.2017).



### 3. Usage Scenario

Before getting into the approach we will propose a usage scenario to strength and motivate our approach which will be presented in the next Chapter. The following scenario is based on the usage scenario found in [25].

First of all we will imagine a software project about Base64 with the following characteristics. The project has adopted Continuous Integration as we described in Section 2.2, using Git as Version Control System, Jenkins as CI Server, and Java as programming language. Moreover the software is developed following the Test-driven development process.

Envisage the following scenario in which a development team is working or has code ownership of a web service application, and recognizes that she/he requires the ability to encode and decode information in the common Base64 format (e.g., the Base64 variant used in MIME transfer encoding [15]).

As the project is being developed using TDD, developers create a test that defines a function before it is implemented. For instance, if we follow the scenario, a member of the team will implement the method *encode* which accept an array of bytes decoded in Base64 and it will return an array of chars which represents the input decoded. Moreover the method *decode* that receives an array of chars and returns an array of bytes that represents the input encoded will need to be implemented too. However, as they are using TDD, this member must create a test of these methods. Listing 3.1 represents the methods *encode* and *decode* and the listing 3.2 represents the test class for these methods.

```
package de.unimannheim.informatik.swt.simile.poc.de.unimannheim.  
    informatik.swt.simile.poc.base64;
```

```
public class Base64 {
```

```
5     public char[] encode(byte[] decoded) {  
        throw new UnsupportedOperationException();  
    }
```

```

    public byte[] decode(char[] encoded) {
10      throw new UnsupportedOperationException();
    }

}

```

Listing 3.1: Base64.java

```

package de.unimannheim.informatik.swt.simile.poc.base64;

import de.unimannheim.informatik.swt.simile.poc.de.unimannheim.
    informatik.swt.simile.poc.base64.Base64;
import org.junit.Test;
5
import static org.junit.Assert.assertEquals;

public class Base64Test {

10    @Test
    public void test_rfc4648() throws Exception{
        Base64 base64 = new Base64();

        assertEquals(chars(""), (char[]) base64.encode(bytes("
            )))");
15        assertEquals(chars("Zg=="), (char[]) base64.encode(
            bytes("f")));
        assertEquals(chars("Zm8="), (char[]) base64.encode(
            bytes("fo")));
        assertEquals(chars("Zm9v"), (char[]) base64.encode(
            bytes("foo")));
        assertEquals(chars("Zm9vYg=="), (char[]) base64.encode(
            bytes("foob")));
        assertEquals(chars("Zm9vYmE="), (char[]) base64.encode(
            bytes("fooba")));
20        assertEquals(chars("Zm9vYmFy"), (char[]) base64.encode(
            bytes("foobar")));

        assertEquals(bytes(""), (byte[]) base64.decode(chars("
            )))");
        assertEquals(bytes("f"), (byte[]) base64.decode(chars("
            Zg==")));
        assertEquals(bytes("fo"), (byte[]) base64.decode(chars("

```



---

```

        "Zm8="))));
25    assertEquals(bytes("foo"), (byte[]) base64.decode(chars
        ("Zm9v")));
    assertEquals(bytes("foob"), (byte[]) base64.decode(
        chars("Zm9vYg==")));
    assertEquals(bytes("fooba"), (byte[]) base64.decode(
        chars("Zm9vYmE=")));
    assertEquals(bytes("foobar"), (byte[]) base64.decode(
        chars("Zm9vYmFy")));
    }
30
    protected byte[] bytes(String s) throws Exception {
        return s.getBytes("ASCII");
    }

35    protected char[] chars(String s) throws Exception {
        return s.toCharArray();
    }
}

```

Listing 3.2: Base64Test.java

Additionally, as the team adopted CI, developers should commit often the changes to the Git server. This action triggers the CI server which checkouts the code and runs the unit tests available. Therefore going along with the example given above, the class *Base64.java* and the test class *Base64Test.java* should be committed to the repository.

From this simple scenario emerge the following questions:

**How might the team realize that what they are working on has not been developed already?**

If we follow the example, the implementation of encode and decode in Base64 is very easy to find, however that does not mean that the team knows that at the moment they are developing. Therefore it would be very useful that an automatic tool analyzes the code and extracts the method signature so it would be able to make a code search for similar methods.

**How might we seize continuous integration in order to improve chances of reusing software?**

Continuous integration process seems to be a very good opportunity for

software reuse. According to CI workflow explained in 2.2.1 every change made in the code should be committed and pushed to the VCS. This pushed code is tested by the CI server and accepted if it passes all the tests otherwise it is rejected. This is a good chance to extract method signatures and make the code search named previously.

**Would TDD be helpful?**

According to TDD process before implementing a method a failure test should be implemented before. If we assume that and that every code change is committed and pushed to the VCS, we could also extract the test classes to search for similar components.

In the following Chapter we will answer these questions and present our approach that improve that chances of reusing software by seizing the use of Continuous Integration.

## 4. Simile

In this chapter we present our approach that seizes Continuous Integration process in order to recommend similar components that are being developed in a software project. The idea of integrating CI and Software reuse emerged with the following research question: *How can code search engines be best married with CI?*. The idea was to find a way where a team could seize the continuous integration process in order to find similar components to the components they are developing. Thus they would be able to reuse instead of implementing them from scratch reducing development time and costs. As an attempt to answer the question we implemented a tool (proof of concept) called Simile. This tool analyses the source code and extract information needed to find similar components.

Following the usage scenario explained previously in section 3, we will describe how our proposed approach works:




Figure 4.1.: Simile approach

In the first step (figure 4.1 - 1) the developer commits code to its local VCS. Then when the developer decides to push changes to the remote repository, the CI server is triggered (figure 4.1 - 2). In the next step (figure 4.1 - 3), Simile will analyse the code and extract information such as interfaces signatures and test classes. This information will be sent to SOCORA (figure 4.1 - 4) in order to find similar components. Then it will return a ranked list of similar components. Simile will receive this information and send this list to the developers by email (figure 4.1 - 5).

The main objective of Simile is to help the team to find similar components so they would be able to reuse them. Thus they would reduce time development and costs through reuse components that are already tested and ready to work.

In the following sections we will explain in details how Simile was implemented. Then we will detail how we integrate Simile into Continuous Integration server (Jenkins). After that we will explain how we integrate Simile and SOCORA for searching for similar components.

## 4.1. Assumptions

Following the usage scenario presented in Chapter 3 we made the following assumptions for the implementation of our proof-of-concept.

- In a normal situation, the usage scenario presented in the previous Chapter would fail because when the CI server runs the test, it will fail. Therefore the CI server would not accept the code committed to the repository. However this can be avoided in the configuration of the CI server. For that reason for the implementation of our proof-of-concept, we assume that the CI server will accept the code even if the test fail.

## 4.2. Design

Simile was formulated as microservice which was designed taking in account that there are several CI servers available. Although we used Jenkins as CI server for our prototype, Simile was designed as an agnostic tool. Figure 4.2 depicts an overview of the design of our implementation.




Figure 4.2.: Overview of implementation's design

Despite the fact that the design is rather simple, this allow us to connect Simile to any CI server available in the market without changing the core. For instance, if in the future we would like to support other CI servers such as Teamcity, TravisCI or Buddy, we would just need to develop a simple plugin with the same features of the plugin developed for this thesis. Figure 4.3 depicts this future scenario.




Figure 4.3.: Future scenario of Simile supporting several CI Servers

### 4.3. Implementation

In this section we will detail how the prototype was developed and the technologies used. First we will start explaining the Simile service which is the starting point of the whole process about cloning the project, analyse code, search components and send result. Then we will continue with the HTTP controller which receives the Git repository of the project to be analysed, the specific branch of the repository, and the email where the result will be sent. Then we will explain the Cloner object which is in charge of cloning the project locally. After that, we will explain how the tool analyses the code and extracts the interface signatures and test classes which will be used to make the requests to SOCORA. Next we will describe how we receive the result from SOCORA. Finally we will explain how we handle the result from the previous step and build the email that will be sent to user.

**NOTE:** The code snippet shown in the following subsections has been cleaned and it does not represent the source code. To see the source code with all the details, please refer to the appendix A or to the CD attached to this work.

### 4.3.1. Simile

The class `Simile.java` [A.1] is a Spring service which contains only one method, *searchForComponents*. This method receives four parameters, `repo`, `branch`, `folder`, and `recipient`. *repo* represents the Git repository of the project to be analysed. *branch* is the branch of the Git repository (optional). *folder* represents the name of the folder where the project will be cloned. Finally *recipient* is the email where Simile will send the result. Listing 4.1 represents the method.

```

1  @Async
2  public void searchForComponents(String repo, String branch, String
    folder, String recipient) throws IOException,
    InterruptedException {
3      Cloner cloner = new Cloner(repo, branch, folder);
4
5      cloner.cloneRepository();
6
7      File maintDir = new File(String.format("%s/src/main", folder
    ));
8      JavaClassHandler classes = new JavaClassHandler();
9      new DirectoryExplorer(classes, new JavaClassFilter()).
    explore(maintDir);
10
11     File testDir = new File(String.format("%s/src/test", folder
    ));
12     JavaClassHandler testClasses = new JavaClassHandler();
13     new DirectoryExplorer(testClasses, new JavaClassFilter()).
    explore(testDir);
14
15     logger.info(String.format("Classes found in project: %s",
    classes.getClasses().size()));
16     logger.info(String.format("Test classes found in project: %s
    ", testClasses.getTestClassesCode().size()));
17
18     this.makeRequestWithClasses(classes.getClassesMQLNotation(),
    recipient);
19     this.makeRequestWithTestClasses(testClasses.
    getTestClassesCode(), recipient);
20 }

```

Listing 4.1: Method `searchForComponents` of `Simile.java`

First, it clones the project in the server by calling the method *cloneRepository* of Cloner [A.8]. Then it analyses the Java main code of the project cloned and the test classes. When it analyses the code it extracts the interface signatures and the test classes, we explain how it does this process in section ???. With the result of the previous step, we make the requests to SOCORA to search for similar components.

It is important to notice that this method is asynchronous by the Java annotation *@Async*. This allows us to run this method many times in parallel (configured in SimileApplication.java A.3).

#### 4.3.2. Cloner

The class Cloner.java [A.8] is in charged of cloning the project in a local directory. The listing 4.2 represents the method *cloneRepository*.

```

1  public int cloneRepository() throws IOException {
2      int exitVal = 0;
3      try {
4          String command = this.setCommand(repo, branch, folder);
5          Process p = Runtime.getRuntime().exec(command);
6          StreamGobbler errorGobbler = new StreamGobbler(p.getErrorStream
              (), "INFO");
7          errorGobbler.start();
8          exitVal = p.waitFor();
9          return exitVal;
10     } catch (InterruptedException e) {
11         e.printStackTrace();
12     }
13     return exitVal;
14 }
```

Listing 4.2: Method cloneRepository of Cloner.java

This method runs the command *git clone* with the parameters *repo*, *branch*, and *folder*. The command is built by the private method *setCommand*. After running the command, the project is cloned locally under the folder with given *folder* name.



### 4.3.3. Interface signature and test class extraction

In this section we will explain how Simile explores the project cloned and extracts the interface signatures and test classes that will be sent to SOCORA to search for similar components.

After the project is cloned locally by the Cloner (4.3.2), Simile goes through the code and extract interface signatures of each class, and test classes. The signatures extracted are transformed into Merobase Query Language (MQL) notation, and the test classes are extracted as is. The snipped code 4.3 shows how the interface signatures are extracted and transformed into MQL. For extracting test classes the principle is the same, the difference is that we differentiate a Test class from another Java file if it contains the annotation *@Test*.

```

1  @Override
2  public void handle(int level, String path, File file) {
3      logger.debug(path);
4      logger.debug(Strings.repeat("=", path.length()));
5      try {
6          JavaClassVisitor jcv = new JavaClassVisitor();
7          jcv.visit(JavaParser.parse(file), null);
8          jcv.getMethods()
9              .forEach(method -> methods.add(
10                  this.getMethodMQLNotation(method.getNameAsString(),
11                                              method.getParameters(),
12                                              method.getType().toString())
13              ));
14          classes.put(jcv.getClassObj().getNameAsString(), methods);
15          methods = new ArrayList<>();
16          if(jcv.getTestClasses().size() > 0)
17              testClassesCode.addAll(jcv.getTestClasses());
18      } catch (IOException e) {
19          new RuntimeException(e);
20      }
21  }
22
23  private String getMethodMQLNotation(String methodName, NodeList<
24      Parameter> params, String returnType) {
25      List<String> paramTypes = new ArrayList<>();
26      params.forEach(param -> paramTypes.add(param.getType().
27          toString()));

```

```

26         logger.debug(
27             String.format("%s(%s):%s", methodName, StringUtils.
                join(paramTypes, ','), returnType)
28         );
29         return String.format("%s(%s):%s", methodName, StringUtils.
                join(paramTypes, ','), returnType);
30     }

```

Listing 4.3: Method handle of `JavaClassHandler.java`

In the class `JavaClassVisitor.java` we can see how Simile differentiate between a normal Java class and a test class. It implements the methods *visit* for a *ClassOrInterfaceDeclaration* and for a *MethodDeclaration* object of the abstract class `VoidVisitorAdapter`. The listing 4.4 show the implementation of these methods.

```

1  @Override
2  public void visit(ClassOrInterfaceDeclaration n, Object arg) {
3      super.visit(n, arg);
4      this.classObj = n;
5      if(n.toString().contains("@Test")) {
6          testClasses.add(n.toString());
7      }
8  }
9
10 @Override
11 public void visit(MethodDeclaration n, Object arg) {
12     super.visit(n, arg);
13     logger.debug(String.format("L[%s] — %s", n.getBegin().get(), n.
        getDeclarationAsString()));
14     methods.add(n);
15 }

```

Listing 4.4: Implementation of methods *visit* of `VoidVisitorAdapter` in `JavaClassVisitor.java`

To analyses the code we use the library Java Parser <sup>1</sup>. This library parses Java code and creates an AST <sup>2</sup>, which records the source code structure, javadoc and comments. Moreover, the library allows to change the AST nodes or create new ones to modify the source code.

<sup>1</sup><https://github.com/javaparser/javaparser> (accessed: 06.02.2017).

<sup>2</sup>Abstract syntax tree (AST): abstract syntax tree (AST), or just syntax tree, is a tree representation of the abstract syntactic structure of source code written in a programming language.

#### 4.3.4. SOCORA Integration

Our prototype uses SOCORA to search for components. After extracting the interface signatures and test classes from the project, Simile make requests to SOCORA using this information. SOCORA then searches for similar components using Merobase and ranks the candidates using non-functional requirements. Once it is done, SOCORA sends the result back to Simile.

Simile communicates with SOCORA by making HTTP requests using the interface signatures and the test classes extracted. The following snippet of code show how Simile is making the request for SOCORA 4.5.

```

1  private void textualSearchComponent(String method) throws
    IOException, SparkPostException {
2
3      CandidateSearchClient candidateSearchClient = new
        CandidateSearchClient(baseURI, auth(user, pass));
4      CandidateSearchRequest request = new
        CandidateSearchRequest();
5
6      int maxResults = 10;
7
8      String testClassSourceQuery = method;
9
10     request.setInput(testClassSourceQuery);
11     QueryParams queryParams = new QueryParams();
12     queryParams.setRows(maxResults);
13
14     queryParams.setArtifactInformation(true);
15     queryParams.setContent(true);
16
17     queryParams.setFilters(Arrays.asList(Filters.
        HASH_CODE_CLONE_FILTER, Filters.
        NO_ABSTRACT_CLASS_FILTER,
18         Filters.NO_INTERFACE_FILTER, Filters.
        LATEST_VERSION_FILTER, Filters.
        FUNCTIONAL_SUFFICIENCY_FILTER));
19     request.setQueryParams(queryParams);
20
21     // no test-driven search
22     request.setTestDrivenSearch(Boolean.FALSE);
23

```

```

24      // set ranking
25      queryParams.setRankingStrategy(Rankings.
          SINGLE_OBJECTIVE);

26
27      // set ranking criteria
28      List<RankingCriterion> rankingCriteria = Arrays.
          asList(
29          // textual score (Lucene/SolR)
30          RankingCriterionBuilder.rankingCriterion().
              withName("luceneScore").withObjective(
                  RankingCriterion.MAX)
31              .build());
32
33      queryParams.setRankingCriteria(rankingCriteria);
34
35      CandidateSearchResponse response =
          candidateSearchClient.search(request);
36
37      CandidateListResult result = response.getCandidates
          ();
38
39      StringBuffer strBuilder = new StringBuffer();
40      strBuilder.append("Result from SOCORA\n");
41      strBuilder.append(Strings.repeat("=", "Result from \n"
          SOCORA".length()));
42      strBuilder.append("\n");
43
44      // all rows
45      result.getCandidates().stream().sorted(new
          SocoraRequester.SortByRank(queryParams.
          getRankingStrategy(), true)).forEach(doc -> {
46          LOG.debug("Rank" + getRank(doc.getRanking())
              , queryParams.getRankingStrategy(), false
              ) + "/"
47              + getRank(doc.getRanking()),
              queryParams.getRankingStrategy(),
              true) + ":" + doc.getFQName() +
              "\n"
48              + doc.getUri() + ".SafeRanking_
              criteria?_"
49              + doc.getSafeRankingCriteria().get(
              queryParams.getRankingStrategy())

```

```

50         + "._Metrics:_"
        + prettify(doc.getMetrics(),
                    queryParams.getRankingCriteria())
        + "._Artifact_Info_"
51        + ToStringBuilder.reflectionToString
          (doc.getArtifactInfo());
52        strBuilder.append(String.format("-%s_\n",
          ToStringBuilder.reflectionToString(doc.
          getArtifactInfo())));
53    });
54    strBuilder.append(Strings.repeat("=", "Result_from_"
          SOCORA".length()));
55    LOG.debug("Total_size_" + result.getTotal());
56    String[] recipients = {"pdivasto@gmail.com"};
57
58    emailSender.sendEmail(recipients, strBuilder.
          toString());
59    }

```

Listing 4.5: Method textualSearchComponent of SocoraRequester.java

The class in charge of making the request to SOCORA is *SocoraRequester.java* [A.18]. The method *searchComponent* receives two parameters, *queries* which represents the interface signatures or the test classes, and *searchType* which represents the type of search (i.e. test driven search, interface driven search or textual search (default)). The snippet of code 4.6 represent the method *searchComponent*.

```

1  public static String TEST_DRIVEN_SEARCH = "TEST_DRIVEN_SEARCH";
2  public static String INTERFACE_DRIVEN_SEARCH = "
    INTERFACE_DRIVEN_SEARCH";
3  public static String KEYWORD_SEARCH = "KEYWORD_SEARCH";
4
5  @Autowired
6  private EmailSender emailSender;
7
8  public void searchComponent(String query, String searchType) throws
    IOException, InterruptedException, SparkPostException {
9      Validate.notBlank(query, "Query_parameter_is_required_and_
        cannot_be_blank");
10     if (StringUtils.compare(searchType, INTERFACE_DRIVEN_SEARCH)
        == 0 ||
11         StringUtils.compare(searchType, KEYWORD_SEARCH) == 0

```

```

12         ||
13         StringUtils.isBlank(searchType)) {
14             this.textualSearchComponent(query);
15         } else if (StringUtils.compare(searchType,
16             TEST_DRIVEN_SEARCH) == 0) {
17             this.testDrivenSearchComponent(query);
18         } else {
19             this.textualSearchComponent(query);
20         }
21     }

```

Listing 4.6: Method `searchComponent` of `SocoraRequester.java`

When SOCORA responses with the list of components found they are sent by email to developers. This action is done in the methods *textualSearchComponent* or *testDrivenSearchComponent* using the service `EmailSender` [A.10].

#### 4.3.5. Email result

After making the requests to SOCORA 4.3.4, it will response with the candidate components found. Simile receives the list of candidates, it extracts the candidates from the response, builds the email, and sends it to the recipient. For textual search results, the method *processTemplateTextualSearchResult* is in charge of interpreting the result and process the email's template before it is sent. For test-driven results, the method *processTemplateTestDrivenSearchResult* is in charge of interpreting the result and process the email's template before it is sent. The listing 4.7 show this method.

```

1 private String processTemplateTestDrivenSearchResult(
2     CandidateListResult result, QueryParams queryParams, String jobId
3 ) throws IOException, TemplateException {
4     Template emailTmp = freeMarker.getTemplate("
5         testdrivenResultEmail.ftl");
6     StringWriter stringWriter = new StringWriter();
7     List<Candidate> candidates = this.extractSearchCandidates(
8         result, queryParams);
9     Map<String, Object> root = new HashMap<>();
10    root.put("jobId", jobId);
11    root.put("numMetrics", candidates.get(0).getMetrics().size());
12    };

```

---

```

8         root.put("metrics", candidates.get(0).getMetrics());
9         root.put("candidates", candidates);
10        emailTmp.process(root, stringWriter);
11
12        return stringWriter.toString();
13    }
14
15    private String processTemplateTextualSearchResult(String
        methodQueried, CandidateListResult result, QueryParams
        queryParams) throws IOException, TemplateException {
16        Template emailTmp = freeMarker.getTemplate("
            interfaceResultEmail.ftl");
17        StringWriter stringWriter = new StringWriter();
18        List<Candidate> candidates = this.extractSearchCandidates(
            result, queryParams);
19        Map<String, Object> root = new HashMap<>();
20        root.put("query", methodQueried);
21        root.put("numMetrics", candidates.get(0).getMetrics().size()
            );
22        root.put("metrics", candidates.get(0).getMetrics());
23        root.put("candidates", candidates);
24        emailTmp.process(root, stringWriter);
25
26        return stringWriter.toString();
27    }
28
29    private List<Candidate> extractSearchCandidates(CandidateListResult
        result, QueryParams queryParams) {
30        List<Candidate> candidates = new ArrayList<>();
31        result.getCandidates().forEach(doc -> {
32            Candidate candidate = new Candidate();
33            candidate.setName(Optional.ofNullable(doc.
                getArtifactInfo().getName()).orElse(""));
34            candidate.setFqName(Optional.ofNullable(doc.
                getFqName()).orElse(""));
35            candidate.setMetrics(extractMetrics(doc.getMetrics()
                , queryParams.getRankingCriteria()));
36            candidate.setDescription(Optional.ofNullable(doc.
                getArtifactInfo().getDescription()).orElse(""));
37            candidate.setVersion(Optional.ofNullable(doc.
                getVersion()).orElse(""));
38            candidates.add(candidate);

```


```

39         });
40         return candidates;
41     }

```

Listing 4.7: Methods *processTemplateTextualSearchResult* and *processTemplateTestDrivenSearchResult* of *SocoraRequester.java*

After the email's body is generated by using the template and the java objects, it is sent to the recipient. For building the email we use FreeMarker <sup>3</sup>, which is a template engine which generates text output (HTML web pages, e-mails, configuration files, source code, etc.) based on templates and changing data. The figures 4.4 and 4.5 show the email with the result of a textual search and a test-driven search respectively.



Feedback from Simile - Textual search

Feedback from Simile - Textual search

**Interface-driven search result**


Query: **Base64(encode(byte[]):char[];decode(char[]):byte[];)**

Component	FQ Name	Ranking Criteria Lucene Score	Version	Description
Apache Tuscany SCA Binding WS Runtime Axis2 Aggregation	org.apache.axiom.om.util.Base64	9.73	2.0.1	
Apache ServiceMix :: Bundles :: \$(pkgArtifactId)	org.apache.axiom.om.util.Base64	9.73	1.2.13-1	This OSGi bundle wraps \$(pkgArtifactId) \$(pkgVersion) jar file.
REST API SDK	com.paypal.base.codec.binary.Base64	9.61	1.3.0	PayPal SDK for integrating with the REST APIs
Ajax4JSF	org.ajax4jsf.framework.util.base64.Base64	8.97	1.0.6	Ajax4jsf is an open source extension to the JavaServer Faces standard that adds AJAX capability to JSF applications without requiring the writing of any JavaScript.
jose4j	org.jose4j.base64url.internal.apache.commons.codec.binary.Base64	8.43	0.4.4	The jose4j library is a robust and easy to use open source implementation of JSON Web Token (JWT) and the JOSE specification suite (JWS, JWE, and JWK). It is written in Java and relies solely on the JCA APIs for cryptography. Please see <a href="https://bitbucket.org/b_c/jose4j/wiki/Home">https://bitbucket.org/b_c/jose4j/wiki/Home</a> for more info, examples, etc..
Lib-Cross-Java JSE5	com.github.libxjava.io.Base64	7.98	0.3	Lib-Cross-Java for the Java Standard Edition v5+
Lib-Cross-Java CDC	com.github.libxjava.io.Base64	7.98	0.3	Lib-Cross-Java for the Connected Device Configuration v1.1.2

Figure 4.4.: Textual search result email

<sup>3</sup><http://freemarker.org/> (accessed: 16.02.2017)





Feedback from Simile - Test-driven search

**Test-driven search result**

Job ID: 5be14600-f997-47b7-9dea-856ef5473d5a

SOCORA Link: [http://socora.merobase.com/socora/app/index.html#?result\\_hash=5be14600-f997-47b7-9dea-856ef5473d5a](http://socora.merobase.com/socora/app/index.html#?result_hash=5be14600-f997-47b7-9dea-856ef5473d5a)

Component	FQ Name	Functional Requirements			Version	Description
		Leaniness default (Instruction)	Efficient Coupling (entry class)	Cohesion LCOM3 (entry class)		
OW2 Util : Base64	org.ow2.util.base64.Base64	1	6	1.33	1.0.37	Base64 implementation
scala-http	scala-http.Base64	0.69	15	1.08	2.0.0	scala-http
bundle-thin-base-util-base64 - base64 code	org.bundle.thin.base.util.base64.Base64	0.1	9	1.14	1.0.9	
Interfaces	org.imixs.workflow.webservices.Base64	0.55	22	1.13	2.1.1	Imixs Workflow XML provides xml libraries to extend the Imixs Workflow API based on xml standards.
\$(artifactId)	org.httpobjects.impl.Base64	0.68	16	1.08	0.11.0	
Core API	org.imixs.workflow.util.Base64	0.55	22	1.13	3.4.4	Imixs-Workflow Core provides the platform for an open and standardized workflow technology. Imixs-Workflow Core provides various components in a Java framework that allow to create, control and monitor process-oriented business tasks.
jcommon	org.free.xml.util.Base64	0.56	22	1.13	1.0.16	JCommon is a free general purpose Java class

Figure 4.5.: Test-driven search result email

Depending on the type of search, the email will have some differences. The text driven search result contains a the query sent to SOCORA and a table with the candidates found. For test-driven search result, the email contains the job id of the search, the link to SOCORA to see more details of the result and the list of candidates found.

#### 4.3.6. HTTP Controller

The Java class `EntryController.java` [A.4] is in charge of receiving the request from a customer with the Git repository and the branch of the project to be analysed, and the email where the result of the similar component will be sent. In the listing 4.8 we can see the method `setupRepository` which represents the entry point which is a POST request with the three parameters described before. The parameter *repo* is required and represent the Git repository of the project that will be analysed and to which similar components will be searched for. The parameter *branch* represents the branch of the git repository, this parameter is optional. Finally, the parameter *email* represents the email where the result of the similar components will be sent to.

```

1 @RequestMapping(name = "/repository", method = RequestMethod.POST)
2 public ResponseEntity<?> setupRepository(@RequestParam(name = "repo"
   ) String repo,

```

```

3

```

```
name
=
"
branch
"
,
default
=
"
master
"
,
require
=
false
)
String
branch
,
@RequestMapping
(
name
=
"
email
"
)
String
```

```

5         if (validateRequest(repo, email).isPresent()) {
6             logger.debug("The request is not valid. Request ->
                repo: %s - branch: %s - email: %s", repo, branch,
                email);
7             return ResponseEntity.badRequest().body(
                validateRequest(repo, email).get());
8         } else {
9             logger.debug("The request is valid. Request -> repo:
                %s - branch: %s - email: %s", repo, branch,
                email);
10            simile.searchForComponents(repo, branch, Cuid.
                createCuid(), email);
11            return ResponseEntity.ok(new Message("Repository set
                successfully", 200));
12        }
13    }

```

Listing 4.8: Method setupRepository of EntryController.java

When a request is received by the controller, it firstly validates if the parameters are correct. If they are not valid, it will respond with HTTP status code 400 and a message describing the errors. Otherwise, it triggers asynchronously the method `searchForComponents` with the repository, the branch, and a random CUID <sup>4</sup> as a folder name of the service Simile. This service is in charge of starting the process of cloning the project, analyse the code, make the request to SOCORA, and to send the email with the result to the customer.

<sup>4</sup>CUID: Collision-resistant ids - <https://github.com/graphcool/cuid-java> (accessed: 04.02.2017).

## 4.4. CI integration

To integrate our prototype to a Continuous Integration process we decided to create a plugin. We decided to create our main prototype as independent as possible thus we do not depend on any CI tool. Therefore in this work to prove our approach we built a plugin for the CI server Jenkins. We decided to use Jenkins because is one of the most popular CI server for Java projects <sup>5</sup> and it is open-source.

The Simile Jenkins plugin is simple. First when a user creates a job in Jenkins, he/she can add a post build step. There he/she select the Simile plugin. When it is done, a new section is added in the task configuration (figure ??). There he/she should add the Git repository of the project, the branch (optional), and the email. Once done, whenever the job is triggered, the plugin will be triggered too. The plugin sends via HTTP POST request the repository, branch, and email to Simile.

In the future if Simile needs to be integrated to another CI server, we just need to develop a simple plugin which sends the information needed to look for similar components.

---

<sup>5</sup><https://www.cloudbees.com/sites/default/files/2016-jenkins-community-survey-responses.pdf> (accessed: 04.02.2017)

## 5. Discussion

The first question that arose during this work is: *Is this approach beneficial?*. As a first attempt to improve software reuse by using continuous integration, it is difficult to answer the question. In fact, it is more likely that at this version it might not be very helpful due to its immaturity. However, it is very promising in the future. In this chapter we will discuss about the possible pros and cons of this work.

This approach reduces the effort of searching suitable components by analyzing the code in background. Simile was conceived as unobtrusive tool as possible, that is why we found a great opportunity in the continuous integration process and the agile technique TDD. When a project is developed using TDD, the tests are written before the code that need to be implemented. Also according to the CI workflow, developers should commit changes as often as possible which trigger the CI server to validate the changes by testing the code. At this moment we visualized a great chance to look for similar components using textual and test-driven search approaches. Whenever the CI server is triggered we have the chance to analyze the code, extract interface signatures, and test classes which are sent to the code-search engine to retrieve similar components to the components that are being implemented. Thus developers might be able to reduce risk and development cost by reusing components which implement the functionality they are working on. Moreover it reduces the effort needed for searching components by running in background without disturbing the work of the developers.

Our prototype is able to provide high precision result that fully meet functional requirements. As test-driven search technique is able to provide the best results from the semantic point of view [40, 22, 20], we can assure that the precision of the components returned is very high (depending on the quality of the tests). We achieve this by relying on Merobase as code-search engine.

Although Simile can provide high precision on the components retrieved, if these are not ranked accordingly the effort invested on reusing components would in-

crease. We solve this problem by relying on SOCORA which is able to rank components using combination of non-functional properties such as performance or maintenance [25].

This approach also has some possible cons. If a team does not use TDD or any test, Simile would only be able to extract interface signatures from the code. Therefore the result retrieved would not be as precise as it would be using tests. This is due to the fact that the search would be based on keyword and text-matching techniques which do not necessarily meet functional requirements.

Another cons is the high time it might takes to deliver a result. Test-driven search component is heavy-weight task because it requires to run tests to for each possible candidate. Although it has been improved by parallelization of test execution and optimizing the underlying code-search engine, it still takes a reasonable time for returning a result. This time can be even bigger depending on the complexity of the tests used for searching components.

One more cons is the bad quality of the documentation of the candidate components. Although the components retrieved meet the functional requirements of the user, if they are poorly documented or they are hard to understand the effort invested on reusing them will be high. Therefore it would be helpful to consider the quality of the code and documentation of the components retrieved.

## 6. Future Work

Although the approach presented in this work seems promising, there are many aspect that can be improved or need to be confirmed.

The current version need to be improved and include more features.

It is necessary to test the approach in real projects in order to evaluate the usefulness of it. One possibility would be to introduce Simile in small open-source projects that adopt test-driven development and some CI server. Another alternative would be to adopt the tool into a company and measure the times inner-developed components are being reused by other development teams of the company.





## 7. Conclusion

In this work we have presented a novel approach which is an attempt to improve the chances of reusing software by seizing the continuous integration process. As a proof-of-concept we also presented Simile, which is a tool that analyzes code, extracts interface signatures and test classes, and send them to SOCORA for searching similar components.

We started presenting the foundations of this work. First we talked about the state-of-art of software reuse, its benefits, and challenges. We also explained the different code-search engines in the market focusing on Merobase. Then we defined what ranking components means and we explained the ranking approach SOCORA. Secondly we exposed about continuous integration, its benefits, challenges, and tools. To finalize the foundation chapter we detailed microservices and its characteristics.



## Bibliography

- [1] Veronika Bauer and Antonio Vetro'. Comparing reuse practices in two large software-producing companies. 117:545–582, 2016. ISSN 01641212. doi: 10.1016/j.jss.2016.03.067.
- [2] Kent Beck. *Extreme Programming Explained: Embrace Change*. Number c. 1999. ISBN 0201616416. doi: 10.1136/adc.2005.076794.
- [3] Kent Beck. Test-Driven Development By Example. 2(c):176, 2003. ISSN 1660-1769. doi: 10.5381/jot.2003.2.2.r1.
- [4] Grady Booch, Robert a. Maksimchuk, Michael W. Engle, Bobbi J. Young, Jim Conallen, and Kelli a. Houston. *Object-Oriented Analysis and Design with Applications*, volume 1. 2007. ISBN 020189551X. doi: 10.1145/1402521.1413138.
- [5] Scott Chacon. Pro Git. pages 1–210, 2009. ISSN 978-1-4302-1833-3. doi: 10.1007/978-1-4302-1834-0.
- [6] Lianping Chen. Towards Architecting for Continuous Delivery. In *2015 12th Working IEEE/IFIP Conference on Software Architecture*, pages 131–134. IEEE, may 2015. ISBN 978-1-4799-1922-2. doi: 10.1109/WICSA.2015.23. URL <http://ieeexplore.ieee.org/document/7158514/>.
- [7] Paul Duvall, Steve Matyas, and Andrew Glover. *Continuous Integration: Improving Software Quality and Reducing Risk*. 2007. ISBN 9780321336385. URL <http://portal.acm.org/citation.cfm?id=1406212>.
- [8] The Apache Software Foundation. Apache Lucene - Apache Lucene Core. <https://lucene.apache.org/core/>, 2017. Accessed: 12.01.2017.
- [9] Martin Fowler. Continuous Integration. <http://martinfowler.com/articles/continuousIntegration.html>, 2006. Accessed: 11.09.2016.

- 
- [10] Martin Fowler. Polyglot Persistence. <https://martinfowler.com/bliki/PolyglotPersistence.html>, 2011. Accessed: 03.02.2017.
- [11] Martin Fowler. Continuous Delivery. <https://martinfowler.com/bliki/ContinuousDelivery.html>, 2013. Accessed: 09.01.2017.
- [12] Martin Fowler and James Lewis. Microservices. <https://martinfowler.com/articles/microservices.html>, 2014.
- [13] W.B. Frakes and Kyo Kyo Kang. Software reuse research: status and future. 31(7):529–536, jul 2005. ISSN 0098-5589. doi: 10.1109/TSE.2005.85. URL <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=1492369>.
- [14] William Frakes and Carol Terry. Software reuse: metrics and models. 28(2):415–435, jun 1996. ISSN 03600300. doi: 10.1145/234528.234531. URL <http://portal.acm.org/citation.cfm?doid=234528.234531>.
- [15] Ned Freed and Nathaniel Borenstein. Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies. RFC 2054, The Internet Engineering Task Force (IETF), November 1996. URL <https://www.ietf.org/rfc/rfc2045.txt>.
- [16] Vinicius C. Garcia, Eduardo S. de Almeida, Liana B. Lisboa, Alexandre C. Martins, Silvio R. L. Meira, Daniel Lucredio, and Renata P. de M. Fortes. Toward a Code Search Engine Based on the State-of-Art and Practice. In *2006 13th Asia Pacific Software Engineering Conference (APSEC'06)*, pages 61–70. IEEE, 2006. ISBN 0-7695-2685-3. doi: 10.1109/APSEC.2006.57. URL <http://ieeexplore.ieee.org/document/4137403/>.
- [17] Bradley Horowitz. Official Google Blog: A fall sweep. <https://googleblog.blogspot.cl/2011/10/fall-sweep.html>, 2011. Accessed: 12.01.2017.
- [18] Jez Humble and David Farley. *Continuous Delivery: Reliable Software Releases through Build, Test, and Deployment Automation*. 2010. ISBN 978-0-321-60191-9. doi: 10.1007/s13398-014-0173-7.2.

- [19] Oliver Hummel and Colin Atkinson. Extreme harvesting: Test driven discovery and reuse of software components. In *Proceedings of the 2004 IEEE International Conference on Information Reuse and Integration, IRI-2004*, pages 66–72, 2004. ISBN 0780388194. doi: 10.1109/IRI.2004.1431438.
- [20] Oliver Hummel and Werner Janjic. Test-Driven Reuse: Key to Improving Precision of Search Engines for Software Reuse. In *Finding Source Code on the Web for Remix and Reuse*, pages 227–250. Springer New York, New York, NY, 2013. doi: 10.1007/978-1-4614-6596-6\_12. URL [http://link.springer.com/10.1007/978-1-4614-6596-6\\_{\\_}12](http://link.springer.com/10.1007/978-1-4614-6596-6_{_}12).
- [21] Oliver Hummel, Werner Janjic, and Colin Atkinson. Evaluating the efficiency of retrieval methods for component repositories. In *19th International Conference on Software Engineering and Knowledge Engineering, SEKE 2007*, pages 404–409, 2007. ISBN 9781627486613 (ISBN).
- [22] Oliver Hummel, Werner Janjic, and Colin Atkinson. Code Conjuror: Pulling Reusable Software out of Thin Air. 25(5):45–52, sep 2008. ISSN 0740-7459. doi: 10.1109/MS.2008.110. URL <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=4602673>.
- [23] Docker Inc. The Docker Platform. <https://www.docker.com>, 2017. Accessed: 19.01.2017.
- [24] Katsuro Inoue, Reishi Yokomori, Tetsuo Yamamoto, Makoto Matsushita, and Shinji Kusumoto. Ranking significance of software components based on use relations. 31(3):213–225, 2005. ISSN 00985589. doi: 10.1109/TSE.2005.38.
- [25] Marcus Kessel and Colin Atkinson. Ranking software components for reuse based on non-functional properties. pages 1–29, jul 2016. ISSN 1387-3326. doi: 10.1007/s10796-016-9685-3. URL <http://link.springer.com/10.1007/s10796-016-9685-3>.
- [26] Y. Kim and E.A. Stohr. Software reuse: issues and research directions. In *Proceedings of the Twenty-Fifth Hawaii International Conference on System Sciences*, pages 612–623 vol.4. IEEE, 1992. ISBN 0-8186-2420-5. doi: 10.

- 1109/HICSS.1992.183360. URL <http://ieeexplore.ieee.org/document/183360/>.
- [27] Charles W. Krueger and Charles W. Software reuse. 24(2):131–183, jun 1992. ISSN 03600300. doi: 10.1145/130844.130856. URL <http://portal.acm.org/citation.cfm?doid=130844.130856>.
- [28] Maarit Laanti, Outi Salo, and Pekka Abrahamsson. Agile methods rapidly replacing traditional methods at Nokia: A survey of opinions on agile transformation. 53(3):276–290, 2011. doi: 10.1016/j.infsof.2010.11.010.
- [29] Otávio Augusto Lazzarini Lemos, Sushil Krishna Bajracharya, and Joel Ossher. CodeGenie: a Tool for Test-Driven Source Code Search. 07pp:525–526, 2007. doi: 10.1145/1321631.1321726. URL <http://portal.acm.org/citation.cfm?id=1321631.1321726>.
- [30] Marko Leppanen, Simo Makinen, Max Pagels, Veli-Pekka Eloranta, Juha Itkonen, Mika V. Mantyla, and Tomi Mannisto. The highways and country roads to continuous deployment. 32(2):64–72, mar 2015. doi: 10.1109/MS.2015.50. URL <http://ieeexplore.ieee.org/document/7057604/>.
- [31] Mika V. Mäntylä, Bram Adams, Foutse Khomh, Emelie Engström, and Kai Petersen. On rapid releases and software testing: a case study and a semi-systematic literature review. 20(5):1384–1425, oct 2015. doi: 10.1007/s10664-014-9338-4. URL <http://link.springer.com/10.1007/s10664-014-9338-4>.
- [32] M.D. McIlroy. Mass Produced Software Components. pages 138–155, 1968.
- [33] a. Mili, R. Mili, and R.T. Mittermeir. A survey of software reuse libraries. 5(1):349–414–414, 1998. ISSN 1022-7091. doi: 10.1023/A:1018964121953. URL <http://www.springerlink.com/content/u7j724230tn12h03/>.
- [34] Hafehdh Mili. *Reuse based software engineering : techniques, organization and measurement*. Wiley, 2002. ISBN 0471398195.
- [35] M. Morisio, M. Ezran, and C. Tully. Success and failure factors in software reuse. 28(4):340–357, apr 2002. ISSN 0098-5589. doi: 10.1109/TSE.2002.995420. URL <http://ieeexplore.ieee.org/document/995420/>.

- [36] Steve Neely and Steve Stolt. Continuous Delivery? Easy! Just Change Everything (Well, Maybe It Is Not That Easy). In *2013 Agile Conference*, pages 121–128. IEEE, aug 2013. ISBN 978-0-7695-5076-3. doi: 10.1109/AGILE.2013.17. URL <http://ieeexplore.ieee.org/document/6612887/>.
- [37] Thomas P. Pole and W.B. Frakes. An Empirical Study of Representation Methods for Reusable Software Components. 20(8):617–630, 1994. ISSN 00985589. doi: 10.1109/32.310671.
- [38] Mary (Mary B.) Poppendieck and Thomas David. Poppendieck. *Lean software development : an agile toolkit*. Addison-Wesley, 2003. ISBN 0321150783.
- [39] Rubén Prieto-Díaz and Peter Freeman. Classifying Software for Reusability. 4(1):6–16, 1987. ISSN 07407459. doi: 10.1109/MS.1987.229789.
- [40] Steven P. Reiss. Semantics-based code search. In *Proceedings - International Conference on Software Engineering*, pages 243–253, 2009. ISBN 9781424434527. doi: 10.1109/ICSE.2009.5070525.
- [41] Kim Rejström. Implementing continuous integration in a small company: A case study. G2 pro gradu, diplomityö, 2016-10-27. URL <http://urn.fi/URN:NBN:fi:aalto-201611025461>.
- [42] Pilar Rodríguez, Alireza Haghighatkhah, Lucy Ellen Lwakatare, Susanna Teppola, Tanja Suomalainen, Juho Eskeli, Teemu Karvonen, Pasi Kuvaja, June M. Verner, and Markku Oivo. Continuous deployment of software intensive products and services: A systematic mapping study. 123:263–291, 2016. doi: 10.1016/j.jss.2015.12.015.
- [43] RC Seacord. Software engineering component repositories. 1999. URL <http://faculty.ksu.edu.sa/ghazy/CBD{ }MSc/Ref-25.pdf{#}page=95>.
- [44] Daniel Ståhl and Jan Bosch. Automated software integration flows in industry: a multiple-case study. In *Companion Proceedings of the 36th International Conference on Software Engineering - ICSE Companion 2014*, pages 54–63, New York, New York, USA, 2014. ACM Press. ISBN 9781450327688. doi: 10.1145/2591062.2591186. URL <http://dl.acm.org/citation.cfm?doid=2591062.2591186>.

- 
- [45] Thomas A. Standish. An Essay on Software Reuse. SE-10(5):494–497, 1984. ISSN 00985589. doi: 10.1109/TSE.1984.5010272.
  - [46] Kathryn T. Stolee, Sebastian Elbaum, and Matthew B. Dwyer. Code search with input/output queries: Generalizing, ranking, and assessment. 116:35–48, 2016. ISSN 01641212. doi: 10.1016/j.jss.2015.04.081.
  - [47] Suresh Thummalapenta and Tao Xie. Parseweb: a programmer assistant for reusing open source code on the web. pages 204–213, 2007. ISSN 03621340. doi: 10.1145/1321631.1321663. URL <http://dl.acm.org/citation.cfm?id=1321663>.
  - [48] Kristina Weis. GitHub CEO and Co-Founder Chris Wanstrath Keynoting Esri’s DevSummit! — ArcGIS Blog. <https://goo.gl/or7oIX>, 2014. Accessed: 14.01.2017.



# Appendix



## A. Simile - Code

In this section we will expose the different Java classes of our prototype.

### A.1. de.unimannheim.informatik.swt.simile

```
package de.unimannheim.informatik.swt.simile;

import com.google.common.base.Strings;
import de.unimannheim.informatik.swt.simile.services.*;
5 import org.apache.commons.lang3.exception.ExceptionUtils;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.scheduling.annotation.Async;
10 import org.springframework.stereotype.Service;

import java.io.File;
import java.io.IOException;
import java.util.List;

15 @Service
public class Simile {

    private static final Logger logger = LoggerFactory.getLogger
        (Simile.class);

20

    private final SocoraRequester socoraRequester;

    @Autowired
    public Simile(SocoraRequester socoraRequester) {
25         this.socoraRequester = socoraRequester;
    }

    @Async
```

```

public void searchForComponents(String repo, String branch,
    String folder, String recipient) throws IOException,
    InterruptedException {
30     Cloner cloner = new Cloner(repo, branch, folder);

    cloner.cloneRepository();

    File maintDir = new File(String.format("%s/src/main"
        , folder));
35     JavaClassHandler classes = new JavaClassHandler();
    new DirectoryExplorer(classes, new JavaClassFilter()
        ).explore(maintDir);

    File testDir = new File(String.format("%s/src/test",
        folder));
    JavaClassHandler testClasses = new JavaClassHandler
        ();
40     new DirectoryExplorer(testClasses, new
        JavaClassFilter()).explore(testDir);

    logger.info(String.format("Classes found in project:
        %s", classes.getClasses().size()));
    logger.info(String.format("Test classes found in
        project: %s", testClasses.getTestClassesCode().
        size()));

45     this.makeRequestWithClasses(classes.
        getClassMQLNotation(), recipient);
    this.makeRequestWithTestClasses(testClasses.
        getTestClassesCode(), recipient);
}

private void makeRequestWithClasses(List<String> classes,
    String recipientEmail) {
50     logger.info("Interface-driven Search");
    logger.info(Strings.repeat("=", "Interface-driven Search".length()));
    classes.forEach(c -> {
        try {
            logger.info(String.format("Class to
                query: %s", c));

```

```

55         socoraRequester.searchComponent(c,
            SocoraRequester.
            INTERFACE_DRIVEN_SEARCH,
            recipientEmail);
        } catch (Exception ex) {
            logger.error(ExceptionUtils.
                getStackTrace(ex));
        }
    });
60 }

    private void makeRequestWithTestClasses(List<String>
        testClasses, String recipientEmail) {
        logger.info("Test-driven_Search");
        logger.info(Strings.repeat("=", "Test-driven_Search"
            .length()));
65        testClasses.forEach(tc -> {
            try {
                logger.info(String.format("Test_
                    Class_to_query:_%s", tc));
                socoraRequester.searchComponent(tc,
                    SocoraRequester.
                    TEST_DRIVEN_SEARCH,
                    recipientEmail);
            } catch (Exception ex) {
70                logger.error(ExceptionUtils.
                    getStackTrace(ex));
            }
        });
    }

75 }

```

Listing A.1: Simile.java

```

package de.unimannheim.informatik.swt.simile;

import org.springframework.boot.builder.SpringApplicationBuilder;
import org.springframework.boot.web.support.
    SpringBootServletInitializer;
5 import org.springframework.context.annotation.Configuration;

/**

```

```

    * Implementation of SpringBootServletInitializer necessary to
      generate a deployable .war
    * file .
10  */
    @Configuration
    public class ServletInitializer extends SpringBootServletInitializer
    {
        @Override
        protected SpringApplicationBuilder configure(
            SpringApplicationBuilder application) {
15         return application.sources(SimileApplication.class);
        }
    }

```

Listing A.2: ServletInitializer.java

```

package de.unimannheim.informatik.swt.simile;

import freemarker.template.Configuration;
import freemarker.template.TemplateExceptionHandler;
5  import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.annotation.Bean;
10 import org.springframework.scheduling.annotation.
    AsyncConfigurerSupport;
import org.springframework.scheduling.annotation.EnableAsync;
import org.springframework.scheduling.concurrent.
    ThreadPoolTaskExecutor;

import java.io.File;
15 import java.io.IOException;
import java.util.concurrent.Executor;

@SpringBootApplication
@EnableAsync
20 public class SimileApplication extends AsyncConfigurerSupport {

    private static final Logger logger = LoggerFactory.getLogger(
        (SimileApplication.class));

    public static void main(String[] args) {

```

```

25         SpringApplication.run(SimileApplication.class, args)
           ;
       }

       @Override
       public Executor getAsyncExecutor() {
30         ThreadPoolTaskExecutor executor = new
           ThreadPoolTaskExecutor();
           executor.setCorePoolSize(2);
           executor.setMaxPoolSize(2);
           executor.setQueueCapacity(500);
           executor.setThreadNamePrefix("SIMILE-");
35         executor.initialize();
           return executor;
       }

       @Bean
40       public Configuration freeMarkerConfiguration() throws
         IOException {
           Configuration cfg = new Configuration(Configuration.
             VERSION_2_3_23);
           cfg.setDirectoryForTemplateLoading(new File(getClass()
             .getClassLoader().getResource("templates").
             getPath()));
           cfg.setDefaultEncoding("UTF-8");
           cfg.setTemplateExceptionHandler(
             TemplateExceptionHandler.RETHROW_HANDLER);
45         cfg.setLogTemplateExceptions(false);
           return cfg;
       }
   }

```

Listing A.3: SimileApplication.java

#### A.1.1. de.unimannheim.informatik.swt.simile.controllers

```

package de.unimannheim.informatik.swt.simile.controllers;

import cool.graph.cuid.Cuid;
import de.unimannheim.informatik.swt.simile.Simile;
5 import de.unimannheim.informatik.swt.simile.model.Message;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

```

```
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.http.ResponseEntity;
10 import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;
import org.springframework.web.bind.annotation.RequestParam;
import org.springframework.web.bind.annotation.RestController;

15 import java.io.IOException;
import java.util.Optional;
import java.util.regex.Pattern;

@RestController
20 public class EntryController {

    private static final Logger logger = LoggerFactory.getLogger
        (EntryController.class);

    @Autowired
25 private Simile simile;

    @RequestMapping(name = "/repository", method = RequestMethod
        .POST)
    public ResponseEntity<?> setupRepository(@RequestParam(name
        = "repo") String repo,
```



```
if(validateRequest(repo, email).isPresent()) {  
    logger.debug("The request is not valid. "  
        Request->repo: %s - branch: %s - email:
```

```

        _%s", repo, branch, email);
        return ResponseEntity.badRequest().body(
            validateRequest(repo, email).get());
    } else {
35         logger.debug("The request is valid. Request
            -> repo: %s - branch: %s - email: %s",
                repo, branch, email);
        simile.searchForComponents(repo, branch,
            Cuid.createCuid(), email);
        return ResponseEntity.ok(new Message("
            Repository set successfully", 200));
    }
}

40
private Optional<Message> validateRequest(String repo,
    String email) {
    logger.debug("Validating required parameters in
        request");
    StringBuilder str = new StringBuilder();
    if(repo.isEmpty()) str.append("repo is required");
45    if(email.isEmpty()) str.append("email is required");
    if(!this.isValidEmail(email)) str.append("email is
        not valid");
    if(!this.isValidGithubWebURL(repo)) str.append("repo
        must be a valid Git Web URL (e.g. https://github
        .com/...)");
    if(!str.toString().isEmpty()) {
        return Optional.ofNullable(new Message(str.
            toString(), 400));
50    }
    return Optional.empty();
}

/**
55    * Validates if a Git repository url is a valid Git Web URL.
    *
    * @param gitRepo Git web URL to be validated.
    * @return true if the git url is valid, otherwise false.
    * */
60 private boolean isValidGithubWebURL(String gitRepo) {
    logger.debug("isValidGithubWebURL: gitRepo=%s",
        gitRepo);

```

```

        final Pattern pattern = Pattern.compile("(http(s)?
            (://)?)([\\w\\.\\@\\:/\\-~]+)(\\.git)?");
        return pattern.matcher(gitRepo).matches();
    }

65
    /**
     * Validates if an email address is valid.
     *
     * @see <a href="http://www.regexr.com/3c0ol">http://www.
         regexr.com/3c0ol</a>
70
     *
     * @param email email address to be validated.
     * @return true in case the email address is valid,
         otherwise false.
     * */
    private boolean isValidEmail(String email) {
75
        logger.debug("isValidEmail: email=%s", email);
        final Pattern pattern = Pattern.compile("[a-z0-9!#$
            %&'*/+=?^_`{|}~-]+(?:\\.[a-z0-9!#$%&'*/+=?^_
            `{|}~-]+)*@(?:[a-z0-9](?:[a-z0-9]*[a-z0-9])?)|[
            a-z0-9](?:[a-z0-9]*[a-z0-9])?)");
        return pattern.matcher(email).matches();
    }
}

```

Listing A.4: EntryController.java

### A.1.2. de.unimannheim.informatik.swt.simile.model

```

package de.unimannheim.informatik.swt.simile.model;

import lombok.Data;

5 import java.util.List;

@Data
public class Candidate {
    private String name;
10    private String fqName;
    private List<Metric> metrics;
    private String version;
    private String description;
}

```

```
}
```

Listing A.5: Candidate.java

```
package de.unimannheim.informatik.swt.simile.model;
```

```
import lombok.Data;
```

```
import lombok.RequiredArgsConstructor;
```

```
5
```

```
@RequiredArgsConstructor
```

```
@Data
```

```
public class Message {
```

```
    private final String message;
```

```
10
```

```
    private final int status;
```

```
}
```

Listing A.6: Message.java

```
package de.unimannheim.informatik.swt.simile.model;
```

```
import lombok.Data;
```

```
5
```

```
@Data
```

```
public class Metric {
```

```
    private String title;
```

```
    private Double value;
```

```
}
```

Listing A.7: Metric.java

### A.1.3. de.unimannheim.informatik.swt.simile.services

```
package de.unimannheim.informatik.swt.simile.services;
```

```
import de.unimannheim.informatik.swt.simile.util.StreamGobbler;
```

```
import lombok.Getter;
```

```
5
```

```
import lombok.RequiredArgsConstructor;
```

```
import java.io.IOException;
```

```
@RequiredArgsConstructor
```

```
10
```

```
public class Cloner {
```

---

```

    @Getter
    private final String repo;
    @Getter
15    private final String branch;
    @Getter
    private final String folder;

    /**
20    * Executes the command <code>git clone</code> with the
        values of
    * repo, branch and folder. It clones the repository of
        specific branch (default master)
    * in a specified folder.
    * */
    public int cloneRepository() throws IOException {
25        int exitVal = 0;
        try {
            String command = this.setCommand(repo,
                branch, folder);
            Process p = Runtime.getRuntime().exec(
                command);
            StreamGobbler errorGobbler = new
                StreamGobbler(p.getErrorStream(), "INFO")
                ;
30            errorGobbler.start();
            exitVal = p.waitFor();
            return exitVal;
        } catch (InterruptedException e) {
            e.printStackTrace();
35        }
        return exitVal;
    }

    String setCommand(String repo, String branch, String folder)
    {
40        if (!branch.isEmpty()) {
            return String.format("git clone %s --branch %s %s",
                repo, branch, folder);
        } else {
            return String.format("git clone %s %s", repo,
                folder);
        }
    }

```

```
45      }  
  
    }
```

Listing A.8: Cloner.java

```
package de.unimannheim.informatik.swt.simile.services;  
  
import lombok.RequiredArgsConstructor;  
import lombok.Setter;  
  
5 import java.io.File;  
  
@RequiredArgsConstructor  
public class DirectoryExplorer {  
10     private final FileHandler fileHandler;  
     private final Filter filter;  
     @Setter  
     private File projectDir;  
  
15     public void explore() {  
         explore(0, "", this.projectDir);  
     }  
  
     public void explore(File root) {  
20         explore(0, "", root);  
     }  
  
     private void explore(int level, String path, File file) {  
         if (file.isDirectory()) {  
25             for (File child : file.listFiles()) {  
                 explore(level + 1, path + "/" +  
                     child.getName(), child);  
             }  
         } else {  
30             if (filter.interested(level, path, file)) {  
                 fileHandler.handle(level, path, file  
                     );  
             }  
         }  
     }  
}
```

35 }

### Listing A.9: DirectoryExplorer.java

```

package de.unimannheim.informatik.swt.simile.services;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
5 import org.springframework.stereotype.Service;

import javax.mail.*;
import javax.mail.internet.InternetAddress;
import javax.mail.internet.MimeMessage;
10 import java.util.Date;
import java.util.Properties;

@Service
public class EmailSender {
15     private static final Logger logger = LoggerFactory.getLogger
        (EmailSender.class);

    /**
     * Sends email to <code>toEmail</code> with subject <code>
       subject</code>
     * and with body <code>body</code>.
20     *
     * @param toEmail recipient of email.
     * @param subject of the email.
     * @param body of the email.
     */
25     public void sendEmail(String toEmail, String subject, String
        body) {
        try {
            MimeMessage msg = new MimeMessage(getSession
                ());
            //set message headers
            msg.addHeader("Content-type", "text/HTML; _
                charset=UTF-8");
30            msg.addHeader("format", "flowed");
            msg.addHeader("Content-Transfer-Encoding", "
                8bit");

            msg.setFrom(new InternetAddress("

```

```

        no_reply@simile.de", "NoReply-Simile"));
msg.setReplyTo(InternetAddress.parse("
        no_reply@simile.de", false));
35 msg.setSubject(subject, "UTF-8");
msg.setText(body, "UTF-8", "html");
msg.setSentDate(new Date());

msg.setRecipients(Message.RecipientType.TO,
        InternetAddress.parse(toEmail, false));
40 logger.info("Message_is_ready");
Transport.send(msg);

logger.info("Email_Sent_Successfully!!");
} catch (Exception e) {
45     e.printStackTrace();
}

}

private Session getSession() {
50     final String fromEmail = "pdivasto@gmail.com"; //
        requires valid gmail id
    final String password = "manK1nd1634;"; // correct
        password for gmail id

    logger.debug("SSEmail_Start");
    Properties props = new Properties();
55 props.put("mail.smtp.host", "smtp.gmail.com"); //
        SMTP Host
    props.put("mail.smtp.socketFactory.port", "465"); //
        SSL Port
    props.put("mail.smtp.socketFactory.class", "javax.
        net.ssl.SSLSocketFactory"); //SSL Factory Class
    props.put("mail.smtp.auth", "true"); //Enabling SMTP
        Authentication
    props.put("mail.smtp.port", "465"); //SMTP Port
60

    Authenticator auth = new Authenticator() {
        protected PasswordAuthentication
            getPasswordAuthentication() {
                return new PasswordAuthentication(
                    fromEmail, password);
            }
    }

```



---

```

65         };

        return Session.getDefaultInstance(props, auth);
    }

70 }

```

Listing A.10: EmailSender.java

```

package de.unimannheim.informatik.swt.simile.services;

import java.io.File;

5 public interface FileHandler {
    void handle(int level, String path, File file);
}

```

Listing A.11: FileHandler.java

```

package de.unimannheim.informatik.swt.simile.services;

import java.io.File;

5 public interface Filter {
    boolean interested(int level, String path, File file);
}

```

Listing A.12: Filter.java

```

package de.unimannheim.informatik.swt.simile.services;

import java.io.File;

5 public class JavaClassFilter implements Filter {
    @Override
    public boolean interested(int level, String path, File file)
    {
        return path.endsWith(".java");
    }

10 }

```

Listing A.13: JavaClassFilter.java

```

package de.unimannheim.informatik.swt.simile.services;

```

```

import com.github.javaparser.JavaParser;
import com.github.javaparser.ast.NodeList;
5 import com.github.javaparser.ast.body.Parameter;
import com.google.common.base.Strings;
import lombok.Getter;
import org.apache.commons.lang3.StringUtils;
import org.apache.commons.lang3.text.StrBuilder;
10 import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

import java.io.File;
import java.io.IOException;
15 import java.util.*;

public class JavaClassHandler implements FileHandler {

    private static final Logger logger = LoggerFactory.getLogger
        (JavaClassHandler.class);

20

    private List<String> methods = new ArrayList<>();
    @Getter
    private List<String> testClassesCode = new ArrayList<>();
    @Getter
25 private Map<String, List<String>> classes = new HashMap<>();

    /**
     * Handles the current Java class and for each method it
     * contains,
     * it transforms the method into Merobase Query Language
     * format.
30 */
    @Override
    public void handle(int level, String path, File file) {
        logger.debug(path);
        logger.debug(Strings.repeat("=", path.length()));
35 try {
            JavaClassVisitor jcv = new JavaClassVisitor
                ();
            jcv.visit(JavaParser.parse(file), null);
            jcv.getMethods().forEach(method -> methods.
                add(this.getMethodMQLNotation(method).

```

---

```

        getNameAsString(), method.getParameters()
        , method.getType().toString())));
        classes.put(jcv.getClassObj().
        getNameAsString(), methods);
40      methods = new ArrayList<>();
        if(jcv.getTestClasses().size() > 0)
            testClassesCode.addAll(jcv.
            getTestClasses());
    } catch (IOException e) {
        new RuntimeException(e);
45    }
}

private String getMethodMQLNotation(String methodName,
    NodeList<Parameter> params, String returnType) {
    List<String> paramTypes = new ArrayList<>();
    params.forEach(param -> paramTypes.add(param.getType
50      ().toString()));
    logger.debug(
        String.format("%s(%s):%s", methodName,
            StringUtils.join(paramTypes, ','),
            returnType)
    );
    return String.format("%s(%s):%s", methodName,
        StringUtils.join(paramTypes, ','), returnType);
55 }

/**
 * Returns the classes and the methods it contains in MQL
 * notation.
 *
 * <p>For example for the following class:
 * <pre>
 * public class TestClass {
 *     public String methodOne(int param){
 *     }
65 * }
 * </pre>
 * <p> This method will return:
 * <pre>
 * TestClass(methodOne(int):String;)
70 * </pre>

```

```

    * */
    public List<String> getClassesMQLNotation() {
        List<String> classesMQLNotation = new ArrayList<>();
        if (classes.size() > 0) {
75         classes.forEach((c, ms) -> {
            StrBuilder strBuilder = new
                StrBuilder();
            strBuilder.append(String.format("%s(
                ", c));
            strBuilder.append(StringUtils.join(
                ms, ' '));
            strBuilder.append(String.format(");")
80         ));
            logger.debug(strBuilder.toString());
            classesMQLNotation.add(strBuilder.
                toString());
        });
        return classesMQLNotation;
    }
85     return Collections.emptyList();
}
}

```

Listing A.14: JavaClassHandler.java

```

package de.unimannheim.informatik.swt.simile.services;

import com.github.javaparser.ast.body.ClassOrInterfaceDeclaration;
import com.github.javaparser.ast.body.MethodDeclaration;
5 import com.github.javaparser.ast.visitor.VoidVisitorAdapter;
import lombok.Getter;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

10 import java.util.ArrayList;
import java.util.List;

public class JavaClassVisitor extends VoidVisitorAdapter {

15     private static final Logger logger = LoggerFactory.getLogger
        (JavaClassVisitor.class);

    @Getter

```

---

```

    private ClassOrInterfaceDeclaration classObj;
    @Getter
20    private List<MethodDeclaration> methods = new ArrayList<>();
    @Getter
    private List<String> testClasses = new ArrayList<>();

    /**
25     * If the node visited is a Java class, it checks if it
        contains
        * annotation <code>@Test</code>. If true, it is added to
        test class
        * list.
        * */
    @Override
30    public void visit(ClassOrInterfaceDeclaration n, Object arg)
        {
            super.visit(n, arg);
            this.classObj = n;
            if(n.toString().contains("@Test")) {
                testClasses.add(n.toString());
35            }
        }

    /**
        * If the node visited is a method, it is added into <code>
        methods</code>
40    * list.
        * */
    @Override
    public void visit(MethodDeclaration n, Object arg) {
        super.visit(n, arg);
45        logger.debug(String.format("L[%s] ──%s", n.getBegin
            ().get(), n.getDeclarationAsString()));
        methods.add(n);
    }
}

```

Listing A.15: JavaClassVisitor.java

```
package de.unimannheim.informatik.swt.simile.services;
```

```
import com.github.javaparser.ast.NodeList;
```

```

import com.github.javaparser.ast.body.MethodDeclaration;
5 import com.github.javaparser.ast.body.Parameter;
import com.github.javaparser.ast.visitor.VoidVisitorAdapter;
import lombok.Getter;
import org.apache.commons.lang3.StringUtils;
import org.slf4j.Logger;
10 import org.slf4j.LoggerFactory;

import java.util.ArrayList;
import java.util.List;

15 public class JavaMethodVisitor extends VoidVisitorAdapter {

    private static final Logger logger = LoggerFactory.getLogger
        (JavaMethodVisitor.class);

    @Getter
20 private String name;
    @Getter
    private String returnType;
    @Getter
    private String parameterTypes;
25 private List<String> params = new ArrayList<>();
    @Getter
    private NodeList<Parameter> parameters;

    @Override
30 public void visit(MethodDeclaration n, Object arg) {
        super.visit(n, arg);
        logger.debug(String.format("L[%s] ↪↪%s", n.getBegin
            ().get(), n.getDeclarationAsString()));
        this.name = n.getName().toString();
        this.returnType = n.getType().toString();
35 n.getParameters().forEach(param -> params.add(param.
            getType().toString()));
        parameterTypes = StringUtils.join(params, ',');
        parameters = n.getParameters();
    }

40 }

```

Listing A.16: JavaMethodVisitor.java

---

```

package de.unimannheim.informatik.swt.simile.services;

import com.github.javaparser.ast.Node;

5  public class NodeIterator {
        public interface NodeHandler {
                boolean handle(Node node);
        }

10     private NodeHandler nodeHandler;

        public NodeIterator(NodeHandler nodeHandler) {
                this.nodeHandler = nodeHandler;
        }

15     public void explore(Node node) {
            if (nodeHandler.handle(node)) {
                    for (Node child : node.getChildNodes()) {
                            explore(child);
20                    }
            }
        }
    }

```

Listing A.17: NodeIterator.java

```

package de.unimannheim.informatik.swt.simile.services;

import com.merobase.socora.engine.index.repository.candidate.
    CandidateDocument;
import com.merobase.socora.engine.index.repository.candidate.
    CandidateListResult;
5  import com.merobase.socora.engine.search.*;
import com.merobase.socora.engine.search.filter.Filters;
import com.merobase.socora.engine.search.ranking.Rankings;
import de.unimannheim.informatik.swt.simile.model.Candidate;
import de.unimannheim.informatik.swt.simile.model.Metric;
10 import freemarker.template.Configuration;
import freemarker.template.Template;
import freemarker.template.TemplateException;
import org.apache.commons.lang3.StringUtils;
import org.apache.commons.lang3.Validate;
15 import org.slf4j.Logger;

```

```
import org.slf4j.LoggerFactory;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

20 import java.io.IOException;
import java.io.StringWriter;
import java.math.BigDecimal;
import java.math.RoundingMode;
import java.util.*;

25 @Service
public class SocoraRequester {
    public static String TEST_DRIVEN_SEARCH = "
        TEST_DRIVEN_SEARCH";
    public static String INTERFACE_DRIVEN_SEARCH = "
        INTERFACE_DRIVEN_SEARCH";
30 public static String KEYWORD_SEARCH = "KEYWORD_SEARCH";

    private static final Logger logger = LoggerFactory.getLogger
        (SocoraRequester.class);

    private static String baseUrl = "http://socora.merobase.com/
        socora";

35 private static String user = "socora";
private static String pass = "d3fudj983r223dhs23";

    private final EmailSender emailSender;
40 private final Configuration freeMarker;

    @Autowired
    public SocoraRequester(EmailSender emailSender,
        Configuration freeMarker) {
        this.emailSender = emailSender;
45 this.freeMarker = freeMarker;
    }

    public void searchComponent(String query, String searchType,
        String recipient) throws IOException,
        InterruptedException, TemplateException {
        Validate.notBlank(query, "Query_parameter_is_
            required_and_cannot_be_blank");
    }
}
```



---

```

50         if (StringUtils.compare(searchType,
                                   INTERFACE_DRIVEN_SEARCH) == 0 ||
               StringUtils.compare(searchType,
                                   KEYWORD_SEARCH) == 0 ||
               StringUtils.isBlank(searchType)) {
               this.textualSearchComponent(query, recipient
               );
        } else if (StringUtils.compare(searchType,
                                   TEST_DRIVEN_SEARCH) == 0) {
55             this.testDrivenSearchComponent(query,
               recipient);
        } else {
               this.textualSearchComponent(query, recipient
               );
        }
    }

60    /**
     * In charge of sending the test class to SOCORA to search
     * for components.
     *
     * @param testClassSourceQuery which is sent to SOCORA to
     * search for components.
65     * @param recipient (email) where the result will be sent.
     * */
    private void testDrivenSearchComponent(String
        testClassSourceQuery, String recipient) throws
        IOException, InterruptedException, TemplateException {
        // Create client
        CandidateSearchClient candidateSearchClient = new
            CandidateSearchClient(baseURI, auth(user, pass));

70        // Search request
        CandidateSearchRequest request = new
            CandidateSearchRequest();

        // Maximum no. of candidates to retrieve
75        int maxResults = 400;

        request.setInput(testClassSourceQuery);
        QueryParams queryParams = new QueryParams();
        queryParams.setRows(maxResults);

```

```

80      // inclusions
      queryParams.setArtifactInformation(true);
      queryParams.setContent(true);

85      // FILTERS
      queryParams.setFilters(Arrays.asList(
          Filters.HASH_CODE_CLONE_FILTER,
          Filters.NO_ABSTRACT_CLASS_FILTER,
          Filters.NO_INTERFACE_FILTER,
90          Filters.LATEST_VERSION_FILTER,
          Filters.FUNCTIONAL_SUFFICIENCY_FILTER
      ));

      request.setQueryParams(queryParams);

95      request.setTestDrivenSearch(Boolean.TRUE);

      // set ranking criteria
      queryParams.setRankingStrategy(Rankings.
          HYBRID_NON_DOMINATED_SORTING);
100      RankingCriterion fsCriterion = new RankingCriterion
          ();
      // FS dynamic
      fsCriterion.setName("sf_instruction_leanness");
      fsCriterion.setObjective(RankingCriterion.MAX);
      // performance criterion
105      RankingCriterion performanceCriterion = new
          RankingCriterion();
      performanceCriterion.setName("jmh_thrpt_score_mean")
          ;
      performanceCriterion.setObjective(RankingCriterion.
          MAX);
      // LCOM
      RankingCriterion lcomCriterion = new
          RankingCriterion();
110      lcomCriterion.setName("entryClass_ckjm_ext_lcom3");
      lcomCriterion.setObjective(RankingCriterion.MIN);
      // Coupling
      RankingCriterion couplingCriterion = new
          RankingCriterion();
      couplingCriterion.setName("entryClass_ckjm_ext_ce");

```

---

```

115         couplingCriterion.setObjective(RankingCriterion.MIN)
            ;

        queryParams.setRankingCriteria(Arrays.asList(
            fsCriterion ,
            performanceCriterion ,
120         lcomCriterion ,
            couplingCriterion
        ));

        CandidateSearchResponse response =
            candidateSearchClient.search(request);

125
        // JobId of the test-driven search, which is used to
            check the status of the job.
        String jobId = response.getJobId();

        // In order to retrieve the result, we need to check
            the status.
130        JobStatus jobStatus = null;
        while (jobStatus == null || jobStatus.getStatusType()
            != JobStatusType.FINISHED) {
            jobStatus = candidateSearchClient.
                getJobStatus(jobId);
            logger.info("Status_of_jobId_" + jobId + "_
                is_" + jobStatus.getStatusType().name());
            Thread.sleep(30 * 1000L);
135        }

        // Once the search is FINISHED, we retrieve the
            result with the candidates.
        if(jobStatus.getStatusType() == JobStatusType.
            FINISHED)
            getTestDrivenSearchResult(jobId, recipient,
                testClassSourceQuery);
140    }

    /**
     * In charge of fetching the result of a job with given id,
        handle it and send the result to the recipient.
     *
145     * @param jobId of the job to fetch the result.

```

```

    * @param recipient (email) to where we will send the result
    .
    * */
private void getTestDrivenSearchResult(String jobId, String
    recipient, String testClassQueried) throws IOException,
    TemplateException {
    // Create client
150    CandidateSearchClient candidateSearchClient = new
        CandidateSearchClient(baseURI, auth(user, pass));

    // Successful tds candidates
    QueryParams queryParams = new QueryParams();
    queryParams.setRows(2000);
155

    // Inclusions
    queryParams.setArtifactInformation(true);
    queryParams.setContent(true);

160    // FILTERS
    queryParams.setFilters(Arrays.asList(
        Filters.HASH_CODE_CLONE_FILTER,
        Filters.NO_ABSTRACT_CLASS_FILTER,
        Filters.NO_INTERFACE_FILTER,
165        Filters.LATEST_VERSION_FILTER,
        Filters.FUNCTIONAL_SUFFICIENCY_FILTER
    ));

    // set ranking criteria
170    queryParams.setRankingStrategy(Rankings.
        HYBRID_NON_DOMINATED_SORTING);
    RankingCriterion fsCriterion = new RankingCriterion
        ();
    // FS dynamic
    fsCriterion.setName("sf_instruction_leanness");
    fsCriterion.setObjective(RankingCriterion.MAX);
175    // performance criterion
    RankingCriterion performanceCriterion = new
        RankingCriterion();
    performanceCriterion.setName("jmh_thrpt_score_mean")
        ;
    performanceCriterion.setObjective(RankingCriterion.
        MAX);

```

---

```

// LCOM
180 RankingCriterion lcomCriterion = new
    RankingCriterion();
lcomCriterion.setName("entryClass_ckjm_ext_lcom3");
lcomCriterion.setObjective(RankingCriterion.MIN);
// Coupling
RankingCriterion couplingCriterion = new
    RankingCriterion();
185 couplingCriterion.setName("entryClass_ckjm_ext_ce");
couplingCriterion.setObjective(RankingCriterion.MIN);
    ;

queryParams.setRankingCriteria(Arrays.asList(
    fsCriterion,
190    performanceCriterion,
    lcomCriterion,
    couplingCriterion
));

// Getting Test-driven result.
195 CandidateSearchResponse response =
    candidateSearchClient.getResults(jobId,
    queryParams);

CandidateListResult result = response.getCandidates
    ();

200 this.sendResult(
    this.processTemplateTestDrivenSearchResult(
        result, queryParams, jobId),
    recipient,
    "Test-driven_search"
    );
205 }

/**
 * In charge of making the request to SOCORA using textual
 * search. The result is sent to the recipient.
 *
210 * @param method in MQL format that will be sent to SOCORA.
 * @param recipient (email) to which the result will be sent
 *

```

```

    * */
    private void textualSearchComponent(String method, String
        recipient) throws IOException, TemplateException {
        // create client
215        CandidateSearchClient candidateSearchClient = new
            CandidateSearchClient(baseURI, auth(user, pass));

        // search request
        CandidateSearchRequest request = new
            CandidateSearchRequest();

220        int maxResults = 10;

        request.setInput(method);
        QueryParams queryParams = new QueryParams();
        queryParams.setRows(maxResults);

225        // inclusions
        queryParams.setArtifactInformation(true);
        queryParams.setContent(true);

        // FILTERS
230        queryParams.setFilters(Arrays.asList(
            Filters.HASH_CODE_CLONE_FILTER,
            Filters.NO_ABSTRACT_CLASS_FILTER,
            Filters.NO_INTERFACE_FILTER,
235            Filters.LATEST_VERSION_FILTER,
            Filters.FUNCTIONAL_SUFFICIENCY_FILTER
        ));

        request.setQueryParams(queryParams);
240        // no test-driven search
        request.setTestDrivenSearch(Boolean.FALSE);

        // set ranking
        queryParams.setRankingStrategy(Rankings.
            SINGLE_OBJECTIVE);

245        // set ranking criteria
        List<RankingCriterion> rankingCriteria = Collections
            .singletonList(
                // textual score (Lucene/SolR)

```

---

```

                RankingCriterionBuilder
250                .rankingCriterion()
                .withName("luceneScore")
                .withObjective(RankingCriterion.MAX)
                .build()

        );

255        queryParams.setRankingCriteria(rankingCriteria);

        CandidateSearchResponse response =
            candidateSearchClient.search(request);

260        CandidateListResult result = response.getCandidates
            ();

        this.sendResult(
            this.processTemplateTextualSearchResult(
                method, result, queryParams),
            recipient,
265            "Textual_search"
        );
    }

    /**
270     * Processes the template using the candidates resulted from
        test-driven search.
        *
        * @param result from interface-driven search.
        * @param queryParams to show more data.
        * @param jobId
275     *
        * @return result in a human-readable format.
        * */
    private String processTemplateTestDrivenSearchResult(
        CandidateListResult result, QueryParams queryParams,
        String jobId) throws IOException, TemplateException {
        Template emailTmp = freeMarker.getTemplate("
            testdrivenResultEmail.ftl");
280        StringWriter stringWriter = new StringWriter();
        List<Candidate> candidates = this.
            extractSearchCandidates(result, queryParams);
        Map<String, Object> root = new HashMap<>();

```

```

        root.put("jobId", jobId);
        root.put("numMetrics", candidates.get(0).getMetrics
            ().size());
285    root.put("metrics", candidates.get(0).getMetrics());
        root.put("candidates", candidates);
        emailTmp.process(root, stringWriter);

        return stringWriter.toString();
290    }

    /**
     * Processes the template using the candidates resulted from
     * interface-driven search.
     *
     * @param methodQueried
     * @param result from interface-driven search.
     * @param queryParams to show more data.
     *
     * @return result in a human-readable format.
300    * */
    private String processTemplateTextualSearchResult(String
        methodQueried, CandidateListResult result, QueryParams
        queryParams) throws IOException, TemplateException {
        Template emailTmp = freeMarker.getTemplate("
            interfaceResultEmail.ftl");
        StringWriter stringWriter = new StringWriter();
        List<Candidate> candidates = this.
            extractSearchCandidates(result, queryParams);
305    Map<String, Object> root = new HashMap<>();
        root.put("query", methodQueried);
        root.put("numMetrics", candidates.get(0).getMetrics
            ().size());
        root.put("metrics", candidates.get(0).getMetrics());
        root.put("candidates", candidates);
310    emailTmp.process(root, stringWriter);

        return stringWriter.toString();
    }

    /**
     * Transforms result into a human-readable format.
     * */

```



---

```

private List<Candidate> extractSearchCandidates(
    CandidateListResult result, QueryParams queryParams) {
    List<Candidate> candidates = new ArrayList<>();
320    result.getCandidates().forEach(doc -> {
        Candidate candidate = new Candidate();
        candidate.setName(Optional.ofNullable(doc.
            getArtifactInfo().getName()).orElse(""));
        candidate.setFqName(Optional.ofNullable(doc.
            getFQName()).orElse(""));
        candidate.setMetrics(extractMetrics(doc.
            getMetrics(), queryParams.
            getRankingCriteria()));
325        candidate.setDescription(Optional.ofNullable
            (doc.getArtifactInfo().getDescription()).
            orElse(""));
        candidate.setVersion(Optional.ofNullable(doc.
            getVersion()).orElse(""));
        candidates.add(candidate);
    });
    return candidates;
330 }

/**
 * Sends the result of a search to the email.
 *
335 * @param result which will be sent.
 * @param email to which the result will be sent.
 * */
private void sendResult(String result, String email, String
    searchType) {
    emailSender.sendEmail(email, String.format("Feedback
        _from_Simile_-_%", searchType), result);
340 }

/**
 * Return rank for passed {@link Map} based on given
 * CandidateRankingStrategy
345 *
 * @param ranking
 *         {@link Map} instance
 * @param candidateRankingStrategy
 *         CandidateRankingStrategy ID {@link Rankings}

```

```

350      * @param partialOrder
      *           true if partial order should be returned (
      *           disables strict
      *           order!). Candidates in non-distinguishable
      *           sets possess the
      *           same ranks.
      * @return rank for given {@link } based on passed
355      *           CandidateRankingStrategy
      */
    private static int getRank(Map<String, Double> ranking,
        String candidateRankingStrategy, boolean partialOrder) {
        Validate.notBlank(candidateRankingStrategy, "
            CandidateRankingStrategy_ID_cannot_be_blank");

360        String key = candidateRankingStrategy;
        if (partialOrder) {
            key += "_po";
        }

365        return ranking.get(key).intValue();
    }

    private static Auth auth(String user, String pass) {
        Auth auth = new Auth();
370        auth.setUser(user);
        auth.setPassword(pass);

        return auth;
    }

375    private static List<Metric> extractMetrics(Map<String,
        Double> metrics, List<RankingCriterion> criteria) {
        List<Metric> metricList = new ArrayList<>();
        for (String key : metrics.keySet()) {
            for (RankingCriterion criterion : criteria)
            {
380                if (StringUtils.equals(criterion.
                    getName(), key)) {
                    Metric m = new Metric();
                    m.setTitle(SocoraRequester.
                        getMetricTitle(key));
                    m.setValue(SocoraRequester.

```

---

```

        round(metrics.get(key),
            2));
        metricList.add(m);
385     }
    }
}
return metricList;
}

390
private static String getMetricTitle(String metricKey) {
    String metricTitle;
    switch (metricKey) {
        case "luceneScore":
395         metricTitle = "Lucene_Score";
            break;
        case "sf_instruction_leanness":
            metricTitle = "Leanness_default_(
                Instruction)";
            break;
400         case "jmh_thrpt_score_mean":
            metricTitle = "Throughput_(
                operations_/_second";
            break;
        case "entryClass_ckjm_ext_lcom3":
            metricTitle = "Cohesion_LCOM3_(entry
                _class)";
405         break;
        case "entryClass_ckjm_ext_ce":
            metricTitle = "Efferent_Coupling_(
                entry_class)";
            break;
        default:
410         throw new IllegalArgumentException(
            String.format("Metric_%s_is_not_
                valid", metricKey));
    }
    return metricTitle;
}

415 private static double round(double value, int places) {
    if (places < 0) throw new IllegalArgumentException()
        ;

```

```

        BigDecimal bd = new BigDecimal(value);
        bd = bd.setScale(places, RoundingMode.HALF_UP);
420     return bd.doubleValue();
    }

    /**
     * Sort {@link CandidateDocument} by rank.
425     *
     * @author Marcus Kessel
     *
     */
    private static class SortByRank implements Comparator<
        CandidateDocument> {

430         private final String candidateRankingStrategy;
        private final boolean partialOrder;

        private SortByRank(String candidateRankingStrategy,
            boolean partialOrder) {
435             Validate.notBlank(candidateRankingStrategy);
            this.candidateRankingStrategy =
                candidateRankingStrategy;
            this.partialOrder = partialOrder;
        }

        @Override
440     public int compare(CandidateDocument o1,
        CandidateDocument o2) {
            int rank1 = getRank(o1.getRanking(),
                candidateRankingStrategy, partialOrder);
            int rank2 = getRank(o2.getRanking(),
                candidateRankingStrategy, partialOrder);

445     return Comparator.<Integer>naturalOrder().
        compare(rank1, rank2);
    }
}

```

---

450 }

Listing A.18: SocoraRequester.java

#### A.1.4. de.unimannheim.informatik.swt.simile.util

```

package de.unimannheim.informatik.swt.simile.util;

import java.io.BufferedReader;
import java.io.IOException;
5 import java.io.InputStream;
import java.io.InputStreamReader;

public class StreamGobbler extends Thread {
    InputStream is;
10    String type;

    public StreamGobbler(InputStream is, String type) {
        this.is = is;
        this.type = type;
15    }

    public void run() {
        try {
            InputStreamReader isr = new
                InputStreamReader(is);
20            BufferedReader br = new BufferedReader(isr);
            String line = null;
            while ((line = br.readLine()) != null)
                System.out.println(type + ">" + line
                    );
        } catch (IOException ioe) {
25            ioe.printStackTrace();
        }
    }
}

```

Listing A.19: StreamGobbler.java



## B. Installation of Simile

In this chapter we will show how to install the tools we used for implementing Simile. First we will start installing the CI Server Jenkins and explain how to configure it. Then, we will continue with installing Simile Jenkins plugin. After that we will explain how to configure Simile Jenkins plugin using the test project.

### B.1. Installation of Jenkins

In this section we will explain how to install Jenkins CI server using Docker and Tomcat 9.

#### B.1.1. Docker

For installing Jenkins, we will use Docker containers and in this subsection we will explain how to install it in different platform such as macOS and Linux.

##### B.1.1.1. Docker on macOS

For macOS we will use Docker for Mac tool. This is an integrated, easy-to-deploy environment for building, assembling, and shipping applications from a Mac. Moreover, it is a native Mac application architected from scratch, with a native user interface and auto-update capability, deeply integrated with OS X native virtualization, Hypervisor Framework, networking and file system, making it faster and more reliable than previous ways of getting Docker on a Mac [23].

First we will download the tool from the following link: <https://download.docker.com/mac/stable/Docker.dmg>.

After downloading the *dmg* image, double-click on it and you will see something like figure B.1. When you get that image, drag and drop the Docker icon to the

Applications folder. After that, go to Applications folder and double click on Docker application.




Figure B.1.: Docker for Mac installation

#### B.1.1.2. Docker on Linux

In this section we will explain how to install Docker in Linux, specifically in Debian (Jessie). For other distros please refer to Docker documentation<sup>1</sup>.

First of all we need to update the repositories.

---

```
1 $ sudo apt-get update
```

---

Then we need to install the packages to allow *apt* to use repositories over HTTPS.

---

```
1 $ sudo apt-get install apt-transport-https \  
2                             ca-certificates \  
3                             software-properties-common
```

---

Then we add the official Docker's GPG key.

---

<sup>1</sup><https://docs.docker.com/engine/installation/linux/> (accessed: 21.01.2017)



---

```
1 $ curl -fsSL https://yum.dockerproject.org/gpg | sudo apt-key add -
```

---

Finally we add the stable repository of Docker and update repositories.

---

```
1 $ sudo add-apt-repository \  
2     "deb https://apt.dockerproject.org/repo/ \  
3     debian-$(lsb_release -cs) \  
4     main"\  
5 $ sudo apt-get update
```

---

Once we added the new repositories, we update the repository list.

---

```
1 $ sudo apt-get update
```

---

Then we install docker.

---

```
1 $ sudo apt-get -y install docker-engine
```

---

After the installation is done we can make a little test to be sure that everything was installed correctly. The following command will download a test image and runs it in a container. Once it is running will print an informational message and exits.

---

```
1 $ sudo docker run hello-world
```

---

### B.1.2. Jenkins in Docker

Open a terminal on your mac and enter the following command to download the Jenkins image for Docker.

---

```
1 $ docker pull jenkins  
2 Using default tag: latest
```

```

3 latest: Pulling from library/jenkins
4
5 # some irrelevant output was remove
6 Digest: sha256:5046434030be395ec977c98e11...
7 Status: Downloaded newer image for jenkins:latest

```

---

Then, we just need to run the Jenkins image with the following command.

---

```

1 $ docker run -p 8080:8080 -p 50000:50000 jenkins
2 # some irrelevant output was remove
3 *****
4
5 Jenkins initial setup is required. An admin user has been
6 created and a password generated.
7 Please use the following password to proceed to installation:
8
9 95199411f1894bfa97e937147c41aa62 # IMPORTANT, default admin pass
10
11 This may also be found at: /var/jenkins_home/secrets/initial.
12
13 *****
14 # some irrelevant output was removed
15 Jan 19, 2017 8:28:05 AM hudson.model.AsyncPeriodicWork$1 run
16 INFO: Finished Download metadata. 25,312 ms

```

---

After that, open the following URL <http://localhost:8080> and you should see some like figure B.2.




Figure B.2.: First page of Jenkins setup

There enter the password generated by Jenkins and that appeared in the logs, and then click on continue.

In the following page click on *Install suggested plugins* like the figure B.3.




Figure B.3.: Second page of Jenkins setup

Then you should see something like the figure B.4. Here we just need to wait untill the plugins installation finish.




Figure B.4.: Third page of Jenkins setup

After the installation of plugins is done, click on *Continue as admin* or create custom admin user. Then you should see the home page of Jenkins (figure )




Figure B.5.: Jenkins home page

### B.1.3. Jenkins in Tomcat 9

**NOTE:** The following steps are based on a UNIX system.

First, go to the following URL and download Tomcat 9: <http://tomcat.apache.org/download-90.cgi>.

Once downloaded, unzip the file and modify the file *tomcat-users.xml* which is under the folder *conf* of where Tomcat was unzipped. Add the following two lines within *tomcat-users.xml* to setup an admin user.

---

```
1 <role rolename="manager-gui"/>
2 <user username="admin" password="1234" roles="manager-gui"/>
```

---

Now open a terminal and enter the following command to run Tomcat server.

---

```
1 $ cd folder/of/tomcat
2 $ cd bin
3 $ sh catalina.sh start
```

---

Then open the following URL and you should see something like Figure B.6: <http://localhost:8080>




Figure B.6.: Tomcat home page

To install Jenkins, we first need to download the *.war* file. To do so go to the following URL: <http://mirrors.jenkins.io/war-stable/latest/jenkins.war>. Once downloaded, move the file into the folder *webapps* which is into the folder where tomcat was installed. Then enter the following commands to restart tomcat.

---

```
1 $ sh catalina.sh stop
2 $ sh catalina.sh start
```

---

If you go to [localhost:8080/jenkins](http://localhost:8080/jenkins) you should see the same page like Figure B.2.

## B.2. Simile Jenkins Plugin installation

To install Simile Jenkins plugin, we need to follow the following steps.

First, open Jenkins URL. Then click on *Manage Jenkins* (figure B.7).




Figure B.7.: Manage Jenkins option

Then click on *Manage Plugins* (figure B.8).




Figure B.8.: Manage Plugins option

Then go to *Advanced*, scroll down until *Upload Plugin* section (figure B.9).




Figure B.9.: Upload Plugin section

There click on choose file and select the hpi file *simile-jenkins-plugin.hpi* provided with the CD.

### **B.3. Simile in Tomcat 9**

To install Simile in Tomcat 9, we just need to copy the file *simile.war*, provided with the CD, into the folder *webapps* which into the folder where Tomcat was installed. Once done, we just need to restart tomcat.





## Eidesstattliche Erklärung

Hiermit versichere ich, dass diese Abschlussarbeit von mir persönlich verfasst ist und dass ich keinerlei fremde Hilfe in Anspruch genommen habe. Ebenso versichere ich, dass diese Arbeit oder Teile daraus weder von mir selbst noch von anderen als Leistungsnachweise andernorts eingereicht wurden. Wörtliche oder sinn-gemäße Übernahmen aus anderen Schriften und Veröffentlichungen in gedruckter oder elektronischer Form sind gekennzeichnet. Sämtliche Sekundärliteratur und sonstige Quellen sind nachgewiesen und in der Bibliographie aufgeführt. Das Gleiche gilt für graphische Darstellungen und Bilder sowie für alle Internet-Quellen.

Ich bin ferner damit einverstanden, dass meine Arbeit zum Zwecke eines Plagiatsabgleichs in elektronischer Form anonymisiert versendet und gespeichert werden kann. Mir ist bekannt, dass von der Korrektur der Arbeit abgesehen werden kann, wenn die Erklärung nicht erteilt wird.

Ort, den Datum

Martin Mustermann