muRata
INNOVATOR IN ELECTRONICS

SF1141B-4

75.00 MHz SAW Filter

- ***Designed for SDARS IF Receiver***
- ***Low Insertion Loss***
- ***5.0 X 7.0 mm Surface-Mount Case***
- ***Differential Input and Output***
- ***Complies with Directive 2002/95/EC (RoHS)***



SMP-03-S

Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+10	dBm
Max. DC voltage between any 2 terminals	30	VDC
Storage Temperature Range	-40 to +85	°C
Max Soldering Profile	265°C for 10 s	

Electrical Characteristics

Characteristic		Sym	Notes	Min	Typ	Max	Units
Nominal Center Frequency		f_C	1		75.000		MHz
Passband	Insertion Loss at fc	IL			12.5	16.0	dB
	1dB Passband	BW_1	1, 2	±6.35	±7.43		MHz
	Fast Amplitude Ripple over fc ±6.35 MHz					1.5	dB_{P-P}
	Group Delay Variation over fc ±6.35 MHz	GDV			75	200	ns_{P-P}
Rejection	fc-100 to fc-18.8 MHz		1, 2, 3	40	45		dB
	fc-18.8 to fc-10.95 MHz			37	45		
	fc+10.95 to fc+18.8 MHz			30	36		
	fc+18.8 to fc+100 MHz			40	45		
Operating Temperature Range		T_A	1	-40		+85	°C
Differential Input and Output Impedance		250 ohms					
Case Style			6	SMP-03-S 7 x 5 mm Nominal Footprint			
Lid Symbolization (YY=year, WW=week, S=shift) See note 4				RFM SF1141B-4 YYWWS			

Electrical Connections

Connection	Port 1 Hot	Port 1 Ground Return or Hot	Port 2 Hot	Port 2 Ground Return or Hot	Case Ground
Terminals	10	1	5	6	All Others

CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

NOTES:

1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50 Ω and measured with 50 Ω network analyzer.
2. Unless noted otherwise, all frequency specifications are referenced to the nominal center frequency, fc.
3. The design, manufacturing process, and specifications of this filter are subject to change.
4. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
5. US and international patents may apply.

Tape and Reel Specifications



"B " Nominal Size		Quantity Per Reel
Inches	millimeters	
7	178	500
13	330	2000

COMPONENT ORIENTATION and DIMENSIONS

Carrier Tape Dimensions		Tolerance
Ao	5.5 mm	± 0.1mm
Bo	7.5 mm	± 0.1mm
Ko	2.0 mm	± 0.1mm
Pitch	8.0 mm	± 0.1mm
W	16.0 mm	± 0.2mm





SMP-03-S Case

12-Terminal Ceramic Surface-Mount Case
5 x 7 mm Nominal Footprint



Case Dimensions						
Dimension	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A	6.80	7.00	7.20	0.268	0.276	0.283
B	4.80	5.00	5.20	0.189	0.197	0.205
C		1.65	2.00		0.065	0.079
D		0.80				
E	2.41	2.54	2.67	0.095	0.100	0.105
H	0.87	1.1	1.13	0.034	0.039	0.044
J		2.54				
K	2.87	3.00	3.13	0.113	0.118	0.123
P	1.14	1.27	1.40	0.045	0.050	0.055

Materials	
Solder Pad Termination	Au plating 30 - 60 µinches (76.2-152 µm) over 80-200 µinches (203-508 µm) Ni.
Lid	Fe-Ni-Co Alloy Electroless Nickel Plate (8-11% Phosphorus) 100-200 µinches Thick
Body	Al_2O_3 Ceramic
Pb Free	



TOP VIEW



BOTTOM VIEW