Preliminary

muRata
INNOVATOR IN ELECTRONICS

RFM products are now Murata products.

SF1213D

462.5 MHz SAW Filter

- ***CDMA 450 F-Band RF SAW Filter***
- ***3.8 x 3.8 x 1.4 mm Surface-mount Package***
- ***Complies with Directive 2002/95/EC (RoHS)***



SM3838-6

Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+27	dBm
Maximum DC Voltage between any Two Terminals	30	VDC
Storage Temperature Range	-40 to +85	°C
Suitable for Lead-free Soldering - Maximum Soldering Profile	260°C for 30 s	

Electrical Characteristics

Characteristic		Sym	Notes	Min	Typ	Max	Units
Nominal 1 dB Center Frequency		f_C			462.5		MHz
Passband Insertion Loss	460.0 to 464.8 MHz	IL	1		2.8	3.5	dB
VSWR	460.0 to 464.8 MHz				1.9:1	2.4:1	
Rejection	0.3 to 450.0 MHz			40	45		
	450.0 to 455.0 MHz		1, 2, 3	35	46		
	485.0 to 505.0 MHz			40	50		dB
	505.0 to 1200 MHz			30	41		
	1200 to 2000 MHz			20	32		
Operating Temperature Range		T_A	1	-30		+80	°C
Impedance at f_c	Source, single ended	50 ohm					
	Load, single ended	50 ohm					

Case Style	SM3838-6 3.8 x 3.8 mm Nominal Footprint
Lid Symbolization (Y=year, WW=week, S=shift) dot=pin 1 indicator	642, YWWS
Standard Reel Quantity Reel Size 7 Inch	1000 Pieces/Reel
Reel Size 13 Inch	3000 Pieces/Reel

Electrical Connections

Connection	Terminals
Port 1	2
Port 2	5
Case Ground	All others

CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

Notes:

1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50 Ω and measured with 50 Ω network analyzer.
2. Unless noted otherwise, all frequency specifications are referenced to the nominal center frequency, fc.
3. Rejection is measured as attenuation below the minimum IL point in the passband. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
4. "LRIP" or "L" after the part number indicates "low rate initial production" and "ENG" or "E" indicates "engineering prototypes."
5. The design, manufacturing process, and specifications of this filter are subject to change.
6. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
7. US and international patents may apply.
8. Murata, stylized Murata logo, and Murata N.A., Inc. are registered trademarks of Murata Manufacturing Co., Ltd.

©2010-2014 by Murata Electronics N.A., Inc.



Passband Plot



Wideband Plot

©2010-2014 by Murata Electronics N.A., Inc.





VSWR





S11 and S22 Plots

©2010-2014 by Murata Electronics N.A., Inc.

Tape and Reel Specifications



"B " Nominal Size		Quantity Per Reel
Inches	millimeters	
7	178	1000
13	330	3000



COMPONENT ORIENTATION and DIMENSIONS

Carrier Tape Dimensions	
Ao	4.25 mm
Bo	4.25 mm
Ko	1.30 mm
Pitch	8.0 mm
W	12.0 mm



©2010-2014 by Murata Electronics N.A., Inc.

SM3838-6 Case

6-Terminal Ceramic Surface-Mount Case

3.8 X 3.8 mm Nominal Footprint



Case Dimensions						
Dimension	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A	3.60	3.80	4.0	0.14	0.15	0.16
B	3.60	3.80	4.0	0.14	0.15	0.16
C	1.30	1.50	1.70	0.05	0.06	0.067
D	0.95	1.10	1.25	0.037	0.043	0.05
E	2.39	2.54	2.69	0.090	0.10	0.110
G	0.90	1.0	1.10	0.035	0.04	0.043
H	1.90	2.0	2.10	0.75	0.08	0.83
I	0.50	0.6	0.70	0.020	0.024	0.028
J	1.70	1.8	1.90	0.067	0.07	0.075



PCB Footprint

Electrical Connections		
Connection		Terminals
Port 1	Single Ended Input	2
Port 2	Single Ended Output	5
	Ground	All others
Single Ended Operation Only		
Dot indicates Pin 1		

Materials	
Solder Pad Termination	Au plating 30 - 60 µinches (76.2-152 µm) over 80-200 µinches (203-508 µm) Ni.
Lid	Fe-Ni-Co Alloy Electroless Nickel Plate (8-11% Phosphorus) 100-200 µinches Thick
Body	Al_2O_3 Ceramic
Pb Free	

TOP VIEW





BOTTOM VIEW





©2010-2014 by Murata Electronics N.A., Inc.