muRata
INNOVATOR IN ELECTRONICS

To Be Discontinued

RFM products are now Murata products.

HO4050B1

622.08 MHz Differential SAW Oscillator



SMC-08A

- ***Quartz SAW Stabilized Differential Output Technology***
- ***Very Low Jitter Fundamental-Mode Operation at 622.08 MHz***
- ***Voltage Tunable for Phase Locked Loop Applications***
- ***Complies with Directive 2002/95/EC (RoHS)***

The HO4050B1 is a voltage-controlled SAW clock (VCSC) designed for phase-locked loop (PLL) applications in optical data communications systems. The differential outputs of the HO4050B1 are generated by high-Q, fundamental mode quartz surface acoustic wave (SAW) technology. This technique provides very low output jitter and phase noise, plus excellent immunity to power supply noise. The HO4050B1 differential outputs feature typical ±1% symmetry, and can be DC-configured to drive a wide range of high-speed logic families. The HO4050B1 is packaged in a hermetic metal-ceramic LCC.

Absolute Maximum Ratings

Rating	Value	Units
DC Suppy Voltage	0 to 5.5	Vdc
Tune Voltage	0 to 5.5	Vdc
Case Temperature	-55 to 100	°C

Electrical Characteristics

Characteristic		Sym	Notes	Minimum	Typical	Maximum	Units
Operating Frequency	Absolute Frequency	f_O	1		622.08		MHz
	Tuning Range		2		±100		ppm
	Tuning Voltage		1	0		3.3	Vdc
	Tuning Linearity		1		±5		%
	Modulation Bandwidth			200			kHz
Q and $\overline{Q}$ Output	Voltage into 50 Ω (VSWR ≤ 1.2)	V_O	1,3	0.60		1.1	V_{P-P}
	Operating Load VSWR		1,3			2:1	
	Symmetry		3, 4, 5	45		55	%
	Harmonic Spurious		3, 4, 6			-15	dBc
	Nonharmonic Spurious		3, 4, 6, 7			-60	dBc
Phase Noise	@ 100 Hz offset		3, 6		-70		dBc/Hz
	@ 1 kHz offset		3, 6		-100		dBc/Hz
	@ 10 kHz offset		3, 6		-125		dBc/Hz
	Noise Floor		3, 6		-150		dBc/Hz
Q and $\overline{Q}$ Jitter	RMS Jitter (10kHz to 80MHz)		3, 4, 6, 7		0.1		ps
	No Noise on V_{CC}		3, 4, 6, 7		12		ps_{P-P}
	200 mV_{P-P} Noise, from 1 MHz to ½ f_O on V_{CC}		3		12		ps_{P-P}
Input Impedence (Tuning Port)				8	10		KΩ
Output DC Resistance (between Q & $\overline{Q}$)			1, 3	50			KΩ
DC Power Supply	Operating Voltage	V_{CC}	1, 3	3.13	3.3	3.6	Vdc
	Operating Current	I_{CC}	1, 3			70	mA
Operating Case Temperature		T_C	1, 3	-40°C		+85°C	°C
Lid Symbolization (YY=Year, WW=Week)		RFM HO4050B1 YYWW					

CAUTION: Electrostatic Sensitive Device. Observe precautions for handling. COCOM CAUTION: Approval by the U.S. Department of Commerce is required prior to export of this device.

NOTES:

1. Unless otherwise noted, all specifications include the combined effects of load VSWR, V_{CC} and T_C.
2. Net tuning range after tuning out the effects of initial manufacturing tolerances, VSWR pushing/pulling, V_{CC}, T_C and aging.
3. The internal design, manufacturing processes, and specifications of this device are subject to change without notice.
4. Specified only for a balanced load with a VSWR < 1.2 (50 ohms each side), and a V_{CC} = 3.0 Vdc.
5. Symmetry is defined as the width in (% of total period) measure at 50% of the peak-to-peak voltage of either output.
6. Jitter and other noise outputs due to power supply noise or mechanical vibration are not included in this specification except where noted.
7. Applies to period jitter of either differential output. Measured with a Tektronix CSA803 signal analyzer with at least 1000 samples.
8. One or more of the following United States patents apply: 4, 616,197; 4,670,681; 4,760,352.

To Be Discontinued

SMC-8A 8-Terminal Surface Mount Case



Typical Printed Circuit Board Land Pattern

A typical land pattern for a circuit board is shown below. Grounding of the metallic center pad is optional.



Typically 0.01" to 0.05" or 0.25 mm to 1.25 mm (8 Places)

(The optimum value of this dimension is dependent on the PCB assembly proces employed.)

Electrical Connections

Terminal Number	Connection
1	Tune
2	*Enable
3	Ground
4	Ground
5	Q Output
6	$\overline{Q}$ Output
7	V_{CC}
8	Ground
LID	Ground



*Enable Sense: Pin 2 Ground-Clock Off

Dimensions

Dimension	mm		Inches	
	MIN	MAX	MIN	MAX
A	13.46	13.97	0.530	0.550
B	9.14	9.66	0.360	0.380
C	1.93 Nominal		0.076 Nominal	
D	1.93 Nominal		0.076 Nominal	
E	2.54 Nominal		0.100 Nominal	
F	1.27 Nominal		0.050 Nominal