muRata
INNOVATOR IN ELECTRONICS

Discontinued

RFM products are now Murata products.

SF1111A

160 MHz SAW Filter

- ***Designed for CDMA2000 BTS Applications***
- ***Simple External Impedance Matching***
- ***Hermetic SMP-97 Surface-Mount Case***
- ***Unbalanced Input and Output***
- ***Complies with Directive 2002/95/EC (RoHS)***



SMP-97

Absolute Maximum Ratings

Rating	Value	Units
Maximum Incident Power in Passband	+10	dBm
Max. DC voltage between any 2 terminals	30	VDC
Storage Temperature Range	-40 to +85	°C
Suitable for lead-free soldering - Max. Soldering Profile	260°C for 30 s	

Electrical Characteristics

Characteristic		Sym	Notes	Min	Typ	Max	Units
Nominal Center Frequency		f_C	1		160.000		MHz
Passband	Insertion Loss at fc	IL			9	11.0	dB
	1.5 dB Passband	$BW_{1.5}$	1, 2	±590			kHz
	3 dB Passband	BW_3			±750		
	Amplitude Ripple over fc ±470 kHz				0.7	1.0	dB
	Phase Linearity over fc ±590 kHz				10	20	deg_{P-P}
Rejection	fc-10.0 to fc-1.25 and fc+1.25 to fc+10.0 MHz		1, 2, 3	40			dB
	fc-20 to fc-10.0 and fc+10.0 to fc+20 MHz			50			
Operating Temperature Range		T_A	1	-20		+70	°C

Impedance Matching to 50 Ω Unbalanced	External L-C
Case Style	SMP-97 24.6 x 9 mm Nominal Footprint
Lid Symbolization (YY = year, WW = week)	RFM SF1111A YYWW

CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

NOTES:

1. Unless noted otherwise, all specifications apply over the operating temperature range with filter soldered to the specified demonstration board with impedance matching to 50 Ω and measured with 50 Ω network analyzer.
2. Unless noted otherwise, all frequency specifications are referenced to the nominal center frequency, fc.
3. Rejection is measured as attenuation below the minimum IL point in the passband. Rejection in final user application is dependent on PCB layout and external impedance matching design. See Application Note No. 42 for details.
4. "LRIP" or "L" after the part number indicates "low rate initial production" and "ENG" or "E" indicates "engineering prototypes."
5. The design, manufacturing process, and specifications of this filter are subject to change.
6. Either Port 1 or Port 2 may be used for either input or output in the design. However, impedances and impedance matching may vary between Port 1 and Port 2, so that the filter must always be installed in one direction per the circuit design.
7. US and international patents may apply.

Electrical Connections

Connection	Terminals
Port 1 Hot	10
Port 1 Gnd Return	1
Port 2 Hot	5
Port 2 Gnd Return	6
Case Ground	All others





SMP-97 Case

10-Terminal Ceramic Surface-Mount Case
24.6 x 9 mm Nominal Footprint



Case Dimensions

Dimension	mm			Inches		
	Min	Nom	Max	Min	Nom	Max
A	24.41	24.64	24.94	0.961	0.970	0.982
B	8.80	8.99	9.30	0.349	0.354	0.366
C		1.75	2.00		0.069	0.079
D		2.29			0.090	
E		1.02			0.040	
H		1.0			0.039	
M		4.83			0.190	
N		3.40			0.134	
P		1.905			0.075	

Materials	
Solder Pad Termination	Au plating 30 - 60 uInches (76.2-152 uM) over 80-200 uInches (203-508 uM) Ni.
Lid	Fe-Ni-Co Alloy Electroless Nickel Plate (8-11% Phosphorus) 100-200 uInches Thick
Body	Al_2O_3 Ceramic
Pb Free	

Electrical Connections

Connection		Terminals
Port 1	Input or Return	10
	Return or Input	1
Port 2	Output or Return	5
	Return or Output	6
Ground		All others
Single Ended Operation		**Return is ground**
Differential Operation		**Return is hot**



TOP VIEW

BOTTOM VIEW