

# Machine Learning 2 — Homework 6

Maurice Frank  
11650656  
maurice.frank@posteo.de

October 12, 2019

## Problem 1.

We have PDF  $p(x)$ ,  $x \in \mathbb{R}^d$  and the approximation of it  $q(x)$ .

1.

---

### Algorithm 1 Rejection Sampler

---

```
function SAMPLE_REJECTION( $q, \tilde{p}, c$ )  
   $acc \leftarrow False$   
  while  $acc == False$  do  
     $z_0 \leftarrow \text{sample}(q(z))$   
     $u \leftarrow \text{rand}[0, c \cdot q(z_0)]$   
     $acc \leftarrow u \leq \tilde{p}(z)$   
  end while  
  return  $z$   
end function
```

---

2.

Yes the generated samples are independent. We sample independently from  $q(z)$  which makes the accepted samples also independently.

3.

$$w_n = \frac{p(z_n)/q(z_n)}{\sum_m p(z_m)/q(z_m)}$$

4.

$$\begin{aligned}
 \alpha(x_{t+1}, x_t) &= \min \left( 1, \frac{\tilde{p}(x_{t+1})q(x_t|x_{t+1})}{\tilde{p}(x_t)q(x_{t+1}|x_t)} \right) \\
 &= \min \left( 1, \frac{\tilde{p}(x_{t+1})q(x_t|x_{t+1})}{\tilde{p}(x_t)q(x_{t+1})} \right) \\
 &= \min \left( 1, \frac{\tilde{p}(x_{t+1})q(x_{t+1}|x_t)q(x_t)}{\tilde{p}(x_t)q(x_{t+1})^2} \right) \\
 &= \min \left( 1, \frac{\tilde{p}(x_{t+1})q(x_t)}{\tilde{p}(x_t)q(x_{t+1})} \right) \\
 &= \min \left( 1, \frac{p(x_{t+1})q(x_t)}{p(x_t)q(x_{t+1})} \right)
 \end{aligned}$$

5.

A proposed sample using the proposal distribution is chosen independent of the previous sample:  $q(x_{t+1}|x_t) = q(x_t)$ . Whether or not the proposal is added to the chain though, is dependent on the previous sample's value. Thus two accepted successive samples in the chain are not independent of each other.

6.

When a proposal is rejected the independence sampler, samples the previous sample again:

$$[x_1, x_1, x_3, x_4, x_4]$$

7.

The rejection sampler compares the volumes between the proposal approximate distribution and the unnormalized true distribution. With higher dimensionality the acceptance ratio will become exponentially small. **TODO FINISH WRITING**

The importance sample importance sampler: no  
independence sampler: yes

**Problem 2.**

**Problem 3.**

1.

2.

3.

**Problem 4.**

1.

2.

3.

4.

5.

6.

7.

8.

9.

10.