

DuPont™ Tuff-R™ Polyisocyanurate Insulation

High-Performance Polyiso Foam with Dual Reflective Foil Facers

OVERVIEW

Description

DuPont™ Tuff-R™ Polyisocyanurate Insulation features high performance, high R-value, closed-cell polyisocyanurate foam core boards sandwiched between a choice of durable exterior foil facers. The polyisocyanurate insulation is created by an exclusive free-rise manufacturing process, which produces a uniform, closed-cell foam for better foam quality than conventional restrained rise process.

Tuff-R™ Insulation helps reduce air infiltration through the wall by covering cracks between the framing members and sealing tightly against the studs. One facer is a continuous sheet of aluminum foil; the other is a durable tri-laminate facer consisting of aluminum foil, kraft and metalized polyester film.



Features and Benefits

- **Ease of Installation:** Lightweight, easy to handle and install with a utility knife or any sharp blade
- **Adaptable and Versatile:** Come with a choice of durable facers depending on design requirements that can be nailed, stapled or glued. Compatible with most exterior siding treatments; ideal for brick, stone, aluminum, vinyl, wood, composite, fiber cement and stucco.
- **High Performance Durability:** Tri-Plex facers improve shipping, storage and job-site durability; less damage and job-site waste. High R-value provides enhanced thermal efficiency. Facers help reduce air penetration and water vapor intrusion allowing products to be detailed as a weather-resistive barrier.
- **Moisture Resistant and UV Stability:** Helps reduce the potential for condensation within the wall assembly

Sustainable Solutions

- **Ozone and Global Warming:** Zero ozone-depleting potential (ODP) and negligible global warming potential.
- Tuff-R™ Insulation is a continuous polyisocyanurate (polyiso) insulation engineered to fulfill key sustainability criteria;
- **Continuous Insulation (CI):** Aids in meeting IECC and ASHRAE 90.1 energy standards.
- **Energy Efficiency:** Glass fiber-reinforced foam core with high R-value. Reduces the carbon footprint by minimizing energy consumption for comfort.
- **Red List Approved:** 99% of ingredients in the final product, present at or above 100 ppm, are free from Red List chemicals and qualify for LEED v4 and v4.1 credits.
- **Sustainable Manufacturing:** Made from 100% renewable electricity. (DuPont has offset electricity usage with Renewable Energy Credits since 2016.)

Applications

- Over roof decks and in cathedral ceilings
- New frame wall construction behind masonry, siding, exterior stucco or other compatible finishes
- Exterior retrofit of existing walls under new exterior sidings
- Install Tuff-R™ Insulation products in residential construction where they will be covered with a minimum of 1/2" gypsum board, or equivalent, thermal barrier. Applications include:
- Interior retrofit of existing walls under a new interior finish of 1/2" (minimum) gypsum board

Warranty

- In the US, a 15-year limited thermal warranty is available. For additional warranty information, please visit building.dupont.com or contact your DuPont representative.