

ReadingMachine: A Computational Methodology for Structured Corpus Reading and Large-Scale Synthesis

James Morrissey

June 4, 2026

Abstract

The volume of written material produced across modern institutions now far exceeds the capacity of human analysts to read, interpret, and synthesize it comprehensively. Existing computational approaches—such as retrieval-augmented generation, hierarchical summarization, and agentic research workflows—scale access to information but typically operate over selectively accessed material, introducing risks of omission, early information loss, and limited analytical transparency. As a result, high-stakes synthesis tasks in research, policy, law, and organizational analysis remain constrained by partial coverage and limited inspectability.

This paper introduces ReadingMachine, a computational methodology for structured corpus reading that reframes large language models as systems for executing bounded reading operations alongside their use as generators of answers. Rather than producing synthesis in a single step, the method decomposes large-scale reading into a sequence of constrained, inspectable tasks—including insight extraction, semantic clustering, thematic schema construction, and iterative omission detection—prior to synthesis. By delaying irreversible compression and explicitly tracking intermediate representations, the approach prioritizes coverage, traceability, and the preservation of disagreement across large corpora. The approach is characterized by several design choices, including insight-level representation as the unit of synthesis, the use of clustering as scaffolding rather than determinant of themes, and explicit omission detection through orphan tracking, which together enable coverage-oriented, self-correcting synthesis under scale. The result is not synthesized output reading for general consumption, but instead an intermediate reading layer to aid with downstream decision-making.

The system is demonstrated on a heterogeneous corpus of 152 documents on industrial policy, producing over 17,500 atomic insights and a structured thematic mapping. We report system costs, runtime, qualitative characteristics of the output, and observed failure modes, including challenges related to synthesis under scale and omission detection. While formal comparative evaluation remains future work, a descriptive account of the results illustrates how structured corpus reading produces outputs that are substantively and epistemically distinct from conventional AI-based summarization.

ReadingMachine is released as an [open-source](#), experimental framework intended to support systematic qualitative synthesis and downstream, explicitly constrained reasoning over stable corpus representations. The paper positions structured corpus reading as a complementary mode of knowledge production, distinct from retrieval-based and agentic AI systems. The results should be un-

derstood as a demonstration of system behavior at scale rather than a validated assessment of performance, and collaboration on evaluation is actively encouraged.

1 Introduction

The volume of written information produced across modern institutions now far exceeds the capacity of any individual—or even coordinated teams—to read, interpret, and synthesize it. In domains ranging from academic research and public policy to organizational learning and legal analysis, the limiting factor is no longer access to information, but the ability to systematically engage with it. As a result, critical insights are routinely overlooked, minority perspectives are lost, and synthesized outputs reflect invisible omissions rather than the full structure of the underlying corpus.

Today, this problem is managed primarily through human-led review. Literature reviews, policy syntheses, and internal analyses rely on expert readers to select, interpret, and compress large bodies of text into coherent narratives. While indispensable, this approach is inherently constrained. Human review is slow and costly, limiting the size of corpora that can be feasibly analyzed. It is bounded by attention, making comprehensive coverage difficult to achieve in practice. And it is path-dependent: as reviewers read, their priors evolve, shaping subsequent interpretation and selection in ways that are rarely visible or reproducible. The resulting analyses are valuable, but they are also partial, contingent, and difficult to systematically audit.

Existing computational approaches do not resolve these limitations. Retrieval-based systems surface fragments of text but leave most of the corpus unexamined. Hierarchical summarization pipelines compress information early, often flattening disagreement and discarding nuance. Agentic research systems explore selectively, producing analyses that depend heavily on intermediate decisions and paths taken [?]. In all cases, omission is common and difficult to detect [?, ?].

This creates a fundamental constraint on knowledge work. As writing scales, reading does not—at least not in a way that preserves coverage, traceability, and consistency. The result is a growing mismatch between what is available to be known and what is actually incorporated into analysis. In high-stakes contexts, where decisions depend on comprehensive and faithful interpretation of large bodies of text, this gap introduces systematic risk.

ReadingMachine is designed to address this constraint directly. It begins from a different premise: the core challenge is not only reasoning over large corpora, but reading them.

Current applications of large language models have largely been developed as systems for generating answers—compressing information into outputs conditioned on queries. This framing has proven highly effective across a wide range of tasks, particularly where rapid synthesis, exploration, or question answering is required. However, it places emphasis on producing outputs from selectively accessed material, rather than systematically engaging with the full structure of a corpus.

For many use cases, this is entirely appropriate. But for tasks where coverage, traceability, and the preservation of disagreement are central, this framing leaves important aspects of the problem under-addressed. The limiting factor in large-scale analysis is not only the ability to generate answers, but the ability to systematically read and organize the underlying material.

Under this view, large language models can be more productively understood not only as general-purpose reasoners, but also as systems capable of performing bounded reading operations at scale. The central challenge is therefore not to produce a synthesis in a single step, but to coordinate many constrained acts of reading in a way that preserves structure and reduces omission.

The novelty of ReadingMachine lies not in improving model performance, but in how these capabilities are organized. The system decomposes large-scale corpus mapping into discrete, inspectable tasks—such as extracting atomic insights, grouping them semantically, and synthesizing them into themes—and coordinates language models to execute these tasks in sequence. This approach shifts compression to later stages of the pipeline and introduces explicit mechanisms to track, detect, and reintegrate omitted material.

This reframing has several implications. First, the marginal cost of reading—both in time and money—declines substantially, enabling analysis over corpora that would be impractical to process through human review alone. Second, by structuring reading as a sequence of explicit transformations, the system enables corpus-level analysis that emphasizes coverage (i.e. prioritizes achieving the incorporation of all relevant claims/arguments/insights from the corpus), traceability, and the preservation of disagreement, while making intermediate steps available for inspection. Third, by applying a computational approach, the system meaningfully increases the scope for structural reproducibility of qualitative data analysis. Fourth, separating reading from downstream interpretation increases transparency and allows reasoning to be applied more deliberately. Finally, because the components of the pipeline can be varied independently, the system supports controlled experimentation over how corpora are organized and interpreted.

This paper introduces ReadingMachine as both a technical framework and a methodological intervention. It outlines the architectural design of the system, the analytical assumptions it encodes, and the trade-offs it makes in shifting from selective, human-limited synthesis toward structured, inspectable corpus mapping. More broadly, it situates the approach within an information landscape where the central challenge is no longer producing knowledge, but ensuring that it can be systematically read, organized, and understood at scale.

The paper makes four contributions: (1) it introduces structured corpus reading as a methodological framing for large-scale synthesis; (2) it describes ReadingMachine, an open-source pipeline implementing this approach; (3) it demonstrates the system on a 152-document industrial policy corpus; and (4) it identifies observed scaling constraints and failure modes, including orphan persistence, context-pressure effects, and late-stage reflation.

Because the system produces a corpus map rather than a query response or short summary, direct comparison with RAG or standard summarization systems is not straightforward: the relevant evaluation question is not only whether the final prose is better, but whether the intermediate representation improves coverage, traceability, disagreement preservation, and downstream usefulness.

ReadingMachine is released as an experimental method and open-source implementation ([GitHub repository](#)). It is not presented as a finalized solution to large-scale synthesis, but as a structured approach that can be inspected, modified, and evaluated across different contexts and configurations. The properties described in this paper—such as improved coverage, omission detection, and traceability—should be understood as design objectives and observed behaviors in a single large-scale run, rather than as formally validated performance characteristics. Support on evaluation and testing of the tool is actively encouraged.

2 The Problem

The production of written language has scaled dramatically over time. From the printing press to digital publishing, networked communication, and mass storage, the rate at which text is generated has increased by orders of magnitude. Reading, however, has not undergone a comparable

transformation. While mass literacy expanded who can read, the act itself remains constrained by attention, time, and sequential comprehension. As a result, a structural imbalance has emerged: the supply of text grows exponentially, while the capacity to process it grows incrementally.

Large language models appear, at first glance, to resolve this constraint. They can process and summarize text at speeds and volumes far beyond human capability, and perform reliably on many comprehension and synthesis tasks. However, current approaches to applying these systems to large corpora inherit important limitations from their underlying architectures [?].

Retrieval-augmented generation (RAG), the dominant paradigm, operates by selecting subsets of a corpus in response to a query. Documents are chunked, indexed, and retrieved based on estimated relevance, with only the retrieved material entering the model’s context [?]. This introduces a fundamental limitation: material that is not retrieved is not analyzed, and the system has no visibility into what has been excluded. As a result, omission is both common and difficult to detect. As corpora grow, this problem is compounded by context constraints. Increasing the number of retrieved passages places pressure on the model’s attention, leading to known degradation effects such as the “missing middle,” where portions of the input receive less effective processing [?], and dropped insights during synthesis/integration [?].

Hierarchical summarization pipelines take a different approach, but encounter related issues. By compressing documents into summaries and then recursively summarizing those summaries, these systems introduce information loss early in the process. Minority or low-frequency claims are often dropped, disagreements are smoothed, and the resulting representations tend toward generalization at the expense of specificity. Each stage of compression reduces the recoverability of the original material [?]. Problems of missing middle and dropped insights during synthesis/integration repeat here as context window pressure grows [?, ?].

Agentic research workflows attempt to mitigate these issues through iterative search and refinement. However, because they depend on sequences of intermediate decisions—what to query, what to retrieve, how to interpret—small variations in prompts or trajectories can produce substantially different results [?, ?]. Coverage remains partial, and omissions remain implicit.

For these reasons, high-stakes synthesis tasks over large corpora continue to rely on human-led review. This approach provides judgment and contextual interpretation, but it does not resolve the underlying scaling problem. Human review is slow and expensive, limiting the feasible size of a corpus. It is constrained by attention, making comprehensive coverage difficult in practice. And it is path-dependent: as reviewers read, their priors evolve, shaping subsequent interpretation and selection in ways that are not fully observable or reproducible.

The result is a persistent gap between what is written and what is systematically understood. In contexts where omission is costly—such as policy analysis, legal review, or scientific synthesis—this gap introduces a form of structural risk. The challenge is not simply to access or summarize information, but to read large corpora in a way that preserves coverage, traceability, and the internal structure of arguments.

3 ReadingMachine: Structured Corpus Reading

To address these limitations, ReadingMachine proposes a different approach to large-scale corpus analysis. Rather than retrieving subsets of documents or compressing texts through successive summaries, the system performs a structured reading pass across the **entire** corpus, extracting and

organizing atomic insights prior to synthesis.

The core design principle is to separate reading from interpretation. This distinction is important. Many contemporary applications treat language models as general-purpose reasoning systems, capable of synthesizing and evaluating complex bodies of information in a single pass. ReadingMachine adopts a different approach: it decomposes the act of reading into bounded, inspectable tasks—such as insight extraction, semantic cluster summarization, and theme formation. This constrains the model to perform narrowly defined reading tasks over bounded inputs, and defers interpretation, evaluation, and judgment to the researcher or downstream analysis. The system is therefore not designed to “reason over” a corpus, or to determine which claims are correct, important or true in a corpus, but to produce a structured representation of what the corpus contains. At the same time, this approach preserves traceability between synthesized outputs and their source material.

The architecture also implements explicit mechanisms to ensure coverage and to preserve conflict during synthesis. This structure is intended to reduce omission, maintain granularity, and make the analytical process inspectable and reproducible.

4 Methodology

ReadingMachine operates over a wide range of natural-language corpora, including academic literature, policy reports, organizational documents, legal materials, and qualitative data. It is designed for structured synthesis tasks over a defined corpus.

ReadingMachine is not a systematic review method: it does not assess study quality, weight evidence, or produce adjudicated conclusions. Its purpose is corpus mapping—structuring what a defined body of text contains. In this respect the method is closer to a “scoping study” as articulated by Arksey and O’Malley [?]. ReadingMachine achieves this through a computational approach that coordinates structured reading passes over the entire corpus to produce a thematic map of its contents without adjudicating evidentiary quality.

At the same time, the pipeline draws on the logic of reflexive thematic analysis [?], particularly the progression from coding to theme development, review, and refinement. Extracted insights function as computational analogues of codes, while theme construction and iteration are implemented as explicit, inspectable stages.

In abstract form, the workflow can be understood as:

reading a corpus → extracting insights → organizing them into themes → synthesizing → checking for completeness → refining structure

This process is implemented as a sequence of constrained, inspectable transformations. Each stage isolates a specific analytical function—such as insight extraction, clustering, or thematic synthesis—so that intermediate representations remain visible and omissions can be detected and corrected. Interpretive judgments are not removed, but they are externalized and structured, allowing them to be inspected and compared across runs.

The resulting pipeline is shown below in Figure ??.

The system is implemented, in Python, as a sequential pipeline in which each stage transforms a shared state object. Analytical choices—such as the definition of insights, extraction instructions, clustering parameters, and theme construction rules—are fixed, inspectable, and version-controlled, making the structure of the synthesis explicit rather than embedded in a single opaque step.




Figure 1: The system decomposes corpus analysis into structured reading stages, extracting atomic insights prior to synthesis. Clustering provides semantic scaffolding for theme generation, while synthesis occurs at the theme level. An explicit orphan detection and reinsertion mechanism enforces coverage, and an iterative loop refines the thematic schema until stable.

4.1 Generate Research Questions

Prior to processing the corpus, the user defines a set of research questions that guide the analysis. These questions determine what constitutes a relevant insight and shape all subsequent stages of the pipeline. ReadingMachine does not generate or refine these questions; they reflect the user’s analytical intent and frame the scope of the synthesis.

4.2 Ingest and Chunk the Corpus

Documents are ingested into the system, with the current implementation supporting PDF and HTML formats. During ingestion, basic metadata (e.g., title, author, year) is extracted using a language model.

The corpus is then divided into smaller semantic units through a chunking process. Chunking uses a greedy, size-constrained strategy to produce segments of approximately fixed length (e.g., ~3500 characters), ensuring consistent coverage of the source text. Within each segment, the splitter preferentially backtracks to the nearest paragraph break, sentence boundary, or whitespace to avoid arbitrary truncation where possible. Preserving strict size constraints takes priority over perfect semantic boundaries.

4.3 Generate Insights

Each chunk is processed alongside the full set of research questions. The language model is instructed to extract discrete insights—defined as atomic claims, arguments, or findings in the text that are relevant to the questions. Each insight is returned as a concise, one- to two-sentence statement. “Atomic” here refers to the smallest operational unit of representation within the system, not to a non-interpretive or pre-analytic unit of meaning.

Insights are formally defined in the prompt as:

“any explicit claims, arguments, findings, or statements in the text that bear on [the question[s]... An explicit claim includes: stated findings or conclusions, causal statements (e.g. X leads to Y), explanations of mechanisms or processes, descriptive statements that clearly assert a relationship, condition or effect. They are not restricted to formal conclusions [as] many valid claims appear as descriptive or explanatory statements. Each [insight] must be concise (one sentence or short phrase) and preserve wording as much as possible.”

To complement this chunk-level pass, the system performs a second, document-level pass. In this stage, the full document (or the largest portion that fits within the model’s context window) is processed with each research question individually. The model is provided with the previously extracted chunk-level insights and instructed to identify additional insights without repetition.

Insights are distinguished from meta-insights as follows in the prompt:

“[meta-insights are] higher-level, traceable arguments or conclusions that span across multiple parts of a text ... Chunk-level insights capture localized claims. [meta-]insights ... ONLY become visible when combining information across multiple parts of the document. [meta-insights] must introduce a substantively new claim that only becomes visible when considering multiple parts of the document together”

This dual approach captures both localized claims and broader arguments that span multiple sections of a document, reducing the likelihood that cross-cutting ideas are missed during chunk-level processing.

4.4 Cluster Insights

Extracted insights are organized using unsupervised learning techniques to group semantically similar claims. Clustering is not a replacement for a conceptual mapping, but serves as scaffolding to the process of conceptual theme generation—see below. This is necessary to afford the model a structured representation of the corpus, upon which to build themes.

Clustering proceeds in a fashion similar to that used in BERTopic [?]. Each insight is first converted into a vector representation (embedding). Because these embeddings exist in a high-dimensional space, dimensionality reduction is applied using UMAP, due to its speed and flexibility [?], to improve clusterability and mitigate sparsity effects associated with high-dimensional data.

Clustering is then performed using HDBSCAN, due to its robustness to parameter selection and effective density-based approach [?], which groups insights based on density while allowing for the identification of outliers. The system includes parameter sweep functionality to support selection of appropriate configurations. UMAP parameters are evaluated using silhouette scores, with research questions used as reference labels to assess separation (the user can exclude subsets of research questions in cases of conceptually overlapping questions). HDBSCAN configurations are assessed using a combination of Davies–Bouldin scores and outlier minimization. Note that while clustering generates the semantic surface that theme generation operates over (see below), it does not fundamentally determine themes. Themes are instead iteratively refined via an orphan reinsertion and re-theming loop (see below).

Dimensionality reduction is applied globally across the insight set, while clustering is performed separately for each research question. From this stage onward, all subsequent steps operate on a per-question basis. The final output is therefore composed of parallel syntheses for each research question.

This design introduces some redundancy across the overall report, as similar insights may appear in multiple question-specific outputs. This is intentional: each question is treated as a self-contained analytical unit, allowing users to engage with individual sections independently without requiring full traversal of the entire synthesis. This is a common reading style for literature synthesis.

4.5 Theme Generation

Clusters group insights by semantic similarity, providing a useful approximation of structure within the corpus. However, semantic proximity does not necessarily correspond to conceptual organization. This distinction is important methodologically. In Braun and Clarke’s account [?], themes are not simply discovered as pre-existing clusters in the data; they are actively constructed through analytic judgment. ReadingMachine preserves this distinction by using clustering only as scaffolding for thematic interpretation, rather than treating clusters themselves as themes. To move from semantic groupings to analytically meaningful categories, the system generates themes through a two-stage process.

First, each cluster of insights is summarized. Clusters are processed in an order determined by the shortest path between cluster centroids in the embedding space. This ordering places semantically similar clusters adjacent to one another. As each cluster is summarized, the last five generated

summaries are provided as frozen context for subsequent steps. This allows for local coherence without risking anchoring on initial clusters summaries (which could happen if global context was frozen). All clusters, including outliers, are included in this process.

The result is a sequence of cluster summaries that forms a structured narrative of the corpus, organized by semantic proximity and with reduced repetition. This narrative serves as the input for theme generation, allowing the model to operate over an ordered representation of the corpus rather than a disorganized set of individual insights.

Second, the cluster summary narrative is passed to a language model to generate a theme schema. This schema defines a set of thematic categories (theme label and theme description), along with rules for assigning insights to each theme. The schema includes an *Other* category to capture minority insights that do not warrant a dedicated theme, preventing unnecessary proliferation of categories. This category is distinct from clustering outliers; outlier insights may be assigned to any theme based on their content.

The schema also includes a *Conflicts* category when substantively incompatible claims are present. This is introduced explicitly to counter the tendency of language models to smooth disagreement during summarization and to preserve contested areas of the corpus. Conflict is defined in the prompt as:

“claims, or prescriptions that cannot be jointly maintained within a single coherent analytical frame. [Conflicts are not]: multiple reinforcing critiques, layered constraints or complexities, [the articulation of] trade-offs within a shared analytical orientation, [expressions of] variations that do not represent incompatible positions. Conflicts ... [require] identifiable polarity between positions”

The output of this stage is a theme schema that represents a conceptual mapping of the corpus. Themes function as structured containers for insights, enabling synthesis at the level of arguments rather than documents.

4.6 Theme Mapping and Population

Once a theme schema has been defined, insights are assigned to themes. Insights are processed in batches alongside the schema, with the language model instructed to map each insight to one or more relevant themes based on the inclusion and exclusion rules generated in the schema development pass. A single insight may be associated with multiple themes where appropriate. The *Other* category is populated both according to its defined criteria and as a fallback for insights that do not clearly fit within existing themes. Additional controls are applied to ensure that the language model only returns valid insight identifiers for each batch.

After all insights have been mapped, each theme—now represented as a theme label, theme description, and collection of associated insights—is passed to the language model for summarization. Because synthesis operates directly over structured insight sets rather than full documents or intermediate summaries, compression occurs at a late stage in the pipeline. Each theme is generated independently, using only the insights assigned to it, which allows the model to focus on a bounded and conceptually coherent subset of the corpus during each synthesis step.

It is worth noting that compression does occur at multiple stages of the pipeline, prior to summarization: during clustering (dimensionality reduction) and schema generation. However, these compressive acts are used to organize the insight space. They are not destructive compressive acts

in that they do not replace or discard the underlying insight set. Irreversible compression occurs only at the point of theme-level synthesis, which operates directly over the full set of assigned insights, and even then raw insights are reinserted in the orphan handling loop—see below.

4.7 Orphan Handling

To reduce omission risk during theme-level synthesis, the pipeline explicitly identifies and reintegrates orphan insights. Orphans are **NOT clustering outliers or insights assigned to the Other category**. Rather, they are insights that were mapped to a theme but do not appear in that theme’s synthesized summary. As such, they represent omissions introduced during the theme synthesis stage. This design responds to known long-context failure modes, including position sensitivity and incomplete coverage of relevant insights during summarization [?, ?].

Orphan detection is performed by comparing the set of insights assigned to each theme with the content of the corresponding theme summary. Insights are processed in batches alongside the summary, and the language model is instructed to identify which insights are substantively represented. Any assigned insights not identified in this process are classified as orphans. The Orphan identification prompt is intentionally strict to drive false positives, as a guard against omission.

Once identified, orphan insights are reintroduced, with orphans and the current theme passed to a language model with instructions to insert them into the existing theme, and return a full re-write. Orphan handling therefore is a mechanism for pursuing coverage at the theme level. This serves to reduce the likelihood of silent omission during synthesis. Orphan insertion also plays a central role in theme iteration (see below)

4.8 Theme Iteration

The initial theme schema is generated from cluster summaries, which introduces an early stage of compression. As a result, the initial set of themes may not fully capture the granularity or range of insights present in the corpus. After orphan handling, all insights have been forcibly incorporated into the existing themes, which can strain or destabilize the initial thematic structure.

To address this, the pipeline regenerates the theme schema using the current theme summaries as input. This second pass operates over a representation that now includes all insights, allowing the model to refine, split, or reorganize themes to better reflect the underlying material. Following schema regeneration, insights are remapped to themes, summaries are regenerated, and orphan handling is applied again.

This theme generation → mapping → orphan handling loop is repeated iteratively. This iterative review process parallels the theme review and refinement phases described by Braun and Clarke [?], in which candidate themes are checked against the underlying data and revised where they fail to adequately capture the dataset. In ReadingMachine, orphan detection operationalizes this by identifying insights that have not been substantively represented in the current thematic synthesis. In the current implementation the model is instructed not to make speculative improvements to the schema and only offer an updated schema when the input material shows obvious opportunities for improved structuring. In this respect an ideal schema prioritizes:

1. Conceptual coherence within each theme
2. Clear conceptual boundaries between themes
3. Complete conceptual coverage of the data
4. Minimizing reliance on the ‘Other’ category only if the above are satisfied

5. Minimizing the number of themes only if the above are satisfied

If the model cannot see obvious improvements for a question’s themes, they are all marked as stable. Only unstable themes are passed to future iterations. Once all themes are stable the user is instructed to move to redundancy handling and summarization. In future it likely makes sense to provide some formal measure of schema stability to track how it evolves over time considering: stability of themes, size of Other category, stability of insight allocation to themes, number of orphans etc.

4.9 Redundancy Pass

Because themes are generated and populated independently, and because individual insights may be assigned to multiple themes, redundancy across theme summaries is expected. To address this, the system includes an optional redundancy reduction pass.

In this stage, theme summaries for a given research question are processed sequentially, with previously generated summaries provided as context. The language model is instructed to reduce repetition by introducing cross-references (e.g., “as discussed above”) while preserving all substantive content.

This step improves readability but introduces a risk of information loss, particularly for insights that were marginal or recently reinserted during orphan handling. For this reason, the redundancy pass is optional. Users can choose between a completeness-first output, which retains some repetition, and a readability-first output, which reduces redundancy at the potential cost of minor omissions.

4.10 Rendering

The final stage of the pipeline produces a structured output that can be rendered as a report. This includes optional generation of a title, executive summary, and research question–level summaries, each created through targeted language model calls.

An additional optional step applies a stylistic rewrite to improve readability. In this pass, theme summaries are processed sequentially, with prior sections provided as context, and the model is instructed to vary phrasing and reduce repetitive or mechanical language. The goal is to produce a more natural and readable document without altering the underlying content.

As with the redundancy pass, this step introduces a trade-off. While it improves readability, it carries a risk of minor information loss or unintended modification of phrasing. It is therefore optional, allowing users to choose between a more literal, completeness-preserving output and a more polished, reader-friendly version.

The final output can be rendered as a PDF, markdown, or Word document.

5 Scaling the methodology

The primary scaling constraint for any LLM is the context window, which comprises both input and output tokens. In addition to this hard limit, there are softer constraints related to attention degradation and “missing middle” effects, which arise when the context window becomes large or contains complex content. The methodology described above is designed primarily to mitigate these soft limitations by constraining the load placed on the model: bounding reading tasks, batching operations, explicitly identifying and reinserting omissions, and iterating on thematic structure.

However, when applied to large and heterogeneous corpora, the method can encounter hard context window limits at specific stages of the pipeline. These limits were observed in practice during large-scale execution. In particular:

- too many insights passed during cluster summarization (input window exceeded)
- too many insights passed during theme population (input window exceeded)
- too many orphans passed during reinsertion (input window exceeded)
- the requirement to represent all orphans while maintaining insight-level granularity during reinsertion can exceed the output window, resulting in truncated outputs

These constraints do not invalidate the methodology, but they do affect how its core properties—coverage, granularity, and structured synthesis—can be maintained under finite context limits. When intermediate representations cannot be fully processed, downstream stages operate on partial inputs, increasing orphan counts and placing additional pressure on reintegration steps. If unaddressed, this can propagate through the pipeline and degrade the system’s ability to maintain a complete and structured representation of the corpus.

To preserve the methodological commitments of the system under these constraints, a set of modifications were introduced. These modifications do not alter the underlying logic of the pipeline, but adapt its execution to operate within bounded context windows while maintaining coverage through iterative reintegration and refinement.

The following sections describe these adjustments.

5.1 Too many insights per cluster

To address cases where clusters contain more insights than can be processed within the context window, a secondary, density-seeded partitioning method is introduced. This method subdivides clusters—including outliers—into smaller, semantically coherent partitions that fall within the model’s input constraints, while preserving the underlying structure of the insight space.

The initial clustering step proceeds as described above, using UMAP for dimensionality reduction and HDBSCAN for density-based clustering. For any cluster exceeding a predefined size threshold (k), the following partitioning procedure is applied:

- Calculate the required number of partitions: $\text{ceil}(\text{cluster size} / k)$
- Use HDBSCAN to identify the single densest point in the cluster and assign it as a seed
- Identify the nearest neighbors to that seed, up to k points and remove these points from the data pool
- Repeat steps 2 and 3 until all partition seeds have been initialized
- Return all data points to the pool, along with the identified seeds
- Allocate points to partitions using a round-robin assignment based on nearest-neighbor distance to each seed, removing each point once assigned
- Continue until all data points have been allocated

This process produces a set of semantically meaningful sub-clusters, each of size $< k$, including those derived from outlier regions. These partitions are then ordered by shortest distance between their centroids and summarized using the frozen-context procedure described above.

This adjustment allows cluster-level summarization to proceed within context limits while preserving local semantic structure. During implementation k is set smaller for outliers than it is for HDBSCAN clusters, to account for the greater heterogeneity of the former.

5.2 Too many insights passed to a theme during population

In cases where the number of insights mapped to a theme exceeds the model’s input capacity, a sampling strategy is introduced to ensure that theme population can proceed within context limits. Specifically, insights are greedily and randomly sampled up to a fixed threshold (e.g., ~70,000 words), ensuring that the input window is not exceeded.

This introduces partial visibility at the point of theme synthesis. However, this does not undermine the overall objective of coverage. The architecture is designed to recover omitted material through the orphan identification and reinsertion process, combined with iterative theme schema refinement. In this way, sampling acts as a temporary constraint on individual synthesis steps, while coverage is pursued across iterations of the pipeline.

This adjustment allows theme population to operate within bounded input constraints while maintaining the broader integrity of the method.

5.3 Too many orphans passed to reinsertion loop

In cases where the number of orphan insights exceeds the model’s context window, orphan reinsertion is performed in batches. Each batch of orphans is processed sequentially, with the full theme summary rewritten at each step.

This approach increases computational cost, as the entire theme output is regenerated for each batch. However, given the central role of orphan reinsertion in maintaining coverage and refining the thematic structure, this trade-off is necessary. Batching allows the reintegration process to proceed within context constraints while preserving the system’s ability to iteratively incorporate omitted material.

5.4 Output constraints and synthesis under bounded length

A further constraint arises from the requirement to represent all orphan insights while maintaining insight-level granularity within a finite output limit. During orphan reinsertion, this can cause the model to exceed its maximum output tokens. When this occurs, outputs are truncated and invalid JSON is returned.

This failure reflects a structural limit: it is not always possible to fully represent all assigned insights at the required level of granularity within a single bounded output. Rather than treating this solely as an execution failure, the system uses it as a diagnostic signal of excessive conceptual heterogeneity within a theme.

This is handled as follows:

1. When an orphan insertion batch fails:
 - (a) A detailed summary of the failed batch is generated.
 - (b) The insertion process proceeds to subsequent batches.
 - (c) Once all batches have been processed, the failed batch summaries are appended to the theme summary.
 - (d) The theme is marked as incomplete; themes with no failed batches are marked as complete.

2. The resulting themes—now including summaries of failed insertions—are passed back to the theme schema generation step, with explicit instructions to prioritize resolving these failures. This is done primarily by splitting themes, and only by redistributing concepts where other themes have sufficient capacity, i.e., conceptual coherence and manageable size.
3. This process is repeated until all themes pass the completeness check.

Under this design, orphan handling serves not only to address omission and refine the thematic structure, but also to operationalize synthesis under bounded output constraints.

5.5 Performative repair

Step 2, above, was initially attempted as a single LLM call. This did not work reliably: the schema repair pass repeatedly reproduced the same failing themes even when given explicit instructions to materially amend them. Providing additional context, including the full history of prior schemas, efforts at population, including failed repair attempts, did not resolve the issue. A self-reported repair accountability mechanism was then added, requiring the model to explain what repairs it had made. This also failed: the model sometimes retained the unchanged failing themes while reporting that repairs had been implemented.

This failure mode suggests that, under schema-repair pressure, the model could satisfy the rhetorical form of repair without performing the underlying structural transformation required to resolve the failure. One interpretation is that the model preferentially stabilized conceptually coherent schemas even when those schemas were operationally incompatible with bounded synthesis constraints.

An initial solution was to separate repair diagnosis from repair implementation. In the first pass, the model generated a schema repair plan based on the history of failed schemas and incomplete themes. In the second pass, a separate call implemented that plan against only the most recent schema, without access to the prior summaries or accountability narratives. The model priors towards producing conceptually coherent synthesis object however was so strong that the repair planner became too averse to splitting conceptually coherent themes even when the system was clearly being shown that they were conceptually overloaded and could not pass orphan reinsertion.

The eventual solution was to split the repair pass first into a decomposition prompt where the sole aim was to break up failing themes into smaller unit, by taking out the largest coherent cluster of concepts that could stand alone as a theme without itself resulting in conceptual overload. This pass had to make no mention of conceptual elegance. Only after a theme was decomposed to that it would survive orphan insertion without errors was it passed it to an optimization prompt which was instructed to recombine coherent conceptual groups and clarify boundaries, so long as this did not risk recreating conceptual overload for any theme. After optimization themes are passed again through the orphan insertion loop to see if they remain viable. If the optimizer can see no obvious opportunities for improvement it defines the schema for the question as "stable". Once all question schema are stable, the iterative process completes.

5.6 Dropped citations

The demands on orphan insertion (large numbers of orphans) eroded citation retention. Citations for papers that produced insights would drop out of the final summary altogether - such that around 1/3 of the total citations were missing from the final paper. This raises the possibility that underlying insights were also being lost during iterative synthesis, although the batched orphan

architecture suggests citation erosion was more common than complete insight deletion. To handle this:

1. After theme population an LLM call on the theme summary identifies all current citations
2. With each orphan batch the list of required citations is sent to the LLM, along with the batch of orphan insights to be incorporated. The instructions are to incorporate orphans and ensure that all the citations in the list appear in the theme.
3. This is bootstrapped by a final citation check where the set of citations for the insights mapped to the theme is compared with the insights currently appearing in the theme. For any missing citations, all the insights for those citations for the theme, are then sent to an LLM with instructions to insert distinct citations at least once.

Notably this approach to citation repair did not initially work. Even though the model was provided with a full set of required citations and the relevant insights to insert it would not successfully reinsert them. The hypothesized reason for this is similar to that explaining failed schema repair: the model is trained to output coherent readable paragraphs; these do not generally include large numbers of citations behind general claims. This preference persisted even when the model was explicitly instructed to stuff the citations. In testing, only about one third of the missing citations would get inserted into the text. To address this an approach similar to that used in schema repair was adopted, whereby instead of asking the model to both track insertion of missed citations and generate an updated complete synthesis, the model was tasked with generating a repair patch the inserted the citations. This could instruct the addition of a citation to an existing claim or the addition of a new sentence to reflect the claim. The patch included, verbatim, the sentence to be replaced, or the preceding sentence. These were then deterministically replaced in python. The model occasionally errored in returning the exact sentence which is what is thought to account for the loss of citations. This problem should be fixable through the use of a fuzzy match on sentences or via a semantic match. This approach was not however implemented in this version of the tool.

The issue of dropped citations raises a question about the role we expect citations to play in the synthesis. It would be technically possible to have every claim list every citation that supports it in the paper, but this would undermine readability and erode token budgets where the hard constraint on operationalizing the pipeline is bounded output length. A compromise was therefore adopted that looks something more like human review. All claims should be cited, with no claim needing more than four citations, prioritizing the most prominent. At the same time, all authors that produce insights for a theme should appear at least once in the theme. In the final output this is partially achieved. The theme summary does not invoke more than four citations to support a point, but the citation repair can insert as many as it likes. The result is some claims supported by large numbers (e.g. 14) of citations. This slightly undermines readability, but for an intermediate reading layer this is considered acceptable.

6 Methodological Contributions

Within this method the following novel methodological contributions to large-scale qualitative corpus analysis are worth highlighting:

- **Insight-level representation** as the atomic unit of synthesis, enabling late-stage integration over granular claims rather than early document-level compression.

- **Formal semantic clustering as scaffolding for qualitative thematization**, with clustering used to expose structure rather than to determine themes.
- **Scale-aware synthesis techniques**, including shortest-path cluster ordering and density-seeded partitioning to preserve semantic neighborhoods under bounded context windows.
- **Orphan-based omission detection**, which treats synthesis gaps as explicit signals and uses them to iteratively refine thematic schemas under coverage constraints.
- **External auditing of iterative LLM synthesis**, using explicit conservation checks for coverage, provenance, thematic coherence, and citation retention across repeated generative transformations

Individually, some of these components draw on existing techniques from qualitative analysis and NLP. Their novelty lies in being operationalized together as a single, inspectable pipeline for corpus-level reading that prioritizes coverage, traceability, and self-correction under scale.

7 Results

7.1 Evaluation Status

The results from ReadingMachine should be understood as a demonstration of system behavior at scale, rather than a formal evaluation of performance. To date, evaluation consists of a single large-scale corpus run and internal qualitative review.

The system was applied to a [corpus](#) of 152 documents on industrial policy. The corpus is heterogeneous, including academic papers, institutional reports (including long-form documents exceeding 400 pages), books, and web-based materials. The analysis was guided by research questions developed through Oxfam America’s formal research processes, reflecting real organizational priorities.

The resulting output was reviewed internally by research staff at Oxfam America. The outputs were assessed as substantively coherent and broadly aligned with existing domain understanding. This review indicates that the system produces plausible and interpretable representations of the corpus. However, it does not constitute a systematic or independent evaluation of performance.

Formal evaluation remains an open area of work. Key directions include:

- Expert review of outputs by domain specialists (e.g., macroeconomists and political economists working on international development)
- Application across additional domains and corpora, with corresponding expert assessment
- Comparative analysis against retrieval-augmented generation (RAG), hierarchical summarization pipelines, and off-the-shelf AI tools (noting that outputs differ in structure - see below - and require appropriate evaluation frameworks)
- Formal benchmarking of system behavior
- Evaluation of the practical usefulness of the outputs

To support this process, this paper constitutes an open invitation to domain experts to [review the industrial policy output](#). Reviews may be submitted via a structured evaluation form and will be published in the project’s GitHub repository as part of an open review archive. Further collaboration on systematic evaluation, including cross-domain testing and benchmarking, is actively invited.

7.2 Experimental Setup

The corpus was constructed using the ReadingMachine *getlit* module, which combines structured search, LLM-assisted retrieval of grey literature, and human filtering. This produced a corpus of 175 documents, of which 152 returned insights. This corpus is intentionally demanding: it is large, spans a diverse literature, and includes multiple document types, including webpages, academic papers, long institutional reports, and books. The final output included 137 citations.

The analysis was guided by the following research questions:

- What drivers account for the resurgence of industrial policy in both highly industrial and industrializing countries?
- How have the definitions and approaches to industrial policy shifted from the post-World War II period to the present, particularly with respect to sustainability, equality, and human rights?
- What challenges and constraints do less-industrialized countries face in implementing effective industrial policy?
- What recommendations can be made to industrialized countries to reduce harm to less-industrialized countries?
- What reforms to transnational institutions could expand policy space for less-industrialized countries?

The pipeline was also provided with contextual framing derived from Oxfam’s Terms of Reference for the research. This framing informed both document retrieval and insight extraction, ensuring that the corpus and subsequent analysis were aligned with the intended scope of inquiry.

7.3 System Metrics

The following metrics describe system behavior observed in a single large-scale run. They are presented as descriptive indicators of execution and output structure, rather than as measures of performance.

The full pipeline execution required approximately 14 hours and incurred a total cost of approximately \$300.

Core system metrics include:

Variable	Value
Document count	152 (175)
Final citation count	137
Total run cost	~ \$300
Insight count	17752
Chunk insight count	12166
Meta insight count	5633
Cluster count	169
Runs to stable schema	5
Theme counts	34, 34, 34, 34, 34
Orphan counts	14008, 15092, 15318, 14927, 15657
Failed theme counts	4, 2, 2, 1, 0

7.4 Example Insights

The following examples illustrate the form and level of granularity of extracted insights. They are drawn from the output of the system.

Question	Insight type	Insight
What challenges and constraints do less-industrialized countries face in implementing effective industrial policy?	Chunk insight	‘Many developing countries had been busy dismantling their industrial policies during the 1980s and the 1990s, which poses a challenge in realizing effective industrial policy now (Chang and Andreoni 2020).’
What drivers account for the resurgence of industrial policy in both highly industrial and industrializing countries?	Meta insight	‘The resurgence of industrial policy in both highly industrialized and industrializing countries is driven by the dual objectives of technological advancement and environmental sustainability, as seen in China’s push for electric vehicles to enhance competitiveness and reduce urban air pollution (Altenburg, T.; Assmann, C. 2017).’

7.5 Qualitative Observations

The [output](#) produced by the system is notable for its scale and density; readers are encouraged to inspect it directly. Even at a glance, it differs from conventional AI-generated summaries in ways that are immediately apparent:

- **Length:** The document is substantially longer than typical AI-generated outputs, often extending to tens of thousands of words.
- **Density:** Sections are tightly packed with discrete claims, with relatively little compression into high-level generalizations.
- **Granularity:** Specific mechanisms, conditions, and qualifications are retained rather than absorbed into broader summaries.
- **Persistence of detail:** The output does not quickly converge to a concise narrative; instead, it maintains a large number of localized statements drawn from across the corpus.
- **Coherence under scale:** Despite the volume of detail, sections read as continuous, structured prose rather than fragmented or list-like outputs.
- **Breadth without compression:** The document remains readable while operating at a level of coverage and detail that is atypical of standard summarization or retrieval-based workflows.

Taken together, these properties give the output a character that is immediately distinguishable from query-based or summarization-driven systems, which typically produce shorter, more compressed representations. The output reads more like an academic review of the literature.

Looking more closely at the output, the system produces a structured mapping of the corpus rather than a single narrative argument. The separation of reading (insight extraction and organization) from downstream interpretation is visible in the descriptive character of the text, which represents the literature without advancing a synthesized position.

The themes generated appear interpretable and broadly consistent with recognizable structures in the industrial policy literature, based on internal review. No themes were identified as clearly

distorted or artificial in this process of internal review. The overall output reads more like an academic literature review than a conventional LLM summary or question-answering response, and remains coherent across research questions. The re-theming process appears to consolidate conceptual structure across iterations: the reduction in theme count between passes is consistent with initial semantic groupings being reorganized into more coherent thematic categories.

Granular claims are preserved throughout the output. The system does not collapse content into high-level abstractions; instead, specific and detailed claims remain visible within thematic summaries, contributing to the overall density of the document.

Conflict is explicitly represented. Tensions within the literature are articulated and are not systematically smoothed over during synthesis.

No obvious hallucinations were identified during internal review, though this has not been formally or systematically evaluated.

Notably theme count remains stable across iterations. In previous testing runs, themes initially split to address output constraints and then stabilized. Nonetheless the total number of failing themes declines across runs indicating that the iterative approach is working to address output constraints, while maintaining high levels of granularity and limiting omission.

The distribution of content across themes is uneven. Some themes are significantly more developed than others. This likely reflects variation in the density of the underlying literature, rather than a constraint imposed by the system. In contrast, human-led reviews often impose balance across sections, even where this diverges from the distribution of available evidence.

The pipeline produces an output that is structurally distinct from conventional AI systems, including query-conditioned and summarization-based approaches. Direct comparison with systems such as RAG is therefore not straightforward, as the outputs differ in form and objective; even where comparisons are possible (e.g., coverage or traceability), the central evaluation question is whether separating reading from reasoning in this way leads to better downstream reasoning, sufficient to justify the additional cost, latency, and complexity.

7.6 Failure Modes and Issues

7.6.1 Large proportion of meta-insights

The meta-insight generation step was the most computationally expensive stage of the pipeline, accounting for approximately \$180 of total cost and producing roughly one third of all insights. This is notable, as the meta pass was originally conceived as a supplement to chunk-level extraction, intended to capture only those arguments that emerge across extended portions of a document.

Given the observed volume of meta-insights, it is likely that the meta-insight prompt is overly permissive. Notably, an earlier run produced higher meta-insight:insight proportions (~2:1), reflecting a too loose meta-insight extraction prompt and a too restrictive chunk extraction prompt. Overall this prior run produced more compressed and narratively coherent output, but with less granular representation. The current run relaxed instructions for chunk-level extraction, and tightened those for meta-insight extraction. The result was better coverage at the cost of redundancy and increased computational pressure. This suggests two important reflections: 1) the system presents as parameterizable where different configurations can produce different trade-offs between compression, coverage, and scalability. 2) Prompt specification likely plays a significant role in controlling

insight generation. This allows for system tuning, but might make model swapping more complicated, and raises the possibility that simultaneously tuning meta-insight extraction and chunk insight extraction to complementary points may be non-trivial. For the purposes of this release, extensive tuning of this component was not pursued.

The prevalence of meta-insights also introduces potential challenges for reproducibility. Because meta-insights are derived from near-full document context, they are likely to be less stable across runs than chunk-level insights. Variability at this stage may propagate through clustering and theme generation, reducing structural consistency. This effect may be limited when meta-insights constitute a small proportion of the total, but becomes more significant when they dominate the insight set.

A further contributing factor may be the model’s ability to track previously extracted insights under context window pressure. If prior chunk-level insights are not effectively retained, the model may reproduce or recombine existing claims during the meta pass, leading to redundancy. Under this interpretation, the meta-insight set may include a mixture of previously extracted chunk-level claims, recombinations of such claims, and genuinely cross-cutting arguments.

These factors together suggest that the observed volume of meta-insights reflects both prompt specification and context management limitations. The resulting redundancy appears to be partially resolved during downstream synthesis, but increases computational cost and may affect reproducibility. Refinement of the meta-insight extraction process remains a priority for future work.

7.6.2 High orphan counts

Orphan counts remain high across all passes and in fact show an upward trend. This is partly expected for two reasons. First, the orphan identification prompt is intentionally strict in order to prioritize coverage: false positives are preferred to missed insights. Second, summaries are fully regenerated during the theme population step rather than incrementally updated with previously reinserted orphans. As a result, improvements introduced during orphan handling are not directly preserved in subsequent synthesis steps. If the context window is under pressure during theme population, and insights are dropped at that stage, this behavior is likely to persist even as the theme schema improves.

Taken together, these effects suggest that the model is operating under synthesis pressure. This likely reflects both the size of the input and the heterogeneity of the insight set, which can lead the model to produce increasingly abstract summaries. Under these conditions, individual claims may be incorporated at a conceptual level without remaining directly recoverable in near-verbatim form. In such cases, the orphan detection step may classify insights as unrepresented even when they have been integrated at a higher level of abstraction.

These dynamics indicate that high orphan counts reflect the interaction between conservative omission detection and abstraction during synthesis. In contrast to conventional summarization workflows—where information loss is often silent and difficult to observe—the orphan mechanism makes such loss explicit, allowing it to be detected and addressed rather than assumed away.

This behavior also suggests a broader reinterpretation of the synthesis process implemented by ReadingMachine. The system was initially designed around delayed compression: preserving high-granularity representations until thematic structure was established, with orphan handling acting as a safeguard against omission. However, the observed scale of orphan reinsertion indicates that

the system is not only compressing late, but also performing substantial late-stage reinflation, in which underlying insights are reintroduced after abstraction.

This contrasts with most synthesis pipelines, where compression is assumed to be monotonic and information flow strictly reductive. Under that assumption, sufficiently capable models are expected to retain all salient information during summarization. The behavior observed here suggests a different dynamic: synthesis may instead involve an iterative process in which abstraction is repeatedly challenged by the reintroduction of underlying material. Under explicit coverage constraints, maintaining representational fidelity may require adding information back in, rather than assuming that abstraction alone preserves substance.

One interpretation of this behavior is that language models do not explicitly track which claims have been preserved, abstracted, or omitted during synthesis. They cannot therefore verify coverage through generation alone. The orphan handling mechanism accounts for this by externalizing this process, treating coverage as something that must be tracked and enforced across coordinated steps rather than inferred from fluent output.

7.6.3 Compute and run time

The computational cost and runtime of the system are non-trivial, and their significance depends on the outcome of future evaluation. If ReadingMachine provides only marginal improvements over lower-cost AI approaches (see complementarity below), these costs would represent a substantial limitation.

However, if the system addresses meaningful failure modes in existing approaches and contributes to the research workflow, the more appropriate comparison is human-led review. In that context, the system represents a reduction in time and cost of one to two orders of magnitude. Under this framing, the relative importance of computational inefficiencies—such as the cost of the meta-insight generation step—becomes less significant.

7.6.4 Claim tracing

Insights are currently referenced using an author–date–year format. As a result, recall operates at the level of themes and source documents rather than individual claims. In cases where multiple documents contribute to a theme, tracing an insight may surface several relevant chunks (and meta-level segments), making it more difficult to locate the precise originating text.

This limitation could be addressed in future iterations by linking each `insight_id` directly to its source span, with human-readable author–date references layered on top. The implementation of such functionality is dependent on the output format—for example, HTML hover interactions versus jump links in PDF or Word documents.

For meta-insights in particular, tracing may return large portions of text even when a single `insight_id` is queried. This reduces the precision of traceability and reinforces the need to further refine the meta-insight extraction process.

7.6.5 Dropped citations

As mentioned above the dropping of citations that are known to hold insights is a concern for the method. It raises the questions not only about citation provenance but also, more concerningly, about whether the insights themselves are being lost. Given the orphan insertion loop, it is thought

unlikely that there is significant insight loss and that this is a citation tracking/model bias towards coherence issue, but this requires evaluation. It is quite possible that citation repair is another process of orphan handling.

Addressing the issue of dropped citations therefore raises three future areas of work:

- Under the current implementation add fuzzy string matches or semantic matches to handle deterministic string replacement in the application of patch repair.
- Evaluate insight coverage to check whether the orphan loop is working sufficiently and identify whether dropped citations are simply an issue of coherence bias/tracking
- Test an approach to orphan handling which mimics the schema and citation repair process which removes the coherence requirement from the model when it comes to inserting orphans.

For item 3 above, the proposed change in approach is not obviously better as this task sits on the boundary of synthesizing information (the orphan) and tracking that you have addressed it. Moving this to more of a tracking framework may result in a far less coherent output.

7.7 Interpretation and Next Steps

Based on the observations above, the architecture appears to function as intended. It produces structured, traceable representations of large corpora, preserves granular claims, and maintains internal coherence without obvious hallucination. Fundamentally, the output looks different to both human-produced reviews and other AI approaches, in ways that reflect its architecture.

However, the extent to which this approach improves upon and/or augments existing methods remains an open empirical question. Addressing this question requires systematic evaluation, including expert review, cross-domain testing, and formal comparison with alternative approaches.

The current results should therefore be understood as a demonstration of system behavior at scale, rather than as a definitive assessment of performance.

8 Implications

If the observed system behavior generalizes beyond this initial run, ReadingMachine has implications both for the practice of large-scale synthesis and for how knowledge is produced and evaluated in institutional settings. These potential implications are discussed below.

8.1 Cost and Time Reductions

By shifting the labor of large-scale reading from human analysts to structured machine processes, the system substantially reduces both the cost and time required to synthesize large corpora. Tasks that would typically require months of expert review can be completed in hours at a fraction of the cost. While computational costs are non-trivial, they remain orders of magnitude lower than comparable human-led efforts, particularly as corpus size increases.

8.2 A Shift in the Bottleneck of Knowledge Work

As the cost of reading declines, the primary constraint in knowledge production shifts. For institutions, the bottleneck moves away from information acquisition and toward:

- absorption and internalization of findings
- organizational learning
- updating prior assumptions
- decision-making and strategic pivoting

In this sense, ReadingMachine does not eliminate human labor; it reallocates it from reading to interpretation and action.

8.3 Increased Coverage

Because the system performs a structured pass over the entire corpus, it reduces the risk of partial engagement that characterizes both human review and retrieval-based AI systems. All documents are processed, and insights are extracted systematically. Mechanisms such as orphan detection further reinforce coverage by identifying and reintegrating omitted material.

8.4 Inspectability and Traceability

Each stage of the pipeline produces intermediate artifacts—chunks, insights, clusters, themes—that can be inspected directly. This makes it possible to trace any element of the final synthesis back to its source material. In contrast to both human synthesis (where intermediate reasoning is rarely visible) and many AI systems (where transformations are opaque), ReadingMachine exposes the structure of the analytical process.

8.5 Separation of Reading and Reasoning

A central implication of the ReadingMachine approach is the explicit separation of reading from reasoning. In most forms of human synthesis, these processes are intertwined: analysts read, interpret, evaluate, and draw conclusions simultaneously, often in ways that are difficult to observe or reconstruct. This coupling was historically necessary when reading was slow, as judgment guided which arguments to engage with, how to resolve debates and whether to balance narrative weights. However, this muddies claims of what the literature says with what the author thinks of the literature, and therefore limits the transparency of how conclusions are formed.

ReadingMachine decomposes this process. It constrains language models to perform bounded reading tasks—such as extracting and organizing claims—while deferring interpretation, evaluation, and judgment to the researcher or to downstream analytical steps. The system therefore produces a structured representation of what the corpus contains, rather than an answer to what it means or what should be concluded.

This separation has two implications. First, it increases transparency: the intermediate representations make it possible to examine how the corpus has been read before any higher-level reasoning is applied. Second, it allows reasoning to be applied more deliberately and, if necessary, iteratively, using the structured output as a stable input. In this sense, the system replaces a single, opaque synthesis step with a sequence of inspectable transformations followed by explicit interpretation.

It is important to note that reading itself remains inherently interpretive. Both human readers and language models rely on prior frameworks (conceptual in the case of humans, and learned

semantic patterns in the case of model) to identify and express what counts as an insight. ReadingMachine does not eliminate this interpretive layer. Instead, it makes these transformations visible by externalizing intermediate outputs. While reasoning over the corpus is deferred, interpretive judgments made during reading are exposed and can be examined, compared, and, where necessary, challenged. This creates opportunities for epistemic analysis, discussed further below.

8.6 Reproducibility

Reproducibility in this system is conceptual rather than semantic. Re-running the pipeline with the same configuration is not expected to produce identical text, but it should produce a similar thematic structure: comparable themes, consistent groupings of insights, and stable relationships between them.

This form of reproducibility is achieved through:

- decomposition of the reading process into constrained, repeatable steps
- use of structured intermediate representations (insights, clusters, themes)
- fixed analytical configurations (e.g., prompts, models, clustering parameters)

Under these conditions, variation across runs is expected to remain at the level of phrasing and emphasis rather than underlying structure. At larger scales, this stability is expected to degrade as clustering noise, context inputs, and corpus heterogeneity increase. This serves to reduce reproducibility. These scaling effects are discussed further in the limitations section.

8.7 Architectural Scaling

ReadingMachine is designed to operate on corpora substantially larger than those typically handled by retrieval systems or hierarchical summarization workflows. However, it is not assumed to be infinitely scalable, and its behavior at scale should be understood as an open empirical question.

The key architectural difference is where scale constraints are expected to appear. In many retrieval or agentic workflows, the context bottleneck occurs during the final synthesis step, when the model must integrate all relevant information gathered across the corpus. As the amount of material grows, this can stress the context window and lead to known failure modes such as attention loss or “missing middle” effects, where portions of the input receive less effective processing. This increases omission risk and complicates citation anchoring.

ReadingMachine is designed to shift this limitation by converting documents into a structured intermediate representation before synthesis, distributing integration across smaller, theme-level synthesis tasks rather than concentrating it in a single corpus-level step. Those intermediate representations are as follows:

documents → chunks → insights → clusters → themes → synthesis

Because synthesis occurs at the theme level rather than the corpus level, the model does not need to comprehend the entire corpus. Instead, it integrates the insights associated with one thematic area at a time. The only stage where broader integration occurs is theme schema generation, which is scaffolded by cluster summaries or prior theme structures and repeated iteratively.

In theory, this decomposition should allow the system to scale beyond the point at which corpus-level synthesis becomes unstable in other approaches.

8.8 Parameterization and Experimental Control

Because each stage of the pipeline is explicitly defined, the system can be treated as an experimental framework. Researchers can hold most parameters constant while varying individual components—such as models, prompts, or clustering settings—to observe how these changes affect the resulting thematic structure. This enables systematic sensitivity analysis that is difficult to achieve in both human-led synthesis and less structured AI workflows. Note however, that such experimentation requires system stability, and therefore reproducibility. As mentioned above (and discussed below) it is not clear this will hold as scale increases.

8.9 Implications for Epistemic Analysis

As noted above, beyond synthesis, ReadingMachine creates opportunities for epistemic experimentation in understanding how knowledge is constructed. A full exploration of these epistemic implications is beyond the scope of this paper, but the system provides a structured basis for such analysis. By comparing outputs across models or configurations, researchers can observe how different systems organize, prioritize, or omit information. These differences can be interpreted as expressions of underlying assumptions or priors embedded in models or analytical choices.

In this sense, the system can be used not only to map a corpus, but also to study the process of mapping itself—providing a structured basis for critical analysis of how interpretations are formed. Under this approach, differences across model runs expose model biases, not as errors requiring correction, but as signals that provide insight into how different systems structure and represent knowledge. Rather than converging on a single “correct” interpretation, the method enables comparison across alternative, internally coherent representations of the same material.

Together, these properties suggest a shift from selective, narrative synthesis toward structured, inspectable corpus mapping as a distinct mode of knowledge production.

8.10 The need for external LLM auditing

The quantity of external structure required for ReadingMachine to maintain coverage, granularity, citation provenance, and thematic coherence under scale suggests that unconstrained LLM synthesis does not naturally conserve these properties. Throughout development, multiple forms of representational drift were observed, including dropped insights, disappearing citations, unstable theme structures, and incomplete repairs. Notably, these failures emerged not during complex reasoning tasks, but during comparatively bounded comprehension, synthesis, and rewriting operations.

In this respect, ReadingMachine can be understood in part as an external auditing architecture for iterative LLM synthesis. Mechanisms such as schema development, insight mapping, orphan handling and citation verification act as external conservation controls, ensuring that coverage, provenance, and structural fidelity are not silently lost during repeated generative transformations.

Notably, the auditing requirements observed in ReadingMachine are largely orthogonal to current dominant scaling strategies in LLM development, such as context-window expansion. The behavior observed in the development of ReadingMachine suggests that increasing context windows may increase rather than eliminate the need for externalized auditing. Larger synthesis contexts likely amplify omission pressure, abstraction pressure, citation drift, and instability in maintaining coherent representational structure across repeated transformations. In this respect, visibility over larger amounts of text should not be conflated with stable integration of that text into a faithful synthesis.

While the instability documented here concerns synthesis and comprehension tasks, the same underlying generative dynamics are likely relevant to reasoning processes, which also operate through iterative transformations over bounded texts. To the extent that reasoning depends on preserving assumptions, constraints, provenance, or intermediate conclusions across extended inference trajectories, similar forms of representational drift may emerge. This suggests that long-horizon reasoning systems may also benefit from external auditing architectures in cases where completeness, consistency, traceability, or preservation of epistemic structure are important.

8.11 Fighting upstream compression

A core element of ReadingMachine’s design was to delay compression as long as possible. However even with that in mind, a repeated pattern appeared in building the workflow. The model would compress outputs, to the detriment of coverage, even when explicitly instructed not to. This was apparent in orphan insertion, which was initially conceived of as defensive bootstrapping but which turned out to be necessary reinflation of compressed material. Likewise with schema repair, the model would anchor on conceptually elegant schema, going so far as to hallucinate repairs. And similarly with citations, the model would simply fail to integrate citations due to its apparent anchoring on more elegant prose.

One interpretation is that the model is optimized more strongly for producing coherent synthesized outputs than for conserving all source information through iterative transformations. This suggests that for a system like ReadingMachine, the operational pattern is to put in place auditing architecture like that described above and separate out repair tasks from those seeking to synthesize information. Effectively fight information loss via compression until completeness is achieved, and only then allow some compression.

It is worth noting that the above failures were not a result of context pressure. When we provided the exact same context but with instructions that ignored synthesis - generate a repair plan, or generate patches - results improved enormously. This again points to the idea that the solutions to effective information preserving synthesis might not be larger context windows - which could actually make the problem worse under models with similar training imperatives. They might be auditing and task separation.

More generally, the repeated success of decomposition, patch generation, auditing, and repair suggests that information-preserving workflows may benefit from separating representational fidelity tasks from synthesis tasks, rather than assuming that a single generative operation can optimize both simultaneously.

9 Limitations

ReadingMachine is designed for a specific analytical task: high-fidelity thematic synthesis of large natural-language corpora. It is not intended to replace other approaches to working with language models, nor should it be considered universally superior. In many contexts—particularly exploratory analysis or question answering—other methods remain more appropriate (see below for complementarity with other approaches).

9.1 Cost

Assuming the results above generalize and are validated, ReadingMachine, stands to reduce the cost of human-led synthesis by one to two orders of magnitude. That said, the pipeline is not

costless. The system performs multiple passes over the entire corpus, incurring both computational and time costs. As a result, it is less well suited to rapid exploration or ad hoc query answering.

Most components of the pipeline scale linearly and predictably with corpus size. However, certain stages—particularly those involving iterative synthesis and reinsertion—can introduce non-linear scaling effects, even if these are not the dominant contributors to total cost.

There are clear pathways for reducing cost. The most immediate is parallelization of language model calls, which are currently executed sequentially. The pipeline is well suited to parallelization, as its most expensive stage—insight extraction—operates independently across chunks and documents.

Additional efficiencies may be achieved through model specialization. Smaller models could be used for bounded tasks such as insight extraction, though higher-capability models are currently preferred given the importance of insight quality in downstream stages. Over time, the system may enable a data flywheel: high-quality, structured insight outputs can serve as training data for smaller, task-specific models, reducing reliance on more expensive general-purpose models.

9.2 Functional Scope

The pipeline does not reason over the corpus. It cannot answer questions such as “how many studies did x” or “what is the strongest method for examining y” unless such claims are explicitly present in the source material. Nor does it independently assess the credibility or weight of claims unless this is discussed within the corpus itself. Its output is therefore a structured mapping of what the corpus contains, not an evaluation of what should be concluded.

This places greater importance on question formulation and corpus selection, which are left entirely to the user. These upstream decisions shape the scope and relevance of the resulting synthesis. Because the system faithfully maps the corpus it is given, biases, omissions, or imbalances in corpus selection will be reflected in the output.

While this constraint limits the range of tasks the system can perform, it also underpins several of its advantages. By avoiding open-ended reasoning, the pipeline increases traceability, inspectability, and reproducibility. Rather than embedding interpretation within a single opaque step, it relocates reasoning to distinct stages: upstream (question definition and corpus selection), external (parameter choices), and downstream (interpretation and decision-making).

9.3 Performance Under Scale

The primary scaling constraints in ReadingMachine arise from two interacting factors: the heterogeneity of insights, which affects the stability of intermediate representations, and the volume of insights assigned to individual themes, which affects the system’s ability to integrate them during synthesis. These constraints emerge at different stages of the pipeline and produce distinct but interacting failure modes.

9.3.1 Representation Under Heterogeneity

As corpus heterogeneity increases, the semantic structure of the insight space becomes more difficult to represent consistently. Small variations in embeddings can lead to different clustering outcomes, particularly as the number and diversity of insights grow. Because clusters serve as scaffolding for theme generation, this variability propagates into the theme schema, altering how the corpus is organized conceptually.

These effects reduce system stability across runs. Even with identical configurations, small stochastic differences in model outputs can produce different cluster structures and, in turn, different thematic organizations. More heterogeneous corpora are therefore expected to yield less stable representations and may require additional iterations to converge on a coherent structure.

9.3.2 Synthesis Under Volume

The mechanisms introduced in the pipeline to handle scale significantly extend the size of corpora that can be processed relative to other AI-supported synthesis methods. However, they do not eliminate scaling constraints entirely. At sufficiently large scales, the primary limitation is expected to arise during theme schema generation, when cluster summaries may become too large to fit within the model’s context window.

One possible approach is to provide the schema generation step with only a partial view of the underlying content and rely on the orphan handling and iterative re-theming process to recover omitted material. However, the effectiveness of this approach remains uncertain and requires further empirical evaluation.

9.3.3 Reproducibility under scale

A fundamental limitation of the system is that language model determinism diminishes as context windows increase. As a result, several central stages of the pipeline—particularly those that rely on large context windows, such as meta-insight generation, cluster summarization, and theme population—are inherently less stable. As scale increases, pressure on the context window grows, further reducing determinism and increasing variability across runs. This suggests that the system’s structural stability is likely to decline at larger scales. The current high proportion of meta-insights may exacerbate this effect, reinforcing the importance of refining the meta-insight extraction process.

It is important to note that reduced stability does not necessarily imply reduced accuracy. A given corpus may admit multiple valid thematic organizations, each internally coherent but differing in structure. In this sense, variation across runs may reflect alternative, but plausible, representations rather than outright error. The system is therefore expected to remain useful at scale for producing structured outputs, even if exact reproducibility is limited.

However, this instability has implications for experimental use. While large-scale runs may produce useful and interpretable outputs, comparative analysis across runs—such as evaluating the effects of parameter changes—may become less reliable as scale increases. This suggests two modes of use: large-scale execution for generating structured syntheses, and smaller-scale runs for controlled experimentation and analysis.

9.4 Coverage and Redundancy Trade-offs

A central aim of ReadingMachine is to maximize coverage and minimize omission. While the system is designed to approach this asymptotically—through full-corpus processing and orphan reinsertion—it cannot guarantee complete coverage, particularly at larger scales.

As volume increases, the system prioritizes local completeness within individual themes. Because themes are synthesized independently, this can lead to redundancy across the final output. This redundancy is an intentional trade-off: it preserves marginal or low-salience insights at the cost

of repetition. As scale increases further, both omission risk and redundancy pressure tend to rise simultaneously.

These limitations reflect trade-offs inherent to the system’s design. Prioritizing coverage, traceability, and inspectability shifts constraints toward scale, stability, and computational cost.

10 Complementarity with Other AI Approaches

ReadingMachine differs from both hierarchical summarization and retrieval-based systems. Unlike hierarchical summarization, it delays compression rather than aggregating it through successive summaries. Unlike retrieval-augmented generation (RAG) and its agentic variants, it performs a structured pass over the entire corpus rather than sampling subsets based on queries.

These differences allow ReadingMachine (assuming preliminary results are validated and generalize) to address limitations in existing approaches—particularly silent omission and early information loss. This makes it particularly suitable to work in research, policy analysis, legal/regulatory review, and efforts at institutional memory. That said, the design objectives also result in specific constraints. ReadingMachine is therefore not a replacement for these methods, but a complementary approach designed for a distinct analytical task.

RAG and agentic systems are well suited to exploratory workflows. They are fast, flexible, and effective when questions are evolving, partial coverage is acceptable, and low latency is important. ReadingMachine is better suited to later stages of research, when questions are more stable and the goal is structured synthesis. It is most useful when omission is costly, edge cases must be preserved, and a comprehensive mapping of the corpus is required.

These approaches can be combined within a broader research workflow:

- Agentic research systems support early exploration and corpus identification
- RAG enables flexible, query-driven exploration of the corpus
- ReadingMachine performs a structured reading pass, producing a thematic map of arguments and insights
- Agentic or retrieval workflows can then be used to interrogate the resulting structure, explore edge cases, and support further analysis

A typical workflow might therefore proceed as follows:

1. Agentic search → corpus identification
2. RAG exploration → initial familiarity with the literature
3. ReadingMachine → structural mapping of arguments and themes
4. Agentic or retrieval workflows → deeper analysis and follow-up questions

11 Status of ReadingMachine and Future Work

ReadingMachine is currently an early-stage experimental method and open-source implementation ([GitHub repository](#)). The project is intended as a methodological framework as much as a software tool, and its robustness, limitations, and boundary conditions require empirical evaluation across domains.

The project is actively seeking collaborators to apply the system in different contexts, using varied corpora and configurations. Particular emphasis is placed on identifying failure modes, assessing thematic quality, and evaluating the stability of outputs under different conditions. Contributions that challenge or stress the pipeline are especially valuable.

Active collaboration is also being sought for code hardening and feature development. Priority areas include:

- Parallelization
- Benchmarking
- Tuning
- Citation management and provenance
- OCR implementation
- Model interchangeability
- Documentation improvement
- Strategic and methodological reflection

A potential direction for future work is the introduction of an explicit downstream reasoning stage operating over the structured outputs produced by ReadingMachine. Rather than performing unconstrained reasoning directly over raw corpora, such a stage would apply interpretive analysis to a stable, traceable representation of the material. This could involve agentic workflows that incorporate external tools (e.g., web search or retrieval systems built on the underlying corpus), while requiring explicit justification of claims, articulation of trade-offs, and transparency in how conclusions are formed.

Under this approach, reasoning would be applied in a controlled and inspectable manner, potentially operating over individual themes or structured subsets of the corpus. Different interpretive stances (e.g., distribution-sensitive, precautionary, growth-oriented) could be applied explicitly, allowing alternative readings of the same material to be compared. In this sense, such a layer would not replace the mapping function of ReadingMachine, but build on it—transforming structured representations into interpretable analytical outputs through a distinct and traceable step.

This direction remains exploratory. It is not assumed to yield canonical answers, eliminate bias, or provide definitive conclusions. Rather, it is proposed as a way to reintroduce reasoning into the synthesis process in a manner that is explicit, inspectable, and consistent with the methodological principles of ReadingMachine.

12 Conclusion

The growth in the volume of written information has created a structural imbalance between what is available to be known and what can be systematically read and synthesized. Existing approaches—both human and computational—address this problem only partially, often introducing forms of omission that are difficult to detect.

ReadingMachine proposes a different approach. By decomposing reading into structured, inspectable tasks and coordinating language models to execute them across an entire corpus, the system shifts the bottleneck in knowledge work from information access to interpretation and decision-making. In doing so, it enables more comprehensive, traceable, and reproducible synthesis of large document collections, while explicitly separating the act of reading from downstream reasoning.

The method does not eliminate interpretation, does not replace human judgment, and does not supersede existing AI tools. Instead, it complements these approaches by introducing a structured reading layer that produces inspectable intermediate representations of the corpus—representations that can be treated as explicit epistemic objects, examined prior to interpretation. This reorganization allows reasoning to be applied more deliberately and transparently, rather than being embedded within a single opaque synthesis step.

As both a technical framework and a methodological proposal, ReadingMachine represents a step toward industrial-scale reading that preserves the structure and diversity of the underlying corpus.

References

- [1] Pengfei He, Zhenwei Dai, Bing He, Hui Liu, Xianfeng Tang, Hanqing Lu, Juanhui Li, Jiayuan Ding, Subhabrata Mukherjee, and Suhang Wang. TRAJECT-Bench: A trajectory-aware benchmark for evaluating agentic tool use. *arXiv preprint arXiv:2510.04550*, 2025.
- [2] Philippe Laban, Alexander Richard Fabbri, Caiming Xiong, and Chien-Sheng Wu. Summary of a haystack: A challenge to long-context LLMs and RAG systems. In *Proceedings of EMNLP*, pages 9885–9903, 2024.
- [3] Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2024.
- [4] Shashi Narayan, Shay B. Cohen, and Mirella Lapata. Don’t give me the details, just the summary! Topic-aware convolutional neural networks for extreme summarization. In *Proceedings of EMNLP*, pages 1797–1807, 2018.
- [5] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, and Tim Rocktäschel. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474, 2020.
- [6] Arman Cohan, Franck Dernoncourt, Doo Soon Kim, Trung Bui, Seokhwan Kim, Walter Chang, and Nazli Goharian. A discourse-aware attention model for abstractive summarization of long documents. In *Proceedings of NAACL-HLT, Volume 2: Short Papers*, pages 615–621, 2018.
- [7] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022.
- [8] Hilary Arksey and Lisa O’Malley. Scoping studies: Towards a methodological framework. *International Journal of Social Research Methodology*, 8(1):19–32, 2005.
- [9] Virginia Braun and Victoria Clarke. Using thematic analysis in psychology. *Qualitative Research in Psychology*, 3(2):77–101, 2006.
- [10] Maarten Grootendorst. BERTopic: Neural topic modeling with a class-based TF-IDF procedure. *arXiv preprint arXiv:2203.05794*, 2022.
- [11] Leland McInnes, John Healy, and James Melville. UMAP: Uniform manifold approximation and projection for dimension reduction. *arXiv preprint arXiv:1802.03426*, 2018.

- [12] Leland McInnes, John Healy, and Steve Astels. HDBSCAN: Hierarchical density-based clustering. *Journal of Open Source Software*, 2(11):205, 2017.