

Search...

Getting started
Components

- M4Q
- About
- Population
- Constructor
- Ajax
- Animation
- Loops
- Visibility
- Effects
- Subtree functions
- Attributes
- Html, text and value
- Css and classes
- Position and size
- Manipulation
- DataSet
- Events
- Utils
- Base
- Containers
- Grid system
- Typography
- Tables
- Forms
- Buttons
- Images
- Figures
- Lists
- Form components
- Checkbox
- File input
- Input
- Input material
- Keypad
- Rating
- Radio
- Select
- Slider
- Double Slider
- Spinner
- Switch
- Tag input
- Textarea
- Menus
- App bar
- Bottom navigation
- Bottom sheet
- Menu
- Ribbon Menu
- Side bar
- Side navigation
- Controls
- Accordion
- Badge
- Carousel
- Cards
- Cube
- Counter
- Charms
- Chat
- Donut
- Image compare
- Image magnifier
- Gravatar
- List
- ListView
- Master
- NavView
- Panels
- Progress & Activity
- Streamer
- Stepper
- Splitter
- Tabs
- Tabs material
- Table
- Tiles
- TreeView
- Wizard
- Information
- Dialogs
- Info box
- Hints
- Notify system
- Popovers
- Toasts
- Windows
- Date & time
- Calendar
- Calendar picker
- Date picker
- Time picker
- Countdown
- Formatting date
- Media

M4Q Visibility

You can control element visibility with special visibility functions.

About

You can control element visibility with special visibility functions: `toggle()` , `hide()` , `show()` , `visible()` .

toggle()

To toggle element `display` property, you can use function `toggle()` .

Toggle

```
<button class="button" onclick="$('#div-toggle').toggle()'>Toggle</button>
<div id="div-toggle"></div>
```

hide(), show()

To hide element (set `display` to `none`), you can use function `hide()` . To show element (set `display` to `your initial`), you can use function `show()` .

Hide Show

```
<button class="button" onclick="$('#div-hide').hide()'>Hide</button>
<button class="button" onclick="$('#div-hide').show()'>Show</button>
<div id="div-hide"></div>
```

visible()

To toggle element `visibility` property, you can use function `visible()` .

Hidden Visible

```
<button class="button" onclick="$('#div-visible').visible(false)'>Hidden</button>
<button class="button" onclick="$('#div-visible').visible(true)'>Visible</button>
<div id="div-visible"></div>
```

Callback

With each visibility functions, you can use your own callback function. This function will be executed when the visibility function works done.

Callback

```
<button class="button" onclick="$('#div-toggle').toggle()'>Toggle</button>
<div id="div-toggle"></div>
```

Table of contents

About

- Video player
- Audio player
- Tools
- Collapse
- Color module
- Draggable
- Dropdown
- Form validator
- Hotkeys
- Micro templates
- Ripple
- Storage
- Session storage
- Sorter
- Touch and swipe

Utilities
Animations
Additional