

Search...

- Getting started
- Introduction

Download

Contents

Browsers & devices

Media breakpoints

Define Events

DOM manipulation

i18n

Including

Configuring

Init components

Components API

Global setup

ReactJS

Angular

VueJS
- Components
- Utilities
- Animations
- Additional

i18n

Metro 4 ready for internationalization and localisation.

About

Some components in Metro 4 use text labels, example `calendar` component. Metro 4 supports i18n mechanism to display text labels.

By default components use value of `METRO_LOCALE` variable. This ia a global variable and can be modified before `Metro 4 js` loaded. You can set `locale` for component with special attribute `data-locale` .

```
<script>
    window.METRO_LOCALE = "de-DE";
</script>
<script src="metro.js"></script>
```

Meta tag

You can set global locale with `<meta>` tag. To set it use meta tag with name `metro4:locale` .

```
<meta name="metro4:locale" content="uk-UA">
```

Locales

You can get hard stored locales with method `Metro.utils.getLocales()` .

```
var locales = Metro.utils.getLocales();
console.log(locales);
```

Add locale

You can add own locale at runtime. To add locale you must use method `Metro.utils.addLocale()` .

```
<script>
    Metro.utils.addLocale({
        'de-DE': {
            "calendar": {
                "months": [
                    "Januar", "Februar", "März", "April", "Mai", "Juni", "Juli", "August", "September", "Oktober", "November",
                    "Jan", "Feb", "Mär", "Apr", "Mai", "Jun", "Jul", "Aug", "Sep", "Okt", "Nov", "Dez"
                ],
                "days": [
                    "Sonntag", "Montag", "Dienstag", "Mittwoch", "Donnerstag", "Freitag", "Samstag",
                    "Sn", "Mn", "Di", "Mi", "Do", "Fr", "Sa",
                    "Son", "Mon", "Die", "Mit", "Don", "Fre", "Sam"
                ],
                "time": {
                    "days": "TAGE",
                    "hours": "UHR",
                    "minutes": "MIN",
                    "seconds": "SEK"
                }
            },
            "buttons": {
                "ok": "OK",
                "cancel": "Abbrechen",
                "done": "Fertig",
                "today": "Heute",
                "now": "Jetzt",
                "clear": "Reinigen",
                "help": "Hilfe",
                "yes": "Ja",
                "no": "Nein",
                "random": "Zufällig"
            }
        }
    });
</script>
```

if you put your javascript in `<head>` , you must use method after `Metro 4 js` loaded. If you put javascript in bottom of page, you must set `<meta>` tag `metro4:init` to false and manually initialise Metro 4, after locale is added.

For head

```
<head>
    <script src="metro.js"></script>
</script>
```

Table of contents

- i18n

About

Meta tag

Locales

Add Locale

```
        Metro.utils.addLocale(...);
    </script>
</head>
```

For bottom of page

```
<head>
  <meta name="metro4:init" content="false">
</head>
<body>
  ...
  <script src="metro.js"></script>
  <script>
    Metro.utils.addLocale(...);
    Metro.init();
  </script>
</body>
```

