Search...

Panel

Group the information and focus the user's attention on it using the panel.

Create panel

To create panel, add attribute `data-role="panel"` to element.

> Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.

```html
<div data-role="panel">
    ...
</div>
```

Create panel with your own size

To create panel with your own size, use attributes `data-width="..."` and `data-height="..."`.

> Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies. Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.

```html
<div data-role="panel" data-width="280" data-height="150">
    ...
</div>
```

Panel title

For more information, you can add a `title` to the panel. To add `title` you must add or **title caption** or **title icon**. To add `caption` use attribute `data-title-caption="..."`, to add `icon` use attribute `data-title-icon="..."`.

Panel title	⊞
Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.	

```html
<div data-role="panel"
     data-title-caption="Panel title"
     data-title-icon="<span class='mif-apps'></span>">
     ...
</div>
```

> For `title icon` you must use a valid `html tag`. It can be icon from font or image.

Collapsible panel

If you need to create **collapsing panel**, add attribute `data-collapsible="true"` to element. To start panel in `collapsed` state, add attribute `data-collapsed="true"`.

Panel title	^
Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.	

Panel title	⌄

```html
<div data-role="panel"
     data-title-caption="Panel title"
     data-collapsible="true">
     ...
</div>

<div data-role="panel"
     data-title-caption="Panel title"
     data-collapsed="true"
     data-collapsible="true">
     ...
</div>
```

Custom buttons

You can add a custom buttons to panel title. To add custom buttons use attribute `data-custom-buttons`. Value for this attribute must be a predefined object.

Panel title

Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.

```
<script>
    var customButtons = [
        {
            html: "<span class='mif-rocket'></span>",
            cls: "sys-button",
            onclick: "alert('You press rocket button')"
        },
        {
            html: "<span class='mif-user'></span>",
            cls: "alert",
            onclick: "alert('You press user button')"
        },
        {
            html: "<span class='mif-cog'></span>",
            cls: "warning",
            onclick: "alert('You press cog button')"
        }
    ];
</script>

<div data-role="panel"
    data-title-caption="Panel title"
    data-collapsible="true"
    data-custom-buttons="customButtons">...</div>
```

Draggable

You can create `draggable` panel with attribute `data-draggable="true"` .

Panel title

Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.

```
<div data-role="panel"
    data-title-caption="Panel title"
    data-title-icon="<span class='mif-apps'></span>"
    data-width="240"
    data-collapsible="true"
    data-draggable="true">
    ...
</div>
```

Events

When panel works, it generated the numbers of events. You can use callback for this events to behavior with panel.

Event	Data-*	Desc
onCollapse(el)	data-on-collapse	Fired when panel was collapsed
onExpand(el)	data-on-expand	Fired when panel was expanded
onDragStart(pos, el)	data-on-drag-start	Fired when panel drag started
onDragStop(pos, el)	data-on-drag-stop	Fired when panel drag stopped
onDragMove(pos, el)	data-on-drag-move	Fired when panel drag moved
onPanelCreate(el)	data-on-panel-create	Fired when panel was created

X: 0
Y: 0

Panel title

Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.

```
<div class="row h-100">
    <div class="stub bg-light" style="width: 100px">
        <div>X: <span id="panel_ev_x">0</span></div>
        <div>Y: <span id="panel_ev_y">0</span></div>
    </div>
    <div class="cell">
        <div data-role="panel"
            data-title-caption="Panel title"
            data-title-icon="<span class='mif-apps'></span>"
            data-width="240"
            data-collapsible="true"
            data-draggable="true"
            data-on-drag-move="
                var pos = arguments[0];
```

```
            $('#panel_ev_x').text(pos.x);
            $('#panel_ev_y').text(pos.y);
        "
    >
        Raptus capios ducunt ad genetrix...
    </div>
</div>
</div>
```

Methods

You can use panel methods to interact with the component.

- **collapse()** - collapse panel
- **expand()** - expand panel
- **customButtons()** - add custom buttons

Customize

If you need to customize the slider, you can use next options:

Option	Data-*	Desc
clsPanel	`data-cls-panel`	Additional class for panel
clsTitle	`data-cls-title`	Additional class for panel title
clsTitleCaption	`data-cls-title-caption`	Additional class for panel title caption
clsTitleIcon	`data-cls-title-icon`	Additional class for panel title icon
clsContent	`data-cls-content`	Additional class for panel content
clsCollapseToggle	`data-cls-collapse-toggle`	Additional class for panel collapse toggle

Panel title ⊞ ^

Raptus capios ducunt ad genetrix. Joy doesn't beautifully respect any believer — but the power is what flies.

```
<div class="mx-auto"
     data-role="panel"
     data-width="280"
     data-title-caption="Panel title"
     data-title-icon="<span class='mif-apps'></span>"
     data-collapsible="true"
     data-cls-panel="shadow-3"
     data-cls-title="bg-red fg-white"
     data-cls-title-icon="bg-green fg-white"
     data-cls-content="bg-cyan fg-white"
     data-cls-collapse-toggle="bg-dark fg-white marker-light"
>
    Raptus capios ducunt ad genetrix.
    Joy doesn't beautifully respect any believer —
    but the power is what flies.
</div>
```