

Search...

Getting started

Components

- M4Q
- About
- Population
- Constructor
- Ajax
- Animation
- Loops
- Visibility
- Effects
- Subtree functions
- Attributes
- Html, text and value
- Css and classes
- Position and size
- Manipulation
- DataSet
- Events
- Utils

- Base
- Containers
- Grid system
- Typography
- Tables
- Forms
- Buttons
- Images
- Figures
- Lists

- Form components
- Checkbox
- File input
- Input
- Input material
- Keypad
- Rating
- Radio
- Select
- Slider
- Double Slider
- Spinner
- Switch
- Tag input
- Textarea

- Menus
- App bar
- Bottom navigation
- Bottom sheet
- Menu
- Ribbon Menu
- Side bar
- Side navigation

- Controls
- Accordion
- Badge
- Carousel
- Cards
- Cube
- Counter
- Charms
- Chat
- Donut
- Image compare
- Image magnifier
- Gravatar
- List
- ListView
- Master
- NavigationView
- Panels
- Progress & Activity
- Streamer
- Stepper
- Splitter
- Tabs
- Tabs material
- Table
- Tiles
- TreeView
- Wizard

- Information
- Dialogs
- Info box
- Hints
- Notify system
- Popovers
- Toasts
- Windows

- Date & time
- Calendar
- Calendar picker
- Date picker
- Time picker
- Countdown
- Formatting date

- Media

Popovers

Use popovers to create element tooltips.

Abouts

Sometimes it is necessary to provide the user with some additional information about the element. For this you can use `popovers` . To create element popover, add role `popover` to element with attribute `data-role` . To set popover text, use attribute `data-popover-text`="..." .

Hover Me

```
<button class="button"
  data-role="popover"
  data-popover-text="This is popover!">
  Hover Me
</button>
```

Triggers

To show popovers you can use any triggers: `hover` (default), `click` and `focus` .

Ubi est festus coordinatae? Zion is not
HOVER ME the simple truth of the wind.

Click Me

Put cursor here

```
<span class="text-bold" data-role="popover"
  data-popover-text="This is popover!">HOVER ME</span>

<button class="button" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-trigger="click">Click Me</button>

<input type="text" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-trigger="focus" placeholder="Put cursor here">
```

Popover text

To set popover text use attributes `data-popover-text` . Value fo this attribute can be simple text or valid html text. You can change this attribute at runtime.

Hover Me

```
<button class="button"
  data-role="popover"
  data-popover-hide="0"
  data-popover-text="
    <iframe width='560'
      height='315'
      src='https://www.youtube.com/embed/MkNeIUgNPQ8?autoplay=1'
      frameborder='0' allowfullscreen>
    </iframe>
  ">
  Hover Me
</button>
```

Popover position

You can use four positions for popovers: `top` , `bottom` , `left` and `right` . To set position use attribute `data-popover-position` .

Right

Top

Bottom

Left

```
<button class="button" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-position="top">Top</button>

<button class="button" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-position="right">Right</button>

<button class="button" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-position="left">Left</button>

<button class="button" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-position="bottom">Bottom</button>
```

Hiding

Attribute `data-popover-hide` is responsible for closing popovers. If a value for this attribute more then zero, popovers auto-hiding after milliseconds defined in this attribute. If this value is zero, popover can be closed when user click on popover.

Hover me

Hover me

Hover me

```
<button class="button m-1" data-role="popover"
```

Table of contents

- Popovers
- About
- Triggers
- Popover text
- Position
- Hiding
- Styling
- Events
- Methods

```
data-popover-text="This popover closed after 5 secs!"
data-popover-position="top" data-popover-hide="5000">
  Hover me
</button>

<button class="button m-1" data-role="popover"
  data-popover-text="Click Me to close!"
  data-popover-position="top"
  data-popover-hide="0"
  data-close-button="false"
>
  Hover me
</button>

<button class="button m-1" data-role="popover"
  data-popover-text="Click close button to close!"
  data-popover-position="top" data-popover-hide="0">
  Hover me
</button>
```

Also, you can use attribute `data-hide-on-leave` to set `event leave` from an element (mouse leave or touch end). When you set value for this attribute to `true` (default) then popover hiding when mouse leave or touch end. If you set value for this attribute to `false`, popover no hiding when mouse leave or touch end.

Styling

You can set your own style for popovers with attribute `data-cls-popover`. Value for this attribute must be valid css classes.

Hover me

```
<button class="button m-1" data-role="popover"
  data-popover-text="
    <div class='text-center'>
      <img src='images/Logo.png' style='height: 64px;'>
    </div>
    This popover styled with custom classes!
  "
  data-cls-popover="bg-dark fg-orange drop-shadow"
  data-popover-hide="5000">
  Hover me
</button>
```

Events

When popovers works, it generated the numbers of events. You can use callback for this event to behavior with popovers or others.

Event	Data-*	Desc
onPopoverShow(popover, element)	<code>data-on-popover-show</code>	Fired when popover showed
onPopoverHide(popover, element)	<code>data-on-popover-hide</code>	Fired when popover hidid

Methods

You can interact with popovers with popovers methods. Use `show()` and `hide()` methods to show/hide popovers.

Show popover Hide popover

```
<button class="button"
  onclick="$('#input_popover').data('popover').show() ">
  Show popover
</button>

<button class="button"
  onclick="$('#input_popover').data('popover').hide() ">
  Hide popover
</button>

<input type="text" data-role="popover"
  data-popover-text="This is popover!"
  data-popover-trigger="focus"
  data-popover-hide="0" id="input_popover">
```