

Search...

Getting started
Components

- M4Q
- About
- Population
- Constructor
- Ajax
- Animation
- Loops
- Visibility
- Effects
- Subtree functions
- Attributes
- Html, text and value
- Css and classes
- Position and size
- Manipulation
- DataSet
- Events
- Utils
- Base
- Containers
- Grid system
- Typography
- Tables
- Forms
- Buttons
- Images
- Figures
- Lists
- Form components
- Checkbox
- File input
- Input
- Input material
- Keypad
- Rating
- Radio
- Select
- Slider
- Double Slider
- Spinner
- Switch
- Tag input
- Textarea

- Menus
- App bar
- Bottom navigation
- Bottom sheet
- Menu
- Ribbon Menu
- Side bar
- Side navigation

- Controls
- Accordion
- Badge
- Carousel
- Cards
- Cube
- Counter
- Charms
- Chat
- Donut
- Image compare
- Image magnifier
- Gravatar
- List
- ListView
- Master
- NavView
- Panels
- Progress & Activity
- Streamer
- Stepper
- Splitter
- Tabs
- Tabs material
- Table
- Tiles
- TreeView
- Wizard

- Information
- Dialogs
- Info box
- Hints
- Notify system
- Popovers
- Toasts
- Windows

- Date & time
- Calendar
- Calendar picker
- Date picker
- Time picker
- Countdown
- Formatting date

Tag input

Enhancement for standard HTML input[type=text] to tag input - managing tags.

About

To create `tag input` , add attribute `data-role="taginput"` to HTML input element. You must assign role `input` to text input `input type="text"` . Enter tag name and press `Enter` or `,` ,

```
<input type="text" data-role="taginput">
```

Init values

You can preset values for `tag-input` . To preset values use attribute `value` . Values can be separated with symbol, defined with attribute `data-tag-separator` .

css3 × javascript × html5 × Metro 4 ×

```
<input type="text" data-role="taginput" value="css3,javascript,html5,Metro 4">
```

Tag trigger

To set trigger for creating tags, use attribute `data-tag-trigger` . By default this attribute have a next value `13, 188` `Enter` `,` . You can set your own trigger with this attribute.

Use `Space` to add tags

```
<input type="text" data-role="taginput" data-tag-trigger="32">
```

Max tags

You can set a maximum count of tag, who can be created. To set maximum, use attribute `data-max-tags` .

You can add 5 tags

```
<input type="text" data-role="taginput" data-max-tags="5">
```

Random colors for tags

With attribute `data-random-color="true"` , you can set special mode for component when tag have random colors.

Tags have a random color

```
<input type="text" data-role="taginput" data-random-color="true">
```

Options

Option	Data-*	Default	Desc
<code>randomColor</code>	<code>data-random-color</code>	false	User random color for tags
<code>maxTags</code>	<code>data-max-tags</code>	0	If value more then 0, user can't create tags more then this value
<code>tagSeparator</code>	<code>data-tag-separator</code>	,	Default - comma, tags separator for result value
<code>tagTrigger</code>	<code>data-tag-trigger</code>	13, 188	Key codes for triggering tags creating. Default - <code>Enter</code> <code>,</code>

Events

Event	Data-*	Context	Desc
<code>onBeforeTagAdd(val, values)</code>	<code>data-on-before-tag-add</code>	input	If this function return false, tag can't be added
<code>onTagAdd(tag, val, values)</code>	<code>data-on-tag-add</code>	input	
<code>onBeforeTagRemove(tag, val, values)</code>	<code>data-on-before-tag-remove</code>	input	If this function return false, tag can't be removed
<code>onTagRemove(tag, val, values)</code>	<code>data-on-tag-remove</code>	input	
<code>onTag(tag, val, values)</code>	<code>data-on-tag</code>	input	

Table of contents

- Tag input
- About
- Init value
- Tag trigger
- Max tags
- Ransom colors
- Options
- Events
- Methods
- Customize
- Additional classes

- Media
 - Video player
 - Audio player
- Tools
 - Collapse
 - Color module
 - Draggable
 - Dropdown
 - Form validator
 - Hotkeys
 - Micro templates
 - Ripple
 - Storage
 - Session storage
 - Sorter
 - Touch and swipe

Utilities
Animations
Additional

Event	Data-*	Context	Desc
onTagInputCreate (input)	data-on-tag-input-create	input	

Methods

You can use methods to interact with input component: `tags()` , `clear()` , `val()` , `val(values_array)` .

```
var input = $(el).data('taginput');
input.clear();
```

Customize

You can customize your input with special attributes:

Option	Data-*	Desc
clsTag	data-cls-tag	Additional classes for tag.
clsTagTitle	data-cls-tag-title	Additional classes for tag title.
clsTagRemover	data-cls-tag-remover	Additional classes for tag remove button.

css × javascript × html × Metro 4 ×

```
<input type="text"
  data-role="taginput"
  data-cls-tag-title="text-bold fg-white"
  data-cls-tag="bg-olive"
  data-cls-tag-remover="bg-darkOlive fg-white"
  value="css, javascript, html, Metro 4">
```

Additional classes

You can use additional classes to change input size: `.input-large` and `.input-small` .

Input small

css × javascript × html × Metro 4 ×

Input regular

css × javascript × html × Metro 4 ×

Input large

css × javascript × html × Metro 4 ×