08-SRS流媒体服务器-HTTP-FLV推拉流

```
1 根据配置文件进行初始化http_remux 配置vhost配置2 RTMP推流时3 HTTP-FLV/TS/AAC/MP3拉流
```

1 根据配置文件进行初始化

```
#0 SrsHttpStreamServer::initialize_flv_entry (this=0xa11fd0, vhost="__defaultVhost__")
    at src/app/srs_app_http_stream.cpp:1163
#1 0x0000000005028d3 in SrsHttpStreamServer::initialize_flv_streaming (this=0xa11fd0)
    at src/app/srs_app_http_stream.cpp:1154
#2 0x000000000500a2a in SrsHttpStreamServer::initialize (this=0xa11fd0) at
src/app/srs_app_http_stream.cpp:873
#3 0x000000000561eb7 in SrsHttpServer::initialize (this=0xa11e00) at
src/app/srs_app_http_conn.cpp:279
#4 0x0000000004c84c0 in SrsServer::initialize (this=0xa11ea0, ch=0x0) at
src/app/srs_app_server.cpp:757
#5 0x0000000005bcb57 in run (svr=0xa11ea0) at src/main/srs_main_server.cpp:395
#6 0x0000000005bb769 in do_main (argc=3, argv=0x7fffffffe4f8) at
src/main/srs_main_server.cpp:184
#7 0x00000000005bb8ad in main (argc=3, argv=0x7fffffffe4f8) at
src/main/srs_main_server.cpp:192
```

http_remux 配置

```
1 SrsLiveEntry::SrsLiveEntry(std::string m)
2 {
3     mount = m;
```

```
5
       stream = NULL:
       cache = NULL;
 6
 7
 8
       reg = NULL;
 9
       source = NULL:
10
       std::string ext = srs_path_filext(m); // 根据mount的值, 比如[vhos
11
   t]/[app]/[stream].flv
12
       is flv = (ext == ".flv");
       _is_ts = (ext == ".ts");
13
       _{is_{mp3}} = (ext == ".mp3");
14
       is aac = (ext == ".aac");
15
16 }
```

http不光支持FLV的拉流

```
# http-flv darren
http_remux {
    enabled on;
    mount [vhost]/[app]/[stream].flv; # 支持.flv .ts .aac .mp3的使用
    hstrs on;
}
```

vhost配置

比较复杂, 具体提供多个客户使用时再考虑

https://github.com/ossrs/srs/wiki/v3_CN_RtmpUrlVhost

2 RTMP推流时

推流的时候根据url创建对应的handler,拉流的时候根据url找到对应处理的handler

```
#0 SrsLiveEntry::SrsLiveEntry
```

#1 0x000000000500ffa in SrsHttpStreamServer::http_mount (this=0xa11dc0, s=0xa3bf80, r=0xa3ae90)

at src/app/srs_app_http_stream.cpp:907

```
#2 0x0000000005620f5 in SrsHttpServer::http mount (this=0xa118f0, s=0xa3bf80,
r=0xa3ae90)
  at src/app/srs_app_http_conn.cpp:308
#3 0x0000000004cd3cc in SrsServer::on_publish (this=0xa103a0, s=0xa3bf80, r=0xa3ae90)
  at src/app/srs_app_server.cpp:1608
#4 0x0000000004e6a9b in SrsSource::on publish (this=0xa3bf80) at
src/app/srs_app_source.cpp:2466
#5 0x0000000004d89f2 in SrsRtmpConn::acquire publish (this=0xa30ce0, source=0xa3bf80)
  at src/app/srs app rtmp conn.cpp:940
#6 0x0000000004d7a74 in SrsRtmpConn::publishing (this=0xa30ce0, source=0xa3bf80) at
src/app/srs_app_rtmp_conn.cpp:822
#7 0x000000004d5229 in SrsRtmpConn::stream service cycle (this=0xa30ce0) at
src/app/srs_app_rtmp_conn.cpp:534
#8 0x0000000004d4141 in SrsRtmpConn::service_cycle (this=0xa30ce0) at
src/app/srs_app_rtmp_conn.cpp:388
#9 0x0000000004d2f09 in SrsRtmpConn::do cycle (this=0xa30ce0) at
src/app/srs_app_rtmp_conn.cpp:209
#10 0x0000000004d10fb in SrsConnection::cycle (this=0xa30d58) at
src/app/srs app conn.cpp:171
---Type <return> to continue, or q <return> to quit---
#11 0x000000000509c88 in SrsSTCoroutine::cycle (this=0xa30f70) at
src/app/srs_app_st.cpp:198
#12 0x000000000509cfd in SrsSTCoroutine::pfn (arg=0xa30f70) at
src/app/srs_app_st.cpp:213
#13 0x0000000005bdd9d in _st_thread_main () at sched.c:337
#14 0x0000000005be515 in st_thread_create (start=0x5bd719 <_st_vp_schedule+170>,
arg=0x700000001, joinable=1,
  stk size=1) at sched.c:616
一个source,对应一个
#0 SrsLiveStream::SrsLiveStream (this=0xa3da40, s=0xa3bbd0, r=0xa3ad40, c=0xa3d520)
  at src/app/srs_app_http_stream.cpp:514
#1 0x000000005010bb in SrsHttpStreamServer::http_mount (this=0xa11fd0, s=0xa3bbd0,
r=0xa3ad40
  at src/app/srs_app_http_stream.cpp:912
#2 0x0000000005620f5 in SrsHttpServer::http_mount (this=0xa11e00, s=0xa3bbd0,
r=0xa3ad40
  at src/app/srs_app_http_conn.cpp:308
#3 0x0000000004cd3cc in SrsServer::on_publish (this=0xa11ea0, s=0xa3bbd0, r=0xa3ad40)
  at src/app/srs_app_server.cpp:1608
```

```
#4 0x0000000004e6a9b in SrsSource::on publish (this=0xa3bbd0) at
src/app/srs_app_source.cpp:2466
#5 0x0000000004d89f2 in SrsRtmpConn::acquire_publish (this=0xa30d00,
source=0xa3bbd0)
  at src/app/srs app rtmp conn.cpp:940
#6 0x000000004d7a74 in SrsRtmpConn::publishing (this=0xa30d00, source=0xa3bbd0) at
src/app/srs_app_rtmp_conn.cpp:822
#7 0x0000000004d5229 in SrsRtmpConn::stream service cycle (this=0xa30d00) at
src/app/srs app rtmp conn.cpp:534
#8 0x0000000004d4141 in SrsRtmpConn::service_cycle (this=0xa30d00) at
src/app/srs_app_rtmp_conn.cpp:388
#9 0x0000000004d2f09 in SrsRtmpConn::do cycle (this=0xa30d00) at
src/app/srs_app_rtmp_conn.cpp:209
#10 0x0000000004d10fb in SrsConnection::cycle (this=0xa30d78) at
src/app/srs_app_conn.cpp:171
#11 0x0000000000509c88 in SrsSTCoroutine::cycle (this=0xa30f90) at
src/app/srs_app_st.cpp:198
#12 0x000000000509cfd in SrsSTCoroutine::pfn (arg=0xa30f90) at
src/app/srs app st.cpp:213
#13 0x0000000005bdd9d in st thread main () at sched.c:337
#14 0x0000000005be515 in st_thread_create (start=0x5bd719 <_st_vp_schedule+170>,
arg=0x70000001, joinable=1,
  stk size=1) at sched.c:616
```

3 HTTP-FLV/TS/AAC/MP3拉流

每个播放的SrsFlvStreamEncoder是独立的

断点: SrsHttpCorsMux::initialize

SrsHttpCorsMux::SrsHttpCorsMux

SrsHttpCorsMux::serve_http

断点: SrsLiveStream::do_serve_http

断点: SrsHttpServeMux::hijack

SrsHttpServeMux::SrsHttpServeMux

SrsHttpServeMux::initialize

#0 **SrsHttpServeMux::hijack** (this=0xa11dd0, h=0xa11eb0) at src/protocol/srs_http_stack.cpp:618

```
#1 0x000000000500294 in SrsHttpStreamServer::SrsHttpStreamServer (this=0xa11dc0,
svr=0xa103a0,
  __in_chrg=<optimized out>, __vtt_parm=<optimized out>) at
src/app/srs_app_http_stream.cpp:841
#2 0x00000000561c45 in SrsHttpServer::SrsHttpServer (this=0xa118f0, svr=0xa103a0)
  at src/app/srs_app_http_conn.cpp:260
#3 0x000000004c7675 in SrsServer::SrsServer (this=0xa103a0, __in_chrg=<optimized out>,
  __vtt_parm=<optimized out>) at src/app/srs_app_server.cpp:635
#4 0x0000000005bb735 in do_main (argc=3, argv=0x7fffffffe4f8) at
src/main/srs_main_server.cpp:181
#5 0x0000000005bb8ad in main (argc=3, argv=0x7fffffffe4f8) at
src/main/srs main server.cpp:192
#0 SrsFlvStreamEncoder::SrsFlvStreamEncoder (this=0xa57820) at
src/app/srs_app_http_stream.cpp:250
#1 0x0000000004fe2fd in SrsLiveStream::do_serve_http (this=0xa3da20, w=0x7ffff7eb5bd0,
r=0xa5d7c0
  at src/app/srs app http stream.cpp:562
#2 0x000000004fe108 in SrsLiveStream::serve_http (this=0xa3da20, w=0x7ffff7eb5bd0,
r=0xa5d7c0
  at src/app/srs_app_http_stream.cpp:544
#3 0x00000000049c86f in SrsHttpServeMux::serve http (this=0xa11fe0, w=0x7ffff7eb5bd0,
r=0xa5d7c0
  at src/protocol/srs_http_stack.cpp:711
#4 0x00000000562080 in SrsHttpServer::serve_http (this=0xa11e00, w=0x7ffff7eb5bd0,
r=0xa5d7c0
  at src/app/srs_app_http_conn.cpp:300
#5 0x0000000049d6be in SrsHttpCorsMux::serve_http (this=0xa52930, w=0x7ffff7eb5bd0,
r=0xa5d7c0
  at src/protocol/srs http stack.cpp:859
#6 0x000000000561086 in SrsHttpConn::process_request (this=0xa5d120,
w=0x7ffff7eb5bd0, r=0xa5d7c0)
  at src/app/srs_app_http_conn.cpp:161
#7 0x000000000560ce8 in SrsHttpConn::do cycle (this=0xa5d120) at
src/app/srs_app_http_conn.cpp:133
#8 0x0000000004d10fb in SrsConnection::cycle (this=0xa5d120) at
src/app/srs_app_conn.cpp:171
#9 0x000000000509c88 in SrsSTCoroutine::cycle (this=0xa5d1c0) at
src/app/srs_app_st.cpp:198
```

```
#11 0x0000000005bdd9d in _st_thread_main () at sched.c:337
#0 SrsHttpFileServer::serve_http (this=0xa122b0, w=0x7ffff7f42bd0, r=0xa71210)
  at src/protocol/srs_http_stack.cpp:360
#1 0x00000000049c86f in SrsHttpServeMux::serve_http (this=0xa11ed0, w=0x7ffff7f42bd0,
r=0xa71210
  at src/protocol/srs_http_stack.cpp:711
#2 0x000000005620a1 in SrsHttpServer::serve_http (this=0xa118f0, w=0x7ffff7f42bd0,
r=0xa71210
  at src/app/srs_app_http_conn.cpp:303 这里是http_static->mux.serve_http(w, r); 不属于直播
的
#3 0x00000000049d6be in SrsHttpCorsMux::serve_http (this=0xa840f0, w=0x7ffff7f42bd0,
r=0xa71210
  at src/protocol/srs_http_stack.cpp:859
#4 0x000000000561086 in SrsHttpConn::process_request (this=0xa70cc0, w=0x7ffff7f42bd0,
r=0xa71210)
  at src/app/srs_app_http_conn.cpp:161
#5 0x00000000560ce8 in SrsHttpConn::do_cycle (this=0xa70cc0) at
src/app/srs_app_http_conn.cpp:133
#6 0x0000000004d10fb in SrsConnection::cycle (this=0xa70cc0) at
src/app/srs_app_conn.cpp:171
#7 0x000000000509c88 in SrsSTCoroutine::cycle (this=0xa70f00) at
src/app/srs_app_st.cpp:198
#8 0x000000000509cfd in SrsSTCoroutine::pfn (arg=0xa70f00) at
src/app/srs_app_st.cpp:213
#9 0x0000000005bdd9d in _st_thread_main () at sched.c:337
```

Breakpoint 16, SrsHttpFileServer::SrsHttpFileServer (this=0xa122b0,

#10 0x0000000000509cfd in SrsSTCoroutine::pfn (arg=0xa5d1c0) at

src/app/srs_app_st.cpp:213

"\320\375\240\000\000\000\000p\026\241\000\000\000\000\000\300\337\377\377\ 377\177", '\000' < repeats 11 times >, "\341\377\377\177\000\000\300\035\241\000\000\000\000\000\000!\241\000\000 241\000\000\000\000\000\000\005\241\000\000\000\000"...) at src/protocol/srs_http_stack.cpp:336 336 SrsHttpFileServer::SrsHttpFileServer(string root_dir) (gdb) bt #0 SrsHttpFileServer::SrsHttpFileServer (this=0xa122b0, 00\000\000\000\000\000\000\204\301\376\366\377\177\000\000\360\034\241\000\000\0 00\000\"\364\322\352!\350\264`\340\377\377\177\000\000\260\"\241\000\000\ 000\000\000`\340\377\377\177\000\000\312\347W\000\000\000\000\000p\026\241\0 00\000\000\000\000\300\036\241\000\000\000\000\000\260\337\377\000\b", '\000' <repeats 11 times>, "\320\375\240\000\000\000\000p\026\241\000\000\000\000\000\300\337\377\377\ $377\177$ ", '\000' < repeats 11 times >, "\341\377\377\377\177\000\000\300\035\241\000\000\000\000\000\000!\241\000\000\00 241\000\000\000\000\000\060\005\241\000\000\000\000"...) at src/protocol/srs_http_stack.cpp:336 #1 0x00000000057d19e in SrsVodStream::SrsVodStream (this=0xa122b0, $'\000'$ <repeats 24 times>, "\"\364\322\352!\350\264\064\003n\000\000\000\000\000\f\241\000\000\000\ 000`\340\377\377\177\000\000\000\"\364\322\352!\350\264\000\000\000\000\ 000\000\000\f\241\000\000\000\000\360\034\241\000\000\000\300\3 41\377\377\377\177\000\000\320\340\377\377\177\000\000\024\037V\000\000\ 000\000\220\340\377\377\177\000\000\360\030\241\000\000\000\000\000\320\340 \000\000\000\000h \241\000\000\000\000"...) at src/app/srs_app_http_static.cpp:54 #2 0x00000000057e7ca in SrsHttpStaticServer::initialize (this=0xa11ec0) at src/app/srs_app_http_static.cpp:235 #3 0x00000000561f14 in SrsHttpServer::initialize (this=0xa118f0) at

src/app/srs_app_http_conn.cpp:283

src/app/srs_app_server.cpp:757

#4 0x0000000004c84c0 in SrsServer::initialize (this=0xa103a0, ch=0x0) at

7

断点: SrsLiveStream::do_serve_http SrsHttpResponseWriter::send_header

```
Breakpoint 2, SrsHttpResponseWriter::write (this=0x7ffff7eb5bd0, data=0x7ffff7eb5470
"FLV\001\005", size=9)
  at src/service/srs_service_http_conn.cpp:727
727 {
(gdb) bt
#0 SrsHttpResponseWriter::write (this=0x7ffff7eb5bd0, data=0x7ffff7eb5470 "FLV\001\005",
size=9)
  at src/service/srs_service_http_conn.cpp:727
#1 0x0000000004fde19 in SrsBufferWriter::write (this=0x7ffff7eb5860, buf=0x7ffff7eb5470,
count=9, pnwrite=0x0)
  at src/app/srs_app_http_stream.cpp:506
#2 0x00000000040e9e1 in SrsFlvTransmuxer::write header (this=0xa71b10,
  flv_header=0x7ffff7eb5470 "FLV\001\005") at src/kernel/srs_kernel_flv.cpp:411
#3 0x00000000040e90d in SrsFlvTransmuxer::write_header (this=0xa71b10, has_video=true,
has audio=true)
   at src/kernel/srs kernel flv.cpp:399
#4 0x0000000004fd11a in SrsFlvStreamEncoder::write_header (this=0xa68b10,
has_video=true, has_audio=true)
   at src/app/srs_app_http_stream.cpp:355
#5 0x0000000004fd04f in SrsFlvStreamEncoder::write tags (this=0xa68b10,
msgs=0xa6da30, count=10)
   at src/app/srs_app_http_stream.cpp:340
#6 0x0000000004ff0dc in SrsLiveStream::do_serve_http (this=0xa3d9d0, w=0x7ffff7eb5bd0,
r = 0xa91c00
  at src/app/srs_app_http_stream.cpp:677
#7 0x0000000004fe108 in SrsLiveStream::serve http (this=0xa3d9d0, w=0x7ffff7eb5bd0,
r=0xa91c00)
  at src/app/srs_app_http_stream.cpp:544
#8 0x00000000049c86f in SrsHttpServeMux::serve_http (this=0xa11fe0, w=0x7ffff7eb5bd0,
r=0xa91c00)
  at src/protocol/srs_http_stack.cpp:711
#9 0x00000000562080 in SrsHttpServer::serve_http (this=0xa11e00, w=0x7ffff7eb5bd0,
r=0xa91c00)
  at src/app/srs_app_http_conn.cpp:300
---Type <return> to continue, or q <return> to quit---
```

```
#10 0x00000000049d6be in SrsHttpCorsMux::serve http (this=0xa3aa60, w=0x7ffff7eb5bd0,
r=0xa91c00)
   at src/protocol/srs_http_stack.cpp:859
#11 0x000000000561086 in SrsHttpConn::process_request (this=0xa626e0,
w=0x7ffff7eb5bd0, r=0xa91c00)
  at src/app/srs_app_http_conn.cpp:161
#12 0x000000000560ce8 in SrsHttpConn::do_cycle (this=0xa626e0) at
src/app/srs app http conn.cpp:133
#13 0x0000000004d10fb in SrsConnection::cycle (this=0xa626e0) at
src/app/srs_app_conn.cpp:171
#14 0x000000000509c88 in SrsSTCoroutine::cycle (this=0xa62a70) at
src/app/srs_app_st.cpp:198
#15 0x0000000000509cfd in SrsSTCoroutine::pfn (arg=0xa62a70) at
src/app/srs_app_st.cpp:213
#16 0x0000000005bdd9d in _st_thread_main () at sched.c:337
\#17.0\times0000000005be515 in st thread create (start=0x5bd719 < st vp schedule+170>,
arg=0x90000001, joinable=1,
  stk_size=1) at sched.c:616
#18 0xfffffffffffff in ?? ()
```

断点: b srs_app_recv_thread.cpp:600

SrsResponseOnlyHttpConn::pop message