```sh
#! /bin/sh



clear
read -p "Press enter to move from task to task"
clear

#Task 1
echo -e "Task 1\n"
echo -e "Hello World\n"
read
clear

#Task 2
echo -e "Task 2\n"
while true;
do
  read -p "Please enter an integer: " user_guess
  if [[ $user_guess =~ ^[+-]?[0-9] ]];then
    echo -e "\nYou entered $user_guess which is an integer\n"
    break
  else
    echo -e "\nThat is not an integer.  Press Enter to try again.\n"
    read
    clear
  fi
done
read
clear

#Task 3
echo -e "Task 3\n"
echo -e "$user_guess times 3 is: $((user_guess * 3)) \n"
read
clear

#Task 4
echo -e "Task 4\n"
for i in {1..20..1}
  do
    if [[ $i -eq 7 ]];then
    echo "$i is a Snowflake"
    elif [[ $(($i % 2)) -eq 0 ]];then
    echo "$i is Even"
    else
    echo "$i is Odd"
    fi
  done
echo
read
```

```bash
clear

#Task 5
echo -e  "Task 5\n"
while true;
do
  read -p "Enter a number greater than 13: " user_guess
  if [[ $user_guess -gt 13 && ( $user_guess -eq $user_guess || $user_guess
-eq 0 ) ]];then
    for (( i=1; i<=$user_guess; i++ ))
      do
        if [ $i -eq 7 ];then
          echo "$i is Lucky"
        elif [ $i -eq 13 ];then
          echo "$i is Unlucky"
        elif [ $(($i % 2)) -eq 0 ];then
          echo "$i is Even"
        else
          echo "$i is Odd"
        fi
      done
  break
  else
    echo "That isn't ok"
  fi
done


echo
read
clear

#Task 6
while true;
do
  echo -e "Task 6\n"
  read -p "Please enter a last name (Burkman): " user_name
  if [ $user_name == "Burkman" ];then
    break
  else
    clear
    continue
  fi
done
echo
clear

#Task 7
echo -e "Task 7\n"
counter=0
while [[ $counter -lt 10 ]];
```

```bash
do
    echo -e $counter
    counter=$(($counter+1))
done
echo
read
clear

#Task 8
echo -e "\nTask 8\n"
small_counter=0
large_counter=0
for j in {0..30..1}
    do
        my_random=$((($RANDOM%21)-10))
        if [ $my_random -lt $small_counter ]; then
            small_counter=$my_random
        elif [ $my_random -gt $large_counter ]; then
            large_counter=$my_random
        fi
    done
echo "The low random value is $small_counter"
echo "The high random value is $large_counter"
echo
read -p "Press Enter once more to leave the script"
```