

Demo: Random Forest



Dr. Goutam Chakraborty

SAS® Professor of Marketing Analytics

Director of MS in Business Analytics and Data Science* (<http://analytics.okstate.edu/mban/>)

Director of Graduate Certificate in Business Data Mining (<http://analytics.okstate.edu/certificate/grad-data-mining/>)

Director of Graduate Certificate in Marketing Analytics (<http://analytics.okstate.edu/certificate/grad-marketing-analytics/>)

- *Note some of these slides are copyrighted by SAS® and used with permission. Reuse or redistribution is prohibited

1

1

Objectives



- Discuss HP Forest node in SAS Enterprise Miner.
- Demonstration of VHP Forest using SAS EM

2

2



HP Forest Algorithm

- *Bagging* is the term for averaging many trees grown on bootstrap samples of the rows of training data. All columns are considered for splitting at every step.
- The HP Forest algorithm in SAS EM does sampling of the rows **and** sampling of the columns at each step.
- The forest algorithm perturbs the training data more than the bagging algorithm, producing more variation among the trees in the ensemble.
- Ensembles of a more diverse set of trees often leads to improved predictive accuracy.

3

3



HP Forest Node

- These are the three main options:
 - Number of trees
 - Specifies the number of trees that make up the forest. (Default = 100)
 - Number of inputs for a node
 - Specifies the number of input variables to consider splitting for each node. (Default = $\sqrt{\# \text{ of inputs }}$)
 - Sampling strategy
 - Specifies the number of observations used for each tree and how this sample is obtained. (Default = “proportion” and 0.6)

4

OOB Metrics

- The out-of-bag sample refers to the training data that is excluded during the construction of an individual tree.
- Observations in the training data that are used to construct an individual tree are the bagged sample.
- Some model assessments such as the iteration plots are computed using the out-of-bag sample as well as all the training data.

5

5

Gini Impurity

$$1 - \sum_{j=1}^r p_j^2 = 2 \sum_{j < k} p_j p_k$$

high diversity, low purity



$$\text{Pr}(\text{interspecific encounter}) = 1 - 2(3/8)^2 - 2(1/8)^2 = .69$$

low diversity, high purity




$$\text{Pr}(\text{interspecific encounter}) = 1 - (6/7)^2 - (1/7)^2 = .24$$

6

6

Variable Importance



7

Demo

- Continue with the SVM diagram
- Add 2 HP Forest nodes (from HPDM tab)
 - Keep one with default settings
 - Change other: 200 for Max Trees and 0.8 for proportion of obs in each sample
- Run and interpret results
- Compare with other models
 - Change selection statistic to average square error

8