PrintDesk API

REST API for tracking custom-print shop orders (T-shirts, hoodies, caps). Backend Development track, BuildLab Stage 1 - Week 1 spec (Order endpoints).

Conventions

- JSON only. Request and response fields use camelCase.
- Resource IDs are 24-character MongoDB ObjectId strings, exposed as `id`.
- A malformed ID (not 24 hex characters) returns 400, not 404 or 500.
- Errors always use the same shape (see the Error schema). Stack traces are never returned.
- Request bodies over 10 KB are rejected with 413 (`PAYLOAD_TOO_LARGE`).
- Timestamps are ISO 8601 UTC. `dueDate` is a plain date (YYYY-MM-DD).
- All data is dummy data.

Version: 1.0.0

Methods

[Jump to Models]

Table of Contents

Orders

- POST /orders
- DELETE /orders/{id}
- GET /orders/{id}
- GET /orders
- PATCH /orders/{id}
- PATCH /orders/{id}/status

System

- GET /
- GET /health

Orders

POST /orders

Create an order (**createOrder**)

Creates an order for an existing customer. `status` is always set to `received` on creation. If `customerId` is well-formed but does not match an existing customer, the response is 400.

Consumes

This API call consumes the following media types via the Content-Type request header:

- `application/json`

Request body

body OrderCreate (required)
Body Parameter —
example: {

```
"customerId" : "665f1c2e8a1b2c3d4e5f6a01",
"dueDate" : "2026-11-05",
```

```
  "notes" : "Church group event, needs matching colours"
}
```

Return type
Order

Example data
Content-Type: application/json

```
{
  "handledBy" : null,
  "createdAt" : "2026-10-13T09:30:00Z",
  "notes" : "Church group event, needs matching colours",
  "dueDate" : "2026-11-05",
  "id" : "665f1c2e8a1b2c3d4e5f6b10",
  "status" : "received",
  "updatedAt" : "2026-10-13T09:30:00Z"
}
```

Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
201
Order created. Order
400
Invalid input: malformed ID, missing or wrongly typed field, unknown field, invalid status value, bad query parameter, a request body that is not valid JSON (code `INVALID_JSON`), or a `customerId` that does not match an existing customer. Error
Example data
Content-Type: application/json

```
{"error":{"code":"VALIDATION_ERROR","message":"Request body is
invalid","details":[{"field":"customerId","issue":"customerId is
required"}]}}
```

500
Unexpected server error. No stack trace or internal detail is returned. Error
Example data
Content-Type: application/json

```
{"error":{"code":"INTERNAL_ERROR","message":"Something went wrong"}}
```

DELETE /orders/{id}

Delete an order (**deleteOrder**)

Permanently deletes the order. Returns 200 with the deleted order's ID so the client can confirm what was removed.

Path parameters

id (required)
Path Parameter — The order's ID (24-character hex string).

Return type
inline_response_200_2

Example data
Content-Type: application/json

```
{
  "id" : "665f1c2e8a1b2c3d4e5f6b10",
  "message" : "Order deleted"
}
```

Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
200
Order deleted. inline_response_200_2
400
Invalid input: malformed ID, missing or wrongly typed field, unknown field, invalid status value, bad query parameter, a request body that is not valid JSON (code `INVALID_JSON`), or a `customerId` that does not match an existing customer. Error
Example data
Content-Type: application/json

```
{"error":{"code":"VALIDATION_ERROR","message":"Request body is
invalid","details":[{"field":"customerId","issue":"customerId is
required"}]}}
```

404
No order exists with that ID. Error
Example data
Content-Type: application/json

```
{"error":{"code":"ORDER_NOT_FOUND","message":"Order not found"}}
```

500
Unexpected server error. No stack trace or internal detail is returned. Error
Example data
Content-Type: application/json

```
{"error":{"code":"INTERNAL_ERROR","message":"Something went wrong"}}
```

GET /orders/{id}

Get one order (**getOrder**)

Path parameters

id (required)
Path Parameter — The order's ID (24-character hex string).

Return type
Order

Example data
Content-Type: application/json

```
{
  "handledBy" : null,
  "createdAt" : "2026-10-13T09:30:00Z",
  "notes" : "Church group event, needs matching colours",
  "dueDate" : "2026-11-05",
  "id" : "665f1c2e8a1b2c3d4e5f6b10",
  "status" : "received",
  "updatedAt" : "2026-10-13T09:30:00Z"
}
```


Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses

200

Order found. Order

400

Invalid input: malformed ID, missing or wrongly typed field, unknown field, invalid status value, bad query parameter, a request body that is not valid JSON (code `INVALID_JSON`), or a `customerId` that does not match an existing customer. Error

Example data

Content-Type: application/json


```
{"error":{"code":"VALIDATION_ERROR","message":"Request body is
invalid","details":[{"field":"customerId","issue":"customerId is
required"}]}}
```


404

No order exists with that ID. Error

Example data

Content-Type: application/json


```
{"error":{"code":"ORDER_NOT_FOUND","message":"Order not found"}}
```


500

Unexpected server error. No stack trace or internal detail is returned. Error

Example data

Content-Type: application/json


```
{"error":{"code":"INTERNAL_ERROR","message":"Something went wrong"}}
```

GET /orders

List orders (**listOrders**)

Returns a paginated list of orders. Filters can be combined.

Query parameters

status (optional)
Query Parameter — Only return orders with this status.

customerId (optional)
Query Parameter — Only return orders for this customer.

page (optional)
Query Parameter — Page number, starting at 1. default: 1

limit (optional)
Query Parameter — Orders per page. default: 20

sort (optional)
Query Parameter — Sort field. Prefix with `-` for descending. default: -createdAt

Return type
OrderList

Example data
Content-Type: application/json


```
{
  "pagination" : {
    "total" : 42,
    "limit" : 20,
    "totalPages" : 3,
    "page" : 1
  },
  "data" : [ {
    "handledBy" : null,
    "createdAt" : "2026-10-13T09:30:00Z",
    "notes" : "Church group event, needs matching colours",
    "dueDate" : "2026-11-05",
    "id" : "665f1c2e8a1b2c3d4e5f6b10",
    "status" : "received",
    "updatedAt" : "2026-10-13T09:30:00Z"
  }, {
    "handledBy" : null,
    "createdAt" : "2026-10-13T09:30:00Z",
    "notes" : "Church group event, needs matching colours",
    "dueDate" : "2026-11-05",
    "id" : "665f1c2e8a1b2c3d4e5f6b10",
    "status" : "received",
    "updatedAt" : "2026-10-13T09:30:00Z"
  } ]
}
```


Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
200
Orders found (an empty list is still a 200). OrderList
400
Invalid input: malformed ID, missing or wrongly typed field, unknown field, invalid status value, bad query parameter, a request body that is not valid JSON (code `INVALID_JSON`), or a `customerId` that does not match an existing customer. Error
Example data
Content-Type: application/json


```
{"error":{"code":"VALIDATION_ERROR","message":"Request body is
invalid","details":[{"field":"customerId","issue":"customerId is
required"}]}}
```


500
Unexpected server error. No stack trace or internal detail is returned. Error

Example data
Content-Type: application/json

```
{"error":{"code":"INTERNAL_ERROR","message":"Something went wrong"}}
```

PATCH /orders/{id}

Update an order's details (**updateOrder**)

Partial update. Send only the fields you want to change; at least one is required. `status` cannot be changed here, use `PATCH /orders/{id}/status`.

Path parameters

id (required)
Path Parameter — The order's ID (24-character hex string).

Consumes
This API call consumes the following media types via the Content-Type request header:

- `application/json`

Request body

body OrderUpdate (required)
Body Parameter —
example: {
"dueDate" : "2026-11-10",
"notes" : "Due date moved back by customer"
}

Return type
Order

Example data
Content-Type: application/json

```
{
  "handledBy" : null,
  "createdAt" : "2026-10-13T09:30:00Z",
  "notes" : "Church group event, needs matching colours",
  "dueDate" : "2026-11-05",
  "id" : "665f1c2e8a1b2c3d4e5f6b10",
  "status" : "received",
  "updatedAt" : "2026-10-13T09:30:00Z"
}
```

Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
200
Order updated. Returns the full updated order. Order
400
Invalid input: malformed ID, missing or wrongly typed field, unknown field, invalid status value, bad query parameter, a request body that is not valid JSON (code `INVALID_JSON`), or a `customerId` that does

not match an existing customer. Error
Example data
Content-Type: application/json

```
{"error":{"code":"VALIDATION_ERROR","message":"Request body is
invalid","details":[{"field":"customerId","issue":"customerId is
required"}]}}
```

404
No order exists with that ID. Error
Example data
Content-Type: application/json

```
{"error":{"code":"ORDER_NOT_FOUND","message":"Order not found"}}
```

500
Unexpected server error. No stack trace or internal detail is returned. Error
Example data
Content-Type: application/json

```
{"error":{"code":"INTERNAL_ERROR","message":"Something went wrong"}}
```

PATCH /orders/{id}/status

Change an order's status (**updateOrderStatus**)

Moves an order to a new status. This is a separate endpoint from `PATCH /orders/{id}` so that, once roles exist (Week 2), staff can be allowed to update status without being allowed to edit other order details.

Path parameters

id (required)
Path Parameter — The order's ID (24-character hex string).

Consumes
This API call consumes the following media types via the Content-Type request header:

- `application/json`

Request body

body OrderStatusUpdate (required)
Body Parameter —
example: {
"status" : "printing"
}

Return type
Order

Example data
Content-Type: application/json

```
{
  "handledBy" : null,
  "createdAt" : "2026-10-13T09:30:00Z",
  "notes" : "Church group event, needs matching colours",
  "dueDate" : "2026-11-05",
  "id" : "665f1c2e8a1b2c3d4e5f6b10",
  "status" : "received",
  "updatedAt" : "2026-10-13T09:30:00Z"
}
```


Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
200
Status updated. Returns the full updated order. Order
400
Invalid input: malformed ID, missing or wrongly typed field, unknown field, invalid status value, bad query parameter, a request body that is not valid JSON (code `INVALID_JSON`), or a `customerId` that does not match an existing customer. Error
Example data
Content-Type: application/json


```
{"error":{"code":"VALIDATION_ERROR","message":"Request body is
invalid","details":[{"field":"customerId","issue":"customerId is
required"}]}}
```


404
No order exists with that ID. Error
Example data
Content-Type: application/json


```
{"error":{"code":"ORDER_NOT_FOUND","message":"Order not found"}}
```


500
Unexpected server error. No stack trace or internal detail is returned. Error
Example data
Content-Type: application/json


```
{"error":{"code":"INTERNAL_ERROR","message":"Something went wrong"}}
```


System

GET /

API root (**getRoot**)

Returns the API name and its top-level endpoints, so the base URL shows something useful in a browser.

Return type
inline_response_200

Example data
Content-Type: application/json

```
{
  "endpoints" : {
    "health" : "/health",
    "orders" : "/orders"
  },
  "name" : "PrintDesk API",
  "status" : "ok"
}
```

Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
200
API is up. inline_response_200

GET /health

Health check (**healthCheck**)

Returns 200 when the server is up. Also wakes a sleeping free-tier host.

Return type
inline_response_200_1

Example data
Content-Type: application/json

```
{
  "status" : "ok"
}
```

Produces
This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- `application/json`

Responses
200
Server is up. inline_response_200_1

Models

[Jump to Methods]

Table of Contents

1. Error
2. Error_error
3. Error_error_details
4. ObjectId
5. Order
6. OrderCreate
7. OrderList
8. OrderList_pagination
9. OrderStatus

10. OrderStatusUpdate
11. OrderUpdate
12. inline_response_200
13. inline_response_200_1
14. inline_response_200_2
15. inline_response_200_endpoints

Error

error
Error_error

Error_error

code
String Stable, machine-readable error code.
example: VALIDATION_ERROR

message
String Human-readable summary, safe to show to a client.
example: Request body is invalid

details (optional)
array[Error_error_details] Field-level problems, present for validation errors.

Error_error_details

field (optional)
String
example: customerId

issue (optional)
String
example: customerId is required

ObjectId

Order

id
ObjectId

customerId
ObjectId

handledBy (optional)
Staff member who handled the order. Null until staff auth exists (Week 2).

status
OrderStatus

dueDate (optional)
date format: date
example: Thu Nov 05 00:00:00 GMT 2026

notes (optional)
String
example: Church group event, needs matching colours

createdAt

Date format: date-time
example: 2026-10-13T09:30Z

updatedAt
Date format: date-time
example: 2026-10-13T09:30Z

OrderCreate

customerId
ObjectId

dueDate (optional)
date Must be today or later. format: date

notes (optional)
String

OrderList

data
array[Order]

pagination
OrderList_pagination

OrderList_pagination

page
Integer
example: 1

limit
Integer
example: 20

total
Integer Total orders matching the filters.
example: 42

totalPages
Integer
example: 3

OrderStatus

OrderStatusUpdate

status
OrderStatus

OrderUpdate

customerId (optional)
ObjectId

dueDate (optional)
date format: date

notes (optional)
String

inline_response_200

name (optional)
String
example: PrintDesk API

status (optional)
String
example: ok

endpoints (optional)
inline_response_200_endpoints

inline_response_200_1

status (optional)
String
example: ok

inline_response_200_2

message
String
example: Order deleted

id
ObjectId

inline_response_200_endpoints

health (optional)
String
example: /health

orders (optional)
String
example: /orders