



Moscow Institute of Physics and Technology

My Pity

Fedor Alekseev, Dmitry Ivaschenko, Daria Kolodzey

Whatever contest
today

1	Contest	1
	template.cpp	1
	.vimrc	1
2	Numerical	1
	PolyRoots.h	1
	PolyInterpolate.h	1
	SolveLinear.h	1
	SolveLinear2.h	1
	FastFourierTransform.h	1
	NumberTheoreticTransform.h	2
3	Strings	2
	SuffixArray.h	2
	Hashes.h	2
	AhoCorasick.h	2
	ZFunction.h	3
	PrefixFunction.h	3
	Manacher.h	3

Contest (1)

template.cpp	13 lines
#include <bits/extc++.h> using namespace std; #define WHOLE(v) v.begin(),v.end() #define sz(v) static_cast<int>(v.size()) using i64 = int64_t; int main() { cin.sync_with_stdio(false); cin.tie(nullptr); cin.exceptions(cin.failbit); } .vimrc	
set nocomp si aw ai is ts=2 sw=2 et tm=100 nu bg=dark sy on im jj <esc>	

Numerical (2)

PolyRoots.h	
Description: Finds the real roots to a polynomial. Usage: poly_roots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2 = 0 Time: $\mathcal{O}(n^2 \log(1/\epsilon))$	
"Polynomial.h"	23 lines
vector<double> poly_roots(Poly p, double xmin, double xmax) { if (sz(p.a) == 2) { return {-p.a[0]/p.a[1]}; } vector<double> ret; Poly der = p; der.diff(); auto dr = poly_roots(der, xmin, xmax); dr.push_back(xmin-1); dr.push_back(xmax+1); sort(all(dr)); rep(i,0,sz(dr)-1) { double l = dr[i], h = dr[i+1]; bool sign = p(l) > 0; if (sign ^ (p(h) > 0)) { rep(it,0,60) { // while (h - l > 1e-8) double m = (l + h) / 2, f = p(m); if ((f <= 0) ^ sign) l = m; else h = m; } ret.push_back((l + h) / 2); } } return ret; } PolyInterpolate.h	
Description: Given n points $(x[i], y[i])$, computes an $n-1$ -degree polynomial p that passes through them: $p(x) = a[0] * x^0 + \dots + a[n-1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n-1) * \pi), k = 0 \dots n-1$. Time: $\mathcal{O}(n^2)$	
typedef vector<double> vd;	13 lines
vd interpolate(vd x, vd y, int n) { vd res(n), temp(n); rep(k,0,n-1) rep(i,k+1,n) y[i] = (y[i] - y[k]) / (x[i] - x[k]); double last = 0; temp[0] = 1; rep(k,0,n) rep(i,0,n) {	

res[i] += y[k] * temp[i]; swap(last, temp[i]); temp[i] -= last * x[k]; } return res; }	
SolveLinear.h	
Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost. Time: $\mathcal{O}(n^2 m)$	
int solveLinear(vector<vector<double>& A, vector<double>& b,	40 lines
vector<double>& x) { int n = sz(A), m = sz(x), rank = 0, br, bc; if (n) assert(sz(A[0]) == m); vector<int> col(m); iota(WHOLE(col), 0); for (int i = 0; i < n; ++i) { double v, bv = 0; for (int r = i; r < n; ++r) for (int c = i; c < m; ++c) if ((v = fabs(A[r][c])) > bv) br = r, bc = c, bv = v; if (bv < eps) { for (int j = 0; j < n; ++j) if (fabs(b[j]) > eps) return -1; break; } swap(A[i], A[br]); swap(b[i], b[br]); swap(col[i], col[bc]); for (int j = 0; j < n; ++j) swap(A[j][i], A[j][bc]); bv = 1. / A[i][i]; for (int j = i + 1; j < n; ++j) { double fac = A[j][i] * bv; b[j] -= fac * b[i]; for (int k = i + 1; k < m; ++k) A[j][k] -= fac * A[i][k]; } rank++; } x.assign(m, 0); for (int i = rank; i--;) { b[i] /= A[i][i]; x[col[i]] = b[i]; for (int j = 0; j < i; ++j) b[j] -= A[j][i] * b[i]; } return rank; // (multiple solutions if rank < m) }	
SolveLinear2.h	
Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:	
"SolveLinear.h"	8 lines
for(int j = 0; j < n; ++j)if(j != i) // instead of for(j=i+1; j<n) // ... then at the end: x.assign(m, undefined); for (int i = 0; i < rank; ++i) { for (int j = rank; j < m; ++j) if (fabs(A[i][j]) > eps) goto fail; x[col[i]] = b[i] / A[i][i]; fail:; } FastFourierTransform.h	
Description: Computes $\hat{f}(k) = \sum_x f(x) \exp(-2\pi i k x / N)$ for all k . Useful for convolution: conv(a, b) = c, where $c[x] = \sum a[i]b[x-i]$. a and b should be of roughly equal size. For convolutions of integers, consider using a number-theoretic transform instead, to avoid rounding issues. Time: $\mathcal{O}(N \log N)$	
<valarray>	29 lines
typedef valarray<complex<double> > carray;	
void fft(carray& x, carray& roots) {	
int N = sz(x);	
if (N <= 1) return;	
carray even = x[slice(0, N/2, 2)];	
carray odd = x[slice(1, N/2, 2)];	
carray rs = roots[slice(0, N/2, 2)];	
fft(even, rs);	
fft(odd, rs);	
rep(k,0,N/2) {	
auto t = roots[k] * odd[k];	
x[k] = even[k] + t;	
x[k+N/2] = even[k] - t;	
}	
typedef vector<double> vd;	
vd conv(const vd& a, const vd& b) {	
int s = sz(a) + sz(b) - 1, L = 32-__builtin_clz(s), n = 1<L;	
if (s <= 0) return {};	
carray av(n), bv(n), roots(n);	
rep(i,0,n) roots[i] = polar(1.0, -2 * M_PI * i / n);	
copy(all(a), begin(av)); fft(av, roots);	
copy(all(b), begin(bv)); fft(bv, roots);	

```
    roots = roots.apply(conj);
    carray cv = av * bv; fft(cv, roots);
    vd c(s); rep(i,0,s) c[i] = cv[i].real() / n;
    return c;
}
```

NumberTheoreticTransform.h

Description: Can be used for convolutions modulo specific nice primes of the form $2^ab + 1$, where the convolution result has size at most 2^a . For other primes/integers, use two different primes and combine with CRT. May return negative values.
Time: $\mathcal{O}(N \log N)$

"ModPow.h"38 lines

```
const ll mod = (119 << 23) + 1, root = 3; // = 998244353
// For p < 2^30 there is also e.g. (5 << 25, 3), (7 << 26, 3),
// (479 << 21, 3) and (483 << 21, 5). The last two are > 10^9.

typedef vector<ll> vl;
void ntt(ll* x, ll* temp, ll* roots, int N, int skip) {
    if (N == 1) return;
    int n2 = N/2;
    ntt(x, temp, roots, n2, skip*2);
    ntt(x+skip, temp, roots, n2, skip*2);
    rep(i,0,N) temp[i] = x[i*skip];
    rep(i,0,n2) {
        ll s = temp[2*i], t = temp[2*i+1] * roots[skip*i];
        x[skip*i] = (s + t) % mod; x[skip*(i+n2)] = (s - t) % mod;
    }
}

void ntt(vl& x, bool inv = false) {
    ll e = modpow(root, (mod-1) / sz(x));
    if (inv) e = modpow(e, mod-2);
    vl roots(sz(x), 1), temp = roots;
    rep(i,1,sz(x)) roots[i] = roots[i-1] * e % mod;
    ntt(&x[0], &temp[0], &roots[0], sz(x), 1);
}

vl conv(vl a, vl b) {
    int s = sz(a) + sz(b) - 1; if (s <= 0) return {};
    int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1 << L;
    if (s <= 200) { // (factor 10 optimization for |a|,|b| = 10)
        vl c(s);
        rep(i,0,sz(a)) rep(j,0,sz(b))
            c[i + j] = (c[i + j] + a[i] * b[j]) % mod;
        return c;
    }
    a.resize(n); ntt(a);
    b.resize(n); ntt(b);
    vl c(n); ll d = modpow(n, mod-2);
    rep(i,0,n) c[i] = a[i] * b[i] % mod * d % mod;
    ntt(c, true); c.resize(s); return c;
}
```

Strings (3)

SuffixArray.h

57 lines

```
struct SuffixArray {
    string s;
    vector<int> order, rank, lcp;

    SuffixArray(const string& _s): s(_s + '$') {
        int n = sz(s);
        std::vector<int> count(n + 130), nextPos(count.size() + 1);
        std::vector<int> nextOrder(n), nextColor(n);
        std::vector<int> color(WHOLE(s));

        auto norm = [n](int i) {
            return i < 0 ? i + n : i >= n ? i - n : i;
        };

        order.resize(n);
        std::iota(WHOLE(order), 0);
        std::sort(WHOLE(order),
            [&](int aa, int bb) { return s[aa] < s[bb]; });

        for (int half = 1; half < n; half *= 2) {
            count.assign(count.size(), 0);
            for (auto col : color)
                ++count[col];

            nextPos[0] = 0;
            partial_sum(WHOLE(count), nextPos.begin() + 1);

            for (auto pos : order) {
                auto shifted = norm(pos - half);
                nextOrder[nextPos[color[shifted]]++] = shifted;
            }
            order.swap(nextOrder);

            nextColor[order[0]] = 0;
            for (int i = 1; i < n; ++i) {
                auto pos = order[i], prev = order[i - 1];
                nextColor[pos] = nextColor[prev] + (
                    tie(color[pos], color[norm(pos + half)]) !=
                    tie(color[prev], color[norm(prev + half)])
                );
            }
            color.swap(nextColor);
        }
    }
};
```

```
    }

    rank.resize(n);
    for (int i = 0; i < n; ++i)
        rank[order[i]] = i;

    lcp.resize(n);
    for (int i = 0; i < n; ++i) if (rank[i]) {
        for (int p0 = order[rank[i] - 1]; s[i + h] == s[p0 + h];)
            h++;
        lcp[rank[i]] = h;
        h -= h > 0;
    }
}

};
```

Hashes.h

29 lines

```
using Hash = array<ui64, 3>;
#define HOP(op) \
    inline Hash operator op (Hash a, Hash b) { \
        return {a[0] op b[0], a[1] op b[1], a[2] op b[2]}; \
    }
HOP(+)HOP(-)HOP(*)HOP(%)
inline Hash makeHash(ui64 val) { return {val, val, val}; }

const Hash Multiplier{{228227, 227223, 22823}};
const Hash Modulus{{424242429, 2922827, 22322347}};

vector<Hash> pows(1);
struct Hashes {
    explicit Hashes(const string& s) {
        pows.front().fill(1);
        while (pows.size() <= s.size())
            pows.push_back(pows.back() * Multiplier % Modulus);
        prefs.push_back(makeHash(0));
        for (auto c : s)
            prefs.push_back((prefs.back() * Multiplier + makeHash(c))
                % Modulus);
    }
    Hash get(size_t begin, size_t end) const {
        return (prefs[end] - prefs[begin] * pows[end - begin]
            % Modulus + Modulus) % Modulus;
    }
private:
    vector<Hash> prefs;
};
```

AhoCorasick.h

Description: on-line tracking of the set of suffixes of a text that are prefixes of some words from a dictionary.

44 lines

```
struct AhoCorasick {
    AhoCorasick(): n(1) {
        n.reserve(TrieSize);
    }

    void addWord(const string& word, int id) {
        int v = 0;
        for (int ch : word) {
            ch -= 'a';
            auto& u = n[v].trans[ch];
            if (!u) {
                u = int(n.size());
                n.emplace_back();
            }
            v = u;
        }
        n[v].termId = id;
    }

    void build() {
        queue<int> q;
        for (q.push(0); !q.empty(); q.pop()) {
            auto v = q.front();
            for (Char ch = 0; ch < Alph; ++ch) {
                auto& u = n[v].trans[ch];
                if (!u) {
                    u = n[n[v].link].trans[ch];
                    continue;
                }
                q.push(u);
                auto i = n[u].link = (v ? n[n[v].link].trans[ch] : 0);
                n[u].nextTerm = (n[i].termId >= 0 ? i : n[i].nextTerm);
            }
        }
    }

private:
    struct Node {
        int trans[Alph]{};
        int nextTerm = -1, termId = -1, link = 0;
    };

    vector<Node> n;
};
```

ZFunction.h

Description: $z[x]$ is $\max L: s[x:x+L] == s[:L]$

11 lines

```
vector<size_t> zFun(const string& s) {
    vector<size_t> z(s.size(), 0);
    for (size_t left = 0, right = 0, i = 1; i < s.size(); ++i) {
        z[i] = (i < right ? min(right - i, z[i - left]) : 0);
        while (i + z[i] < s.size() && s[i + z[i]] == s[z[i]])
            ++z[i];
        if (i + z[i] > right)
            tie(left, right) = {i, i + z[i]};
    }
    return z;
}
```

PrefixFunction.h

Description: $pi[x]$ is the length of the longest prefix of s that ends at x , other than $s[0..x]$ itself

10 lines

```
vector<size_t> pi(const string& s) {
    vector<size_t> p(s.size(), 0);
    for (size_t i = 1; i < s.size(); ++i) {
        auto px = p[i - 1];
        while (px && s[i] != s[px])
            px = p[px - 1];
        p[i] = px + (s[i] == s[p]);
    }
    return p;
}
```

Manacher.h

Description: For each position in a string, computes $p[0][i] =$ half length of longest even palindrome around pos i , $p[1][i] =$ longest odd (half rounded down).

Time: $\mathcal{O}(N)$

17 lines

```
void manacher(const string& s) {
    auto n = int(s.size());
    vector<int> p[2];
    p[0].resize(n + 1);
    p[1].resize(n);
    for (int z = 0; z < 2; ++z) {
        for (int i=0, l=0, r=0; i < n; ++i){
            int t = r - i + !z;
            if (i<r) p[z][i] = min(t, p[z][l + t]);
            int L = i - p[z][i], R = i + p[z][i] - !z;
            while (L >= 1 && R + 1 < n && s[L - 1] == s[R + 1])
                p[z][i]++, L--, R++;
            if (R > r)
                tie(l, r) = {L, R};
        }
    }
}
```