

adaReach Business SMS API

Documentation

Introduction

The adaReach Platform offers a simplified solution for sending and receiving messages, along with managing and launching bulk advertising campaigns. It enables efficient organization of contacts and bulk lists, while providing robust reporting and analytics tools that generate detailed reports from multiple angles. Furthermore, the adaReach Platform integrates with external applications and services through web services, facilitating SMS transmission for both transactional & advertising purposes. This interface allows client applications to send messages and track their status

In summary, the adaReach Platform enables businesses to:

- Send transactional and promotional SMS
- Track message delivery status (DLR)
- Manage credit balances
- Authenticate securely using bearer tokens

API Security

All endpoints require **Bearer Token Authorization** (Authorization: Bearer <token>)

Token Validity

Token Type	Description	Validity Duration
token	Main access token for sending and querying SMS	1 hour
refresh_token	Used to generate a new access token without login again	1 hour

- It is suggested to call the refresh Token API before completing 1 hour for seamless service.

HTTP Status Codes

Code	Meaning	Explanation
200	OK	Request processed successfully
201	Created	Resource created (not used in this API)
400	Bad Request	Missing or invalid input
401	Unauthorized	Invalid or expired token
403	Forbidden	Access denied
404	Not Found	Resource or endpoint doesn't exist
429	Too Many Requests	Server Rate/TPS limit exceeded
500	Internal Server Error	Server malfunction
501	Not Implemented	Feature or endpoint not available

1. Generate Token

Method: POST

Endpoint: <https://api.mobireach.com.bd/auth/tokens>

◆ Parameters

Name	Type	Required	Description
username	string	✓	Your account username
password	string	✓	Your account password

✓ Success Response

```
{
  "token": "312dsadaaga123",
  "refresh_token": "2141511eqsfasga1123"
}
```

✗ Failure Response

```
{
  "error": "Unauthorized",
  "message": "Invalid username or password"
}
```

cURL Example

```
curl --location 'https://api.mobireach.com.bd/auth/tokens' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "username": "your_username",  
  "password": "your_password"  
'
```

*Error message will be given based on the relevant error code

2. Refresh Token

Method: POST

Endpoint: https://api.mobireach.com.bd/auth/token/refresh

◆ Headers

Name	Type	Required	Description
Authorization	string		Bearer <refresh_token>

Success Response

```
{  
  "token": "new_valid_token",  
  "refresh_token": "new_refresh_token"  
}
```

cURL Example

```
curl --location --request POST 'https://api.mobireach.com.bd/auth/token/refresh' \  
--header 'Content-Type: application/json' \  
--header 'Authorization: Bearer <your_refresh_token>'
```

*Error message will be given based on the relevant error code

✉ 3. Send SMS (Single or Bulk)

Method: POST

Endpoint: <https://api.mobireach.com.bd/sms/send>

◆ Headers

Name	Type	Required	Description
Authorization	string	✓	Bearer <token>
Content-Type	string	✓	application/json

◆ Body Parameters

Name	Type	Required	Description
sender	string	✓	Sender ID (e.g., Masking, Longcode, Shortcode)
receiver	array	✓	Array of 13-digit MSISDN numbers (e.g.,8801XXXXXXXX). For bulk request maximum 400 MSISDNs can be passed as values using commas in the array. E.g.["8801XXXXXXXX","8801XXXXXXXX"]
content	string	✓	Message text to be sent
msgType	string	✓	Message type: "T" for transactional, "P" for promotional
requestType	string	✓	"S" for single, "B" for bulk
contentType	string	✓	"1" for Regular, "2" for Unicode (mandatory for promotional messages)

✓ Success Response

```
{  
  "status": "SUCCESS",  
  "description": "Message sent",  
  "msgCost": "0.0",  
  "currentBalance": "49999.7915",  
  "contentType": 1,  
  "msgCount": 1,  
  "errorCode": 0,  
  "messageId": 626312999124078592  
}
```

✗ Failure Response

```
{  
  "status": "FAILED",  
  "description": "Invalid Parameter",  
  "msgCost": "0.0",  
  "currentBalance": "0",  
  "contentType": 1,  
  "msgCount": 0,  
  "errorCode": 1504,  
  "messageId": 0  
}
```

cURL Example

```
curl --location 'https://api.mobireach.com.bd/sms/send' \  
--header 'Content-Type: application/json' \  
--header 'Authorization: Bearer your_token' \  
--data '{  
  "sender": "adaReach",  
  "receiver": ["8801XXXXXXXX"],  
  "content": "Test message",  
  "msgType": "T",  
  "requestType": "S",  
  "contentType": 1  
}'
```

*Error message will be given based on the relevant error code

4. Check Message Status (DLR)

Method: GET

Endpoint: <https://api.mobireach.com.bd/sms/status>

◆ Query Parameters

Name	Type	Required	Description
sender	string	✓	The sender ID used
messageId	string	✓	Message ID returned when the message was sent
receiver	string	✓	13-digit MSISDN of the receiver (e.g., 8801XXXXXXXX)

✅ Success Response

```
{
  "status": "SUCCESS",
  "description": "Successfully transmitted",
  "msgCost": "0.01390",
  "duringMsgBalance": "49999.7776",
  "contentType": 1,
  "msgCount": 1,
  "errorCode": 0,
  "messageId": 626314298741755904
}
```

❌ Failure Response

```
{
  "status": "FAILED",
  "description": "Invalid Parameter",
  "msgCost": "0",
  "duringMsgBalance": "0",
  "contentType": 1,
  "msgCount": 0,
  "errorCode": 1504,
  "messageId": 0
}
```

📘 cURL Example

```
curl --location
'https://api.mobireach.com.bd/sms/status?sender=adaReach&messageId=626314298741755904&receiver=8801XXXXXXX' \
--header 'Authorization: Bearer <your_token>'
```

*Error message will be given based on the relevant error code

5. Check Balance

Method: GET

Endpoint: https://api.mobireach.com.bd/balance?username=your_username

◆ Headers

Name	Type	Required	Description
Authorization	string	☒	Bearer <token>

✅ Success Response

```
{  
  "status": "SUCCESS",  
  "guiBalance": "123456.12345",  
  "apiBalance": "456.12345"  
}
```

❌ Failure Response

```
{  
  "status": "FAILED",  
  "guiBalance": "0",  
  "apiBalance": "0"  
}
```

cURL Example

```
curl --location 'https://api.mobireach.com.bd/balance?username=your_username' \  
--header 'Authorization: Bearer <your_token>'
```

*Error message will be given based on the relevant error code

Error Code Reference

Code	Description	Explanation
1501	Invalid Token	Authorization token is invalid or missing
1502	Exceed Capacity	TPS (transaction per second) limit exceeded
1503	Sender Not Allowed	Masking not configured for your account
1504	Invalid Parameter	One or more API parameters are invalid
1505	Missing Parameter	Required field is missing
1506	Insufficient Balance	Not enough balance to send SMS
1508	API Auth Fail	Invalid authentication credentials
1509	New API Not Allowed	Account not allowed to use the new adaReach API
1510	New API Other Error	General error not covered by other codes
1512	System Error (remote node down)	Server is down
1513	Wrong Content Type	Unicode message sent with wrong contentType
1514	MSISDN Limit Exceeded	Bulk request exceeded max 400 MSISDNs
1201	Data API Not Allowed	Data API access not enabled
1202	Receiver Number Not Valid	Wrong Receiver Number(Also not Robi/Airtel)
1203	Provision Pack Not Allowed	No provision pack available for the user
1204	Provision Pack Invalid	Invalid provision pack
1001	International Not Allowed	International SMS not allowed for the user
1002	SMS Other Error	SMSC submission error (especially in DLR check)

Final Notes

- Use refresh_token to renew your session rather than calling /auth/tokens repeatedly.
- Failure to comply with the refresh_token API rule will result in automatic banned from using the application for suspicious activity.
- For Unicode content or promotional messages, ensure contentType = 2.
- To send SMS, Ensure receiver MSISDN is in 13 or 11-digit format (e.g., 8801XXXXXXXXX or 01XXXXXXXXX).
- Promotional messages must be sent between 9 AM – 8 PM as per regulatory compliance.
- For promotional messages, ensure msgType = "P".

Thank You

For any queries or further assistance, kindly reach out to helpdesk@adaglobal.com

