

OneNote

Home Insert Draw View Tell me

New Window Switch Background Immersive Reader Page Versions Deleted Notes Zoom Out Zoom In 50% Reset Zoom Page Width Password Protection Paper Color Paper Style Hide Page Title Hide Authors Translate Check Accessibility

CSE495A  
Sunday, February 11, 2024 10:37 AM

Introduction to Robotics

Prerequisite : Linear Algebra, Differential equations,  
Probability (less important this specific class),  
Programming (CSE 115 minimum)  
CSE 225 (if you focus on that part  
CSE 373 of robotics)

Computer vision → Linear Algebra  
Eigenvalues, SVD

{ Research paper  
or  
Project (for example: simulation)

SS

OneNote

Home Insert Draw View Tell me

New Window Switch Background Immersive Reader Page Versions Deleted Notes Zoom Out Zoom In 60% Reset Zoom Page Width Password Protection Paper Color Paper Style Hide Page Title Hide Authors Translate Check Accessibility

# See - Think - Act cycle

Engineering models → inspired from natural phenomena  
for example : planes

Example : Advising process

```
graph LR; A[See offered courses] --> B[Decide on courses]; B --> C[Advise in RDS]; C -- "Revise Accordingly" --> A
```

See offered courses → Decide on courses → Advise in RDS

See Perception  
Think Decision making  
Act Action

Revise Accordingly

SS

OneNote

Home Insert Draw View Tell me

New Window Switch Background Immersive Reader Page Versions Deleted Notes Zoom Out Zoom In 50% Reset Zoom Page Width Password Protection Paper Color Paper Style Hide Page Title Hide Authors Translate Check Accessibility

Sunday, February 11, 2024 11:31 AM

## Stages of analysis & design

stage ① ✓ Develop mathematical model for the robot.  
i.e. : differential equations (this Newton's laws)  
↓  
Apply Newton's laws to obtain DE.

stage ② ✓ Simulate the mathematical model to  
find the correct algorithms to solve  
your mission/problem. Example: python, gazebo, pybullet  
matlab etc.

stage ③ ✓ Implement in physical robot

SS

# Robot dynamical models ( differential equations, equations of motion )

General equation

$$\dot{x} = f(x(t), u(t))$$

$t$  : time

$x(t)$  : state vector

$u(t)$  : control vector

$$\dot{x} = \frac{dx}{dt}$$

$$\ddot{x} = \frac{d^2x}{dt^2}$$

← differential equation

↑  
from applying  
Newton's law

Example :  $x = \begin{bmatrix} - \\ - \\ - \end{bmatrix}_{3 \times 1}$

$$u = \begin{bmatrix} - \\ - \end{bmatrix}_{2 \times 1}$$

OneNote

Home Insert Draw View Tell me

New Window Switch Background Immersive Reader Page Versions Deleted Notes Zoom Out Zoom In 60% Reset Zoom Page Width Password Protection Paper Color Paper Style Hide Page Title Hide Authors Translate Check Accessibility

$u(t)$  : control vector

$x = \frac{d^2x}{dt^2}$

from applying Newton's law

Example :  $x = \begin{bmatrix} - \\ - \\ - \end{bmatrix}_{3 \times 1}$

$u = \begin{bmatrix} - \\ - \end{bmatrix}_{2 \times 1}$

$x(t)$  input from sensor

$\dot{x} = f(x, u)$  Decision making

$u(t)$  output to actuators

SS

OneNote

Home Insert Draw View Tell me

New Window Switch Background Immersive Reader Page Versions Deleted Notes Zoom Out Zoom In 40% Reset Zoom Page Width Password Protection Paper Color Paper Style Hide Page Title Hide Authors Translate Check Accessibility

Sunday, February 13, 2024 11:57 AM

Unicycle model

$$\begin{bmatrix} \dot{x} \\ \dot{y} \\ \dot{\theta} \end{bmatrix} = \begin{bmatrix} \cos \theta & 0 \\ \sin \theta & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} v \\ \omega \end{bmatrix}$$

$\dot{x} = f(x, u)$

$x = \begin{bmatrix} x \\ y \\ \theta \end{bmatrix}$   $u = \begin{bmatrix} v \\ \omega \end{bmatrix}$

$(x, y) \Rightarrow$  position  
 $\theta \Rightarrow$  angle with x-axis

$v \Rightarrow$  translational velocity  
 $\omega \Rightarrow$  rotational velocity

SS

