

LEGEND 112S

C&I Battery Pack

**64.3kWh-241.1kWh
Expandable Capacity**



Product Features



Built for Maximum Flexibility

Modular, stackable design allows capacity expansion up to 720kWh, easily adapting to different site sizes and evolving energy demands.



Quick to Install. Easy to Deploy

Plug-and-play stack architecture enables fast system installation in less than 30 minutes, minimizing on-site work and reducing deployment time.



15+ Years of Daily Cycling

Built with HITHIUM 314Ah LFP cells rated for 11,000 cycles, designed for long-term daily operation, helping reduce battery replacements and lifetime energy costs.



Smart BMS with Intelligent Air Cooling

An intelligent Smart BMS combined with optimized air-cooling control continuously monitors system status, enhances thermal stability, and helps ensure safe, reliable operation at the system level.

PRODUCT DETAILS

Model	HeroEE LEGEND 112S
Battery Type	LiFePO4
Battery Cycles	11000 cycles@(25 C , 100%DOD, 0.5P, @70%SOH)
Module Voltage/Capacity	51.2V/314Ah
Module Stacking Quantity	4~15
System Energy Range	64.3kWh~241.1kWh
System Operating Voltage	172.8[VDC]~876[VDC]
Standard Charge/Discharge Current	157A/157A (0.5C)
Maximum Charge/Discharge Current	200A/200A
Type of Cooling	Natural Cooling
Operating Temperature	Charging: 0°C - 45°C Discharging: -10°C - 45°C
Storage Temperature	-20°C - 60°C
System Size	770*435*1986mm (7 packs) 770*435*1738mm (6 packs) 770*435*1490mm (5 packs) 770*435*1242mm (4 packs)
Mounting Method	Stack-style
Levels of Protection	IP20
Allow Relative Humidity	10% - 90% (No Condensation)
Allowable Altitude Above Sea Level	≤4000 (Decreased Above 2000m)
Communication Interface	RS485
Approval Standards	UN38.3 IEC62619 CE

*The above is for reference only, the specification sheet shall prevail.

LEGEND 112S

Battery Pack



Battery Pack	112S51314
Battery Type	LiFePO ₄
Combination Mode	1P16S
Nominal Voltage	51.2[VDC]
Operating Voltage	43.2[VDC]~58.4[VDC]
Nominal Capacity	314Ah
Nominal Energy Capacity	16076Wh
Dimensions (Width x Depth x Height)	770×435×248mm
Single Module Weight	130kg
Cycle Life	≥11000 cycles@25℃±2℃ , 0.5P , 70%SOH
Charge Temperature	0℃~45℃
Discharge Temperature	-10℃~45℃
Storage Environment Temperature	-20℃~60℃
Relative Humidity	10%~90%

*The above is for reference only, the specification sheet shall prevail.

LEGEND 112S

High Voltage Battery Control Box



High Voltage Battery Control Box	112SPDU
Dimensions (Width x Depth x Height)	770*435*150mm
System Voltage	172.8[VDC]~876[VDC]
Maximum Operating Current	200A
Charge Temperature	0℃ ~ 45℃
Discharge Temperature	- 10℃ ~ 45℃
Storage Environment Temperature	-20℃~60℃

*The above is for reference only, the specification sheet shall prevail.

Contact:

Tel:

<https://www.hero-ee.com>



Business Cooperation



website