

Rows - Grid System

Rows are in .container or .container-fluid

Columns

.col-xs-	Always	Full
.col-sm-	>768	750 wide
.col-md-	>992	970 wide
.col-lg-	>1200	1170 wide

Resets, Offsets, Pushes, Pulls

.clearfix

.col-xs-offset- (sm, md, lg)

Nest using a .row inside a col

.col-xs-push- (sm, md, lg)

.col-xs-pull- (sm, md, lg)

.visible-xs (sm, md, lg)

.hidden-xs (sm, md, lg)

.visible-print

.hidden-print

Grid Variables

@grid-columns: 12

@grid-gutter-width: 30px

@grid-float-breakpoint: 768px

Using Grid Mixin CSS

```
.wrapper { .make-row();
.content-main { .make-lg-column(8);
.content-secondary {
.make-lg-column(3);
.make-lg-column-offset(1);
}
```

Using Grid Mixin HTML

```
<div class="wrapper">
<div class="content-main">...</div>
<div class="content-secondary">...</div>
</div>
```

Typography

.h1 .h2 .h3

.h4 .h5 .h6

.small <small> .lead

@font-size-base | @line-height-base

Align

.text-left .text-right

.text-center .text-justify

Text Helpers

.text-muted .text-primary

.text-success .text-info

.text-warning .text-danger

.bg-primary .bg-success

.bg-info .bg-warning

.bg-danger

.text-hide .sr-only

Lists

.list-unstyled .list-inline

Descriptions

```
<dl> <dt>...</dt> <dd>...</dd> </dl>
.dl-horizontal
```

Images

.img-responsive (max-width:100%, height:auto)

.img-rounded

.img-circle

.img-thumbnail (double border)

Forms

NEED TO DO

Buttons

```
<button type="button" class="btn btn-default">Default</button>
<a href="#" class="btn btn-primary btn-lg active" role="button">Primary link</a>
```

Button Classes

.btn-default .btn-primary

.btn-success .btn-info

.btn-warning .btn-danger

.btn-link (to look like a link)

.btn-lg .btn-sm

.btn-xs .btn-block

.active (A tag) .disabled (A tag)

disabled="disabled"

Labels

.label .label-default

primary, success, info, warning, danger

```
<span class="label label-default">New</span>
```

Badge

```
<span class="badge">42</span>
```


Alerts

.alert .alert-success

success, info, warning, or danger

.alert-dismissible

```
<button type="button" class="close" data-dismiss="alert" aria-hidden="true">&times;
</button>
<a href="#" class="alert-link">...</a>
```



By **John Mason** (masonjo)
cheatography.com/masonjo/
www.e-rehab.com

Published 29th April, 2014.
 Last updated 9th May, 2014.
 Page 1 of 2.

Sponsored by **Readability-Score.com**
 Measure your website readability!
<https://readability-score.com>

Tables

.table .table-striped

.table-bordered .table-hover

.table-condensed

.table-responsive

```
Wrap .table in .table-responsive
<div class='table-responsive'>
...table
</div>
```

Rows or Cells

.active .success .info

.warning .danger

Tags

abbr

```
<abbr title="attribute">attr</abbr>
```

address

```
<address> <strong>Twitter, Inc.</strong>
<br> 795 Folsom Ave, Suite 600<br> San
Francisco, CA 94107<br> <abbr
title="Phone">P:</abbr> (123) 456-7890
</address>
```

blockquote

```
<blockquote> <p>Lorem ipsum dolor sit
amet, consectetur adipiscing elit.
Integer</p> </blockquote>
```

blockquote footer

```
<footer>Someone famous in <cite
title="Source Title">Source
Title</cite></footer>
```

blockquote right justify

```
.blockquote-reverse
```

code

```
<code>&lt;section&gt;</code>
```

kbd Keyboard Entry

```
<kbd>cd</kbd>
```

.pre-scrollable

Max Height 350px box, with y-axis scrollbar.
Used with **pre** tag

close button

```
<button type="button" class="close" aria-
hidden="true">&times;</button>
```

Caret

```
<span class="caret"></span>
```

Tags (cont)

Floats

```
.pull-left .pull-right
```

Float Mixin

```
.element { .pull-left(); }
```

Clear Floats

```
.clearfix
```

Center Block (mixin also)

```
.center-block (display:block, margin auto) |
.center-block();
```

Show (mixin also)

```
.show | .show();
```

Hide (mixin also)

```
.hide | .hide();
```

Glyphicons

```
<span class="glyphicon glyphicon-search">
</span>
```

