

Safety Data Sheet

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Screen Wash -60°C

UFI: 8RK3-U9P6-2207-A11P; HC15-EX2V-XQ0C-JF

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Anti-freeze and de-icing products. Cleaning agent.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

E-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements**GB CLP Regulation Signal word:** Warning**Pictograms:
Hazard
statements**

H226

Flammable liquid
and vapour.

Safety Data Sheet

H319 Causes serious eye irritation.

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 2 of 13

Precautionary statements

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Inhalation causes narcotic effects/intoxication. Diminished responsiveness. The product is skin resorptive. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Keep in a cool, well-ventilated place.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64-17-5	ethanol; ethyl alcohol			40 - < 60 %
	200-578-6	603-002-00-5		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
107-21-1	ethanediol; ethylene glycol			5 - < 10 %
	203-473-3	603-027-00-1		
	Acute Tox. 4, STOT RE 2; H302 H373			
78-93-3	butanone; ethyl methyl ketone			0.5 - < 1 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
--------	-------	---------------	----------

Safety Data Sheet

	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	ethanol; ethyl alcohol	40 - < 60 %
	inhalation: LC50 = 95,6 mg/l (vapours); oral: LD50 = 6200 mg/kg		
107-21-1	203-473-3	ethanediol; ethylene glycol	5 - < 10 %
	dermal: LD50 = > 3500 mg/kg; oral: LD50 = 7712 mg/kg		
78-93-3	201-159-0	butanone; ethyl methyl ketone	0.5 - < 1 %
	oral: LD50 = 2193 mg/kg		

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 3 of 13

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Inhalation causes narcotic effects/intoxication.

Move victim to fresh air. Put victim at rest and keep warm. In case of breathing difficulties administer oxygen. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Use skin protection ointment after cleaning. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration!

Rinse mouth immediately and drink plenty of water. Call a physician immediately.

Never give anything by mouth to an unconscious person or a person with cramps.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Safety Data Sheet

5.1. Extinguishing media

Suitable extinguishing media alcohol resistant foam. Extinguishing powder. Atomized water. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO₂). Sulfur oxides. Nitrogen oxides (NO_x). carbon black.

Flammable. Vapours can form explosive mixtures with air. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. When using do not smoke. Wear personal protection equipment. The following must be prevented: Inhalation of vapours or spray/mists. Provide adequate ventilation as well as local exhaustion at critical locations. Avoid contact with skin, eye and clothing.

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 4 of 13

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

Emirates lubricants

Screen Wash -60 °C

Page 5 of
13

Revision date: 17.10.2024

7.1. Precautions for safe handling**Advice on safe handling**

The vapours are heavier than air and can accumulate in high concentrations on the ground, in cavities, channels and cellars. Provide adequate ventilation as well as local exhaust at critical locations. Wear personal protection equipment. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Take precautionary measures against static discharges. Use only antistatically equipped (spark-free) tools.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Pyrophoric or self-heating substances

Further information on storage conditions

Protect from direct sunlight. Store in a cool dry place.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
107-21-1	Ethane-1,2-diol, particulate	-	10		TWA (8 h)	WEL
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
--------	-----------	-----------	-------	---------------	---------------

Safety Data Sheet

78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift
---------	-------------	-------------	-----------	-------	------------

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
64-17-5	ethanol; ethyl alcohol			
Worker DNEL, long-term	inhalation		systemic	380 mg/m ³
Consumer DNEL, long-term	inhalation		systemic	114 mg/m ³
107-21-1	ethanediol; ethylene glycol			
Worker DNEL, long-term	inhalation		local	35 mg/m ³
Worker DNEL, long-term	dermal		systemic	106 mg/kg bw/day
Consumer DNEL, long-term	inhalation		local	7 mg/m ³
Consumer DNEL, long-term	dermal		systemic	53 mg/kg bw/day
78-93-3	butanone; ethyl methyl ketone			
Worker DNEL, long-term	inhalation		systemic	600 mg/m ³
Worker DNEL, acute	inhalation		systemic	900 mg/m ³
Worker DNEL, long-term	dermal		systemic	1161 mg/kg bw/day
Consumer DNEL, long-term	inhalation		systemic	106 mg/m ³
Consumer DNEL, acute	inhalation		systemic	450 mg/m ³
Consumer DNEL, long-term	dermal		systemic	412 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	31 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
64-17-5	ethanol; ethyl alcohol	
Freshwater	0,96 mg/l	
Freshwater (intermittent releases)	2,75 mg/l	
Marine water	0,79 mg/l	
Freshwater sediment	3,6 mg/kg	
Marine sediment	2,9 mg/kg	
Secondary poisoning	380 mg/kg	
Micro-organisms in sewage treatment plants (STP)	580 mg/l	

Safety Data Sheet

Emirates lubricants

Page 6 of
13

Revision date: 17.10.2024

Screen Wash -60 °C

Soil

0,63 mg/kg

Additional advice on limit values

source:

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter against organic vapours (type A). A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	blue
Odour:	fruity

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 7 of 13

Odour threshold: not determined

Test method

Melting point/freezing point: not determined ASTM D 1177

Boiling point or initial boiling point and 100 °C

boiling range: No data
Flammability: available

Lower explosion limits: not determined

Safety Data Sheet

Upper explosion limits:	not determined
Flash point:	> 23 °C DIN EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	No data available
pH-Value (at 20 °C):	8,0 DIN 51369
Water solubility:	easily soluble.
Solubility in other solvents	No data available
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	23 hPa
(at 20 °C)	0,915
Density (at 20 °C):	g/cm ³ DIN 51757
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive	
properties	
not	
Explosive.	
Self-ignition	
temperature	
Solid:	not applicable
Gas:	not applicable

Oxidizing properties
No data available

Other safety characteristics

Evaporation rate:	No data available
Pour point:	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable. No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Strong acid. Oxidising agent, strong.

Safety Data Sheet

10.6. Hazardous decomposition products

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 8 of 13

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO₂). Sulfur oxides. Nitrogen oxides (NO_x). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) 5556 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol; ethyl alcohol				
	oral	LD50 6200 mg/kg	Rat	IUCLID	
	inhalation (4 h) vapour	LC50 95,6 mg/l	Rat	RTECS	
107-21-1	ethanediol; ethylene glycol				
	oral	LD50 7712 mg/kg	Rat	Study report (1968)	according to BASF-internal standards
	dermal	LD50 > 3500 mg/kg	Mouse	Fundamental and Applied Toxicology 27: 1	LD50 derived from developmental toxicity
78-93-3	butanone; ethyl methyl ketone				
	oral	LD50 2193 mg/kg	Rat	REACH Registration Dossier	OECD Guideline 423

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 9 of
13**Aspiration hazard**

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol; ethyl alcohol					
	Acute crustacea toxicity	EC50 9268 - 14221 mg/l	48 h	Daphnia magna	IUCLID	
107-21-1	ethanediol; ethylene glycol					
	Acute fish toxicity	LC50 53000 mg/l	96 h	Pimephales promelas	Publication (1983)	other: ASTM Subcommittee on Safety to Aq
	Acute algae toxicity	ErC50 6500 - 13000 mg/l	96 h	Raphidocelis subcapitata	Study report (1982)	other: EPA 600/9-78-018, 1978
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Fish toxicity	NOEC > 40 mg/l	28 d	Menidia peninsulae	Publication (1985)	other: ASTM E-47.01
	Crustacea toxicity	NOEC 8590 mg/l	7 d	Ceriodaphnia dubia	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	activated sludge, domestic	Chemosphere 14(9), 1239-1251 (1985)	OECD Guideline 209
78-93-3	butanone; ethyl methyl ket one					
	Acute fish toxicity	LC50 2973 mg/l	96 h	Pimephales promelas	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 1220 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 308 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202

Safety Data Sheet

12.2. Persistence and degradabilityNo data available **12.3.****Bioaccumulative potential** No data available**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol; ethyl alcohol	-0,31
107-21-1	ethanediol; ethylene glycol	-1,36
78-93-3	butanone; ethyl methyl ketone	0,3

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting propertiesThis product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria. **12.7. Other adverse effects****Emirates lubricants**

Revision date: 17.10.2024

Screen Wash -60 °C

Page 10 of 13

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 1987

14.2. UN proper shipping name:

ALKOHOLE, N.A.G.

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Special Provisions:

274

Safety Data Sheet

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1987
14.2. UN proper shipping name: ALKOHOLE, N.A.G.
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 274
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S.
14.3. Transport hazard class(es): 3

Revision date: 17.10.2024

Emirates lubricants

Screen Wash -60 °C

Page 11 of 13

14.4. Packing group: III

Hazard label: 3



Special Provisions: 223, 274
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D
Segregation group: alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: III

Safety Data Sheet

Hazard label:

3



Special Provisions:	A3 A180
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable liquids.

14.7. Maritime transport in bulk according to I not applicable **MO instruments**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 59,804 % (554,379 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 59,82 % (554,534 g/l)
P5c FLAMMABLE LIQUIDS

Information according to Directive 2012/18/EU (SEVESO III):

Additional information [Detergents regulation]

To follow: Regulation (EC) No. 648/2004/EC, 1107/2009/EC, 649/2012/

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,5,7,9,15.

Safety Data Sheet

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 12 of
13

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous

Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50

- Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

Emirates lubricants

Revision date: 17.10.2024

Screen Wash -60 °C

Page 13 of 13

Safety Data Sheet

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)