

Safety Data Sheet

Revision date: 15.07.2024

Emirates lubricants

Lube Oil RL 5

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Lube Oil RL 5

UFI: GUNA-F6CS-K20Y-PR6V

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant and additive.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

E-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

Safety Data Sheet

2.1. Classification of the substance or mixture**GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

White mineral oil

Distillates (petroleum), hydrotreated heavy paraffinic

Signal word:

Danger

**Pictograms:****Hazard statements**

H304

May be fatal if swallowed and enters airways.

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 2 of 12

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to a waste disposal system.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Process vapors can irritate airways, skin and eyes.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture of mineral oil raffinates and additives.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
8042-47-5	White mineral oil			80 - < 100 %
	232-455-8		01-2119487078-27	

Safety Data Sheet

	Asp. Tox. 1; H304			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic			10 - < 20 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
128-37-0	2,6-Di-tert-butyl-4-methylphenol			0.1 - < 0.3 %
	204-881-4		01-2119480433-40	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
8042-47-5	232-455-8	White mineral oil	80 - < 100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	10 - < 20 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
128-37-0	204-881-4	2,6-Di-tert-butyl-4-methylphenol	0.1 - < 0.3 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg Aquatic Acute 1; H400: M=1		

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 3 of 12

Safety Data Sheet

rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Coughing. difficulties of breathing.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Atomized water. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Sulfur oxides. Phosphorus oxides. carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

Safety Data Sheet

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 5 of
12

Revision date: 15.07.2024

Lube Oil RL 5

Page 4 of 12

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance
DNEL type	Exposure route
8042-47-5	White mineral oil

Safety Data Sheet

Worker DNEL, long-term		dermal	systemic	217,05 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	164,56 mg/m ³
Consumer DNEL, long-term		dermal	systemic	93,02 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	34,78 mg/m ³
Consumer DNEL, long-term		oral	systemic	25 mg/kg bw/day
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
128-37-0	2,6-Di-tert-butyl-4-methylphenol			
Consumer DNEL, long-term		inhalation	systemic	0,435 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,25 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	0,5 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	1,76 mg/m ³

PNEC values

CAS No	Substance		
Environmental compartment			Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic		
Secondary poisoning			9,33 mg/kg
128-37-0	2,6-Di-tert-butyl-4-methylphenol		
Freshwater			0,000199 mg/l
Freshwater (intermittent releases)			0,00199 mg/l
Marine water			0,00002 mg/l
Freshwater sediment			0,458 mg/kg
Marine sediment			0,046 mg/kg
Secondary poisoning			16,67 mg/kg

Safety Data Sheet

Micro-organisms in sewage treatment plants (STP)	0,017 mg/l
Soil	0,054 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 6 of 12

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	yellow
Odour:	like: mineral oil.
Odour threshold:	not determined

Melting point/freezing point:	Test method
	No data available

Safety Data Sheet

Boiling point or initial boiling point and	not determined
boiling range:	
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	128 °C DIN 22719
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic: (at 40 °C)	5,0 mm²/s ASTM D 7042

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 7 of 12

Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,830 g/cm³ DIN 51757
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Self-ignition temperature	
Solid:	No data available
Gas:	No data available

Oxidizing properties	
No data available	

Other safety characteristics

Evaporation rate:	No data available
Pour point:	-48 °C ASTM D 7346

SECTION 10: Stability and reactivity

Safety Data Sheet

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Sulfur oxides. Phosphorus oxides. carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 8 of
12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
8042-47-5	White mineral oil				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
128-37-0	2,6-Di-tert-butyl-4-methyl phenol				
	oral	LD50 > 6000 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Evaluation: no danger of sensitization.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 9 of
12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
8042-47-5	White mineral oil					
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Leuciscus idus melanotus	Study report (1992) OECD Guideline 203
	Acute crustacea toxicity	EL50 mg/l	> 100	48 h	Daphnia magna	Study report (2008) OECD Guideline 202
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h		
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010) The aquatic toxicity was estimated by a
128-37-0	2,6-Di-tert-butyl-4-methylphenol					
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACH Registration Dossier OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l ()	> 10000	3 h	Activated sludge	Study report (2000) OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
128-37-0	2,6-Di-tert-butyl-4-methylphenol	5,03

Safety Data Sheet

BCF

CAS No	Chemical name	BCF	Species	Source
128-37-0	2,6-Di-tert-butyl-4-methylphenol	465	Fish	REACH Registration D

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 10 of 12

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Marine transport (IMDG)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Safety Data Sheet

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 11 of 12

Air transport (ICAO-TI/IATA-DGR)

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,12.

Abbreviations and acronyms

Asp. Tox: Aspiration hazard

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -

European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM

- American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -

Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -

Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -

European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air

Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation

Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO

- International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50

- Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the

Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise

Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;

Safety Data Sheet

NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Emirates lubricants

Revision date: 15.07.2024

Lube Oil RL 5

Page 12 of
12

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)