

Safety Data Sheet

Revision date: 02.08.2023

Emirates lubricants

Wear Protect RS 2 MO

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Wear Protect RS 2 MO

UFI: DRF2-12UV-M20Q-VQXA

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant and additive.

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

1.4. Emergency telephone number: +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification**

Safety Data Sheet

2.1. Classification of the substance or mixture

GB CLP Regulation

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts

Sulfonic acids, petroleum, calcium salts

Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts C14-16-18 Alkyl phenol

Signal word:

Warning



Pictograms:

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 2 of 16

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container to industrial incineration plant.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts			5 - < 10 %
	271-529-4			

Safety Data Sheet

	Skin Sens. 1B; H317			
61789-86-4	Sulfonic acids, petroleum, calcium salts			<3 %
	263-093-9		01-2119488992-18	
	Skin Sens. 1B; H317			
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts			1 - < 2.5 %
	274-263-7		01-2119492616-28	
	Skin Sens. 1B; H317			
1335202-81-7	Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt			1 - < 2.5 %
	932-231-6		01-2119560592-37	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H315 H318 H412			
68411-46-1	alkylated diphenylamine			0.5 - < 1 %
	270-128-1		01-2119491299-23	
	Repr. 2, Aquatic Chronic 3; H361f H412			
1190625-94-5	C14-16-18 Alkyl phenol			0.1 - < 0.3 %
	931-468-2		01-2119498288-1	
	Skin Sens. 1B, STOT RE 2; H317 H373			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68584-23-6	271-529-4	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	5 - < 10 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		
61789-86-4	263-093-9	Sulfonic acids, petroleum, calcium salts	<3 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 16000 mg/kg Skin Sens. 1B; H317: >= 10 - 100		
70024-69-0	274-263-7	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	1 - < 2.5 %
	dermal: LD50 = > 4000 mg/kg; oral: LD50 = > 16000 mg/kg		
1335202-81-7	932-231-6	Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt	1 - < 2.5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4445 mg/kg		
68411-46-1	270-128-1	alkylated diphenylamine	0.5 - < 1 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
1190625-94-5	931-468-2	C14-16-18 Alkyl phenol	0.1 - < 0.3 %

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 3 of 16

	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
--	--	--

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Provide fresh air. In case of persistent complaints seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). ABC-powder Foam. Water spray.

Co-ordinate fire-fighting measures to the fire surroundings.

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 4 of 16

Safety Data Sheet

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Take up mechanically. Dispose of waste according to applicable legislation. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet

7.1. Precautions for safe handling

Advice on safe handling

Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 5 of 16

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 7 of 19

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day
61789-86-4	Sulfonic acids, petroleum, calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm ²
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts			
Worker DNEL, long-term		inhalation	systemic	11,75 mg/m ³
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day
Worker DNEL, long-term		dermal	local	1,03 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m ³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DNEL, long-term		dermal	local	0,513 mg/cm ²

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 8 of 19

Consumer DNEL, long-term	oral	systemic	0,833 mg/kg bw/day
1335202-81-7	Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt		
Worker DNEL, long-term	dermal	systemic	1,7 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	85 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	89 mg/kg bw/day
68411-46-1	alkylated diphenylamine		
Worker DNEL, long-term	inhalation	systemic	0,6 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,08 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,14 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,04 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,04 mg/kg bw/day
1190625-94-5	C14-16-18 Alkyl phenol		
Worker DNEL, long-term	inhalation	systemic	1,17 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 9 of 19

PNEC values

CAS No	Substance	
Environmental compartment		Value
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg
61789-86-4	Sulfonic acids, petroleum, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	
Freshwater		1 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		226000000 mg/kg
Marine sediment		226000000 mg/kg
Secondary poisoning		16,667 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		271000000 mg/kg

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 10 of 19

1335202-81-7	Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt
Freshwater	0,023 mg/l
Freshwater (intermittent releases)	0,01 mg/l
Marine water	0,002 mg/l
Freshwater sediment	0,174 mg/kg
Marine sediment	0,017 mg/kg
Micro-organisms in sewage treatment plants (STP)	3 mg/l
Soil	0,62 mg/kg
68411-46-1	alkylated diphenylamine
Freshwater	0,034 mg/l
Freshwater (intermittent releases)	0,51 mg/l
Marine water	0,003 mg/l
Freshwater sediment	0,446 mg/kg
Marine sediment	0,045 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	1,76 mg/kg
1190625-94-5	C14-16-18 Alkyl phenol
Freshwater	0,1 mg/l
Freshwater (intermittent releases)	1 mg/l
Marine water	0,01 mg/l
Freshwater sediment	4266,16 mg/kg
Marine sediment	426,62 mg/kg
Secondary poisoning	3,3 mg/kg
Micro-organisms in sewage treatment plants (STP)	100 mg/l
Soil	852,58 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³STEL: 10 mg/m³

Does not contain substances above concentration limits fixing an occupational exposure limit.

8.2. Exposure controls

Safety Data Sheet**Emirates lubricants**

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 11 of 19

**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.2 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 10 of 16

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	solid:
Colour:	grey - black
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	220 mm ² /s DIN 51562 - Base oil
Water solubility:	insoluble
Solubility in other solvents	No data available
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 20 °C):	0,9 g/cm ³ DIN 51757
Relative vapour density:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Self-ignition temperature	
Solid:	No data available
Gas:	No data available

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 13 of 19

Oxidizing properties

No data available

Other safety characteristics

Pour point:

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂). carbon black. No known hazardous decomposition products.**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
61789-86-4	Sulfonic acids, petroleum calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1981)	OECD Guideline 402
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts				
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40

Safety Data Sheet

	dermal	LD50 mg/kg	> 4000	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal
1335202-81-7	Benzenesulfonic acid, C10-13-alkyl derivatives, calcium salt					
	oral	LD50 mg/kg	4445	Rat	Study report	other: W.S. Spector, Handbook of Toxicol
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1986)	OECD Guideline 402
68411-46-1	alkylated diphenylamine					
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1988)	OECD Guideline 402
1190625-94-5	C14-16-18 Alkyl phenol					
	oral	LD50 mg/kg	> 2000	Rat	Study report (2014)	OECD Guideline 423
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2015)	OECD Guideline 402

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 12 of 16

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 15 of 19

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68584-23-6	Benzenesulfonic acid, C1 -16-alkyl derivs., calcium salts					
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Raphidocelis subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute bacteria toxicity	(EC50 > 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)	OECD Guideline 209
61789-86-4	Sulfonic acids, petroleum, calcium salts					
	Acute fish toxicity	LL50 > 10000 mg/l	96 h	Cyprinodon variegatus	Study report (1986)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1994)	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1993)	EPA OTS 797.1300
	Acute bacteria toxicity	(EC50 > 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	Study report (1994)	OECD Guideline 209
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts					
	Acute fish toxicity	LL50 > 10000 mg/l	96 h	Cyprinodon variegatus	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	EPA OTS 797.1050
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EPA OTS 797.1300
	Acute bacteria toxicity	(EC50 > 10000 mg/l)	3 h	activated sludge of a predominantly domestic sewage	REACH Registration Dossier	OECD Guideline 209
1335202-81-7	Benzenesulfonic acid, C1 -13-alkyl derivs., calcium salt					
	Acute fish toxicity	LC50 1,67 mg/l	96 h	Lepomis macrochirus	REACH Registration Dossier	other: US EPA, 1975. Reliability, deviated
	Acute algae toxicity	ErC50 29 mg/l	96 h	Pseudokirchneriella subcapitata	Water Res. 16: 675-680. (1986)	other: ASTM 1984
	Acute crustacea toxicity	EC50 2,9 mg/l	48 h	Daphnia magna	Other company data (1990)	OECD Guideline 202
	Fish toxicity	NOEC 0,23 mg/l	72 d	Oncorhynchus mykiss	Study report (2010)	Fertilized eggs of Salmo gairdneri were

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 14 of
16

	Crustacea toxicity	NOEC mg/l	1,18	21 d	Daphnia magna	Publication (1979)	A modified 0.5-L proportional diluter wa
68411-46-1	alkylated diphenylamine						
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Danio rerio	Study report (1988)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EC50	51 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	> 4,46
61789-86-4	Sulfonic acids, petroleum, calcium salts	> 4,46
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	18,05
1335202-81-7	Benzenesulfonic acid, C10-13-alkyl derivs., calcium salt	2,89
68411-46-1	alkylated diphenylamine	6,66
1190625-94-5	C14-16-18 Alkyl phenol	> 16000000

BCF

CAS No	Chemical name	BCF	Species	Source
68411-46-1	alkylated diphenylamine	411	Cyprinus carpio	Study report (2000)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

Safety Data Sheet**Emirates lubricants**

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 17 of 19

List of Wastes Code - residues/unused products

120112 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS; wastes from shaping and physical and mechanical surface treatment of metals and plastics; spent waxes and fats; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

Inland waterways transport (ADN)

14.1. UN number or ID number: -

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 15 of 16

14.2. UN proper shipping name: -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental
regula****tions/legislation specific for the substance or mixture****National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,7,8,9,10,12,16.

Abbreviations and acronyms

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -

Safety Data Sheet

Emirates lubricants

Revision date: 02.08.2023

Wear Protect RS 2 MO

Page 16 of
16

Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure. H412
	Harmful to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)