

# Safety Data Sheet

**Emirates lubricants**

Revision date: 04.01.2024

Belt Lube HT 100

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Belt Lube HT 100

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant and additive.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

|                         |                                            |                  |
|-------------------------|--------------------------------------------|------------------|
| Company name:           | Emirates lubricants                        |                  |
| Street:                 | Ras Al khaimah                             |                  |
| Place:                  | United Arab Emirates                       |                  |
| Telephone:              | +971 55 105 2851                           | +971 52 660 6888 |
| e-mail:                 | info@emirateslubricant.                    |                  |
| Contact person:         | Application Technology                     |                  |
| Internet:               | www.emirateslubricant.com                  |                  |
| Responsible Department: | Emirates lubricants Application Technology |                  |

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements****GB CLP Regulation Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

|      |                                                           |
|------|-----------------------------------------------------------|
| P273 | Avoid release to the environment.                         |
| P501 | Dispose of contents/container to a waste disposal system. |

**Additional advice on labelling**

The product is classified and labelled according to EC directives or corresponding national laws.

## Safety Data Sheet

### 2.3. Other hazards

#### Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 2 of 11

The mixture contains the following substances fulfilling the PBT criteria : alkylated diphenylamine.  
 Prolonged/repetitive skin contact may cause skin defatting or dermatitis.  
 Spilled product must not leak into the ground.  
 Do not allow uncontrolled leakage of product into the environment.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of synthetic base components and additives.

##### Hazardous components

| CAS No     | Chemical name                                                                                                                                |          |                  | Quantity      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------|----------|------------------|---------------|
|            | EC No                                                                                                                                        | Index No | REACH No         |               |
|            | Classification (GB CLP Regulation)                                                                                                           |          |                  |               |
| 68411-46-1 | alkylated diphenylamine                                                                                                                      |          |                  | 0.3 - < 0.5 % |
|            | 270-128-1                                                                                                                                    |          | 01-2119491299-23 |               |
|            | Repr. 2; H361f                                                                                                                               |          |                  |               |
| 1330-78-5  | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate |          |                  | 0.1 - < 0.3 % |
|            | 809-930-9                                                                                                                                    |          | 01-2119531335-46 |               |
|            | Repr. 2, Aquatic Acute 1, Aquatic Chronic 1; H361f H400 H410                                                                                 |          |                  |               |

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

| CAS No     | EC No                                                                                 | Chemical name                                                                                                                                | Quantity      |
|------------|---------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|---------------|
|            | Specific Conc. Limits, M-factors and ATE                                              |                                                                                                                                              |               |
| 68411-46-1 | 270-128-1                                                                             | alkylated diphenylamine                                                                                                                      | 0.3 - < 0.5 % |
|            | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg                                |                                                                                                                                              |               |
| 1330-78-5  | 809-930-9                                                                             | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate | 0.1 - < 0.3 % |
|            | oral: LD50 = > 20000 mg/kg Aquatic Acute 1; H400: M=1<br>Aquatic Chronic 1; H410: M=1 |                                                                                                                                              |               |

##### Further Information

This mixture does not contain any substances which either present a health or environmental hazard according to Regulation (EC) No. 1272/2008 or have an occupational exposure limit assigned.

DMSO-Extrakt < 3 %, IP 346.

## Safety Data Sheet

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### **After inhalation**

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

##### **After contact with skin**

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In

### Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 3 of 11

case of skin irritation, seek medical treatment. Change contaminated clothing.

##### **After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

##### **After ingestion**

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

##### **Unsuitable extinguishing media**

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Nitrogen oxides (NO<sub>x</sub>). Phosphorus oxides. carbon black.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

##### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### SECTION 6: Accidental release measures

## Safety Data Sheet

### Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 4 of 11

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **6.3. Methods and material for containment and cleaning up**

##### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

#### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

##### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Provide adequate ventilation as well as local exhaust at critical locations. Keep/Store only in original container.

##### **Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

##### **Further information on storage conditions**

Protect against: UV-radiation/sunlight. frost. heat.

Recommended storage temperature: 5 - 40°C

#### **7.3. Specific end use(s)**

Further information: see technical data sheet.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

## Safety Data Sheet

### DNEL/DMEL values

| CAS No                   | Substance                                                                                                                                    |                |          |                        |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|----------------|----------|------------------------|
| DNEL type                |                                                                                                                                              | Exposure route | Effect   | Value                  |
| 68411-46-1               | alkylated diphenylamine                                                                                                                      |                |          |                        |
| Worker DNEL, long-term   |                                                                                                                                              | inhalation     | systemic | 0,6 mg/m <sup>3</sup>  |
| Worker DNEL, long-term   |                                                                                                                                              | dermal         | systemic | 0,08 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                                                                                              | inhalation     | systemic | 0,14 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                                                                                                                              | dermal         | systemic | 0,04 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                                                                                              | oral           | systemic | 0,04 mg/kg bw/day      |
| 1330-78-5                | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate |                |          |                        |
| Worker DNEL, long-term   |                                                                                                                                              | inhalation     | systemic | 0,18 mg/m <sup>3</sup> |
| Worker DNEL, long-term   |                                                                                                                                              | dermal         | systemic | 0,41 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                                                                                              | inhalation     | systemic | 0,03 mg/m <sup>3</sup> |
| Consumer DNEL, long-term |                                                                                                                                              | dermal         | systemic | 0,15 mg/kg bw/day      |
| Consumer DNEL, long-term |                                                                                                                                              | oral           | systemic | 0,02 mg/kg bw/day      |

### PNEC values

| CAS No                                           | Substance                                                                                                                                    |  |  |             |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|--|--|-------------|
| Environmental compartment                        |                                                                                                                                              |  |  | Value       |
| 68411-46-1                                       | alkylated diphenylamine                                                                                                                      |  |  |             |
| Freshwater                                       |                                                                                                                                              |  |  | 0,034 mg/l  |
| Freshwater (intermittent releases)               |                                                                                                                                              |  |  | 0,51 mg/l   |
| Marine water                                     |                                                                                                                                              |  |  | 0,003 mg/l  |
| Freshwater sediment                              |                                                                                                                                              |  |  | 0,446 mg/kg |
| Marine sediment                                  |                                                                                                                                              |  |  | 0,045 mg/kg |
| Micro-organisms in sewage treatment plants (STP) |                                                                                                                                              |  |  | 10 mg/l     |
| Soil                                             |                                                                                                                                              |  |  | 1,76 mg/kg  |
| 1330-78-5                                        | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate |  |  |             |
| Freshwater                                       |                                                                                                                                              |  |  | 0,001 mg/l  |
| Freshwater (intermittent releases)               |                                                                                                                                              |  |  | 0,001 mg/l  |

## Safety Data Sheet

## Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 5 of 11

|                                                  |             |
|--------------------------------------------------|-------------|
| Marine water                                     | 0 mg/l      |
| Freshwater sediment                              | 2,05 mg/kg  |
| Marine sediment                                  | 0,205 mg/kg |
| Secondary poisoning                              | 0,65 mg/kg  |
| Micro-organisms in sewage treatment plants (STP) | 100 mg/l    |
| Soil                                             | 1,01 mg/kg  |

**Additional advice on limit values**

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Individual protection measures, such as personal protective equipment Eye/face protection**

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

**Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

## Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 6 of 11

## Safety Data Sheet

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                           |                         |                    |
|-----------------------------------------------------------|-------------------------|--------------------|
| Physical state:                                           | liquid                  |                    |
| Colour:                                                   | yellow - brown          |                    |
| Odour:                                                    | characteristic          |                    |
| Odour threshold:                                          | not determined          |                    |
|                                                           |                         | <b>Test method</b> |
| Melting point/freezing point:                             | No data available       |                    |
| Boiling point or initial boiling point and boiling range: | No data available       |                    |
| Flammability:                                             | No data available       |                    |
| Lower explosion limits:                                   | No data available       |                    |
| Upper explosion limits:                                   | No data available       |                    |
| Flash point:                                              | 280 °C                  | DIN EN ISO 2592    |
| Auto-ignition temperature:                                | No data available       |                    |
| Decomposition temperature:                                | No data available       |                    |
| pH-Value:                                                 | not applicable          |                    |
| Viscosity / kinematic:<br>(at 40 °C)                      | 108 mm <sup>2</sup> /s  | ASTM D 7042        |
| Water solubility:                                         | virtually insoluble     |                    |
| Solubility in other solvents                              |                         |                    |
| No data available                                         |                         |                    |
| Partition coefficient n-octanol/water:                    | No data available       |                    |
| Vapour pressure:                                          | No data available       |                    |
| Density (at 15 °C):                                       | 0,930 g/cm <sup>3</sup> | DIN 51757          |
| Relative vapour density:                                  | No data available       |                    |

## Safety Data Sheet

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

#### Other safety characteristics

Evaporation rate:

No data available

Pour point:

-27 °C ASTM D 7346

### SECTION 10: Stability and reactivity

#### Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 7 of 11

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

#### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### 10.5. Incompatible materials

Reacts with: Oxidising agent, strong Acid.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Nitrogen oxides (NO<sub>x</sub>). Phosphorus oxides. carbon black.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

##### Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

| CAS No     | Chemical name                                                                                              |                   |         |                     |                    |
|------------|------------------------------------------------------------------------------------------------------------|-------------------|---------|---------------------|--------------------|
|            | Exposure route                                                                                             | Dose              | Species | Source              | Method             |
| 68411-46-1 | alkylated diphenylamine                                                                                    |                   |         |                     |                    |
|            | oral                                                                                                       | LD50 > 5000 mg/kg | Rat     | Study report (1982) | OECD Guideline 401 |
|            | dermal                                                                                                     | LD50 > 2000 mg/kg | Rat     | Study report (1988) | OECD Guideline 402 |
| 1330-78-5  | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate |                   |         |                     |                    |



## Safety Data Sheet

## Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 8 of 11

|  |                                   |               |         |     |                                                                           |
|--|-----------------------------------|---------------|---------|-----|---------------------------------------------------------------------------|
|  | and tris(3-methylphenyl)phosphate |               |         |     |                                                                           |
|  | oral                              | LD50<br>mg/kg | > 20000 | Rat | Study report (1976)<br><br>other: Standard<br>Federal Hazardous<br>Substa |

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

Mixture not tested.

| CAS No     | Chemical name                                                                                                                                |               |           |         |                                  |                                                                                      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|---------|----------------------------------|--------------------------------------------------------------------------------------|
|            | Aquatic toxicity                                                                                                                             | Dose          | [h]   [d] | Species | Source                           | Method                                                                               |
| 68411-46-1 | alkylated diphenylamine                                                                                                                      |               |           |         |                                  |                                                                                      |
|            | Acute fish toxicity                                                                                                                          | LC50<br>mg/l  | > 100     | 96 h    | Danio rerio                      | Study report (1988)<br>OECD Guideline 203                                            |
|            | Acute algae toxicity                                                                                                                         | ErC50<br>mg/l | > 100     | 72 h    | Desmodesmus subspicatus          | Study report (2006)<br>OECD Guideline 201                                            |
|            | Acute crustacea toxicity                                                                                                                     | EC50<br>mg/l  | 51        | 48 h    | Daphnia magna                    | Study report (2004)<br>OECD Guideline 202                                            |
| 1330-78-5  | Reaction mass of 3-Methylphenyl di-3-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate |               |           |         |                                  |                                                                                      |
|            | Acute fish toxicity                                                                                                                          | LC50<br>mg/l  | 0,6       | 96 h    | rainbow trout and fathead minnow | Study report (1979)<br>Five nominal concentrations of sample; a                      |
|            | Acute crustacea toxicity                                                                                                                     | EC50<br>mg/l  | 0,146     | 48 h    | Daphnia magna                    | Study report (2005)<br>OECD Guideline 202                                            |
|            | Fish toxicity                                                                                                                                | NOEC<br>mg/l  | 0,01      | 28 d    | Jordanella floridae              | Rijksinstituut voor Volksgezondheid en M<br>Test was carried out based on the nation |

## Safety Data Sheet

|  |                         |                    |      |                            |                                          |                    |
|--|-------------------------|--------------------|------|----------------------------|------------------------------------------|--------------------|
|  | Crustacea toxicity      | NOEC 0,1 mg/l      | 21 d | Daphnia magna              | Rijksinstituut voor Volksgezondheid en M | other: NEN 6502    |
|  | Acute bacteria toxicity | (EC50 > 1000 mg/l) | 3 h  | activated sludge, domestic | Study report (2010)                      | OECD Guideline 209 |

### **12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

### **12.3. Bioaccumulative potential**

No data available

### **Partition coefficient n-octanol/water**

| CAS No     | Chemical name                                                                                                                                | Log Pow    |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------|------------|
| 68411-46-1 | alkylated diphenylamine                                                                                                                      | 6,66       |
| 1330-78-5  | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate | ca. 860000 |

### **BCF**

| CAS No     | Chemical name                                                                                                                                | BCF | Species               | Source              |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------|-----|-----------------------|---------------------|
| 68411-46-1 | alkylated diphenylamine                                                                                                                      | 411 | Cyprinus carpio       | Study report (2000) |
| 1330-78-5  | Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate | 77  | Not applicable - QSAR | QSAR                |

### **12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste

## Safety Data Sheet

### Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 9 of 11

water treatment plants.

#### **12.5. Results of PBT and vPvB assessment**

The mixture contains the following substances fulfilling the PBT criteria according to UK REACH: alkylated diphenylamine.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

No data available

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

##### **List of Wastes Code - residues/unused products**

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

##### **Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

#### **Inland waterways transport (ADN)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

#### **Marine transport (IMDG)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

## Safety Data Sheet

**Emirates lubricants**

Revision date: 04.01.2024

Belt Lube HT 100

Page 10 of 11

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

No dangerous good in sense of these transport regulations.

**SECTION 15: Regulatory information****14.4. Packing group:**

-

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:**

-

**14.2. UN proper shipping name:**

-

**14.3. Transport hazard class(es):**

-

**14.4. Packing group:**

-

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 5,7,8,9,10,12,15,16.

**Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50

## Safety Data Sheet

- Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s.; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Classification for mixtures and used evaluation method according to GB CLP Regulation

|                         |                          |
|-------------------------|--------------------------|
| Classification          | Classification procedure |
| Aquatic Chronic 3; H412 | Calculation method       |

### Relevant H and EUH statements (number and full text)

H361f Suspected of damaging fertility. H400  
Very toxic to aquatic life.

### Emirates lubricants

Revision date: 04.01.2024

Belt Lube HT 100

Page 11 of 11

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

### Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*