

# Safety Data Sheet

**Emirates lubricants**

Revision date: 09.02.2022

Guideway Oil XG 68

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Guideway Oil XG 68

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Lubricant and additive.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Emirates lubricants

Street: Ras Al khaimah

Place: United Arab Emirates

Telephone: +971 55 105 2851 +971 52 660 6888

e-mail: info@emirateslubricant.

Contact person: Application Technology

Internet: www.emirateslubricant.com

Responsible Department: Emirates lubricants Application Technology

**1.4. Emergency telephone number:** +971 52 660 6888 - This number is serviced during office hours.**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements****GB CLP Regulation Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P273 Avoid release to the environment.

P501 Dispose of contents/container to industrial incineration plant.

**Additional advice on labelling**

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

## Safety Data Sheet

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 2 of  
13

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

## Hazardous components

| CAS No       | Chemical name                                                                                                                                           |          |                  | Quantity      |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|----------|------------------|---------------|
|              | EC No                                                                                                                                                   | Index No | REACH No         |               |
|              | Classification (GB CLP Regulation)                                                                                                                      |          |                  |               |
| 64742-54-7   | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified                                                                           |          |                  | 60 - < 80 %   |
|              | 265-157-1                                                                                                                                               |          | 01-2119484627-25 |               |
|              | Asp. Tox. 1; H304                                                                                                                                       |          |                  |               |
| 1213789-63-9 | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines                                                                  |          |                  | 0.1 - < 0.3 % |
|              | 627-034-4                                                                                                                                               |          | 01-2119473797-19 |               |
|              | Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410 |          |                  |               |
| 104-76-7     | 2-Ethylhexan-1-ol                                                                                                                                       |          |                  | < 0.1 %       |
|              | 203-234-3                                                                                                                                               |          |                  |               |
|              | Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H332 H315 H319 H335                                                                               |          |                  |               |

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

| CAS No       | EC No                                                                                                         | Chemical name                                                                          | Quantity      |
|--------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------|
|              | Specific Conc. Limits, M-factors and ATE                                                                      |                                                                                        |               |
| 64742-54-7   | 265-157-1                                                                                                     | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified          | 60 - < 80 %   |
|              | dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg                                                        |                                                                                        |               |
| 1213789-63-9 | 627-034-4                                                                                                     | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines | 0.1 - < 0.3 % |
|              | dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1689 mg/kg M acute; H400: M=10<br>M chron.; H410: M=10              |                                                                                        |               |
| 104-76-7     | 203-234-3                                                                                                     | 2-Ethylhexan-1-ol                                                                      | < 0.1 %       |
|              | inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = ca. 2047 mg/kg |                                                                                        |               |

## Further Information

DMSO-Extrakt &lt; 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## Safety Data Sheet

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

##### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

##### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

##### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

### Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 3 of 13

apart. Subsequently consult an ophthalmologist.

##### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water. Sand.

##### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. Phosphorus oxides. carbon black.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

##### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### SECTION 6: Accidental release measures

## Safety Data Sheet

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

#### **Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered,

## **Emirates lubricants**

Revision date: 09.02.2022

Guideway Oil XG 68

Page 4 of 13

arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

#### **Advice on general occupational hygiene**

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### **Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

#### **Further information on storage conditions**

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

### **7.3. Specific end use(s)**

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

## Safety Data Sheet

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 5 of  
13

## Exposure limits (EH40)

| CAS No   | Substance         | ppm | mg/m <sup>3</sup> | fibres/ml | Category  | Origin |
|----------|-------------------|-----|-------------------|-----------|-----------|--------|
| 104-76-7 | 2-ethylhexan-1-ol | 1   | 5.4               |           | TWA (8 h) | WEL    |

## DNEL/DMEL values

| CAS No                   | Substance                                                                              |          |                         |  |
|--------------------------|----------------------------------------------------------------------------------------|----------|-------------------------|--|
| DNEL type                | Exposure route                                                                         | Effect   | Value                   |  |
| 64742-54-7               | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified          |          |                         |  |
| Worker DNEL, long-term   | inhalation                                                                             | systemic | 2,73 mg/m <sup>3</sup>  |  |
| Worker DNEL, long-term   | inhalation                                                                             | local    | 5,58 mg/m <sup>3</sup>  |  |
| Worker DNEL, long-term   | dermal                                                                                 | systemic | 0,97 mg/kg bw/day       |  |
| Consumer DNEL, long-term | inhalation                                                                             | local    | 1,19 mg/m <sup>3</sup>  |  |
| Consumer DNEL, long-term | oral                                                                                   | systemic | 0,74 mg/kg bw/day       |  |
| 1213789-63-9             | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines |          |                         |  |
| Worker DNEL, long-term   | inhalation                                                                             | systemic | 0,38 mg/m <sup>3</sup>  |  |
| Worker DNEL, long-term   | inhalation                                                                             | local    | 1 mg/m <sup>3</sup>     |  |
| Worker DNEL, acute       | inhalation                                                                             | local    | 1 mg/m <sup>3</sup>     |  |
| Consumer DNEL, long-term | inhalation                                                                             | systemic | 0,035 mg/m <sup>3</sup> |  |
| Consumer DNEL, long-term | oral                                                                                   | systemic | 0,04 mg/kg bw/day       |  |
| 104-76-7                 | 2-Ethylhexan-1-ol                                                                      |          |                         |  |
| Worker DNEL, long-term   | inhalation                                                                             | systemic | 12,8 mg/m <sup>3</sup>  |  |
| Worker DNEL, long-term   | inhalation                                                                             | local    | 53,2 mg/m <sup>3</sup>  |  |
| Worker DNEL, acute       | inhalation                                                                             | local    | 53,2 mg/m <sup>3</sup>  |  |
| Worker DNEL, long-term   | dermal                                                                                 | systemic | 23 mg/kg bw/day         |  |
| Consumer DNEL, long-term | inhalation                                                                             | systemic | 2,3 mg/m <sup>3</sup>   |  |
| Consumer DNEL, long-term | inhalation                                                                             | local    | 26,6 mg/m <sup>3</sup>  |  |
| Consumer DNEL, acute     | inhalation                                                                             | local    | 26,6 mg/m <sup>3</sup>  |  |
| Consumer DNEL, long-term | dermal                                                                                 | systemic | 11,4 mg/kg bw/day       |  |

## Safety Data Sheet

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 6 of  
13

|                          |      |          |                  |
|--------------------------|------|----------|------------------|
| Consumer DNEL, long-term | oral | systemic | 1,1 mg/kg bw/day |
|--------------------------|------|----------|------------------|

**PNEC values**

| CAS No                                           | Substance                                                                              |
|--------------------------------------------------|----------------------------------------------------------------------------------------|
| Environmental compartment                        | Value                                                                                  |
| 64742-54-7                                       | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified          |
| Secondary poisoning                              | 9,33 mg/kg                                                                             |
| 1213789-63-9                                     | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines |
| Freshwater                                       | 0,00026 mg/l                                                                           |
| Freshwater (intermittent releases)               | 0,0016 mg/l                                                                            |
| Marine water                                     | 0,000026 mg/l                                                                          |
| Freshwater sediment                              | 3,76 mg/kg                                                                             |
| Marine sediment                                  | 0,376 mg/kg                                                                            |
| Micro-organisms in sewage treatment plants (STP) | 0,55 mg/l                                                                              |
| Soil                                             | 10 mg/kg                                                                               |
| 104-76-7                                         | 2-Ethylhexan-1-ol                                                                      |
| Freshwater                                       | 0,017 mg/l                                                                             |
| Freshwater (intermittent releases)               | 0,17 mg/l                                                                              |
| Marine water                                     | 0,002 mg/l                                                                             |
| Freshwater sediment                              | 0,284 mg/kg                                                                            |
| Marine sediment                                  | 0,028 mg/kg                                                                            |
| Secondary poisoning                              | 55 mg/kg                                                                               |
| Micro-organisms in sewage treatment plants (STP) | 10 mg/l                                                                                |
| Soil                                             | 0,047 mg/kg                                                                            |

**Additional advice on limit values**

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

**8.2. Exposure controls**

## Safety Data Sheet



### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

### Individual protection measures, such as personal protective equipment Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480

min Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 7 of 13

Suitable material: NBR (Nitrile rubber).

Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                 |                    |
|-----------------|--------------------|
| Physical state: | liquid             |
| Colour:         | brown              |
| Odour:          | like: mineral oil. |

### Test method

#### Changes in the physical state

Melting point/freezing point:

No data available

Boiling point or initial boiling point and

not determined

boiling range:

Pour point:

-26 °C ASTM D 7346

Flash point:

257 °C DIN EN ISO 2592

#### Flammability

Solid/liquid:

No data available

Gas:

No data available

## Safety Data Sheet

### Explosive properties

No data available

Lower explosion limits:

No data available

Upper explosion limits:

No data available

Auto-ignition temperature:

not determined

### Self-ignition temperature

Solid:

No data available

Gas:

No data available

Decomposition temperature:

No data available

pH-Value:

No data available

Viscosity / kinematic:  
(at 40 °C)

68,4 mm<sup>2</sup>/s ASTM D 7042

Water solubility:

virtually insoluble

### Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 15 °C):

0,874 g/cm<sup>3</sup> DIN 51757

Relative vapour density:

No data available

### 9.2. Other information

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 8 of 13

### Information with regard to physical hazard classes

Oxidizing properties

No data available

### Other safety characteristics

Evaporation rate:

No data available

### Further Information

No data available

## SECTION 10: Stability and reactivity

## Safety Data Sheet

---

### **10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

### **10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature. **10.3. Possibility of hazardous reactions** No known hazardous reactions.

### **10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

### **10.5. Incompatible materials**

No data available

### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Sulfur oxides. Phosphorus oxides. carbon black.

## **SECTION 11: Toxicological information**

### **11.1. Information on hazard classes as defined in GB CLP Regulation**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

## Safety Data Sheet

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 9 of  
13

| CAS No       | Chemical name                                                                          |                     |         |                     |                    |
|--------------|----------------------------------------------------------------------------------------|---------------------|---------|---------------------|--------------------|
|              | Exposure route                                                                         | Dose                | Species | Source              | Method             |
| 64742-54-7   | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified          |                     |         |                     |                    |
|              | oral                                                                                   | LD50 > 5000 mg/kg   | Rat     | Study report (1982) | OECD Guideline 401 |
|              | dermal                                                                                 | LD50 > 5000 mg/kg   | Rabbit  | Study report (1982) | OECD Guideline 402 |
| 1213789-63-9 | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines |                     |         |                     |                    |
|              | oral                                                                                   | LD50 1689 mg/kg     | Rat     | Study report (1993) | OECD Guideline 401 |
|              | dermal                                                                                 | LD50 > 2000 mg/kg   | Rat     | Study report (1985) | OECD Guideline 402 |
| 104-76-7     | 2-Ethylhexan-1-ol                                                                      |                     |         |                     |                    |
|              | oral                                                                                   | LD50 ca. 2047 mg/kg | Rat     | Publication (1969)  | OECD Guideline 401 |
|              | inhalation vapour                                                                      | ATE 11 mg/l         |         |                     |                    |
|              | inhalation dust/mist                                                                   | ATE 1,5 mg/l        |         |                     |                    |

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

not applicable

**SECTION 12: Ecological information****12.1. Toxicity** No data

available Mixture

not tested.

## Safety Data Sheet

## Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 10 of 13

| CAS No       | Chemical name                                                                          |                   |           |                                                     |                                   |                                         |
|--------------|----------------------------------------------------------------------------------------|-------------------|-----------|-----------------------------------------------------|-----------------------------------|-----------------------------------------|
|              | Aquatic toxicity                                                                       | Dose              | [h]   [d] | Species                                             | Source                            | Method                                  |
| 64742-54-7   | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified          |                   |           |                                                     |                                   |                                         |
|              | Acute fish toxicity                                                                    | LL50 > 100 mg/l   | 96 h      | Pimephales promelas                                 | Study report (1995)               | OECD Guideline 203                      |
|              | Acute algae toxicity                                                                   | ErC50 >100 mg/l   | 72 h      |                                                     |                                   |                                         |
|              | Fish toxicity                                                                          | NOEC >= 1000 mg/l | 14 d      | Oncorhynchus mykiss                                 | CONCAWE, Brussels, Belgium (2010) | The aquatic toxicity was estimated by a |
| 1213789-63-9 | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines |                   |           |                                                     |                                   |                                         |
|              | Acute fish toxicity                                                                    | LC50 0,84 mg/l    | 96 h      | Danio rerio                                         | Study report (2006)               | OECD Guideline 203                      |
|              | Acute algae toxicity                                                                   | ErC50 0,39 mg/l   | 72 h      | Desmodesmus subspicatus                             | Study report (2002)               | OECD Guideline 201                      |
|              | Acute crustacea toxicity                                                               | EC50 0,32 mg/l    | 48 h      | Daphnia magna                                       | Study report (2006)               | OECD Guideline 202                      |
|              | Crustacea toxicity                                                                     | NOEC 0,013 mg/l   | 21 d      | Daphnia magna                                       | Study report (2002)               | OECD Guideline 211                      |
|              | Acute bacteria toxicity                                                                | (EC50 32 mg/l)    | 3 h       | activated sludge of a predominantly domestic sewage | Study report (1989)               | OECD Guideline 209                      |
| 104-76-7     | 2-Ethylhexan-1-ol                                                                      |                   |           |                                                     |                                   |                                         |
|              | Acute fish toxicity                                                                    | LC50 17,1 mg/l    | 96 h      | Leuciscus idus melanotus                            | Study report (1991)               | EU Method C.1                           |
|              | Acute algae toxicity                                                                   | ErC50 11,5 mg/l   | 72 h      | Desmodesmus subspicatus                             | Study report (1991)               | EU Method C.3                           |
|              | Acute crustacea toxicity                                                               | EC50 39 mg/l      | 48 h      | Daphnia magna                                       | Study report (1991)               | EU Method C.2                           |

**12.2. Persistence and degradability**

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

| CAS No       | Chemical name                                                                          | Log Pow |
|--------------|----------------------------------------------------------------------------------------|---------|
| 1213789-63-9 | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines | 5,16    |
| 104-76-7     | 2-Ethylhexan-1-ol                                                                      | 2,9     |

**BCF**

| CAS No | Chemical name | BCF | Species | Source |
|--------|---------------|-----|---------|--------|
|--------|---------------|-----|---------|--------|

## Safety Data Sheet

|              |                                                                                          |     |  |                     |
|--------------|------------------------------------------------------------------------------------------|-----|--|---------------------|
| 1213789-63-9 | (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated) - alkylamines | 173 |  | Environmental Toxic |
|--------------|------------------------------------------------------------------------------------------|-----|--|---------------------|

**12.4. Mobility in soil**

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria.

**12.6. Endocrine disrupting properties****Emirates lubricants**

Revision date: 09.02.2022

Guideway Oil XG 68

Page 11 of 13

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

**Marine transport (IMDG)**

**14.1. UN number or ID number:** -

**14.2. UN proper shipping name:** -

**14.3. Transport hazard class(es):** -

**14.4. Packing group:** -

## Safety Data Sheet

### Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 12 of 13

#### SECTION 15: Regulatory information

##### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

##### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

##### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

##### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

##### Other applicable information

No dangerous good in sense of these transport regulations.

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

###### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

###### National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

##### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### SECTION 16: Other information

##### Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,11,12,16.

##### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate;

## Safety Data Sheet

NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Classification for mixtures and used evaluation method according to GB CLP Regulation

|                         |                          |
|-------------------------|--------------------------|
| Classification          | Classification procedure |
| Aquatic Chronic 3; H412 | Calculation method       |

### Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage. H319 Causes serious eye irritation.

### Emirates lubricants

Revision date: 09.02.2022

Guideway Oil XG 68

Page 13 of 13

H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

### Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*